CPW resonators Noise and Decoherence vs Spin Echo Xmon cQED




Fedorov G. P. Moscow Institute of Physics and Technology


Supervisor: A. Bilmes September 16, 2015

- 1 Coplanar waveguide resonators
 - Quality factors and effective parameters
 - S-parameters
 - Xmon design features
 - Sonnet simulations
- 2 Noise and decoherence versus Hahn echo technique
 - Quantum-mechanically treated pure dephasing (Ramsey)
 - Classically treated pure dephasing (Ramsey)
 - Hahn echo
 - Noise PSD filtration
 - Who wins?
- 3 Xmon cQED (QuTiP simulations)
 - Circuit quantization
 - Cooper pair distribution for an isolated Xmon
 - Eigenproblem for a qubit-resonator system
 - Dispersive shifts










Coplanar waveguide resonators




Capacitively coupled CPW resonator as a lumped-element model:



Coplanar waveguide resonators



Capacitively coupled CPW resonator as a lumped-element model:




$$R^* = \frac{1 + \omega^2 C_\kappa^2 (Z_0/2)^2}{\omega^2 C_\kappa^2 (Z_0/2)}, \quad C^* = \frac{C_\kappa}{1 + \omega^2 C_\kappa^2 (Z_0/2)^2} \approx C_\kappa \text{ (for our case)}.$$

Coplanar waveguide resonators



Capacitively coupled CPW resonator as a lumped-element model:




$$R^* = \frac{1 + \omega^2 C_\kappa^2 (Z_0/2)^2}{\omega^2 C_\kappa^2 (Z_0/2)}, \quad C^* = \frac{C_\kappa}{1 + \omega^2 C_\kappa^2 (Z_0/2)^2} \approx C_\kappa \text{ (for our case)}.$$

$$Q_i = \omega(C + C^*)R_{in}, \quad Q_e = \omega(C + C^*)R^*, \quad Q_l = \omega(C + C^*)\frac{1}{1/R^* + 1/R_{in}}.$$

Coplanar waveguide resonators




Q-factors depending on C_{κ} :




Coplanar waveguide resonators



General algorithm for calculating S-parameters of a given device:





$$V_{1,2} = V_{1,2}^+ + V_{1,2}^-,$$

Kirchgoff's laws
$$\Rightarrow$$


$$I_{1,2} = \frac{V_{1,2}^+ - V_{1,2}^-}{Z_0}$$

$$\Rightarrow \begin{pmatrix} V_1^- \\ V_2^- \end{pmatrix} = \begin{pmatrix} S_{11} & S_{12} \\ S_{21} & S_{22} \end{pmatrix} \begin{pmatrix} V_1^+ \\ V_2^+ \end{pmatrix}.$$

Coplanar waveguide resonators



Analytical $S_{21}(C_{\kappa}, \omega) = (1 + Z_0/2Z_{sh})^{-1}, \ Z_{sh} = 1/i\omega C_{\kappa} + Z_{res}$:




Xmon design features

Coplanar waveguide resonators



Designed in LayoutEditor



$$l = \lambda/4$$
 coplanar resonators, $W = 4 \mu m$, $G = 2 \mu m$.

Unconventional coupling to the feedline:

$$C_{\kappa}^{eff} = C_{\kappa} \cos \frac{\pi x_{\kappa}}{2l} ? [1]$$

$$M_{\kappa} = ?$$

"Claw" coupler at the open end. Adds up some phase $\phi(\omega)$ and can be replaced [1] with high accuracy by

$$\Delta l = \frac{\phi(\omega_r)c}{2\omega_r\sqrt{\varepsilon_{eff}}}$$


[1] D. Sank, PhD Thesis, 2014 (J. Martinis group)


Sonnet simulations

Coplanar waveguide resonators



Resonator without a claw. Frequency expected from the length and $C_{\kappa} \approx 6$ fF (extracted from $Q_{l} \approx 10^{4}$) is 7.925 GHz.







Sonnet simulations

Coplanar waveguide resonators




Resonator with a claw. Frequency expected from the previous simulation and ϕ (also simulated separately for the given claw) is 7.4255 GHz.





- 1 Coplanar waveguide resonators
 - Quality factors and effective parameters
 - S-parameters
 - Xmon design features
 - Sonnet simulations
- 2 Noise and decoherence versus Hahn echo technique
 - Quantum-mechanically treated pure dephasing (Ramsey)
 - Classically treated pure dephasing (Ramsey)
 - Hahn echo
 - Noise PSD filtration
 - Who wins?
- 3 Xmon cQED (QuTiP simulations)
 - Circuit quantization
 - Cooper pair distribution for an isolated Xmon
 - Eigenproblem for a qubit-resonator system
 - Dispersive shifts

Quantum-mechanically treated pure dephasing (Ramsey)





Qubit-environment interaction Hamiltonian:

$$\hat{\mathcal{H}}_{qe} = \hat{O}_e \otimes \hat{\sigma}_z.$$

 \hat{O}_e is an arbitrary environment operator, $\hat{\sigma}_z$ – qubit observable.

Master equation:

$$\partial_t \hat{
ho}_q = rac{i}{\hbar} [\hat{
ho}_q, \hat{\mathcal{H}}_q] + \gamma_\phi (\hat{\sigma}_z \hat{
ho}_q \hat{\sigma}_z - \hat{
ho}_q).$$

Steady state:

$$\hat{\rho}_q(\infty) = \begin{pmatrix} \rho_{11}(0) & 0\\ 0 & \rho_{22}(0) \end{pmatrix}.$$

Quantum-mechanically treated pure dephasing (Ramsey)


Noise and decoherence versus Hahn echo technique



 $\langle \sigma_x \rangle$

14

Example: pure dephasing of the $|+\rangle$ state, **lab frame**.




16


Quantum-mechanically treated pure dephasing (Ramsey)

Noise and decoherence versus Hahn echo technique



Example: pure dephasing of the $|+\rangle$ state, **rotating frame**.





(dynamics simulated with QuTiP)

Classically treated pure dephasing (Ramsey)

Noise and decoherence versus Hahn echo technique



$$\hat{O}_e \otimes \hat{\sigma}_z \to f(t) \cdot \hat{\sigma}_z, \ f(t) \text{ is random}$$

Rotating frame evolution (single run!):

$$\hat{\rho}_{q}(t) = \hat{U}^{\dagger}(t,0) \ \hat{\rho}_{q}(0) \ \hat{U}(t,0), \quad \hat{U}(t,0) = \hat{T} \exp\left\{-\frac{i}{\hbar} \int_{0}^{t} f(\tau) \,d\tau \ \hat{\sigma}_{z}\right\}.$$

$$\hat{\rho}_{q}(t) = \begin{pmatrix} 1/2 - N(t)/2 & \rho(t) \\ \rho^{*}(t) & 1/2 + N(t)/2 \end{pmatrix},$$

$$\left. \begin{array}{l} N(t) = N(0), \\ \\ \rho(t) = \rho(0) \exp \left\{ \frac{2i}{\hbar} \int_0^t f(\tau) \, \mathrm{d}\tau \right\} \end{array} \right\} \Rightarrow \begin{array}{l} \text{unitary random walk,} \\ \text{no dephasing!} \end{array}$$

Classically treated pure dephasing (Ramsey)

Noise and decoherence versus Hahn echo technique



Averaging. For Gaussian instantaneous distribution of f(t):

$$\langle \rho(t) \rangle = \rho(0) \exp \left\{ -\frac{2}{\hbar^2} \int_0^t \int_0^t \langle f(\tau_1) f(\tau_2) \rangle d\tau_1 d\tau_2 \right\}.$$

Presuming also that f(t) is a wide-sense stationary process:

$$\langle f(\tau_1)f(\tau_2)\rangle = K_f(\tau_2 - \tau_1) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^{\infty} S_f(\omega)e^{i\omega(\tau_2 - \tau_1)} d\omega.$$

$$\langle \rho(t) \rangle = \rho(0) \exp \left\{ -\frac{2}{\sqrt{2\pi}\hbar^2} \int_{-\infty}^{\infty} \frac{4\sin^2(\frac{\omega t}{2})}{\omega^2} S_f(\omega) d\omega \right\} \equiv \rho(0) e^{-\alpha(t)}$$


 \Rightarrow ensemble averaged behaviour of $\rho(t)$ is a decay!

Noise and decoherence versus Hahn echo technique

Time, ns



$S_f(\omega) = \delta(\omega)$ (f(t) = const on the timescale of a single run):





Add one instant π -pulse. Accumulated phase:

$$\rho(t) = \rho(0) \exp\Big\{\underbrace{-\frac{2i}{\hbar} \int_0^{t/2} f(\tau) \, \mathrm{d}\tau}_{\text{before π-pulse}} + \underbrace{\frac{2i}{\hbar} \int_{t/2}^t f(\tau) \, \mathrm{d}\tau}_{\text{after π-pulse}}\Big\}.$$


After averaging:


$$\langle \rho(t) \rangle = \rho(0) \exp \left\{ -\frac{2}{\sqrt{2\pi}\hbar^2} \int_{-\infty}^{\infty} S_f(\omega) W_t^H(\omega) d\omega \right\},$$
$$W_t^H(\omega) = \tan^2(\omega t/4) \frac{4\sin^2(\omega t/2)}{\omega^2}.$$

Noise PSD filtration

Noise and decoherence versus Hahn echo technique








■ Ramsey: $\int \frac{4\sin^2(\frac{\omega t}{2})}{\omega^2} S_f(\omega) d\omega$

■ Hahn: $\int \tan^2(\omega t/4) \frac{4\sin^2(\frac{\omega t}{2})}{\omega^2} S_f(\omega) d\omega$




$$S_f(\omega) = 1/\omega$$
 (pink noise):





No echo

Noise and decoherence versus Hahn echo technique










efficient!



$$S_f(\omega) = S_f(0) = const$$
 (white noise):





No echo

Noise and decoherence versus Hahn echo technique



$$S_f(\omega) = S_f(0) = const$$
 (white noise):





No echo Echo

■ totally inefficient, same for the master equation description


- 1 Coplanar waveguide resonators
 - Quality factors and effective parameters
 - S-parameters
 - Xmon design features
 - Sonnet simulations
- 2 Noise and decoherence versus Hahn echo technique
 - Quantum-mechanically treated pure dephasing (Ramsey)
 - Classically treated pure dephasing (Ramsey)
 - Hahn echo
 - Noise PSD filtration
 - Who wins?
- 3 Xmon cQED (QuTiP simulations)
 - Circuit quantization
 - Cooper pair distribution for an isolated Xmon
 - Eigenproblem for a qubit-resonator system
 - Dispersive shifts

Circuit quantization

Xmon cQED (QuTiP simulations)



Equivalent circuit for the transmon-resonator system:



Circuit quantization

Xmon cQED (QuTiP simulations)




$$\begin{split} \hat{\mathcal{H}} &= \underbrace{\frac{\hat{\phi}_r^2}{2L_r} + \frac{(C_q + C_g)\hat{Q}_r^2}{2C_*^2}}_{\text{resonator}} + \underbrace{\frac{(C_g + C_\kappa + C_r)\hat{Q}_q^2}{2C_*^2} - E_J(\Phi_{ext})\cos\frac{2e}{\hbar}\hat{\phi}_q}_{\text{qubit}} + \underbrace{\frac{C_g\hat{Q}_r\hat{Q}_q}{C_*^2}}_{\text{coupling}} = \\ &= \hbar\omega_r \ \hat{a}^\dagger\hat{a}\otimes\hat{\mathbb{1}}_q \quad (\hat{\mathcal{H}}_r) \\ &+ 4E_C \ \hat{\mathbb{1}}_r\otimes\hat{n}^2 - \frac{E_J(\Phi_{ext})}{2} \ \hat{\mathbb{1}}_r\otimes\sum_{n=-\infty}^{+\infty}|n+1\rangle\langle n| + |n\rangle\langle n+1| \quad (\hat{\mathcal{H}}_q) \\ &- 2e\frac{C_g}{C_*}\sqrt{\frac{\hbar\omega_r}{2(C_q + C_q)}} \ i(\hat{a}^\dagger - \hat{a})\otimes\hat{n}, \quad (\hat{\mathcal{H}}_i) \end{split}$$

Cooper pair distribution for an isolated Xmon

Xmon cQED (QuTiP simulations)







Strong driving

Xmon cQED (QuTiP simulations)



For weak driving the two-level dynamics is preserved ($|\psi(t)\rangle = \sum_k c_k(t)|E_k\rangle$):







Strong driving

Xmon cQED (QuTiP simulations)



But not for the strong drive $(|\psi(t)\rangle = \sum_k c_k(t)|E_k\rangle)$:






Eigenproblem for a qubit-resonator system Xmon cQED (QuTiP simulations)



Energy level structure:




Eigenproblem for a qubit-resonator system

Xmon cQED (QuTiP simulations)



Frequencies $f_{0n} = (E_n - E_0)/h$ for $\omega_q > \omega_r$:






The Grotrian diagram:



Dispersive shifts originate from the level structure of the whole composite system:





It's possible to determine these shifts with high accuracy using the second order perturbation theory:

$$\chi_0 = g^2 \left[\frac{n_{ge}^2}{\omega_r - \omega_{ge}} - \frac{n_{ge}^2}{\omega_r + \omega_{ge}} \right],$$

$$\chi_1 = g^2 \left[\frac{n_{ef}^2}{\omega_r - \omega_{ef}} - \frac{n_{ef}^2}{\omega_r + \omega_{ef}} + \frac{n_{eg}^2}{\omega_r + \omega_{ge}} - \frac{n_{eg}^2}{\omega_r - \omega_{ge}} \right],$$


$$\chi_2 = g^2 \left[\frac{n_{fd}^2}{\omega_r - \omega_{fd}} - \frac{n_{fd}^2}{\omega_r + \omega_{fd}} + \frac{n_{fe}^2}{\omega_r + \omega_{ef}} - \frac{n_{fe}^2}{\omega_r - \omega_{ef}} \right].$$

Dispersive shifts

Xmon cQED (QuTiP simulations)




The shifts depend on the detuning $\Delta_{\omega} = \omega_r - \omega_{qe}$ and Φ_{ext} :




Final words



- Quality factors and coupling capacitance calculations, simulations of CPW resonators and extraction of capacitances using Sonnet
- Investigation of classical and quantum noise influence on the qubit, numerical simulations of the pure dephasing under different types of noise
- Quantization of Xmon-resonator circuit to transform capacitances and quality factors to the coupling strengths, driving amplitudes and decay rates





${\bf Acknowledgements}$

Final words



- A. V. Ustinov
- J. Lisenfeld and A. Bilmes

Acknowledgements Final words





Thank you!