

WPL - Pgm 5

position.html

```
<html>

<head>

<title>CSS Positioning Comparison</title>

<link rel="stylesheet" href="style_relative.css"> <link rel="stylesheet"
href="style_absolute.css"> <style>
```

```
.item {
    height: 90px;
    width: 90px;
    margin: 8px;
    border: 1px solid #333;
}
```

```
.absolute-container {
    position: relative;
    width: 650px;
    height: 220px;
    border: 3px dashed #004d99;
    margin-top: 50px;
    margin-left: 20px;
    background-color: #f0f8ff;
}
```

```
.relative-flow-parent {
    display: flex;
    width: 650px;
    height: 220px;
```

```
border: 3px solid #1a7e46;
background-color: #f7fff7;
}
```

```
h1 {
  color: #004d99;
  border-bottom: 2px solid #ccc;
  padding-bottom: 5px;
}
```

```
p {
  margin-bottom: 25px;
  font-style: italic;
  color: #444;
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<h1>CSS RELATIVE POSITIONING</h1>
```

```
<p>An element with <b>position: relative;</b> is offset from its original
position. Critically, it does <b>not</b> affect the layout of other surrounding
elements, preserving their space in the normal document flow.</p>
```

```
<div class="relative-flow-parent">
```

```
<div class="item" id="cyan-box"></div>
```

```
<div class="item" id="magenta-box"></div>
```

```
<div class="item" id="orange-box"></div>
```

```
<div class="item" id="purple-box"></div>
```

```
</div>
```

```
<hr>
```

<h1>CSS ABSOLUTE POSITIONING</h1>

<p>An element with position: absolute; is removed from the normal document flow and positioned relative to the nearest ancestor that has a position property other than static. Here, the positioning ancestor is the div with class "absolute-container", which is set to relative.</p>

```
<div class="absolute-container">
<div class="item" id="box-one"></div>
<div class="item" id="box-two"></div>
<div class="item" id="box-three"></div>
<div class="item" id="box-four"></div>
</div>
</body>
</html>
```

style relative.css

```
#cyan-box {
  position: relative;
  left: 40px;
  top: 15px;
  background-color: #00bcd4;
}
```

```
#magenta-box {
  position: relative;
  left: 80px;
  top: 40px;
  background-color: #e91e63;
}
```

```
#orange-box {
```

```
position: relative;
left: 120px;
top: 15px;
background-color: #ff9800;
}
```

```
#purple-box {
position: relative;
left: 160px;
top: 40px;
background-color: #9c27b0;
}
background-color: #ffffff;
}
```

style absolute.css

```
#box-one {
position: absolute;
left: 40px;
top: 10px;
background-color: #3f51b5;
}
```

```
#box-two {
position: absolute;
right: 30px;
bottom: 40px;
background-color: #f44336;
}
```


```
#box-three {  
  position: absolute;  
  left: 45%;  
  top: 50%;  
  transform: translate(-50%, -50%);  
  background-color: #4caf50;  
}
```

```
#box-four {  
  position: absolute;  
  right: 10px;  
  top: 10px;  
  background-color: #ffc107;  
}
```

Output

CSS RELATIVE POSITIONING

*An element with **position: relative;** is offset from its original position. Critically, it does **not** affect the layout of other surrounding elements, preserving their space in the normal document flow.*



CSS ABSOLUTE POSITIONING

*An element with **position: absolute;** is removed from the normal document flow and positioned relative to the nearest ancestor that has a position property other than **static**. Here, the positioning ancestor is the div with class "absolute-container", which is set to relative.*

