Q1. You are automating a modern web app with heavy JavaScript and dynamic DOM updates. Which Selenium tool is MOST appropriate?

Correct Answer: C – Selenium WebDriver

Explanation:

- Modern JS apps need real browser control
- Selenium IDE is limited
- Selenium RC is obsolete
- Selenium Grid is for parallel execution, not automation itself

---

Q2. Selenium RC is no longer used. What is the practical reason?

Correct Answer: B – RC requires a server and injects JavaScript into browser

Explanation:

- RC uses an intermediate server
- WebDriver talks directly to browser
- RC is slower and less stable

Q3. Before writing your first Selenium WebDriver script, which prerequisite is mandatory?

Correct Answer: C – Browser driver executable (e.g., chromedriver)

Explanation:
Without ChromeDriver / GeckoDriver, WebDriver **cannot launch browser**.

Q4. Which code correctly creates a Chrome browser instance?

Options included:

- `driver = Chrome()` ❌
- `driver = webdriver.Chrome()` ✅
- `driver = new ChromeDriver()` ❌ (Java syntax)
- `driver = webdriver("chrome")` ❌

Correct Answer: B – `driver = webdriver.Chrome()`

Q5. You use `send_keys("admin")` but text does not appear. MOST likely reason?

Correct Answer: B – Element is not visible or interactable

Explanation:

- Element may be hidden
- Not clickable yet
- Needs explicit wait

Q6. You want to press CTRL + A and DELETE. Which approach is correct?

Correct option shown:

ActionChains(driver)\
.key_down(Keys.CONTROL)\
.send_keys('a')\
.key_up(Keys.CONTROL)\
.perform()

Correct Answer: B – ActionChains

Explanation:

- Keyboard shortcuts require ActionChains
- `send_keys("CTRL+A")` does not work

Q7. You expect multiple elements matching the same locator. Which method should you use?

Correct Answer: C – `find_elements_by_xpath()`

Explanation:

- `find_element` → single element
- `find_elements` → list of elements

Q8. Which locator is fastest and most reliable when available?

Options: XPath, CSS Selector, Name, ID

Correct Answer: D – ID

Explanation:

- ID is unique
- Fastest lookup

Q9. Locate a button with text “Login” and no unique attributes. Best XPath?

Options included:

- `//button[@id='Login']` ❌
- `//button[text()='Login']` ✅
- `//Login/button` ❌
- `/html/body/button[1]` ❌

Correct Answer: B

Q10. Which XPath is relative and robust?

Options included absolute and relative XPaths.

Correct Answer: B – `//*[@id='username']`

Explanation:

- Starts with `//`
- Independent of DOM hierarchy

Q11. Dropdown implemented using `<select>` tag. Which Selenium utility should be used?

Correct Answer: Select class

Q12. Which code correctly selects an option by visible text?

Correct code:

Select(element).select_by_visible_text("India")

Correct Answer: B

Q13. Test fails intermittently because elements load late. BEST practice?

Correct Answer: C – Explicit wait with expected_conditions

Explanation:

- Most reliable
- Waits for condition, not time

Q14. Key difference between implicit and explicit wait?

Correct Answer: C – Explicit wait is applied for a specific element and condition

---

Q15. Which Expected Condition waits until element is present AND clickable?

Options:

- presence_of_element_located
- visibility_of_element_located
- element_to_be_clickable
- frame_to_be_available_and_switch_to_it

Correct Answer: C – element_to_be_clickable

Q16. Drag and drop an element. Which Selenium feature is required?

Correct Answer: ActionChains

Q17. Selenium IDE: which command types text into input field?

Options: sendKeys, type, input, write

Correct Answer: B – type

Q18. Selenium IDE command that verifies condition but does NOT stop execution if it fails?

Correct Answer: C – verifyText

Explanation:

- `assert` stops execution

- `verify` continues

Q19. Selenium IDE command that is an ACTION, not assertion?

Options included:

- assertElementPresent
- verifyText
- click
- assertTitle

Correct Answer: C – click

Q20. Selenium IDE uses `waitForElementPresent`. What does this indicate?

Correct Answer: C – Explicit synchronization