Aplicações para a Internet II

Create App React with Bootstrap

2021/2022

<React.js (Frontend)/>

Para instalar é necessário executar o comando seguinte:

npx create-react-app frontend

```
Success! Created frontend at C:\nodejsSites\react\frontend
Inside that directory, you can run several commands:

npm start
   Starts the development server.

npm run build
   Bundles the app into static files for production.

npm test
   Starts the test runner.

npm run eject
   Removes this tool and copies build dependencies, configuration files and scripts into the app directory. If you do this, you can't go back!


We suggest that you begin by typing:
   cd frontend
   npm start

Happy hacking!
C:\nodejsSites\react>
```

<React.js (Frontend)/>

Para executar a aplicação, devemos entrar na diretoria *frontend* e executar o comando:

npm start



< Instalação do Bootstrap/>

 Neste exercício vamos utilizar o Bootstrap, e para isso é necessário instalar o JQuery. Para isso vamos executar os seguintes comandos:

npm install jquery popper.js

. . .

npm install bootstrap

- A aplicação vai ter três componentes (vistas):
 - 1. ./view/form: apresentar o formulário para registo de employee;
 - 2. ./view/list: listar os employee existentes;
 - 3. ./view/edit: apresentar o formulário para edição de employee.
- Instalação de uma solução de roteamento, o React Router.

npm install react-router-dom

Adicionar o código seguinte no ficheiro App.js:

import { BrowserRouter as Router, Route, Link, Routes } from "react-router-dom";

Uma outra consideração que devemos ter em conta é colocar:

```
<Router>
...
// a nossa App
...
</Router>
```

Definição de rotas no ficheiro App.js

```
    src/view/list.is

import React from 'react';
import 'bootstrap/dist/css/bootstrap.min.css';
import 'bootstrap/dist/js/bootstrap.bundle.min';
export default function ListComponent(){
return (
  <thead class="thead-dark">
   #
    Role
    Name
    Email
    Address
    Phone
    Action
   </thead>
```

```
1
    Admin
    Nuno Costa
    ncosta@estgv.ipv.pt
    Viseu
    232480533
    <button class="btn btn-outline-info"> Edit
</button>
    <button class="btn btn-outline-danger"> Delete
</button>
    );
```

```
    src/view/form.is

import 'bootstrap/dist/css/bootstrap.min.css';
import 'bootstrap/dist/js/bootstrap.bundle.min';
import React ,{useEffect, useState} from "react";
export default function EditComponent(){
 return (
   <div>
    <div className="form-row justify-content-center">
     <div className="form-group col-md-6">
      <label htmlFor="inputPassword4">Name </label>
      <input type="text" className="form-control"
placeholder="Name" />
     </div>
     <div className="form-group col-md-6">
      <label htmlFor="inputEmail4">Email</label>
      <input type="email" className="form-control"
placeholder="Email" />
     </div>
    </div>
```

```
<div className="form-row">
     <div className="form-group col-md-6">
      <label htmlFor="inputState">Role</label>
      <select id="inputState" className="form-control">
       <option defaultValue>Choose...
       <option value="1">Admin...</option>
       <option value="2">Project Manager</option>
       <option value="3">Programer</option>
      </select>
     </div>
     <div className="form-group col-md-6">
      <label htmlFor="inputEmail4">Phone</label>
      <input type="number" className="form-control"
placeholder="Phone"/>
     </div>
    </div>
    <div className="form-group">
     <label htmlFor="inputAddress">Address</label>
     <input type="text" className="form-control" id="inputAddress"</pre>
placeholder="1234 Main St" />
    </div>
    <button type="submit" className="btn btn-primary">Save</button
   </div>
 );
```

```
    src/view/edit.is

import 'bootstrap/dist/css/bootstrap.min.css';
import 'bootstrap/dist/js/bootstrap.bundle.min';
import React ,{useEffect, useState} from "react";
import {useParams} from "react-router-dom";
export default function EditComponent(){
   const {employeeld} = useParams();
return (
   <div>
    <div className="form-row justify-content-center">
      <div className="form-group col-md-6">
       <label htmlFor="inputPassword4">Name</label>
       <input type="text" className="form-control"</pre>
placeholder="Name"/>
      </div>
     <div className="form-group col-md-6">
       <label htmlFor="inputEmail4">Email</label>
       <input type="email" className="form-control"
placeholder="Email"/>
      </div>
    </div>
```

```
<div className="form-row">
     <div className="form-group col-md-6">
      <label htmlFor="inputState">Role</label>
      <select id="inputState" className="form-control">
        <option value="1">Admin</option>
        <option value="2">Project Manager</option>
        <option value="3">Programer</option>
       </select>
      </div>
     <div className="form-group col-md-6">
      <label htmlFor="inputEmail4">Phone</label>
      <input type="number" className="form-control"</pre>
placeholder="Phone" />
      </div>
    </div>
    <div className="form-group">
     <label htmlFor="inputAddress">Address</label>
      <input type="text" className="form-control"
id="inputAddress" placeholder="1234 Main St"/>
    </div>
    <button type="submit" className="btn btn-
primary">Update</button>
   </div>
  );
```

```
    src/App.is

                                                                   <div class="collapse navbar-collapse"
import React from 'react';
                                                                   id="navbarSupportedContent">
                                                                          ul class="navbar-nav mr-auto">
import 'bootstrap/dist/css/bootstrap.min.css';
                                                                           import 'bootstrap/dist/js/bootstrap.bundle.min';
                                                                            <Link class="nav-link" to="/"> Employee List </Link>
import { BrowserRouter as Router, Route, Link, Routes } from "react-
                                                                           router-dom":
                                                                          </11/>
import Form from './view/form';
                                                                          <Link class="btn btn-success " to="/form">Add
import List from './view/list';
                                                                   Employee</Link>
import Edit from './view/edit';
                                                                         </div>
                                                                        </nav>
function App() {
 return (
                                                                        <div class="container py-4">
  <Router>
                                                                         <div class="row">
   <div className="App">
                                                                    <Routes>
                                                                         <Route path="/" element={<List/>} />
    <nav class="navbar navbar-expand-lg navbar-light bg-light">
                                                                         <Route path="/form" element={<Form/>} />
     <a class="navbar-brand" href="https://www.estgv.ipv.pt/"</pre>
                                                                         <Route path="/edit/:employeeld" element={<Edit/>} />
style={{color:'red',fontWeight:'bold'}}>www.estgv.ipv.pt</a>
                                                                   </Routes>
     <button class="navbar-toggler" type="button" data-
                                                                   </div>
toggle="collapse" data-target="#navbarSupportedContent" aria-
                                                                        </div>
controls="navbarSupportedContent" aria-expanded="false" aria-
label="Toggle navigation">
                                                                       </div>
      <span class="navbar-toggler-icon"></span>
                                                                      </Router>
     </button>
                                                                    );
                                                                   export default App;
```

http://localhost:3000/



http://localhost:3000/form



http://localhost:3000/edit/2391

