

C Programming Basics

Lab Session: IPC using Message Queue with fork()

Course: Operating Systems

Date: 31.05.2025

Program: IPC using Message Queue with fork()

```
#include <stdio.h>

#include <stdlib.h>

#include <string.h>

#include <sys/ipc.h>    // For IPC key generation
#include <sys/msg.h>    // For message queue functions
#include <unistd.h>     // For fork()


#define MAX 10         // Max size of message text


// Structure for message queue
struct mesg_buffer {
    long mesg_type;
    char mesg_text[100];
} message;

int main() {

    int f = fork(); // Create child process


    if (f == 0) {

        // Child - Receive

        key_t key;
```

```

int msgid;

key = ftok("nuzha1", 130);
msgid = msgget(key, 0666 | IPC_CREAT);
msgrcv(msgid, &message, sizeof(message.mesg_text), 1, 0);

// Parse received message
char name[30], regno[30], age[10];
sscanf(message.mesg_text, "%s %s %s", name, regno, age);

printf("\nReceived Name : %s\n", name);
printf("Received RegNo : %s\n", regno);
printf("Received Age : %s\n", age);

msgctl(msgid, IPC_RMID, NULL); // Remove message queue
} else {
    // Parent - Send
    key_t key;
    int msgid;
    char name[30], regno[30], age[10];

    key = ftok("nuzha1", 130);
    msgid = msgget(key, 0666 | IPC_CREAT);

    printf("Enter Name: ");
    scanf("%s", name);

```

```
printf("Enter RegNo: ");
scanf("%s", regno);
printf("Enter Age: ");
scanf("%s", age);

message.mesg_type = 1;
snprintf(message.mesg_text, sizeof(message.mesg_text), "%s %s %s", name, regno, age);

msgsnd(msgid, &message, sizeof(message.mesg_text), 0);
printf("\nMessage sent successfully.\n");
}

return 0;
}
```

Fedora Output:

```
[2021ict108@fedora ~]$ vi nuzha1.c
[2021ict108@fedora ~]$ gcc nuzha1.c -o nuzha1
[2021ict108@fedora ~]$ ./nuzha1
```

Enter Name: nuzha

Enter RegNo: 2021ict108

Enter Age: 24

Message sent successfully.

Received Name : nuzha

Received RegNo : 2021ict108

Received Age : 24

[2021ict108@fedora ~]\$

Explanation:

- This program demonstrates **IPC using System V message queues** and **process creation with fork()**.
- The **parent process** reads user input (Name, RegNo, Age) and sends it through the message queue.
- The **child process** reads from the queue, parses the message, and prints the received data.
- `ftok()` generates a unique key.
- `msgget()` creates/accesses the queue.
- `msgsnd()` and `msgrcv()` handle communication.
- `msgctl()` removes the message queue after use.