

## C Programming Basics

### Lab Session: Introduction to C Language (Conditional Statements, Loops & Functions)

**Course:** Operating Systems

**Date:** 19.05.2025

#### Introduction to Conditional Statements

Conditional statements allow the program to take different actions based on specific conditions. This includes decision-making structures like if-else, ternary operators, and switch-case structures.

##### 1. if-else Statement

The if-else statement lets you execute certain code when a condition is true and different code when it's false. It is useful for branching logic based on conditions.

```
if (condition) {  
    // body of if statement  
} else {  
    // body of else statement  
}
```

##### Example:

Check if a person is eligible to vote (age >= 18)

```
#include<stdio.h>  
  
int main() {  
    int age;  
    printf("Enter your age: ");  
    scanf("%d", &age);  
  
    if (age >= 18) {  
        printf("You are eligible for voting\n");  
    } else {
```

```
        printf("Not eligible for voting\n");
    }

    return 0;
}
```

### **Fedora Output:**

```
[2021ict108@fedora ~]$ gcc eligible.c -o eligible
```

```
[2021ict108@fedora ~]$ ./eligible
```

```
Enter your age: 24
```

```
You are eligible for voting
```

```
[2021ict108@fedora ~]$ ./eligible
```

```
Enter your age: 13
```

```
Not eligible for voting
```

---

## **2. Ternary Operator**

The ternary operator is a shorthand way of writing simple if-else conditions. It is ideal for conditions that assign or return values based on a boolean expression.

```
test_condition ? expression1 : expression2;
```

### **Example:**

```
#include<stdio.h>
```

```
int main() {
```

```
    int age;
```

```
    printf("Enter your age: ");
```

```
    scanf("%d", &age);
```

```
    (age >= 18) ? printf("You are eligible\n") : printf("You are not eligible\n");
```

```
    return 0;
```

```
}
```

### **Fedora Output:**

```
[2021ict108@fedora ~]$ gcc ternary.c -o ternary
```

```
[2021ict108@fedora ~]$ ./ternary
```

```
Enter your age: 25
```

```
You are eligible
```

```
[2021ict108@fedora ~]$ ./ternary
```

```
Enter your age: 14
```

```
You are not eligible
```

---

### **Introduction to switch Statement**

#### **Example 1:** Day of the Week

The switch-case structure is used here to execute different outputs depending on the numeric input value. It is particularly helpful for discrete values like menu options or days of the week.

```
#include <stdio.h>
```

```
int main() {
```

```
    int day;
```

```
    printf("Enter the number between 1 to 7: ");
```

```
    scanf("%d", &day);
```

```
    switch (day) {
```

```
        case 1: printf("Today is Sunday!\n"); break;
```

```
        case 2: printf("Today is Monday!\n"); break;
```

```
        case 3: printf("Today is Tuesday!\n"); break;
```

```
        case 4: printf("Today is Wednesday!\n"); break;
```

```
        case 5: printf("Today is Thursday!\n"); break;
```

```

        case 6: printf("Today is Friday!\n"); break;
        case 7: printf("Today is Saturday!\n"); break;
        default: printf("Invalid input!\n");
    }

    return 0;
}

```

### **Fedora Output:**

```
[2021ict108@fedora ~]$ gcc weekday.c -o weekday
```

```
[2021ict108@fedora ~]$ ./weekday
```

Enter the number between 1 to 7: 5

Today is Thursday!

### **Example 2: Life Path Number Astrology**

```
#include <stdio.h>
```

```
int main() {
```

```
    int date, a, b, c;
```

```
    printf("Enter your birth date (1 to 31): ");
```

```
    scanf("%d", &date);
```

```
    if (date < 1 || date > 31) {
```

```
        printf("Invalid date input!\n");
```

```
        return 0;
```

```
    }
```

```
    a = date % 10;
```

```
    b = date / 10;
```

```
    c = a + b;
```

```
printf("Date: %d\n", date);  
printf("Life Path Number: %d\n", c);  
  
switch (c) {  
    case 1: printf("Lucky\n"); break;  
    case 2: printf("Carefully do your work\n"); break;  
    case 3: printf("Stronger\n"); break;  
    case 4: printf("Happy\n"); break;  
    case 5: printf("Can get help\n"); break;  
    case 6: printf("Doubt\n"); break;  
    case 7: printf("Sad\n"); break;  
    case 8: printf("Like\n"); break;  
    case 9: printf("Courage\n"); break;  
    default: printf("Invalid life path number\n");  
}  
return 0;  
}
```

### **Fedora Output:**

```
[2021ict108@fedora ~]$ gcc astrology.c -o astrology
```

```
[2021ict108@fedora ~]$ ./astrology
```

```
Enter your birth date (1 to 31): 30
```

```
Date: 30
```

```
Life Path Number: 3
```

```
Stronger
```

---

## Looping & Iteration Examples

### Example 3: Sum and Multiplication using for loop

A for loop is used to perform repeated operations. Here, it calculates the sum and product of numbers from 1 to 5.

```
#include <stdio.h>

int main() {

    int i, sum = 0, mul = 1;

    for (i = 1; i <= 5; i++) {

        sum += i;

        mul *= i;

    }

    printf("Summation = %d\n", sum);

    printf("Multiplication = %d\n", mul);

    return 0;

}
```

#### Fedora Output:

Summation = 15

Multiplication = 120

### Example 4: Print 1 to 10 using while loop

```
#include <stdio.h>

int main() {

    int i = 1;

    while (i <= 10) {

        printf("%d\n", i);

        i++;

    }

}
```

```
    return 0;
}
```

#### **Fedora Output:**

```
1
2
3
4
5
6
7
8
9
10
```

#### **Example 5: Fibonacci Series**

A Fibonacci series is a sequence where each term is the sum of the two previous terms. This example prints the first N numbers of the series using a loop.

```
#include <stdio.h>
```

```
int main() {
```

```
    int n, i;
```

```
    long long t1 = 0, t2 = 1, nextTerm;
```

```
    printf("Enter the number of terms: ");
```

```
    scanf("%d", &n);
```

```
    printf("Fibonacci Series: ");
```

```
    for (i = 1; i <= n; i++) {
```

```
        printf("%lld ", t1);
```

```

        nextTerm = t1 + t2;

        t1 = t2;

        t2 = nextTerm;
    }

    return 0;
}

```

#### **Fedora Output:**

Enter the number of terms: 5

Fibonacci Series: 0 1 1 2 3

#### **Example 6: Factorial Calculation**

```

#include <stdio.h>

long long factorial(int n) {

    long long fact = 1;

    for (int i = 1; i <= n; i++)

        fact *= i;

    return fact;
}

int main() {

    int num;

    printf("Enter a number: ");

    scanf("%d", &num);

    printf("Factorial: %lld\n", factorial(num));

    return 0;
}

```

#### **Fedora Output:**

Enter a number: 5



Factorial: 120

### **Example 7: String Concatenation**

```
#include <stdio.h>

#include <string.h>

int main() {

    char str1[100], str2[100], result[200];

    printf("Enter first string: ");

    fgets(str1, sizeof(str1), stdin);

    printf("Enter second string: ");

    fgets(str2, sizeof(str2), stdin);


    str1[strcspn(str1, "\n")] = '\0';

    str2[strcspn(str2, "\n")] = '\0';


    strcpy(result, str1);

    strcat(result, str2);

    printf("Concatenated string: %s\n", result);

    return 0;

}
```

### **Fedora Output:**

```
Enter first string: Hello

Enter second string: World

Concatenated string: HelloWorld
```

### **Example 8: Binary to Decimal Conversion**

```
#include <stdio.h>

int main() {
```

```

int binary, decimal = 0, base = 1, rem;

printf("Enter a binary number: ");

scanf("%d", &binary);

while (binary > 0) {
    rem = binary % 10;
    decimal += rem * base;
    binary /= 10;
    base *= 2;
}

printf("Decimal equivalent: %d\n", decimal);

return 0;
}

```

#### **Fedora Output:**

Enter a binary number: 1010

Decimal equivalent: 10

#### **Example 9: Find Max and Min in an Array**

```

#include <stdio.h>

int main() {
    int n, i;

    printf("Enter number of elements: ");

    scanf("%d", &n);

    int arr[n];

    printf("Enter %d elements: ", n);

    for (i = 0; i < n; i++)

```

```

scanf("%d", &arr[i]);

int max = arr[0], min = arr[0];
for (i = 1; i < n; i++) {
    if (arr[i] > max) max = arr[i];
    if (arr[i] < min) min = arr[i];
}

printf("Max = %d, Min = %d\n", max, min);

return 0;
}

```

#### **Fedora Output:**

Enter number of elements: 5

Enter 5 elements: 2 4 6 1 9

Max = 9, Min = 1

#### **Example 10: Pascal's Triangle**

Pascal's Triangle is a triangular arrangement of numbers. Each number is the sum of the two directly above it. This program generates it using nested loops.

```
#include <stdio.h>
```

```

int main() {

    int rows, coef = 1, space, i, j;

    printf("Enter number of rows: ");

    scanf("%d", &rows);

    for (i = 0; i < rows; i++) {

        for (space = 1; space <= rows - i; space++)

            printf(" ");

        for (j = 0; j <= i; j++) {

```

```
    if (j == 0 || i == 0)
        coef = 1;
    else
        coef = coef * (i - j + 1) / j;
    printf("%4d", coef);
}
printf("\n");
}
return 0;
}
```

**Fedora Output:**

Enter number of rows: 5

```
1
1 1
1 2 1
1 3 3 1
1 4 6 4 1
```