

Some Java questions

Question 1: What will be the Output of the below code:

```
public class A {  
    public static void main(String[] args)  
    {  
        if (true)  
            break;  
    }  
}
```

Choices:

- a) Nothing
- b) Error

Question 2: What will be the Output of the below code:

```
public class A {  
    public static void main(String[] args)  
    {  
        System.out.println('j' + 'a' + 'v' + 'a');  
    }  
}
```

Choices:

- a) java
- b) Something else (Other than simple concatenation)

Question 3: What will be the Output of the below code:

```
public class A {  
    public static void main(String[] args)  
    {  
        int $_ = 5;  
    }  
}
```

Choices:

- a) Nothing
- b) Error

Question 4: What will be the Output of the below code:

```
public class Demo{  
    public static void main(String[] arr){  
        Integer num1 = 100;  
        Integer num2 = 100;  
        Integer num3 = 500;  
        Integer num4 = 500;  
  
        if(num1==num2){  
            System.out.println("num1 == num2");  
        }  
        else{  
            System.out.println("num1 != num2");  
        }  
        if(num3 == num4){  
            System.out.println("num3 == num4");  
        }  
    }  
}
```

```

else{
    System.out.println("num3 != num4");
}
}
}

```

Choices:

- a) num1 == num2 num3 == num4
- b) num1 == num2 num3 != num4
- c) num1 != num2 num3 == num4
- d) num1 != num2 num3 != num4

Question 5: What will be the Output of the below code:

```

public class Demo{
    public static void main(String[] arr){

    }

    public static void main(String arr){

    }

}

```

Choices:

- a) Nothing
- b) Error

===

1. What will be the output of the below program?

```

public class StrEqual {

```

```

public static void main(String[] args) {
    String s1 = "hello";
    String s2 = new String("hello");
    String s3 = "hello";
    if (s1 == s2) {
        System.out.println("s1 and s2 equal");
    } else {
        System.out.println("s1 and s2 not equal");
    }
    if (s1 == s3) {
        System.out.println("s1 and s3 equal");
    } else {
        System.out.println("s1 and s3 not equal");
    }
}
}

```

Answer

s1 and s2 not equal

s1 and s3 equal

===

2. What will be the output of the below program?

```

public class Test {
    public static void main(String[] args) {
        String s = new String("5");
        System.out.println(1 + 10 + s + 1 + 10);
    }
}

```

```
}
```

Answer

115110

===

3. What will be the output of the below program?

```
public class Test {  
  
    public static void main(String[] args) {  
  
        String str = null;  
  
        System.out.println(str.valueOf(10));  
  
    }  
  
}
```

This program will print 10 in the console.

4. What will be the output of the below statements?

```
public class Test {  
  
  
  
  
  
  
  
  
    public static void main(String[] args) {  
  
        String s1 = "abc";  
  
        StringBuffer s2 = new StringBuffer(s1);  
  
        System.out.println(s1.equals(s2));  
  
    }  
  
}
```

Answer

false

5. What is the output of the below program?

```
public class A {  
  
    public static void main(String[] args) {  
  
        String s1 = new String("javaguides");
```

```
String s2 = new String("javaguides");  
  
System.out.println(s1 = s2);  
  
}  
  
}
```

The above program prints “javaguides” because we are assigning s2 String to s1. Don’t get confused with == comparison operator.

6. What is the output of the following program?

```
public class Test {  
  
    public static void main(String[] args) {  
        String s1 = "hello";  
        String s2 = new String("hello");  
  
        s2 = s2.intern();  
        System.out.println(s1 == s2);  
    }  
}
```

Answer

true

7. How many objects will be created in the following code and where they will be stored in the memory?

```
String s1 = "javaguides";
```

```
String s2 = "javaguides";
```

Answer

Only one object will be created and this object will be stored in the string constant pool.

8. How many objects will be created in the following code and where they will be stored?

```
String s1 = new String("javaguides");
```

```
String s2 = "javaguides";
```

Answer

Here, two string objects will be created. An object created using a new operator(s1) will be stored in the heap memory. The object created using a string literal(s2) is stored in the string constant pool.

9. What is the output of the below code snippet?

```
String s1 = new String("javaguides");
```

```
String s2 = new String("javaguides");
```

```
System.out.println(s1 == s2);
```

The above code snippet prints output as *false* because we are using a **new** operator to create String, so it will be created in the heap memory and both s1, s2 will have different references.

If we create them using double quotes, then they will be part of the string pool and it will print true.

10. What is the output of the below code snippet?

```
String s1 = "javaguides"
```

```
String s2 = "javaguides";
```

```
System.out.println(s1 == s2);
```

The above code snippet prints output as *true* because we have created both String objects using double quotes (String literals), then they will be part of the string pool and it will print true.

<https://codefinity.com/blog/The-80-Top-Java-Interview-Questions-and-Answer>

[The 80 Top Java Interview Questions and Answers](#)

[Tricky Java Interview questions and answers | Talent500 blog](#)