### **SYDE 556/750**

#### Simulating Neurobiological Systems Lecture 13: Conclusion

Chris Eliasmith

April 2, 2020

- ► Slide design: Andreas Stöckel
- ► Content: Terry Stewart, Andreas Stöckel, Chris Eliasmith






Image Sources. Left: "A chimpanzee brain at the Science Museum London", from Wikimedia. Centre: "Robot at a campus faire in São Paulo" from Wikimedia. Right: The Braindrop Neuromorphic hardware system, from "Braindrop: A Mixed-Signal Neuromorphic Architecture With a Dynamical Systems-Based Programming Model", Neckar et al., 2019.

## Building Large-Scale Brain Models

## Building Large-Scale Brain Models Why?

# Building Large-Scale Brain Models Why?



Understand how Brains Work

## Building Large-Scale Brain Models Why?



Understand how Brains Work



Build Better Al Systems

Image Sources. Left: "A chimpanzee brain at the Science Museum London", from Wikimedia. Centre: "Robot at a campus faire in São Paulo" from Wikimedia. Right: The Braindrop Neuromorphic hardware system, from "Braindrop: A Mixed-Signal Neuromorphic Architecture With a Dynamical Systems-Based Programming Model", Neckar et al., 2019.


## Building Large-Scale Brain Models Why?



Understand how Brains Work




Build Better Al Systems



Program Neuromorphic Hardware

Image Sources. Left: "A chimpanzee brain at the Science Museum London", from Wikimedia. Centre: "Robot at a campus faire in São Paulo" from Wikimedia. Right: The Braindrop Neuromorphic hardware system, from "Braindrop: A Mixed-Signal Neuromorphic Architecture With a Dynamical Systems-Based Programming Model", Neckar et al., 2019.

### Theoretical Neuroscience



### The Brain – Some Statistics

- ► Weight: 2 kg (2% of the body weight)
- ► Power consumption: 20 W (25% of the body's total power consumption)
- ► Surface area: 1500 cm² to 2000 cm² (roughly four A4/letter pages of paper)
- Number of neurons:  $100 \text{ billion } (10^{11}, 150 000 \text{ mm}^{-2})$
- Number of synapses: 100 trillion ( $10^{14}$ , about 1000 per neuron)

Goal: Brain-inspired hardware; lower power consumption; stream processing

Goal: Brain-inspired hardware; lower power consumption; stream processing

**Digital** 

Goal: Brain-inspired hardware; lower power consumption; stream processing

**Digital** 

- Specialised digital hardware for simulating spiking neural networks
- ► Trivial weight-spike multiplication
- Often asynchronous (no central clock)

Goal: Brain-inspired hardware; lower power consumption; stream processing

#### **Digital**

- Specialised digital hardware for simulating spiking neural networks
- Trivial weight-spike multiplication
- Often asynchronous (no central clock)

- ► Neuron models in analogue hardware (capacitors, resistors, ...)
- Digital interconnect and programming (weights, neuron parameters)

Goal: Brain-inspired hardware; lower power consumption; stream processing

#### **Digital**

- Specialised digital hardware for simulating spiking neural networks
- ► Trivial weight-spike multiplication
- Often asynchronous (no central clock)
- Deterministic
- Higher power consumption than analogue

- Neuron models in analogue hardware (capacitors, resistors, ...)
- Digital interconnect and programming (weights, neuron parameters)

Goal: Brain-inspired hardware; lower power consumption; stream processing

### **Digital**

- Specialised digital hardware for simulating spiking neural networks
- ► Trivial weight-spike multiplication
- Often asynchronous (no central clock)
- Deterministic
- Higher power consumption than analogue

- Neuron models in analogue hardware (capacitors, resistors, ...)
- Digital interconnect and programming (weights, neuron parameters)
- Not deterministic
- Hard to program
- Very low power consumption

## Neuromorphic Hardware – SpiNNaker



- ► Manchester/Dresden collaboration; HBP
- ► Fully digital
- ▶ 18 ARM968 processors @ 180 MHz per chip
- ▶ 1000 current-based LIF neurons per core
- ► Toroidal, asynchronous interconnect mesh
- ▶ Up to  $\approx 10^9$  neurons in one system

## Neuromorphic Hardware – SpiNNaker



- ► Manchester/Dresden collaboration; HBP
- Fully digital
- ▶ 18 ARM968 processors @ 180 MHz per chip
- ▶ 1000 current-based LIF neurons per core
- ► Toroidal, asynchronous interconnect mesh
- ▶ Up to  $\approx 10^9$  neurons in one system
- **Easy to program, (outdated) Nengo interface**
- Public access via HBP
- Not very power efficient (version from 2013)
- High setup times

## Neuromorphic Hardware – Loihi




Image Sources. Intel Marketing Material

- Developed by Intel
- ► Digital, fully asynchronous architecture
- Circuits accelerating individual spiking neurons

## Neuromorphic Hardware – Loihi




Image Sources. Intel Marketing Material

- Developed by Intel
- Digital, fully asynchronous architecture
- Circuits accelerating individual spiking neurons
- Extremely low power consumption
- Nengo Interface
- Proprietary/no low level programming without signing an NDA

## Neuromorphic Hardware – BrainDrop




Image Sources. Braindrop: A Mixed-Signal Neuromorphic Architecture With a Dynamical Systems-Based Programming Model, Neckar et al. 2019

- ► Research project at Stanford
- Mixed signal, analogue neurons, synapse arrays
- Exploits process noise for diverse neural tuning
- Optimized for NEF networks

## Neuromorphic Hardware – BrainDrop




Image Sources. Braindrop: A Mixed-Signal Neuromorphic Architecture With a Dynamical Systems-Based Programming Model, Neckar et al. 2019

- ► Research project at Stanford
- Mixed signal, analogue neurons, synapse arrays
- Exploits process noise for diverse neural tuning
- Optimized for NEF networks
- Extremely low power consumption
- Nengo Interface
- Availability/Documentation?
- Small networks only

## Neuromorphic Hardware – BrainScaleS





- Research Project in Heidelberg; HBP
- ► Mixed signal; above realtime
- ► Wafer-scale system; 384 x 256 neurons

## Neuromorphic Hardware – BrainScaleS





- Research Project in Heidelberg; HBP
- ► Mixed signal; above realtime
- ► Wafer-scale system; 384 x 256 neurons

- Low power consumption
- Public access via HBP
- Complex; relatively low precision

- ► Theory for theoretical neuroscience ( bridging laws )
- Principle 1: Populations of neurons represent values x
- Principle 2: Connections compute functions f
- Principle 3: Values are states in a dynamical system

- ► Theory for theoretical neuroscience ( bridging laws )
- Principle 1: Populations of neurons represent values x
- Principle 2: Connections compute functions f
- Principle 3:Values are states in a dynamical system
- Model of how the brain computes.

- ► Theory for theoretical neuroscience ( bridging laws )
- Principle 1: Populations of neurons represent values x
- Principle 2: Connections compute functions f
- Principle 3: Values are states in a dynamical system
- ▶ Model of *how* the brain computes. Is it wrong?

- ► Theory for theoretical neuroscience ( bridging laws )
- Principle 1: Populations of neurons represent values x
- Principle 2: Connections compute functions f
- Principle 3: Values are states in a dynamical system
- ▶ Model of *how* the brain computes. Is it wrong? Of course!

- ► Theory for theoretical neuroscience ( bridging laws )
- Principle 1: Populations of neurons represent values x
- Principle 2: Connections compute functions f
- Principle 3: Values are states in a dynamical system
- ▶ Model of *how* the brain computes. Is it wrong? Of course! But hopefully useful!

#### **▶** Cognitive Architectures

- ► Jackendoff's Challenges: How to explain language in neural networks?
- Vector Symbolic Architectures:
   Compressing symbolic information into vectors,
   circular convolution, word embeddings
- Semantic Pointer Architecture:
   Combination of four ideas What the brain computes.
  - VSAs
  - ▶ NEF
  - Deep Semantics: compression, decompression
  - ► Architecture: Basal Ganglia/Thalamus/Cortex Loop

#### ► Methods & Techniques

- ► The Delay Network: Efficiently compress past history into a vector; optimal recurrent update rule
- Spatial Semantic Pointers:
   Bio-inspired representation of continuous spaces; e.g., maps, probabilities
- Machine Learning:
   Unsupervised, supervised learning, gradient descent,
   least squares, nonnegative least squares, delta learning rule (PES)
- Signal Processing:
   Fourier, Laplace transformation; computing optimal filters
- Dimensionality Reduction: PCA/SVD; function bases; Hebbian learning/Oja learning rule

#### ► "Meta-Level Skills"

- Solving Problems by Building a Signal Flow Graph: Applications to Hardware design, differentiable computing
- Programming with Python/Numpy
- Building Neural Networks using Nengo:
   Can be applied to neuromorphic hardware (see above), cognitive modeling, machine learning

Thank You!

14 / 14