

Classification Model Evaluation



Outline


- ML Model Evaluation Metrics
- Underfitting & Overfitting Issues
- Reducing Model Complexity
(e.g., Tree Pruning)
- Ensemble Learning

ML Model Evaluation Metrics




This part is adapted from this [source](#)

Defining Training and Test Set Splits



- The model is trained on the **training set** (aka the train set), typically 70 to 80% of the data
- The remaining 20 to 30% of data that is **unseen** by the model during the training phase is called the **test set**
- Test set serves mimics the real-world scenario of running the model to predict new data points

Training, validation, and test set splits



- The **validation set** enables you to diagnose weak spots of the model and tune its parameters

Evaluating Classifier Accuracy



Cat

Cat

Cat

Not Cat

Cat

Not Cat

Cat

Not Cat


Cat

Cat

Evaluating Classifier Accuracy

- **What to Evaluate?**

- Accuracy is measured in terms of error rate
- Details of errors are shown in a confusion matrix



- A confusion matrix is a **table** that summarizes the performance of a classification model
- It shows the number of **correct predictions**: true positives (TP) and true negatives (TN)
- It also shows the **model errors**: false positives (FP) are “false alarms,” and false negatives (FN) are missed cases
- Using TP, TN, FP, and FN, you can calculate various classification quality metrics, such as precision and recall


False Positive vs False Negative

	Predicted	Actual	Correct?
1.	Not fraud	Not fraud	✓ True Negative
2.	Not fraud	Not fraud	✓ True Negative
3.	Not fraud	Fraud	✗ False Negative
4.	Fraud	Fraud	✓ True Positive
...			
n.	Fraud	Not fraud	✗ False Positive

- There are two types of errors the model can make:
 - It can make a **false alarm** and label an ordinary transaction as fraudulent (False Positive)
 - It can **miss real fraud** and label a fraudulent transaction as ordinary (False Negative)


True Positive vs True Negative

- How well the model can identify fraudulent transactions rather than how often the model is right overall



False Positive vs False Negative

- The distinction between false positives and negatives is important because the consequences of errors are different. You might consider one error less or more harmful than the other
 - In this scenario, False negative is more harmful



Spam Classifier

- **True Positive (TP)**

- Number of correctly identified positive cases: the number of correctly predicted spam emails (true positives is 600)

- **True Negative (TN)**

- It shows the number of correctly identified negative: the number of correctly predicted non-spam emails (true negatives is 9000)

- **False Positive (FP):**

- It shows the number of incorrectly predicted positive cases: these are **false alarms**
- This is the number of emails incorrectly labeled as spam (number of false positives is 100)


- **False Negative (FN):**

- It shows the number of incorrectly predicted negative cases: these are **missed cases**
- This is the number of missed spam emails that made their way into the primary inbox (false negatives is 300)




		Predicted	
		Spam	Non-spam
Actual	Spam	600 (True positive)	300 (False negative)
	Non-spam	100 (False positive)	9000 (True negative)

Accuracy



- Calculate accuracy by dividing all true predictions by the total number of predictions
- In our example, accuracy is $(9000+600)/10000 = 0.96$. The model was correct in 96% of cases
- However, accuracy can be misleading for imbalanced datasets when one class has significantly more samples (e.g., we have many non-spam emails: 9100 out of 10000 are regular emails)

Precision



- Precision is the % of **true positive predictions** in all positive predictions
 - It shows how often the model is right when it predicts the target class
- Calculate precision by dividing the **correctly identified positives** by the total number of positive predictions made by the model
- In our example, precision is $600/(600+100) = 0.86$. When predicting “spam” the model was correct in 86% of cases
- Precision is a good metric when the **cost of false positives is high**
 - If you prefer to avoid sending good emails to spam folders, you might want to focus primarily on precision

Recall

		Predicted	
		Spam	Not
Actual	Spam	600 (TP)	300 (FN)
	Not	100 (FP)	9000 (TN)

Recall

$$\frac{\text{Actual spam (TP)}}{\text{All spam (TP + FN)}}$$

- Recall, or **true positive rate (TPR)** shows the % of true positive predictions made by the model out of all positive samples in the dataset
 - i.e., the recall shows % instances of the target class the model can find
- Calculate the recall by dividing the number of true positives by the total number of positive cases
- In our example, recall is $600/(600+300)= 0.67$. The model correctly found 67% of spam emails. The other 33% made their way to the inbox
- Recall is a helpful metric when the **cost of false negatives is high**
 - E.g., you can optimize for recall for the classifier of Fraudulent transactions

F1 Score

$$\text{F1 Score} = \frac{2 \times (\text{Precision} \times \text{Recall})}{\text{Precision} + \text{Recall}}$$

- The F1 score is the harmonic mean of precision and recall. It provides a single metric that balances both precision and recall
- The F1 score reaches its best value at 1 (perfect precision and recall) and worst at 0.
- The F1 score is particularly useful in situations where there is an imbalance between the number of positive and negative instances in the dataset
 - It provides a more informative evaluation of the model's performance compared to accuracy alone, especially when the classes are unevenly distributed

Evaluating Classifier Accuracy


```
► y_pred = tree_clf.predict(X_test)
print("Predicted Labels:", y_pred) #Predicted labels the testing points
print("True Labels:      ", y_test) #True labels
print("Testing Accuracy:", metrics.accuracy_score(y_test, y_pred)) #1 mistake .. 59/60 = 0.983
```

```
Predicted Labels: [1 0 2 1 1 0 1 2 1 1 2 0 0 0 0 1 2 1 1 2 0 2 0 2 2 2 2 2 0 0 0 0 1 0 0 2 1
 0 0 0 2 1 1 0 0 1 1 2 1 2 1 2 1 0 2 1 0 0 0 1]
True Labels:      [1 0 2 1 1 0 1 2 1 1 2 0 0 0 0 1 2 1 1 2 0 2 0 2 2 2 2 2 0 0 0 0 1 0 0 2 1
 0 0 0 2 1 1 0 0 1 2 2 1 2 1 2 1 0 2 1 0 0 0 1]
Testing Accuracy: 0.9833333333333333
```

```
► from sklearn.metrics import confusion_matrix
confusion_matrix(y_test, y_pred) # 1 wrong prediction is made .. Accuracy |
```

```
|: array([[23,  0,  0],
        [ 0, 19,  0],
        [ 0,  1, 17]], dtype=int64)
```

```
► from sklearn.metrics import confusion_matrix, ConfusionMatrixDisplay
cm = confusion_matrix(y_test, y_pred) # 1 wrong prediction is made .. Accuracy
disp = ConfusionMatrixDisplay(confusion_matrix=cm, display_labels=tree_clf.classes_)
disp.plot()
plt.show()
```



Evaluating Classifier Accuracy

- **How to Evaluate?**

- Normally, a separate independently sampled test set is used to measure accuracy of a classification model
- Evaluation methods:
 - **Holdout Method**: divide data set (e.g., 70/30) as training and test sets

```
In [6]: ▶ #Take 40% of the data as testing and the remaining 60% as training
X_train, X_test, y_train, y_test = train_test_split(X_iris, y_iris, test_size=0.4, random_state=42)
y_train = y_train.to_numpy()
y_test = y_test.to_numpy()
print("Training Data", X_train.shape)
print("Testing Data", X_test.shape) #60 points for testing

Training Data (90, 2)
Testing Data (60, 2)
```

Decision tree trained on X_train

```
In [7]: ▶ tree_clf = DecisionTreeClassifier(random_state=42)
tree_clf.fit(X_train, y_train)
# Accuracy on the training dataset using the score method
print("Training Accuracy:", tree_clf.score(X_train, y_train))
```

Training Accuracy: 0.9888888888888889

Making Prediction

```
In [8]: ▶ y_pred = tree_clf.predict(X_test)
print("Predicted Labels:", y_pred) #Predicted labels the testing points
print("True Labels:      ", y_test) #True labels
print("Testing Accuracy:", metrics.accuracy_score(y_test, y_pred)) #1 mistake .. 59/60 = 0.983
```

```
Predicted Labels: [1 0 2 1 1 0 1 2 1 1 2 0 0 0 0 1 2 1 1 2 0 2 0 2 2 2 2 2 0 0 0 0 1 0 0 2 1
0 0 0 2 1 1 0 0 1 1 2 1 2 1 2 1 0 2 1 0 0 0 1]
True Labels:      [1 0 2 1 1 0 1 2 1 1 2 0 0 0 0 1 2 1 1 2 0 2 0 2 2 2 2 2 0 0 0 0 1 0 0 2 1
0 0 0 2 1 1 0 0 1 2 2 1 2 1 2 1 0 2 1 0 0 0 1]
Testing Accuracy: 0.9833333333333333
```

Evaluating Classifier Accuracy

- Evaluation methods:
 - **Cross Validation**: the data set is divided into k equal-size partitions. For each round of decision tree induction, one partition is used for testing and the rest used for training. After k rounds, the average error rate is used



Cross Validation

Every single point is used for testing once

```
In [12]: from sklearn.model_selection import cross_val_score
scores = cross_val_score(tree_clf, X_iris, y_iris, cv=5)
print(scores)

print("%.2f accuracy with a standard deviation of %.2f" % (scores.mean(), scores.std()))


[0.96666667 0.96666667 0.9        0.96666667 1.        ]
0.96 accuracy with a standard deviation of 0.03
```

```
In [18]: #50 cross validation. Each time, train on 147 and test on 3 samples
scores = cross_val_score(tree_clf, X_iris, y_iris, cv=50)
print(scores.round(2))

print("%.2f accuracy with a standard deviation of %.2f" % (scores.mean(), scores.std()))

[1.  1.  1.  1.  1.  1.  0.67 1.  1.  1.  1.  1.  1.  1.
 1.  1.  1.  1.  1.  0.67 0.67 1.  1.  1.  1.  1.  0.67 0.67
 1.  0.67 1.  1.  1.  0.67 1.  1.  1.  1.  0.67 1.  1.  1.
 1.  1.  1.  1.  1.  1.  1.  1.  ]
0.95 accuracy with a standard deviation of 0.12
```


Cross-validation



Splitting up the dataset into smaller chunks and rotating through them as training sets

Underfitting & Overfitting Issues


An **underfitted** model



Doesn't capture any logic

- High loss
- Low accuracy


A **good** model



Captures the underlying logic of the dataset

- Low loss
- High accuracy


An **overfitted** model



Captures all the noise, thus "misses the point"


- Low loss
- Low accuracy

Underfitting vs. Overfitting




$$\theta_0 + \theta_1 x$$

High Bias
(Underfitting)



$$\theta_0 + \theta_1 x + \theta_2 x^2$$

Low Bias, Low Variance
(Goodfitting)




$$\theta_0 + \theta_1 x + \theta_2 x^2 + \theta_3 x^3 + \theta_4 x^4$$

High Variance
(Overfitting)

Bias vs. Variance


- **Bias:** inaccurate predictions due to over-simplified model that underfits the training data and fails to capture important patterns and relationships between features and the target variable
 - E.g., a model that assumes that house prices are solely determined by size and ignores other relevant factors like location and number of bedrooms, it exhibits **high bias**. As a result, it will likely make inaccurate predictions (i.e., consistently under- or overestimate the true house value)
- **Variance:** measures the sensitivity of a model's predictions to changes in the training dataset
 - High variance indicates that the model is too complex and fits the training data too closely, including noise and outliers. Consequently, making it less generalizable to new, unseen data.
 - It performs well on the training data but fails to generalize to unseen data
 - E.g., Consider a classification model trained to distinguish between different types of flowers. If the model is too complex and captures random variations or noise in the training data, it will have high variance. As a result, it may perform well on the training set but fail to generalize to new data, misclassifying flowers it hasn't seen before
- Balancing these two aspects helps ensure that our models generalize well to unseen data and make accurate predictions

High variance example




- High variance: test error varies greatly based on the selected training set

High bias example



- High bias: high training error
 - Model performed poorly in both the training set and the testing set


Underfitting (High Bias) vs. Overfitting (High Variance)



- Underfitting: when model is too simple, **both training and testing errors are large**
- Overfitting: when the model is too complex than necessary, higher errors for unseen testing samples

The Problem of Model Overfitting

- Learning a tree that fits the training examples too well (e.g., a deep tree with pure leaves) may lead to **overfitting** of the training data (lower **generalization**). Causes include:
 - There may be noise (i.e., some feature values or class labels are incorrect) in the training data the tree is fitting
 - The algorithm might be making decisions based on specific features of the training examples than features of actual data at large




A decision tree **overfits the training data** when the model complexity grows:

- Its accuracy on the training data goes up but
- Its accuracy on unseen test data goes down


Overfitting

If we keep splitting, we will be reducing the error, but this causes **overfitting**




Overfitting = produced decision tree is more complex than necessary
Results in poor accuracy for unseen samples

Overfitting due to Noise



Decision boundary is distorted by noise point

Bias-Variance Tradeoff



Simple models:
High bias and low variance




Complex models:
High variance and low bias

Diagnosing ML Models

- **Simple model** → prone to underfitting (high bias & low variance)
 - It is computationally cheaper
 - The model fits poorly consistently
 - **Fixes:**
 - **Add features:** to have sufficient information, e.g., Not just use the size, add features like location and number of bedrooms to predict housing price
 - **Build more complex model**, e.g., larger trees, ANN with higher number of hidden layers, etc.
- **Complex model** → prone to overfitting (high variance & low bias)
 - It is computationally expensive
 - **Fixes:**
 - Use more data for training
 - Build less complex models, e.g., shorter trees, ANN with less number of hidden layers, etc.
 - Use Ensembling methods that aggregate responses of multiple base classifiers
 - Features selection -> use smaller set of features
- In real world, we would want to choose a model somewhere in between, that can generalize well but also fits the data reasonably well


Occam's Razor Principle

- In the context of evaluating ML models, Occam's Razor suggests that among competing models with similar predictive performance, **the simpler model should be preferred over the more complex model**
 - Simpler models are easier to understand, interpret, and maintain
 - Overly complex models may capture noise or irrelevant patterns in the training data (overfitting). Instead, select models that strike a balance between model complexity and generalization performance on unseen data
 - Therefore, one should include model complexity when evaluating a model





Tree Pruning



Pruning DT

- *Overfitting* the training data can be reduced by pruning the tree
 - Simplifying a Decision Tree making it smaller and more robust
- Two pruning strategies:
 - ***Pre-pruning***: stop building the tree before it is "complete"
 - ***Post-pruning***: build a full tree and then “cut back” certain subtrees and replace them with leaf nodes
- Pre-pruning is much faster but can stop prematurely, post-pruning is more accurate

Pre-pruning strategies

Stop building the tree (and make a leaf):

- At **max** tree depth
- When **number of instances in a leaf** is less than certain minimum
- When the change in Error rate, Gini index, or Entropy is below some threshold
- When **percentage of majority class** at a node is more than $n\%$

Post-pruning

- Build a full tree, then prune
- Pruning methods:
 - reduced error pruning
 - cost complexity pruning
 - pessimistic pruning
 - ...and many others

Reduced Error Pruning Method


- Split dataset into training and validation set
- Test the tree using the validation set instances. Note down the errors count at each node
- Prune the node with the highest reduction in error (applied in a bottom-up fashion)
 - Pruning = convert the node to a leaf labeled with the majority class at that node
 - In case of nodes with the same error reduction, choose to prune the node with the largest subtree
- Repeat until any further pruning increases the number of errors

Reduced Error Pruning - Example

Training set

AgeGroup	Gender	Married	YearsOf Experience	Class
teen	male	no	1	P
teen	male	yes	1	P
teen	female	no	2	N
adult	male	no	2	P
adult	female	yes	2	N
adult	male	yes	1	N
teen	female	yes	2	N
teen	male	no	3	N
adult	female	yes	1	P
senior	male	yes	2	N
senior	female	yes	2	N
senior	male	no	3	P


The Tree




Validation set

AgeGroup	Gender	Married	YearsOf Experience	Class
teen	male	no	2	P
teen	male	no	3	P
teen	female	no	2	P
teen	female	yes	2	P
adult	female	no	3	N
adult	female	yes	3	N
adult	female	no	2	N
teen	female	yes	1	P
senior	male	yes	1	N
senior	female	yes	1	N
senior	female	yes	3	N
adult	male	yes	2	N

The Tree with Errors count





Reduced Error Pruning - Example




Reduced Error Pruning - Example

Replacing this subtree
by N reduce errors by 1




Reduced Error Pruning - Example


Replacing this subtree by P has the same number of errors




Further pruning the tree increases the number of errors and hence pruning terminates



Ensemble Learning



General Approach of Ensemble Learning



- Basic Idea: Instead of learning one model, learn several and combine them
- Ensemble methods try to reduce the (overfitting) variance of complex models by *aggregating* responses of multiple base classifiers

Ensemble Methods

```
graph TD; A[Ensemble Methods] --> B[Bagging]; A --> C[Boosting]; A --> D[Stacking]; B --- B_desc[Homogeneous Learners<br/>Parallel Learning<br/>e.g. Random Forest]; C --- C_desc[Homogeneous Learners<br/>Sequential Learning<br/>e.g. Gradient Boosted Trees]; D --- D_desc[Heterogeneous Learners<br/>Parallel Learning];
```

Bagging

Homogeneous Learners
Parallel Learning
e.g. Random Forest

Boosting

Homogeneous Learners
Sequential Learning
e.g. Gradient Boosted Trees

Stacking

Heterogeneous Learners
Parallel Learning

Bagging (Bootstrap AGGREGatING)

Bootstrapping


(sampling with replacement)

Model Training

(train a model on each bootstrap using one type of algorithm such as Decision Tree, Logistic Regression)


Aggregation

(Classification: Majority vote is taken
Regression: Average of outputs)



Random forest: an example implementation of bagging

- Construct multitude of decision trained on a random subset of the data and makes independent predictions
- The final prediction is determined by **aggregating** the predictions of individual trees, such as through a majority vote for classification tasks or averaging for regression tasks
- **Pros:**
 - Improve accuracy over single models; reduces overfitting (variance)
 - Easy to parallelize
- **Cons:** Difficult to interpret the resulting model



Random Forest

One Single Tree

```
In [27]:  ▶ #One Single Tree  
          tree_clf = DecisionTreeClassifier(random_state=42)  
          tree_clf.fit(X_train, y_train)  
          print("Accuracy:", tree_clf.score(X_test, y_test))
```

Accuracy: 0.8716666666666667

Random Forest

```
In [28]:  ▶ randomForest_clf = RandomForestClassifier(n_estimators=100, random_state=42, max_samples=480)  
          randomForest_clf.fit(X_train, y_train)  
          print("Accuracy:", randomForest_clf.score(X_test, y_test))
```

Accuracy: 0.9166666666666666

Boosting

- Boosting allow **incrementally** building an ensemble
 - In each iteration, it sequentially train a **new model by focusing more on previously misclassified instances**
 - Initially, all **N** instances are assigned equal weights (equal chance for being selected for training)
 - For next round, the misclassified instances are assigned a **weight higher** than the correctly classified instances
 - Example 4 was misclassified in round 2
 - Its weight is increased. Therefore, it is more likely to be chosen again in subsequent rounds

Original Data	1	2	3	4	5	6	7	8	9	10
Boosting (Round 1)	7	3	2	8	7	9	4	10	6	3
Boosting (Round 2)	5	4	9	4	2	5	1	7	4	2
Boosting (Round 3)	4	4	8	10	4	5	4	6	3	4

Pros:


Reduces bias and variance
In some cases, boosting has been shown to yield better accuracy than bagging


Cons:

Tends to be more likely to overfit the training data
Sensitive to noisy data and outliers

Boosting

- **Equal weight** is given to the training data instances (D_1) at the **starting** round
 - (D_1) is then given to a base learner (L_1)
- The **mis-classified** instances by L_1 are assigned a weight higher than the correctly classified instances
 - This boosted data (D_2) is then given to second learner (L_2) and so on
- The results are then combined in the form of **weighted voting**, based on how **well a learner** performs






Stacking: training a ML model that combines the predictions of several base models trained using the same training data

- 1. Base Models:** Train several diverse base models on the training data using different algorithms
- 2. Generate Predictions:** Use each base model to make predictions on the validation set
- 3. Meta-Model Training:** Combine the predictions from the base models and use them to train a meta-model (typically a simple model like logistic regression, or decision tree)
- 4. Prediction:** Use the trained meta-model to make final predictions on unseen data

Stacking

- The main goal of stacking is to **improve the predictive performance** by leveraging the strengths of several base models, often yielding better performance than any single model in the ensemble
- It can help the model capture non-linear patterns and interactions between features that might be missed by individual models

Stacking Example



- Multiple machine learning algorithms (e.g., Decision Tree, XGBoost) are used as the base models trained on the same dataset
- Then we use the trained models to predict using the validation set
- The output of the base models on the validation set are then used to train the meta-model (Logistic regression in this example)