

Problem set 4

```

10
11 int main()
12 {
13     unsigned int i = 0x00646c72;
14     printf("H%x Wo%s", 57616, (char *) &i);
15 }

```

Hel10 World

...Program finished with exit code 0
Press ENTER to exit console.

```

11 int main()
12 {
13 |
14     printf("x=%d y=%d", 3);
15 }

```

x=3 y=1608135416

...Program finished with exit code 0
Press ENTER to exit console.

```

11 int main()
12 {
13 |
14     printf("x=%d y=%d", 3);
15 }

```

x=3 y=-1688812072

...Program finished with exit code 0
Press ENTER to exit console.

Value of y is not specific.

Backtrace:

```

xv6 kernel is booting

hart 1 starting
hart 2 starting
init: starting sh
$ bttest
backtrace:
0x0000000080001e98
0x0000000080001d72
0x0000000080001aac
0x00000003fffffff09c
$ |

```

Alarmtest

```

$ alarm test
exec alarm failed
$ alarmtest
test0 start
.....alarm!
test0 passed
test1 start
....alarm!
....alarm!
....alarm!
....alarm!
....alarm!
....alarm!
...alarm!
....alarm!
....alarm!
....alarm!
test1 passed
test2 start
.....alarm!
test2 passed
test3 start
test3 passed
$ |

```

Make grade:

```

== Test answers-traps.txt ==
answers-traps.txt: OK
== Test backtrace test ==
$ make qemu-gdb
backtrace test: OK (5.7s)
== Test running alarmtest ==
$ make qemu-gdb (7.8s)
== Test alarmtest: test0 ==
alarmtest: test0: OK
== Test alarmtest: test1 ==
alarmtest: test1: OK
== Test alarmtest: test2 ==
alarmtest: test2: OK
== Test alarmtest: test3 ==
alarmtest: test3: OK
== Test usertests ==
$ make qemu-gdb
usertests: OK (289.0s)
== Test time ==
time: OK
Score: 95/95
FatimaFaisal:~/xv6-labs-2025$

```