Mobile Application Development

Class Activity No.01

Of

Formik and Modal

Submitted By: Fatima Zahra

Sap Id: 55551

Submitted To: Ma’am Kausar Nasreen

Riphah International University of Islamabad

Modal

Simple:

```
import React, { useState } from 'react';
import { View, Text, Button, Modal } from 'react-native';
export default function App() {
  const [modalVisible, setModalVisible] = useState(false);
  return (
    <View>
      <Text>Hey Fatima Zahra 👀</Text>
      <Button
        title="Open Modal"
        onPress={() => setModalVisible(true)}
      />
      <Modal visible={modalVisible} >
        <View>
          <Text>This is modal popup text</Text>
          <Button
            title="Close"
            onPress={() => setModalVisible(false)}
          />
        </View>
      </Modal>
    </View>
  );
}
```

Internal styling:

```
import React, { useState } from 'react';
import { View, Text, Button, Modal } from 'react-native';
import { setDynamicFeatureFlag } from 'react-native-reanimated';
```

```
export default function App() {
  const [modalVisible, setModalVisible] = useState(false);
  return (
    <View style ={{flex:1,justifyContent:'center',allignItems:'center'}}>
      <Text style={{fontStyle:'italic',fontSize:20,marginBottom:20}}>Hey Fatima Zahra
👀</Text>
      <Button
        title="Open Modal"
        onPress={() => setModalVisible(true)}
      />
      <Modal visible={modalVisible} >
        <View
style={{flex:1,justifyContent:'center',alignItems:'center',backgroundColor:'rgba(0,0,0,0.5)'}>
          <view style={{backgroundColor:'white',padding:20,borderRadius:10}}>
           <Text style={{marginBottom:10}}> This is modal popup text</Text>
            <Button
           title="Close"
           onPress={() => setModalVisible(false)}
          />
           </view>
        </View>
     </Modal>
    </View>
  );
}
```

Global Styling:

```
const styles = StyleSheet.create({
  container: {
    flex: 1,
    justifyContent: 'center',
```

```
    alignItems: 'center',
  },
  title: {
    fontSize: 20,
    fontWeight: 'bold',
    marginBottom: 20,
  },
  modalBackground: {
    flex: 1,
    justifyContent: 'center',
    alignItems: 'center',
    backgroundColor: 'rgba(0,0,0,0.5)',
  },
  modalBox: {
    backgroundColor: 'white',
    padding: 20,
    borderRadius: 10,
  },
  modalText: {
    marginBottom: 20,
    fontSize: 16,
  }
});
```

Formik

Simple:

```
import React from 'react';
import { View, Text, TextInput, Button, StyleSheet } from 'react-native';
import { Formik } from "formik";
```

```
const styles = StyleSheet.create({
  container: {
    flex: 1,
    padding: 20,
    justifyContent: 'center',
  },
  input: {
    borderWidth: 1,
    borderColor: 'gray',
    padding: 10,
    marginBottom: 15,
  },
});
export default function App() {
  return (
    <Formik
      initialValues={{ title: "", body: "", rating: "" }}
      onSubmit={(values) => {
        console.log(values);
      }}
    >
      {({ handleChange, handleSubmit, values }) => (
        <View style={styles.container}>
          <Text>Title:</Text>
          <TextInput
            style={styles.input}
            onChangeText={handleChange('title')}
            value={values.title}
          />
```

```
        <Text>Body:</Text>
        <TextInput
          style={styles.input}
          onChangeText={handleChange('body')}
          value={values.body}
        />
        <Text>Rating:</Text>
        <TextInput
          style={styles.input}
          onChangeText={handleChange('rating')}
          value={values.rating}
        />
        <Button title="Submit" onPress={handleSubmit} />
      </View>
    )}
  </Formik>
 );
}
```

Output:

LOG {"body": "Call of duty", "rating": "5", "title": "Game"}

Using Props:

```
import React from 'react';
import { View, Text, TextInput, Button, StyleSheet } from 'react-native';
import { Formik } from "formik";
const styles = StyleSheet.create({
  container: {
    flex: 1,
    padding: 20,
    justifyContent: 'center',
```

```
  },
  input: {
    borderWidth: 1,
    borderColor: 'gray',
    padding: 10,
    marginBottom: 15,
  },
});
export default function App() {
  return (
    <Formik
      initialValues={{ title: " ", body: "", rating: "" }}
      onSubmit={(values) => {
        console.log(values);
      }}
    >
      {(props) => (
        <View style={styles.container}>
          <Text>Title:</Text>
          <TextInput
            style={styles.input}
            onChangeText={props.handleChange('title')}
            value={props.values.title}
          />
          <Text>Body:</Text>
          <TextInput
            style={styles.input}
            onChangeText={props.handleChange('body')}
            value={props.values.body}
```

```
        />
        <Text>Rating:</Text>
        <TextInput
          style={styles.input}
          onChangeText={props.handleChange('rating')}
          value={props.values.rating}
        />
        <Button title="Submit" onPress={props.handleSubmit} />
      </View>
    )}
  </Formik>
);
}
```

With destructuring:

```
import React from 'react';
import { View, Text, TextInput, Button, StyleSheet } from 'react-native';
import { Formik } from "formik";
const styles = StyleSheet.create({
  container: {
    flex: 1,
    padding: 20,
    justifyContent: 'center',
  },
  input: {
    borderWidth: 1,
    borderColor: 'gray',
    padding: 10,
    marginBottom: 15,
  },
```

```
});
export default function App() {
  return (
    <Formik
      initialValues={{ title: "", body: "", rating: "" }}
      onSubmit={(values) => {
        console.log(values);
      }}
    >
      {({ handleChange, handleSubmit, values }) => (
        <View style={styles.container}>
          <Text>Title:</Text>
          <TextInput
            style={styles.input}
            onChangeText={handleChange('title')}
            value={values.title}
          />
          <Text>Body:</Text>
          <TextInput
            style={styles.input}
            onChangeText={handleChange('body')}
            value={values.body}
          />
          <Text>Rating:</Text>
          <TextInput
            style={styles.input}
            onChangeText={handleChange('rating')}
            value={values.rating}
          />
```

```
        <Button title="Submit" onPress={handleSubmit} />
      </View>
    )}
  </Formik>
 );
}
```

Form in modal:

```
import React, { useState } from 'react';
import { View, Text, TextInput, Button, Modal, StyleSheet } from 'react-native';
import { Formik } from "formik";
const styles = StyleSheet.create({
 container: {
  flex: 1,
  justifyContent: 'center',
  alignItems: 'center',
 },
 modalBackground: {
  flex: 1,
  justifyContent: 'center',
  alignItems: 'center',
  backgroundColor: 'rgba(153, 141, 141, 0.5)',
 },
 modalBox: {
  backgroundColor: 'white',
  padding: 20,
  width: '80%',
  borderRadius: 10,
 },
 input: {
```

```
    borderWidth: 1,
    borderColor: 'black',
    padding: 10,
    marginBottom: 10,
  }

});
export default function App() {
  const [modalVisible, setModalVisible] = useState(false);
  return (
    <View style={styles.container}>
      <Button title="Open Form" onPress={() => setModalVisible(true)} />
      <Modal visible={modalVisible} transparent={true}>
        <View style={styles.modalBackground}>
          <View style={styles.modalBox}>
            <Formik
              initialValues={{ title: "", body: "", rating: "" }}
              onSubmit={(values) => {
                console.log(values);
                setModalVisible(false);
              }}
            >
              {({ handleChange, handleBlur, handleSubmit, values }) => (
                <View>
                  <Text>Title:</Text>
                  <TextInput
                    style={styles.input}
                    onChangeText={handleChange('title')}
                    onBlur={handleBlur('title')}
```

```
                value={values.title}
              />
              <Text>Body:</Text>
              <TextInput
                style={styles.input}
                onChangeText={handleChange('body')}
                onBlur={handleBlur('body')}
                value={values.body}
              />
              <Text>Rating:</Text>
              <TextInput
                style={styles.input}
                onChangeText={handleChange('rating')}
                onBlur={handleBlur('rating')}
                value={values.rating}
                keyboardType="numeric"
              />
              <Button title="Submit" onPress={handleSubmit} />
              <Button title="Close" onPress={() => setModalVisible(false)} />
            </View>
          )}
        </Formik>
      </View>
    </View>
  </Modal>
 </View>
);
}
```