




Software Development


Articles Ebooks Free Practice Tests On-demand Webinars Tutorials Live Webinars

Home Resources Software Development CSS Interview Questions and Answers [Top 75+]

 Sign in to simplilearn.com with Google 



fatma ghazouley
fatmaghazouley@gmail.com



Fatma Ashraf
bashraf500@gmail.com

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards



CSS Interview Questions and Answers [Top 75+]

By Simplilearn

Last updated on Oct 11, 2023

123772



Table of Contents

[Basic CSS Interview Questions](#)

[Intermediate CSS Interview Questions](#)

[Advanced CSS Interview Questions](#)

[Frequently Asked CSS Interview Questions](#)

[Choose The Right Software Development Program](#)

[View More](#)

Web applications and websites are increasing in every industry, and [CSS](#) is essential to build attractive websites. Currently, there is a tremendous demand for web developers who have a good knowledge of [HTML](#) and CSS. To build a career in web designing, candidates need to [crack interviews](#) where they ask CSS interview questions.

In this article, we have consolidated a list of CSS interview questions and divided the questions into four sections: basic CSS interview questions,

Level-Up Your Experience For Free!

[Course Recommendations](#)

[Salary Guides](#)

[Personalized Newsletters](#)

[Surprise Rewards](#)

Basic CSS Interview Questions

Let us begin with the basic CSS interview questions!

1. Name some CSS frameworks.

[CSS](#) frameworks are libraries that make web page styling easier. Some of them are Foundation, Bootstrap, Gumby, Uikit, Semantic UI, etc.



2. What do you understand by the universal selector?

A universal selector is a selector that matches any element type's name instead of selecting elements of a particular type.

Example:

```
<style>

* {

    color: blue;

    font-size: 10px;

}

</style>
```

Basics to Advanced - Learn It All!

Caltech PGP Full Stack Development

EXPLORE PROGRAM

3. Tell us about the use of the ruleset.

The ruleset is used for the identification of selectors, which can be attached with other selectors. The two parts of a ruleset are:

- Declaration block: contains one or more semicolon-separated declarations
- Sector: indicates the HTML element needed to be styled

4. What are the elements of the CSS Box Model?

The [CSS box model](#) defines the layout and design of CSS elements. The elements are content (like text and images, padding (the area around content), border (the area around padding), and margin (the area around the border).

5. Differentiate between CSS3 and CSS2.

The main difference between [CSS3](#) and CSS2 is that CSS divides different sections into modules and supports many browsers. It also contains new General Sibling Combinators responsible for matching similar elements.

6. How can CSS be integrated into an HTML page?

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards

Get the Coding Skills You Need to Succeed

Full Stack Development-MEAN

EXPLORE PROGRAM



7. Explain a few advantages of CSS.

With CSS, different documents can be controlled using a single site, styles can be grouped in complex situations using selectors and grouping methods, and multiple HTML elements can have classes.

8. What is meant by RGB stream?

RGB represents colors in CSS. The three streams are namely Red, Green, and Blue. The intensity of colors is represented using numbers 0 to 256. This allows CSS to have a spectrum of visible colors.

9. What was the purpose of developing CSS?

CSS was developed to define the visual appearances of websites. It allows developers to separate the structure and content of a website that was not possible before.

10. What is the difference between a class and an ID?

Ans. Class is a way of using HTML elements for styling. They are not unique and have multiple elements. Whereas ID is unique and it can be assigned to a single element.

Basics to Advanced - Learn It All!

Caltech PGP Full Stack Development

EXPLORE PROGRAM

Intermediate CSS Interview Questions

In the next section, let us learn some intermediate level CSS interview questions!

1. Define z-index.

This is one of the most frequently asked CSS interview questions. Z-index is used to specify the stack order of elements that overlap each other. Its default value is zero and can take both negative and positive values. A higher z-index value is stacked above the lower index element. It takes the following values- auto, number, initial, and inherit.

2. What are the benefits of CSS Sprites?

With CSS sprites, loading multiple images is not an issue.

Level-Up Your Experience For Free!

Course Recommendations

Salary Guides

Personalized Newsletters

Surprise Rewards

3. How can you target h3 and h2 with the same styling?

Multiple elements can be targeted by separating with a comma:

```
h2, h3 {color: red;}
```

4. Name media types allowed by CSS.

The different media types allowed by CSS are:

The different media types allowed by CSS are:

- speech
- audio
- visual
- tactile media
- continuous or paged media
- grip media or bitmap
- interactive media

5. How can you use CSS to control image repetition?

The background-repeat property is used to control the image. Example:

```
h3 {  
  
background-repeat: none;  
  
}
```

Basics to Advanced - Learn It All!

Caltech PGP Full Stack Development

EXPLORE PROGRAM

6. Tell us about the property used for image scroll controlling?

The background-attachment property is used to set whether the background image is fixed or it scrolls with the rest of the page. Example for a fixed background-image:

```
body {  
  
background-image: url('url_of_image');  
  
background-repeat: no-repeat;  
  
background-attachment: fixed;  
  
}
```

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards

The font-related attributes are font-style, variant, weight, family, size, etc.

8. Define contextual [selectors](#).

In CSS, contextual selectors allow developers to specify styles of different parts of the document. Styles can be assigned directly to specific HTML tags or create independent classes and assign tags to them.

9. Explain responsive web design.

Responsive Design is a web page creation approach that uses flexible images, flexible layouts, and CSS media queries. This design approach aims to create a web page that can be accessed and viewed on any device, from a desktop computer to a smartphone.

Responsive Design is a web page creation approach that uses flexible images, flexible layouts, and CSS media queries. This design approach aims to build web pages that detect the orientation and screen size of the visitors so that the layout can be changed accordingly.

10. Tell us about the general CSS nomenclature.

In CSS, the styling commands are written in value and property fashion. CSS includes a system terminator- semicolon. The entire style is wrapped in curly braces and attached to the selector. This creates a style sheet that can be applied to an HTML page.

Find the Most Suitable Course For

YOU

11. What are the limitations of CSS?

1. CSS cannot always assure compatibility with every browser; you need to be cautious while choosing the style selector.
2. The parent selector tag is not available, thus you can't select the parent selector tag.
3. Some selectors can lead to cross-browser issues due to their less browser-friendly behavior.
4. We cannot request a webpage through CSS.

12. How to include CSS in the webpage?

1. With the help of a link tag, you can include an external style sheet file as a CSS file into your HTML file.
2. You can add CSS styles included within your HTML page and write it in the stand-alone stylesheet form of CSS.
3. CSS can be included directly in the HTML tag by adding an inline style to HTML elements.
4. One can import an external stylesheet file as a new CSS file by using the @import rule.

Boost Your Coding Skills. Nail Your Next Interview

Full Stack Development-MEAN

EXPLORE PROGRAM

13. What are the different types of Selectors in CSS?

Universal Selector, Element type Selector, ID selector, Class selector, Descendant combinatory, Child Combinator, General Sibling Combinator, Adjacent sibling combinator, and Attribute selector.

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards

and code nesting within vanilla CSS scripts themselves.

1. Sass (Syntactically Awesome Style Sheets) uses .sass extension. It is used for indentation; it doesn't use semicolons or curly brackets.
2. Less (Leener Stylesheets) uses .less extension. It is easy to add to any JavaScript Project by using NPM or less.js file. Here, @ is used to define the variables.
3. Stylus provides great flexibility in writing syntax. It is able to use native CSS as well as the exclusion of brackets, colons, and semicolons. There is no need to use @ or \$ to define the variables.

People use SASS, LESS, and Stylus in order to extend the basic functionality of vanilla CSS.

15. What is VH/VW (viewport height/ viewport width) in CSS?

VH and VW are CSS units used to measure viewport height and viewport width respectively in percentage form in the responsive design techniques. E.g. If the height of the browser is 1000px, then VH is 1/100 of the height of the viewport that is $1000\text{px} \times (1/100) = 10\text{px}$, which is the height of the browser. The same applies to VW (viewport width).

16. Difference between reset vs normalize CSS? How do they differ?

1. Reset CSS is used to remove all built-in styles in the browser such as paddings, margins, and font sizes, and can be reset using all the elements.
2. Normalize CSS is used to make all built-in styles in the browser consistent and correct bugs as per varying browsers.

17. What is the difference between inline, inline-block, and block?

1. Block Elements are <div> and <p>. They usually start on a new line and can take space for an entire row or width.
2. Inline elements are <a>, , , and tags. They don't start on a new line. However, they appear on the same line as the content and tags beside them.
3. Inline block elements have padding and margins and set height and width values. Though, they are similar to inline elements.

18. Is it important to test the webpage in different browsers?

Yes, it is the most crucial thing or the most important trial to do when you design a webpage for the first time and make changes to it. Testing your website periodically in different browsers will help you make every webpage compatible with it as browsers have been going through many updates.

19. What are Pseudo classes?

Pseudo-classes are the type of pseudo-elements that don't exist in a normal document tree. It allows selecting the regular elements under certain conditions especially when we try to hover over the link; the anchor tags are :link, :visited, :hover, :active, :focus

In this example, the color will be red on the anchor tag when it's hovered.

```
/* mouse over link */
```

```
a:hover {
```

```
color: #FF00FF;
```

```
}
```

20. How do you specify units in the CSS? What are the different ways to do it?

There are mainly four different units in the CSS that are px, em, pt, and percentage (%).

1. Px (Pixel) is used for fine-grained control and alignment and not cascade. To get it sharp, we can use 1px or multiple of px.

Level-Up Your Experience For Free![Course Recommendations](#)[Salary Guides](#)[Personalized Newsletters](#)[Surprise Rewards](#)

4. Percentage (%) is used to set the font size with respect to the font size of the body. Thus, it is necessary to set the reasonable font size of the body.

21. Does margin-top or margin-bottom have an effect on inline elements?

No, mMargin-top or margin-bottom does not have an effect on the inline elements.

22. What property is used for changing the font face?

The font-family property is used for changing the font face that is applied to the element in the DOM.

23. What are the differences between adaptive design and responsive design?

- **Adaptive Design:**
- Main focus is to develop a website in multiple fixed layout sizes.
- Offers good control over the design to develop variation in screens.
- It is very time-consuming and takes a lot of effort to build the best possible adaptive design as examining it will need to go for many options with respect to the realities of the end user.
- There are six standard screen sizes for the appropriate layouts; they are 320px, 480px, 760px, 960px, 1200px, 1600px to design.
- **Responsive Design**
- Main focus is to show content with respect to browser space.
- Offers less control over the design.
- It takes less time to build the design and there is no screen size issue irrespective of content.
- It uses CSS media queries to design the screen layouts with respect to specific devices and property changes in the screen.

24. How are the CSS selectors matched against the elements by the browser?

Initially, there is a filtration of elements in the DOM via browsers with respect to key selectors that are traversed until we get parents' elements to determine the matches. Then the browser works on finding all the span elements present in the DOM and traverses them to parent elements to check whether they are matched to paragraph p elements. At last, when the browser finds all matches as parents, the matching process will be stopped and there will be black color applied to the content.

Here's How to Land a Top Software Developer Job

Full Stack Development-MEAN

EXPLORE PROGRAM

25. How is the border-box different from the content box?

Border-box consists of properties such as content, padding, and the border with respect to height and width. However, Content-box is a default value property used for the box-sizing as well as it helps to add border and padding to give proper height and width to the box without having a border and padding properties.

26. How is opacity specified in CSS3?

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards

27. What is cascading in CSS?

Cascading is defined as the process of style declaration and its weight that will help the browser in selecting the styling rules with respect to time.

28. When does DOM reflow occur?

DOM reflow occurs when you insert, move, update, remove, and animate the elements in the DOM as well as when you modify content on the and change style.

29. Different Box Sizing Property?

Content-box, Padding-box and Border-box

30. How to center align a div inside another div?

A div inside another div A is center aligned with the help of aligning div property to content via HTML script and CSS to the element in the DOM.

31. What is the grid system?

The CSS grid system is a type of powerful layout of 2 dimensional systems with respect to columns and rows.

32. What are the different ways to hide the element using CSS?

display: none, visibility: hidden, position: absolute

33. What does the: root pseudo-class refer to?

The: root selector pseudo-class refers to the CSS selector level 3. It helps to target the highest-level parent element present in the DOM.

34. What does Accessibility (a11y) mean?

Accessibility is to make the system accessible in such a manner that the website should have the text-to-speech capability, for people with physical disabilities, designed with the help of software or hardware combinations.

35. How do I restore the default value of a property?

keyword "initial" is used to restore the default value of a property.

36. Difference between CSS grid vs flexbox?

1. CSS Grid Layout is a two-dimensional system along with rows and columns. It is used for large-sized layouts.
2. Flexbox is a Grid layout with a one-dimensional system either within a row or a column. It is used for the components of an application.

37. How does Calc work?

Calc can be used to specify the result of the mathematical operation of two or more elements. For example to specify the width elements by the addition of two or more elements, we can write as

```
.foo {
```

```
Width: calc(100px+50px)
```

```
}
```

Level-Up Your Experience For Free![Course Recommendations](#)[Salary Guides](#)[Personalized Newsletters](#)[Surprise Rewards](#)**39. What is the difference between CSS variables and pre-processor (SASS, LESS, Stylus) variables?**

1. CSS variables don't need a pre-processor. It is cascaded, accessed, and manipulated in JavaScript.
2. Preprocessor variables don't cascade.

40. What does * { box-sizing: border-box; } do? What are its advantages?

Box-sizing: border-box is used to provide the inner dimension for the elements in the document by providing padding and border with respect to the

height and width of the content.

41. What does !important mean in CSS?

The style “!important” in the CSS has the highest precedence. Also, the cascaded property will be overridden with it.

42. What is progressive rendering? How do you implement progressive rendering on the website? What are its advantages?

Progressive rendering is the process of improving the performance of a webpage with respect to loading time in order to display the content speedily. The use of loading the lazy loading of the image with the help of Intersection Observer API via viewport.

43. Does style1.css have to be downloaded and parsed before style2.css can be fetched?

No. The CSS file will be downloaded via browser in order to appear on the HTML page.

44. How to determine if the browser supports a certain feature?

@support tag in the CSS is used to scan and determine whether the browser supports a certain feature or not.

45. How does absolute positioning work?

Absolute positioning is used to place the element which is then removed from the HTML document from the normal workflow without creating any space for the element in the HTML page layout. The element can be positioned respectively to the closest positioned ancestor; otherwise, if the ancestor is not found, the element is placed with respect to the initial container box. The values provided to the top, right, left and bottom determine the final position of the element.

46. Does this property work overflow: hidden?

Overflow: the hidden property is used to specify the content’s clipping. We need to add scrollbars to the content area at the time of specified container size exceeding the content limit where the content gets enclosed. This makes the content invisible via clipping; also the overflow value will be hidden.

Advanced CSS Interview Questions

Here are some advanced CSS interview questions!

1. When should you use translate () instead of absolute positioning?

Translate is a CSS transform value. On changing opacity or transform, browser reflow or repaint is not triggered. Transform requires the browser to create a GPU layer for elements but using the CPU changes absolutes positioning properties. Translate () is more efficient and results in shorter paint times. On using translate (), element occupies original space, unlike in changing absolute positioning.

2. Name different ways to position some aspects in CSS.

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards

3. What are mixins?

A mixin is similar to a function block of code returning a single value—mixin output lines of Sass code that directly compiles into CSS styles. At the same time, the function returns a value that becomes the value for a CSS property or something that can be passed to another mixin.

4. How can you optimize the webpage for prints?

Identify and control 'content areas' of the website. A website generally has a footer, header, sidebar, [navbar](#), and main content area. Most of the work is done by controlling the content area. So, conquer print media without changing the website's integrity by using page breaks, creating a stylesheet for print, size your page for print, and avoid unnecessary HTML tables.

for print, size your page for print, and avoid unnecessary HTML tables.

5. What is meant by CSS working under the hood?

When a browser displays a document, it combines style information and document content. The document is processed in two stages:

- Conversion of HTML and CSS into Document Object Model
- DOM displays contents of browser

6. Differentiate between the use of ID selector and class selector.

ID Selector:

```
<style>

{

text-align: right;

color: blue;

}

</style>
```

CSS class Selector:

```
<style>

.right {

text-align: right;

color: blue;

}

</style>
```

7. Tell us about CSS float property.

The float property of CSS positions an image to the right or left as needed, including text wrapping around it. All properties of elements used before it remain unchanged.

8. What do you understand by pseudo-elements?

Level-Up Your Experience For Free!

[Course Recommendations](#)[Salary Guides](#)[Personalized Newsletters](#)[Surprise Rewards](#)

Logical tags mainly focus on content and are older as compared to physical ones. Logical ones do not find much usage in presentation and terms of aesthetics. At the same time, physical ones find application in presentation.

10. How media types in CSS work?

The four types of media properties are print, speech, and screen. Example of using print-media type:

```
@media print {
```

```
h2 {  
  
background-color: blue;  
  
}  
  
}
```

Frequently Asked CSS Interview Questions

In this last section, we look at the most frequently asked CSS interview questions!

1. Tell us something about CSS3.

CSS3 is divided into modules and is supported by almost every browser. Many graphics-related characteristics are introduced in CSS3 like box-shadow, Border-radius, and flexbox. A user can create precise multiple background images using properties like background-position, background-repeat, and background-image styles.

2. How is a CSS selector used?

With a CSS selector, we can choose the content we want to style to bridge between HTML files and style sheets. CSS selector syntax is "select" HTML elements created on their class, id, type, etc.

3. What are CSS image scripts?

A group of images placed into one image is a CSS image script. It can reduce load time and project multiple images into a single web page.

4. Explain CSS specificity.

CSS specificity is a rank or score that decides style declaration to be used to an element. ID selectors have high specificity, while universal selector * has low specificity. The four CSS categories that authorize the selector's specificity level are IDs, inline style, elements/pseudo-elements, and classes and attributes.

5. Define gradients in CSS.

A property of CSS that allows displaying smooth transformation between two or more specified colors. The types of gradients are linear and radial.

6. What are the properties of flexbox?

The properties of flexbox are flex-direction, wrap, flow, content, and align-items, and content.

7. Tell us about the use of the CSS Box Model.

The CSS Box model is a box binding HTML element that includes padding, border, margin, and the actual content. With the box model, we get the

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards

The four-position states in CSS are relative, static, absolute, and fixed. The default position state is static.

9. Differentiate between absolute and relative in CSS.

The main difference is that relative is used for the same tag in CSS. If we write right:20 px, then padding shifts 20 px in the right. Whereas absolute is relative to the non-static parent, i.e., if we write right:20 px, the result will be 20 px far from the right edge of the parent element.

10. What is common between class and ID?

Both class and ID are used in HTML to assign a value from CSS. The ID is used as an element, whereas the class is used as a block.

Choose The Right Software Development Program

This table compares various courses offered by Simplilearn, based on several key features and details. The table provides an overview of the courses' duration, skills you will learn, additional benefits, among other important factors, to help learners make an informed decision about which course best suits their needs.

Program Name	Full Stack Java Developer Career Bootcamp	Automation Testing Masters Program	Post Graduate Program in Full Stack Web Development
Geo	IN	All	Non-US
University	Simplilearn	Simplilearn	Caltech
Course Duration	11 Months	11 Months	9 Months
Coding Experience Required	Basic Knowledge	Basic Knowledge	Basic Knowledge
Skills You Will Learn	15+ Skills Including Core Java, SQL, AWS, ReactJS, etc.	Java, AWS, API Testing, TDD, etc.	Java, DevOps, AWS, HTML5, CSS3, etc.
Additional Benefits	Interview Preparation Exclusive Job Portal 200+ Hiring Partners	Structured Guidance Learn From Experts Hands-on Training	Caltech CTME Circle Membership Learn 30+ Tools and Skills 25 CEUs from Caltech CTME
Cost	\$\$	\$\$	\$\$\$
	Explore Program	Explore Program	Explore Program

Conclusion

With this, we conclude our CSS interview questions article, and there is a high probability that your interviewer asks you these questions. Be thorough with your answers. You can also check [HTML-CSS training](#) for your preparation. If you are however looking for a comprehensive learning in full stack development, you should definitely check out our [Post Graduate Program in Full Stack Web Development](#) in collaboration with Caltech CTME. This online coding bootcamp offers applied industry-ready training in all the skills, tools, and languages you need to learn to become a successful full stack developer and accelerate your web development journey. Good luck!

Level-Up Your Experience For Free!

Course Recommendations Salary Guides Personalized Newsletters Surprise Rewards

Name	Date	Place	
Full Stack Developer - MEAN Stack	Cohort starts on 20th Dec 2023, Weekend batch	Your City	View Details
Full Stack Developer - MEAN Stack	Cohort starts on 3rd Jan 2024, Weekend batch	Your City	View Details

About the Author



Simplilearn

Simplilearn is one of the world's leading providers of online training for Digital Marketing, Cloud Computing, Project Management, Data Science, IT, Software Development, and many other emerging ...

[View More](#)

Recommended Programs



Full Stack Web Developer - MEAN Stack

868 Learners

Lifetime
Access*

*Lifetime access to high-quality, self-paced e-learning content.

[Explore Category](#)

NEXT ARTICLE



Talend Interview Questions for Freshers and Experienced Tech Professionals

By Simplilearn

4091

Feb 17, 2023

Level-Up Your Experience For Free!

[Course Recommendations](#)

[Salary Guides](#)

[Personalized Newsletters](#)

[Surprise Rewards](#)



Disclaimer

PMP, PMI, PMBOK, CAPM, PgMP, PfMP, ACP, PBA, RMP, SP, and OPM3 are registered marks of the Project Management Institute, Inc.

Level-Up Your Experience For Free!

- Course Recommendations
- Salary Guides
- Personalized Newsletters
- Surprise Rewards

