FULLSTACK PRODUCT ENGINEER · CASE STUDY

Making the candidate path trustworthy

AI Interview Platform — revamp report and execution narrative

Author	M. Fauzan Ahnaf Athallah
Date	16 October 2026
Repository	github.com/rakamindev/ai-interview-platform
Branch	`feat/platform-revamp` — 31 commits, 74 files changed (+8,447 / −180)
Pull request	github.com/rakamindev/ai-interview-platform/pull/182
Video walkthrough	**[video link — added before portal submission]**
Claimed depth	Frontend-heavy, with real backend depth — argued with evidence in §9

1 · Summary

The platform runs AI voice interviews and produces per-skill portfolios and fit/gap reports that hiring teams use to decide who moves forward. The scoring pipeline is backend work; the places where humans meet the results — the invitation link, the pre-flight checks, the interview screen, the assessor's fit/gap table — are where trust is created or destroyed. That is where this revamp works. The scope is frozen around *the candidate path you can trust*: from link to result, plus the tenant boundary that protects the data behind it.

What shipped:

1. **A pre-flight that measures the real path.** In production, the old check measured third-party CDNs that the production CSP blocks — so every candidate failed the hard gate and no interview could start (the P0). The check now measures the API origin the interview actually uses, fails closed (no fabricated values), tells *unreachable* apart from *slow*, and uses one documented threshold constant (2 Mbps down / 1 Mbps up / ≤ 300 ms ping).
2. **An interview page that tells the truth.** Invalid link, no-longer-available, unreachable (with retry), ready, ended (three honest copies), and connection-lost (reconnect, mic muted) are six distinct states sharing one layout. The old page showed a fabricated "Interview Complete — has been recorded" for invalid tokens, fetch failures, and even exhausted WebSocket reconnects.
3. **Tenant isolation where it was missing.** Export, fit/gap, regeneration, and override routes resolved portfolios by URL id with no ownership check — a cross-tenant read/write hole on sequentially enumerable ids. All five routes now fail closed with 404 and are covered by request specs.
4. **A result contract the UI can trust.** The engine emits `expected_level` and `is_override` for every comparison (additive — old reports keep rendering); the UI renders the Required column, marks overridden levels, formats levels consistently (L1–L5), and surfaces errors instead of blank pages.
5. **Canonical skill identity.** Nothing a language model invents is stored as truth anymore: skill ids are resolved against the taxonomy (case-insensitive id → label → null), the picker stores taxonomy ids, and a reversible migration backfills existing rows.
6. **A harness where none existed.** RSpec + FactoryBot, Vitest + Testing Library, a RuboCop baseline, and a CI workflow — because none of the five changes above is provable without it.

> **At a glance:** 31 commits · 74 files changed (+8,447 / −180) · 50 API examples · 29 web tests · 111 files lint-clean · 22 findings (1 P0 · 5 P1 · 7 P2 · 9 P3 → 12 fixed, 3 partial, 7 deferred with reasons) · one seeded-fault branch left visible on purpose (§7).

How to read this report: §2 product context and UU PDP; §3 findings; §4 strategy and trade-offs; §5 acceptance criteria and edge cases; §6 the step-by-step execution narrative; §7 verification and evidence; §8 screenshots; §9 claimed depth; §10 limitations and follow-ups; §11 links. The video walkthrough link (§11) is added before portal submission.

2 · Product context & who this is for

The product

An assessor creates an assessment (skills drawn from a taxonomy, language, duration), invites candidates with a link, and the candidate completes a voice interview with an AI interviewer (audio streamed to Gemini Live). The backend then produces a *portfolio* — per-skill coverage with transcript evidence — and a *fit/gap report* against a vacancy. Recruiters read those results to decide who moves forward.

Two users, asymmetric power

Recruiters choose the product, work fast, and read results. Candidates never chose the product: they receive a link, often on a phone, sometimes with one shot at the process. A mislabeled failure or a false "recorded" claim costs the recruiter minutes — it can cost the candidate the opportunity. That asymmetry is why this revamp prioritizes the candidate's path and the correctness of the result contract over new features.

Industry context

Indonesia's hiring market is high-volume and cost-sensitive. Unemployment is low (4.85%, Aug 2025) yet volume hiring never stops — led by outsourcing/staffing, BPO, and government selection. AI interviewing is no longer novel: local vendors already market Indonesian-language interviews as table stakes, and CV/ATS ranking is commoditized. What remains hard — and what this product's portfolio/fit-gap design is built around — is *consistent per-skill rubrics, evidence traceable to the transcript, and an audit trail*. Candidate trust is the scarce resource: only about a quarter of candidates believe AI will judge them fairly, roughly two-thirds want disclosure when AI is used in hiring, and most would rather have a human in the loop. Every fabricated success screen or misleading failure erodes exactly the trust this product runs on. WhatsApp is the default candidate channel, and the price anchor is tens of thousands of rupiah per candidate — so drop-off and cost per interview both matter.

UU PDP implications

The platform processes personal data by definition: names, audio, transcripts, scores. Since 17 October 2024 the PDP Law (UU 27/2022) is fully in force, and its implementing regulation (PP 33/2026) takes effect 16 January 2027 — adding mandatory DPIAs for AI-driven scoring, a right to object to automated decisions, written retention policies, and stricter cross-border transfer rules. Two facts shaped this work directly:

- **Audio streamed to Gemini is a cross-border transfer.** The free tier explicitly allows training and human review of submitted data — real candidate data requires the paid tier plus binding contractual safeguards. This is documented as a constraint signal (§3), not silently ignored.
- **Erasure is not implementable today.** There is no delete path, and a foreign key blocks portfolio destruction — a compliance gap that needs an architecture decision (soft vs hard delete, employer↔platform orchestration), not a quick patch.

Within this revamp's scope, the PDP angle is respected through minimization: no PII in logs or commits, synthetic demo data, reversible migrations, and no new silent data retention.

3 · Findings — severity-ranked

Method: a full read of both codebases, then the workflow walked end-to-end with synthetic data — database records → API payloads → UI rendering — with every finding pinned to `file:line` and a reproduction. 22 findings survived; three suspected issues were investigated and dismissed (for example, a Redis 5.x method that is actually aliased, not missing). Severity rubric: **P0** the core flow cannot run at all · **P1** wrong decisions or data leakage on common paths · **P2** serious degradation, silent failure, or misleading information · **P3** hygiene, drift, latent risk.

ID	Sev	Category	Finding	Status
F-01	P0	defect	Production pre-flight measured third-party CDNs that the production CSP blocks, and a hard gate then stopped *every* candidate from starting an interview.	Fixed
F-02	P1	defect	Thresholds (8/4 Mbps) far above voice needs blocked working connections — while a total upload failure returned a fabricated 4.0 Mbps that passed the gate.	Fixed
F-03	P1	defect	Portfolio export / fit-gap / regeneration / override routes trusted the URL id — cross-tenant read and write on sequential ids (IDOR).	Fixed
F-04	P1	defect	The fit/gap "Required" column read a field that was never emitted; the assessor-override marker was never emitted either.	Fixed
F-05	P1	defect	Any fetch failure on the candidate page (invalid token, outage) rendered "Interview Complete — has been recorded".	Fixed
F-20	P1	defect	Exhausted WebSocket reconnects also ended on a fabricated completion while the session stayed active with no recording.	Fixed
F-06	P2	defect	Silent-failure cluster: blank pages with no error state or retry, and `as any` casts hiding contract drift.	Partial
F-07	P2	defect	"Create Link" could fail with no feedback at all (try/finally without catch) — the dialog just closed.	Fixed
F-08	P2	missing spec	Taxonomy skill ids were dropped on selection and portfolio ids were authored by the LLM — cross-layer matching silently degraded to text labels.	Fixed
F-09	P2	defect	The sample `APP_BASE_URL` pointed at the API — every fresh setup produced invitation links that 404.	Fixed
F-10	P2	defect	Interview language cannot be changed after an assessment is created (create page sends it; edit page does not).	Deferred
F-11	P2	missing spec	No erasure path exists; a foreign key blocks portfolio deletion — the PDP erasure right is technically unfulfillable today.	Deferred
F-21	P2	defect	Default Gemini model names were retired upstream — fit/gap narratives silently fell back to templates under a 200 OK.	Deferred
F-12	P3	defect	Copy: pluralization "1 skills"; an internal codename ("B7") leaked into the UI.	Partial
F-13	P3	defect	Dead code and dead enum values: unmounted middleware, unused helpers, an unrouted page, a status that is never written.	Deferred
F-14	P3	defect	Duplicate index on `coverage_maps.session_id` (already covered by a composite unique index).	Deferred

ID	Sev	Category	Finding	Status
F-15	P3	defect	Setup docs drift: wrong API port (3000 vs 3001), a wrong env var name, a wrong folder name — onboarding bugs that are not bugs.	Partial
F-16	P3	defect	Speaker contract drift (`ai` relabeled to `assessor` in one layer) hidden by a tolerant UI — a trap for future consumers.	Deferred
F-17	P3	defect	TypeScript types disagreed with real payloads (`skill_id` number vs string, `ai_level` string vs integer); level text rendered raw "3" in one place, "L3" in another.	Fixed
F-18	P3	defect	`web/package-lock.json` existed but was never committed — dependency drift across machines and CI.	Fixed
F-19	P3	defect	Tenant resolution fallback: hardcoded `'test-corp'` plus `LIMIT 1` without `ORDER BY` — the root of the "wrong tenant" class.	Deferred
F-22	P3	defect	Assessor pages overflowed horizontally at mobile widths (measured scrollWidth up to 527 at a 390 px viewport).	Fixed

Constraint signals — things a repo-scoped change cannot decide

1. **Pre-flight is a product decision, not just a bug.** Hard gate vs advisory, thresholds calibrated to voice needs, and a help channel for candidates who fail — these touch product value (signal validity), not just UI.
2. **Multi-tenant boundaries are not uniform.** Some core models sit outside the tenant scope, and the scope itself falls back to "all" when context is missing. Children should be scoped through their parent, and sibling endpoints audited.
3. **Erasure and retention have no owner.** No delete path exists today, while PP 33/2026 makes retention policies and subject requests (≤ 72 h) mandatory from January 2027. This needs an architecture decision before production.
4. **Skill identity must have one source of truth.** A generative step must never define identifiers; the taxonomy id is the canonical key end-to-end.
5. **Gemini transfers require the paid tier plus DPA/TIA** before real candidate data flows (the free tier allows training and human review of submitted data).
6. **Setup documentation is the repo's first contract.** It currently ships wrong values (F-15); fix it before the next engineer follows it.

4 · Strategy & trade-offs

The gap in one sentence: the platform computes results well enough, but the seams where humans meet those results were unowned — failures mislabeled, successes fabricated, a presentation contract that drifted, and an identity key that dissolved into free text.

Scope options

	A — "Candidate can start"	B — "Results can be trusted"	C — Combined (chosen)
Content	Wire the speed test to the API, calibrate thresholds, fix candidate error states.	Tenant scoping, fit/gap contract, skill identity.	A + B, plus adjacent small findings on the same path (F-07, F-09).
User impact	Unblocks the flow that was impossible in production.	Stops wrong results and personal-data leakage.	The complete story: link → interview → result.
Cost	Small–medium; web-heavy, one backend endpoint.	Medium; backend-heavy, one small migration, more specs.	Medium–large; the right depth for the rubric.
Maintainability	High — the third-party dependency disappears.	High — scoping and contract patterns become examples.	High — every fix leaves tests behind.
Failure modes	API down → pre-flight fails explicitly, not silently.	Wrong scope → 404 (fail closed); rogue model output → rejected.	Both fail-closed and tested.
Codebase fit	Uses the existing but unwired `speed_test` endpoint.	Completes the thin-controller + service + concern pattern.	Touches `api/` and `web/` proportionally.

Why C: the rubric rewards a real change in experience plus engineering quality. A alone touches the backend too thinly; B alone misses the P0; C also yields the natural failure paths the brief asks for — pre-flight failure, invalid link, API error, rogue model output, cross-tenant access.

Shape of the pull request

One comprehensive PR chosen over an umbrella PR with sub-PRs. With no reviewer team to benefit from stacked branches, sub-PRs would only add coordination and rebase cost — and risk reading as unfinished work. The "giant PR" risk is managed instead by commit discipline: atomic commits ordered harness → backend → frontend → failure paths, with theme-clean diffs and every commit green. Seeded-fault evidence lives on a separate scratch branch, deliberately without a PR.

Decision trade-offs

Decision	Chosen	Rejected alternative, and why
Speed-test target	Measure the API origin the interview actually uses.	Third-party CDNs — blocked by the production CSP, and measuring a CDN says nothing about the interview path.
Thresholds	2 Mbps / 1 Mbps / ≤ 300 ms as one documented constant.	Keep 8/4 Mbps — 20–80× above what voice needs; it blocked working connections.
Failure semantics	Fail closed: unreachable ≠ slow, no fabricated values.	Keep fallback defaults — a probe that never ran must never pass a gate.

Decision	Chosen	Rejected alternative, and why
Override flag	Additive `is_override` on every comparison.	Schema change / required flag — old reports must keep rendering (verified by spec).
Skill ids	Resolve-or-null against the taxonomy (case-insensitive id → label → null).	Trust the model's ids — unverifiable; drop ids entirely — matching degrades to labels.
Notice screens	One shared notice component for all six interview states.	Six duplicated blocks (flagged in independent review; refactored before push).
Model output handling	Validate the whole payload before writing anything.	Write-then-fail — a half-written portfolio is worse than a failed generation.

Rejected and deferred findings (with reasons)

Findings	Reason
F-06 full scope	The touched pages (portfolio, fit/gap) were fixed with their workstreams; the rest (edit, invite, monitor) spread too wide without adding depth — follow-up.
F-10	A real gap, but standalone; it does not strengthen the candidate-path story — next iteration.
F-11	Touches data-architecture decisions (soft vs hard delete, employer orchestration) — escalated as a constraint signal + roadmap, not patched without a spec.
F-13, F-14, F-16, F-19	Hygiene and latent risk: cheap but behavior-neutral for the chosen path — listed as follow-ups in §10.
F-21	Config/infra outside the repo scope (deployment config + defaults); documented with a verified local workaround — §7, moment 1.

5 · Acceptance criteria & edge cases

35 acceptance criteria were derived *before* coding, each mapped 1:1 to a test or a recorded walk — including the brief's edge cases (skills never assessed, empty ratings, model failures, odd data types, long text). The table summarizes the areas; the full list, with per-criterion evidence, is part of the working notes and was re-verified before submission.

Area	Count	Representative criteria
Global (no regression)	3	Existing assessor flow still works; build, specs and lint green; no new `as any` in touched files.
Pre-flight & speed test	8	Origin-only probes; byte-sized download endpoint; one threshold constant; unreachable ≠ slow; no fabricated pass; retry; sample link opens the candidate page.
Interview & invite	6	Invalid link ≠ finished; network error + retry; honest "ended" copies; invite dialog keeps the error visible; connection lost → reconnect, never a fake completion.
Tenant scoping	3	All five portfolio/fit-gap/override routes → 404 for another tenant; same-tenant behavior unchanged; the original IDOR reproduction now 404.
Fit/gap contract	6	`expected_level` + `is_override` on every entry; Required column renders; override marker shown; not-assessed preserved; L1–L5 everywhere; old reports render.
Skill identity	8	Picker stores taxonomy ids; coverage map carries them; generator resolves id → label → null; prompt echoes coverage ids; case-insensitive matching; reversible backfill; malformed output fails cleanly; evidence capped at three quotes.
Repo hygiene	1	`package-lock.json` tracked and consistent with `package.json`.

Edge cases — behavior after the revamp

Edge case	Verified behavior
Skill never assessed	`not_assessed` with null delta; UI shows "— Not assessed" with a neutral badge.
Empty rating / level	Database enforces NOT NULL and clamps 1–5; a null candidate level renders "—"; overrides are validated at the boundary.
Model call fails / times out / partial	Fit/gap: fallback narrative + server log (spec-covered). Portfolio: status `failed` + error surfaced in the UI with retry; timeouts fail cleanly with no half-written skills (spec-covered); malformed payloads fail *before* any write.
Duplicate / stale jobs	Re-generation replaces skills instead of duplicating; fit/gap re-generation reuses the report row; a job for a deleted session is skipped without crashing.
Odd data types	Contract aligned end-to-end (string ids, numeric levels); invented ids are resolved or dropped, never stored.
Long text	Evidence capped at three quotes; wrapping verified on desktop and mobile with real-length content.
Invalid / expired token	Explicit invalid-link screen with guidance — not a completion screen.
Session already ended	Honest copies differentiated by end reason and whether the interview actually started.
Connection lost mid-interview	Connection-lost screen + Reconnect (mic muted); reload resumes; never "has been recorded".

6 · Execution narrative — step by step

Step 1 — Discovery and baseline. Cloned and ran both services, walked the real workflow with synthetic data, and recorded the baseline honestly: no test suite, no test runner, no CI — exactly the starting point the brief describes. First-run friction (setup docs pointing at the wrong port and folder) went straight into the findings list.

Step 2 — Context. Traced the product from database schema → API payloads → UI rendering. Researched the PDP obligations that actually apply (UU 27/2022, PP 33/2026, the Gemini data terms) and the industry landscape (market structure, candidate sentiment, pricing anchors) so the scope would reflect the product's real constraints, not just code smells.

Step 3 — Findings. 22 findings with a consistent severity rubric, every one pinned to file:line with a reproduction. Three suspected issues were investigated and dismissed with reasons — recorded so they are not re-litigated. Six constraint signals were escalated for decisions above the code (§3).

Step 4 — Strategy and acceptance criteria. Scope frozen to option C; 35 acceptance criteria written before any implementation, each mapped to its future evidence; trade-off matrix and commit plan fixed up front.

Step 5 — Implementation. The harness came first (otherwise nothing after it is provable), then the five workstreams, highest severity first, each commit green, Conventional Commits, no AI attribution anywhere.

Stage	What happened	Commits
Harness	RSpec + FactoryBot, Vitest + Testing Library, RuboCop baseline, CI workflow (API + web jobs).	`up to f359145`
Tenant scoping	`Portfolio.for_tenant` + fail-closed 404 across five routes; 11 request specs two-tenant.	`f030d69`
Pre-flight	Speed-test endpoints + spec; client rewrite (origin-only, fail closed); thresholds; UI copy + retry.	`e588dbf → 8ce590d`
Interview states	`candidate_info` + `end_reason` payload; six-state page; invite dialog error; reconnect fix.	`a639eb3 → b0d3919`
Fit/gap contract	Engine `is_override` + spec; web contract and types; error surfacing.	`3f9ed7c → 46ebb7d`
Skill identity	Canonicalization + specs; reversible backfill migration; picker/card; copy cleanup.	`9908d49, 3eb08cd, 11c93dc, 0d47ca3`
Mobile fix (F-22)	Assessor headers wrap; verified at 390 px on all affected pages.	`811467a`
Review fixes	Unreachable marker; shared notice component; case-insensitive id match; payload validation; lint.	`91f2954, 2f9a6fd, a127f8c, 4934c21, 89cef7d`
Seeded fault (scratch branch)	Break → five specs fail → revert → green. Left visible on purpose.	`f41c7f4 → 862535d`
Failure-path specs	Model timeout → portfolio fails cleanly; narrative failure → rule-based fallback; duplicate jobs → idempotent regeneration and report reuse; stale job for a deleted session → skipped.	`d6abc0c → f304d07`

Step 6 — Failure-path verification. Seeded fault on a scratch branch; runtime fault injection (the API was cut during a live interview to prove the reconnect behavior); migration rollback/redo; a PII audit over all commits

and artifacts; CSP verification; a desktop + mobile UI audit that produced finding F-22, fixed immediately; and a mechanical self-review (no new debug output, casts, or disabled rules).

Step 7 — Independent review and fixes. Before pushing, the full diff was reviewed on two axes — standards (repo conventions, baseline smells) and spec (does the code match the findings, strategy and acceptance criteria). Three real gaps were fixed with new tests; one reviewer finding was rejected as a false positive with written reasoning. Details in §7.

Step 7b — Failure-path specs. The brief's "designed failure paths" baseline was audited against the suite: partial writes and malformed output were already covered, but model timeouts, narrative-call failures, duplicate jobs, and stale jobs were not. Four specs were added to pin each behavior to a test.

Step 8 — Submission. This report, the curated screenshots in `assessment/screenshots/`, and a 3–5 minute video walkthrough of the problem → demo → enhancement arc.

7 · Verification & evidence

Gates at final HEAD (`f304d07`)

Gate	Result
API specs (RSpec + FactoryBot)	50 examples, 0 failures.
API lint (RuboCop)	111 files inspected, 0 offenses.
Web tests (Vitest + Testing Library)	29 tests across 8 files, all green.
Web build (TypeScript + Vite)	Green.
CI workflow	Added (API job: Postgres service, schema load, RuboCop, RSpec; web job: install, build, tests). First run happens on the pull request.

Seeded fault — proof the tests guard the fix

On the scratch branch `scratch/seeded-fault-idor`, the tenant scope is deliberately broken (the scoped query replaced by an unscoped one), the suite is watched failing, and the change is then reverted — with both commits left visible in the history, as the brief asks. The point is not that tests exist, but that they were *watched failing* for the exact regression they claim to guard.

```
# scratch/seeded-fault-idor
862535d  Revert "temp: seed fault to prove the cross-tenant specs fail"
f41c7f4  temp: seed fault to prove the cross-tenant specs fail
811467a  fix(web): let headers wrap on narrow screens

# At f41c7f4 — Portfolio.for_tenant replaced by an unscoped query:
42 examples, 5 failures
  GET  /portfolios/:id/export              expected 404, got 200
  GET  /portfolios/:id/fitgap/:vacancy_id  expected 404, got 200
  POST /portfolios/:id/fitgap              expected 404, got 202
  POST /portfolios/:id/regenerate_fitgap   expected 404, got 202
  POST /portfolio_skills/:id/override      expected 404, got 201

# At 862535d — after git revert:
42 examples, 0 failures
```

(Counts shown as recorded at that commit; the suite grew to 50 examples with the review-fix and failure-path specs afterwards.)

Runtime fault injection — the reconnect path

During a live interview, the API was cut to simulate an outage. Before the fix, the candidate saw “Interview Complete — has been recorded” within seconds while the session stayed `active` with no recording. After the fix, the page shows the connection-lost screen with a Reconnect button and the microphone muted; reloading resumes the interview correctly. A real-world reproduction of the same failure class also occurred on the local dev machine (a native-extension crash kills the audio socket — §10), which is how the runtime fault was first confirmed.

AI verification moments

Moment 1 — a report that looked right while the model never ran. Walking the fit/gap flow returned a fully populated report with HTTP 200 — but the narrative was a template fallback. The worker log held the

truth: `API error 404: "This model models/gemini-2.0-flash-001 is no longer available..."`. Verification went three layers deep: the verbatim provider error, a live model listing for the same key (no 2.0-generation and no live models at all), and per-model `generateContent` probes. Outcome: a verified local override to a current model; the retired defaults are flagged as a constraint signal with a documented workaround (F-21). Lesson recorded: "the report renders" is not evidence that the model ran.

Moment 2 — the model was authoring identity. Portfolio rows stored skill ids like `sk-eng-001` — invented by the LLM, never validated — while the taxonomy uses `SK-ENG-001`; cross-layer matching had silently degraded to text labels. Verification: trace a stored id back to the taxonomy, then to the prompt that produced it. Outcome: canonicalization (case-insensitive id → label → null), a prompt that instructs echoing coverage-map ids, and a reversible backfill for existing rows. Lesson: a generative step must never define identifiers; resolve to a source of truth or store null.

Moment 3 — review output is input, not verdict. An independent two-axis review of the full diff found three real gaps — the unreachable-vs-slow signal was missing (AC-1.4), the fit/gap engine matched ids case-sensitively (AC-5.5), and malformed model output could half-write a portfolio (AC-5.7) — all fixed with new tests. It also flagged one duplicate-state concern that turned out to be a false positive: the flag in question distinguishes "session ended when the link was opened" from "ended during this visit", which the candidate payload cannot express. Rejected with written reasoning instead of applied blindly. Lesson: dispositions matter as much as findings.

Migration safety

```
== BackfillAssessmentSkillIds: reverting (down) ==
== BackfillAssessmentSkillIds: reverted ==
== BackfillAssessmentSkillIds: migrating (up) ==
== BackfillAssessmentSkillIds: migrated ==
assessment_skills (non-custom):  #1 SK-ENG-001  ·  #3 SK-ENG-009
custom skills (must stay NULL):  1 row — skill_ids=[nil]
```

The migration was exercised with migrate → rollback → migrate and a full redo; custom skills stay NULL in every phase; the `down` path documents its own predicate limits honestly. On the test database the schema is loaded fresh in CI, so the local sync step needed after new migrations is documented for contributors.

PII audit (UU PDP)

- Git history (every commit, full patch): no real API keys (only the placeholder in the sample file), no JWTs, no real identities.
- Sensitive files (`.env` , `application.yml` , logs, tmp) are untracked — verified with `git check-ignore` .
- All demo data is synthetic; screenshots and evidence contain no real candidate data.
- Commit messages: English, no candidate data, no AI attribution.

This audit verifies that *no PII leaked in the artifacts this work created* — it is not a compliance claim; the compliance gaps are listed as constraint signals (§3) and in §10.


CSP verification (the P0's root cause)

Production CSP allows `connect-src 'self'` plus the API origin. The speed test now uses the same origin as every other REST call, so it is covered by design; the third-party endpoints that violated the policy were removed rather than added to the allow-list. Verified against the deployment config before pushing.


8 · Screenshots

All screenshots come from a local run with synthetic demo data. They are embedded here and stored in `assessment/screenshots/`.

Candidate flow




Pre-flight passes with real measurements from the API origin (download, upload, ping) against the documented threshold. Start Interview stays disabled until every check passes.




Live interview in progress: audio stream active, transcript building, timer running — the flow that the P0 had made impossible in production.


Error states




Server unreachable is distinct from slow: the failed probe says so explicitly, with Retry — instead of the old fabricated pass or a generic failure.



Connection lost mid-interview: reconnect screen, microphone muted, no “has been recorded” claim while the session is still open.




Invalid link is an explicit, actionable state — not the old “Interview Complete” screen.




Invite creation failure keeps the dialog open with the error visible; previously the dialog closed silently and the link never appeared.


Assessor flow & edge cases




Fit/gap with a manual assessor override: required levels now render (L3/L4), the overridden candidate level carries the ✏ marker, and the Exceeds badge is computed from real numbers.



Full fit/gap report — required vs candidate level per skill, not-assessed rows preserved as "—", and long generated text wrapping safely.




Skill picker now stores taxonomy ids (SK-ENG-xxx) with the selected skills — the identity that survives the whole pipeline.




Skill card shows the canonical taxonomy id after the backfill; custom skills deliberately stay NULL.


Responsive (390 px)



Before: header rows could not wrap; measured scrollWidth up to 527 px at a 390 px viewport.



After: headers wrap; scrollWidth 375–390 px on every assessor page.



Candidate interview at 390 px — clean layout, no horizontal scroll.

9 · Claimed engineering depth

Claim: frontend-heavy, with real backend depth. The working surface was dominated by the candidate experience and the presentation contract — but every frontend guarantee is backed by a backend decision that is tested, not decorative. I can defend each of the following live, with the specific code paths and tests.

Frontend-heavy — what that means concretely

- A six-state interview page (loading / invalid / unavailable / unreachable / ready / ended / connection-lost) with one shared notice layout instead of six duplicated screens.
- A pre-flight client rewritten around the real API origin: fail-closed semantics, an explicit *unreachable* signal that is distinct from slow, measured values shown next to the threshold, and per-check retry.
- Result presentation the UI can trust: required column, override marker, consistent L1–L5 formatting, error surfacing instead of blank pages, and types aligned with the real payloads (the `as any` casts removed).
- Failure UX on the assessor side: the invite dialog keeps its error visible instead of closing silently.
- Responsive fix verified by measurement (scrollWidth at 390 px), plus 29 unit/component tests covering the states and the speed-test logic.

Backend depth — what backs it

- Tenant scoping with fail-closed 404 on five routes, guarded by 11 two-tenant request specs — the seeded fault proves those specs fail when the fix is removed.
- An additive engine contract change (`expected_level` , `is_override` on every comparison) that keeps old reports rendering — verified by spec, not assumption.
- A canonicalization service resolving model-authored ids against the taxonomy, with four specs covering the id / label / null paths.
- A reversible backfill migration whose rollback limits are documented in the file itself.
- Payload validation that rejects malformed model output before any write — no half-written portfolios.
- Failure paths covered by specs, not prose: a timing-out model call fails the portfolio cleanly, a failing narrative call persists the rule-based fallback, duplicate jobs regenerate idempotently, and stale jobs for deleted records are skipped.
- The harness that makes all of the above provable: RSpec + FactoryBot, Vitest, RuboCop, and a CI workflow — added where the repository had none.

10 · Limitations & follow-ups

Deferred findings

Finding	Follow-up needed
F-10	Add language editing to the assessment edit page (backend already accepts it).
F-11	Decide and implement the erasure architecture (soft vs hard delete; employer orchestration) — prerequisite for PDP subject requests.
F-13	Remove dead code and dead enum values; decide the fate of the unrouted signup page.
F-14	Drop the duplicate index.
F-16	Align the speaker contract on one vocabulary end-to-end.
F-19	Make tenant resolution deterministic (explicit header/selection, no hardcoded fallback).
F-21	Update default model names and deployment config in the repository (config/infra change; local workaround verified).
F-06, F-12, F-15 (remainder)	Error states for the remaining pages; "1 skills" pluralization; the rest of the setup-doc drift (`web/README.md`).

Local environment limits (honestly stated)

- The Gemini Live interview cannot run end-to-end on this Windows dev machine: a native extension without OpenSSL support crashes the server on the first WebSocket to the live model (production Linux is unaffected). The failure path was still exercised — the crash itself reproduces the connection-lost scenario that F-20 fixed — and the fix is unit-tested at the WebSocket-hook level; a full happy-path live interview remains unverified locally.
- The candidate WebSocket flow was verified through fault injection and state tests rather than a complete recorded conversation.

Compliance scope (UU PDP)

Not implemented, by scope decision: consent capture at the invitation link, the subject-request workflow (access/erasure, ≤ 72 h), ROPA, DPIA, a written retention policy, and a human-review UI for automated decisions. These are escalated as constraint signals with a roadmap (§3) rather than half-built. What this work does verify: no PII in logs, commits, or artifacts; reversible data changes; synthetic demo data.

New-endpoint and concurrency notes

- The speed-test download endpoint (new) should get rate limiting before production traffic.
- Portfolio regeneration is idempotent (destroy-and-rebuild, last-write-wins) but has no distributed lock — acceptable for the current single-worker queue; noted for scale.

11 · Links & artifacts

Artifact	Where
Pull request	github.com/rakamindev/ai-interview-platform/pull/182
Video walkthrough (3–5 min)	**[video link — added before portal submission]**
Main work	`feat/platform-revamp` — 31 commits, from the harness through the failure-path specs.
Seeded-fault evidence	`scratch/seeded-fault-idor` — break (`f41c7f4`) → revert (`862535d`), history left visible on purpose.
Report source	`assessment/report.html` (print source for this PDF).
Screenshots	`assessment/screenshots/` — the curated set embedded in §8.

Prepared 16 October 2026, finalized 23 October 2026 · M. Fauzan Ahnaf Athallah · All screenshots and evidence captured from a local run with synthetic demo data; no real candidate data is included anywhere in this repository.