
TCP/IP网络编程(十六)

笔记本: 网络编程

创建时间: 2018/11/16 9:56 **更新时间:** 2018/11/19 21:13

作者: xiangkang94@outlook.com **标签:** 第十六章(I/O流分离的相关内容)


- IO流分离方式(两种)
 - 第十章TCP IO routine分离,通过fork文件描述符区分输入输出,虽然文件描述符不会根据输入、输出进行区分,但是分开了两个文件描述符的用途(父进程负责读,子进程负责写)
 - 。 第十五章 调用fdopen创建FILE指针,分离输入工具和输出工具。
- 分离流的好处
 - 。 //通过fork文件描述符区分输入输出
 - 。 通过分开输入过程和输出过程降低实现难度
 - 与输入无关的输出操作可以提高速度
 - o //调用fdopen创建FILE指针
 - o 将FILE指针按读模式、写模式加以区分
 - 可以通过区分读写模式降低难度
 - o 通过区分IO缓冲提高缓冲性能
 - 。 将文件描述符转成文件指针后,可以使用标准IO函数
- 流分离带来的EOF问题
 - 。 在流分离的情况下半关闭连接需要额外处理
 - o 读模式FILE指针、写模式FILE指针都是基于同一个文件描述符创建的,fclose关闭任意一个,都将关闭文件描述



符, 套接字终止

图16-2 调用fclose函数的结果

o 解决如上问题,只需在创建FILE指针前复制文件描述符



- o 但是上图中虽然关闭了其中一个文件文件描述符,但是仍然没有进入半关闭状态,<mark>因为剩下的这个文件描述符,</mark> 仍然可以同时进行I/O
- 复制文件描述符的方法dup/dup2

#include <unistd.h>
int dup(int fildes)
int dup2(int fildes, int fildes2)

```
//成功时返回复制的文件描述符,失败返回-1
//fildes: 需要复制的文件描述符
//filders2: 明确指定的文件描述符整数值
```

• 无论复制出多少文件描述符,均应该通过shutdown函数发送EOF并进入半关闭状态

```
server.c:
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <arpa/inet.h>
#include <sys/socket.h>
#define BUF_SIZE 1024
int main(int argc, char * argv[]){
    int serv_sock,clnt_sock;
    FILE *readfp;
   FILE *writefp;
    struct sockaddr_in serv_adr,clnt_adr;
    socklen_t clnt_adr_sz;
   char buf[BUF_SIZE];
    serv_sock = socket(PF_INET,SOCK_STREAM,0);
   memset(&serv adr,0,sizeof(serv adr));
    serv adr.sin family = AF INET;
    serv_adr.sin_addr.s_addr = htonl(INADDR_ANY);
   serv_adr.sin_port = htons(atoi(argv[1]));
   bind(serv_sock,(struct sockaddr *)&serv_adr,sizeof(serv_adr));
   listen(serv sock,5);
    clnt adr sz = sizeof(clnt adr);
    clnt_sock = accept(serv_sock,(struct sockaddr *)&clnt_adr,&clnt_adr_sz);
   readfp = fdopen(clnt sock, "r");
   writefp = fdopen(dup(clnt_sock),"w");
    fputs("from server: Hi~ client? \n",writefp);
    fputs("I love all the world! \n", writefp);
   fflush(writefp);
    shutdown(fileno(writefp),SHUT_WR);
                                       //keypoint,无论复制了多少文件描述符,只要调用了shutdown均会进入半状态
    fclose(writefp);
    fgets(buf, sizeof(buf), readfp);
    fputs(buf,stdout);
    fclose(readfp);
    return 0;
}
```