



CS1002 – Programming Fundamentals

Lecture # 05
Monday, September 06, 2022
FALL 2022
FAST – NUCES, Faisalabad Campus

Muhammad Yousaf

Pseudocode – Comparing two numbers

```
1.0 start
2.0 declare n1, n2
3.0 input n1,n2
4.0 if (n1 > n2)
    4.1 print "n1 is greater"
5.0 endif
6.0 if (n2 < n1)
    6.1 print "n2 is greater"
7.0 endif
8.0 if (n1 = n2)
    8.1 print "they are equal"
9.0 endif
10.0 end
```

Nested if/else Selection Structure

- Nested if/else structures
 - One inside another, test for multiple cases
 - Once condition met, other statements skipped

Example 1– Comparing two numbers with nested if-else

1.0 start

2.0 declare n1, n2

3.0 input n1,n2

4.0 if (n1 > n2)

 4.1 print "n1 is greater"

5.0 else

 5.1 if (n2 < n1)

 5.1.1 print "n2 is greater"

 5.2 else

 5.2.1 print "they are equal"

 5.3 endif

6.0 endif

7.0 end

CS1002 - FALL 2022

Example 2: Grading with Nested if-else:

```
if student's grade is greater than or equal to 90
    Print "A"
else
    if student's grade is greater than or equal to 80
        Print "B"
    else
        if student's grade is greater than or equal to 70
            Print "C"
        else
            if student's grade is greater than or equal to 60
                Print "D"
            else
                Print "F"
```

Example 2: Pseudocode for Grading with Nested if-else:

```
if ( grade >= 90 ) then           // 90 and above
    Print "A"
else if ( grade >= 80 ) then      // 80-89
    Print "B"
else if ( grade >= 70 ) then      // 70-79
    Print "<< "C";
else if ( grade >= 60 ) then      // 60-69
    Print "D";
else                             // less than 60
    Print "F";
end
```

if/else Selection Structure

Compound statement

- Set of statements within a pair of braces

```
if grade >= 60 then
    Print "Passed"
else
    Print "Failed"
    Print "You must take this course again"
endif
```

Example 3

- Write pseudocode and draw a flowchart that will calculate the roots of a quadratic equation
- $ax^2 + bx + c = 0$
- Hint $d = b^2 - 4ac$ and roots are
 - $X_1 = (-b + \text{sqrt}(d)) / 2a$
 - $X_2 = (-b - \text{sqrt}(d)) / 2a$
- Real roots are only possible if $d > 0$
- **Cater this as well**

Example 4

- Write a pseudocode and draw a flowchart
 - to read an employee name (NAME), overtime hours worked (OVERTIME), hours absent (ABSENT)
 - determine the bonus payment (PAYMENT)

Bonus Schedule	
OVERTIME – $(2/3)*ABSENT$	Bonus Paid
>40 hours	5000
>30 but \leq 40 hours	4000
>20 but \leq 30 hours	3000
>10 but \leq 20 hours	2000
\leq 10 hours	1000

Questions

