UI BASICS

INTERACTION – TRANSFORM

CSS - TRANSFORM

CSS **transform** allows you to move, rotate, scale, and skew elements.

With the CSS **transform** property you can use the following transformation methods:

- translate()
- rotate()
- scale()
- skew()
- matrix()

translate()

- The **translate()** method moves an element from its current position (according to the parameters given for the X-axis and the Y-axis).
- It moves an element sideways or up and down.

transform: translateX(x value);

transform: translateY(y value);

transform: translate(x value, y value);



CSS - TRANSFORM

translate()

```css
.translate {
    height: 100px;
    width: 100px;
    background-color: #3d9970;
}
```

```html
<p>Lorem ipsum dolor sit amet, consectetur adipisicing elit. Accusamus porro officia, quae, explicabo deleniti quasi molestias dolorum non ad pariatur. Illo, inventore at. Odio iure adipisci quisquam, molestias impedit quo.</p>

<div class="translate"></div>

<p>Lorem ipsum dolor sit amet, consectetur adipisicing elit. Harum sit aperiam odit libero soluta delectus voluptatibus saepe laboriosam maiores, quas, fuga vitae. Suscipit eum assumenda hic sunt, debitis voluptatum odit.</p>
```

Lorem ipsum dolor sit amet, consectetur adipisicing elit. Accusamus porro officia, quae, explicabo deleniti quasi molestias dolorum non ad pariatur. Illo, inventore at. Odio iure adipisci quisquam, molestias impedit quo.

Lorem ipsum dolor sit amet, consectetur adipisicing elit. Harum sit aperiam odit libero soluta delectus voluptatibus saepe laboriosam maiores, quas, fuga vitae. Suscipit eum assumenda hic sunt, debitis voluptatum odit.

```css
.translate {
    height: 100px;
    width: 100px;
    background-color: #3d9970;

    transform: translate(200px, 350px);
}
```

Lorem ipsum dolor sit amet, consectetur adipisicing elit. Accusamus porro officia, quae, explicabo deleniti quasi molestias dolorum non ad pariatur. Illo, inventore at. Odio iure adipisci quisquam, molestias impedit quo.



CSS - TRANSFORM

translate()




```
transform: translate(-50px, -50px);
```




```
transform: translate(30px, -50px);
```



rotate()

The **rotate()** method rotates an element clockwise or counter-clockwise according to a given degree.

transform: rotateX(deg);

transform: rotateY(deg);

transform: rotateZ(deg);

transform: rotate(deg); → Rotates the element clockwise from its current position.



CSS - TRANSFORM

rotate()

```css
div {
    height: 100px;
    width: 100px;
    margin: 20px;
}
.rotate-x {
    background: #3d9970;
}
.rotate-y {
    background: #4089e1;
}
.rotate-z {
    background: #a957e4;
}
```

```html
<p>Lorem ipsum dolor sit amet, consectetur adipisicing elit. </p>

<div class="rotate-x"></div>
<div class="rotate-y"></div>
<div class="rotate-z"></div>

<p>Lorem ipsum dolor sit amet, consectetur adipisicing elit.</p>
```

Lorem ipsum dolor sit amet, consectetur adipisicing elit.

Lorem ipsum dolor sit amet, consectetur adipisicing elit.

```css
.rotate-x {
    background: #3d9970;
    transform: rotateX(70deg);
}
.rotate-y {
    background: #4089e1;
    transform: rotateY(70deg);
}
.rotate-z {
    background: #a957e4;
    transform: rotateZ(70deg);
}
```

Lorem ipsum dolor sit amet, consectetur adipisicing elit.



Lorem ipsum dolor sit amet, consectetur adipisicing elit.



scale()

The **scale()** method increases or decreases the size of an element (according to the parameters given for the **width** and **height**).

transform: scaleX(width);

transform: scaleY(height);

transform: scale(width, height);

value > 1 : increment

0 < value < 1 : decrement

CSS - TRANSFORM

scale()

```css
div {
    height: 100px;
    width: 100px;
    margin: 20px 100px;
    background: #f9c004;
    padding: 10px;
}
.scale-x {
    background: #3d9970;
    transform: scaleX(2);
}
.scale-y {
    background: #4089e1;
    transform: scaleY(0.5);
}
.scale {
    background: #a957e4;
    transform: scale(2, 0.5);
}
```

```html
<p>Lorem ipsum dolor sit amet, consectetur
adipisicing elit. </p>

<div>Div</div>
<div class="scale-x">ScaleX</div>
<div class="scale-y">ScaleY</div>
<div class="scale">Scale</div>

<p>Lorem ipsum dolor sit amet, consectetur
adipisicing elit.</p>
```



NOTE : This also applies to the font-size, padding, height, and width of an element, too.

skew()

The **skew()** method skews an element along the X and Y-axis by the given angles.

transform: skewX(deg);

transform: skewY(deg);

transform: skew(x-deg, y-deg);

transform: skew(value-deg); → If the second parameter is not specified, it has a **zero value**. So, it will skew value-degree along the X-axis:

CSS - TRANSFORM

skew()

```css
div {
    height: 100px;
    width: 100px;
    margin: 20px 100px;
    background: #f9c004;
    padding: 10px;
}
.skew-x {
    background: #3d9970;
    transform: skewX(20deg);
}
.skew-y {
    background: #4089e1;
    transform: skewY(20deg);
}
.skew {
    background: #a957e4;
    transform: skew(20deg, 20deg);
}
```

```html
<p>Lorem ipsum dolor sit amet, consectetur
adipisicing elit. </p>

<div>Div</div>
<div class="skew-x">SkewX</div>
<div class="skew-y">SkewY</div>
<div class="skew">Skew</div>

<p>Lorem ipsum dolor sit amet, consectetur
adipisicing elit.</p>
```



matrix()

- The **matrix()** method combines all the 2D transform methods into one.

matrix (scaleX(), skewY(), skewX(), scaleY(), translateX(), translateY());

```css
div {
    height: 100px;
    width: 100px;
    margin: 20px 100px;
    background: #f9c004;
    padding: 10px;
}
.matrix1 {
    background: #3d9970;
    transform: matrix(1, -0.3, 0, 1, 0, 0);
}
.matrix2 {
    background: #4089e1;
    transform: matrix(1, 0, 0.5, 1, 150, 0);
}
```

```html
<p>Lorem ipsum dolor sit amet, consectetur adipisicing elit. </p>

<div>Div</div>
<div class="matrix1">Matrix-1</div>
<div class="matrix2">Matrix-2</div>

<p>Lorem ipsum dolor sit amet, consectetur adipisicing elit.</p>
```



to convert a group of transforms into a single matrix declaration.

https://meyerweb.com/eric/tools/matrix/

CSS – TRANSFORM-ORIGIN

- The **transform-origin** property is used in conjunction with CSS transforms, letting you change the point of origin of a transform.

- Values can be lengths, percentages or the keywords top, left, right, bottom, and center.

```css
.div1 {
    height: 100px;
    width: 100px;
    margin: 100px;
    border: 1px solid black;
    position: relative;
}
.div2 {
    position: absolute;
    height: 30px;
    width: 100px;
    background-color: red;
    transform: rotate(45deg);
    transform-origin: top left;

}
```

```html
<p>Lorem ipsum dolor sit amet, consectetur
adipisicing elit. </p>

<div class="div1">
    <div class="div2">HI</div>
</div>

<p>Lorem ipsum dolor sit amet, consectetur
adipisicing elit.</p>
```



NOTE : This property must be used together with the transform property.