Classification of Network Traffic Attack Categories: A Tuned Random Forest Compared with k-Nearest Neighbours and Classification Trees

S.L. Johnson
27356485
Department of Computer Science
Stellenbosch University
27356485@sun.ac.za
https://github.com/FearlessSnail/ML-assignment4

***Abstract*—This study investigated ensemble learning for the classification of network traffic into attack categories. A random forest was selected because the method combines classification trees of the type used in a previous assignment. The forest was tuned through a staged grid search, and further analyses examined the reasons behind the observed performance. All models were evaluated under five-fold stratified cross-validation on the folds of the previous assignment. The forest tuned for macro-averaged F1 outperformed both previous models on that measure. A bias–variance decomposition revealed that the previous classification tree was heavily pruned, and removal of the pruning alone accounted for most of the gain in macro-averaged F1. Ensembling reduced variance as theory predicts but improved accuracy rather than macro-averaged F1. A forest tuned for the Matthews correlation coefficient matched the macro-averaged F1 of the first forest at a far higher accuracy.**

I. Introduction

Network intrusion detection systems classify traffic records in order to identify malicious activity, and classification models support that task by assigning each record to an attack category. Moustafa and Slay constructed the UNSW-NB15 dataset from a mixture of real normal traffic and synthetic attack traffic [1].

A previous assignment compared the k-nearest neighbours (kNN) model with the classification tree on a revised version of the dataset. The present report refers to that work as assignment 2. The classification tree achieved the higher score under a performance measure that weights every attack category equally.

The present study explores ensemble learning as a means of predicting cyberattacks. An ensemble combines the predictions of several models into a single prediction [2], and the random forest is an ensemble of classification trees [3]. The random forest was chosen deliberately because the forest uses the same type of tree and the same data preparation as the classification tree of assignment 2. A comparison between the forest and a single tree of the same configuration therefore isolates the ensemble mechanism. A dissimilar ensemble method would change several factors at once and obscure the source of any difference.

The purpose of the study was to determine whether a random forest outperforms the models of assignment 2. Further analyses examined the source of any improvement, the behaviour of the forest under tuning and the effect of class weighting.

The forest tuned for the primary measure outperformed both models of assignment 2. A decomposition of the error into bias and variance then revealed that the classification tree of assignment 2 was heavily pruned, so most of the improvement over that tree arose from the absence of pruning in the forest. The ensemble itself improved overall accuracy rather than the primary measure.

The remainder of the report is structured as follows. Section II provides background on the models, on ensemble learning and on the dataset. Section III describes the data preparation, the models and the implementation. Section IV details the empirical procedure. Section V presents and discusses the results, and Section VI concludes the study.

II. Background

This section provides the theoretical foundation for the study. The general setting of supervised classification is introduced first, followed by the performance measures and the decomposition of error into bias and variance. The two models of assignment 2 are then described, followed by ensemble learning and the random forest. The section closes with the treatment of class imbalance and the data quality issues of the dataset.

A. Supervised Classification

An instance is one object to be classified. In the present study an instance is one network flow, namely one connection between two hosts. Each instance is described by a vector $\mathbf{x}$ of d descriptive features and carries a class label y drawn from a set C of q classes. A training set D is a collection of n labelled instances.

A classifier is a function $\hat{f}_D$ that maps a feature vector to a class label, where the subscript indicates the training set used to construct the classifier. The algorithm that constructs

a classifier from a training set is called a learning algorithm or learner. The quality of a single prediction is measured by the zero-one loss, defined as

$$\ell\big(y, \hat{f}_D(\mathbf{x})\big) = \begin{cases} 0 & \text{if } \hat{f}_D(\mathbf{x}) = y, \\ 1 & \text{otherwise.} \end{cases} \tag{1}$$

The generalisation error of a classifier is the expected loss on instances not seen during training [4]. The training error is optimistic because the classifier was fitted to the training instances. Performance is therefore estimated on held-out instances throughout the study.

Hyperparameters are settings fixed before learning and are also called control parameters. A hyperparameter shapes the class of rules that the learner is able to represent, and tuning selects hyperparameter values through estimates of the generalisation error.

B. Performance Measures

Let θ_c denote the number of true positives of class c, namely the instances of class c predicted as class c. Let ξ_c denote the number of false positives, namely the instances of other classes predicted as class c. Let ζ_c denote the number of false negatives, namely the instances of class c predicted as another class. The precision and the recall of class c are given by

$$\pi_c = \frac{\theta_c}{\theta_c + \xi_c}, \qquad \gamma_c = \frac{\theta_c}{\theta_c + \zeta_c}. \tag{2}$$

Precision is the proportion of predictions of class c that are correct, while recall is the proportion of class c that is detected. The F1 of class c is the harmonic mean of the two, given by

$$\eta_c = \frac{2\,\pi_c\,\gamma_c}{\pi_c + \gamma_c}, \tag{3}$$

so that η_c is low when either component is low.

Macro-averaged F1 is the unweighted mean of η_c over the q classes and is denoted $\bar{\eta}$. Every class therefore counts equally regardless of size. Macro-averaged F1 was the primary measure in assignment 2 and remained the primary measure in the present study. Macro-averaged precision and balanced accuracy are the unweighted means of π_c and γ_c over the classes. Accuracy is the proportion of all instances predicted correctly, namely $\sum_c \theta_c / n$. Accuracy therefore counts every instance equally and is dominated by the large classes.

The Matthews correlation coefficient (MCC) measures the correlation between predicted and true labels, and Gorodkin defined the multi-class form used in the present study [5]. With $\hat{n}_c$ the number of instances predicted as class c, the multi-class MCC is given by

$$\varphi = \frac{n \sum_c \theta_c - \sum_c \hat{n}_c\, n_c}{\sqrt{\big(n^2 - \sum_c \hat{n}_c^2\big)\big(n^2 - \sum_c n_c^2\big)}}, \tag{4}$$

where a value of one indicates perfect prediction and a value of zero indicates no better than chance. Like accuracy, the MCC counts every instance equally and therefore represents the opposite value judgement to macro-averaged F1.

C. Bias and Variance

The training set is a random sample, so a different sample produces a different classifier with different predictions at the same feature vector $\mathbf{x}$. Domingos decomposed the expected zero-one loss at $\mathbf{x}$ into terms that describe this behaviour [6].

Let y_* denote the optimal prediction at $\mathbf{x}$, namely the most probable class. Let $\bar{y}$ denote the main prediction, namely the class predicted most often across training sets. The bias at $\mathbf{x}$ is given by

$$\beta(\mathbf{x}) = \ell(y_*, \bar{y}), \tag{5}$$

so the bias equals one when the main prediction is wrong. The variance at $\mathbf{x}$ is given by

$$\nu(\mathbf{x}) = \mathbb{E}_D\big[\ell\big(\bar{y}, \hat{f}_D(\mathbf{x})\big)\big], \tag{6}$$

where $\mathbb{E}_D$ denotes the expectation over training sets. The variance is therefore the probability that a single classifier disagrees with the main prediction.

The noise is the expected loss of the optimal prediction and is unavoidable for every classifier. Domingos showed that the expected loss equals a weighted noise term plus the bias plus $\kappa\,\nu(\mathbf{x})$ [6]. The coefficient κ equals one when the main prediction is correct and is negative when the main prediction is wrong. Variance therefore adds to the loss on instances predicted correctly on average. On instances predicted incorrectly on average, variance reduces the loss because a classifier that disagrees with a wrong main prediction is sometimes correct.

Capacity is the ability of a model to represent complex rules. A model with high capacity tends towards low bias and high variance, while a model with low capacity tends towards high bias and low variance [4].

D. k-Nearest Neighbours

The kNN rule assigns a query instance to the class most heavily represented among the k training instances closest to the query [7]. The training set therefore constitutes the model, and all computation is deferred to prediction time.

Closeness is measured by a distance function. With $\mathbf{z}$ a second feature vector, the Minkowski distance of order λ between $\mathbf{x}$ and $\mathbf{z}$ is given by

$$\delta_\lambda(\mathbf{x}, \mathbf{z}) = \Big(\sum_{j=1}^{d} |x_j - z_j|^\lambda\Big)^{1/\lambda}, \tag{7}$$

where x_j and z_j denote the j-th components of $\mathbf{x}$ and $\mathbf{z}$. The order $\lambda = 2$ yields the Euclidean distance, while $\lambda = 1$ yields the Manhattan distance that grows more slowly with a large difference in a single component. Under distance weighting, each neighbour casts a vote weighted by the inverse of the distance to the query.

A decision boundary separates the regions of the feature space assigned to different classes. The neighbourhood size k controls the capacity of the model [4]. A small value of k produces a boundary that follows individual instances, while a large value produces a smooth boundary. Two further properties follow from the reliance on distance. A feature with

a large numeric range dominates the distance, and redundant features contribute one underlying quantity more than once.

E. Classification Trees

A classification tree predicts through a sequence of yes-or-no questions. Each question tests whether one feature lies below a threshold and sends the instance to one of two branches. A point in the tree where a question is asked is called a node, and the questions continue until the instance reaches a leaf that carries a class prediction.

Hastie *et al.* described the construction of such trees through recursive binary splitting [4]. At each node the algorithm selects the feature and threshold that most reduce impurity, a measure of how mixed the classes in a node are. With p_c the proportion of class c among the training instances in a node, the Gini impurity of the node is given by

$$g = 1 - \sum_{c \in C} p_c^2 \tag{8}$$

as given by Hastie *et al.* [4]. The entropy of the node is given by

$$h = -\sum_{c \in C} p_c \log_2 p_c \tag{9}$$

as used by Quinlan [8]. Both measures equal zero for a node that contains a single class and are largest when the classes are evenly mixed. Growth stops when a node is pure or when a split would leave fewer instances in a leaf than the minimum leaf size ω.

A tree grown until every leaf is pure reproduces the training sample exactly, including noise. Cost-complexity pruning removes a branch when the improvement from the branch does not justify the size of the branch [4]. With r the training misclassification cost of a tree and l the number of leaves, the pruned tree minimises

$$r_\alpha = r + \alpha\, l, \tag{10}$$

where $\alpha \geq 0$ is the complexity parameter. Each leaf must justify the cost α, so a larger value of α yields a smaller tree with fewer leaves and a lower capacity.

A threshold test is invariant under any strictly increasing transformation of the feature tested, because the transformation preserves the order of the values. A tree is therefore unaffected by the numeric range of a feature. Breiman identified classification trees as unstable, meaning that a small change in the training data produces a large change in the tree [9]. A change in an early split alters every node below the split, so a fully grown tree has low bias and high variance.

F. Ensemble Learning and Random Forests

An ensemble combines the predictions of several models, and Dietterich identified three reasons why an ensemble often outperforms the individual members [2]. The statistical reason is that averaging hedges against an unlucky choice among equally good models. The computational reason concerns greedy learners. A greedy learner makes the best choice at each step without look-ahead and is therefore liable to stop at a local optimum, namely a solution that no small change improves. A tree is a greedy learner because the tree selects each split in turn, and different runs of a greedy learner reach different local optima. The representational reason is that a combination represents decision boundaries beyond the reach of any single member.

Averaging reduces variance. Let m denote the number of models, and let $\hat{f}_b(\mathbf{x})$ denote the prediction of model b. If each prediction has variance σ^2 and each pair of predictions has correlation ρ, the variance of the average prediction is given by

$$\operatorname{Var}\left(\frac{1}{m}\sum_{b=1}^{m} \hat{f}_b(\mathbf{x})\right) = \rho\,\sigma^2 + \frac{1-\rho}{m}\,\sigma^2, \tag{11}$$

where Var denotes the variance over training sets [4]. The second term vanishes as m grows, so additional models never increase the variance. The first term remains as a floor on the variance, and only a reduction in the correlation ρ lowers that floor.

The name bagging is short for bootstrap aggregating, a method that creates variety through bootstrap samples [9]. A bootstrap sample draws n instances with replacement from the n available. A given instance is missed by all n draws with probability $(1 - 1/n)^n$, a value that tends to $e^{-1} \approx 0.368$ as n grows. Here e denotes the base of the natural logarithm, so each bootstrap sample contains about 63.2 percent of the distinct instances. Bagging trains one model on each bootstrap sample and averages the predictions.

The base learner of an ensemble is the type of model that the ensemble combines. A random forest uses classification trees as base learners and adds a second source of variety [3]. Each tree considers only a random subset of a features at every split, and the trees are grown without pruning. Without the random subsets, every tree would select the same dominant features near the root and the trees would be highly correlated. The setting $a = d$ reduces the random forest to bagging. The implementation used in the present study combines the trees through soft voting.[1] Soft voting averages the class proportions in the leaves reached by the trees and predicts the class with the largest average.

Breiman quantified the trade-off in the choice of a [3]. The margin $\mu(\mathbf{x}, y)$ is the proportion of trees that vote for the true class minus the largest proportion that vote for any other class. The raw margin of a single tree is one for a vote for the true class, minus one for a vote for the strongest other class and zero otherwise. The strength s is the expected margin, and the mean correlation $\bar{\rho}$ is the mean correlation between the raw margins of pairs of trees. Breiman showed that the generalisation error ψ of the forest is bounded by

$$\psi \leq \bar{\rho}\,\frac{1 - s^2}{s^2}. \tag{12}$$

Breiman observed that the correlation rises steadily as a grows, while the strength stops rising beyond a small value of a [3]. The best value of a therefore balances the two effects.

[1] https://scikit-learn.org/stable/modules/ensemble.html

TABLE I
CLASS DISTRIBUTION, CONFLICT RATE AND IDEALISED CEILING

Class	Instances	Conflicting	Ceiling F1
Normal	93 000	0.010	0.996
Generic	58 871	0.006	0.997
Exploits	44 525	0.371	0.813
Fuzzers	24 246	0.149	0.924
Denial of service	16 353	0.774	0.549
Reconnaissance	13 987	0.161	0.914
Analysis	2 677	0.770	0.375
Backdoor	2 329	0.849	0.265
Shellcode	1 511	0.009	0.997
Worms	174	0.086	0.955

Boosting is the main alternative family of ensembles. Freund and Schapire showed that boosting builds a strong classifier from a sequence of weak classifiers [10], where a weak classifier performs only slightly better than chance. Each classifier in the sequence concentrates on the instances misclassified by the earlier classifiers. Boosting therefore targets weak classifiers with high bias, whereas the random forest targets strong classifiers with high variance such as fully grown trees [4].

G. Class Imbalance

A class distribution is imbalanced when the classes differ greatly in size. He and Garcia reported that a learner that minimises the overall error rate tends to neglect the small classes [11]. One remedy is cost-sensitive learning, an approach that assigns a higher cost to errors on the small classes.

Class weighting is a form of cost-sensitive learning. With n_c the number of instances of class c, the balanced weighting of the implementation used in the present study assigns class c the weight

$$w_c = \frac{n}{q\, n_c} \tag{13}$$

so that every class carries the same total weight.[2] In a tree, each instance counts with the weight of the class of the instance in both the impurity and the prediction of each leaf.

H. Data Quality Issues

The revised dataset contains 257 673 instances, 42 descriptive features and 10 classes. Of the 42 features, 39 are numeric and three are nominal. A nominal feature takes category names as values. The three nominal features are the transaction protocol, the service and the connection state. The dataset has five data quality issues relevant to the present study.

First, the class distribution is imbalanced. The Normal class holds 93 000 instances against 174 for the Worms class, a ratio of 534 to 1. Table I reports the full distribution.

Second, the numeric ranges differ by many orders of magnitude. The source load feature reaches 5.99×10^9 while the transaction depth feature reaches only 172. Third, 12 pairs of numeric features have a Pearson correlation of at least 0.95 in absolute value. Pearson correlation measures the strength of the linear relationship between two features on a scale from -1 to 1. Fourth, the service feature is missing for 141 321 instances.

Fifth, many instances are exact duplicates. The 257 673 instances contain only 153 684 distinct feature vectors, and 46.5 percent of instances share a feature vector with another instance. More seriously, 40 400 instances share a feature vector with an instance of a different class. The column "Conflicting" of Table I gives the proportion of each class affected, a proportion that reaches 0.849 for Backdoor and 0.774 for denial of service (DoS).

Instances with identical features and different labels set a floor on the error of every classifier. A classifier assigns one label to all instances with the same feature vector, so at least one of the conflicting instances is misclassified. Label noise refers to incorrect class labels. Frénay and Verleysen identified insufficient information in the description of an instance as one source of label noise [12]. The conflicting instances fit that source, because the 42 features fail to distinguish the classes involved.

The size of the floor was estimated through an idealised ceiling classifier that memorises every instance. For each group of identical feature vectors, the ceiling classifier predicts the most frequent label of the group. The ceiling classifier achieved an accuracy of 0.914, and the column "Ceiling F1" of Table I reports the per-class F1. The ceiling is optimistic because the ceiling classifier is evaluated on the instances memorised.

In summary, the trees and the forest require only a numeric encoding of the nominal features. The kNN model additionally requires scaling and the removal of redundant features. No model is able to separate the conflicting instances. The DoS, Analysis and Backdoor classes therefore have low ceilings for every model.

III. METHODOLOGY

This section describes the treatment of the dataset and the construction of the models. The data preparation common to all models is described first, followed by the pre-processing specific to each family of models. The section closes with the model configurations and the implementation.

A. Data Preparation

The dataset was read with the character "?" treated as a missing value marker. The identifier feature was removed for every model. A unique identifier allows a tree to isolate single instances and adds an uninformative dimension to every distance.

Missing values in the service feature were recorded as a separate category named "none". The feature description supplied with the dataset records a service only when the service is commonly used, so a missing service indicates an uncommon service. The absence is itself informative, and imputation would destroy that information.

[2] https://scikit-learn.org/stable/modules/generated/sklearn.utils.class_weight.compute_class_weight.html

The login feature for the file transfer protocol is documented as binary. The feature nonetheless held the value 2 for 10 instances and the value 4 for 16 instances, and the irregular values were clipped to the interval $[0, 1]$. No numeric value was missing and no feature was constant. Duplicate instances were retained so that every model used the same instances as assignment 2.

B. Pre-processing for k-Nearest Neighbours

The kNN pipeline of assignment 2 was retained unchanged. A pipeline is a sequence of transformations followed by a model and is fitted as one unit. Four transformations addressed the issues identified in Section II.

The 12 correlated pairs form six groups of features that each describe one quantity. One representative of each group was retained, so nine features were removed. The retained byte counts were `sbytes` and `dbytes`, and the retained window feature was `swin`. The retained connection counters were `ct_srv_src` and `ct_dst_ltm`, and the retained login feature was `is_ftp_login`. Every pair of features within a group is correlated at 0.95 or above, so the choice of representative has little effect on the distance.

A logarithmic transformation of the form $\log(1 + x)$ was then applied to every numeric feature. Every numeric value in the dataset is non-negative, so the transformation is defined everywhere. The transformation compresses the large values while preserving the order of the values.

Each numeric feature was then scaled. Standardisation subtracts the mean and divides by the standard deviation, a measure of spread around the mean. Robust scaling subtracts the median and divides by the interquartile range, namely the width of the middle half of the values. Extreme values therefore have little effect on robust scaling. The tuning of assignment 2 selected robust scaling.

The three nominal features were one-hot encoded. One-hot encoding replaces a nominal feature by one binary feature per category, and categories with a relative frequency below 0.01 were merged into a single infrequent category. An integer code would impose an order and a distance between categories that do not exist. Wilson and Martinez proposed heterogeneous distance functions that treat nominal features directly [13]. One-hot encoding was preferred because the resulting space of 48 features admits a single Minkowski distance for all features.

C. Pre-processing for the Tree-Based Models

The classification trees and the random forests received a single transformation. The three nominal features were ordinal encoded because the implementation of the trees requires numeric input. Ordinal encoding replaces each category by an integer and so imposes an arbitrary order on the categories. A tree still isolates any single category through two threshold tests, so the arbitrary order costs at most additional depth. The invariance argument of Section II makes scaling and logarithmic transformation unnecessary.

D. Model Configurations

Six models were compared. The kNN model of assignment 2 used robust scaling and distance weighting with $\lambda = 1$ and $k = 3$. The classification tree of assignment 2 used the Gini impurity without class weighting or depth limit, with $\omega = 1$ and $\alpha = 10^{-4}$.

The untuned forest used the default settings of the implementation, namely 100 trees with the Gini impurity and no class weighting. The untuned forest also used $\omega = 1$ and $a = 6$, the square root of d rounded down.[3] Two tuned forests were constructed through a staged grid search. The first forest was selected by macro-averaged F1 and the second by the MCC.

The sixth model is the classification tree of assignment 2 without pruning, namely with $\alpha = 0$. The unpruned tree was added after the decomposition into bias and variance revealed the extent of the pruning. The unpruned tree is the base learner of the random forest, so a comparison with the unpruned tree separates the effect of ensembling from the effect of pruning.

E. Implementation

All models were implemented in Python.[4] The scikit-learn library provided the models, the transformations and the cross-validation procedure [14]. The library was selected because one library implements all three model families behind a common interface. Every model therefore received identical data splits and identical evaluation code. The pandas library provided the data structures,[5] and the NumPy library provided the numerical routines.[6] The SciPy library provided the statistical tests,[7] and the Matplotlib library provided the figures.[8]

Each model was a single pipeline fitted within each training partition, so no transformation was fitted on data used for evaluation. The predictions of the kNN model were taken from assignment 2 rather than recomputed. Prediction with the kNN model requires about 10^{10} distance computations per fold because every test instance is compared with every training instance. The model is deterministic, so a refit would reproduce the saved predictions. The classification tree of assignment 2 was refitted and reproduced the predictions of assignment 2 on all 257 673 instances. The data and the partitions were therefore identical to those of assignment 2.

In summary, every tree-based model shared one pre-processing step. Differences among the trees and forests therefore arise from the learning mechanism and the configuration alone.

IV. Empirical Procedure

This section describes the procedure followed to obtain the results. The cross-validation protocol is described first, followed by the tuning procedure. The analyses that explain the

[3] https://scikit-learn.org/stable/modules/generated/sklearn.ensemble.RandomForestClassifier.html
[4] https://www.python.org
[5] https://pandas.pydata.org
[6] https://numpy.org
[7] https://scipy.org
[8] https://matplotlib.org

TABLE II
SEARCH SPACE AND SELECTED CONFIGURATIONS OF THE RANDOM FOREST

Parameter	Values	Selected for Macro F1	Selected for MCC
a	1, 6, 10, 21, 42	21	21
Weighting	none, balanced, balanced per tree	balanced	none
ω	1, 2, 5, 10, 25	2	10
Impurity	Gini, entropy	entropy	entropy
m	1 to 500	100	50

results then follow, and the section closes with the statistical analysis.

A. Cross-Validation Protocol

Performance was estimated through v-fold cross-validation [4] with stratified folds. The dataset is partitioned into v folds. Each fold serves once as the test partition while the remaining folds form the training partition. Every instance is therefore predicted once by a model that did not see the instance. Stratification preserves the class distribution in every fold, and without stratification a fold could contain almost no Worms instances.

Five folds were used, as in assignment 2. The folds were generated from the random seed of assignment 2, a number that fixes the sequence of random numbers used to form the folds. Every model was therefore evaluated on identical partitions, so the scores of any two models on the same fold are paired. The evaluation on the five folds is referred to as the outer cross-validation.

B. Tuning Procedure

The forest was tuned through a staged grid search. A grid search evaluates every combination of the candidate values, while a staged search fixes the winner of one small grid before the next grid is searched. The staged search is cheaper but assumes little interaction between stages. Hyperparameters expected to interact were therefore searched in the same stage, and each stage was designed to reveal one aspect of the behaviour of the forest.

Each candidate was evaluated by five-fold cross-validation within the tuning data, referred to as the inner cross-validation. The tuning data was the stratified subsample of 40 000 instances used by assignment 2, so the forest received the same tuning budget as the models of assignment 2. Table II reports the search space and the selected values.

The first stage measured how much decorrelation benefits the forest and whether class weighting helps the small classes. The two hyperparameters were searched together because weighting changes the splits that appear best. The values of a span the full range from one feature to all 42 features, with the default of 6 and the values 10 and 21 filling the gap. The weighting options are the three options of the implementation, and the option "balanced per tree" recomputes the weights on each bootstrap sample.

The second stage crossed ω with the impurity measure to establish whether the trees of a forest should be fully grown. The values of ω run from fully grown trees to clearly restrained trees in roughly doubling steps. Both stages used 200 trees so that the randomness of a small forest did not decide the comparison.

The number of trees was not tuned in the usual sense, because Breiman showed that the error of a random forest converges as trees are added [3]. A forest of 500 trees was therefore grown once per inner fold. A forest of m trees equals the average of the first m trees of the larger forest, so every forest of up to 500 trees was scored from a single fit. The smallest forest within 0.002 of the 500-tree score was selected. The tolerance lies below the fold-to-fold standard deviation of 0.0025 observed for the tree of assignment 2.

The second tuned forest repeated the full procedure on the same subsample and folds, with the MCC as the selection criterion. A comparison of the two tuned forests shows how strongly the selected configuration depends on the measure used for selection.

C. Analysis of Mechanisms

Three further analyses examined the reasons behind the performance of the forest. The decomposition of Domingos tested whether the forest outperforms the tree through a reduction in variance. Each model was trained on 10 stratified subsamples of each outer training partition, each holding half of the partition. The 10 predictions for each test instance gave the loss, the bias and the variance. The observed label replaced the optimal prediction, so the noise term merged with the bias. The decomposition was reported over all instances and as the mean over classes, where the mean over classes weights every class equally like macro-averaged F1. The subsamples overlap and therefore understate every variance. All models used the same subsamples, so the comparison between models remains fair.

The strength and the mean correlation of Breiman explained the effect of the number of features per split. For each value of a, a forest of 100 trees was fitted in every inner fold of the tuning subsample with all other settings taken from the first tuned forest. The strength and the mean correlation were computed from the votes of the individual trees on the held-out instances.

The conflicting instances were also analysed. Within each group of identical feature vectors, the winning label was determined twice. The first vote counted each instance once, while the second vote weighted each instance by w_c. The labels predicted by each model for the conflicting instances were then compared with the two votes.

D. Statistical Analysis

Two models were compared through the differences in their scores on the five outer folds. Let u_i denote the difference on fold i, and let $\bar{u}$ denote the mean difference. Let ς^2 denote the sample variance of the differences. The null hypothesis states that the two models perform equally well, and the paired t-test

TABLE III
PERFORMANCE ACROSS FIVE FOLDS, REPORTED AS THE MEAN WITH THE STANDARD DEVIATION OF MACRO-AVERAGED F1

Measure	kNN	Tree	Unpruned tree	Untuned forest	Forest, macro F1	Forest, MCC
Macro-averaged F1	0.516 ± 0.007	0.533 ± 0.003	0.577 ± 0.007	0.574 ± 0.008	$\mathbf{0.591 \pm 0.006}$	0.590 ± 0.006
Accuracy	0.785	0.816	0.808	**0.829**	0.771	0.828
MCC	0.722	0.763	0.751	**0.777**	0.719	**0.777**
Balanced accuracy	0.510	0.524	0.557	0.543	**0.635**	0.568
Macro-averaged precision	0.562	0.702	0.643	0.734	0.591	**0.765**
Fit time per fold	–	3 s	3 s	7 s	21 s	15 s

assumes independent differences. Nadeau and Bengio showed that a test of this kind ignores the variability due to the choice of training set and therefore underestimates the variance [15]. The paired t-test then rejects the null hypothesis too often.

Nadeau and Bengio proposed a corrected statistic. With n_1 and n_2 the numbers of training and test instances per fold, the corrected statistic is given by

$$t = \frac{\bar{u}}{\sqrt{\left(\frac{1}{v} + \frac{n_2}{n_1}\right)\varsigma^2}}. \tag{14}$$

Under the null hypothesis, the statistic follows a t distribution with $v-1$ degrees of freedom. The correction was derived for repeated random splits into training and test sets, and serves as an approximation for the five folds. The probability value is the probability of a difference at least as large as the observed difference under the null hypothesis. Every probability value reported in the present study is that of the corrected test, and a difference was considered significant below a probability value of 0.05. The number of folds won by each model is also reported because the count makes no distributional assumption.

In summary, every model was evaluated on the same five partitions. Every comparison between models was therefore paired.

V. RESULTS AND DISCUSSION

This section presents the results obtained under the procedure described in Section IV. The comparison with assignment 2 is presented first, followed by the sources of the improvement. The behaviour of the forest under tuning then follows. The section closes with the effect of class weighting and of the duplicated instances.

A. Comparison with Assignment 2

Table III reports the outer cross-validation results, and Table IV reports the paired comparisons. The forest tuned for macro-averaged F1 outperformed the tree of assignment 2 by 0.059 on the primary measure and won on all five folds at a probability value of 3×10^{-5}. The forest outperformed the kNN model by 0.075 at a probability value of 2×10^{-4}. The random forest therefore outperformed both models of assignment 2 on the primary measure.

The size of the advantage depended on the measure. On the MCC, the forest tuned for macro-averaged F1 scored 0.044 below the tree of assignment 2. The forest tuned for the MCC matched the primary score of the first forest at 0.590 and outperformed the tree by 0.013 on the MCC. The forest tuned for the MCC was therefore the only model that outperformed the tree on both measures.

Figure 1 shows the per-class F1. The forests gained most where the tree of assignment 2 was weak. The forest tuned for macro-averaged F1 raised the F1 of Worms from 0.466 to 0.740. The same forest raised Shellcode from 0.558 to 0.688 and Fuzzers from 0.572 to 0.681. No model approached the ceiling for the DoS, Analysis or Backdoor classes. The conflicting instances of Section II explain the shortfall, and a better model would not close the gap. For an operator, the forests detect the rare Worms and Shellcode attacks far better than the models of assignment 2. The forests nonetheless separate DoS from Exploits no better than before.

B. Sources of the Improvement

The comparison alone does not show why the forest won. The choice of a random forest assumed that averaging reduces the variance of the tree, so the untuned forest was expected to outperform the tree through a lower variance. Table V shows the opposite. Both forests showed more variance than the tree of assignment 2 over all instances, at 0.065 and 0.089 against 0.036.

The cause lay in the tree rather than in the theory. On a full outer training partition, the tree of assignment 2 had 174 leaves and a depth of 22. The same tree without pruning had 14 568 leaves and a depth of 58, so the tree of assignment 2 was heavily pruned. Pruning lowers the capacity of a tree and therefore yields low variance and high bias. The argument for bagging applies to the unpruned tree instead, and the unpruned tree therefore served as the reference for the effect of ensembling.

The pruning had been selected on the tuning subsample. The implementation weights the cost of each node by the proportion of training instances in the node,[9] so the same value of α prunes more on a larger training set. On an inner training fold of 32 000 instances, $\alpha = 10^{-4}$ retained 353 of 3 914 leaves. On an outer training partition of about 206 000 instances, the same value retained only 174 of 14 568 leaves. A hyperparameter tuned on a subsample therefore did not carry the same meaning on the full dataset.

[9]https://scikit-learn.org/stable/modules/tree.html

TABLE IV
PAIRED COMPARISONS, REPORTED AS THE MEAN DIFFERENCE, THE FOLDS WON AND THE CORRECTED PROBABILITY VALUE

	Macro-averaged F1			MCC		
Comparison	Difference	Folds	Probability	Difference	Folds	Probability
Forest, macro F1 against tree	$+0.059$	5/5	3×10^{-5}	-0.044	0/5	3×10^{-5}
Forest, macro F1 against kNN	$+0.075$	5/5	2×10^{-4}	-0.003	1/5	0.11
Untuned forest against tree	$+0.041$	5/5	0.002	$+0.014$	5/5	4×10^{-4}
Untuned forest against unpruned tree	-0.002	3/5	0.76	$+0.027$	5/5	3×10^{-6}
Tree against unpruned tree	-0.044	0/5	5×10^{-4}	$+0.013$	5/5	8×10^{-4}
Forest, macro F1 against untuned forest	$+0.017$	5/5	0.097	-0.058	0/5	3×10^{-6}
Forest, MCC against forest, macro F1	-0.001	2/5	0.57	$+0.058$	5/5	1×10^{-6}
Forest, MCC against tree	$+0.057$	5/5	1×10^{-4}	$+0.013$	5/5	0.001
Forest, MCC against untuned forest	$+0.016$	5/5	0.15	-0.001	1/5	0.36




Fig. 1. Per-class F1, ordered by the number of instances, with the idealised ceiling

TABLE V
DECOMPOSITION OF THE ZERO-ONE LOSS OVER ALL INSTANCES AND AS THE MEAN OVER CLASSES

	All instances			Mean over classes		
Model	Loss	Bias	Variance	Loss	Bias	Variance
Unpruned tree	0.202	0.177	0.112	0.452	0.428	0.209
Tree	0.184	0.180	0.036	0.481	0.469	0.080
Untuned forest	0.177	0.174	0.065	0.469	0.469	0.130
Tuned forest	0.228	0.230	0.089	0.365	0.366	0.157


The unpruned tree separates the two effects, as Table IV shows. Removal of the pruning raised macro-averaged F1 by 0.044 at a probability value of 5×10^{-4}. Ensembling added nothing to macro-averaged F1, with a difference of -0.002 at a probability value of 0.76. Most of the gain on the primary measure therefore came from the absence of pruning rather than from ensembling. The pruning was nonetheless a trade-off rather than a mistake, since the pruned tree scored 0.013 higher on the MCC than the unpruned tree.

Figure 2 shows that the theory held against the correct reference. Over all instances, the untuned forest lowered the variance of the unpruned tree from 0.112 to 0.065. The bias barely changed from 0.177 to 0.174, while the loss fell from 0.202 to 0.177. Ensembling therefore raised the MCC by 0.027 over the unpruned tree.

The mean over classes explains why macro-averaged F1 did not improve. Averaged over classes, the bias of the forest rose from 0.428 to 0.469 and cancelled the reduction in variance. An average of many trees converges on the majority vote, and the majority vote favours the large class wherever a small class overlaps a large class. A single unpruned tree is noisier, and the noise of a single tree sometimes falls on the small class. The tuned forest lowered the mean bias over classes to 0.366 through class weighting.

C. Behaviour of the Forest under Tuning


The tuning results show whether the compared forest was well configured, and why the selected values work. Figure 3 shows the score of the forest against the number of trees. On the full dataset, a single tree scored 0.545. Ten trees scored 0.583 and 100 trees scored 0.591, so most of the gain arrived within the first 10 trees. The curve never declined, in line with the variance of an average. The selected 100 trees made the



(a) All instances

(b) Mean over classes

Fig. 2. Loss, bias and variance of the zero-one loss



(a) Tuning subsample

(b) Full dataset

Fig. 3. Macro-averaged F1 against the number of trees





Fig. 4. Macro-averaged F1 in the first tuning stage

tuned forest about seven times slower to train than the tree, at 21 seconds per fold against three seconds.

Figure 4 shows the first tuning stage. A single feature per split scored lowest at 0.490 without weighting, and the default of six features also scored below the best. Twenty-one features with balanced weighting scored best at 0.543, against 0.526 for all 42 features under the same weighting. Without weighting, every value of a from 10 to 42 scored between 0.523 and 0.524. Weighting per tree scored below no weighting at every value of a. Excessive randomness clearly hurt, but the advantage of moderate decorrelation over bagging was only about one standard deviation.

Figure 5 explains the shape of the first-stage curve. The mean correlation rose with every additional feature, from 0.526 to 0.612. The strength rose quickly from 0.475 to 0.534 at 10 features before levelling off and dipping slightly at 42 features. Beyond 21 features, the trees therefore grew more alike without growing stronger. Breiman observed the same pattern on other datasets [3]. The forest score fell from 0.562 to 0.540 over that range, even though the single trees improved from 0.500 to 0.505. The bound of Breiman exceeded one and was not informative as a bound, although the minimum of the bound coincided with the best forest at 21 features. A



(a) Strength (b) Mean correlation (c) Macro-averaged F1

Fig. 5. Strength, mean correlation and macro-averaged F1 against the number of features considered at each split

moderate number of features per split therefore balanced the strength and the correlation of the trees.

The second stage favoured nearly fully grown trees. The combination of $\omega = 2$ and the entropy scored best at 0.560, while a minimum leaf size of 25 lowered the score to 0.491. Fully grown trees suited the forest because averaging removes much of the variance of each tree. The heavy pruning of the tree of assignment 2 is therefore unnecessary inside a forest. The search for the MCC preferred larger leaves with $\omega = 10$, so the preferred size of the trees depended on the objective.

D. Class Weighting and the Tuning Objective

The two tuned forests achieved the same macro-averaged F1 of 0.591 and 0.590, with a probability value of 0.57 for the difference. The forest tuned for macro-averaged F1 nonetheless had the lowest accuracy of all six models at 0.771, against 0.828 for the forest tuned for the MCC. Class weighting explains the difference, because the first forest used balanced weighting while the second forest used none.

Balanced weighting was selected on the strength of a single class. In the inner cross-validation, weighting raised macro-averaged F1 by 0.019 at $a = 21$. The Worms class gained 0.24 in F1, while the Normal and Exploits classes each lost about 0.03. The Reconnaissance and Backdoor classes each lost about 0.04. One class contributes one tenth of macro-averaged F1, so the Worms class alone contributed 0.024 and exceeded the net gain. A class with 27 instances in the tuning subsample therefore decided the weighting. The search for the MCC counted every instance equally and rejected weighting at every value of a.

Table VI shows the cost of the weighting on the full dataset. Among the 40 400 conflicting instances, an unweighted vote awarded 26 332 instances to Exploits and two to Backdoor. A vote weighted by w_c awarded 136 instances to Exploits and 20 939 to Backdoor, because a Backdoor instance carries about 19 times the weight of an Exploits instance. The weighted forest predicted Backdoor for 20 591 conflicting instances and therefore reproduced the weighted vote. The precision of the weighted forest on Backdoor fell to 0.021, while the forest tuned for the MCC predicted Backdoor for none of the conflicting instances.

TABLE VI
LABELS AWARDED TO THE 40 400 CONFLICTING INSTANCES

Source	Exploits	Backdoor	DoS	Analysis
Unweighted vote	26 332	2	8 706	6
Weighted vote	136	20 939	12 777	4 409
Tree	36 151	0	377	0
Untuned forest	26 230	61	10 466	41
Forest, macro F1	516	20 591	9 134	8 093
Forest, MCC	27 531	0	9 243	0

The weighting did buy recall on the small classes. The weighted forest detected 89.7 percent of Worms against 49.5 percent for the unweighted forest, at the cost of a macro-averaged precision of only 0.591. The unweighted forest achieved the highest macro-averaged precision of all six models at 0.765. The two forests therefore reached the same macro-averaged F1 by opposite routes.

Class weighting adds no information. Between separable classes, weighting moves the decision boundary towards the small class. Among identical instances, weighting only changes the winning label. The cost on the large classes became visible only on the full dataset, so the macro-averaged F1 of the tuning subsample did not reveal the cost. The forest tuned for the MCC is therefore preferable unless a missed Worms attack costs more than many false positives.

E. Duplicated Instances

Duplicated instances could have distorted the comparison. About 45 percent of the instances in each outer test fold had an exact copy in the training partition, so a model could score well on those instances by memorisation alone. Copies with a consistent label were indeed classified almost perfectly, with an accuracy between 0.97 and 1.00 for every model. The conflicting instances formed a third of the copies. Every model misclassified most conflicting instances. Table VII shows that the two effects combined to lower the score of every model on the instances with a copy. On the instances without a copy,

TABLE VII
MACRO-AVERAGED F1 ON TEST INSTANCES WITH AND WITHOUT A COPY IN THE TRAINING PARTITION

Test instances	kNN	Tree	Unpruned tree	Untuned forest	Forest, macro F1	Forest, MCC
All	0.516	0.533	0.577	0.574	0.591	0.590
With a copy	0.505	0.491	0.521	0.529	0.539	0.522
Without a copy	0.549	0.591	0.633	0.658	0.715	0.671

every model scored higher. The ranking of the models was unchanged and the gaps widened, so the duplicates do not explain the advantage of the forest.

In summary, the random forest outperformed both models of assignment 2 on the primary measure and on the instances without a copy. The absence of pruning explained most of the gain, while ensembling reduced variance and improved the MCC rather than macro-averaged F1. Class weighting traded overall accuracy for the detection of the small classes, so the forest tuned for the MCC offered the best balance between the two measures.

VI. CONCLUSION

The study examined whether a random forest outperforms the k-nearest neighbours (kNN) model and the classification tree of assignment 2 in the classification of network traffic attack categories. The random forest was chosen because the forest shares the base learner and the pre-processing of the tree. All models were evaluated on identical five-fold stratified partitions.

The random forest outperformed both models. The forest tuned for macro-averaged F1 exceeded the tree by 0.059 and the kNN model by 0.075 on that measure. The forest tuned for the Matthews correlation coefficient (MCC) matched that score at an accuracy of 0.828 and was the only model that outperformed the tree on both measures.

The supporting analyses qualified the source of the improvement. The tree of assignment 2 was heavily pruned because the pruning parameter scales with the size of the training set. Removal of the pruning explained most of the gain on macro-averaged F1, while ensembling reduced variance and improved the MCC rather than macro-averaged F1.

The tuning showed that about 100 trees sufficed and that a moderate number of features per split balanced the strength and the correlation of the trees. Class weighting raised macro-averaged F1 through a single small class. The same weighting flipped groups of identical instances to the Backdoor class and cost 5.7 percentage points of accuracy. Conflicting instances limited every model on the denial of service (DoS), Analysis and Backdoor classes.

The forest tuned for the MCC was concluded to be the most suitable model. An operator who must detect every Worms attack would prefer the weighted forest at the cost of many false positives.

A few directions remain for future work. Nested cross-validation would remove the overlap between the tuning subsample and the test folds [16]. The forest predicts the class with the largest share of the votes. Scaling the share of each class by a factor tuned after training would offer an alternative to class weighting without retraining the forest. Bias formed most of the loss of every forest, so averaging left most of the error untouched. Future work could compare the forest with boosting, an ensemble that targets bias rather than variance [4]. Boosting is sensitive to label noise [12], so the comparison would also show whether the conflicting instances limit boosting more than the forest

REFERENCES

[1] N. Moustafa and J. Slay, "UNSW-NB15: A comprehensive data set for network intrusion detection systems," in *Proceedings of the Military Communications and Information Systems Conference*. Canberra, Australia: IEEE, 2015, pp. 1–6.

[2] T. G. Dietterich, "Ensemble methods in machine learning," in *Proceedings of the International Workshop on Multiple Classifier Systems*, ser. Lecture Notes in Computer Science, vol. 1857. Berlin: Springer, 2000, pp. 1–15.

[3] L. Breiman, "Random forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

[4] T. Hastie, R. Tibshirani, and J. Friedman, *The Elements of Statistical Learning*, 2nd ed. New York: Springer, 2009.

[5] J. Gorodkin, "Comparing two K-category assignments by a K-category correlation coefficient," *Computational Biology and Chemistry*, vol. 28, no. 5–6, pp. 367–374, 2004.

[6] P. Domingos, "A unified bias-variance decomposition for zero-one and squared loss," in *Proceedings of the Seventeenth National Conference on Artificial Intelligence*. Austin, Texas: AAAI Press, 2000, pp. 564–569.

[7] T. Cover and P. Hart, "Nearest neighbor pattern classification," *IEEE Transactions on Information Theory*, vol. 13, no. 1, pp. 21–27, 1967.

[8] J. R. Quinlan, "Induction of decision trees," *Machine Learning*, vol. 1, no. 1, pp. 81–106, 1986.

[9] L. Breiman, "Bagging predictors," *Machine Learning*, vol. 24, no. 2, pp. 123–140, 1996.

[10] Y. Freund and R. E. Schapire, "A decision-theoretic generalization of on-line learning and an application to boosting," *Journal of Computer and System Sciences*, vol. 55, no. 1, pp. 119–139, 1997.

[11] H. He and E. A. Garcia, "Learning from imbalanced data," *IEEE Transactions on Knowledge and Data Engineering*, vol. 21, no. 9, pp. 1263–1284, 2009.

[12] B. Frénay and M. Verleysen, "Classification in the presence of label noise: A survey," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 25, no. 5, pp. 845–869, 2014.

[13] D. R. Wilson and T. R. Martinez, "Improved heterogeneous distance functions," *Journal of Artificial Intelligence Research*, vol. 6, pp. 1–34, 1997.

[14] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and É. Duchesnay, "Scikit-learn: Machine learning in Python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.

[15] C. Nadeau and Y. Bengio, "Inference for the generalization error," *Machine Learning*, vol. 52, no. 3, pp. 239–281, 2003.

[16] G. C. Cawley and N. L. C. Talbot, "On over-fitting in model selection and subsequent selection bias in performance evaluation," *Journal of Machine Learning Research*, vol. 11, pp. 2079–2107, 2010.