Lab 09 - matrix-free computations with MPI

Numerical Solution of PDEs Using the Finite Element Method

MHPC P2.13_seed

Martin Kronbichler kronbichler@lnm.mw.tum.de and **Luca Heltai** luca.heltai@sissa.it

---

1. Run the included step-37 example. Compile the code in release mode ("make release") and run with 1 and 2 MPI processes. Record the solver time and the number of iterations.

2. This example uses a geometric multigrid preconditioner that gives constant iteration numbers as the mesh is refined, as opposed to the `PreconditionIdentity` that was used in the early labs. Check the number of iterations with the conjugate gradient method.

3. Enable the code `compare_performance_matrix_vector()` in the `run()` function. Study the steps in this function. Which of the matrix-based and the matrix-free product is faster on your machine?

4. Change the polynomial degree from `2` (set at the top of the file through the variable `degree_finite_element`) to `1` and `3`. Observe the difference in the performance of the matrix-vector product. Be careful with the large problem sizes and degree `3` as the sparse matrix could run out of RAM memory.

5. Compare the ratio between the sparse matrix-vector with the Trilinos sparse matrix and the matrix-free `LaplaceOperator` when run on `1` processor core with the ratio when using all processors on your system. What could be an explanation of the difference in the ratio?