FORM U-1A MANUFACTURERS' DATA REPORT FOR PRESSURE VESSELS

(Alternate Form for Single Chamber, Completely Shop-Fabricated Vessels Only)
As Required by the Provisions of the ASME Code Rules, Section VIII, Division 1

1. Manufactured by COASTAL IRON WORKS, INC. 1133 E. Port, Corpus Christi, Texas 78403
(Name and address of manufacturer)
2. Manufactured for E.I. Du Pont de Nemours & Co., Inc., 1007 Market St., Wilmington, DE. 1989
(Name and address of purchaser)
3. Location of Installation E.I. Du Pont de Nemours & Co., Inc., Bloomington, Texas 77901
(Name and address)
4. Type Vert. Vessel (Horiz., or vert. tank) Vessel No. 331519 (Mfgr's Serial No.) N/A (CRN) 80-2191, 2192 81-2459 (Drawing No.)
314 (Nat'l Brd No.) Year Built 1981

5. The chemical and physical properties of all parts meet the requirements of material specifications of the ASME BOILER AND PRESSURE VESSEL CODE. The design, construction, and workmanship conform to ASME Rules, Section VIII, Division 1 1980 (Year) and Addenda to Winter'80 (Date) and Code Case no. N/A

Special Service per UG-120(d) N/A

Manufacturers' Partial Data Reports properly identified and signed by Commissioned Inspectors have been furnished for the following items of the report:

N/A
(Name of part, item number, mfgr's name and identifying stamp)

6. Shell: Material SA-516-70 (Spec. No., Grade) Nominal Thickness 1/4 in. Corrosion Allowance 1/16 in.
Diam. 3 ft 6 in. Length 4 ft 9 in.
7. Seams: Longitudinal Single Butt (Welded, Dbl., Sngl. Lap, Butt) R.T. Spot (Spot or Full) Efficiency 85 %
H.T. Temp N/A F Time N/A Girth Single Butt (Welded, Dbl. Sngl. Lap, Butt)
R.T. Spot (Spot, Partial, or Full) No. of Courses 1

CERTIFICATE OF COMPLIANCE

We certify that the statements made in this report are correct and that all details of design, material, construction, and workmanship of this vessel conform to the ASME Code for Pressure Vessels, Section VIII, Division 1.

Date 5-18-81 Signed Coastal Iron Works, Inc. (Manufacturer) by E.E. True, III (Representative) E.E. True III

"U"-Certificate of Authorization No. 3450 expires March 30, 19 84.

CERTIFICATE OF SHOP INSPECTION

Vessel made by Coastal Iron Works, Inc. at 1133 E. Port, Corpus Christi, Tx

I, the undersigned, holding a valid commission issued by the National Board of Boiler and Pressure Vessel Inspectors and/or the State or Province of Texas and employed by Commercial Union Ins. have inspected the pressure vessel described in this Manufacturers' Data Report on 10-1, 1981, and state that, to the best of my knowledge and belief, the Manufacturer has constructed this pressure vessel in accordance with ASME Code, Section VIII, Division 1.

By signing this certificate neither the Inspector nor his employer makes any warranty, expressed or implied, concerning the pressure vessel described in the Manufacturers' Data Report. Furthermore, neither the Inspector nor his employer shall be liable in any manner for any personal injury or property damage or a loss of any kind arising from or connected with this inspection.

Date 10-1-81 Signed Roger N. Loftis (Inspector) Commissions N.B. # 9015 (Nat'l Board, State, Province and No.)

This form (E00109) may be obtained from the Order Dept., ASME, 345 E. 47th St., New York, N.Y. 10017

FORM U-1A (BACK)

8. **Heads:** (a) Material SA-516-70 (Spec. No., Grade) (b) Material Same (Spec. No., Grade)

	Location (Top, Bottom, Ends)	Minimum Thickness	Corrosion Allowance	Crown Radius	Knuckle Radius	Elliptical Ratio
(a)	Top	.1875"	1/16"	40"	2-5/8"	N/A
(b)	Btm.	Do	Do	Do	Do	Do

	Conical Apex Angle	Hemispherical Radius	Flat Diameter	Side to Pressure (Convex or Concave)
(a)	N/A	N/A	N/A	Concave
(b)	Do	Do	Do	Do

If removable, bolts used (describe other fastenings) N/A (Material, Spec. No., Gr., Size, No.)

Constructed for max. allowable working pressure FV & 52 psi at max. temp. 500 F. Min. temp. (when less than -20 F) N/A F. Hydrostatic, [redacted] test pressure 78 psi.

9. **Safety Valve Outlets:** Number N/A Size N/A Location N/A

10. **Nozzles:**

Purpose (Inlet, Outlet, Drain)	Number	Diam. or Size	Type	Material	Nominal Thickness	Reinforcement Material	How Attached
	3	1½"-150#	RFWN	SA-106-B	.281"	N/R	Welded
	1	2"	Do	Do	.343"	Do	Do
	2	3"	Do	Do	.300"	Do	Do
	3	4"	Do	Do	.337"	Do	Do
	2	8"-150#	Studding Outlet	SA-105	2.750"	Do	Do

11. **Inspection Openings:**
Manholes No. 1 Size 24" Location Shell
Handholes No. N/A Size N/A Location N/A
Threaded No. N/A Size N/A Location N/A

12. **Supports:** Skirt No (Yes or no) Lugs N/A (No.) Legs 3 (No.) Other N/A (Describe)
Attached Welded to Shell. (Where and how)

13. **Remarks:** One (1) Pressure Vessel Item Number 4062-1220-3, Designed and Fabricated per the ASME Boiler and Pressure Vessel Code, Section VIII, Division I, 1980 Edition.