

Your Optimizing Compiler is Not Optimizing Enough. To Hell With Multiple Recursions!

Federico Bruzzone,¹ PhD Candidate

Milan, Italy – 4 December 2025



¹ADAPT Lab – Università degli Studi di Milano,

Website: federicobruzzone.github.io,

Github: github.com/FedericoBruzzone,


Email: federico.bruzzone@unimi.it

Slides: federicobruzzone.github.io/activities/presentations/your-optimizing-compiler-is-not-optimizing-enough.pdf

Premature Optimizations

Donald E. Knuth warned in 1974 about the dangers of **premature optimization** in programming [1]:

We should forget about small efficiencies, say about 97% of the time: premature optimization is the root of all evil. Yet we should not pass up our opportunities in that critical 3%.



In the absence of either empirically measured or theoretically justified performance issues, programmers should **avoid** making optimizations based **solely** on assumptions about potential performance gains.

Optimizing Compilers

Compilers use information collected during analysis passes to guide transformations [2], [3].

Compiler optimizations² are such transformations (say *meaning-preserving mappings* [5]) applied to the input code to improve certain aspects—such as performance, resource utilization, and power consumption—without altering its observable behavior.

In accordance with the literature [6], [7], such compilers are referred to as **optimizing compilers**.

²A *chronologically* sorted list of papers on compiler optimization, from the works of 1952 through the techniques of 1994, is available at [4].

Optimizing Compilers

Compilers use information collected during analysis passes to guide transformations [2], [3].

Compiler optimizations³ are such transformations (say *meaning-preserving mappings* [5]) applied to the input code to improve certain aspects—such as performance, resource utilization, and power consumption—without altering its observable behavior.

In accordance with the literature [6], [7], such compilers are referred to as **optimizing compilers**.

³A *chronologically* sorted list of papers on compiler optimization, from the works of 1952 through the techniques of 1994, is available at [4].

Optimizing Compilers



Compilers use information collected during analysis passes to guide transformations [2], [3].

Compiler optimizations⁴ are such transformations (say *meaning-preserving mappings* [5]) applied to the input code to improve certain aspects—such as performance, resource utilization, and power consumption—without altering its observable behavior.

In accordance with the literature [6], [7], such compilers are referred to as **optimizing compilers**.

⁴A *chronologically* sorted list of papers on compiler optimization, from the works of 1952 through the techniques of 1994, is available at [4].

Machine Learning Framework are Just Optimizing Compilers⁵



⁵TensorFlow XLA, NVIDIA CUDA Compiler (NVCC), MLIR, and TVM all use **LLVM** [8]. Li *et al.*, [9] compiled a survey on ML compilers.

Peephole Optimizations in x86-64 (cf. [10], [11])

```
1 ; x = x * 2, s.t. x: i32 asm
2 mov     eax, dword ptr [rbp - 4]
3 imul    eax, 2
4 mov     dword ptr [rbp - 4], eax
```


Peephole Optimizations in x86-64 (cf. [10], [11])

```
1 ; x = x * 2, s.t. x: i32      asm
2 mov     eax, dword ptr [rbp - 4]
3 imul    eax, 2
4 mov     dword ptr [rbp - 4], eax
```

The optimized version replaces the multiplication by 2 with a **more efficient** binary shift operation.

```
1 ; x = x << 1, s.t. x: i32    asm
2 mov     eax, dword ptr [rbp - 4]
3 shl     eax
4 mov     dword ptr [rbp - 4], eax
```

Peephole Optimizations in x86-64 (cf. [10], [11])

```
1 ; x = x * 2, s.t. x: i32
2 mov     eax, dword ptr [rbp - 4]
3 imul    eax, 2
4 mov     dword ptr [rbp - 4], eax
```

asm

The optimized version replaces the multiplication by 2 with a **more efficient** binary shift operation.

```
1 ; x = x << 1, s.t. x: i32
2 mov     eax, dword ptr [rbp - 4]
3 shl     eax
4 mov     dword ptr [rbp - 4], eax
```

asm

```
1 ; x = x + 0, s.t. x: i32
2 mov     eax, dword ptr [rbp - 4]
3 add     eax, 0
4 mov     dword ptr [rbp - 4], eax
```

asm

Peephole Optimizations in x86-64 (cf. [10], [11])

```
1 ; x = x * 2, s.t. x: i32
2 mov     eax, dword ptr [rbp - 4]
3 imul    eax, 2
4 mov     dword ptr [rbp - 4], eax
```

asm

The optimized version replaces the multiplication by 2 with a **more efficient** binary shift operation.

```
1 ; x = x << 1, s.t. x: i32
2 mov     eax, dword ptr [rbp - 4]
3 shl     eax
4 mov     dword ptr [rbp - 4], eax
```

asm

```
1 ; x = x + 0, s.t. x: i32
2 mov     eax, dword ptr [rbp - 4]
3 add     eax, 0
4 mov     dword ptr [rbp - 4], eax
```

asm

The optimized version removes the **unnecessary** addition operation.

```
1 mov     eax, dword ptr [rbp - 4]
2 mov     dword ptr [rbp - 4], eax
```

asm

Peephole Optimizations in x86-64 (cf. [10], [11])

```
1 ; x = x * 2, s.t. x: i32      asm
2 mov     eax, dword ptr [rbp - 4]
3 imul    eax, 2
4 mov     dword ptr [rbp - 4], eax
```

The optimized version replaces the multiplication by 2 with a **more efficient** binary shift operation.

```
1 ; x = x << 1, s.t. x: i32    asm
2 mov     eax, dword ptr [rbp - 4]
3 shl     eax
4 mov     dword ptr [rbp - 4], eax
```

```
1 ; x = x + 0, s.t. x: i32    asm
2 mov     eax, dword ptr [rbp - 4]
3 add     eax, 0
4 mov     dword ptr [rbp - 4], eax
```


The optimized version removes the **unnecessary** addition operation.

```
1 mov     eax, dword ptr [rbp - 4]  asm
2 mov     dword ptr [rbp - 4], eax
```

The mov instructions are redundant and can be **pruned** as well!

Loop Nest Optimizations — Loop Tiling (cf. [12], [13])

```
for (int i=0; i<n; ++i) {  
    for (int j=0; j<m; ++j) {  
        c[i][j] = a[i] * b[j];  
    }  
}
```




The vector **b** **may not** fit into a line of CPU cache, causing multiple cache misses during the inner loop.

It implies multiple **fetches** from the main memory, which is **slow**.


Loop Nest Optimizations — Loop Tiling (cf. [12], [13])

```
for (int i=0; i<n; ++i) {  
    for (int j=0; j<m; ++j) {  
        c[i][j] = a[i] * b[j];  
    }  
}
```



The inner loop works on a **tile** of b that fits into the cache.

```
for (int jj = 0; jj < m; jj += TILE_SIZE) {  
    for (int i = 0; i < n; ++i)  
        for (int j = jj; j < MIN(jj + TILE_SIZE, m); ++j)  
            c[i][j] = a[i] * b[j];  
}
```




The vector b **may not** fit into a line of CPU cache, causing multiple cache misses during the inner loop.

It implies multiple **fetches** from the main memory, which is **slow**.


Loop Nest Optimizations — Loop Tiling (cf. [12], [13])

```
for (int i=0; i<n; ++i) {  
    for (int j=0; j<m; ++j) {  
        c[i][j] = a[i] * b[j];  
    }  
}
```



The vector **b** **may not** fit into a line of CPU cache, causing multiple cache misses during the inner loop.

It implies multiple **fetches** from the main memory, which is **slow**.



The inner loop works on a **tile** of **b** that fits into the cache.

```
for (int jj = 0; jj < m; jj += TILE_SIZE)  
    for (int i = 0; i < n; ++i)  
        for (int j = jj; j < MIN(jj + TILE_SIZE, m); ++j)  
            c[i][j] = a[i] * b[j];
```


Careful readers may notice that, in this version, the values for the array **a** will be read $m / \text{TILE_SIZE}$!

```
for (int ii = 0; ii < n; ii += TILE_SIZE_I)  
    for (int jj = 0; jj < m; jj += TILE_SIZE_J)  
        for (int i = ii; i < MIN(n, ii + TILE_SIZE_I); i++)  
            for (int j = jj; j < MIN(m, jj + TILE_SIZE_J); j++)  
                c[i][j] = a[i] * b[j];
```

Tail Call/Recursion Optimization (cf. [2], [14], [15])

Guy L. Steele, Jr. in 1977 observed that **tail-recursive procedure calls** can be optimized to avoid growing the call stack [16]:

In general, procedure calls may be usefully thought of as GOTO statements which also pass parameters, and can be uniformly coded as [machine code] JUMP instructions.



From Recursion to Iteration (cf. [17])

$$f(x) = \begin{cases} b(x_0) & \text{if } x = x_0 \\ a(x, f(d(x))) & \text{otherwise} \end{cases}$$

s.t. a, b , and so on may denote any pieces of code.

From Recursion to Iteration (cf. [17])

$$f(x) = \begin{cases} b(x_0) & \text{if } x = x_0 \\ a(x, f(d(x))) & \text{otherwise} \end{cases}$$

s.t. a, b , and so on may denote any pieces of code.

To transform recursive function f into iterative form, we need to:

1. Identifies an increment \oplus to the argument of f , *id est*, $x' = x \oplus y$ such that $x = \text{prev}(x')$, where prev is based on the arguments of the recursive call. In this case, $\text{prev}(x) = d(x)$ and, if d^{-1} exists, $x \oplus y = d^{-1}(x)$, can be plugged in for y .
2. Derives an incremental program $f'(x, r)$ that computes $f(x)$ using an accumulator r of $f(\text{prev}(x))$.
3. Forms an iterative version that initializes using the base case of f and iteratively applies f' until reaching the desired argument.

$$f(x) = \{$$
$$x_1 = x_0; r = b(x_0);$$
$$\mathbf{while} (x_1 \neq x) \{$$
$$x_1 = d^{-1}(x_1);$$
$$r = a(x_1, r);$$
$$\}$$
$$\mathbf{return} r;$$
$$\}$$

Note that, when a is in the form $a(a_1(x), y)$ and a is associative, we do not need d^{-1} and x_1 .

Tail-recursive Factorial Function

```
int fact(int n) {  
    if (n == 0) {  
        return 1;  
    }  
    return n * fact(n - 1);  
}
```

The replacement of $n * ((n - 1) * (n - 2))$ by $(n * (n - 1)) * (n - 2)$ is valid due to the **associativity** of multiplication. In the general form:

$$f(x) = \{$$
$$r = b(x_0);$$
$$\text{while } (x \neq x_0) \{$$
$$r = a(r, a_1(x));$$
$$x = d(x);$$
$$\}$$
$$\text{return } r;$$
$$\}$$

Note that, (i) when dealing with IEEE754 numbers, multiplication is **not** strictly associative, and (ii) the latter *might be* slower due to multiply bigger numbers.

Tail-recursive Factorial Function

```
int fact(int n) {  
    if (n == 0) {  
        return 1;  
    }  
    return n * fact(n - 1);  
}
```

The replacement of $n * ((n - 1) * (n - 2))$ by $(n * (n - 1)) * (n - 2)$ is valid due to the **associativity** of multiplication. In the general form:

$$f(x) = \{$$
$$r = b(x_0);$$
$$\text{while } (x \neq x_0) \{$$
$$r = a(r, a_1(x));$$
$$x = d(x);$$
$$\}$$
$$\text{return } r;$$
$$\}$$

Note that, (i) when dealing with IEEE754 numbers, multiplication is **not** strictly associative, and (ii) the latter *might be* slower due to multiply bigger numbers.

Tail-recursive Factorial Function

```
int fact(int n) {  
    if (n == 0) {  
        return 1;  
    }  
    return n * fact(n - 1);  
}
```

The replacement of $n * ((n - 1) * (n - 2))$ by $(n * (n - 1)) * (n - 2)$ is valid due to the **associativity** of multiplication. In the general form:

$$f(x) = \{$$
$$r = b(x_0);$$
$$\text{while } (x \neq x_0) \{$$
$$r = a(r, a_1(x));$$
$$x = d(x);$$
$$\}$$
$$\text{return } r;$$
$$\}$$

Note that, (i) when dealing with IEEE754 numbers, multiplication is **not** strictly associative, and (ii) the latter *might be* slower due to multiply bigger numbers.

“clang -O3 -S -emit-llvm fact.c -o -” produces something like:

```
define i32 @fact(i32 %n) {  
entry:  
    %cmp3 = icmp eq i32 %n, 0  
    br i1 %cmp3, label %return, label %if.else  
  
if.else:  
    %n.tr5 = phi i32 [ %sub, %if.else ], [ %n, %entry ]  
    %acc.tr4 = phi i32 [ %mul, %if.else ], [ 1, %entry ]  
    %sub = add nsw i32 %n.tr5, -1  
    %mul = mul nsw i32 %n.tr5, %acc.tr4  
    %cmp = icmp eq i32 %sub, 0  
    br i1 %cmp, label %return, label %if.else  
  
return:  
    %acc.tr.lcssa = phi i32 [ 1, %entry ], [ %mul, %if.else ]  
    ret i32 %acc.tr.lcssa  
}
```

The basic blocks related to loop vectorization (for performing SIMD operations) have been omitted for clarity

What About Fibonacci? To Hell With Multiple Recursions!

```
int fib(int n) {  
    if (n <= 1) {  
        return n;  
    }  
    return fib(n - 1) + fib(n - 2);  
}
```

The LLVM Optimized Version (but human readable)

```
int fib(int n) {  
    if (n < 2) {  
        return n;  
    }  
    int acc = 0;  
loop: /* while (1) { */  
    int call = fib(n - 1);  
    acc = call + acc;  
    if (n < 4) goto ret; /* return acc + (n - 2); */  
    n = n - 2;  
    goto loop; /* } */  
ret:  
    return acc + (n - 2);  
}
```

Note that, the following LLVM IR is a fixed-point representation of the fib function; observable by the output of “`opt -passes=“default<03>” -S fib-03.ll -o -`”

```
define i32 @fib(i32 %n) {  
entry:  
    %cmp6 = icmp slt i32 %n, 2  
    br i1 %cmp6, label %return, label %if.end  
if.end:  
    %n.tr8 = phi i32 [ %sub1, %if.end ], [ %n, %entry ]  
    %accumulator.tr7 = phi i32 [ %add, %if.end ], [ 0, %entry ]  
    %sub = add nsw i32 %n.tr8, -1  
    %call = tail call i32 @fib(i32 %sub)  
    %sub1 = add nsw i32 %n.tr8, -2  
    %add = add nsw i32 %call, %accumulator.tr7  
    %cmp = icmp samesign ult i32 %n.tr8, 4  
    br i1 %cmp, label %return, label %if.end  
return:  
    %accumulator.tr.lcssa = phi i32 [ 0, %entry ], [ %add, %if.end ]  
    %n.tr.lcssa = phi i32 [ %n, %entry ], [ %sub1, %if.end ]  
    %accumulator.ret.tr = add nsw i32 %n.tr.lcssa, %accumulator.tr.lcssa  
    ret i32 %accumulator.ret.tr  
}
```

The Y. Annie Liu's Incrementalization



In 1990, Liu *et al.* have done extensive research on **Incrementalization** [17], [18], [19], [20].

Even in presence of multiple recursions, in [17, Sect. 7], they proposed a **systematic** approach (*static analysis* and *semantic-preserving transformations*) to derive an incremental program following the three steps outlined earlier (cf. slide “*From Recursion to Iteration*”).

But the Step 2. builds upon the principles of [18] and [19] — which, typically rely on user-provided knowledge or a theorem prover to derive the incremental program.

Conclusions

The papers are a little bit old-fashioned, and the key aspect of deriving the incremental program in presence of multiple recursions is **opaque**.

Last week I wrote an email to Liu asking for clarification, and two days ago I received a kind reply directing me to [21] (2024)—which confirms my understanding of the situation.

Despite her work, we are trying to understand whether it is really possible to rely exclusively on static analysis steps to automatically perform the transformation in a “general” context.

Thank You!

Bibliography

- [1] D. E. Knuth, “Structured Programming with go to Statements,” *ACM Comput. Surv.*, vol. 6, no. 4, pp. 261–301, Dec. 1974.
- [2] K. D. Cooper and L. Torczon, *Engineering a Compiler*, no. . Morgan Kaufmann, 2022.
- [3] K. Kennedy and J. R. Allen, *Optimizing compilers for modern architectures: a dependence-based approach*. Morgan Kaufmann Publishers Inc., 2001.
- [4] F. Bruzzone, “Papers on Compiler Optimizations: Analysis and Transformations (1952-1994).” <https://github.com/FedericoBruzzone/papers-on-compiler-optimizations>, 2025.
- [5] R. Paige, “Future directions in program transformations,” *SIGPLAN Not.*, vol. 32, no. 1, pp. 94–98, Jan. 1997.
- [6] F. E. Allen, “Program Optimization,” *Annual Review of Automatic Programming*, vol. 5. Pergamon Press, pp. 239–307, 1966.
- [7] W. A. Wulf, “The design of an optimizing compiler,” 1973.

- [8] C. Lattner and V. Adve, “LLVM: A compilation framework for lifelong program analysis & transformation,” in *International symposium on code generation and optimization, 2004. CGO 2004.*, 2004, pp. 75–86.
- [9] M. Li *et al.*, “The deep learning compiler: A comprehensive survey,” *IEEE Transactions on Parallel and Distributed Systems*, vol. 32, no. 3, pp. 708–727, 2020.
- [10] W. M. McKeeman, “Peephole optimization,” *Commun. ACM*, vol. 8, no. 7, pp. 443–444, July 1965.
- [11] A. S. Tanenbaum, H. van Staveren, and J. W. Stevenson, “Using Peephole Optimization on Intermediate Code,” *ACM Trans. Program. Lang. Syst.*, vol. 4, no. 1, pp. 21–36, Jan. 1982.
- [12] M. Wolfe, “More iteration space tiling,” in *Proceedings of the 1989 ACM/IEEE Conference on Supercomputing*, in Supercomputing '89. Reno, Nevada, USA: Association for Computing Machinery, 1989, pp. 655–664.
- [13] M. E. Wolf and M. S. Lam, “A data locality optimizing algorithm,” *SIGPLAN Not.*, vol. 26, no. 6, pp. 30–44, May 1991.

- [14] A. V. Aho, R. Sethi, and J. D. Ullman, *Compilers: Principles, Techniques, and Tools*,. Reading, Massachusetts: Addison Wesley, 1986.
- [15] S. Muchnick, *Advanced compiler design implementation*. Morgan kaufmann, 1997.
- [16] G. L. Steele, “Debunking the “expensive procedure call” myth or, procedure call implementations considered harmful or, LAMBDA: The Ultimate GOTO,” in *Proceedings of the 1977 Annual Conference*, in ACM '77. Seattle, Washington: Association for Computing Machinery, 1977, pp. 153–162.
- [17] Y. A. Liu and S. D. Stoller, “From recursion to iteration: what are the optimizations?,” in *Proceedings of the 2000 ACM SIGPLAN workshop on Partial evaluation and semantics-based program manipulation*, 1999, pp. 73–82.
- [18] Y. A. Liu, S. D. Stoller, and T. Teitelbaum, “Static caching for incremental computation,” *ACM Transactions on Programming Languages and Systems (TOPLAS)*, vol. 20, no. 3, pp. 546–585, 1998.
- [19] Y. A. Liu and T. Teitelbaum, “Systematic derivation of incremental programs,” *Science of Computer Programming*, vol. 24, no. 1, pp. 1–39, 1995.

- [20] Y. A. Liu, “CACHET: An interactive, incremental-attribution-based program transformation system for deriving incremental programs,” in *Proceedings 1995 10th Knowledge-Based Software Engineering Conference*, 1995, pp. 19–26.
- [21] Y. A. Liu, “Incremental Computation: What Is the Essence? (Invited Contribution),” in *Proceedings of the 2024 ACM SIGPLAN International Workshop on Partial Evaluation and Program Manipulation*, in PEPM 2024. London, UK: Association for Computing Machinery, 2024, pp. 39–52.
- [22] D. F. Bacon, S. L. Graham, and O. J. Sharp, “Compiler transformations for high-performance computing,” *ACM Computing Surveys (CSUR)*, vol. 26, no. 4, pp. 345–420, 1994.

Compilers as Musical Compositions

Compilers are frequently perceived as intricate musical compositions—like the unfinished *J. S. Bach's Art of Fugue*—where mathematical precision and logical interplay guide each part.

Every module enters in perfect timing, weaving together a structure that only the keenest ears can fully grasp.

