ANDROID STATIC ANALYSIS REPORT

Booking.com (60.2.1.11)

File Name: Booking.apk

Package Name:	com.booking
Scan Date:	Nov. 4, 2025, 4:27 p.m.
App Security Score:	48/100 (MEDIUM RISK)
Grade:	B
Trackers Detection:	9/432

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
8	92	3	3	20

FILE INFORMATION

File Name: Booking.apk
Size: 281.34MB
MD5: fe2fc14061f3482ee16ee52c701d7850
SHA1: 6b89ff2ced8af473b62f576de484fae3a4bb70f0
SHA256: 46c91b44addd15d38af6ba95b80f3e0b87ca279f6258c5cd82b3dd1bb7d5d449

APP INFORMATION

App Name: Booking.com
Package Name: com.booking
Main Activity: com.booking.startup.HomeActivity
Target SDK: 35
Min SDK: 29
Max SDK:
Android Version Name: 60.2.1.11
Android Version Code: 901692

APP COMPONENTS

Activities: 307
Services: 44
Receivers: 31
Providers: 17
Exported Activities: 70
Exported Services: 4
Exported Receivers: 6

Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: O=Booking
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2011-02-04 17:52:27+00:00
Valid To: 2111-01-11 17:52:27+00:00
Issuer: O=Booking
Serial Number: 0x4d4c3cdb
Hash Algorithm: sha1
md5: e3641de5ae76e3c7a97efcecefe2fe01
sha1: 9c9fbe258a146be83a4a0f1cb64be96a13790324
sha256: 6ac8c8a9e6f36e14e52a0a0515a36b7066e720a1b0c8a1b059e0781750a87199
sha512: 92bb9a670606b22bbbe936c034b5f9d8b2da4220134e0ed0b152445ba733d6f8189d95ff10ecf5f7b640ea0236032009e74a723f94179d80c863e0adf53be127
PublicKey Algorithm: rsa
Bit Size: 1024
Fingerprint: 6b915d75a01c0ee1ce962b9af31cb543d43c60a56207477c66972de2493701b8
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.NFC	normal	control Near-Field Communication	Allows an application to communicate with Near-Field Communication (NFC) tags, cards and readers.
android.permission.USE_CREDENTIALS	dangerous	use the authentication credentials of an account	Allows an application to request authentication tokens.
com.android.alarm.permission.SET_ALARM	unknown	Unknown permission	Unknown permission from android reference
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
com.sfr.android.console.permission.partner.READ_STATISTICS	unknown	Unknown permission	Unknown permission from android reference
com.android.launcher.permission.INSTALL_SHORTCUT	unknown	Unknown permission	Unknown permission from android reference
com.google.android.gms.permission.AD_ID	normal	application shows advertisements	This app uses a Google advertising ID and can possibly serve advertisements.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_SYNC_SETTINGS	normal	read sync settings	Allows an application to read the sync settings, such as whether sync is enabled for Contacts.
android.permission.WRITE_SYNC_SETTINGS	normal	write sync settings	Allows an application to modify the sync settings, such as whether sync is enabled for Contacts.
android.permission.AUTHENTICATE_ACCOUNTS	dangerous	act as an account authenticator	Allows an application to use the account authenticator capabilities of the Account Manager, including creating accounts as well as obtaining and setting their passwords.
android.permission.GET_ACCOUNTS	dangerous	list accounts	Allows access to the list of accounts in the Accounts Service.
android.permission.MANAGE_ACCOUNTS	dangerous	manage the accounts list	Allows an application to perform operations like adding and removing accounts and deleting their password.
android.permission.HIGH_SAMPLING_RATE_SENSORS	normal	Access higher sampling rate sensor data	Allows an app to access sensor data with a sampling rate greater than 200 Hz.
com.booking.permission.AFFILIATE_ID_RESPONSE	unknown	Unknown permission	Unknown permission from android reference
com.samsung.android.mapsagent.permission.READ_APP_INFO	unknown	Unknown permission	Unknown permission from android reference
com.booking.permission.C2D_MESSAGE	unknown	Unknown permission	Unknown permission from android reference
com.booking.permission.RECEIVER	unknown	Unknown permission	Unknown permission from android reference
com.google.android.providers.gsf.permission.READ_GSERVICES	unknown	Unknown permission	Unknown permission from android reference
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_MEDIA_IMAGES	dangerous	allows reading image files from external storage.	Allows an application to read image files from external storage.
android.permission.READ_CALENDAR	dangerous	read calendar events	Allows an application to read all of the calendar events stored on your phone. Malicious applications can use this to send your calendar events to other people.
android.permission.WRITE_CALENDAR	dangerous	add or modify calendar events and send emails to guests	Allows an application to add or change the events on your calendar, which may send emails to guests. Malicious applications can use this to erase or modify your calendar events or to send emails to guests.
manifest.permission.CAMERA	unknown	Unknown permission	Unknown permission from android reference
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.REQUEST_INSTALL_PACKAGES	dangerous	Allows an application to request installing packages.	Malicious applications can use this to try and trick users into installing additional malicious packages.
com.huawei.android.launcher.permission.CHANGE_BADGE	unknown	Unknown permission	Unknown permission from android reference
android.permission.RECORD_AUDIO	dangerous	record audio	Allows application to access the audio record path.
android.permission.DOWNLOAD_WITHOUT_NOTIFICATION	unknown	Unknown permission	Unknown permission from android reference
com.google.android.apps.aicore.service.BIND_SERVICE	unknown	Unknown permission	Unknown permission from android reference
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.

PERMISSION	STATUS	INFO	DESCRIPTION
com.booking.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference
com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE	normal	permission defined by google	A custom permission defined by Google.
android.permission.ACCESS_ADSERVICES_ATTRIBUTION	normal	allow applications to access advertising service attribution	This enables the app to retrieve information related to advertising attribution, which can be used for targeted advertising purposes. App can gather data about how users interact with ads, such as clicks or impressions, to measure the effectiveness of advertising campaigns.
android.permission.ACCESS_ADSERVICES_AD_ID	normal	allow app to access the device's advertising ID.	This ID is a unique, user-resettable identifier provided by Google's advertising services, allowing apps to track user behavior for advertising purposes while maintaining user privacy.
android.permission.ACCESS_ADSERVICES_TOPICS	normal	allow applications to access advertising service topics	This enables the app to retrieve information related to advertising topics or interests, which can be used for targeted advertising purposes.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
com.huawei.appmarket.service.commondata.permission.GET_COMMON_DATA	unknown	Unknown permission	Unknown permission from android reference
android.permission.READ_PHONE_STATE	dangerous	read phone state and identity	Allows the application to access the phone features of the device. An application with this permission can determine the phone number and serial number of this phone, whether a call is active, the number that call is connected to and so on.
com.booking.permission.PROCESS_PUSH_MSG	unknown	Unknown permission	Unknown permission from android reference
com.booking.permission.PUSH_PROVIDER	unknown	Unknown permission	Unknown permission from android reference
com.asus.msa.SupplementaryDID.ACCESS	unknown	Unknown permission	Unknown permission from android reference
freemme.permission.msa	unknown	Unknown permission	Unknown permission from android reference

PERMISSION	STATUS	INFO	DESCRIPTION
freemme.permission.msa.SECURITY_ACCESS	unknown	Unknown permission	Unknown permission from android reference
oplus.permission.settings.LAUNCH_FOR_EXPORT	unknown	Unknown permission	Unknown permission from android reference
com.vivo.identifier.permission.OAID_STATE_DIALOG	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check Build.BOARD check possible Build.SERIAL check SIM operator check network operator name check</td></tr><tr><td>Anti Debug Code</td><td>Debug.isDebuggerConnected() check</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes10.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Anti-VM Code</td><td>Build.MANUFACTURER check</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
<tr><td>classes11.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Anti-VM Code</td><td>Build.MANUFACTURER check
Build.BOARD check
SIM operator check</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
</table>

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes12.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.PRODUCT check
SIM operator check</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
<tr><td>classes13.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.PRODUCT check
Build.HARDWARE check
Build.TAGS check
SIM operator check
network operator name check</td></tr>
<tr><td>Anti Debug Code</td><td>Debug.isDebuggerConnected() check</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
</table>

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes2.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Anti-VM Code</td><td>Build.MANUFACTURER check
Build.BOARD check
network operator name check</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
<tr><td>classes3.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.PRODUCT check
Build.HARDWARE check
Build.TAGS check
network operator name check
possible VM check</td></tr>
<tr><td>Anti Debug Code</td><td>Debug.isDebuggerConnected() check</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
</table>

FILE	DETAILS
classes4.dex	

FINDINGS	DETAILS
yara_issue	yara issue - dex file recognized by apkid but not yara module
Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check possible Build.SERIAL check SIM operator check network operator name check ro.kernel.qemu check possible VM check
Anti Debug Code	Debug.isDebuggerConnected() check
Compiler	unknown (please file detection issue!)

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes5.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.PRODUCT check
Build.HARDWARE check
Build.BOARD check
Build.TAGS check
network operator name check
subscriber ID check
emulator file check</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
<tr><td>classes6.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
<tr><td>classes7.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table>
</td></tr>
</table>

FILE	DETAILS
classes8.dex	

FINDINGS	DETAILS
yara_issue	yara issue - dex file recognized by apkid but not yara module
Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check network operator name check device ID check subscriber ID check ro.product.device check ro.kernel.qemu check emulator file check
Anti Debug Code	Debug.isDebuggerConnected() check
Compiler	unknown (please file detection issue!)

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes9.dex</td><td><table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr>
<tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr>
</table></td></tr>
<tr><td>lib/arm64-v8a/libTMXProfiling-8.0-82-jni.so</td><td><table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>anti_hook</td><td>syscalls</td></tr>
</table></td></tr>
<tr><td>lib/arm64-v8a/libba4e.so</td><td><table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Obfuscator</td><td>DexGuard 9.x</td></tr>
<tr><td>anti_hook</td><td>syscalls</td></tr>
</table></td></tr>
<tr><td>lib/arm64-v8a/libmapbox-common.so</td><td><table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>anti_hook</td><td>syscalls</td></tr>
</table></td></tr>
<tr><td>lib/arm64-v8a/libmsaoaidauth.so</td><td><table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Protector</td><td>MSA SDK</td></tr>
</table></td></tr>
</table>

FILE	DETAILS
lib/arm64-v8a/libmsaoaidsec.so	FINDINGS: Protector DETAILS: MSA SDK
lib/arm64-v8a/libtiny_magic.so	FINDINGS: anti_hook DETAILS: syscalls
lib/armeabi-v7a/libmsaoaidauth.so	FINDINGS: Protector DETAILS: MSA SDK
lib/armeabi-v7a/libmsaoaidsec.so	FINDINGS: Protector DETAILS: MSA SDK
lib/x86/libmsaoaidauth.so	FINDINGS: Protector DETAILS: MSA SDK
lib/x86/libmsaoaidsec.so	FINDINGS: Protector DETAILS: MSA SDK

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>lib/x86_64/libmsaoaidauth.so</td><td><table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Protector</td><td>MSA SDK</td></tr></table></td></tr>
<tr><td>lib/x86_64/libmsaoaidsec.so</td><td><table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Protector</td><td>MSA SDK</td></tr></table></td></tr>
</table>

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.booking.deeplink.decoder.AssistantShortcutDeeplinkActivityDecoder	Schemes: https://, Hosts: secure.booking.com, Path Prefixes: /assistant,
com.booking.deeplink.decoder.GuestMessagingDecoderDeeplinkActivity	Schemes: https://, Hosts: secure.booking.com, Path Prefixes: /inbox/partner_chat, /inbox/partner-chat,
com.booking.deeplink.decoder.TaxisDeeplinkActivityDecoder	Schemes: https://, Hosts: taxi.booking.com, Path Patterns: /..*/promotions/free-taxi/..*,
com.booking.deeplink.decoder.TaxiPostbookDeeplinkActivityDecoder	Schemes: https://, Hosts: pickup.taxi.booking.com, Path Patterns: /link/..*/..*/..*,
com.booking.deeplink.decoder.RewardsDeeplinkActivityDecoder	Schemes: https://, Hosts: secure.booking.com, Path Prefixes: /rewardshub, /rewards_and_wallet/rewards,

ACTIVITY	INTENT
com.booking.deeplink.decoder.WalletDeeplinkActivityDecoder	Schemes: https://, Hosts: secure.booking.com, Path Prefixes: /rewards_and_wallet/wallet,
com.booking.deeplink.decoder.FlightsOrderDeeplinkActivityDecoder	Schemes: https://, Hosts: flights.booking.com, Path Prefixes: /booking/order-details/,
com.booking.attractions.app.navigation.deeplink.AttractionsDeeplinkActivityDecoder	Schemes: https://, Hosts: www.booking.com, booking.com, Path Prefixes: /attractions/push/,
com.booking.cruises.deeplink.CruisesDeeplinkActivityDecoder	Schemes: https://, Hosts: www.cruises.booking.com, cruises.booking.com,
com.booking.deeplink.decoder.PaymentRedirectDeeplinkDecoderActivity	Schemes: http://, https://, Hosts: secure.booking.com, Path Prefixes: /payment_redirect.html,
com.booking.deeplink.decoder.ShareLinkDecoderActivity	Schemes: http://, https://, Hosts: *.booking.com, *.booking.cn, booking.com, booking.cn, Path Prefixes: /Share-,
com.booking.deeplink.decoder.GeniusLandingDeeplinkDecoder	Schemes: http://, https://, Hosts: www.booking.com, Path Prefixes: /genius,
com.booking.deeplink.decoder.WishlistDetailDeepLinkDecoder	Schemes: http://, https://, Hosts: www.booking.com, Path Prefixes: /mywishlist,
com.booking.deeplink.decoder.PaymentsDecoderDeeplinkActivity	Schemes: https://, Hosts: secure.booking.com, secure.booking.cn, Path Prefixes: /payments/accommodations/paylater/paynow, /payments/accommodations/paylater/updatepaymentmethod, /payments/accommodations/paytoproperty/paynow, /payments/accommodations/paytoproperty/updatepaymentmethod,

ACTIVITY	INTENT
com.booking.deeplink.decoder.PrivacyDeeplinkDecoder	Schemes: https://, Hosts: www.booking.com, Paths: /content/dsar-request.html,
com.booking.flightsdeeplinkpresentation.FlightsDeeplinkActivityDecoder	Schemes: https://, Hosts: flights.booking.com, Path Prefixes: /flights, /confirmation, /booking/webcheckin,
com.booking.deeplink.decoder.FlightsDeeplinkActivityDecoderAPI35	Schemes: https://, Hosts: flights.booking.com, Path Prefixes: /flights, /confirmation, /booking/webcheckin,
com.booking.bookingprocess.activity.BookingStageActivity	Schemes: bookingpayin://, Hosts: payin, Path Prefixes: /accommodation,
com.booking.tpi.bookprocess.marken.TPIBookProcessActivity	Schemes: tpi://, Hosts: booking, Path Prefixes: /payin,
com.booking.attractions.app.AttractionsActivity	Schemes: attractions://,
com.booking.flights.activity.FlightsActivity	Schemes: flights://, Hosts: book, Path Prefixes: /payment-status,
com.booking.flightspostbooking.FlightsPostBookingActivity	Schemes: flights://, Hosts: post-book, Path Prefixes: /payment-status,
com.booking.insurance.common.InsuranceActivity	Schemes: bookingpayin://, Hosts: payin, Path Prefixes: /insurance,
com.booking.requesttobook.deeplink.RtbDeeplinkEntryActivity	Schemes: https://, Hosts: *.booking.com, booking.com, secure.booking.com, Path Prefixes: /request_to_book/app, /request_to_book/request_details,

ACTIVITY	INTENT
com.booking.cruises.CruisesActivity	Schemes: cruises://,
com.booking.damagepayment.deeplink.DamagePaymentDeeplinkActivityDecoder	Schemes: https://, Hosts: *.booking.com, booking.com, Path Prefixes: /damage_deposit_payment,
com.booking.identity.guest.AuthGuestActivity	Schemes: https://, Hosts: account.booking.com, Path Prefixes: /applink/booking,
net.openid.appauth.RedirectUriReceiverActivity	Schemes: idp1://, Hosts: facebookCallback, amazonCallback,
com.booking.deeplinkui.scheme.BookingDeeplinkSchemeActivity	Schemes: booking://,

ACTIVITY	INTENT
com.booking.deeplinkui.decoder.DecoderDeeplinkActivity	Schemes: http://, https://, Hosts: booking.com, booking.cn, secure.booking.com, secure.booking.cn, link.sg.booking.com, s.sg.booking.com, t.spe.booking.com, www.booking.com, www.booking.cn, Paths: /deep-link, Path Prefixes: /App-, /review/, /apps, /app_link/mybooking., /app_link/mytrips, /app_link/myreservations, /app_link/mybookings, /mytrips, /myreservations, /myaccount, /mybenefits, /mybookings, /app_link/login., /mybooking., /myreferrals, /free_cancellation_addon, /uni, /f/uni, /index, /app_link/city/, /app_link/index., /app_link/searchresults., /app_link/hotel/, /hotel/, /searchresults., /landmark, /dealspage, /deals/black-friday, /deals/obon, /apartments, /region, /guest-house, /accommodation, /district, /hostels, /motels, /bed-and-breakfast, /country, /city/, /airport, /s/, /c/uefa-2024, /chinacampaign, /deals-special-offers, /best-price-guarantee, /book-now-pay-later, /free-cancellation, /get-instant-confirmation, /no-booking-fees, /secure-booking, /we-speak-your-language, /aparthotels, /homestay, /lodges, /campings, /country-houses, /love-hotel, /villas, /boats, /riad, /ryokans, /capsule-hotel, /cottages, /holiday-parks, /booking-home, /backtotravel, /back-to-travel, /book_and_unlock_landing, /geniusvip_lp, /monthly-stays, /extended-stays, /flights/index, /flights/route/to-country, /flights/destination/city, /flights/destination/to-region, /flights/destination/to-airport, /flight-, /inbox/partner_chat, /cars/region, /accessible-traveling, /alberghi, /biz, /budget, /camp, /chalet, /cheap, /design, /family, /farm-holidays, /fivestars, /flat, /fourstars, /gites, /glamping, /golf, /gostinicy, /holiday-homes, /inns, /jacuzzi, /lodging, /luxury, /onsen, /parking, /pets, /placestostay, /pool, /resorts, /romantic, /rooms, /self-catering, /ski, /spa, /threestars, /tiny-house, /gating/authkey, /partnerships, /beach-rental, /hanok, /condos, /bungalows, /lake-houses, /co_brand_card, /co_brand_card/signup, Path Patterns: /c3go,
com.booking.android.payment.payin.standalone.StandaloneActivity	Schemes: bookingpayments://, Hosts: standalone,
com.booking.identity.auth.activity.AuthActivity	Schemes: http://, https://, Hosts: account.booking.com, account.booking.cn, Path Prefixes: /applink/booking,
com.booking.payment.component.ui.screen.directintegration.klarna.KlarnaDirectIntegrationActivity	Schemes: com.booking://, Hosts: klarna,
com.booking.payment.component.core.directintegration.braintree.paypal.PayPalBraintreeHostActivity	Schemes: com.booking.braintree://,

ACTIVITY	INTENT
com.booking.payment.component.core.threedomainsecure2.braintree.Braintree3ds2HostActivity	Schemes: com.booking.3ds.braintree://,
com.booking.payment.component.core.directintegration.revolut.RevolutHostActivity	Schemes: com.booking://, Hosts: revolut,
com.stripe.android.link.LinkRedirectHandlerActivity	Schemes: link-popup://, Hosts: complete, Paths: /com.booking,
com.stripe.android.payments.StripeBrowserProxyReturnActivity	Schemes: stripesdk://, Hosts: payment_return_url, Paths: /com.booking,
com.revolut.revolutpay.ui.sandbox.SandboxConfirmationActivity	Schemes: https://, Hosts: sandbox-merchant.revolut.com/,
com.klarna.mobile.sdk.activity.KlarnaAuthenticationRedirectReceiverActivity	Schemes: @string/authentication_redirect_url_scheme://, Hosts: com.booking,
com.adyen.threeds2.internal.ui.activity.ChallengeActivity	Schemes: adyen3ds2://, Hosts: com.booking,
com.braintreepayments.api.BraintreeDeepLinkActivity	Schemes: com.booking.braintree.deeplinkhandler://,
com.stripe.android.financialconnections.lite.FinancialConnectionsSheetLiteRedirectActivity	Schemes: stripe://, Hosts: financial-connections-lite, Path Prefixes: /com.booking/auth_redirect,
com.google.android.gms.tagmanager.TagManagerPreviewActivity	Schemes: tagmanager.c.com.booking://,

NETWORK SECURITY

HIGH: **1** | WARNING: **0** | INFO: **0** | SECURE: **0**

NO	SCOPE	SEVERITY	DESCRIPTION
1	bstatic.com static.booking.cn localhost	high	Domain config is insecurely configured to permit clear text traffic to these domains in scope.

CERTIFICATE ANALYSIS

HIGH: 1 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Certificate algorithm vulnerable to hash collision	high	Application is signed with SHA1withRSA. SHA1 hash algorithm is known to have collision issues.

MANIFEST ANALYSIS

HIGH: 1 | WARNING: 81 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	Clear text traffic is Enabled For App [android:usesCleartextTraffic=true]	high	The app intends to use cleartext network traffic, such as cleartext HTTP, FTP stacks, DownloadManager, and MediaPlayer. The default value for apps that target API level 27 or lower is "true". Apps that target API level 28 or higher default to "false". The key reason for avoiding cleartext traffic is the lack of confidentiality, authenticity, and protections against tampering; a network attacker can eavesdrop on transmitted data and also modify it without being detected.

NO	ISSUE	SEVERITY	DESCRIPTION
2	App has a Network Security Configuration [android:networkSecurityConfig=@xml/network_security_config_with_localhost_enabled]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
3	TaskAffinity is set for activity (com.booking.searchresult.SearchResultsActivityJPC)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
4	Activity (com.booking.deeplink.decoder.AssistantShortcutDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Activity (com.booking.deeplink.decoder.GuestMessagingDecoderDeeplinkActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Activity (com.booking.deeplink.decoder.TaxisDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Activity (com.booking.deeplink.decoder.TaxiPostbookDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	Activity (com.booking.deeplink.decoder.RewardsDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
9	Activity (com.booking.deeplink.decoder.WalletDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
10	Activity (com.booking.deeplink.decoder.FlightsOrderDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
11	Activity (com.booking.attractions.app.navigation.deeplink.AttractionsDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
12	Activity (com.booking.cruises.deeplink.CruisesDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
13	Activity (com.booking.deeplink.decoder.PaymentRedirectDeeplinkDecoderActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
14	Activity (com.booking.deeplink.decoder.ShareLinkDecoderActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
15	Activity (com.booking.deeplink.decoder.GeniusLandingDeeplinkDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
16	Activity (com.booking.deeplink.decoder.WishlistDetailDeepLinkDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
17	Activity (com.booking.deeplink.decoder.PaymentsDecoderDeeplinkActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
18	Broadcast Receiver (com.booking.subscriptions.NotificationAppBlockStateChangedReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
19	Broadcast Receiver (com.booking.subscriptions.NotificationChannelBlockStateChangedReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
20	Activity (com.booking.login.WXEntryActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
21	Activity-Alias (com.booking.dev.wxapi.WXEntryActivity) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
22	Activity-Alias (com.booking.dev.wxapi.WXPayEntryActivity) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
23	Activity-Alias (com.booking.wxapi.WXPayEntryActivity) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
24	Activity-Alias (com.booking.wxapi.WXEntryActivity) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
25	Broadcast Receiver (com.booking.preinstall.ExternalAppBroadcastReceiver) is Protected by a permission. Permission: com.booking.permission.AFFILIATE_ID_RESPONSE protectionLevel: signature [android:exported=true]	info	A Broadcast Receiver is found to be exported, but is protected by permission.
26	Activity (com.booking.deeplink.decoder.PrivacyDeeplinkDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
27	Activity (com.booking.postbooking.confirmation.activities.BookingDetailsActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
28	Activity (com.booking.postbooking.confirmation.activities.BookingDetailsComposeActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
29	Activity (com.booking.flightsdeeplinkpresentation.FlightsDeeplinkActivityDecoder) is not Protected. An intent-filter exists.	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. The presence of intent-filter indicates that the Activity is explicitly exported.
30	Activity-Alias (com.booking.deeplink.decoder.FlightsDeeplinkActivityDecoderAPI35) is not Protected. An intent-filter exists.	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. The presence of intent-filter indicates that the Activity-Alias is explicitly exported.
31	Activity (com.booking.bookingprocess.activity.BookingStageActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
32	Activity (androidx.compose.ui.tooling.PreviewActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
33	Activity (com.booking.tpi.bookprocess.marken.TPIBookProcessActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
34	Activity (com.booking.rewardsandwalletpresentation.RewardsAndWalletActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
35	Activity (com.booking.taxispresentation.TaxisSingleFunnelActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
36	Activity (com.booking.attractions.app.AttractionsActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
37	Activity (com.booking.flights.activity.FlightsActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
38	Activity (com.booking.flightspostbooking.FlightsPostBookingActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
39	Activity (com.booking.insurance.common.InsuranceActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
40	Activity (com.booking.requesttobook.deeplink.RtbDeeplinkEntryActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
41	Broadcast Receiver (com.booking.subscriptionsservices.tracking.push.PushChannelAndGroupBlockStateChangedReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
42	Activity (com.booking.cruises.CruisesActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
43	Activity (com.booking.identity.privacy.ui.PrivacyAppActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
44	Activity (com.booking.identity.privacy.ui.PrivacySettingsActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
45	Activity (com.booking.damagepayment.deeplink.DamagePaymentDeeplinkActivityDecoder) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
46	Activity (com.booking.cobrandcreditcardpresentation.CoBrandCreditCardActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
47	Activity (com.booking.identity.guest.AuthGuestActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
48	Activity (net.openid.appauth.RedirectUriReceiverActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
49	Activity (com.booking.bugreporter.presentation.activity.BugReporterActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
50	Activity (com.booking.deeplinkui.scheme.BookingDeeplinkSchemeActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
51	Activity (com.booking.deeplinkui.decoder.DecoderDeeplinkActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
52	Activity (com.booking.android.payment.payin.standalone.StandaloneActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
53	Activity (com.booking.android.payment.payin.standalone.WebViewStandaloneActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
54	Activity (com.booking.identity.account.migration.AccountMigrationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
55	Activity (com.booking.identity.account.AccountActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
56	Activity (com.booking.identity.account.cotravellers.presentation.AccountCoTravellersActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
57	Activity (com.booking.identity.account.presentation.AccountMvvmActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
58	Activity (com.booking.identity.auth.activity.AuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
59	Activity (com.booking.identity.auth.BottomSheetAuthActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
60	Activity (com.booking.identity.privacy.ui.management.PrivacyManagementActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
61	Activity (com.booking.identity.privacy.ui.webview.PrivacyDSRWebView) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
62	Activity (com.booking.identity.privacy.ui.webview.PrivacyWebView) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
63	Activity (com.booking.payment.component.ui.screen.directintegration.klarna.KlarnaDirectIntegrationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
64	Activity (com.booking.payment.component.core.directintegration.wechat.WeChatResultActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
65	Activity (com.booking.payment.component.core.directintegration.braintree.paypal.PayPalBraintreeHostActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
66	Activity (com.booking.payment.component.core.threedomainsecure2.braintree.Braintree3ds2HostActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
67	Activity (com.booking.payment.component.core.directintegration.revolut.RevolutHostActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
68	Activity (com.stripe.android.link.LinkRedirectHandlerActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
69	Activity (com.stripe.android.payments.StripeBrowserProxyReturnActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
70	Activity (com.revolut.revolutpay.ui.sandbox.SandboxConfirmationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
71	Activity (com.klarna.mobile.sdk.activity.KlarnaAuthenticationRedirectReceiverActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
72	Activity (com.adyen.threeds2.internal.ui.activity.ChallengeActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
73	Activity (com.braintreepayments.api.BraintreeDeepLinkActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
74	Activity (com.stripe.android.financialconnections.lite.FinancialConnectionsSheetLiteRedirectActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
75	Activity (com.google.android.gms.tagmanager.TagManagerPreviewActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
76	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
77	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
78	Service (com.google.assistant.appactions.widgets.pinappwidget.PinAppWidgetService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
79	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
80	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
81	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
82	Activity (com.alipay.sdk.app.PayResultActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
83	Activity (com.alipay.sdk.app.AlipayResultActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
84	Broadcast Receiver (com.huawei.hms.support.api.push.PushMsgReceiver) is Protected by a permission. Permission: com.booking.permission.PROCESS_PUSH_MSG protectionLevel: signature [android:exported=true]	info	A Broadcast Receiver is found to be exported, but is protected by permission.
85	Broadcast Receiver (com.huawei.hms.support.api.push.PushReceiver) is Protected by a permission. Permission: com.booking.permission.PROCESS_PUSH_MSG protectionLevel: signature [android:exported=true]	info	A Broadcast Receiver is found to be exported, but is protected by permission.
86	Service (com.huawei.hms.support.api.push.service.HmsMsgService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
87	Content Provider (com.huawei.hms.support.api.push.PushProvider) is Protected by a permission. Permission: com.booking.permission.PUSH_PROVIDER protectionLevel: signature [android:exported=true]	info	A Content Provider is found to be exported, but is protected by permission.

CODE ANALYSIS

HIGH: **4** | WARNING: **10** | INFO: **2** | SECURE: **2** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	com/airbnb/lottie/network/NetworkCache.java com/baidu/b/d/b.java com/baidu/lbsapi/auth/q.java com/baidu/mapapi/map/BitmapDescriptor.java com/baidu/mshield/b/f/e.java com/baidu/platform/comapi/util/MD5.java com/booking/tpiservices/utils/pageviewid/DefaultPropertyViewGenerator.java com/heytap/openid/sdk/m_a.java
				com/alipay/android/phone/mrpc/core/b.java com/apollographql/apollo3/exception/ApolloExceptionHandlerKt.java com/booking/core/exps3/DbUtils.java com/booking/geniusvipservices/common/squeaks/GeniusVipProductSqueak.java com/booking/postbooking/confirmation/activities/BookingConfirmationComposeActivity.java com/booking/saba/marken/components/bui/components/forms/InputSelectComponent.java com/booking/wishlist/ui/components/WishlistButtonKt.java com/bumptech/glide/Glide.java com/bumptech/glide/disklrucache/DiskLruCache.java com/bumptech/glide/gifdecoder/StandardGifDecoder.java com/bumptech/glide/load/data/HttpUrlFetcher.java com/bumptech/glide/load/data/mediastore/ThumbFetcher.java com/bumptech/glide/load/engine/DecodeJob.java com/bumptech/glide/load/engine/DecodePath.java com/bumptech/glide/load/engine/Engine.java com/bumptech/glide/load/engine/SourceGenerator.java com/bumptech/glide/load/engine/bitmap_recycle/LruArrayPool.java com/bumptech/glide/load/engine/bitmap_recycle/LruBitmapPool.java com/bumptech/glide/load/engine/cache/DiskLruCacheWrapper.java com/bumptech/glide/load/engine/cache/MemorySizeCalculator.java com/bumptech/glide/load/model/ResourceUriLoader.java com/bumptech/glide/load/resource/DefaultOnHeaderDecodedListener.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/bumptech/glide/load/resource/bitmap/BitmapEncoder.java com/bumptech/glide/load/resource/bitmap/BitmapImageDecoderResourceDecoder.java com/bumptech/glide/load/resource/bitmap/Downsampler.java com/bumptech/glide/load/resource/bitmap/DrawableToBitmapConverter.java com/bumptech/glide/load/resource/bitmap/TransformationUtils.java com/bumptech/glide/load/resource/gif/ByteBufferGifDecoder.java com/bumptech/glide/manager/RequestManagerRetriever.java com/bumptech/glide/request/SingleRequest.java com/bumptech/glide/util/pool/FactoryPools.java com/flexdb/utils/Debug.java com/huawei/hms/aaid/init/AutoInitHelper.java com/huawei/hms/aaid/utils/PushPreferences$$ExternalSyntheticOutline0.java com/huawei/hms/aaid/utils/PushPreferences.java com/huawei/hms/adapter/BaseAdapter$$ExternalSyntheticOutline0.java com/huawei/hms/android/SystemUtils.java com/huawei/hms/api/FailedBinderCallBack.java com/huawei/hms/availableupdate/a.java com/huawei/hms/availableupdate/c.java com/huawei/hms/availableupdate/q.java com/huawei/hms/common/internal/ConnectionErrorMessages.java com/huawei/hms/common/internal/DialogRedirect.java com/huawei/hms/common/util/Base64Utils.java com/huawei/hms/framework/common/Logger.java com/huawei/hms/opendevice/g.java com/huawei/hms/opendevice/h.java com/huawei/hms/opendevice/p.java com/huawei/hms/opendevice/r.java com/huawei/hms/opendevice/s.java com/huawei/hms/push/c.java com/huawei/hms/push/g.java com/huawei/hms/push/h.java com/huawei/hms/push/k.java com/huawei/hms/push/q.java com/huawei/hms/push/r.java com/huawei/hms/push/utils/DateUtil.java com/huawei/hms/push/utils/JsonUtil.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/huawei/hms/stats/c.java com/huawei/hms/support/api/push/PushProvider.java com/huawei/hms/support/common/ActivityMgr.java com/huawei/hms/support/log/HMSDebugger.java com/huawei/hms/ui/AbstractDialog.java com/huawei/hms/utils/IOUtils.java com/huawei/hms/utils/SHA256.java com/huawei/hms/utils/UIUtil.java com/jakewharton/disklrucache/DiskLruCache.java com/mapbox/common/MapboxCommonLogger.java com/mapbox/common/MapboxMapsAndroidLogger.java com/mapbox/common/TelemetrySystemUtils.java com/onetrust/otpublishers/headless/Internal/Log/OTLogger.java com/tencent/mm/opensdk/modelbiz/ChooseCardFromWXCardPackage.java com/tencent/mm/opensdk/modelbiz/SubscribeMessage.java com/tencent/mm/opensdk/modelbiz/SubscribeMiniProgramMsg.java com/tencent/mm/opensdk/modelbiz/WXChannelBaseJumpInfo.java com/tencent/mm/opensdk/modelbiz/WXChannelJumpMiniProgramInfo.java com/tencent/mm/opensdk/modelbiz/WXChannelJumpUrlInfo.java com/tencent/mm/opensdk/modelbiz/WXChannelOpenFeed.java com/tencent/mm/opensdk/modelbiz/WXChannelOpenLive.java com/tencent/mm/opensdk/modelbiz/WXChannelOpenProfile.java com/tencent/mm/opensdk/modelbiz/WXInvoiceAuthInsert.java com/tencent/mm/opensdk/modelbiz/WXLaunchMiniProgram.java com/tencent/mm/opensdk/modelbiz/WXLaunchMiniProgramWithToken.java com/tencent/mm/opensdk/modelbiz/WXNontaxPay.java com/tencent/mm/opensdk/modelbiz/WXOpenBusinessView.java com/tencent/mm/opensdk/modelbiz/WXPayInsurance.java com/tencent/mm/opensdk/modelbiz/WXPreloadMiniProgram.java com/tencent/mm/opensdk/modelmsg/LaunchFromWX.java com/tencent/mm/opensdk/modelmsg/SendAuth.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/tencent/mm/opensdk/modelmsg/WXDesignerSharedObject.java com/tencent/mm/opensdk/modelmsg/WXDynamicVideoMiniProgramObject.java com/tencent/mm/opensdk/modelmsg/WXEmojiSharedObject.java com/tencent/mm/opensdk/modelmsg/WXEnterpriseCardObject.java com/tencent/mm/opensdk/modelmsg/WXMediaMessage.java com/tencent/mm/opensdk/modelmsg/WXMiniProgramObject.java com/tencent/mm/opensdk/modelmsg/WXMusicObject.java com/tencent/mm/opensdk/modelmsg/WXStateJumpChannelProfileInfo.java com/tencent/mm/opensdk/modelmsg/WXStateJumpMiniProgramInfo.java com/tencent/mm/opensdk/modelmsg/WXStateJumpUrlInfo.java com/tencent/mm/opensdk/modelmsg/WXStateSceneDataObject.java com/tencent/mm/opensdk/modelmsg/WXTextObject.java com/tencent/mm/opensdk/modelmsg/WXVideoObject.java com/tencent/mm/opensdk/modelpay/PayReq.java com/tencent/mm/opensdk/openapi/WXApiImplComm.java com/tencent/mm/opensdk/utils/Log.java com/tencent/mm/opensdk/utils/b.java com/vivo/identifier/IdentifierIdClient.java mijtkD/ESLzFk.java net/openid/appauth/internal/Logger.java org/conscrypt/ct/CTVerifier.java
				org/greenrobot/eventbus/Logger.java org/joda/time/tz/DateTimeZoneBuilder.java com/booking/bookingprocess/payment/steps/PaymentStepParams.java com/booking/cars/beefclient/managebooking/nativepostbook/BeefShell.java com/booking/common/data/price/PriceDisplayConfigData.java com/booking/core/exp/storage/CopyExperimentsStorageKt.java com/booking/guestmessagingservices/chat/data/DomainChatScreenSelfServiceCompleteActionInput.java com/booking/guestmessagingservices/inbox/data/DMLInboxListRepo.java com/booking/guestmessagingservices/inbox/data/FlexDBUnifiedInboxCache.java com/booking/identity/account/api/SubmitEmailChallengeRe

NO	ISSUE	SEVERITY	STANDARDS	FILES
				quest.java com/booking/identity/account/api/model/totp/authenticator/TotpGenerateSecretResponse.java com/booking/identity/account/personaldetails/email/AccountEnterPasswordFacet.java com/booking/identity/api/AuthResponse.java com/booking/identity/api/DeviceContext.java com/booking/identity/auth/data/model/passkey/CreatePasskeyRequest.java com/booking/identity/auth/facet/email/AuthSignInPasswordFacet.java com/booking/identity/auth/reactor/AuthReactor.java com/booking/identity/auth/reactor/AuthState.java com/booking/identity/session/internal/Token.java com/booking/insurance/common/DetailsPageParams.java com/booking/insurancecomponents/rci/common/OpenInsuranceDetails.java com/booking/insurancepostbookdomain/model/PostbookSalesStatus.java com/booking/marken/reactors/persist/FlexDBStorage.java com/booking/marken/store/LazyRegisterReactorAction.java com/booking/marken/store/ReferenceReactorAction.java com/booking/marken/store/RestoreValue.java com/booking/multiproduct/session/PersistentSessionStore.java com/booking/mybookingslist/domain/mapping/legacy/PublicTransportReservationMapperKt.java com/booking/mybookingslist/service/model/LegacyAccommodationReservation.java com/booking/notification/handlers/NotificationOptInHandler.java com/booking/notification/push/PushDuplicationDetector.java com/booking/notification/settings/NotificationPreferences.java com/booking/notification/track/LastClickedNotificationStorage.java com/booking/partnershipscomponents/rewards/pb/PbLoyaltyBlockViewModel.java com/booking/partnershipsservices/data/net/loyaltyfields/reservation/UpdateLoyaltyFieldsRequest.java com/booking/payment/PaymentSqueaks.java com/booking/payment/component/core/directintegration/googlepay/GooglePayRequest.java com/booking/payment/component/core/network/data/ConfigureUiResponse.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/booking/payment/component/core/session/data/Configuration.java com/booking/payment/component/core/session/data/GooglePayAttribute.java
3	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/booking/payment/component/core/threedomainsecure2/stripe/Stripe3ds2ComponentDetails.java com/booking/postbooking/confirmation/tpi/TpiOtherServicesUiState.java com/booking/postbooking/marken/redesign/propertyinfo/HotelFacilitiesFragment.java com/booking/postbooking/marken/redesign/propertyinfo/PoliciesAndFacilitiesActivity.java com/booking/saba/content/ExternalAction.java com/booking/saba/error/DebugInfo.java com/booking/saba/sabaview/SabaContentSource.java com/booking/saba/sabaview/mainlayout/SabaEnvironment.java com/booking/saba/spec/abu/pricing/components/PriceBreakdownBexBadgeContract.java com/booking/saba/spec/abu/pricing/components/PriceBreakdownPricingServerTranslationContract.java com/booking/saba/spec/abu/search/types/SearchQuerySorterParamContract.java com/booking/settings/services/Setting.java com/booking/subscriptionsservices/data/models/Copy.java com/booking/taxipostbookservices/domain/model/ZendeskCredentialsDto.java com/booking/taxiservices/flow/FlowDataWithKey.java com/booking/taxispresentation/navigation/LaunchpadArgs.java com/booking/taxispresentation/ui/flightfinder/flightselection/filters/domain/FilterOptionID.java com/booking/thirdpartyinventory/TPIBookResponse.java com/booking/transactionalpolicies/compose/NoCreditCardNeedView$Props.java com/booking/transactionalpolicies/compose/PolicyBannerItemView$Props.java com/booking/transactionalpolicies/data/BookingCondition.java com/booking/transactionalpolicies/data/NoCCData.java com/booking/transactionalpolicies/data/NoCreditCardData.java com/booking/transactionalpolicies/data/Parameter.java com/booking/transactionalpolicies/data/PolicyDisplayData.java com/booking/transactionalpolicies/data/TransactionalPolicy

NO	ISSUE	SEVERITY	STANDARDS	FILES
				Data.java com/booking/tripcomponents/ui/jpc/connectormodal/model/ConnectorModal.java com/booking/tripcomponents/ui/jpc/timeline/model/TimelineItem.java com/booking/tripcomponents/ui/jpc/viewmodel/MyTripsUiEvent.java com/braintreepayments/api/AuthenticationInsight.java com/braintreepayments/api/BaseCard.java com/braintreepayments/api/BinData.java com/braintreepayments/api/BraintreeError.java com/braintreepayments/api/Card.java com/braintreepayments/api/CardNonce.java com/braintreepayments/api/ErrorWithResponse.java com/braintreepayments/api/PayPalAccountNonce.java com/braintreepayments/api/PayPalCreditFinancing.java com/braintreepayments/api/PayPalCreditFinancingAmount.java com/braintreepayments/api/PayPalLineItem.java com/braintreepayments/api/PayPalPhoneNumber.java com/braintreepayments/api/PayPalRequest.java com/braintreepayments/api/PaymentMethod.java com/braintreepayments/api/ThreeDSecureInfo.java com/braintreepayments/api/ThreeDSecureLookup.java com/braintreepayments/api/ThreeDSecurePostalAddress.java com/braintreepayments/api/ThreeDSecureResult.java com/braintreepayments/api/VenmoAccountNonce.java com/braintreepayments/api/VenmoLineItem.java com/bumptech/glide/load/engine/DataCacheKey.java com/bumptech/glide/load/engine/EngineResource.java com/bumptech/glide/load/engine/ResourceCacheKey.java com/huawei/hms/framework/common/hianalytics/HianalyticsBaseData.java com/huawei/hms/push/constant/RemoteMessageConst.java com/huawei/hms/support/hianalytics/HiAnalyticsConstant.java com/klarna/mobile/sdk/core/ui/dialog/DialogAbstraction.java com/lexisnexisrisk/threatmetrix/TMXConfigurationKeys.java com/mapbox/common/geofencing/GeofencingPropertiesKeys.java com/onetrust/otpublishers/headless/Internal/a.java com/onetrust/otpublishers/headless/Public/Keys/OTUXParamsKeys.java com/stripe/android/model/AttachConsumerToLinkAccountS

NO	ISSUE	SEVERITY	STANDARDS	FILES
				ession.java com/stripe/android/model/ConfirmStripeIntentParams.java com/stripe/android/model/FinancialConnectionsSession.jav a com/stripe/android/paymentsheet/PaymentSheet$Custome rAccessType.java com/stripe/android/stripe3ds2/transaction/AcsData.java com/tencent/mm/opensdk/constants/ConstantsAPI.java com/vivo/identifier/IdentifierIdClient.java io/embrace/android/embracesdk/internal/payload/UserInfo. java org/conscrypt/OpenSSLECKeyFactory.java
4	[The App uses an insecure Random Number Generator.](#)	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	org/conscrypt/OpenSSLRSAKeyFactory.java atd/aw/ChallengeResultCancelled.java zendesk/conversationkit/android/model/ActivityEvent.java com/amazonaws/waf/mobilesdk/d/SDKError.java com/appsflyer/internal/AFa1uSDK.java com/appsflyer/internal/AFc1fSDK.java com/baidu/b/c/b/b.java com/baidu/xclient/gdid/j/d.java com/booking/commons/android/IntentKtKt.java com/booking/notification/SystemNotificationClickServiceKt.j ava com/booking/postbooking/notifications/RoomUpgradeNotifi cationScheduler.java com/booking/ugc/presentation/reviewform/marken/Review FormPresentationReactor.java com/booking/ugc/ui/AvatarUtils.java com/booking/upcomingNotification/UpcomingPersistentNot ification.java com/huawei/hms/common/internal/TransactionIdCreater.ja va io/opentelemetry/sdk/internal/AndroidFriendlyRandomHold er.java io/opentelemetry/sdk/internal/RandomSupplier.java io/opentelemetry/sdk/trace/RandomIdGenerator.java
				com/booking/commons/globals/BuildData.java com/booking/helpcenter/net/BFFRequestKt.java com/booking/incentivesservices/api/requestData/ValidateCo uponCodeArgs.java com/booking/qna/services/reactors/MatchMakingExpressed NeedsReactor.java com/booking/qna/services/reactors/MatchMakingTrackingR eactor.java com/booking/qna/services/reactors/QnAInstantAnswerReact or$$ExternalSyntheticLambda1.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/booking/qna/services/reactors/QnAInstantAnswerReactor$$ExternalSyntheticLambda3.java com/booking/qna/services/reactors/QnAMatchingQuestionsReactor$$ExternalSyntheticLambda0.java com/booking/qna/services/reactors/QnAQuestionsListReactor$$ExternalSyntheticLambda2.java com/booking/qna/services/reactors/QnAQuestionsListReactor$$ExternalSyntheticLambda3.java com/booking/qnacomponents/exps/c2bqna/QnAEditNeedsActivity.java com/booking/search/SearchModule.java com/booking/service/UpdateAppServiceRequestBuilder.java com/booking/settings/presentation/navigation/SettingsNavGraphKt.java com/booking/startup/appinitialization/initializables/GlobalsInitializable.java com/booking/startup/appinitialization/initializables/OnCreateInitializable.java com/booking/taxipostbookservices/data/dto/SessionEventRequest.java com/booking/taxipostbookservices/domain/model/SessionEventData.java com/booking/web/interceptors/EmailFeedbackWebViewUrlInterceptor.java com/cardinalcommerce/a/DSASigner.java com/cardinalcommerce/a/GM$Mappings.java com/cardinalcommerce/a/IESCipher$IESwithDESedeCBC.java com/cardinalcommerce/a/KeyAgreementSpi$MQVwithSHA1KDF.java com/cardinalcommerce/dependencies/internal/nimbusds/jose/jwk/Curve.java com/hihonor/ads/identifier/BuildConfig.java com/huawei/hms/base/device/BuildConfig.java com/huawei/hms/common/PackageConstants.java com/huawei/hms/framework/common/BuildConfig.java com/huawei/hms/framework/common/PackageManagerCompat.java com/huawei/hms/framework/network/frameworkcompat/BuildConfig.java com/huawei/hms/framework/network/grs/g/l/a.java com/huawei/hms/hatool/e1.java com/huawei/hms/hatool/z.java com/huawei/hms/support/hianalytics/a.java com/nimbusds/jose/jwk/Curve.java lib/android/paypal/com/magnessdk/h.java
5	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	

NO	ISSUE	SEVERITY	STANDARDS	FILES
				org/conscrypt/CertificatePriorityComparator.java org/conscrypt/ChainStrengthAnalyzer.java org/conscrypt/EvpMdRef.java
				org/conscrypt/OAEPParameters.java org/conscrypt/OidData.java org/conscrypt/OpenSSLCipherRSA.java org/conscrypt/OpenSSLECGroupContext.java org/conscrypt/OpenSSLProvider.java org/conscrypt/OpenSSLSignature.java org/conscrypt/TrustManagerImpl.java
6	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	org/conscrypt/ct/CTConstants.java com/alipay/sdk/m/l0/a.java com/baidu/lbsapi/auth/a.java com/booking/identity/storage/IdentityEncryptor.java com/huawei/agconnect/config/a/i.java com/huawei/secure/android/common/encrypt/aes/AesCbc.java com/nimbusds/jose/crypto/impl/AESCBC.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
7	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	com/booking/identity/data/source/retrofit/RetrofitApiProvider.java com/booking/identity/profile/services/di/ProfileServicesModule_ProvideRetrofitFactory.java com/booking/identity/reactor/IdentityApiReactor.java com/booking/mybookingslist/service/MyTripsUserServiceKt$$ExternalSyntheticLambda0.java com/booking/network/RetrofitFactory.java com/booking/payment/component/core/network/RetrofitClient.java com/booking/publictransportservices/di/PublicTransportModule_ProvideRagRetrofitFactory.java com/booking/publictransportservices/di/PublicTransportModule_ProvideRetrofitFactory.java com/booking/taxiservices/di/application/network/RidesAppsGatewayNetworkModule_ProvideRagTaxiAppRetrofitFactory.java com/booking/taxiservices/di/application/network/RidesAppsGatewayNetworkModule_ProvideRetrofitFactory.java com/booking/taxiservices/di/services/network/NetworkModule_ProvideRetrofitFactory.java com/booking/taxispresentation/di/modules/NetworkModule_ProvideRetrofitFactory.java com/booking/ugc/reviewform/photoupload/di/UGCPhotoUploadNetworkConfigModule_ProvideUploadRetrofitFactory.java com/braintreepayments/api/TLSSocketFactory.java com/huawei/secure/android/common/ssl/SecureX509TrustManager.java lib/android/paypal/com/magnessdk/network/base/f.java org/conscrypt/Conscrypt.java org/conscrypt/DefaultSSLContextImpl.java org/conscrypt/SSLParametersImpl.java zendesk/analyticskit/android/internal/di/AnalyticsKitNetworkModule_ProvidesRetrofitFactory.java zendesk/android/internal/network/NetworkModule_RetrofitFactory.java zendesk/conversationkit/android/internal/rest/RestClientFactory.java zendesk/guidekit/android/internal/di/module/NetworkModule_RetrofitFactory.java zendesk/messaging/android/internal/rest/NetworkModule_RetrofitFactory.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/alipay/sdk/m/b0/c.java
8	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/baidu/mapsdkplatform/comapi/util/d.java com/baidu/mshield/x0/c/b.java com/baidu/platform/comapi/util/a/b.java com/booking/identity/privacy/dma/DMADataExportViewModel$downloadData$1.java com/booking/privacy/presentation/deeplink/PrivacyDMAExportHelper$downloadDMA$2.java com/fingerprintjs/android/fpjs_pro_internal/C0066a1.java lib/android/paypal/com/magnessdk/h.java lib/android/paypal/com/magnessdk/i.java zendesk/conversationkit/android/internal/attachments/AttachmentDownloader.java zendesk/conversationkit/android/internal/attachments/AttachmentsDownloadReceiver.java
9	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	com/booking/identity/auth/composable/authenticator/setup/AuthenticatorSetupStep2Kt.java com/booking/payment/component/ui/screen/qr/QrMethodPollingActivity.java com/booking/privacy/presentation/deeplink/PrivacyDMAExportHelper$exportDMA$1.java com/booking/saba/marken/components/core/actions/CopyToClipboardFactory.java zendesk/messaging/android/internal/conversationscreen/ConversationFragment.java
10	Insecure WebView Implementation. Execution of user controlled code in WebView is a critical Security Hole.	warning	CWE: CWE-749: Exposed Dangerous Method or Function OWASP Top 10: M1: Improper Platform Usage OWASP MASVS: MSTG-PLATFORM-7	com/booking/identity/privacy/ui/webview/PrivacyWebViewComposeKt.java com/booking/marketplacewebviewcomponents/webcontainer/MarketplaceWebView.java com/booking/survey/gizmo/GizmoWebViewActivity.java zendesk/ui/android/conversation/conversationextension/ConversationExtensionView.java
11	This App may request root (Super User) privileges.	warning	CWE: CWE-250: Execution with Unnecessary Privileges OWASP MASVS: MSTG-RESILIENCE-1	lib/android/paypal/com/magnessdk/c$k.java
12	The file or SharedPreference is World Readable. Any App can read from the file	high	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/booking/sharing/AppAdapter.java com/booking/sharing/MinimalistSharePresenter.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
13	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	com/alipay/sdk/m/a/a.java com/alipay/sdk/m/z/a.java com/baidu/b/d/c.java com/baidu/lbsapi/auth/d.java com/baidu/mapsdkplatform/comapi/util/a.java com/baidu/sec/privacy/f/d.java com/heytap/openid/sdk/m_a.java com/huawei/agconnect/config/a/g.java com/huawei/hms/hatool/e.java com/huawei/secure/android/common/encrypt/hash/PBKDF2.java
14	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	zendesk/messaging/android/internal/conversationscreen/ConversationScreenCoordinator.java
15	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/booking/core/exps3/DbUtils.java
16	Insecure Implementation of SSL. Trusting all the certificates or accepting self signed certificates is a critical Security Hole. This application is vulnerable to MITM attacks	high	CWE: CWE-295: Improper Certificate Validation OWASP Top 10: M3: Insecure Communication OWASP MASVS: MSTG-NETWORK-3	com/alipay/android/phone/mrpc/core/b.java org/conscrypt/Conscrypt.java
17	The file or SharedPreference is World Writable. Any App can write to the file	high	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	atd/al/AuthenticationRequestParameters.java
18	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	com/cardinalcommerce/a/setProgressTintList.java lib/android/paypal/com/magnessdk/h.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strlcpy_chk', '__strlcat_chk', '__vsnprintf_chk', '__strchr_chk', '__snprintf_chk', '__sprintf_chk', '__strrchr_chk', '__read_chk', '__strcat_chk', '__strcpy_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86_64/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86_64/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	x86_64/libTMXProfiling-8.0-82-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86_64/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	x86_64/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	x86_64/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	x86_64/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	x86_64/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__strchr_chk', '__memcpy_chk', '__memset_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	x86_64/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	x86_64/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	x86_64/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strlcpy_chk', '__strlcat_chk', '__vsnprintf_chk', '__strchr_chk', '__snprintf_chk', '__sprintf_chk', '__strrchr_chk', '__read_chk', '__strcat_chk', '__strcpy_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	x86_64/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	x86_64/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	x86_64/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	armeabi-v7a/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	armeabi-v7a/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	armeabi-v7a/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	armeabi-v7a/libTMXProfiling-8.0-82-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	armeabi-v7a/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	armeabi-v7a/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	armeabi-v7a/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	armeabi-v7a/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
26	armeabi-v7a/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	armeabi-v7a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
28	armeabi-v7a/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	armeabi-v7a/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
30	armeabi-v7a/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	armeabi-v7a/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
32	armeabi-v7a/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	arm64-v8a/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strrchr_chk', '__snprintf_chk', '__strcpy_chk', '__sprintf_chk', '__vsnprintf_chk', '__strlcpy_chk', '__strcat_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
34	arm64-v8a/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	arm64-v8a/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
36	arm64-v8a/libTMXProfiling-8.0-82-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	arm64-v8a/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
38	arm64-v8a/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	arm64-v8a/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
40	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	arm64-v8a/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
42	arm64-v8a/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strchr_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
44	arm64-v8a/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	arm64-v8a/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strrchr_chk', '__snprintf_chk', '__strcpy_chk', '__sprintf_chk', '__vsnprintf_chk', '__strlcpy_chk', '__strcat_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
46	arm64-v8a/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	arm64-v8a/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
48	arm64-v8a/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	x86/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
50	x86/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	x86/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
52	x86/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
53	x86/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
54	x86/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
55	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
56	x86/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
57	x86/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
58	x86/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
59	x86/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
60	x86/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
61	x86/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
62	x86/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
63	x86/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
64	x86_64/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strlcpy_chk', '__strlcat_chk', '__vsnprintf_chk', '__strchr_chk', '__snprintf_chk', '__sprintf_chk', '__strrchr_chk', '__read_chk', '__strcat_chk', '__strcpy_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
65	x86_64/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
66	x86_64/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
67	x86_64/libTMXProfiling-8.0-82-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
68	x86_64/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
69	x86_64/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
70	x86_64/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
71	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
72	x86_64/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
73	x86_64/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__strchr_chk', '__memcpy_chk', '__memset_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
74	x86_64/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
75	x86_64/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
76	x86_64/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strlcpy_chk', '__strlcat_chk', '__vsnprintf_chk', '__strchr_chk', '__snprintf_chk', '__sprintf_chk', '__strrchr_chk', '__read_chk', '__strcat_chk', '__strcpy_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
77	x86_64/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
78	x86_64/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
79	x86_64/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
80	armeabi-v7a/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
81	armeabi-v7a/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
82	armeabi-v7a/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
83	armeabi-v7a/libTMXProfiling-8.0-82-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strncpy_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
84	armeabi-v7a/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
85	armeabi-v7a/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
86	armeabi-v7a/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
87	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
88	armeabi-v7a/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
89	armeabi-v7a/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
90	armeabi-v7a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
91	armeabi-v7a/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
92	armeabi-v7a/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
93	armeabi-v7a/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
94	armeabi-v7a/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
95	armeabi-v7a/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
96	arm64-v8a/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strrchr_chk', '__snprintf_chk', '__strcpy_chk', '__sprintf_chk', '__vsnprintf_chk', '__strlcpy_chk', '__strcat_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
97	arm64-v8a/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
98	arm64-v8a/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
99	arm64-v8a/libTMXProfiling-8.0-82-jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__strncpy_chk', '__vsnprintf_chk', '__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
100	arm64-v8a/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
101	arm64-v8a/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
102	arm64-v8a/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
103	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
104	arm64-v8a/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
105	arm64-v8a/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strchr_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
106	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__read_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
107	arm64-v8a/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
108	arm64-v8a/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__strrchr_chk', '__snprintf_chk', '__strcpy_chk', '__sprintf_chk', '__vsnprintf_chk', '__strlcpy_chk', '__strcat_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
109	arm64-v8a/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
110	arm64-v8a/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
111	arm64-v8a/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
112	x86/libmsaoaidauth.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
113	x86/libtiny_magic.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
114	x86/libBaiduMapSDK_map_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__vsnprintf_chk', '__memcpy_chk', '__strcpy_chk', '__memset_chk', '__FD_ISSET_chk', '__FD_SET_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
115	x86/libbb7cbb.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
116	x86/libandroid-tests-support-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
117	x86/libembrace-native.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strchr_chk', '__vsprintf_chk', '__memcpy_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
118	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
119	x86/libBaiduMapSDK_base_v7_6_3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strcat_chk', '__strchr_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
120	x86/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
121	x86/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
122	x86/libba4e.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
123	x86/libmsaoaidsec.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
124	x86/libmapbox-maps.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memmove_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
125	x86/libleveldb_wrapper.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__vsprintf_chk', '__vsnprintf_chk', '__read_chk', '__pread_chk', '__write_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
126	x86/libmapbox-common.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__memmove_chk', '__strlen_chk', '__vsnprintf_chk', '__read_chk', '__strchr_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	atd/an/getSDKEphemeralPublicKey.java atd/aw/BuildConfig.java atd/w/protocolError.java com/alipay/sdk/m/z/b.java com/baidu/b/e/a.java com/baidu/mapapi/map/BitmapDescriptorFactory.java com/baidu/mshield/b/f/e.java com/baidu/platform/comapi/util/MD5.java com/booking/core/util/FileUtils.java com/booking/hotelinfo/details/HotelBlockProvider.java com/booking/preinstall/PreinstalledAffiliateIdProvider.java com/bumptech/glide/disklrucache/DiskLruCache.java com/bumptech/glide/disklrucache/StrictLineReader.java com/bumptech/glide/load/model/FileLoader.java com/bumptech/glide/load/resource/bitmap/ImageReader.java com/cardinalcommerce/a/setAutoSizeTextTypeUniformWithPresetSizes.java com/flexdb/storage/leveldb/LevelDBStorage.java com/huawei/hms/hatool/r0.java com/huawei/hms/opendevice/s.java com/huawei/hms/utils/SHA256.java com/huawei/updatesdk/a/a/d/d.java com/jakewharton/disklrucache/DiskLruCache.java com/jakewharton/disklrucache/StrictLineReader.java com/riskified/android_sdk/RxBeacon.java okio/Okio.java org/conscrypt/DefaultSSLContextImpl.java org/conscrypt/FileClientSessionCache.java org/conscrypt/KeyManagerFactoryImpl.java org/joda/time/tz/ZoneInfoProvider.java
00191	Get messages in the SMS inbox	sms	com/alipay/sdk/m/i0/f.java com/alipay/sdk/m/p0/c.java com/huawei/updatesdk/b/e/d.java zendesk/messaging/android/internal/conversationscreen/ConversationScreenViewModel$dispatchAction$15.java
			com/alipay/sdk/m/i0/f.java com/booking/attractions/entrypoint/intent/DeviceAppSettingsIntentKt.java com/booking/helpcenter/ui/HelpCenterActivity.java com/booking/hotelinfo/util/HotelIntentHelper.java

RULE ID	BEHAVIOUR	LABEL	FILES
			com/booking/identity/account/cotravellers/presentation/list/CoTravellerListContentKt.java com/booking/identity/auth/composable/AuthClickableTermComposeKt.java com/booking/identity/auth/facet/AuthAccountDisabledFacet$Reactor$$ExternalSyntheticLambda0.java com/booking/identity/auth/facet/AuthConfirmAgeFacet$Reactor$$ExternalSyntheticLambda1.java com/booking/identity/auth/facet/email/AuthSignin2faFacetKt$$ExternalSyntheticLambda12.java com/booking/identity/auth/facet/facebook/AccountPortalWeb.java com/booking/identity/auth/facet/landing/AuthLandingFacet$Reactor$$ExternalSyntheticLambda3.java com/booking/identity/auth/facet/legal/CCPAConsentViewFacet.java com/booking/incentivescomponents/IncentivesDeeplinkLauncher.java com/booking/insurancecomponents/rci/common/InsuranceIntentHelper.java com/booking/insuranceflightscomponents/addon/InsuranceConfirmationAddOn.java com/booking/insurancepostbookcomponents/delegate/PostbookSalesFunnelAnchorActivityDelegate.java com/booking/manager/UserProfileReactor$$ExternalSyntheticLambda3.java com/booking/marketing/MainAppMarketingDelegate.java com/booking/marketplacewebviewcomponents/webcontainer/MarketplaceWebView.java com/booking/notification/ActionReceiver.java com/booking/notification/NotificationDeeplinkResolverKt.java com/booking/partnershipscomponents/rewards/common/rewardsummary/RewardSummaryFacet.java com/booking/partnershipscomponents/rewards/common/rewardsummary/RewardSummaryInfoFacet.java com/booking/partnershipscomponents/rewards/common/rewardsummary/RewardSummaryKt.java com/booking/payment/component/core/directintegration/revolut/RevolutHostActivity.java com/booking/payment/component/ui/embedded/intention/screen/OpenWebScreenIntention.java com/booking/payment/component/ui/screen/upi/UpiPaymentPollingActivity.java com/booking/payment/component/ui/screen/web/deeplink/UniversalDeeplinksWebViewUrlInterceptor.java com/booking/pdf/DefaultPDFLauncher.java com/booking/postbooking/changecancel/RoomUpgrader.java com/booking/postbooking/confirmation/activities/BookingDetailsActivity.java com/booking/postbooking/confirmation/activities/PostBookingIntentHelperKt.java com/booking/postbooking/confirmation/components/payments/PaymentInfoReactor$$ExternalSyntheticLambda0.java com/booking/postbooking/confirmation/components/whatsnext/WhatsNextActionHandler.java com/booking/postbooking/confirmation/locationdialog/LocationShareDialog.java com/booking/postbooking/modifybooking/ModifyBookingFragment.java com/booking/postbooking/notifications/InAppRoomUpgradeNotification.java com/booking/postbooking/notifications/RoomUpgradeNotificationAlarmHandler.java com/booking/postbookinguicomponents/PostBookingDirectionsFacet.java com/booking/preinstall/PreinstalledAffiliateIdProvider.java com/booking/price/ui/compose/RewardDetailsCollapsableComposeKt.java com/booking/propertycard/ui/PropertyCardKt$$ExternalSyntheticLambda16.java com/booking/publictransportpresentation/ui/PublicTransportBookingConfirmationFragment$observeUiActions$1.java com/booking/publictransportpresentation/ui/PublicTransportPaymentFragment$observeUiActions$1.java com/booking/rewards/wallet_payout/WalletCashoutActivityMarken.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	

RULE ID	BEHAVIOUR	LABEL	FILES
			com/booking/rewardsandwalletpresentation/ui/CreateWalletLinkHandlerKt$$ExternalSyntheticLambda0.java com/booking/rewardsandwalletpresentation/ui/CreateWalletLinkHandlerKt.java com/booking/saba/marken/components/core/components/OnTapComponent.java com/booking/saba/network/SabaResponsePersistenceInterceptor.java com/booking/search/MainAppWishlistProvider$$ExternalSyntheticLambda0.java com/booking/searchbox/activity/AdvancedSearchActivity.java com/booking/searchbox/activity/DisambiguationActivity$$ExternalSyntheticLambda1.java com/booking/searchbox/disambiguation/viewmodel/DisambiguationViewModel$handleSearchQueryDeeplinks$1.java com/booking/selfbuild/DownloadPulseActivity.java com/booking/sharing/GetChannel.java com/booking/sharing/ShareUtils.java com/booking/taxispresentation/marken/FreeTaxiActivity.java com/booking/taxispresentation/navigation/FlowManagerImpl.java com/booking/taxispresentation/ui/postbook/pickupcompanion/scheduledNotification/FlightNumberCheckWorker.java com/booking/taxispresentation/ui/postbook/pickupcompanion/scheduledNotification/ScheduleFlightNumberPushUseCaseImpl.java com/booking/tripcomponents/ui/jpc/trips/TripCardKt.java com/booking/trippresentation/ui/activity/SingleTripActivityVariant.java com/booking/trippresentation/ui/timeline/jpc/MyTripsJPCExtKt.java com/booking/util/IntentHelper.java com/booking/util/NotificationBuilder.java com/booking/web/interceptors/MdotExternalLinkWebViewUrlInterceptor.java com/booking/web/interceptors/PlayStoreWebViewUrlInterceptor.java com/booking/wishlist/ui/handler/WishlistDetailsActionsHandlerBase.java com/braintreepayments/api/BraintreeClient.java com/braintreepayments/api/BrowserSwitchClient.java com/braintreepayments/api/VenmoClient.java com/cardinalcommerce/shared/cs/userinterfaces/ChallengeHTMLView.java com/heytap/openid/base/m_c.java com/huawei/hms/push/q.java com/vivo/identifier/IdentifierIdClient.java io/noties/markwon/core/spans/LinkSpan.java net/openid/appauth/AuthorizationManagementActivity.java zendesk/messaging/android/internal/AttachmentIntentsLauncher.java zendesk/messaging/android/internal/conversationscreen/ConversationFragment.java zendesk/messaging/android/internal/conversationscreen/guidearticleviewer/GuideArticleViewerBottomSheetFragment$onViewCreated$1.java
00053	Monitor data identified by a given content URI changes(SMS, MMS, etc.)	sms	com/vivo/identifier/IdentifierIdClient.java

RULE ID	BEHAVIOUR	LABEL	FILES
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/booking/identity/auth/facet/facebook/AccountPortalWeb.java com/booking/identity/auth/facet/landing/AuthLandingFacet$Reactor$$ExternalSyntheticLambda3.java com/booking/identity/auth/facet/legal/CCPAConsentViewFacet.java com/booking/payment/component/ui/screen/web/deeplink/UniversalDeeplinksWebViewUrlInterceptor.java com/booking/postbooking/confirmation/locationdialog/LocationShareDialog.java com/booking/postbookinguicomponents/PostBookingDirectionsFacet.java com/booking/propertycard/ui/PropertyCardKt$$ExternalSyntheticLambda16.java com/booking/saba/marken/components/core/components/OnTapComponent.java com/booking/search/MainAppWishlistProvider$$ExternalSyntheticLambda0.java com/booking/taxispresentation/navigation/FlowManagerImpl.java com/booking/taxispresentation/ui/postbook/pickupcompanion/schedulednotification/FlightNumberCheckWorker.java com/booking/taxispresentation/ui/postbook/pickupcompanion/schedulednotification/ScheduleFlightNumberPushUseCaseImpl.java com/booking/util/IntentHelper.java com/booking/web/interceptors/MdotExternalLinkWebViewUrlInterceptor.java com/booking/wishlist/ui/handler/WishlistDetailsActionsHandlerBase.java com/braintreepayments/api/BraintreeClient.java com/heytap/openid/base/m_c.java com/huawei/hms/push/q.java com/vivo/identifier/IdentifierIdClient.java net/openid/appauth/AuthorizationManagementActivity.java
00036	Get resource file from res/raw directory	reflection	com/booking/notification/NotificationDeeplinkResolverKt.java com/booking/notifications/carrier/HwNotificationCarrier.java com/booking/preinstall/SamsungMapsInfo.java com/booking/searchbox/disambiguation/viewmodel/DisambiguationViewModel$handleSearchQueryDeeplinks$1.java com/booking/taxispresentation/navigation/FlowManagerImpl.java com/heytap/openid/base/m_c.java com/huawei/hms/push/q.java com/vivo/identifier/IdentifierIdClient.java io/noties/markwon/core/spans/LinkSpan.java lib/android/paypal/com/magnessdk/h.java

RULE ID	BEHAVIOUR	LABEL	FILES
00163	Create new Socket and connecting to it	socket	mijtkD/Jlkvq.java mijtkD/RGsnKs.java org/conscrypt/AbstractConscryptSocket.java org/conscrypt/KitKatPlatformOpenSSLSocketImplAdapter.java org/conscrypt/PreKitKatPlatformOpenSSLSocketImplAdapter.java
00022	Open a file from given absolute path of the file	file	com/baidu/mapsdkplatform/comapi/NativeLoader.java com/baidu/mapsdkplatform/comapi/commonutils/a.java com/baidu/mapsdkplatform/comapi/util/d.java com/baidu/mshield/b/a/b.java com/baidu/mshield/x0/c/b.java com/baidu/platform/comapi/util/a/b.java com/booking/assistant/intercommessaging/outgoing/images/ImageResizer.java com/booking/core/util/FileUtils.java com/booking/taxiservices/domain/fulfilment/imagecache/PickupInstructionsImageRepository$getImageAsBitmap$2.java com/fingerprintjs/android/fpjs_pro_internal/A0.java com/fingerprintjs/android/fpjs_pro_internal/C0066a1.java com/fingerprintjs/android/fpjs_pro_internal/Z0.java com/flexdb/storage/leveldb/LevelDBStorage.java com/getkeepsafe/relinker/ReLinkerInstance.java lib/android/paypal/com/magnessdk/g.java
00078	Get the network operator name	collection telephony	com/appsflyer/internal/AFi1xSDK.java zendesk/conversationkit/android/internal/MainEnvironment.java
00089	Connect to a URL and receive input stream from the server	command network	com/appsflyer/internal/AFe1qSDK.java com/baidu/mapauto/auth/net/a.java com/bumptech/glide/load/data/HttpUrlFetcher.java com/cardinalcommerce/a/setProgressBackgroundTintBlendMode.java com/huawei/updatesdk/a/a/b/b.java com/riskified/android/a/b.java
00030	Connect to the remote server through the given URL	network	com/airbnb/lottie/network/DefaultLottieNetworkFetcher.java com/baidu/mapauto/auth/net/a.java com/bumptech/glide/load/data/HttpUrlFetcher.java com/riskified/android/a/a.java com/riskified/android/a/b.java

RULE ID	BEHAVIOUR	LABEL	FILES
00109	Connect to a URL and get the response code	network command	com/appsflyer/internal/AFe1qSDK.java com/baidu/mapauto/auth/net/a.java com/braintreepayments/api/SynchronousHttpClient.java com/bumptech/glide/load/data/HttpUrlFetcher.java com/cardinalcommerce/a/setProgressBackgroundTintBlendMode.java com/huawei/updatesdk/a/a/b/b.java com/riskified/android/a/a.java com/riskified/android/a/b.java
00012	Read data and put it into a buffer stream	file	atd/w/protocolError.java com/huawei/hms/utils/SHA256.java org/conscrypt/DefaultSSLContextImpl.java
00042	Query WiFi BSSID and scan results	collection wifi	lib/android/paypal/com/magnessdk/i.java
00130	Get the current WIFI information	wifi collection	atd/aa/ChallengeStatusReceiver.java lib/android/paypal/com/magnessdk/MagnesSDK.java lib/android/paypal/com/magnessdk/h.java lib/android/paypal/com/magnessdk/i.java
00137	Get last known location of the device	location collection	lib/android/paypal/com/magnessdk/i.java
00004	Get filename and put it to JSON object	file collection	com/baidu/xclient/gdid/j/d.java lib/android/paypal/com/magnessdk/h.java lib/android/paypal/com/magnessdk/i.java
00115	Get last known location of the device	collection location	lib/android/paypal/com/magnessdk/i.java
00066	Query the ICCID number	collection	lib/android/paypal/com/magnessdk/i.java
00067	Query the IMSI number	collection	lib/android/paypal/com/magnessdk/i.java
00076	Get the current WiFi information and put it into JSON	collection wifi	lib/android/paypal/com/magnessdk/MagnesSDK.java lib/android/paypal/com/magnessdk/h.java lib/android/paypal/com/magnessdk/i.java
00113	Get location and put it into JSON	collection location	lib/android/paypal/com/magnessdk/i.java

RULE ID	BEHAVIOUR	LABEL	FILES
00016	Get location info of the device and put it to JSON object	location collection	lib/android/paypal/com/magnessdk/i.java
00108	Read the input stream from given URL	network command	com/baidu/mapauto/auth/net/a.java com/braintreepayments/api/BaseHttpResponseParser.java com/huawei/hms/hatool/r0.java
00091	Retrieve data from broadcast	collection	com/booking/preinstall/ExternalAppBroadcastReceiver.java com/booking/settings/presentation/SettingsActivity.java com/booking/taxispresentation/marken/freetaxi/FreeTaxiFacet.java com/booking/util/IntentHelper.java com/cardinalcommerce/shared/cs/userinterfaces/ChallengeNativeView.java net/openid/appauth/AuthorizationManagementActivity.java
00096	Connect to a URL and set request method	command network	com/airbnb/lottie/network/DefaultLottieNetworkFetcher.java com/appsflyer/internal/AFe1qSDK.java com/baidu/mapauto/auth/net/a.java com/braintreepayments/api/SynchronousHttpClient.java com/huawei/updatesdk/a/a/b/b.java com/riskified/android/a/a.java com/riskified/android/a/b.java
00202	Make a phone call	control	com/booking/util/IntentHelper.java
00203	Put a phone number into an intent	control	com/booking/util/IntentHelper.java
00125	Check if the given file path exist	file	com/baidu/sec/privacy/f/d.java
00132	Query The ISO country code	telephony collection	com/booking/identity/phone/PhoneNumberUtil.java com/booking/phonenumberservices/PhoneNumberProvider.java
00162	Create InetSocketAddress object and connecting to it	socket	mijtkD/Jlkvq.java org/conscrypt/AbstractConscryptSocket.java

RULE ID	BEHAVIOUR	LABEL	FILES
00005	Get absolute path of file and put it to JSON object	file	lib/android/paypal/com/magnessdk/g.java
00034	Query the current data network type	collection network	com/baidu/mapapi/NetworkUtil.java com/baidu/platform/comapi/util/NetworkUtil.java
00011	Query data from URI (SMS, CALLLOGS)	sms calllog collection	com/booking/preinstall/SamsungMapsInfo.java com/fingerprintjs/android/fpjs_pro_internal/C0120h1.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	com/booking/preinstall/SamsungMapsInfo.java com/bumptech/glide/load/data/mediastore/ThumbFetcher.java zendesk/messaging/android/internal/AttachmentFileResolver.java
00023	Start another application from current application	reflection control	com/huawei/hms/push/q.java
00147	Get the time of current location	collection location	com/booking/location/LocationUtilsKt.java
00075	Get location of the device	collection location	com/booking/location/LocationUtilsKt.java
00135	Get the current WiFi id and put it into JSON.	wifi collection	com/cardinalcommerce/a/setProgressDrawable.java
00094	Connect to a URL and read data from it	command network	com/baidu/lbsapi/auth/i.java com/baidu/mapauto/auth/net/a.java
00153	Send binary data over HTTP	http	com/baidu/mapauto/auth/net/a.java com/huawei/updatesdk/a/a/b/b.java
00054	Install other APKs from file	reflection	zendesk/messaging/android/internal/conversationscreen/ConversationFragment$collectEvents$2.java
00072	Write HTTP input stream into a file	command network file	com/huawei/hms/hatool/r0.java
00033	Query the IMEI number	collection	com/huawei/hms/hatool/z0.java

RULE ID	BEHAVIOUR	LABEL	FILES
00189	Get the content of a SMS message	sms	zendesk/messaging/android/internal/AttachmentFileResolver.java
00188	Get the address of a SMS message	sms	zendesk/messaging/android/internal/AttachmentFileResolver.java
00200	Query data from the contact list	collection contact	zendesk/messaging/android/internal/AttachmentFileResolver.java
00201	Query data from the call log	collection calllog	zendesk/messaging/android/internal/AttachmentFileResolver.java
00062	Query WiFi information and WiFi Mac Address	wifi collection	lib/android/paypal/com/magnessdk/h.java
00009	Put data in cursor to JSON object	file	lib/android/paypal/com/magnessdk/h.java
00116	Get the current WiFi MAC address and put it into JSON	wifi collection	lib/android/paypal/com/magnessdk/h.java
00082	Get the current WiFi MAC address	collection wifi	lib/android/paypal/com/magnessdk/h.java
00121	Create a directory	file command	com/booking/web/WebViewStaticOfflineBaseActivity.java
00092	Send broadcast	command	com/booking/settings/presentation/SettingsActivity.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
App talks to a Firebase database	info	The app talks to Firebase database at https://booking-oauth.firebaseio.com
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/901905703382/namespaces/firebase:fetch?key=AIzaSyCecagEEJNckS_25xBvdfmgeieLoGy_E2o. This is indicated by the response: The response code is 403

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	14/25	android.permission.INTERNET, android.permission.ACCESS_NETWORK_STATE, android.permission.ACCESS_FINE_LOCATION, android.permission.ACCESS_COARSE_LOCATION, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.WAKE_LOCK, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.CAMERA, android.permission.GET_ACCOUNTS, android.permission.READ_EXTERNAL_STORAGE, android.permission.ACCESS_WIFI_STATE, android.permission.REQUEST_INSTALL_PACKAGES, android.permission.RECORD_AUDIO, android.permission.READ_PHONE_STATE
Other Common Permissions	7/44	com.android.launcher.permission.INSTALL_SHORTCUT, com.google.android.gms.permission.AD_ID, android.permission.AUTHENTICATE_ACCOUNTS, com.google.android.c2dm.permission.RECEIVE, android.permission.READ_CALENDAR, com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE, android.permission.FOREGROUND_SERVICE

Malware Permissions:
Top permissions that are widely abused by known malware.

Other Common Permissions:
Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
www.localhome.cn	IP: 61.170.81.224 Country: China Region: Shanghai City: Shanghai
aispace.baidu.com	IP: 111.45.11.121 Country: China Region: Guangdong City: Guangzhou

DOMAIN	COUNTRY/REGION
offmap2.baidu.com	IP: 218.94.231.38 Country: China Region: Jiangsu City: Suzhou
beian.miit.gov.cn	IP: 112.45.27.156 Country: China Region: Sichuan City: Kangding
newclient.map.baidu.com	IP: 182.61.62.127 Country: China Region: Beijing City: Beijing
www.yunzhanggui.net	IP: 1.15.158.76 Country: China Region: Beijing City: Beijing
pms.lvyuetravel.com	IP: 47.94.181.238 Country: China Region: Zhejiang City: Hangzhou
lbs.baidu.com	IP: 112.34.111.148 Country: China Region: Beijing City: Beijing
v.map.baidu.com	IP: 112.34.116.1 Country: China Region: Beijing City: Beijing
client.map.baidu.com	IP: 180.76.11.166 Country: China Region: Beijing City: Beijing

DOMAIN	COUNTRY/REGION
ac-a.static.booking.cn	IP: 61.170.81.223 Country: China Region: Shanghai City: Shanghai
itsmap3.baidu.com	IP: 180.97.107.91 Country: China Region: Jiangsu City: Nanjing
mapoffdownload.bdstatic.com	IP: 42.59.17.36 Country: China Region: Liaoning City: Dalian
mobilegw.alipay.com	IP: 205.204.122.81 Country: Hong Kong Region: Hong Kong City: Hong Kong
newvector.map.baidu.com	IP: 14.215.182.52 Country: China Region: Guangdong City: Guangzhou
api.map.baidu.com	IP: 180.76.11.208 Country: China Region: Beijing City: Beijing
mobilegwpre.alipay.com	IP: 110.75.138.35 Country: China Region: Zhejiang City: Hangzhou
sv.map.baidu.com	IP: 112.34.116.10 Country: China Region: Beijing City: Beijing

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
secure-mobile-apps.booking.com	ok	**IP:** 108.139.210.63 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
group.accor.com	ok	**IP:** 45.60.155.180 **Country:** France **Region:** Ile-de-France **City:** Paris **Latitude:** 48.853409 **Longitude:** 2.348800 **View:** Google Map
www.majorel.com	ok	**IP:** 35.180.214.174 **Country:** France **Region:** Ile-de-France **City:** Paris **Latitude:** 48.853409 **Longitude:** 2.348800 **View:** Google Map
r-xx.bstatic.com	ok	**IP:** 3.166.81.38 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
go.microsoft.com	ok	**IP:** 23.11.193.246 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
account.booking.com	ok	**IP:** 18.65.82.62 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
www.appsflyer.com	ok	**IP:** 18.154.161.79 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
checkoutshopper-live-in.adyen.com	ok	**IP:** 147.12.21.133 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
www.localhome.cn	ok	**IP:** 61.170.81.224 **Country:** China **Region:** Shanghai **City:** Shanghai **Latitude:** 31.222219 **Longitude:** 121.458061 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
bookinglite.ru	ok	**IP:** 91.197.97.192 **Country:** Russian Federation **Region:** Moskva **City:** Moscow **Latitude:** 55.752220 **Longitude:** 37.615559 **View:** Google Map
checkoutanalytics-live-us.adyen.com	ok	**IP:** 62.146.255.10 **Country:** Germany **Region:** Bayern **City:** Nuremberg **Latitude:** 49.447781 **Longitude:** 11.068330 **View:** Google Map
api.braintreegateway.com	ok	**IP:** 159.242.242.193 **Country:** United States of America **Region:** Illinois **City:** Chicago **Latitude:** 41.888401 **Longitude:** -87.635101 **View:** Google Map
booking-dp-it.lastminute.com	ok	**IP:** 172.64.149.10 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
m.booking.com	ok	**IP:** 3.166.81.123 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
skimgroup.com	ok	**IP:** 94.237.43.208 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
www.uber.com	ok	**IP:** 69.48.218.1 **Country:** United States of America **Region:** Georgia **City:** Atlanta **Latitude:** 33.785400 **Longitude:** -84.384804 **View:** Google Map
agoda.com	ok	**IP:** 103.6.182.20 **Country:** Thailand **Region:** Krung Thep Maha Nakhon **City:** Bangkok **Latitude:** 13.750000 **Longitude:** 100.516670 **View:** Google Map
www.amazon.com	ok	**IP:** 18.154.152.226 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
www.paypal.com	ok	**IP:** 151.101.129.21 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.pinterest.com.au	ok	**IP:** 104.85.8.193 **Country:** Italy **Region:** Lombardia **City:** Milan **Latitude:** 45.464272 **Longitude:** 9.189510 **View:** Google Map
counters.booking.com	ok	**IP:** 108.139.229.52 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
terms.aliyun.com	ok	**IP:** 163.181.50.214 **Country:** Italy **Region:** Lombardia **City:** Milan **Latitude:** 45.464272 **Longitude:** 9.189510 **View:** Google Map
aws.amazon.com	ok	**IP:** 13.35.198.99 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** London **Latitude:** 51.508530 **Longitude:** -0.125740 **View:** Google Map
q-xx.bstatic.com	ok	**IP:** 3.166.81.74 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
secure.booking.com	ok	**IP:** 18.154.161.6 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
ec.europa.eu	ok	**IP:** 147.67.34.30 **Country:** Luxembourg **Region:** Luxembourg **City:** Luxembourg **Latitude:** 49.611671 **Longitude:** 6.130000 **View:** Google Map
www.ttec.com	ok	**IP:** 23.185.0.1 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.792030 **Longitude:** -122.406853 **View:** Google Map
www.caa.co.uk	ok	**IP:** 13.107.246.43 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
join.booking.com	ok	**IP:** 18.154.161.128 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
booking.com	ok	**IP:** 3.166.81.80 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
static.zdassets.com	ok	**IP:** 216.198.54.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.773968 **Longitude:** -122.410446 **View:** Google Map
maps.google.com	ok	**IP:** 142.251.209.46 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.kantar.com	ok	**IP:** 23.202.156.232 **Country:** United States of America **Region:** Virginia **City:** Manassas **Latitude:** 38.750950 **Longitude:** -77.475273 **View:** Google Map
booking.lastminute.ie	ok	**IP:** 104.18.34.254 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
centinelapi.cardinalcommerce.com	ok	**IP:** 198.217.251.251 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.609699 **Longitude:** -122.386948 **View:** Google Map
loop-ux.com	ok	**IP:** 94.231.103.154 **Country:** Denmark **Region:** Midtjylland **City:** Skanderborg **Latitude:** 56.039909 **Longitude:** 9.927200 **View:** Google Map
website.qa.taxis.booking.com	ok	**IP:** 108.139.210.4 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
ethn.io	ok	**IP:** 52.24.64.105 **Country:** United States of America **Region:** Oregon **City:** Portland **Latitude:** 45.523449 **Longitude:** -122.676208 **View:** Google Map
10.0.2.2	ok	**IP:** 10.0.2.2 **Country:** - **Region:** - **City:** - **Latitude:** 0.000000 **Longitude:** 0.000000 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.seznam.cz	ok	**IP:** 77.75.79.222 **Country:** Czechia **Region:** Praha, Hlavni mesto **City:** Prague **Latitude:** 50.088039 **Longitude:** 14.420760 **View:** Google Map
www.360.cn	ok	**IP:** 47.89.195.194 **Country:** United States of America **Region:** California **City:** San Mateo **Latitude:** 37.547424 **Longitude:** -122.330589 **View:** Google Map
stripe.com	ok	**IP:** 18.202.131.124 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
www.yieldplanet.com	ok	**IP:** 104.18.18.88 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
docs.mapbox.com	ok	**IP:** 18.65.82.71 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
rides-apps-gateway.rideways.com	ok	**IP:** 3.166.81.2 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
24-7intouch.com	ok	**IP:** 141.193.213.11 **Country:** United States of America **Region:** Texas **City:** Austin **Latitude:** 30.271158 **Longitude:** -97.741699 **View:** Google Map
aispace.baidu.com	ok	**IP:** 111.45.11.121 **Country:** China **Region:** Guangdong **City:** Guangzhou **Latitude:** 23.116671 **Longitude:** 113.250000 **View:** Google Map
vectormap0.bdimg.com	ok	**IP:** 185.10.104.124 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
www.booking.com	ok	**IP:** 3.166.81.36 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
sg.yahoo.com	ok	**IP:** 87.248.119.251 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
apps.bstatic.com	ok	**IP:** 3.166.81.99 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
booking.bravofly.ch	ok	**IP:** 108.139.229.118 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
checkoutanalytics-live-au.adyen.com	ok	**IP:** 85.184.230.95 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
paymentcomponent-pci.dqs.booking.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
booking-dp.lastminute.com	ok	**IP:** 172.64.149.10 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
.booking.com	ok	No Geolocation information available.
eu.api.fpjs.io	ok	**IP:** 99.83.255.25 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
offmap2.baidu.com	ok	**IP:** 218.94.231.38 **Country:** China **Region:** Jiangsu **City:** Suzhou **Latitude:** 31.311390 **Longitude:** 120.618057 **View:** Google Map
www.oracle.com	ok	**IP:** 23.211.189.105 **Country:** United States of America **Region:** Kansas **City:** Shawnee Mission **Latitude:** 39.004372 **Longitude:** -94.669388 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
docs.google.com	ok	**IP:** 142.250.180.142 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
cmsdk.cardinalcommerce.com	ok	**IP:** 198.217.251.251 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.609699 **Longitude:** -122.386948 **View:** Google Map
www.usertesting.com	ok	**IP:** 151.101.66.49 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.shijigroup.com	ok	**IP:** 15.160.106.203 **Country:** Spain **Region:** Madrid, Comunidad de **City:** Madrid **Latitude:** 40.416500 **Longitude:** -3.702560 **View:** Google Map
chat.booking.com	ok	**IP:** 18.65.82.93 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
cf.bstatic.com	ok	**IP:** 3.166.81.129 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
ap.api.fpjs.io	ok	**IP:** 15.197.228.86 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
ct.ctrip.com	ok	**IP:** 23.61.250.48 **Country:** Japan **Region:** Osaka **City:** Osaka **Latitude:** 34.693890 **Longitude:** 135.502213 **View:** Google Map
www.amadeus-hospitality.com	ok	**IP:** 23.61.250.49 **Country:** Japan **Region:** Osaka **City:** Osaka **Latitude:** 34.693890 **Longitude:** 135.502213 **View:** Google Map
developer.android.com	ok	**IP:** 142.250.180.174 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
android.googlesource.com	ok	**IP:** 173.194.69.82 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.ingenico.com	ok	**IP:** 104.20.34.59 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
checkoutshopper-live-au.adyen.com	ok	**IP:** 62.146.255.16 **Country:** Germany **Region:** Bayern **City:** Nuremberg **Latitude:** 49.447781 **Longitude:** 11.068330 **View:** Google Map
www.schlesingergroup.com	ok	**IP:** 192.190.221.112 **Country:** United States of America **Region:** Michigan **City:** Lansing **Latitude:** 42.733280 **Longitude:** -84.637764 **View:** Google Map
taxi-webform.booking.com	ok	**IP:** 216.198.54.11 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.773968 **Longitude:** -122.410446 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
taxis.booking.com	ok	**IP:** 108.139.210.4 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
www.caa.co.ukend	ok	No Geolocation information available.
store.hispace.hicloud.com	ok	**IP:** 164.30.19.234 **Country:** Germany **Region:** Nordrhein-Westfalen **City:** Bielefeld **Latitude:** 52.007084 **Longitude:** 8.545701 **View:** Google Map
www.impots.gouv.fr	ok	**IP:** 23.202.156.228 **Country:** United States of America **Region:** Virginia **City:** Manassas **Latitude:** 38.750950 **Longitude:** -77.475273 **View:** Google Map
booking.bravofly.at	ok	**IP:** 108.139.229.13 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
link.com	ok	**IP:** 52.30.58.64 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
github.com	ok	**IP:** 140.82.121.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.leonardo-hotels.com	ok	**IP:** 18.154.161.22 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
booking-oauth.firebaseio.com	ok	**IP:** 35.201.97.85 **Country:** United States of America **Region:** Missouri **City:** Kansas City **Latitude:** 39.099731 **Longitude:** -94.578568 **View:** Google Map
www.google.com	ok	**IP:** 216.58.204.132 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.concentrix.com	ok	**IP:** 172.64.147.172 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
ir.baidu.com	ok	**IP:** 23.39.107.204 **Country:** Spain **Region:** Madrid, Comunidad de **City:** Madrid **Latitude:** 40.416500 **Longitude:** -3.702560 **View:** Google Map
beian.miit.gov.cn	ok	**IP:** 112.45.27.156 **Country:** China **Region:** Sichuan **City:** Kangding **Latitude:** 30.051270 **Longitude:** 101.960327 **View:** Google Map
yandex.com	ok	**IP:** 77.88.44.55 **Country:** Russian Federation **Region:** Moskva **City:** Moscow **Latitude:** 55.752220 **Longitude:** 37.615559 **View:** Google Map
www.assistdigital.com	ok	**IP:** 162.159.140.127 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
checkoutanalytics-live-in.adyen.com	ok	**IP:** 147.12.20.148 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
www.agoda.com	ok	**IP:** 23.211.188.106 **Country:** United States of America **Region:** Kansas **City:** Shawnee Mission **Latitude:** 39.004372 **Longitude:** -94.669388 **View:** Google Map
cars-apps.booking.com	ok	**IP:** 108.139.210.3 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
checkoutanalytics-live.adyen.com	ok	**IP:** 147.12.17.60 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
www.urssaf.fr	ok	**IP:** 193.178.136.246 **Country:** France **Region:** Ile-de-France **City:** Malakoff **Latitude:** 48.819988 **Longitude:** 2.299980 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.fisglobal.com	ok	**IP:** 23.206.246.130 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
mailchimp.com	ok	**IP:** 23.211.188.188 **Country:** United States of America **Region:** Kansas **City:** Shawnee Mission **Latitude:** 39.004372 **Longitude:** -94.669388 **View:** Google Map
www.perimeterx.com	ok	**IP:** 63.176.8.218 **Country:** United States of America **Region:** Virginia **City:** Reston **Latitude:** 38.925961 **Longitude:** -77.397331 **View:** Google Map
www.adyen.com	ok	**IP:** 15.197.167.90 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
gitlab.booking.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
www.luopan.com	ok	**IP:** 54.176.193.150 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.774929 **Longitude:** -122.419418 **View:** Google Map
www.marriott.com	ok	**IP:** 23.211.188.84 **Country:** United States of America **Region:** Kansas **City:** Shawnee Mission **Latitude:** 39.004372 **Longitude:** -94.669388 **View:** Google Map
www.derbysoft.com	ok	**IP:** 52.34.89.197 **Country:** United States of America **Region:** Oregon **City:** Portland **Latitude:** 45.523449 **Longitude:** -122.676208 **View:** Google Map
newclient.map.baidu.com	ok	**IP:** 182.61.62.127 **Country:** China **Region:** Beijing **City:** Beijing **Latitude:** 39.907501 **Longitude:** 116.397232 **View:** Google Map
www.beian.gov.cn	ok	**IP:** 127.0.0.1 **Country:** - **Region:** - **City:** - **Latitude:** 0.000000 **Longitude:** 0.000000 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
unbabel.com	ok	**IP:** 104.18.11.30 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.navercorp.com	ok	**IP:** 61.247.194.49 **Country:** Korea (Republic of) **Region:** Gyeonggi-do **City:** Seongnam **Latitude:** 37.438610 **Longitude:** 127.137779 **View:** Google Map
developer.paypal.com	ok	**IP:** 104.18.2.198 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
jin-han.com.cn	ok	**IP:** 35.71.142.77 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
otel-gw.booking.com	ok	**IP:** 18.65.64.90 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
cars.booking.com	ok	**IP:** 108.139.210.39 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
incling.com	ok	**IP:** 178.79.149.107 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** London **Latitude:** 51.508530 **Longitude:** -0.125740 **View:** Google Map
booking-fr.lastminute.be	ok	**IP:** 104.18.33.116 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
www.apple.com	ok	**IP:** 2.20.200.178 **Country:** France **Region:** Ile-de-France **City:** Paris **Latitude:** 48.853409 **Longitude:** 2.348800 **View:** Google Map
www.yunzhanggui.net	ok	**IP:** 1.15.158.76 **Country:** China **Region:** Beijing **City:** Beijing **Latitude:** 39.907501 **Longitude:** 116.397232 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.hotel-spider.com	ok	**IP:** 185.177.60.230 **Country:** Switzerland **Region:** Geneve **City:** Carouge **Latitude:** 46.180962 **Longitude:** 6.139210 **View:** Google Map
api.fpjs.io	ok	**IP:** 76.223.60.10 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.
pms.lvyuetravel.com	ok	**IP:** 47.94.181.238 **Country:** China **Region:** Zhejiang **City:** Hangzhou **Latitude:** 30.293650 **Longitude:** 120.161423 **View:** Google Map
paymentcomponent.booking.com	ok	**IP:** 18.65.82.17 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
rategain.com	ok	**IP:** 159.60.153.26 **Country:** Netherlands **Region:** Zuid-Holland **City:** The Hague **Latitude:** 52.076672 **Longitude:** 4.298610 **View:** Google Map
insurance.biba.org.uk	ok	**IP:** 185.216.78.164 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** Manchester **Latitude:** 53.480949 **Longitude:** -2.237430 **View:** Google Map
packages.booking.com	ok	**IP:** 104.18.25.187 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
checkoutshopper-live-us.adyen.com	ok	**IP:** 62.146.255.16 **Country:** Germany **Region:** Bayern **City:** Nuremberg **Latitude:** 49.447781 **Longitude:** 11.068330 **View:** Google Map
policy.medium.com	ok	**IP:** 162.159.152.4 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.viator.com	ok	**IP:** 151.101.129.91 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
sapp.s	ok	No Geolocation information available.
www.ehawk.net	ok	**IP:** 94.228.142.86 **Country:** Netherlands **Region:** Zuid-Holland **City:** Rijswijk **Latitude:** 52.036339 **Longitude:** 4.325010 **View:** Google Map
flights.booking.com	ok	**IP:** 13.35.198.109 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** London **Latitude:** 51.508530 **Longitude:** -0.125740 **View:** Google Map
lbs.baidu.com	ok	**IP:** 112.34.111.148 **Country:** China **Region:** Beijing **City:** Beijing **Latitude:** 39.907501 **Longitude:** 116.397232 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
b.stats.paypal.com	ok	**IP:** 34.147.177.40 **Country:** United States of America **Region:** Texas **City:** Houston **Latitude:** 29.941401 **Longitude:** -95.344498 **View:** Google Map
global.wave.onda.me	ok	No Geolocation information available.
v.map.baidu.com	ok	**IP:** 112.34.116.1 **Country:** China **Region:** Beijing **City:** Beijing **Latitude:** 39.907501 **Longitude:** 116.397232 **View:** Google Map
www.messagebird.com	ok	**IP:** 18.65.64.116 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
booking-it.bravofly.ch	ok	**IP:** 108.139.229.13 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
checkoutanalytics-test.adyen.com	ok	**IP:** 147.12.17.121 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
www.sabre.com	ok	**IP:** 45.60.46.204 **Country:** France **Region:** Ile-de-France **City:** Paris **Latitude:** 48.853409 **Longitude:** 2.348800 **View:** Google Map
www.siteminder.com	ok	**IP:** 104.20.10.67 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
taxi.booking.com	ok	**IP:** 108.139.210.102 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
mobile-apps.booking.com	ok	**IP:** 108.139.229.111 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.alchemer.com	ok	**IP:** 162.159.135.42 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.shopify.com	ok	**IP:** 104.18.42.163 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
checkoutanalytics-live-apse.adyen.com	ok	**IP:** 85.184.228.219 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
reports.booking.com	ok	**IP:** 18.65.64.10 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
www.ryanair.com	ok	**IP:** 108.139.229.24 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
client.map.baidu.com	ok	**IP:** 180.76.11.166 **Country:** China **Region:** Beijing **City:** Beijing **Latitude:** 39.907501 **Longitude:** 116.397232 **View:** Google Map
booking-dp.lastminute.de	ok	**IP:** 172.64.144.124 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
developer.huawei.com	ok	**IP:** 23.202.156.230 **Country:** United States of America **Region:** Virginia **City:** Manassas **Latitude:** 38.750950 **Longitude:** -77.475273 **View:** Google Map
www.mapbox.com	ok	**IP:** 199.232.196.143 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
checkoutshopper-live-apse.adyen.com	ok	**IP:** 62.146.255.12 **Country:** Germany **Region:** Bayern **City:** Nuremberg **Latitude:** 49.447781 **Longitude:** 11.068330 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
centinelapistag.cardinalcommerce.com	ok	**IP:** 198.217.251.251 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.609699 **Longitude:** -122.386948 **View:** Google Map
helpcenter-api.booking.com	ok	**IP:** 18.65.64.108 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
booking-fr.bravofly.ch	ok	**IP:** 108.139.229.13 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
x.klarnacdn.net	ok	**IP:** 3.166.81.6 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
ugcupload.booking.com	ok	**IP:** 18.65.64.50 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.rmscloud.com	ok	**IP:** 199.60.103.225 **Country:** United States of America **Region:** Massachusetts **City:** Cambridge **Latitude:** 42.370129 **Longitude:** -71.086304 **View:** Google Map
booking-dp-es.lastminute.com	ok	**IP:** 104.18.38.246 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
zendesk.taxis.booking.com	ok	No Geolocation information available.
samdesk.io	ok	**IP:** 108.139.210.22 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
ac-a.static.booking.cn	ok	**IP:** 61.170.81.223 **Country:** China **Region:** Shanghai **City:** Shanghai **Latitude:** 31.222219 **Longitude:** 121.458061 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.musement.com	ok	**IP:** 18.65.82.103 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
api.sandbox.braintreegateway.com	ok	**IP:** 159.242.242.129 **Country:** United States of America **Region:** Illinois **City:** Chicago **Latitude:** 41.888401 **Longitude:** -87.635101 **View:** Google Map
xx.bstatic.com	ok	**IP:** 3.166.81.38 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
www.facebook.com	ok	**IP:** 157.240.231.35 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
client.cardinaltrusted.com	ok	**IP:** 104.18.22.157 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.rtbhouse.com	ok	**IP:** 34.117.237.115 **Country:** United States of America **Region:** Missouri **City:** Kansas City **Latitude:** 39.099731 **Longitude:** -94.578568 **View:** Google Map
www.optimalworkshop.com	ok	**IP:** 198.202.211.1 **Country:** United States of America **Region:** New York **City:** White Plains **Latitude:** 41.009331 **Longitude:** -73.747353 **View:** Google Map
www.louvrehotels.com	ok	**IP:** 23.61.250.42 **Country:** Japan **Region:** Osaka **City:** Osaka **Latitude:** 34.693890 **Longitude:** 135.502213 **View:** Google Map
www.gotogate.co.uk	ok	**IP:** 104.83.105.79 **Country:** Italy **Region:** Lombardia **City:** Milan **Latitude:** 45.464272 **Longitude:** 9.189510 **View:** Google Map
itsmap3.baidu.com	ok	**IP:** 180.97.107.91 **Country:** China **Region:** Jiangsu **City:** Nanjing **Latitude:** 32.061668 **Longitude:** 118.777779 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.staah.com	ok	**IP:** 3.166.81.46 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
api-m.paypal.com	ok	**IP:** 151.101.195.1 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
xml.org	ok	**IP:** 104.239.142.8 **Country:** United States of America **Region:** Texas **City:** Windcrest **Latitude:** 29.499678 **Longitude:** -98.399246 **View:** Google Map
opendocs.alipay.com	ok	**IP:** 163.181.50.195 **Country:** Italy **Region:** Lombardia **City:** Milan **Latitude:** 45.464272 **Longitude:** 9.189510 **View:** Google Map
www.meliahotelsinternational.com	ok	**IP:** 23.61.250.31 **Country:** Japan **Region:** Osaka **City:** Osaka **Latitude:** 34.693890 **Longitude:** 135.502213 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.choicehotels.com	ok	**IP:** 23.61.250.49 **Country:** Japan **Region:** Osaka **City:** Osaka **Latitude:** 34.693890 **Longitude:** 135.502213 **View:** Google Map
mapoffdownload.bdstatic.com	ok	**IP:** 42.59.17.36 **Country:** China **Region:** Liaoning **City:** Dalian **Latitude:** 41.069592 **Longitude:** 122.598511 **View:** Google Map
tt-static-content-temp.s3-eu-west-1.amazonaws.com	ok	**IP:** 3.5.66.91 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
alwaysbeforward.com	ok	**IP:** 3.215.100.79 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
booking.lastminute.be	ok	**IP:** 172.64.154.140 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
checkoutshopper-live.adyen.com	ok	**IP:** 62.146.255.11 **Country:** Germany **Region:** Bayern **City:** Nuremberg **Latitude:** 49.447781 **Longitude:** 11.068330 **View:** Google Map
cp.betweendigital.com	ok	**IP:** 172.240.241.27 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.786339 **Longitude:** -96.820503 **View:** Google Map
condens.io	ok	**IP:** 3.33.249.164 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
img.riskified.com	ok	**IP:** 44.199.168.68 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
bstatic.com	ok	**IP:** 3.166.81.99 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
venmo.com	ok	**IP:** 52.84.150.58 **Country:** Germany **Region:** Rheinland-Pfalz **City:** Isenburg **Latitude:** 50.483330 **Longitude:** 7.600000 **View:** Google Map
www.transportation.gov	ok	**IP:** 104.83.100.102 **Country:** Italy **Region:** Lombardia **City:** Milan **Latitude:** 45.464272 **Longitude:** 9.189510 **View:** Google Map
play.google.com	ok	**IP:** 142.250.180.142 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
cas.client.cardinaltrusted.com	ok	**IP:** 104.18.6.75 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
booking-dp-fr.lastminute.com	ok	**IP:** 172.64.149.10 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
mobilegw.alipay.com	ok	**IP:** 205.204.122.81 **Country:** Hong Kong **Region:** Hong Kong **City:** Hong Kong **Latitude:** 22.285521 **Longitude:** 114.157692 **View:** Google Map
d8c14d4960ca.edge.sdk.awswaf.com	ok	**IP:** 108.139.229.23 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
appgallery.cloud.huawei.com	ok	**IP:** 80.158.19.46 **Country:** Germany **Region:** Schleswig-Holstein **City:** Kiel **Latitude:** 54.321331 **Longitude:** 10.134890 **View:** Google Map
hotelrunner.com	ok	**IP:** 18.200.208.87 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
www.qualtrics.com	ok	**IP:** 92.123.112.100 **Country:** Italy **Region:** Lombardia **City:** Milan **Latitude:** 45.464272 **Longitude:** 9.189510 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
hostex.io	ok	**IP:** 172.66.41.32 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
newvector.map.baidu.com	ok	**IP:** 14.215.182.52 **Country:** China **Region:** Guangdong **City:** Guangzhou **Latitude:** 23.116671 **Longitude:** 113.250000 **View:** Google Map
api.map.baidu.com	ok	**IP:** 180.76.11.208 **Country:** China **Region:** Beijing **City:** Beijing **Latitude:** 39.907501 **Longitude:** 116.397232 **View:** Google Map
mobilegwpre.alipay.com	ok	**IP:** 110.75.138.35 **Country:** China **Region:** Zhejiang **City:** Hangzhou **Latitude:** 30.293650 **Longitude:** 120.161423 **View:** Google Map
braintreepayments.com	ok	**IP:** 151.101.3.1 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.w3.org	ok	**IP:** 104.18.23.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
transport.booking.com	ok	**IP:** 18.154.161.94 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
www.snap.com	ok	**IP:** 34.120.54.238 **Country:** United States of America **Region:** Missouri **City:** Kansas City **Latitude:** 39.099731 **Longitude:** -94.578568 **View:** Google Map
www.cint.com	ok	**IP:** 141.193.213.11 **Country:** United States of America **Region:** Texas **City:** Austin **Latitude:** 30.271158 **Longitude:** -97.741699 **View:** Google Map
c.sandbox.paypal.com	ok	**IP:** 151.101.67.1 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
checkoutshopper-test.adyen.com	ok	**IP:** 62.146.255.2 **Country:** Germany **Region:** Bayern **City:** Nuremberg **Latitude:** 49.447781 **Longitude:** 11.068330 **View:** Google Map
c.paypal.com	ok	**IP:** 151.101.193.21 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.iponweb.com	ok	**IP:** 192.124.249.165 **Country:** United States of America **Region:** California **City:** Menifee **Latitude:** 33.679798 **Longitude:** -117.189484 **View:** Google Map
www.cloudbeds.com	ok	**IP:** 3.166.81.22 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
www.paypalobjects.com	ok	**IP:** 151.101.195.1 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
c.riskified.com	ok	**IP:** 52.6.160.211 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
sv.map.baidu.com	ok	**IP:** 112.34.116.10 **Country:** China **Region:** Beijing **City:** Beijing **Latitude:** 39.907501 **Longitude:** 116.397232 **View:** Google Map
www.wexinc.com	ok	**IP:** 45.60.156.173 **Country:** France **Region:** Ile-de-France **City:** Paris **Latitude:** 48.853409 **Longitude:** 2.348800 **View:** Google Map
xmlpull.org	ok	**IP:** 185.199.111.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map

EMAILS

EMAIL	FILE
inactive_code@3x.png	com/booking/incentivescomponents/activeoffer/IncentivesActiveOfferBlockKt.java
android-feedback@booking.com	com/booking/web/interceptors/EmailFeedbackWebViewUrlInterceptor.java
validate@booking.com□□ dataprotectionoffice@booking.com □□□validate@booking.com validate@booking.com s@booking.com helpline@uk.sedgwick support.booking.com□@partner.booking □□□□□□validate@booking.com □□□□□□□□validate@booking.com support@stripe.com your.email@domain.com □□□validate@booking.com□□□□□□□	Android String Resource
appro@openssl.org	lib/arm64-v8a/libBaiduMapSDK_map_v7_6_3.so
appro@openssl.org	lib/arm64-v8a/libconscrypt_jni.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libBaiduMapSDK_map_v7_6_3.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libconscrypt_jni.so

TRACKERS

TRACKER	CATEGORIES	URL
AppsFlyer	Analytics	https://reports.exodus-privacy.eu.org/trackers/12
Baidu Map		https://reports.exodus-privacy.eu.org/trackers/99
Facebook Flipper	Analytics	https://reports.exodus-privacy.eu.org/trackers/392

TRACKER	CATEGORIES	URL
Google AdMob	Advertisement	https://reports.exodus-privacy.eu.org/trackers/312
Google CrashLytics	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/27
Google Firebase Analytics	Analytics	https://reports.exodus-privacy.eu.org/trackers/49
Google Tag Manager	Analytics	https://reports.exodus-privacy.eu.org/trackers/105
Huawei Mobile Services (HMS) Core	Location, Advertisement, Analytics	https://reports.exodus-privacy.eu.org/trackers/333
OpenTelemetry (OpenCensus, OpenTracing)	Analytics	https://reports.exodus-privacy.eu.org/trackers/412

🔑 HARDCODED SECRETS

POSSIBLE SECRETS
"bui_icon_brand_secret_deal" : "□"
"zma_notification_default_author_name" : "Usuário"
"android_rl_filter_private" : "Privat"
"ccp_apps_bs3_sanction_dob_title" : "□□□□□□□□□□□□□"
"bs3_wallet_credits_header" : "□□□□"
"android_private_beach" : "Einkaströnd"
"bs3_wallet_credits_header" : "■■■■■■"
"android_promo_code_bs3_quick_tcs_link_tcs" : "Condicions"

POSSIBLE SECRETS
"bs3_select_payment_method_bancontact_card" : "Κάρτα"
"zma_notification_default_author_name" : "Użytkownik"
"android_bs3_card_details_ask_page_title" : "Kortoplysninger"
"attractions_apps_hackathon_ai_badges_private_group" : "□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■"
"bs3_wallet_credits_header" : "Inneign"
"membership_hub_account_preferences_region_item_user" : "Personalisasi"
"zma_notification_default_author_name" : "משתמש"
"android_cars_bc_tax_authority_website" : "■■■■■■■■■■■■■■■■■■■■■■■■■■■"
"bs3_wallet_credits_header" : "Credito"
"membership_hub_account_preferences_region_item_user" : "□□□□□□"
"android_key_collection_meeting" : "□□□□□□□□□□□□"
"android_promo_code_bs3_field_cta_apply" : "Mehet"
"android_promo_code_bs3_quick_tcs_link_tcs" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□"
"zma_notification_default_author_name" : "Пользователь"
"iux_security_active_sessions_cta" : "Deconectare"

POSSIBLE SECRETS
"android_pt_ticket_details_select_travel_pass" : "[redacted]"
"zma_notification_default_author_name" : "Gebruiker"
"cm_sm_bs3_v2_a_android" : "Booking.com□□□□□□□□□□□□□□□□□□□□□□□□□□Booking.com□□□□□□□□□□□□□□□□□□□

POSSIBLE SECRETS
"ccp_apps_bs3_sanction_dob_entry" : "Geburtsdatum"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□□□□"
"android_tpi_bs3_booking_conditions" : "varausehdot"
"android_tpi_bs3_general_terms" : "üldtingimuste"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "ລະຫັດຜ່ານ"
"login_password" : "□□"
"ccp_apps_bs3_sanction_country_entry" : "□□□□/□□"
"android_pt_ticket_details_select_travel_pass" : "□□□□□□□□"
"ccp_apps_bs3_sanction_country_entry" : "■■■■■■■■■■■■■■■■"
"iux_security_active_sessions_help" : "□□“□□”□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□10□□□"
"android_bhpse_key_collect_method_on_loc_secret" : "□□□□□□□□□□□□□"
"android_bp_bs3_cta_book_now" : "□□□□"
"login_password" : "Contraseña"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Jelszó"
"android_bhpse_key_collect_method_on_loc_meet" : "□□□□□□□□□□□□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Eltávolítás"
"bs3_wallet_credits_header" : "Credits"
"rewards_bs3_aob_points_codeapplied" : "□□□□□□□□□%1$s"

POSSIBLE SECRETS
"android_identity_phone_verify_using_password" : "[redacted]"
"android_bhpse_key_collect_method_diff_loc_recep" : "□□□%3$s□%2$s□%1$s□□□□□□□□□□□□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Palavra-passe"
"login_password" : "Heslo"
"ccp_apps_bs3_sanction_country_entry" : "Bostadsland"
"bs3_wallet_credits_header" : "Credit"
"android_promo_code_bs3_field_cta_apply" : "Bruk"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Գաղտնաբառ"
"ccp_apps_bs3_sanction_country_entry" : "Bostedsland"
"bs3_select_payment_method_bancontact_card" : "Kart"
"bs3_wallet_credits_header" : "Premija"
"android_bhpse_key_collect_contact_methods_month_before" : "□□□□□□□1□□□□□□□□□□"
"android_bhpse_key_collect_contact_methods_phone" : "[redacted]"
"bs3_select_payment_method_bancontact_card" : "□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Usuń"
"android_promo_code_bs3_field_cta_apply" : "Nota"
"android_promo_code_bs3_field_cta_apply" : "Primijeni"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lösenord"

POSSIBLE SECRETS
"android_bhpse_key_collect_contact_methods_straight_after" : "□□□□□□□□□□□□□□□□□□"
"bs3_wallet_credits_header" : "Jóváírás"
"android_bp_key_highlights" : "Erityistä"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Fjarlægja"
"com.google.firebase.crashlytics.mapping_file_id" : "f06e7042aebd4460b1a712d11a900885"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Heslo"
"android_bhpse_key_collect_method_diff_loc_box_nozip" : "□□□%2$s□%1$s□□□□□□□□□□□□□□□□"
"bs3_wallet_credits_header" : "Πίστωση"
"android_promo_code_bs3_field_cta_apply" : "Anwenden"
"android_bs3_card_details_ask_page_header" : "□□□□□□□□□□□□□□□"
"login_password" : "Palavra-passe"
"iam_totp_authentication_screen_description" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"android_tpi_bs3_legal_disclaimer_provider_match" : "□□□□□%s□□□□□□□□□□□□□□%s□%s□□%s□Booking.com□□□□□□□□□□□□□□□□□□□□□□□Booking.com□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_on_loc_recep" : "□□□□□□□□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Poista"
"bs3_wallet_credits_header" : "Кредити"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■"
"zma_notification_default_author_name" : "□□"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android_bhpse_key_collect_method_diff_loc_secret_nozip" : "□□□%2$s□%1$s□□□□□□□□□□□□□□□□□□□□□□□□"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"android_tpi_bs3_privacy_policy" : "Datenschutzrichtlinien"
"android_tpi_bs3_privacy_policy" : "□□□□□□□□□□□"
"android_bhpse_key_collect_contact_methods_sms" : "□□□□□□□□□□□□□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Elimină"
"android_bhpse_key_collect_method_what_if" : "□□□□□□□□□□□□"
"android_bh_key_pu_elsewhere" : "%1$s□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□%2$s%3$s"
"android_tpi_bs3_general_terms" : "□□□□"
"icon_compass" : "□"
"android_bs3_enter_your_promo_code" : "□□□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "ภะแจช่าม"
"android_bhpse_key_collect_method_on_loc_box" : "□□□□□□□□□□□□□□□□□□"
"android_rl_filter_private" : "Prywatny"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Wagwoordsleutel"
"bs3_wallet_credits_header" : "□□"
"android_rl_filter_private" : "Privado"

POSSIBLE SECRETS
"bs3_select_payment_method_bancontact_card" : "Kortti"
"android_key_collection_meeting" : "[redacted]"
"bs3_wallet_credits_header" : "Tegoed"
"android_pb_check_in_instructions_description_key_collection_no_zip" : "□□□□□□□□□□□□%2$s%1$s"
"android_bp_bs3_cta_book_now" : "Забронировать"
"ccp_apps_bs3_sanction_complete_cta" : "[redacted]"
"iux_security_active_sessions_title" : "□□□□"
"bs3_chargeback_checkbox_consent_links" : "Booking.com□{start_link1}□□□□{end_link1}□{start_link2}□□□□{end_link2}"
"android_bs3_card_details_ask_page_title" : "□□□□□"
"android_tpi_bs3_privacy_policy" : "□□□□□"
"bs3_select_payment_method_bancontact_app" : "Aplikacja"
"zma_notification_default_author_name" : "□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Aðgangsorð"
"android_rl_filter_private" : "פרטי"
"bs3_chargeback_checkbox_master_header" : "□□□□□□□□□□□□□□□"
"iux_security_active_sessions_cta" : "Изход"
"zma_notification_default_author_name" : "□□□"
"agency_installments_bs3_apps_title" : "□□□□□□□□"

POSSIBLE SECRETS
"android_rewards_bs3_active_promotion_block_remove_cta" : "Pašalinti"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passnøkkel"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■"
"android_rl_filter_private" : "Privāts"
"android_tpi_bs3_booking_conditions" : "■■■■■■■■■■■■■■"
"android_rewards_bs3_active_promotion_block_remove_cta" : "הסרה"
"android_bhpse_key_collect_method_on_loc_box" : "□□□□□□□□□□□□□□"
"android_promo_code_bs3_quick_tcs_link_tcs" : "□□□□"
"android_bhpse_key_collect_method_on_loc_meet" : "□□□□□□□□□□"
"android_promo_code_bs3_quick_tcs_link_tcs" : "Ehdot"
"android_tpi_bs3_booking_conditions" : "bokningsvillkoren"
"android_bhpse_key_collect_method_diff_loc_box_nozip" : "□□□□□□□□□□□□□□□□□%2$s%1$s"
"membership_hub_account_preferences_region_item_user" : "Personalização"
"iux_security_active_sessions_cta" : "Abmelden"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Pääsuvõti"
"android_bhpse_key_collect_method_cont_for_instr" : "□□□□□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parol"

POSSIBLE SECRETS
"android_promo_code_bs3_field_cta_apply" : "Aplicați"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"android_bhpse_key_collect_method_generic_other" : "[redacted]"
"android_tpi_bs3_general_terms" : "[redacted]"
"membership_hub_account_preferences_region_item_user" : "Personalizavimas"
"agency_installments_bs3_apps_title" : "[redacted]"
"android_bs3_card_details_ask_page_header" : "[redacted]"
"android_rewards_bs3_active_promo_block_book_before" : "%1$s[redacted]"
"android_bhpse_key_collect_method_diff_loc_recep" : "[redacted]%3$s%2$s%1$s[redacted]"
"membership_hub_account_preferences_region_item_user" : "Sérstillingar"
"iam_totp_authentication_screen_title" : "[redacted]"
"zma_notification_default_author_name" : "[redacted]"
"bs3_select_payment_method_bancontact_app" : "[redacted]"
"android_rewards_bs3_promo_code_field_replacing_promotion" : "[redacted]"
"android_rewards_bs3_active_promotion_block_remove_cta" : "[redacted]"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Wagwoord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"

POSSIBLE SECRETS
"android_rewards_bs3_active_promotion_block_add_promo_code_cta" : "□□□□□□□□□□□□□"
"android_private_beach" : "Privéstrand"
"android_bhpse_key_collect_method_generic_diff_nozip" : "□□□□□□□□%2$s%1$s□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Nenosiri"
"bui_icon_bathroom_private" : "□"
"iam_security_2fa_step2_copy_key_button" : "□□□□"
"android_bhpse_key_collect_method_diff_loc_meet_nozip" : "□□□□□□□□□□□□□%2$s%1$s"
"android_rl_filter_private" : "Özel"
"android_rl_filter_private" : "Peribadi"
"iux_security_active_sessions_success" : "□□□□□□□□□□□□□□□□□□□□□□"
"bs3_select_payment_method_bancontact_card" : "Carta"
"bs3_chargeback_checkbox_consent_links" : "Booking.com□{start_link1}□□□□□□□□□□{end_link1}□□□{start_link2}□□□□{end_link2}"
"android_promo_code_bs3_field_cta_apply" : "Applica"
"login_password" : "Lozinka"
"android_rewards_bs3_active_promotion_block_add_promo_code_cta" : "[redacted]"
"zma_notification_default_author_name" : "Потребител"
"ccp_apps_bs3_sanction_complete_cta" : "□□□□"
"bs3_saved_in_gallery" : "□□□□□□□□□□□□□□□□□□□"

POSSIBLE SECRETS
"android_bhpse_key_collect_contact_methods_week_before" : "□□□□□□□□□□□□□□□"
"ccp_apps_bs3_sanction_failed_no_link" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□validate@booking.com□"
"android_private_beach" : "□□□□□□□□□□"
"android_tpi_bs3_general_terms" : "□□□□"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"android_promo_code_bs3_field_cta_apply" : "Uygula"
"android_rewards_bs3_active_promotion_block_remove_cta" : "□□"
"ccp_apps_bs3_sanction_dob_entry" : "Syntymäaika"
"android_promo_code_bs3_field_cta_apply" : "Rakenda"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Удалить"
"icon2_private_bathroom" : "□"
"bs3_select_payment_method_bancontact_app" : "Aplikácia"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□□□"
"android_rewards_bs3_active_promotion_block_headline" : "□□□□"
"bs3_select_payment_method_bancontact_app" : "Programėlė"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Remover"
"iux_security_active_sessions_description" : "□□□□□□□□"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parole"
"android_bhpse_key_collect_contact_methods_month_before" : "□□□□□□□□□□□□□□□□□"
"android_pb_check_in_instructions_description_key_collection_zip" : "□□□□□□□□%1$s□%3$s/□□%2$s)"
"bs3_select_payment_method_bancontact_card" : "Kártya"
"bs3_select_payment_method_bancontact_app" : "Rakendus"
"icon2_key" : "□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Kaldır"
"android_identity_phone_verify_using_password" : "□□□□□□□□"
"android_promo_code_bs3_quick_tcs_link_faq" : "FAQ"
"icon_acuser" : "□"
"bs3_wallet_credits_header" : "■■■■■■■"
"bs3_wallet_credits_header" : "Créditos"
"android_bhpse_key_collect_method_diff_loc_meet_nozip" : "□□□□□□□□□□□□□□□%2$s%1$s□"
"android_bhpse_key_collect_contact_methods_sms" : "□□□□□□□□□□□□□□□□□□SMS□□□□□□□□□□□□"
"android_private_beach_free" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"iux_security_active_sessions_title" : "□□□□□□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "□□"
"login_password" : "Salasana"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Sandi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "პაროლი"
"ccp_apps_bs3_sanction_dob_title" : "□□□□□□□"
"bs3_wallet_credits_header" : "Saldo"
"bs3_chargeback_checkbox_master_header" : "□□□□□□□□□"
"android_bs3_card_details_ask_page_title" : "Kártyaadatok"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■"
"ccp_apps_bs3_sanction_dob_entry" : "Fæðingardagur"
"bs3_wallet_credits_header" : "□□"
"login_password" : "Contrasenya"
"login_password" : "Κωδικός"
"android_bp_key_highlights" : "Highlights"
"bs3_wallet_credits_header" : "Bonus"
"bs3_select_payment_method_bancontact_card" : "□□□"
"android_tpi_bs3_booking_conditions" : "□□□□"
"android_rl_filter_private" : "Privaatne"
"iux_security_active_sessions_cta" : "Iziet"
"android_rl_filter_private" : "Privé"

POSSIBLE SECRETS
"ccp_apps_bs3_sanction_country_entry" : "Asuinmaa"
"android_private_beach" : "Privatstrand"
"android_private_beach" : "Magánstrand"
"android_promo_code_bs3_field_cta_apply" : "Apply"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Remove"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Eliminar"
"bs3_chargeback_checkbox_consent_line" : "□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"membership_hub_account_preferences_region_item_user" : "Prispôsobenie"
"bs3_select_payment_method_bancontact_app" : "App"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passord"
"android_rl_filter_private" : "□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Sarbide-gakoa"
"android_key_collection_door_code" : "□□□□□□□□□□□□□□□□□□□□"
"iux_security_active_sessions_cta" : "Esci"
"bs3_select_payment_method_bancontact_card" : "□□□"
"android_private_beach_free" : "□□□□□□□□□□□□□□"
"iux_security_active_sessions_description" : "[redacted]"

POSSIBLE SECRETS
"zma_notification_default_author_name" : "Kullanıcı"
"sp_ext_cashback_expand_bs3_i_want" : "[redacted]"
"android_bp_key_highlights" : "□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Премахване"
"bs3_wallet_credits_header" : "الرصيد"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Pasahitza"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Avainkoodi"
"zma_notification_default_author_name" : "Bruger"
"android_rewards_bs3_active_promotion_block_headline" : "□□□□"
"zma_notification_default_author_name" : "Utilisateur"
"iux_security_active_sessions_description" : "□□□□□□□□"
"android_promo_code_bs3_field_cta_apply" : "Anvend"
"iux_security_active_sessions_cta" : "Вийти"
"android_pb_check_in_instructions_description_key_collection_zip" : "□□□□□□□□□□□□%3$s%1$s□□□□□□%2$s□"
"sp_ext_cashback_expand_bs3_i_want" : "□□□□□□□"
"android_bhpse_key_collect_contact_methods_call_them" : "□□□□□%1$s□□□□"
"iux_security_active_sessions_cta" : "Útskráning"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Noņemt"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passwort"
"android_rl_filter_private" : "Ιδιωτικό"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Hasło"
"sp_ext_cashback_expand_bs3_acknowledge" : "□□□

POSSIBLE SECRETS
"icon2_compass" : "□"
"android_rl_filter_private" : "Yksityinen"
"android_promo_code_bs3_field_cta_apply" : "I-apply"
"zma_notification_default_author_name" : "المستخدم"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android_rl_filter_private" : "Zasebno"
"membership_hub_account_preferences_region_item_user" : "Personalizacija"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"bs3_chargeback_checkbox_master_header" : "■■■■■

POSSIBLE SECRETS
"android_pb_check_in_instructions_description_key_collection_no_zip" : "□□□□□□□%1$s□%2$s□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Odstrániť"
"android_bhpse_key_collect_method_on_loc_recep" : "□□□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_generic_diff" : "□□□□□□□%3$s%2$s%1$s□"
"zma_notification_default_author_name" : "Uživatel"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android_bs3_card_details_ask_page_title" : "□□□□□"
"iux_security_active_sessions_cta" : "[redacted]"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contraseña"
"android_promo_code_bs3_field_cta_apply" : "Прилагане"
"android_rl_filter_private" : "Privativo"
"bs3_wallet_credits_header" : "Kredi"
"rewards_bs3_aob_rewardvalue_monetary" : "□□□□□□□%1$s□□□□"
"zma_notification_default_author_name" : "Käyttäjä"
"android_key_collection_lockbox" : "□□□□□□□□□□□□□□□

POSSIBLE SECRETS
"android_rewards_bs3_active_promotion_block_remove_cta" : "Видалити"
"iux_security_active_sessions_cta" : "התנתקות"
"iux_security_active_sessions_cta" : "□□"
"android_bp_bs3_cta_book_now" : "Rezervovať"
"android_bhpse_key_collect_method_diff_loc_meet" : "□□□□□□□□□□□□□□%3$s%2$s%1$s□"
"android_rl_filter_private" : "Собствено"
"attractions_apps_hackathon_ai_badges_private_group" : "■■■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Aðgangslykill"
"bs3_select_payment_method_bancontact_card" : "Kaart"
"agency_installments_bs3_apps_title" : "□□□□□□□□□□□□"
"android_bhpse_key_collect_method_generic_diff" : "□□□□□□□□%2$s%1$s□□□□%3$s□"
"login_password" : "Senha"
"bs3_select_payment_method_bancontact_card" : "Thẻ"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasinal"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■"
"ccp_apps_bs3_sanction_dob_entry" : "Birthdate"
"android_insurance_stti_covered_bullet_possessions_flights" : "1□□□□£1,500□□□□□□□"
"sp_ext_cashback_expand_bs3_acknowledge" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"

POSSIBLE SECRETS
"android_promo_code_bs3_quick_tcs_link_tcs" : "Warunki"
"android_promo_code_bs3_field_cta_apply" : "Применить"
"android_rl_filter_private" : "Private"
"bui_icon_account_user" : "□"
"bui_icon_key" : "□"
"iux_security_active_sessions_title" : "□□□□□□□□□□□"
"android_bhpse_key_collect_method_diff_loc_secret" : "□□□□□□□□□□□□%3$s%2$s%1$s□"
"ccp_apps_bs3_sanction_country_entry" : "Elukohariik"
"android_promo_code_bs3_field_cta_apply" : "Gunakan"
"sp_ext_cashback_expand_bs3_i_want" : "□□□□□□"
"android_bp_bs3_cta_book_now" : "□□□□"
"android_key_collection_lockbox" : "□□□□□□/□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"bs3_select_payment_method_bancontact_app" : "التطبيق"
"android_key_collection_reception" : "□□□□□□□□/□□□"
"android_cars_bc_tax_authority_website" : "□□□□□□"
"bs3_select_payment_method_bancontact_card" : "Kortelė"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■"
"sp_ext_cashback_expand_bs3_acknowledge" : "□□□□□□□□□□□□□□□□□□□

POSSIBLE SECRETS
"android_bhpse_key_collect_method_on_loc_box" : "□□□□□□□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_generic_diff_nozip" : "□□□□□□□□□%2$s□%1$s□□□□□□□□□"
"android_bhpse_key_collect_method_on_loc_recep" : "□□□□□□□□□□□□□□□□□□□□□□"
"android_key_collection_door_code" : "□□□□□□□□□□□□□□"
"android_bs3_card_details_ask_page_title" : "Kaardiandmed"
"android_bhpse_key_collect_method_on_loc_meet" : "□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Azonosítókulcs"
"android_rewards_bs3_active_promotion_block_headline" : "[redacted]"
"android_identity_phone_verify_using_password" : "□□□□□□□□□□□□"
"android_tpi_bs3_privacy_policy" : "trúnaðaryfirlýsinguna"
"android_bp_bs3_cta_book_now" : "□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"login_password" : "□□□□□"
"android_key_collection_door_code" : "[redacted]"
"android_bhpse_key_collect_method_what_if" : "□□□□□□□□□□"
"iux_security_active_sessions_cta" : "Sair"
"zma_notification_default_author_name" : "Benutzer"
"bs3_select_payment_method_bancontact_card" : "Kad"

POSSIBLE SECRETS
"attractions_apps_hackathon_ai_badges_private_group" : "Privégids"
"iux_security_active_sessions_cta" : "□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Odstrani"
"android_promo_code_bs3_field_cta_apply" : "□□"
"ccp_apps_bs3_sanction_country_entry" : "Bopælsland"
"bs3_select_payment_method_bancontact_card" : "Karta"
"android_rewards_bs3_promo_code_field_replacing_promotion" : "□□□□□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_prop_sends_instr" : "□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Klucz"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Zaporka"
"ccp_apps_bs3_sanction_dob_entry" : "Födelsedatum"
"login_password" : "□□□□"
"android_tpi_bs3_booking_conditions" : "bókunarskilmálana"
"membership_hub_account_preferences_region_item_user" : "التخصيص"
"android_bhpse_key_collect_method_diff_loc_meet" : "□%3$s□%2$s□%1$s□□□□□□□□□□□□□□□□"
"agency_installments_bs3_cell_subtitle" : "□□%2$s□□□□□□%1$s□□□"
"ccp_apps_bs3_sanction_dob_entry" : "□□□□"
"ccp_apps_bs3_sanction_dob_entry" : "□□□□"

POSSIBLE SECRETS
"bs3_select_payment_method_bancontact_app" : "Uygulama"
"login_password" : "[redacted]"
"android_key_collection_reception" : "□□□□□□□□□□□□□□□□□□□□□□"
"bs3_select_payment_method_bancontact_card" : "Kartica"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android_tpi_bs3_booking_conditions" : "boekingsvoorwaarden"
"membership_hub_account_preferences_region_item_user" : "Personalització"
"bs3_chargeback_checkbox_consent_line" : "□□□□□□□□□□□□"
"bs3_wallet_credits_header" : "Kredity"
"android_private_beach_unknown" : "□□□□□□□□□□□□□□□□□□□□"
"bs3_wallet_credits_header" : "□□□"
"android_pt_ticket_details_select_travel_pass" : "□□□□□□□□□□"
"account_portal_facebook_oauth_client_id" : "210068525731476"
"rewards_bs3_aob_points_codeapplied" : "□□□□□□□%1$s"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Supprimer"
"bs3_select_payment_method_bancontact_card" : "Cartão"
"android_promo_code_bs3_field_cta_apply" : "[redacted]"

POSSIBLE SECRETS
"android_private_beach" : "□□□□"
"android_bhpse_key_collect_method_diff_loc_box" : "□□□□□□□□□□□□□□□□□□□□%3$s%2$s%1$s□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Rimuovi"
"android_rewards_bs3_active_promotion_block_headline" : "□□□□□□□□□"
"android_bhpse_key_collect_method_what_if" : "■■■

POSSIBLE SECRETS
"bs3_select_payment_method_bancontact_app" : "Приложение"
"android_bhpse_key_collect_method_diff_loc_recep_nozip" : "□□□%2$s□%1$s□□□□□□□□□□□□□□□□□□□□"
"android_bhpse_key_collect_contact_methods_day_of_arrival" : "□□□□□□□□□□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Verwijderen"
"android_beachfront_private" : "□□□□□□□□□□□□□□□□□□□□□□"
"iux_security_active_sessions_description" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"android_bs3_card_details_ask_page_title" : "[redacted]"
"iux_security_active_sessions_title" : "[redacted]"
"android_bhpse_key_collect_contact_methods_week_before" : "□□□□□□□□□□□□□□"
"android_rl_filter_private" : "[redacted]"
"bs3_select_payment_method_bancontact_card" : "Картка"
"icon_secret" : "□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Ukloni"
"android_rewards_bs3_promo_code_field_replacing_promotion" : "□□□□□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"zma_notification_default_author_name" : "Pengguna"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"android_promo_code_bs3_quick_tcs_link_tcs" : "[redacted]"

POSSIBLE SECRETS
"android_rewards_bs3_active_promotion_block_remove_cta" : "Excluir"
"ccp_apps_bs3_sanction_dob_entry" : "□□□□"
"bs3_wallet_credits_header" : "Kreditt"
"android_rewards_bs3_active_promo_block_book_before" : "%1$s□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lozinka"
"android_bhpse_key_collect_method_diff_loc_secret_nozip" : "□□□□□□□□□□□□%2$s%1$s□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Iphasiwedi"
"android_bhpse_key_collect_contact_methods_email" : "□□□□□□□□□□□□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"android_bhpse_key_collect_contact_methods_phone" : "□□□□□□□□□□□□□"
"android_bp_key_highlights" : "[redacted]"
"attractions_apps_hackathon_ai_badges_private_group" : "Einkaleiðsögumaður"
"ccp_apps_bs3_sanction_dob_entry" : "[redacted]"
"icon_key" : "□"
"agency_installments_bs3_cell_subtitle" : "%2$s□□□%1$s□□□□□□□□□□□□□□"
"android_bhpse_key_collect_contact_methods_call_them" : "□□□□□□□□□□%1$s□□□□□□□□□□□□□□"
"android_rl_filter_private" : "□□□"
"android_promo_code_bs3_quick_tcs_link_faq" : "[redacted]"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Лозинка"
"android_bhpse_key_collect_contact_methods_phone" : "□□□□□□□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_diff_loc_recep_nozip" : "□□□□□□□□□□□□□□□%2$s%1$s□"
"android_bp_key_highlights" : "□□"
"login_password" : "Пароль"
"iux_security_active_sessions_success" : "□□□□□□□□□□□□□□□□□"
"shared_prefs_app_id_key_klarna_inapp_sdk" : "sdk-application-id"
"login_password" : "■■■■■■■"
"android_promo_code_bs3_field_cta_apply" : "Uporabi"
"android_rl_filter_private" : "Privatno"
"iux_security_active_sessions_success" : "□□□□□□□□□□□□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "■■■■■"
"bs3_select_payment_method_bancontact_app" : "Sovellus"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android_bh_key_pu_elsewhere" : "%1$s□□□□□□□□□□□□□□□□□□□□□%2$s%3$s"
"android_key_collection_meeting" : "□□□□□□□□□□□□□□"
"bs3_wallet_credits_header" : "Guthaben"
"android_promo_code_bs3_quick_tcs_link_faq" : "□□□□□□"

POSSIBLE SECRETS
"android_bs3_enter_your_promo_code" : "[redacted]"
"android_bs3_card_details_ask_page_title" : "Kaartgegevens"
"android_tpi_bs3_booking_conditions" : "□□□□"
"bs3_select_payment_method_bancontact_app" : "□□□"
"login_password" : "Şifre"
"android_bhpse_key_collect_method_diff_loc_box_nozip" : "□□□□□□□□□□□□□□□□□□□□%2$s%1$s□"
"membership_hub_account_preferences_region_item_user" : "□□□□□□"
"sp_ext_cashback_expand_bs3_acknowledge" : "[redacted]"
"zma_notification_default_author_name" : "[redacted]"
"membership_hub_account_preferences_region_item_user" : "Personalización"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "گذرکلید"
"android_rewards_bs3_active_promotion_block_add_promo_code_cta" : "□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"bs3_wallet_credits_header" : "Kredit"
"android_bs3_card_details_ask_page_title" : "Kartenangaben"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parool"
"attractions_apps_hackathon_ai_badges_private_group" : "□□□□"

POSSIBLE SECRETS
"android_rl_filter_private" : "Riêng"
"bs3_select_payment_method_bancontact_card" : "Tarjeta"
"android_promo_code_bs3_field_cta_apply" : "Piemērot"
"login_password" : "Wachtwoord"
"android_rewards_bs3_active_promotion_block_headline" : "Angebotsinfos"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Salasana"
"iux_security_active_sessions_cta" : "Uitloggen"
"android_promo_code_bs3_field_cta_apply" : "החל"
"bs3_select_payment_method_bancontact_app" : "אפליקציה"
"bs3_select_payment_method_bancontact_app" : "[redacted]"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android_bhpse_key_collect_method_diff_loc_secret" : "□□□%3$s□%2$s□%1$s□□□□□□□□□□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_on_loc_recep" : "[redacted]"
"bs3_select_payment_method_bancontact_app" : "Додаток"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Keluarkan"
"android_identity_platform_oauth_state" : "mobile-android!guest"
"bs3_select_payment_method_bancontact_app" : "Appli"
"bs3_chargeback_checkbox_master_header" : "□□□□□□□□□□□"

POSSIBLE SECRETS
"login_password" : "Lösenord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasenya"
"android_pb_check_in_instructions_description_key_collection_no_zip" : "□□%1$s□%2$s□□□□□□□□□□□□"
"iux_security_active_sessions_cta" : "Logout"
"android_cars_bc_tax_authority_website" : "□□□□□□"
"rewards_bs3_aob_points_codeapplied" : "□□□□□□□□%1$s"
"android_tpi_bs3_privacy_policy" : "□□□□"
"android_identity_debug_auth_state_button_save" : "Save"
"android_tpi_bs3_booking_conditions" : "□□□□"
"bs3_select_payment_method_bancontact_card" : "Kort"
"android_pt_one_ticket_one_day_pass" : "□□□□□1□□1□□□□"
"rewards_bs3_aob_rewardvalue_monetary" : "□□□□□□□□□□□□□%1$s□□□□□□□□"
"android_bhpse_key_collect_method_on_loc_meet" : "■■■

POSSIBLE SECRETS
"android_rewards_bs3_active_promotion_block_remove_cta" : "Entfernen"
"login_password" : "סיסמה"
"login_password" : "□□"
"android_pt_ticket_details_select_travel_pass" : "□□□□□"
"android_bhpse_key_collect_method_diff_loc_secret_nozip" : "□□□□□□□□□□□□□□%2$s%1$s"
"bs3_select_payment_method_bancontact_card" : "□□"
"android_tpi_bs3_booking_conditions" : "bookingvilkårene"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Odstranit"
"bs3_wallet_credits_header" : "קרדיט"
"android_bhpse_key_collect_method_generic_other" : "□□□□□□□"
"bs3_select_payment_method_bancontact_app" : "Aplikacija"
"android_promo_code_bs3_quick_tcs_link_tcs" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Slaptažodis"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parolă"
"android_bs3_card_details_ask_page_header" : "□□□□□□□□□□□"
"android_bhpse_key_collect_method_on_loc_box" : "[redacted]/[redacted]"
"login_password" : "Jelszó"
"android_bhpse_key_collect_contact_methods_phone" : "□□□□□□□□□□□□□□"

POSSIBLE SECRETS
"android_promo_code_bs3_field_cta_apply" : "Primeni"
"android_bhpse_key_collect_method_prop_sends_instr" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"iam_totp_authentication_screen_title" : "□□□□□□□"
"android_bhpse_key_collect_contact_methods_email" : "[redacted]"
"android_bhpse_key_collect_method_diff_loc_box" : "□□□%3$s□%2$s□%1$s□□□□□□□□□□□□□□□□□"
"android_tpi_bs3_privacy_policy" : "personvernerklæringen"
"login_password" : "Password"
"android_private_beach_paid" : "□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□"
"icon2_logo_secret_deal" : "□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "סיסמה"
"android_private_beach" : "□□□□"
"android_promo_code_bs3_field_cta_apply" : "Zastosuj"
"android_promo_code_bs3_field_cta_apply" : "Aplicar"
"android_promo_code_bs3_field_cta_apply" : "Застосувати"
"login_password" : "Hasło"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Αφαίρεση"
"android_promo_code_bs3_field_cta_apply" : "Käytä"

POSSIBLE SECRETS
"android_bs3_card_details_ask_page_header" : "[redacted]"
"bs3_select_payment_method_bancontact_card" : "[redacted]"
"android_bhpse_key_collect_contact_methods_week_before" : "□□□□□□□1□□□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Geslo"
"android_private_beach_unknown" : "□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Tanggalin"
"agency_installments_bs3_apps_title" : "□□□□□□□□"
"cm_sm_bs3_v2_a_android" : "□□□□□□□Booking.com□□□□□□□□□□□□□□□□□□□□□□□□□Booking.com□□□□□□□□□□"
"android_bs3_card_details_ask_page_title" : "Kortaupplýsingar"
"ccp_apps_bs3_sanction_country_entry" : "□□□"
"android_bs3_card_details_ask_page_title" : "Kortuppgifter"
"android_bp_key_highlights" : "Höjdpunkter"
"android_beachfront_private" : "□□□□□□□□□□□□□□□□□□□□□□□□"
"bs3_select_payment_method_bancontact_app" : "Aplicație"
"icon_private_shower" : "□"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□

POSSIBLE SECRETS
"android_private_beach" : "[redacted]"
"android_bhpse_key_collect_method_on_loc_secret" : "□□□□□□□□□□□□□"
"login_password" : "Salasõna"
"bs3_wallet_credits_header" : "Bonuss"
"android_insurance_stti_covered_bullet_possessions_flights" : "□□£1500□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "گذرواژه"
"bs3_select_payment_method_bancontact_card" : "כרטיס"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Senha"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Xóa"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android_bhpse_key_collect_method_what_if" : "□□□□□□□□□□□□□□□□□□□□"
"android_rl_filter_private" : "Pribado"
"login_password" : "Geslo"
"bs3_select_payment_method_bancontact_card" : "Kartu"
"android_promo_code_bs3_quick_tcs_link_tcs" : "Avtalevilkår"
"android_private_beach_paid" : "□□□□□□□□□□□□□□□□"
"zma_notification_default_author_name" : "User"
"android_promo_code_bs3_field_cta_apply" : "□□"

POSSIBLE SECRETS
"android_bhpse_key_collect_contact_methods_straight_after" : "[redacted]"
"android_bhpse_key_collect_contact_methods_day_of_arrival" : "□□□□□□□□□□□□□□□"
"zma_notification_default_author_name" : "Användare"
"android_bhpse_key_collect_method_cont_for_instr" : "□□□□□□□□□□□□□□□□□"
"android_tpi_bs3_legal_disclaimer_provider_not_match" : "□%s□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□%s□%s□□%s□Booking.com□□□□□□□□□□□□□□□□□□□□□□□□Booking.com□□□□□□□□□□□□□□"
"android_bs3_card_details_ask_page_title" : "□□□□□□"
"iux_security_active_sessions_cta" : "□□□□"
"android_key_collection_meeting" : "□□□□□□□□□□□□□□□□□□□□□□"
"zma_notification_default_author_name" : "Bruker"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Elimina"
"android_bhpse_key_collect_method_on_loc_code" : "□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Toegangssleutel"
"android_tpi_bs3_privacy_policy" : "privacybeleid"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Nyckel"
"bs3_wallet_credits_header" : "Бонуси"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Парола"
"android_tpi_bs3_privacy_policy" : "[redacted]"
"android_promo_code_bs3_field_cta_apply" : "□□"

POSSIBLE SECRETS
"android_rl_filter_private" : "□□"
"bs3_saved_in_gallery" : "□□□□□□□□□□□□□□□□□□"
"membership_hub_account_preferences_region_item_user" : "Brugertilpasning"
"attractions_apps_hackathon_ai_badges_private_group" : "□□□□□□□□"
"membership_hub_account_preferences_region_item_user" : "Personnalisation"
"iam_security_2fa_step2_copy_key_button" : "□□□□"
"ccp_apps_bs3_sanction_failed_no_link" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□validate@booking.com□□□□□□□□□□□□□□□□□□□"
"zma_notification_default_author_name" : "Usuario"
"android_promo_code_bs3_quick_tcs_link_tcs" : "□□□□□"
"android_bp_bs3_cta_book_now" : "■■■■■■"
"membership_hub_account_preferences_region_item_user" : "□□□□□□□"
"android_bhpse_key_collect_method_on_loc_secret" : "■■■■■■

POSSIBLE SECRETS
"android_tpi_bs3_legal_disclaimer_provider_not_match" : "□□□%s□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□%s□%s□□□%s□□□□□□□□□□□□□□□□Booking.com□□□□□□□□□□□□□□□□□□□

POSSIBLE SECRETS
"android_bhpse_key_collect_method_diff_loc_meet_nozip" : "□%2$s□%1$s□□□□□□□□□□□□□□□□"
"ccp_apps_bs3_sanction_complete_cta" : "□□□□□□□□"
"bs3_select_payment_method_bancontact_app" : "APP"
"android_bhpse_key_collect_method_cont_for_instr" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"iux_security_active_sessions_cta" : "Выйти"
"android_bhpse_key_collect_method_diff_loc_recep" : "□□□□□□□□□□□□□%2$s%1$s□□□□%3$s□"
"bui_icon_compass" : "□"
"membership_hub_account_preferences_region_item_user" : "Mukautusasetukset"
"android_bhpse_key_collect_contact_methods_day_of_arrival" : "□□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_generic_diff_nozip" : "□□□□□□□□□□%2$s%1$s"
"membership_hub_account_preferences_region_item_user" : "Personalizzazione"
"bs3_select_payment_method_bancontact_card" : "البطاقة"
"login_password" : "Parolă"
"android_promo_code_bs3_field_cta_apply" : "Taikyti"
"android_promo_code_bs3_quick_tcs_link_faq" : "□□□□□□□□"
"android_bhpse_key_collect_contact_methods_email" : "□□□□□□□□□□□□□□□"
"android_bhpse_key_collect_method_on_loc_code" : "■■■■■■■■■■■■■■■■"
"android_rewards_bs3_active_promotion_block_remove_cta" : "Fjern"

POSSIBLE SECRETS
"android_tpi_bs3_legal_disclaimer_provider_match" : "□□□%s□□□□□□□□□□□□□□□□□□□□□□□%s□%s□□□%s□□□□□□□□□□□□□□□□Booking.com□□□□□□□□□□□□□□□□□□□

POSSIBLE SECRETS
"bs3_select_payment_method_bancontact_app" : "Εφαρμογή"
"android_promo_code_bs3_field_cta_apply" : "Εφαρμογή"
"android_promo_code_bs3_field_cta_apply" : "Toepassen"
"android_bhpse_key_collect_method_generic_diff" : "□□□□□□□□%3$s□%2$s□%1$s□□□□□□□□"
"login_password" : "Парола"
"android_bhpse_key_collect_method_on_loc_code" : "□□□□□□□□□□□"
"zma_notification_default_author_name" : "■■■■■■"
"login_password" : "Passwort"
"android_bhpse_key_collect_contact_methods_day_of_arrival" : "■■■■■■

POSSIBLE SECRETS
"iam_totp_authentication_screen_title" : "□□□□□□□□"
"iux_security_active_sessions_cta" : "Desativar"
"bs3_wallet_credits_header" : "Бонусы"
"android_bp_key_highlights" : "Højdepunkter"
"android_private_beach_free" : "□□□□□□□□□□□□□□□□□"
"android_promo_code_bs3_field_cta_apply" : "□□"
"android_bs3_enter_your_promo_code" : "□□□□□□□□"
"android_rewards_bs3_active_promotion_block_remove_cta" : "□□"
"iam_security_2fa_step2_copy_key_button" : "□□□□□□□□□"
"android_bhpse_key_collect_method_prop_sends_instr" : "■■■

POSSIBLE SECRETS
"android_tpi_bs3_privacy_policy" : "privaatsusreeglitega"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Adgangsnøgle"
"bs3_select_payment_method_bancontact_card" : "Card"
"ccp_apps_bs3_sanction_country_entry" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"bs3_select_payment_method_bancontact_app" : "□"
"ccp_apps_bs3_sanction_country_entry" : "Búsetuland"
04BED5AF16EA3F6A4F62938C4631EB5AF7BDBCDBC31667CB477A1A8EC338F94741669C976316DA6321
26617408020502170632287687167233609607298591687569731477066713684188029449964278084915450806277719023520942412250655586621571135455709168141616373158959998 46
36DF0AAFD8B8D7597CA10520D04B
e4437ed6010e88286f547fa90abfe4c42212
7D5A0975FC2C3057EEF67530417AFFE7FB8055C126DC5C6CE94A4B44F330B5D9
8CB91E82A3386D280F5D6F7E50E641DF152F7109ED5456B31F166E6CAC0425A7CF3AB6AF6B7FC3103B883202E9046565
114ca50f7a8e2f3f657c1108d9d44cfd8
41ECE55743711A8C3CBF3783CD08C0EE4D4DC440D4641A8F366E550DFDB3BB67
36134250956749795798585127919587881956611106672985015071877198253568414405109

POSSIBLE SECRETS
3081a0adab3018d57165e6dd24074bdbac640f6dbe21a9e24d3474a87ebf38b8
c39c6c3b3a36d7701b9c71a1f5804ae5d0003f4
A335926AA319A27A1D00896A6773A4827ACDAC73
047B6AA5D85E572983E6FB32A7CDEBC14027B6916A894D3AEE7106FE805FC34B44
b0b4417601b59cbc9d8ac8f935cadaec4f5fbb2f23785609ae466748d9b5a536
aa87ca22be8b05378eb1c71ef320ad746e1d3b628ba79b9859f741e082542a385502f25dbf55296c3a545e3872760ab7
70B5E1E14031C1F70BBEFE96BDDE66F451754B4CA5F48DA241F331AA396B8D1839A855C1769B1EA14BA53308B5E2723724E090E02DB9
e2f856b9f9a4fd4cb2795aeaf83268e4bff189aaec05d691ffde76e075b82648
56c8ea595c439f4f70d21d9755ea39fc
6dd6d73f298f90c00d543121f76165a134c42cfde0bcdac3c99e25226f9e3c79
27580193559959705877849011840389048093056905856361568521428707301988689241309860865136260764883745107765439761230575
bb85691939b869c1d087f601554b96b80cb4f55b35f433c2
3617de4a96262c6f5d9e98bf9292dc29f8f41dbd289a147ce9da3113b5f0b8c00a60b1ce1d7e819d7a431d7c90ea0e5f
714114B762F2FF4A7912A6D2AC58B9B5C2FCFE76DAEB7129
115792089237316195423570985008687907852837564279074904382605163141518161494337
0fc52b42fcb131cbcb78bb72f8b7e33a22d939fa7153ba5f75daeb996bf20e9d
027d29778100c65a1da1783716588dce2b8b4aee8e228f1896

POSSIBLE SECRETS
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE65381FFFFFFFFFFFFFFFF
5EEEFCA380D02919DC2C6558BB6D8A5D
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A93AD2CAFFFFFFFFFFFFFFFF
000E0D4D696E6768756151750CC03A4473D03679
5363ad4cc05c30e0a5261c028812645a122e22ea20816678df02967c1b23bd72
0409487239995A5EE76B55F9C2F098A89CE5AF8724C0A23E0E0FF77500
1854BEBDC31B21B7AEFC80AB0ECD10D5B1B3308E6DBF11C1
5f0be9c2-1aff-4f04-aaf7-721439bad393
5ac635d8aa3a93e7b3ebbd55769886bc651d06b0cc53b0f63bce3c3e27d2604b
383F2407-53F9-475B-87BD-6D2F1CE12105
dc39751b-10af-4fcb-bd9e-622254a99dce
9DEF3CAFB939277AB1F12A8617A47BBBDBA51DF499AC4C80BEEEA9614B19CC4D5F4F5F556E27CBDE51C6A94BE4607A291558903BA0D0F84380B655BB9A22E8DCDF028A7CEC67F0D08134B1C8B97989149B609E0BE3BAB63D47548381DBC5B1FC764E3F4B53DD9DA1158BFD3E2B9C8CF56EDF019539349627DB2FD53D24B7C48665772E437D6C7F8CE442734AF7CCB7AE837C264AE3A9BEB87F8A2FE9B8B5292E5A021FFF5E91479E8CE7A28C2442C6F315180F93499A234DCF76E3FED135F9BB
04A3E8EB3CC1CFE7B7732213B23A656149AFA142C47AAFBC2B79A191562E1305F42D996C823439C56D7F7B22E14644417E69BCB6DE39D027001DABE8F35B25C9BE
5AC635D8AA3A93E7B3EBBD55769886BC651D06B0CC53B0F63BCE3C3E27D2604B

POSSIBLE SECRETS
FFFFFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD65612433F51F5F066ED0856365553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFFA886B4238611FCFDCDE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE598CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C4484E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B66C62E37FFFFFFFFFFFFFFFF
92974c6802419e4d18b5ec536cbfa167b8e8eff09ec4c8510a5b95750b1e0c82
10E723AB14D696E6768756151756FEBF8FCB49A9
617fab6832576cbbfed50d99f0249c3fee58b94ba0038c7ae84c8c832f2c
046AB1E344CE25FF3896424E7FFE14762ECB49F8928AC0C76029B4D5800374E9F5143E568CD23F3F4D7C0D4B1E41C8CC0D1C6ABD5F1A46DB4C
3086d221a7d46bcde86c90e49284eb153dab
04B199B13B9B34EFC1397E64BAEB05ACC265FF2378ADD6718B7C7C1961F0991B842443772152C9E0AD
033C258EF3047767E7EDE0F1FDAA79DAEE3841366A132E163ACED4ED2401DF9C6BDCDE98E8E707C07A2239B1B097
03188da80eb03090f67cbf20eb43a18800f4ff0afd82ff1012
24B7B137C8A14D696E6768756151756FD0DA2E5C
68A5E62CA9CE6C1C299803A6C1530B514E182AD8B0042A59CAD29F43
9B9F605F5A858107AB1EC85E6B41C8AACF846E86789051D37998F7B9022D7598
df536f84-c0f6-4952-beac-3fe3af90c3f9
22123dc2395a05caa7423daeccc94760a7d462256bd56916
7CBBBCF9441CFAB76E1890E46884EAE321F70C0BCB4981527897504BEC3E36A62BCDFA2304976540F6450085F2DAE145C22553B465763689180EA2571867423E
db92371d2126e9700324977504e8c90e

POSSIBLE SECRETS
01AF286BCA1AF286BCA1AF286BCA1AF286BCA1AF286BC9FB8F6B85C556892C20A7EB964FE7719E74F490758D3B
F5CE40D95B5EB899ABBCCFF5911CB8577939804D6527378B8C108C3D2090FF9BE18E2D33E3021ED2EF32D85822423B6304F726AA854BAE07D0396E9A9ADDC40F
040060F05F658F49C1AD3AB1890F7184210EFD0987E307C84C27ACCFB8F9F67CC2C460189EB5AAAA62EE222EB1B35540CFE902374601E369050B7C4E42ACBA1DACBF04299C3460782F918EA427E6325165E9EA10E3DA5F6C42E9C55215AA9CA27A5863EC48D8E0286B
07A11B09A76B562144418FF3FF8C2570B8
EEAF0AB9ADB38DD69C33F80AFA8FC5E86072618775FF3C0B9EA2314C9C256576D674DF7496EA81D3383B4813D692C6E0E0D5D8E250B98BE48E495C1D6089DAD15DC7D7B46154D6B6CE8EF4AD69B15D4982559B297BCF1885C529F566660E57EC68EDBC3C05726CC02FD4CBF4976EAA9AFD5138FE8376435B9FC61D2FC0EB06E3
37571800257700204635455072244911836035944551347697624866945677796155444774405563166912344050129455395621444445372894285225856667291965808101243442775783767 84
d80f18e8081b624cc64985f87f70118f1702985d2e10dbc985ee7be334fd3c7d
90066455B5CFC38F9CAA4A48B4281F292C260FEEF01FD61037E56258A7795A1C7AD46076982CE6BB956936C6AB4DCFE05E6784586940CA544B9B2140E1EB523F009D20A7E7880E4E5BFA690F1B9004A27811CD9904AF70420EEFD6EA11EF7DA129F58835FF56B89FAA637BC9AC2EFAAB903402229F491D8D3485261CD068699B6BA58A1DDBBEF6DB51E8FE34E8A78E542D7BA351C21EA8D8F1D29F5D5D15939487E27F4416B0CA632C59EFD1B1EB66511A5A0FBF615B766C5862D0BD8A3FE7A0E0DA0FB2FE1FCB19E8F9996A8EA0FCCDE538175238FC8B0EE6F29AF7F642773EBE8CD5402415A01451A840476B2FCEB0E388D30D4B376C37FE401C2A2C2F941DAD179C540C1C8CE030D460C4D983BE9AB0B20F69144C1AE13F9383EA1C08504FB0BF321503EFE43488310DD8DC77EC5B8349B8BFE97C2C560EA878DE87C11E3D597F1FEA742D73EEC7F37BE43949EF1A0D15C3F3E3FC0A8335617055AC91328EC22B50FC15B941D3D1624CD88BC25F3E941FDDC6200689581BFEC416B4B2CB73
1E589A8595423412134FAA2DBDEC95C8D8675E58
E95E4A5F737059DC60DF5991D45029409E60FC09
0307AF69989546103D79329FCC3D74880F33BBE803CB
DC9203E514A721875485A529D2C722FB187BC8980EB866644DE41C68E143064546E861C0E2C9EDD92ADE71F46FCF50FF2AD97F951FDA9F2A2EB6546F39689BD3
71169be7330b3038edb025f1d0f9
678471b27a9cf44ee91a49c5147db1a9aaf244f05a434d6486931d2d14271b9e35030b71fd73da179069b32e2935630e1c2062354d0da20a6c416e50be794ca4

POSSIBLE SECRETS
03375D4CE24FDE434489DE8746E71786015009E66E38A926DD
fb306c43-64ec-49cb-ab90-0e9de01ec978
e17e6868-3882-41e3-be53-9aace5142a32
1C31E768AA674E7C96EC9C9F7749B7E6
0418DE98B02DB9A306F2AFCD7235F72A819B80AB12EBD653172476FECD462AABFFC4FF191B946A5F54D8D0AA2F418808CC25AB056962D30651A114AFD2755AD336747F93475B7A1FCA3B88F2B6A208CCFE469408584DC2B2912675BF5B9E582928
00689918DBEC7E5A0DD6DFC0AA55C7
a335926aa319a27a1d00896a6773a4827acdac73
fe0e87005b4e83761908c5131d552a850b3f58b749c37cf5b84d6768
B3312FA7E23EE7E4988E056BE3F82D19181D9C6EFE8141120314088F5013875AC656398D8A2ED19D2A85C8EDD3EC2AEF
12511cfe811d0f4e6bc688b4d
010092537397ECA4F6145799D62B0A19CE06FE26AD
b3fb3400dec5c4adceb8655d4c94
ebcf9808-de10-4de3-a5c1-db19269f8eed
AADD9DB8DBE9C48B3FD4E6AE33C9FC07CB308DB3B3C9D20ED6639CCA703308717D4D9B009BC66842AECDA12AE6A380E62881FF2F2D82C68528AA6056583A48F3
c49d360886e704936a6678e1139d26b7819f7e90
4D696E676875615175985BD3ADBADA21B43A97E2
bcd5e85d-7e61-4e76-be2e-888a447ee823

POSSIBLE SECRETS
32010857077C5431123A46B808906756F543423E8D27877578125778AC76
7d064354-026e-4240-82a8-148a3dc0dbb0
C302F41D932A36CDA7A3462F9E9E916B5BE8F1029AC4ACC1
003088250CA6E7C7FE649CE85820F7
103FAEC74D696E676875615175777FC5B191EF30
2866537B676752636A68F56554E12640276B649EF7526267
038D16C2866798B600F9F08BB4A8E860F3298CE04A5798
E87579C11079F43DD824993C2CEE5ED3
96341f1138933bc2f503fd44
RmxpZ2h0cyAtIEZBUSAtIFNlbGYgVHJhbnNmZXI
7F519EADA7BDA81BD826DBA647910F8C4B9346ED8CCDC64E4B1ABD11756DCE1D2074AA263B88805CED70355A33B471EE
d602c1cd-b98f-4bdd-a20b-51866127435b
8CB91E82A3386D280F5D6F7E50E641DF152F7109ED5456B412B1DA197FB71123ACD3A729901D1A71874700133107EC50
2AA058F73A0E33AB486B0F610410C53A7F132310
6b8cf07d4ca75c88957d9d67059037a4
410583637251521421293261297800472684091144410159937255548352563140394674012 91
28E9FA9E9D9F5E344D5A9E4BCF6509A7F39789F515AB8F92DDBCBD414D940E93
9B9F605F5A858107AB1EC85E6B41C8AA582CA3511EDDFB74F02F3A6598980BB9

POSSIBLE SECRETS
5667676A654B20754F356EA92017D946567C46675556F19556A04616B567D223A5E05656FB549016A96656A557
6b016c3bdcf18941d0d654921475ca71a9db2fb27d1d37796185c2942c0a
b3312fa7e23ee7e4988e056be3f82d19181d9c6efe8141120314088f5013875ac656398d8a2ed19d2a85c8edd3ec2aef
D7C134AA264366862A18302575D0FB98D116BC4B6DDEBCA3A5A7939F
6b8cf07d4ca75c88957d9d670591
29C41E568B77C617EFE5902F11DB96FA9613CD8D03DB08DA
0405F939258DB7DD90E1934F8C70B0DFEC2EED25B8557EAC9C80E2E198F8CDBECD86B1205303676854FE24141CB98FE6D4B20D02B4516FF702350EDDB0826779C813F0DF45BE8112F4
3086d221a7d46bcde86c90e49284eb15
04C0A0647EAAB6A48753B033C56CB0F0900A2F5C4853375FD614B690866ABD5BB88B5F4828C1490002E6773FA2FA299B8F
2472E2D0197C49363F1FE7F5B6DB075D52B6947D135D8CA445805D39BC345626089687742B6329E70680231988
0452DCB034293A117E1F4FF11B30F7199D3144CE6DFEAFFEF2E331F296E071FA0DF9982CFEA7D43F2E
686479766013060971498190079908139321726943530014330540939446345918554318339765605212255964066145455497729631139148085803712198799971664381257402829111505715 1
021085E2755381DCCCE3C1557AFA10C2F0C0C2825646C5B34A394CBCFA8BC16B22E7E789E927BE216F02E1FB136A5F
25FBC363582DCEC065080CA8287AAFF09788A66DC3A9E
04A8C7DD22CE28268B39B55416F0447C2FB77DE107DCD2A62E880EA53EEB62D57CB4390295DBC9943AB78696FA504C11
7d7374168ffe3471b60a857686a19475d3bfa2ff
91E38443A5E82C0D880923425712B2BB658B9196932E02C78B2582FE742DAA28

POSSIBLE SECRETS
020ffa963cdca8816ccc33b8642bedf905c3d358573d3f27fbbd3b3cb9aaaf
h0JkGwAIB0gIkMDgwNzEzZTItYjJiNC00ZmM4LWJhNzYtMDE4NzI3NjFjMDk02AIE4AIB
02F40E7E2221F295DE297117B7F3D62F5C6A97FFCB8CEFF1CD6BA8CE4A9A18AD84FFABBD8EFA59332BE7AD6756A66E294AFD185A78FF12AA520E4DE739BACA0C7FFEFF7F2955727A
034034034

POSSIBLE SECRETS
4f6f7c08-309a-4303-b7ad-eb167ee374bb
64210519e59c80e70fa7e9ab72243049feb8deecc146b9b1
e7b8f7a1-4c5d-4a2f-8e7d-3b9a1f4c5d6e
6A941977BA9F6A435199ACFC51067ED587F519C5ECB541B8E44111DE1D40
9760508f15230bccb292b982a2eb840bf0581cf5
108576C80499DB2FC16EDDF6853BBB278F6B6FB437D9
88342353238919216479164875036030888531447659725296036279245086060969983 9
A9FB57DBA1EEA9BC3E660A909D838D726E3BF623D52620282013481D1F6E5377
AADD9DB8DBE9C48B3FD4E6AE33C9FC07CB308DB3B3C9D20ED6639CCA703308717D4D9B009BC66842AECDA12AE6A380E62881FF2F2D82C68528AA6056583A48F0
d09e8800291cb85396cc6717393284aaa0da64ba
b49eb43118f247acbf664b77e2c429654fb03a73f6593de72db462b53f917644
027B680AC8B8596DA5A4AF8A19A0303FCA97FD7645309FA2A581485AF6263E313B79A2F5
2580F63CCFE44138870713B1A92369E33E2135D266DBB372386C400B
11839296a789a3bc0045c8a5fb42c7d1bd998f54449579b446817afbd17273e662c97ee72995ef42640c550b9013fad0761353c7086a272c24088be94769fd16650
faa1ff61-a094-4a76-a488-6a642085598e
2E2F85F5DD74CE983A5C4237229DAF8A3F35823BE
7167EFC92BB2E3CE7C8AAAFF34E12A9C557003D7C73A6FAF003F99F6CC8482E540F7
10D9B4A3D9047D8B154359ABFB1B7F5485B04CEB868237DDC9DEDA982A679A5A919B626D4E50A8DD731B107A9962381FB5D807BF2618

POSSIBLE SECRETS
0713612DCDDCB40AAB946BDA29CA91F73AF958AFD9
5DDA470ABE6414DE8EC133AE28E9BBD7FCEC0AE0FFF2
0238af09d98727705120c921bb5e9e26296a3cdcf2f35757a0eafd87b830e7
Y29tLmhleXRhcC5vcGVuaWQuSU9wZW5JRA==
04161FF7528B899B2D0C28607CA52C5B86CF5AC8395BAFEB13C02DA292DDED7A83
e88e4809-af3c-4d37-8643-333a04bbc037
0228F9D04E900069C8DC47A08534FE76D2B900B7D7EF31F5709F200C4CA205
03E5A88919D7CAFCBF415F07C2176573B2
b368b110e3b565fe97c91f786e11bc48754cc8e4e6f21d8a94a68ac6ad67aaaf
0017858FEB7A98975169E171F77B4087DE098AC8A911DF7B01
94bf946c-4130-4d26-8af2-346db328963d
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A92108011A723C12A787E6D788719A10BDBA5B2699C327186AF4E23C1A946834B6150BDA2583E9CA2AD44CE8DBBBC2DB04DE8EF92E8EFC141FBECAA6287C59474E6BC05D99B2964FA090C3A2233BA186515BE7ED1F612970CEE2D7AFB81BDD762170481CD0069127D5B05AA993B4EA988D8FDDC186FFB7DC90A6C08F4DF435C93402849236C3FAB4D27C7026C1D4DCB2602646DEC9751E763DBA37BDF8FF9406AD9E530EE5DB382F413001AEB06A53ED9027D831179727B0865A8918DA3EDBEBCF9B14ED44CE6CBACED4BB1BDB7F1447E6CC254B332051512BD7AF426FB8F401378CD2BF5983CA01C64B92ECF032EA15D1721D03F482D7CE6E74FEF6D55E702F46980C82B5A84031900B1C9E59E7C97FBEC7E8F323A97A7E36CC88BE0F1D45B7FF585AC54BD407B22B4154AACC8F6D7EBF48E1D814CC5ED20F8037E0A79715EEF29BE32806A1D58BB7C5DA76F550AA3D8A1FBFF0EB19CCB1A313D55CDA56C9EC2EF29632387FE8D76E3C0468043E8F663F4860EE12BF2D5B0B7474D6E694F91E6DCC4024FFFFFFFFFFFFFFFF
10686D41FF744D4449FCCF6D8EEA03102E6812C93A9D60B978B702CF156D814EF
040081BAF91FDF9833C40F9C181343638399078C6E7EA38C001F73C8134B1B4EF9E150

POSSIBLE SECRETS
07A526C63D3E25A256A007699F5447E32AE456B50E
D35E472036BC4FB7E13C785ED201E065F98FCFA5B68F12A32D482EC7EE8658E98691555B44C59311
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A92108011A723C12A787E6D788719A10BDBA5B2699C327186AF4E23C1A946834B6150BDA2583E9CA2AD44CE8DBBBC2DB04DE8EF92E8EFC141FBECAA6287C59474E6BC05D99B2964FA090C3A2233BA186515BE7ED1F612970CEE2D7AFB81BDD762170481CD0069127D5B05AA993B4EA988D8FDDC186FFB7DC90A6C08F4DF435C93402849236C3FAB4D27C7026C1D4DCB2602646DEC9751E763DBA37BDF8FF9406AD9E530EE5DB382F413001AEB06A53ED9027D831179727B0865A8918DA3EDBEBCF9B14ED44CE6CBACED4BB1BDB7F1447E6CC254B332051512BD7AF426FB8F401378CD2BF5983CA01C64B92ECF032EA15D1721D03F482D7CE6E74FEF6D55E702F46980C82B5A84031900B1C9E59E7C97FBEC7E8F323A97A7E36CC88BE0F1D45B7FF585AC54BD407B22B4154AACC8F6D7EBF48E1D814CC5ED20F8037E0A79715EEF29BE32806A1D58BB7C5DA76F550AA3D8A1FBFF0EB19CCB1A313D55CDA56C9EC2EF29632387FE8D76E3C0468043E8F663F4860EE12BF2D5B0B7474D6E694F91E6DBE115974A3926F12FEE5E438777CB6A932DF8CD8BEC4D073B931BA3BC832B68D9DD300741FA7BF8AFC47ED2576F6936BA424663AAB639C5AE4F5683423B4742BF1C978238F16CBE39D652DE3FDB8BEFC848AD922222E04A4037C0713EB57A81A23F0C73473FC646CEA306B4BCBC8862F8385DDFA9D4B7FA2C087E879683303ED5BDD3A062B3CF5B3A278A66D2A13F83F44F82DDF310EE074AB6A364597E899A0255DC164F31CC50846851DF9AB48195DED7EA1B1D510BD7EE74D73FAF36BC31ECFA268359046F4EB879F924009438B481C6CD7889A002ED5EE382BC9190DA6FC026E479558E4475677E9AA9E3050E2765694DFC81F56E880B96E7160C980DD98EDD3DFFFFFFFFFFFFFFFFF
39402006196394479212279040100143613805079739270465446667946905279627659399113263569398956308152294913554433653942643
5c6685795fc64b5ba30e0c2e6901547a
04AA87CA22BE8B05378EB1C71EF320AD746E1D3B628BA79B9859F741E082542A385502F25DBF55296C3A545E3872760AB73617DE4A96262C6F5D9E98BF9292DC29F8F41DBD289A147CE9DA3113B5F0B8C00A60B1CE1D7E819D7A431D7C90EA0E5F
040503213F78CA44883F1A3B8162F188E553CD265F23C1567A16876913B0C2AC245849283601CCDA380F1C9E318D90F95D07E5426FE87E45C0E8184698E45962364E34116177DD2259
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AACAA68FFFFFFFFFFFFFFFF
36edd577-b5f0-42a9-9eb9-7797e8166782
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112319
9B9F605F5A858107AB1EC85E6B41C8AACF846E86789051D37998F7B9022D759B

POSSIBLE SECRETS
e8b4011604095303ca3b8099982be09fcb9ae616
0100FAF51354E0E39E4892DF6E319C72C8161603FA45AA7B998A167B8F1E629521
8D91E471E0989CDA27DF505A453F2B7635294F2DDF23E3B122ACC99C9E9F1E14
127971af8721782ecffa3
0d89f14a-263d-43d4-947f-62c8f6f01d3a
3d84f26c12238d7b4f3d516613c1759033b1a5800175d0b1
32879423AB1A0375895786C4BB46E9565FDE0B5344766740AF268ADB32322E5C
74D59FF07F6B413D0EA14B344B20A2DB049B50C3
0429A0B6A887A983E9730988A68727A8B2D126C44CC2CC7B2A6555193035DC76310804F12E549BDB011C103089E73510ACB275FC312A5DC6B76553F0CA
BDDB97E555A50A908E43B01C798EA5DAA6788F1EA2794EFCF57166B8C14039601E55827340BE
eyJ1IjoibWFwYm94LWJvb2tpbmciLCJhIjoiY2o5OGZxOGE0MGpzazJ3dDQ3ZnBxZmk2NiJ9
04925BE9FB01AFC6FB4D3E7D4990010F813408AB106C4F09CB7EE07868CC136FFF3357F624A21BED5263BA3A7A27483EBF6671DBEF7ABB30EBEE084E58A0B077AD42A5A0989D1EE71B1B9BC0455FB0D2C3
0620048D28BCBD03B6249C99182B7C8CD19700C362C46A01
0400FAC9DFCBAC8313BB2139F1BB755FEF65BC391F8B36F8F8EB7371FD558B01006A08A41903350678E58528BEBF8A0BEFF867A7CA36716F7E01F81052
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA237327FFFFFFFFFFFFFFFF
D7C134AA264366862A18302575D1D787B09F075797DA89F57EC8C0FF
c6858e06b70404e9cd9e3ecb662395b4429c648139053fb521f828af606b4d3dbaa14b5e77efe75928fe1dc127a2ffa8de3348b3c1856a429bf97e7e31c2e5bd66

POSSIBLE SECRETS
D09E8800291CB85396CC6717393284AAA0DA64BA
E95E4A5F737059DC60DFC7AD95B3D8139515620C
9ba48cba5ebcb9b6bd33b92830b2a2e0e192f10a
9162fbe73984472a0a9d0590
393C7F7D53666B5054B5E6C6D3DE94F4296C0C599E2E2E241050DF18B6090BDC90186904968BB
e43bb460f0b80cc0c0b075798e948060f8321b7d
1b9fa3e518d683c6b65763694ac8efbaec6fab44f2276171a42726507dd08add4c3b3f4c1ebc5b1222ddba077f722943b24c3edfa0f85fe24d0c8c01591f0be6f63
QrMgt8GGYI6T52ZY5AnhtxkLzb8egpFn3j5JELI8H6wtACbUnZ5cc3aYTsTRbmkAkRJeYbtx92LPBWm7nBO9UIl7y5i5MQNmUZNf5QENurR5tGyo7yJ2G0MBjWvy6iAtlAbacKP0SwOUeUWx5dsBdyhxa7Id1APtybSdDgicBDuNjI0mlZFUzZSS9dmN8IBD0WTVOMz0pRZbR3cysomRXOO1ghqjJdTcyDIxzpNAEszN8RMGjrzyU7Hjbmwi6YNK
8d5155894229d5e689ee01e6018a237e2cae64cd
c76b9b6a188d43a09957c13e835bc6a2fe7ac772-
7A556B6DAE535B7B51ED2C4D7DAA7A0B5C55F380
C2173F1513981673AF4892C23035A27CE25E2013BF95AA33B22C656F277E7335
04B6B3D4C356C139EB31183D4749D423958C27D2DCAF98B70164C97A2DD98F5CFF6142E0F7C8B204911F9271F0F3ECEF8C2701C307E8E4C9E183115A1554062CFB
77E2B07370EB0F832A6DD5B62DFC88CD06BB84BE
026108BABB2CEEBCF787058A056CBE0CFE622D7723A289E08A07AE13EF0D10D171DD8D
0401A57A6A7B26CA5EF52FCDB816479700B3ADC94ED1FE674C06E695BABA1D
b869c82b35d70e1b1ff91b28e37a62ecdc34409b

POSSIBLE SECRETS
1053CDE42C14D696E67687561517533BF3F83345
07B6882CAAEFA84F9554FF8428BD88E246D2782AE2
b9b2a04c-6f80-435e-9346-b98e8e65fe6d
cc22d6dfb95c6b25e49c0d6364a4e5980c393aa21668d953
10B51CC12849B234C75E6DD2028BF7FF5C1CE0D991A1
b70e0cbd6bb4bf7f321390b94a03c1d356c21122343280d6115c1d21
295F9BAE7428ED9CCC20E7C359A9D41A22FCCD9108E17BF7BA9337A6F8AE9513
115792089210356248762697446949407573529996955224135760342422259061068512044369
32670510020758816978083085130507043184471273380659243275938904335757337482424
0236B3DAF8A23206F9C4F299D7B21A9C369137F2C84AE1AA0D
D35E472036BC4FB7E13C785ED201E065F98FCFA6F6F40DEF4F92B9EC7893EC28FCD412B1F1B32E24
00FDFB49BFE6C3A89FACADAA7A1E5BBC7CC1C2E5D831478814
43FC8AD242B0B7A6F3D1627AD5654447556B47BF6AA4A64B0C2AFE42CADAB8F93D92394C79A79755437B56995136
4230baa077b401374d0fc012375047e79ea0790d58d095ef18d97d95470c738d
26DC5C6CE94A4B44F330B5D9BBD77CBF958416295CF7E1CE6BCCDC18FF8C07B6
90EAF4D1AF0708B1B612FF35E0A2997EB9E9D263C9CE659528945C0D
403f14ad2f0e5eb3c4f3a0bcd5c1592cc4492662ad53191c92905255d4990656
662C61C430D84EA4FE66A7733D0B76B7BF93EBC4AF2F49256AE58101FEE92B04

POSSIBLE SECRETS
4B337D934104CD7BEF271BF60CED1ED20DA14C08B3BB64F18A60888D
3E1AF419A269A5F866A7D3C25C3DF80AE979259373FF2B182F49D4CE7E1BBC8B
FFFFFFFE0000000075A30D1B9038A115
8CB91E82A3386D280F5D6F7E50E641DF152F7109ED5456B412B1DA197FB71123ACD3A729901D1A71874700133107EC53
340E7BE2A280EB74E2BE61BADA745D97E8F7C300
0108B39E77C4B108BED981ED0E890E117C511CF072
255705fa2a306654b1f4cb03d6a750a30c250102d4988717d9ba15ab6d3e
258EAFA5-E914-47DA-95CA-C5AB0DC85B11
1AB597A5B4477F59E39539007C7F977D1A567B92B043A49C6B61984C3FE3481AAF454CD41BA1F051626442B3C10
040D9029AD2C7E5CF4340823B2A87DC68C9E4CE3174C1E6EFDEE12C07D58AA56F772C0726F24C6B89E4ECDAC24354B9E99CAA3F6D3761402CD
687D1B459DC841457E3E06CF6F5E2517B97C7D614AF138BCBF85DC806C4B289F3E965D2DB1416D217F8B276FAD1AB69C50F78BEE1FA3106EFB8CCBC7C5140116
484395612939064517590525852527979142027629495260417479958440807170824046352 86
d08595f3-1009-42df-9102-e67c50b60e50
6b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296
07ff9b7aeeff969173c45b285fe0fecdbaae244576ff7a2796a36f1c0c11adb4
51953eb9618e1c9a1f929a21a0b68540eea2da725b99b315f3b8b489918ef109e156193951ec7e937b1652c0bd3bb1bf073573df883d2c34f1ef451fd46b503f00
0095E9A9EC9B297BD4BF36E059184F
33baae15-2023-4174-92e5-d42297aaf48a

POSSIBLE SECRETS
C8619ED45A62E6212E1160349E2BFA844439FAFC2A3FD1638F9E
0403F0EBA16286A2D57EA0991168D4994637E8343E3600D51FBC6C71A0094FA2CDD545B11C5C0C797324F1
4bdecdf772491e35c4e8b48f88aee22bae1311984f2e1da4dfad0b78ee7f5163
13D56FFAEC78681E68F9DEB43B35BEC2FB68542E27897B79
6db14acc9e21c820ff28b1d5ef5de2b0
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A637ED6B0BFF5CB6F406B7EDEE386BFB5A899FA5AE9F24117C4B1FE649286651ECE45B3DC2007CB8A163BF0598DA48361C55D39A69163FA8FD24CF5F83655D23DCA3AD961C62F356208552BB9ED529077096966D670C354E4ABC9804F1746C08CA18217C32905E462E36CE3BE39E772C180E86039B2783A2EC07A28FB5C55DF06F4C52C9DE2BCBF6955817183995497CEA956AE515D2261898FA051015728E5A8AAAC42DAD33170D04507A33A85521ABDF1CBA64ECFB850458DBEF0A8AEA71575D060C7DB3970F85A6E1E4C7ABF5AE8CDB0933D71E8C94E04A25619DCEE3D2261AD2EE6BF12FFA06D98A0864D87602733EC86A64521F2B18177B200CBBE117577A615D6C770988C0BAD946E208E24FA074E5AB3143DB5BFCE0FD108E4B82D120A92108011A723C12A787E6D788719A10BDBA5B2699C327186AF4E23C1A946834B6150BDA2583E9CA2AD44CE8DBBBC2DB04DE8EF92E8EFC141FBECAA6287C59474E6BC05D99B2964FA090C3A2233BA186515BE7ED1F612970CEE2D7AFB81BDD762170481CD0069127D5B05AA993B4EA988D8FDDC186FFB7DC90A6C08F4DF435C934063199FFFFFFFFFFFFFFFF
E4E6DB2995065C407D9D39B8D0967B96704BA8E9C90B
790408F2EEDAF392B012EDEFB3392F30F4327C0CA3F31FC383C422AA8C16
6C0107475609912222105691 1C77D77E77A777E7E7E77FCB
7503CFE87A836AE3A61B8816E25450E6CE5E1C93ACF1ABC1778064FDCBEFA921DF1626BE4FD036E93D75E6A50E3A41E98028FE5FC235F5B889A589CB5215F2A4
FFFFFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD65612433F51F5F066ED0856365553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFFA886B423861285C97FFFFFFFFFFFFFFFF
fb8e1673b29c9c4d0f9c0c91df2d88be39a57be448d6c0725fc08002b269d8db
659EF8BA043916EEDE8911702B22
048BD2AEB9CB7E57CB2C4B482FFC81B7AFB9DE27E1E3BD23C23A4453BD9ACE3262547EF835C3DAC4FD97F8461A14611DC9C27745132DED8E545C1D54C72F046997

POSSIBLE SECRETS
4fe342e2fe1a7f9b8ee7eb4a7c0f9e162bce33576b315ececbb6406837bf51f5
04017232BA853A7E731AF129F22FF4149563A419C26BF50A4C9D6EEFAD612601DB537DECE819B7F70F555A67C427A8CD9BF18AEB9B56E0C11056FAE6A3
0051953EB9618E1C9A1F929A21A0B68540EEA2DA725B99B315F3B8B489918EF109E156193951EC7E937B1652C0BD3BB1BF073573DF883D2C34F1EF451FD46B503F00
FFFFFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD65612433F51F5F066ED0856365553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFFA886B4238611FCFDCDE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE598CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C4484E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B669E1EF16E6F52C3164DF4FB7930E9E4E58857B6AC7D5F42D69F6D187763CF1D5503400487F55BA57E31CC7A7135C886EFB4318AED6A1E012D9E6832A907600A918130C46DC778F971AD0038092999A333CB8B7A1A1DB93D7140003C2A4ECEA9F98D0ACC0A8291CDCEC97DCF8EC9B55A7F88A46B4DB5A851F44182E1C68A007E5E0DD9020BFD64B645036C7A4E677D2C38532A3A23BA4442CAF53EA63BB454329B7624C8917BDD64B1C0FD4CB38E8C334C701C3ACDAD0657FCCFEC719B1F5C3E4E46041F388147FB4CFDB477A52471F7A9A96910B855322EDB6340D8A00EF092350511E30ABEC1FFF9E3A26E7FB29F8C183023C3587E38DA0077D9B4763E4E4B94B2BBC194C6651E77CAF992EEAAC0232A281BF6B3A739C1226116820AE8DB5847A67CBEF9C9091B462D538CD72B03746AE77F5E62292C311562A846505DC82DB854338AE49F5235C95B91178CCF2DD5CACEF403EC9D1810C6272B045B3B71F9DC6B80D63FDD4A8E9ADB1E6962A69526D43161C1A41D570D7938DAD4A40E329CD0E40E65FFFFFFFFFFFFFFFF
AADD9DB8DBE9C48B3FD4E6AE33C9FC07CB308DB3B3C9D20ED6639CCA70330870553E5C414CA92619418661197FAC10471DB1D381085DDADDB58796829CA90069
e9e642599d355f37c97ffd3567120b8e25c9cd43e927b3a9670fbec5d890141922d2c3b3ad2480093799869d1e846aab49fab0ad26d2ce6a22219d470bce7d777d4a21fbe9c270b57f607002f3cef8393694cf45ee3688c11a8c56ab127a3daf
0202F9F87B7C574D0BDECF8A22E6524775F98CDEBDCB
036b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296
D35E472036BC4FB7E13C785ED201E065F98FCFA6F6F40DEF4F92B9EC7893EC28FCD412B1F1B32E27
5FF6108462A2DC8210AB403925E638A19C1455D21
044AD5F7048DE709AD51236DE65E4D4B482C836DC6E410664002BB3A02D4AAADACAE24817A4CA3A1B014B5270432DB27D2
8e722de3125bddb05580164bfe20b8b432216a62926c57502ceede31c47816edd1e89769124179d0b695106428815065
D6031998D1B3BBFEBF59CC9BBFF9AEE1

POSSIBLE SECRETS
db48223fd9e143f7e133c57f5d08a4e38549ce3ebd921fe3b4003c26e5e35bed
0402FE13C0537BBC11ACAA07D793DE4E6D5E5C94EEE80289070FB05D38FF58321F2E800536D538CCDAA3D9
0667ACEB38AF4E488C407433FFAE4F1C811638DF20
4E13CA542744D696E67687561517552F279A8C84
2fc7f551-b850-43cf-aca8-ee2592d5d0aa
540d596c-c4de-11ed-afa1-0242ac120002
401028774D7777C7B7666D1366EA432071274F89FF01E718
F1FD178C0B3AD58F10126DE8CE42435B53DC67E140D2BF941FFDD459C6D655E1
173cf86fe9894a0f70dadd09d4fd88c380836099d4939f8c3754361bdc16a32b
BDB6F4FE3E8B1D9E0DA8C0D46F4C318CEFE4AFE3B6B8551F
22caae15-1239-4174-92e3-d42237aaf413
010090512DA9AF72B08349D98A5DD4C7B0532ECA51CE03E2D10F3B7AC579BD87E909AE40A6F131E9CFCE5BD967
83257109614890299855467512895201081792878530488613155947092059024805031998844192244386437603929473330780865116278 71
71169be7330b3038edb025f1
115792089237316195423570985008687907853269984665640564039457584007908834671663
E2E31EDFC23DE7BDEBE241CE593EF5DE2295B7A9CBAEF021D385F7074CEA043AA27272A7AE602BF2A7B9033DB9ED3610C6FB85487EAE97AAC5BC7928C1950148
065b039e1e06945e854870d014261016

POSSIBLE SECRETS
f7e1a085d69b3ddecbbcab5c36b857b97994afbbfa3aea82f9574c0b3d0782675159578ebad4594fe67107108180b449167123e84c281613b7cf09328cc8a6e13c167a8b547c8d28e0a3ae1e2bb3a675916ea37f0bfa213562f1fb627a01243bcca4f1bea8519089a883dfe15ae59f06928b665e807b552564014c3bfecf492a
3045AE6FC8422F64ED579528D38120EAE12196D5
b28ef557ba31dfcbdd21ac46e2a91e3c304f44cb87058ada2cb815151e610046
6127C24C05F38A0AAAF65C0EF02C
3045AE6FC8422f64ED579528D38120EAE12196D5
42debb9da5b3d88cc956e08787ec3f3a09bba5f48b889a74aaf53174aa0fbe7e3c5b8fcd7a53bef563b0e98560328960a9517f4014d3325fc7962bf1e049370d76d1314a76137e792f3f0db859d095e4a5b932024f079ecf2ef09c797452b0770e1350782ed57ddf794979dcef23cb96f183061965c4ebc93c9c71c56b925955a75f94cccf1449ac43d586d0beee43251b0b2287349d68de0d144403f13e802f4146d882e057af19b6f6275c6676c8fa0e3ca2713a3257fd1b27d0639f695e347d8d1cf9ac819a26ca9b04cb0eb9b7b035988d15bbac65212a55239cfc7e58fae38d7250ab9991ffbc97134025fe8ce04c4399ad96569be91a546f4978693c7a
020A601907B8C953CA1481EB10512F78744A3205FD
0066647EDE6C332C7F8C0923BB58213B333B20E9CE4281FE115F7D8F90AD
3826F008A8C51D7B95284D9D03FF0E00CE2CD723A
044BA30AB5E892B4E1649DD0928643ADCD46F5882E3747DEF36E956E97
FFFFFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD65612433F51F5F066ED0856365553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFFA886B4238611FCFDCDE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE598CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C4484E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B669E1EF16E6F52C3164DF4FB7930E9E4E58857B6AC7D5F42D69F6D187763CF1D5503400487F55BA57E31CC7A7135C886EFB4318AED6A1E012D9E6832A907600A918130C46DC778F971AD0038092999A333CB8B7A1A1DB93D7140003C2A4ECEA9F98D0ACC0A8291CDCEC97DCF8EC9B55A7F88A46B4DB5A851F44182E1C68A007E5E655F6AFFFFFFFFFFFFFFFF
4D41A619BCC6EADF0448FA22FAD567A9181D37389CA
324A6EDDD512F08C49A99AE0D3F961197A76413E7BE81A400CA681E09639B5FE12E59A109F78BF4A373541B3B9A1

POSSIBLE SECRETS
6864797660130609714981900799081393217269435300143305409394463459185543183397655394245057746333217197532963996371363321113864768612440380340372808892707005449
B99B99B099B323E02709A4D696E6768756151751
C49D360886E704936A6678E1139D26B7819F7E90
FFFFFFFF00000000FFFFFFFFFFFFFFFFBCE6FAADA7179E84F3B9CAC2FC632551
9CA8B57A934C54DEEDA9E54A7BBAD95E3B2E91C54D32BE0B9DF96D8D35
308202eb30820254a00302010202044d36f7a4300d06092a864886f70d01010505003081b9310b3009060355040613023836311230100603550408130947756 16e67646f6e673111300f060355040713085368656e7a68656e31353033060355040a132c54656e63656e7420546563686e6f6c6f6779285368656e7a68656e2920436f6d70616e79204c696d69746564313a3038060355040b133154656e63656e74204775616e677a686f752052657365617263682061 6e6420446576656c6f706d656e742043656e7465723110300e060355040313075465656e63656e74301e170d3131303131393134333933325a170d3431303131313131343333933325a3081b9310b3009060355040613023836311230100603550408130947756 16e67646f6e673111300f060355040713085368656e7a68656e31353033060355040a132c54656e63656e7420546563686e6f6c6f6779285368656e7a68656e2920436f6d70616e79204c696d69746564313a3038060355040b133154656e63656e74204775616e677a686f752052657365617263682061 6e6420446576656c6f706d656e742043656e7465723110300e060355040313075465656e63656e7430819f300d06092a864886f70d010101050003818d0030818902818100c05f34b231b083fb1323670bfbe7bdab40c0c0a6efc87ef2072a1ff0d60cc67c8edb0d0847f210bea6cbfaa241be70c86daf56be08b723c859e52428a064555d80db448cdcacc1aea2501eba06f8bad12a4fa49d85cacd7abeb68945a5cb5e061629b52e3254c373550ee4e40cb7c8ae6f7a8151ccd8df582d446f39ae0c5e930203010001300d06092a864886f70d010105050003818100 9c8d9d7f2f908c42081b4c764c377109a8b2c70582422125ce545842d5f520aea69550b6bd8bfd94e987b75a3077eb04ad341f481aac266e89d3864456e69fba13df018acdc168b9a19dfd7ad9d9cc6f6ace57c746515f71234df3a053e33ba93ece5cd0fc15f3e389a3f365588a9fcb439e069d3629cd7732a13fff7b891499
8e0cd15d01f05c9aaa3965184e507ae52711f8723684ce931581e2de9c01b362
04640ECE5C12788717B9C1BA06CBC2A6FEBA85842458C56DDE9DB1758D39C0313D82BA51735CDB3EA499AA77A7D6943A64F7A3F25FE26F06B51BAA2696FA9035DA5B534BD595F5AF0FA2C892376C84ACE1BB4E3019B71634C01131159CAE03CEE9D9932184BEEF216BD71DF2DADF86A627306ECFF96DBB8BACE198B61E00F8B332
BDB6F4FE3E8B1D9E0DA8C0D40FC962195DFAE76F56564677
115792089210356248762697446949407573530086143415290314195533631308867097853948
AC6BDB41324A9A9BF166DE5E1389582FAF72B6651987EE07FC3192943DB56050A37329CBB4A099ED8193E0757767A13DD52312AB4B03310DCD7F48A9DA04FD50E8083969EDB767B0CF6095179A163AB3661A05FBD5FAAAE82918A9962F0B93B855F97993EC975EEAA80D740ADBF4FF747359D041D5C33EA71D281E446B14773BCA97B43A23FB801676BD207A436C6481F1D2B9078717461A5B9D32E688F87748544523B524B0D57D5EA77A2775D2ECFA032CFBDBF52FB3786160279004E57AE6AF874E7303CE53299CCC041C7BC308D82A5698F3A8D0C38271AE35F8E9DBFBB694B5C803D89F7AE435DE236D525F54759B65E372FCD68EF20FA7111F9E4AFF73
fca682ce8e12caba26efccf7110e526db078b05edecbcd1eb4a208f3ae1617ae01f35b91a47e6df63413c5e12ed0899bcd132acd50d99151bdc43ee737592e17

POSSIBLE SECRETS
e4f420c1-0068-4ea7-afa6-9f8040973802
469A28EF7C28CCA3DC721D044F4496BCCA7EF4146FBF25C9
e555a5d7-dddc-4b77-9355-52a84e09ebb5
E0D2EE25095206F5E2A4F9ED229F1F256E79A0E2B455970D8D0D865BD94778C576D62F0AB7519CCD2A1A906AE30D
04DB4FF10EC057E9AE26B07D0280B7F4341DA5D1B1EAE06C7D9B2F2F6D9C5628A7844163D015BE86344082AA88D95E2F9D
83065532-9c0f-4079-85c9-0bbef904ec48
044A96B5688EF573284664698968C38BB913CBFC8223A628553168947D59DCC912042351377AC5FB32
22baae15-3620-4174-92e4-d42297aaf48b
03CE10490F6A708FC26DFE8C3D27C4F94E690134D5BFF988D8D28AAEAEDE975936C66BAC536B18AE2DC312CA493117DAA469C640CAF3
040303001D34B856296C16C0D40D3CD7750A93D1D2955FA80AA5F40FC8DB7B2ABDBDE53950F4C0D293CDD711A35B67FB1499AE60038614F1394ABFA3B4C850D927E1E7769C8EEC2D19037BF27342DA639B6DCCFFFEB73D69D78C6C27A6009CBBCA1980F8533921E8A684423E43BAB08A576291AF8F461BB2A8B3531D2F0485C19B16E2F1516E23DD3C1A4827AF1B8AC15B
11bade15-1989-4174-92e1-d42297baf482
00F50B028E4D696E676875615175290472783FB1
043B4C382CE37AA192A4019E763036F4F5DD4D7EBB938CF935318FDCED6BC28286531733C3F03C4FEE
db53fcdc9ab71e9bdd4eab257fe1aba7989ad2b24fbe3a85dfef72ea1dd6bae2
secret=WTL6HCNRXQSNI26SLY5JL4NAMOGXWQXC

POSSIBLE SECRETS
5E5CBA992E0A680D885EB903AEA78E4A45A469103D448EDE3B7ACCC54D521E37F84A4BDD5B06B0970CC2D2BBB715F7B82846F9A0C393914C792E6A923E2117AB805276A975AADB5261D91673EA9AAFFEECBFA6183DFCB5D3B7332AA19275AFA1F8EC0B60FB6F66CC23AE4870791D5982AAD1AA9485FD8F4A60126FEB2CF05DB8A7F0F09B3397F3937F2E90B9E5B9C9B6EFEF642BC48351C46FB171B9BFA9EF17A961CE96C7E7A7CC3D3D03DFAD1078BA21DA425198F07D2481622BCE45969D9C4D6063D72AB7A0F08B2F49A7CC6AF335E08C4720E31476B67299E231F8BD90B39AC3AE3BE0C6B6CACEF8289A2E2873D58E51E029CAFBD55E6841489AB66B5B4B9BA6E2F784660896AFF387D92844CCB8B69475496DE19DA2E58259B090489AC8E62363CDF82CFD8EF2A427ABCD65750B506F56DDE3B988567A88126B914D7828E2B63A6D7ED0747EC59E0E0A23CE7D8A74C1D2C2A7AFB6A29799620F00E11C33787F7DED3B30E1A22D09F1FBDA1ABBBFBF25CAE05A13F812E34563F99410E73B
5fed96c85bd58c58aadbd465c172a4c9a794d8eb2f86cbc7bcee6caf4c7a2c5f
F1FD178C0B3AD58F10126DE8CE42435B3961ADBCABC8CA6DE8FCF353D86E9C03
00E8BEE4D3E2260744188BE0E9C723
DB7C2ABF62E35E668076BEAD208B
04B70E0CBD6BB4BF7F321390B94A03C1D356C21122343280D6115C1D21BD376388B5F723FB4C22DFE6CD4375A05A07476444D5819985007E34
D7C134AA264366862A18302575D1D787B09F075797DA89F57EC8C0FC
FD0D693149A118F651E6DCE6802085377E5F882D1B510B44160074C1288078365A0396C8E681
7d25e644-aa94-4abb-b5e8-2b3806130cdb
91A091F03B5FBA4AB2CCF49C4EDD220FB028712D42BE752B2C40094DBACDB586FB20
03eea2bae7e1497842f2de7769cfe9c989c072ad696f48034a
036768ae8e18bb92cfcf005c949aa2c6d94853d0e660bbf854b1c9505fe95a
4230017757A767FAE42398569B746325D45313AF0766266479B75654E65F
3EE30B568FBAB0F883CCEBD46D3F3BB8A2A73513F5EB79DA66190EB085FFA9F492F375A97D860EB4
C302F41D932A36CDA7A3463093D18DB78FCE476DE1A86294
0101D556572AABAC800101D556572AABAC8001022D5C91DD173F8FB561DA6899164443051D

POSSIBLE SECRETS
FFFFFFFFFFFFFFFFC90FDAA22168C234C4C6628B80DC1CD129024E088A67CC74020BBEA63B139B22514A08798E3404DDEF9519B3CD3A431B302B0A6DF25F14374FE1356D6D51C245E485B576625E7EC6F44C42E9A63A3620FFFFFFFFFFFFFFFF
8ee6e1b2-ad84-4689-8aa0-e699bb2117dd
023b1660dd701d0839fd45eec36f9ee7b32e13b315dc02610aa1b636e346df671f790f84c5e09b05674dbb7e45c803dd
VFVWYVZGVkhiekprVmxJMFRqTmFiVTVWVG5wUk0yaFpZa1JHYjJGVlZqRlVNVnAwV25wWk5XVlVVbFpqYTJRMVpWWmFWR1JVVGtoaFZXaHBWMVV4Y0dSWE1EVlJaejA5
6EE3CEEB230811759F20518A0930F1A4315A827DAC
3FCDA526B6CDF83BA1118DF35B3C31761D3545F32728D003EEB25EFE96
30470ad5a005fb14ce2d9dcd87e38bc7d1b1c5facbaecbe95f190aa7a31d23c4dbbcbe06174544401a5b2c020965d8c2bd2171d3668445771f74ba084d2029d83c1c158547f3a9f1a2715be23d51ae4d3e5a1f6a7064f316933a346d3f529252
D2C0FB15760860DEF1EEF4D696E6768756151754
040356DCD8F2F95031AD652D23951BB366A80648F06D867940A5366D9E265DE9EB240F
f8183668ba5fc5bb06b5981e6d8b795d30b8978d43ca0ec572e37e09939a9773
b4050a850c04b3abf54132565044b0b7d7bfd8ba270b39432355ffb4
7ae96a2b657c07106e64479eac3434e99cf0497512f58995c1396c28719501ee
E8C2505DEDFC86DDC1BD0B2B6667F1DA34B82574761CB0E879BD081CFD0B6265EE3CB090F30D27614CB4574010DA90DD862EF9D4EBEE4761503190785A71C760
02120FC05D3C67A99DE161D2F4092622FECA701BE4F50F4758714E8A87BBF2A658EF8C21E7C5EFE965361F6C2999C0C247B0DBD70CE6B7
06973B15095675534C7CF7E64A21BD54EF5DD3B8A0326AA936ECE454D2C
68647976601306097149819007990813932172694353001433054093944634591855431833976560521225596406614545549772963113914808580371219879997166438125740282911150571 48
04009D73616F35F4AB1407D73562C10F00A52830277958EE84D1315ED31886

POSSIBLE SECRETS
26247035095799689268623156744566981891852923491109213387815615900925518854738050089022388053975719786650872476732087
6BA06FE51464B2BD26DC57F48819BA9954667022C7D03
0400D9B67D192E0367C803F39E1A7E82CA14A651350AAE617E8F01CE94335607C304AC29E7DEFBD9CA01F596F927224CDECF6C
E95E4A5F737059DC60DFC7AD95B3D8139515620F
4A6E0856526436F2F88DD07A341E32D04184572BEB710
7830A3318B603B89E2327145AC234CC594CBDD8D3DF91610A83441CAEA9863BC2DED5D5AA8253AA10A2EF1C98B9AC8B57F1117A72BF2C7B9E7C1AC4D77FC94CA
04026EB7A859923FBC82189631F8103FE4AC9CA2970012D5D46024804801841CA44370958493B205E647DA304DB4CEB08CBBD1BA39494776FB988B47174DCA88C7E2945283A01C89720349 DC807F4FBF374F4AEADE3BCA95314DD58CEC9F307A54FFC61EFC006D8A2C9D4979C0AC44AEA74FBEBBB9F772AEDCB620B01A7BA7AF1B320430C8591984F601CD4C143EF1C7A3
A7F561E038EB1ED560B3D147DB782013064C19F27ED27C6780AAF77FB8A547CEB5B4FEF422340353
5be3729e-9cb0-4b1f-9de9-5d668e624f24
DB7C2ABF62E35E7628DFAC6561C5
5D9306BACD22B7FAEB09D2E049C6E2866C5D1677762A8F2F2DC9A11C7F7BE8340AB2237C7F2A0
000102030405060708090A0B0C0D0E0F101112131415161718191A1B1C1D1E1F
BD71344799D5C7FCDC45B59FA3B9AB8F6A948BC5
9cdbd84c9f1ac2f38d0f80f42ab952e7338bf511
3a594b1b-6cc1-4c85-9fcd-e137cea7e766
10B7B4D696E676875615175137C8A16FD0DA2211
EE353FCA5428A9300D4ABA754A44C00FDFEC0C9AE4B1A1803075ED967B7BB73F

POSSIBLE SECRETS
0432C4AE2C1F1981195F9904466A39C9948FE30BBFF2660BE1715A4589334C74C7BC3736A2F4F6779C59BDCEE36B692153D0A9877CC62A474002DF32E52139F0A0
00C9517D06D5240D3CFF38C74B20B6CD4D6F9DD4D9
115792089210356248762697446949407573530086143415290314195533631308867097853951
71FE1AF926CF847989EFEF8DB459F66394D90F32AD3F15E8
3517262215D8D3008CBF888750B6418EDC4D562AC33ED6874E0D73ABA667BC3C
0370F6E9D04D289C4E89913CE3530BFDE903977D42B146D539BF1BDE4E9C92
dc190116-d99a-4c7f-881d-366b589fefdc
A59A749A11242C58C894E9E5A91804E8FA0AC64B56288F8D47D51B1EDC4D65444FECA0111D78F35FC9FDD4CB1F1B79A3BA9CBEE83A3F811012503C8117F98E5048B089E387AF6949BF8784E BD9EF45876F2E6A5A495BE64B6E770409494B7FEE1DBB1E4B2BC2A53D4F893D418B7159592E4FFFDF6969E91D770DAEBD0B5CB14C00AD68EC7DC1E5745EA55C706C4A1C5C88964E34D09D EB753AD418C1AD0F4FDFD049A955E5D78491C0B7A2F1575A008CCD727AB376DB6E695515B05BD412F5B8C2F4C77EE10DA48ABD53F5DD498927EE7B692BBBCDA2FB23A516C5B4533D7398 0B2A3B60E384ED200AE21B40D273651AD6060C13D97FD69AA13C5611A51B9085
04A1455B334DF099DF30FC28A169A467E9E47075A90F7E650EB6B7A45C7E089FED7FBA344282CAFBD6F7E319F7C0B0BD59E2CA4BDB556D61A5
3d1a292b-5849-4008-8a68-530c7f5fecb1
1243ae1b4d71613bc9f780a03690e
F1FD178C0B3AD58F10126DE8CE42435B3961ADBCABC8CA6DE8FCF353D86E9C00
1d80658f-889a-4180-88f4-1db4e219e6df
60dcd2104c4cbc0be6eeefc2bdd610739ec34e317f9b33046c9e4788
072546B5435234A422E0789675F432C89435DE5242
C302F41D932A36CDA7A3463093D18DB78FCE476DE1A86297
002757A1114D696E6768756151755316C05E0BD4

POSSIBLE SECRETS
51DEF1815DB5ED74FCC34C85D709
4099B5A457F9D69F79213D094C4BCD4D4262210B
eae97aa71692b47f75bf58f680440e1e4e23bc114a682faa39db521af4ecb9b6
7B425ED097B425ED097B425ED097B425ED097B425ED097B4260B5E9C7710C864
7fffffffffffffffffffffff800000cfa7e8594377d414c03821bc582063
675968c6a3bd176ef9ee01088bf43460ef08cc706ba0dda6a27a9272b70dfe98
c469684435deb378c4b65ca9591e2a5763059a2e
0289FDFBE4ABE193DF9559ECF07AC0CE78554E2784EB8C1ED1A57A
1A8F7EDA389B094C2C071E3647A8940F3C123B697578C213BE6DD9E6C8EC7335DCB228FD1EDF4A39152CBCAAF8C0398828041055F94CEEEC7E21340780FE41BD
x34mMawEUcCG8l95riWCOK+kAJYejVmdt44l6tzcyUc=
0217C05610884B63B9C6C7291678F9D341
7885fc01def1ba72a879d1965b3d3ce05da15dbf2e4ac89067da9d7dfd294040
520883949DFDBC42D3AD198640688A6FE13F41349554B49ACC31DCCD884539816F5EB4AC8FB1F1A6
85E25BFE5C86226CDB12016F7553F9D0E693A268

POSSIBLE SECRETS
FFFFFFFFFFFFFFFFADF85458A2BB4A9AAFDC5620273D3CF1D8B9C583CE2D3695A9E13641146433FBCC939DCE249B3EF97D2FE363630C75D8F681B202AEC4617AD3DF1ED5D5FD65612433F51F5F066ED0856365553DED1AF3B557135E7F57C935984F0C70E0E68B77E2A689DAF3EFE8721DF158A136ADE73530ACCA4F483A797ABC0AB182B324FB61D108A94BB2C8E3FBB96ADAB760D7F4681D4F42A3DE394DF4AE56EDE76372BB190B07A7C8EE0A6D709E02FCE1CDF7E2ECC03404CD28342F619172FE9CE98583FF8E4F1232EEF28183C3FE3B1B4C6FAD733BB5FCBC2EC22005C58EF1837D1683B2C6F34A26C1B2EFFA886B4238611FCFDCDE355B3B6519035BBC34F4DEF99C023861B46FC9D6E6C9077AD91D2691F7F7EE598CB0FAC186D91CAEFE130985139270B4130C93BC437944F4FD4452E2D74DD364F2E21E71F54BFF5CAE82AB9C9DF69EE86D2BC522363A0DABC521979B0DEADA1DBF9A42D5C4484E0ABCD06BFA53DDEF3C1B20EE3FD59D7C25E41D2B669E1EF16E6F52C3164DF4FB7930E9E4E58857B6AC7D5F42D69F6D187763CF1D5503400487F55BA57E31CC7A7135C886EFB4318AED6A1E012D9E6832A907600A918130C46DC778F971AD0038092999A333CB8B7A1A1DB93D7140003C2A4ECEA9F98D0ACC0A8291CDCEC97DCF8EC9B55A7F88A46B4DB5A851F44182E1C68A007E5E0DD9020BFD64B645036C7A4E677D2C38532A3A23BA4442CAF53EA63BB454329B7624C8917BDD64B1C0FD4CB38E8C334C701C3ACDAD0657FCCFEC719B1F5C3E4E46041F388147FB4CFDB477A52471F7A9A96910B855322EDB6340D8A00EF092350511E30ABEC1FFF9E3A26E7FB29F8C183023C3587E38DA0077D9B4763E4E4B94B2BBC194C6651E77CAF992EEAAC0232A281BF6B3A739C1226116820AE8DB5847A67CBEF9C9091B462D538CD72B03746AE77F5E62292C311562A846505DC82DB854338AE49F5235C95B91178CCF2DD5CACEF403EC9D1810C6272B045B3B71F9DC6B80D63FDD4A8E9ADB1E6962A69526D43161C1A41D570D7938DAD4A40E329CCFF46AAA36AD004CF600C8381E425A31D951AE64FDB23FCEC9509D43687FEB69EDD1CC5E0B8CC3BDF64B10EF86B63142A3AB8829555B2F747C932665CB2C0F1CC01BD70229388839D2AF05E454504AC78B7582822846C0BA35C35F5C59160CC046FD8251541FC68C9C86B022BB7099876A460E7451A8A93109703FEE1C217E6C3826E52C51AA691E0E423CFC99E9E31650C1217B624816CDAD9A95F9D5B8019488D9C0A0A1FE3075A577E23183F81D4A3F2FA4571EFC8CE0BA8A4FE8B6855DFE72B0A66EDED2FBABFBE58A30FAFABE1C5D71A87E2F741EF8C1FE86FEA6BBFDE530677F0D97D11D49F7A8443D0822E506A9F4614E011E2A94838FF88CD68C8BB7C5C6424CFFFFFFFFFFFFFFFF
B4050A850C04B3ABF54132565044B0B7D7BFD8BA270B39432355FFB4
57f20381-8cd5-4ed5-9cba-ffc5539f0791
0257927098FA932E7C0A96D3FD5B706EF7E5F5C156E16B7E7C86038552E91D
0101BAF95C9723C57B6C21DA2EFF2D5ED588BDD5717E212F9D
041D1C64F068CF45FFA2A63A81B7C13F6B8847A3E77EF14FE3DB7FCAFE0CBD10E8E826E03436D646AAEF87B2E247D4AF1E8ABE1D7520F9C2A45CB1EB8E95CFD55262B70B29FEEC5864E19C054FF99129280E4646217791811142820341263C5315
0479BE667EF9DCBBAC55A06295CE870B07029BFCDB2DCE28D959F2815B16F81798483ADA7726A3C4655DA4FBFC0E1108A8FD17B448A68554199C47D08FFB10D4B8
5F49EB26781C0EC6B8909156D98ED435E45FD59918
1C97BEFC54BD7A8B65ACF89F81D4D4ADC565FA45
1093849038073734274511112390766805569936207598951683748994586394495953116150735016013708737573759623248592132296706313309438452531591012912142327488478985984
5037EA654196CFF0CD82B2C14A2FCF2E3FF8775285B545722F03EACDB74B
3FA8124359F96680B83D1C3EB2C070E5C545C9858D03ECFB744BF8D717717EFC

POSSIBLE SECRETS
00C9BB9E8927D4D64C377E2AB2856A5B16E3EFB7F61D4316AE
FC1217D4320A90452C760A58EDCD30C8DD069B3C34453837A34ED50CB54917E1C2112D84D164F444F8F74786046A
a2efcee6-28ae-4478-ab0d-88fbdfd1f3c4
CFA0478A54717B08CE64805B76E5B14249A77A4838469DF7F7DC987EFCCFB11D
1CEF494720115657E18F938D7A7942394FF9425C1458C57861F9EEA6ADBE3BE10
6A91174076B1E0E19C39C031FE8685C1CAE040E5C69A28EF
4edf0d63-f306-4513-aa91-8ab510ac5ca5
d16b066c-fa71-4520-bd74-b1fe771ab415
A9FB57DBA1EEA9BC3E660A909D838D718C397AA3B561A6F7901E0E82974856A7
004D696E67687561517512D8F03431FCE63B88F4
cac221e8-f3cd-4ab1-97ba-6af7a487705c
04015D4860D088DDB3496B0C6064756260441CDE4AF1771D4DB01FFE5B34E59703DC255A868A1180515603AEAB60794E54BB7996A70061B1CFAB6BE5F32BBFA78324ED106A7636B9C5A7BD198D0158AA4F5488D08F38514F1FDF4B4F40D2181B3681C364BA0273C706
B3EEABB8EE11C2BE770B684D95219ECB
10C0FB15760860DEF1EEF4D696E676875615175D
b8adf1378a6eb73409fa6c9c637ba7f5
64210519E59C80E70FA7E9AB72243049FEB8DEECC146B9B1
02197B07845E9BE2D96ADB0F5F3C7F2CFFBD7A3EB8B6FEC35C7FD67F26DDF6285A644F740A2614

POSSIBLE SECRETS
BB8E5E8FBC115E139FE6A814FE48AAA6F0ADA1AA5DF91985
A9FB57DBA1EEA9BC3E660A909D838D726E3BF623D52620282013481D1F6E5374
0443BD7E9AFB53D8B85289BCC48EE5BFE6F20137D10A087EB6E7871E2A10A599C710AF8D0D39E2061114FDD05545EC1CC8AB4093247F77275E0743FFED117182EAA9C77877AAAC6AC7D35245D1692E8EE1
31a92ee2029fd10d901b113e990710f0d21ac6b6
C196BA05AC29E1F9C3C72D56DFFC6154A033F1477AC88EC37F09BE6C5BB95F51C296DD20D1A28A067CCC4D4316A4BD1DCA55ED1066D438C35AEBAABF57E7DAE428782A95ECA1C143DB701FD48533A3C18F0FE23557EA7AE619ECACC7E0B51652A8776D02A425567DED36EABD90CA33A1E8D988F0BBB92D02D1D20290113BB562CE1FC856EEB7CDD92D33EEA6F410859B179E7E789A8F75F645FAE2E136D252BFFAFF89528945C1ABE705A38DBC2D364AADE99BE0D0AAD82E5320121496DC65B3930E38047294FF877831A16D5228418DE8AB275D7D75651CEFED65F78AFC3EA7FE4D79B35F62A0402A1117599ADAC7B269A59F353CF450E6982D3B1702D9CA83
043AE9E58C82F63C30282E1FE7BBF43FA72C446AF6F4618129097E2C5667C2223A902AB5CA449D0084B7E5B3DE7CCC01C9
02A29EF207D0E9B6C55CD260B306C7E007AC491CA1B10C62334A9E8DCD8D20FB7
1f3bdba585295d9a1110d1df1f9430ef8442c5018976ff3437ef91b81dc0b8132c8d5c39c32d0e004a3092b7d327c0e7a4d26d2c7b69b58f9066652911e457779de
040369979697AB43897789566789567F787A7876A65400435EDB42EFAFB2989D51FEFCE3C80988F41FF883
3DF91610A83441CAEA9863BC2DED5D5AA8253AA10A2EF1C98B9AC8B57F1117A72BF2C7B9E7C1AC4D77FC94CADC083E67984050B75EBAE5DD2809BD638016F723
030024266E4EB5106D0A964D92C4860E2671DB9B6CC5
B4E134D3FB59EB8BAB57274904664D5AF50388BA
0163F35A5137C2CE3EA6ED8667190B0BC43ECD69977702709B
1A62BA79D98133A16BBAE7ED9A8E03C32E0824D57AEF72F88986874E5AAE49C27BED49A2A95058068426C2171E99FD3B43C5947C857D
c97445f45cdef9f0d3e05e1e585fc297235b82b5be8ff3efca67c59852018192
a2ed0d18-af9f-4e63-8a92-ec5f2a1c600a

POSSIBLE SECRETS
7BC86E2102902EC4D5890E8B6B4981ff27E0482750FEFC03
7A1F6653786A68192803910A3D30B2A2018B21CD54
B4C4EE28CEBC6C2C8AC12952CF37F16AC7EFB6A9F69F4B57FFDA2E4F0DE5ADE038CBC2FFF719D2C18DE0284B8BFEF3B52B8CC7A5F5BF0A3C8D2319A5312557E1
ffffffff00000000ffffffffffffffffbce6faada7179e84f3b9cac2fc632551
985BD3ADBAD4D696E676875615175A21B43A97E3
DB7C2ABF62E35E668076BEAD2088
216EE8B189D291A0224984C1E92F1D16BF75CCD825A087A239B276D3167743C52C02D6E7232AA
394020061963944792122790401001436138050797392704654466679482934042457217714968703290472660882589380018616069731123 16
1A827EF00DD6FC0E234CAF046C6A5D8A85395B236CC4AD2CF32A0CADBDC9DDF620B0EB9906D0957F6C6FEACD615468DF104DE296CD8F
95475cf5d93e596c3fcd1d902add02f427f5f3c7210313bb45fb4d5bb2e5fe1cbd678cd4bbdd84c9836be1f31c0777725aeb6c2fc38b85f48076fa76bcd8146cc89a6fb2f706dd719898c2083dc8d896f84062e2c9c94d137b054a8d8096adb8d51952398eeca852a0af12df83e475aa65d4ec0c38a9560d5661186ff98b9fc9eb60eee8b030376b236bc73be3acdbd74fd61c1d2475fa3077b8f080467881ff7e1ca56fee066d79506ade51edbb5443a563927dbc4ba520086746175c8885925ebc64c6147906773496990cb714ec667304e261faee33b3cbdf008e0c3fa90650d97d3909c9275bf4ac86ffcb3d03e6dfc8ada5934242dd6d3bcca2a406cb0b
171e879b-6075-45c7-b22a-3b429a186328
8138e8a0fcf3a4e84a771d40fd305d7f4aa59306d7251de54d98af8fe95729a1f73d893fa424cd2edc8636a6c3285e022b0e3866a565ae8108eed8591cd4fe8d2ce86165a978d719ebf647f362d33fca29cd179fb42401cbaf3df0c614056f9c8f3cfd51e474afb6bc6974f78db8aba8e9e517fded658591ab7502bd41849462f
0481AEE4BDD82ED9645A21322E9C4C6A9385ED9F70B5D916C1B43B62EEF4D0098EFF3B1F78E2D0D48D50D1687B93B97D5F7C6D5047406A5E688B352209BCB9F8227DDE385D566332ECC0EABFA9CF7822FDF209F70024A57B1AA000C55B881F8111B2DCDE494A5F485E5BCA4BD88A2763AED1CA2B2FA8F0540678CD1E0F3AD80892
be292c7b-660e-4985-906e-f7858d8e001d
04B8266A46C55657AC734CE38F018F2192
0401F481BC5F0FF84A74AD6CDF6FDEF4BF6179625372D8C0C5E10025E399F2903712CCF3EA9E3A1AD17FB0B3201B6AF7CE1B05

POSSIBLE SECRETS
0400C6858E06B70404E9CD9E3ECB662395B4429C648139053FB521F828AF606B4D3DBAA14B5E77EFE75928FE1DC127A2FFA8DE3348B3C1856A429BF97E7E31C2E5BD66011839296A789A3BC0045C8A5FB42C7D1BD998F54449579B446817AFBD17273E662C97EE72995EF42640C550B9013FAD0761353C7086A272C24088BE94769FD16650
B92825C2BD5D6D6D1E7F39EECD17843B7D9016F611136B75441BC6F4D3F00F05
023809B2B7CC1B28CC5A87926AAD83FD28789E81E2C9E3BF10
7BC382C63D8C150C3C72080ACE05AFA0C2BEA28E4FB22787139165EFBA91F90F8AA5814A503AD4EB04A8C7DD22CE2826

PLAYSTORE INFORMATION

Title: Booking.com: Hotels & Travel

Score: 4.8054485 **Installs:** 500,000,000+ **Price:** 0 **Android Version Support:** **Category:** Travel & Local **Play Store URL:** com.booking

Developer Details: Booking.com Hotels & Vacation Rentals, 8601716327451933581, None, http://www.booking.com/apps.html?source=googleplay, customer.service@booking.com,

Release Date: Feb 4, 2011 **Privacy Policy:** Privacy link

Description:

Save on your next trip with the Booking.com app! Find great hotel or apartment deals and book in just a few minutes. You can also book flights, rental cars, and more through the app. - Book your whole trip in one app (accommodations, flights, car rentals, taxis and more) - Stay flexible with free cancellation (available at most properties) - 24/7 customer service in more than 40 languages - No booking or credit card fees - Chat directly with your property in the app - Enjoy mobile-only discounts - Use filters to easily find the perfect place out of millions of available accommodations (hotels, apartments, homes, villas, ryokai and more) - Get paperless confirmation of your reservation — no printing required - Manage your bookings on the go, making changes whenever and wherever you want - Discover local attractions and make the most of your trip - Share your experience and get local advice on our Travel Communities forums Access millions of accommodations From cozy country homes to funky city apartments, find the perfect place out of millions of available accommodations. Our app offers hotels, apartments, hostels, vacation rentals, resorts, motels, guest houses, and bed and breakfasts. Quickly find the perfect place to stay Filter hotels by price, review score, WiFi quality, and other things important to you. Search cheap hotels by city, attraction, landmark, or hotel name. Special requests? Pet-friendly hotels? We have filters for everything. You can also compare your favorite accommodation options side by side to ensure you get the best price and quality. Deals for any budget Discover daily accommodation deals and save on your next hotel, apartment, or villa booking. Get exclusive mobile-only discounts of 10% or more on select properties when you book in the app. Savings available on motels and hostels, B&Bs and resorts, and luxury hotels, inns, homes, houses, apartments and vacation rentals. Find your ideal accommodation at an ideal price. Stay flexible with free cancellation Change of plans? Not a problem. You can cancel for free at most hotels, apartments and other properties on Booking.com. And the app makes things even easier — it only takes a few taps to cancel, and you're free to find a place that better suits your needs. Last-minute travel Heading somewhere in a hurry? With the app, you can quickly book hotels at the last minute (as well as far in advance). Finding a place in short order has never been easier. Our app allows you to search for properties nearby, fill in a few details, and secure your reservation. You can also change, cancel, or make additional reservations on the go. Jet off with the perfect flight Book domestic or international flights on the go with ease. The app allows you to search thousands of airfare deals per day. Plane tickets available for all major airlines and destinations. Hit the road with car rentals Car hire has recently been added to the app. Whether you just need a ride to explore your destination, or you're going on an epic road trip, the Booking.com app can help. Rent a car from all the major companies and hit the road! Reserve taxis with ease Book in advance for a seamless connection from the airport to your destination. You can also book taxis to and from other pick-up points, such as hotels and local attractions. Find and book a great experience Whether you're looking for attraction or museum tickets, boat tours, or walking tours, you can book experiences online in minutes, with free cancellation on many options. Get and share tips with other travelers Connect with fellow travelers, share your experiences, and get local advice on the best accommodations,

attractions, and more. Discover new experiences with our app, the perfect trip planner.

SCAN LOGS

Timestamp	Event	Error
2025-11-04 16:27:06	Generating Hashes	OK
2025-11-04 16:27:07	Extracting APK	OK
2025-11-04 16:27:07	Unzipping	OK
2025-11-04 16:27:07	Android Behaviour Analysis Completed	OK
2025-11-04 16:27:07	Extracting Emails and URLs from Source Code	OK
2025-11-04 16:27:08	Email and URL Extraction Completed	OK
2025-11-04 16:27:08	Extracting String data from APK	OK
2025-11-04 16:27:19	Extracting String data from SO	OK
2025-11-04 16:27:21	Extracting String data from Code	OK
2025-11-04 16:27:21	Extracting String values and entropies from Code	OK

2025-11-04 16:27:22	Performing Malware check on extracted domains	OK
2025-11-04 16:27:23	Parsing APK with androguard	OK
2025-11-04 16:27:28	Extracting APK features using aapt/aapt2	OK
2025-11-04 16:27:33	Getting Hardcoded Certificates/Keystores	OK
2025-11-04 16:27:35	Updating Database...	OK
2025-11-04 16:27:41	Parsing AndroidManifest.xml	OK
2025-11-04 16:27:41	Extracting Manifest Data	OK
2025-11-04 16:27:41	Manifest Analysis Started	OK
2025-11-04 16:27:42	Reading Network Security config from network_security_config_with_localhost_enabled.xml	OK
2025-11-04 16:27:42	Parsing Network Security config	OK
2025-11-04 16:27:42	Performing Static Analysis on: Booking.com (com.booking)	OK
2025-11-04 16:27:43	Fetching Details from Play Store: com.booking	OK

2025-11-04 16:27:43	Checking for Malware Permissions	OK
2025-11-04 16:27:43	Fetching icon path	OK
2025-11-04 16:27:44	Library Binary Analysis Started	OK
2025-11-04 16:27:44	Analyzing lib/x86_64/libmsaoaidauth.so	OK
2025-11-04 16:27:44	Analyzing lib/x86_64/libtiny_magic.so	OK
2025-11-04 16:27:44	Analyzing lib/x86_64/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:44	Analyzing lib/x86_64/libTMXProfiling-8.0-82-jni.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libbb7cbb.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libandroid-tests-support-code.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libembrace-native.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libandroidx.graphics.path.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libBaiduMapSDK_base_v7_6_3.so	OK

2025-11-04 16:27:45	Analyzing lib/x86_64/libconscrypt_jni.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libc++_shared.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libba4e.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libmsaoaidsec.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libmapbox-maps.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libleveldb_wrapper.so	OK
2025-11-04 16:27:45	Analyzing lib/x86_64/libmapbox-common.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libmsaoaidauth.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libtiny_magic.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libTMXProfiling-8.0-82-jni.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libbb7cbb.so	OK

2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libandroid-tests-support-code.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libembrace-native.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libBaiduMapSDK_base_v7_6_3.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libconscrypt_jni.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libc++_shared.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libba4e.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libmsaoaidsec.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libmapbox-maps.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libleveldb_wrapper.so	OK
2025-11-04 16:27:45	Analyzing lib/armeabi-v7a/libmapbox-common.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libmsaoaidauth.so	OK

2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libtiny_magic.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libTMXProfiling-8.0-82-jni.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libbb7cbb.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libandroid-tests-support-code.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libembrace-native.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libBaiduMapSDK_base_v7_6_3.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libconscrypt_jni.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libc++_shared.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libba4e.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libmsaoaidsec.so	OK

2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libmapbox-maps.so	OK
2025-11-04 16:27:45	Analyzing lib/arm64-v8a/libleveldb_wrapper.so	OK
2025-11-04 16:27:46	Analyzing lib/arm64-v8a/libmapbox-common.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libmsaoaidauth.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libtiny_magic.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libbb7cbb.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libandroid-tests-support-code.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libembrace-native.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libandroidx.graphics.path.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libBaiduMapSDK_base_v7_6_3.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libconscrypt_jni.so	OK

2025-11-04 16:27:46	Analyzing lib/x86/libc++_shared.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libba4e.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libmsaoaidsec.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libmapbox-maps.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libleveldb_wrapper.so	OK
2025-11-04 16:27:46	Analyzing lib/x86/libmapbox-common.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libmsaoaidauth.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libtiny_magic.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libTMXProfiling-8.0-82-jni.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libbb7cbb.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libandroid-tests-support-code.so	OK

2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libembrace-native.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libandroidx.graphics.path.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libBaiduMapSDK_base_v7_6_3.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libconscrypt_jni.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libc++_shared.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libba4e.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libmsaoaidsec.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libmapbox-maps.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libleveldb_wrapper.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/x86_64/libmapbox-common.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libmsaoaidauth.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libtiny_magic.so	OK

2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libTMXProfiling-8.0-82-jni.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libbb7cbb.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libandroid-tests-support-code.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libembrace-native.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libBaiduMapSDK_base_v7_6_3.so	OK
2025-11-04 16:27:46	Analyzing apktool_out/lib/armeabi-v7a/libconscrypt_jni.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/armeabi-v7a/libc++_shared.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/armeabi-v7a/libba4e.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/armeabi-v7a/libmsaoaidsec.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/armeabi-v7a/libmapbox-maps.so	OK

2025-11-04 16:27:47	Analyzing apktool_out/lib/armeabi-v7a/libleveldb_wrapper.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/armeabi-v7a/libmapbox-common.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libmsaoaidauth.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libtiny_magic.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libTMXProfiling-8.0-82-jni.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libbb7cbb.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libandroid-tests-support-code.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libembrace-native.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libBaiduMapSDK_base_v7_6_3.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libconscrypt_jni.so	OK

2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libc++_shared.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libba4e.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libmsaoaidsec.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libmapbox-maps.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libleveldb_wrapper.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/arm64-v8a/libmapbox-common.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libmsaoaidauth.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libtiny_magic.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libBaiduMapSDK_map_v7_6_3.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libbb7cbb.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libandroid-tests-support-code.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libembrace-native.so	OK

2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libandroidx.graphics.path.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libBaiduMapSDK_base_v7_6_3.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libconscrypt_jni.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libc++_shared.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libba4e.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libmsaoaidsec.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libmapbox-maps.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libleveldb_wrapper.so	OK
2025-11-04 16:27:47	Analyzing apktool_out/lib/x86/libmapbox-common.so	OK
2025-11-04 16:27:47	Reading Code Signing Certificate	OK
2025-11-04 16:27:48	Running APKiD 3.0.0	OK
2025-11-04 16:27:56	Detecting Trackers	OK

2025-11-04 16:28:11	Decompiling APK to Java with JADX	OK
2025-11-04 16:28:16	Decompiling with JADX failed, attempting on all DEX files	OK
2025-11-04 16:28:16	Decompiling classes13.dex with JADX	OK
2025-11-04 16:28:32	Decompiling classes12.dex with JADX	OK
2025-11-04 16:28:48	Decompiling classes2.dex with JADX	OK
2025-11-04 16:29:09	Decompiling classes5.dex with JADX	OK
2025-11-04 16:29:22	Decompiling classes.dex with JADX	OK
2025-11-04 16:29:54	Decompiling with JADX failed, attempting on all DEX files	OK
2025-11-04 16:29:54	Decompiling classes13.dex with JADX	OK
2025-11-04 16:30:10	Decompiling classes12.dex with JADX	OK
2025-11-04 16:30:22	Decompiling classes2.dex with JADX	OK
2025-11-04 16:30:34	Decompiling classes5.dex with JADX	OK

2025-11-04 16:30:46	Decompiling classes.dex with JADX	OK
2025-11-04 16:46:02	Decompiling with JADX timed out	TimeoutExpired(['/home/mobsf/.MobSF/tools/jadx/jadx-1.5.0/bin/jadx', '-ds', '/home/mobsf/.MobSF/uploads/fe2fc14061f3482ee16ee52c701d7850/java_source', '-q', '-r', '--show-bad-code', '/home/mobsf/.MobSF/uploads/fe2fc14061f3482ee16ee52c701d7850/classes.dex'], 999.9999773919999)
2025-11-04 16:46:02	Converting DEX to Smali	OK
2025-11-04 16:46:02	Code Analysis Started on - java_source	OK
2025-11-04 16:46:39	Android SBOM Analysis Completed	OK
2025-11-04 16:46:54	Android SAST Completed	OK
2025-11-04 16:46:54	Android API Analysis Started	OK
2025-11-04 16:47:08	Android API Analysis Completed	OK
2025-11-04 16:47:08	Android Permission Mapping Started	OK
2025-11-04 16:47:26	Decompiling with JADX timed out	TimeoutExpired(['/home/mobsf/.MobSF/tools/jadx/jadx-1.5.0/bin/jadx', '-ds', '/home/mobsf/.MobSF/uploads/fe2fc14061f3482ee16ee52c701d7850/java_source', '-q', '-r', '--show-bad-code', '/home/mobsf/.MobSF/uploads/fe2fc14061f3482ee16ee52c701d7850/classes.dex'], 999.9999854560001)
2025-11-04 16:47:26	Converting DEX to Smali	OK

2025-11-04 16:47:26	Code Analysis Started on - java_source	OK
2025-11-04 16:48:03	Android SBOM Analysis Completed	OK
2025-11-04 16:48:22	Android Permission Mapping Completed	OK
2025-11-04 16:48:24	Android SAST Completed	OK
2025-11-04 16:48:24	Android API Analysis Started	OK
2025-11-04 16:48:25	Android Behaviour Analysis Started	OK
2025-11-04 16:48:49	Android API Analysis Completed	OK
2025-11-04 16:48:49	Android Permission Mapping Started	OK
2025-11-04 16:49:09	Android Behaviour Analysis Completed	OK
2025-11-04 16:49:09	Extracting Emails and URLs from Source Code	OK
2025-11-04 16:49:37	Android Permission Mapping Completed	OK
2025-11-04 16:49:38	Email and URL Extraction Completed	OK

2025-11-04 16:49:38	Extracting String data from APK	OK
2025-11-04 16:49:48	Extracting String data from SO	OK
2025-11-04 16:49:50	Extracting String data from Code	OK
2025-11-04 16:49:50	Extracting String values and entropies from Code	OK
2025-11-04 16:49:55	Android Behaviour Analysis Started	OK
2025-11-04 16:50:16	Performing Malware check on extracted domains	OK
2025-11-04 16:50:24	Android Behaviour Analysis Completed	OK
2025-11-04 16:50:24	Extracting Emails and URLs from Source Code	OK
2025-11-04 16:50:36	Saving to Database	OK
2025-11-04 16:50:49	Email and URL Extraction Completed	OK
2025-11-04 16:50:49	Extracting String data from APK	OK
2025-11-04 16:50:59	Extracting String data from SO	OK

2025-11-04 16:51:01	Extracting String data from Code	OK
2025-11-04 16:51:01	Extracting String values and entropies from Code	OK
2025-11-04 16:51:08	Performing Malware check on extracted domains	OK
2025-11-04 16:51:15	Saving to Database	OK

Report Generated by - MobSF v4.4.3

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2025 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.