MOBSF

ANDROID STATIC ANALYSIS REPORT

trivago (6.46.0)

File Name: Trivago.apk

Package Name:	com.trivago
Scan Date:	Nov. 4, 2025, 4:05 p.m.
App Security Score:	51/100 (MEDIUM RISK)
Grade:	B
Trackers Detection:	5/432

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
2	25	4	2	1

FILE INFORMATION

File Name: Trivago.apk
Size: 47.77MB
MD5: 561f7e2955f08d5cbb51324381f094a4
SHA1: dd3194feaeb099866c8a0c874c808c45d13891cc
SHA256: 716117aa3c49759f6dda13beaed864c3319271243166a4948a0f4484fc340ea0

APP INFORMATION

App Name: trivago
Package Name: com.trivago
Main Activity: com.trivago.ft.splash.frontend.SplashActivity
Target SDK: 35
Min SDK: 28
Max SDK:
Android Version Name: 6.46.0
Android Version Code: 2025100801

APP COMPONENTS

Activities: 51
Services: 17
Receivers: 14
Providers: 6
Exported Activities: 7
Exported Services: 1
Exported Receivers: 3

Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: False
v3 signature: True
v4 signature: False
X.509 Subject: C=DE, ST=NRW, L=trivago.com, O=trivago.com, OU=trivago.com, CN=trivago GmbH
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2010-12-03 14:51:36+00:00
Valid To: 2284-09-17 14:51:36+00:00
Issuer: C=DE, ST=NRW, L=trivago.com, O=trivago.com, OU=trivago.com, CN=trivago GmbH
Serial Number: 0x4cf903f8
Hash Algorithm: sha1
md5: 5b6d186cc17d8f6bfaf679bcd82c8b37
sha1: 6ee7489999214ba6b180de82f42a31e5cf6d8118
sha256: 90553a3356f4319b08b3b23dd29947fcb05229050bfb738152610760ce880ecf
sha512: 4e5f9d8b41b9818dccfd7bed55cc5dded0fc49e2792fa006e8866db46d8ac1b6fc10f7c59e98dafcd2a5139cdb73f2f8a8f98aa9d45c8b195064fef4bdf89292
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: d16b95328b533c60f20bd7d09f49d59a25109dab042eb9d9592e87fd22d4776a
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.DETECT_SCREEN_CAPTURE	normal	notifies when a screen capture of the app's windows is attempted.	Allows an application to get notified when a screen capture of its windows is attempted.
com.google.android.gms.permission.AD_ID	normal	application shows advertisements	This app uses a Google advertising ID and can possibly serve advertisements.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.EXPAND_STATUS_BAR	normal	expand/collapse status bar	Allows application to expand or collapse the status bar.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.trivago.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

PERMISSION	STATUS	INFO	DESCRIPTION
com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE	normal	permission defined by google	A custom permission defined by Google.
android.permission.ACCESS_ADSERVICES_ATTRIBUTION	normal	allow applications to access advertising service attribution	This enables the app to retrieve information related to advertising attribution, which can be used for targeted advertising purposes. App can gather data about how users interact with ads, such as clicks or impressions, to measure the effectiveness of advertising campaigns.
com.samsung.android.mapsagent.permission.READ_APP_INFO	unknown	Unknown permission	Unknown permission from android reference
com.huawei.appmarket.service.commondata.permission.GET_COMMON_DATA	unknown	Unknown permission	Unknown permission from android reference
com.google.android.providers.gsf.permission.READ_GSERVICES	unknown	Unknown permission	Unknown permission from android reference
android.permission.ACCESS_ADSERVICES_AD_ID	normal	allow app to access the device's advertising ID.	This ID is a unique, user-resettable identifier provided by Google's advertising services, allowing apps to track user behavior for advertising purposes while maintaining user privacy.

APKID ANALYSIS

FILE	DETAILS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>
classes2.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check possible Build.SERIAL check Build.TAGS check SIM operator check network operator name check ro.hardware check ro.kernel.qemu check possible VM check</td></tr><tr><td>Anti Debug Code</td><td>Debug.isDebuggerConnected() check</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>

FILE	DETAILS
classes3.dex	

FINDINGS	DETAILS
yara_issue	yara issue - dex file recognized by apkid but not yara module
Anti-VM Code	Build.MODEL check
Compiler	unknown (please file detection issue!)

FILE	DETAILS
classes4.dex	

FINDINGS	DETAILS
yara_issue	yara issue - dex file recognized by apkid but not yara module
Anti-VM Code	possible Build.SERIAL check
Compiler	unknown (please file detection issue!)

FILE	DETAILS
lib/arm64-v8a/libakamaibmp.so	

FINDINGS	DETAILS
anti_hook	syscalls

BROWSABLE ACTIVITIES

ACTIVITY	INTENT

ACTIVITY	INTENT
com.trivago.ft.deeplink.frontend.DeepLinkActivity	Schemes: trivago://, trivago.survey://, https://, Hosts: *, www.trivago.com.tw, www.trivago.com.tr, www.trivago.in, ar.trivago.com, www.trivago.com.ar, www.trivago.hk, www.trivago.com.co, www.trivago.ae, www.trivago.ch, www.trivago.co.id, www.trivago.co.il, www.trivago.co.kr, www.trivago.com.ph, www.trivago.pt, www.trivago.sg, www.trivago.co.th, www.trivago.co.za, www.trivago.at, www.trivago.com.au, www.trivago.be, www.trivago.dk, www.trivago.fi, www.trivago.ie, www.trivago.com.mx, www.trivago.nl, www.trivago.no, www.trivago.pl, www.trivago.se, www.trivago.vn, www.trivago.bg, www.trivago.cl, www.trivago.cz, www.trivago.com.ec, www.trivago.gr, www.trivago.hr, www.trivago.hu, www.trivago.co.nz, www.trivago.pe, www.trivago.ro, www.trivago.rs, www.trivago.si, www.trivago.sk, www.trivago.com.uy, www.trivago.com.br, www.trivago.ca, www.trivago.es, www.trivago.fr, www.trivago.it, www.trivago.com.my, www.trivago.de, www.trivago.jp, www.trivago.co.uk, www.trivago.com, Paths: /, Path Patterns: /.*/srl/.*, /.*/lm/.*, /.*/map/.*, /.*/srl, /.*/lm, /.*/map, /.*/oar/.*, /.*/odr/.*, /.*/opr/.*, /.*/odrb/.*, /.*/odrs/.*, /.*/odrp/.*, /.*-.*/otel, /.*-.*/□□, /.*-.*/hotel, /.*-.*/فندق, /.*-.*/хотел, /.*-.*/ξενοδοχειο, /.*-.*/hotelli, /.*-.*/□□□, /.*-.*/hotell, /.*-.*/■■■■■■, /bg.*,
com.google.firebase.analytics.GoogleAnalyticsServerPreviewActivity	Schemes: tagmanager.sgtm.c.com.trivago://,
com.google.firebase.auth.internal.GenericIdpActivity	Schemes: genericidp://, Hosts: firebase.auth, Paths: /,
com.google.firebase.auth.internal.RecaptchaActivity	Schemes: recaptcha://, Hosts: firebase.auth, Paths: /,
net.openid.appauth.RedirectUriReceiverActivity	Schemes: trivago.auth://,

NETWORK SECURITY

HIGH: **1** | WARNING: **1** | INFO: **0** | SECURE: **0**

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	high	Base config is insecurely configured to permit clear text traffic to all domains.
2	*	warning	Base config is configured to trust system certificates.

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Certificate algorithm might be vulnerable to hash collision	warning	Application is signed with SHA1withRSA. SHA1 hash algorithm is known to have collision issues. The manifest file indicates SHA256withRSA is in use.

MANIFEST ANALYSIS

HIGH: 0 | WARNING: 14 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable Android version Android 9, minSdk=28]	warning	This application can be installed on an older version of android that has multiple vulnerabilities. Support an Android version => 10, API 29 to receive reasonable security updates.
2	App has a Network Security Configuration [android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
3	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
4	Activity (com.trivago.ft.onboarding.frontend.OnboardingActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Activity (com.trivago.ft.deeplink.frontend.DeepLinkActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
6	Broadcast Receiver (com.appsflyer.MultipleInstallBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Activity (com.google.firebase.analytics.GoogleAnalyticsServerPreviewActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	TaskAffinity is set for activity (com.salesforce.marketingcloud.notifications.NotificationOpenActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.
9	Activity (com.google.firebase.auth.internal.GenericIdpActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
10	Activity (com.google.firebase.auth.internal.RecaptchaActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
11	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
12	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
13	Activity (androidx.compose.ui.tooling.PreviewActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
14	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
15	Activity (net.openid.appauth.RedirectUriReceiverActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

CODE ANALYSIS

HIGH: **0** | WARNING: **8** | INFO: **3** | SECURE: **1** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/salesforce/marketingcloud/events/g.java com/salesforce/marketingcloud/events/h.java com/salesforce/marketingcloud/registration/Registration.java com/view/AbstractC1645Gf4.java com/view/C0801Az2.java com/view/C0957Bz2.java com/view/C10091oA2.java com/view/C10227oX0.java com/view/C10464pA2.java com/view/C10835qA2.java com/view/C11141qz2.java com/view/C1139Cz2.java com/view/C11513rz2.java com/view/C11885sz2.java com/view/C12258tz2.java com/view/C12657uz2.java com/view/C1297Dz2.java com/view/C13030vz2.java com/view/C13124wF.java com/view/C13402wz2.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/C13775xz2.java com/view/C14148yz2.java com/view/C14521zz2.java
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/view/C1453Ez2.java com/view/C1608Fz2.java com/view/C2384Kz2.java com/view/C2539Lz2.java com/view/C2694Mz2.java com/view/C2850Nz2.java com/view/C3011Oz2.java com/view/C3478Rz2.java com/view/C3790Tz2.java com/view/C3946Uz2.java com/view/C4102Vz2.java com/view/C4257Wz2.java com/view/C4413Xz2.java com/view/C4568Yz2.java com/view/C4724Zz2.java com/view/C4792aA2.java com/view/C5113b14.java com/view/C5165bA2.java com/view/C5538cA2.java com/view/C6313eA2.java com/view/C6686fA2.java com/view/C7272gh4.java com/view/C7471hA2.java com/view/C7843iA2.java com/view/C8215jA2.java com/view/C8335jU2.java com/view/C8588kA2.java com/view/C9345mA2.java com/view/C9351mB2.java com/view/C9378mG.java com/view/C9718nA2.java com/view/C9751nG.java com/view/FadeInFadeOutAnimationItem.java com/view/ImageRequest.java com/view/ImagesUi.java com/view/ImpressionLoggedItem.java com/view/InterfaceC0915Bs2.java com/view/InterfaceC6804fU0.java com/view/ItemImpressionViewCoordinatesInfo.java com/view/KeyDefaultParams.java com/view/LazyListImpressionViewCoordinatesInfo.java com/view/OF.java com/view/OpaqueKey.java com/view/Options.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/Options.java com/view/PageLogDetailsInput.java com/view/RemoteCacheDbEntity.java com/view/SinglePaneScene.java com/view/SlotReader.java com/view/SuccessResult.java com/view/TextContextMenuItem.java com/view/TextContextMenuRemoteActionItem.java com/view/TrackingData.java com/view/TypefaceRequest.java com/view/UD.java com/view/UserFriendlyUrlQueryParameters.java com/view/VisibleItem.java
2	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/view/C10931qQ2.java com/view/ZV2.java
				com/appsflyer/internal/AFg1eSDK.java com/cyberfend/cyfsecurity/SensorDataBuilder.java com/cyberfend/cyfsecurity/b.java com/mikepenz/aboutlibraries/ui/LibsSupportFragment.java com/salesforce/marketingcloud/MCLogListener.java com/salesforce/marketingcloud/g.java com/salesforce/marketingcloud/legacycrypto/OldSdkHash.java com/salesforce/marketingcloud/media/q.java com/salesforce/marketingcloud/sfmcsdk/components/encryption/EncryptedSharedPreferences.java com/salesforce/marketingcloud/sfmcsdk/components/encryption/Encryptor.java com/salesforce/marketingcloud/sfmcsdk/components/encryption/KeyStoreWrapper.java com/salesforce/marketingcloud/sfmcsdk/components/encryption/SalesforceKeyGenerator.java com/salesforce/marketingcloud/sfmcsdk/components/logging/LogListener.java com/salesforce/marketingcloud/sfmcsdk/components/logging/Logger.java com/salesforce/marketingcloud/tozny/AesCbcWithIntegrity$PrngFixes$LinuxPRNGSecureRandom.java com/view/AC4.java com/view/AbstractBinderC7188gT4.java com/view/AbstractC0731An3.java com/view/AbstractC0866Bk1.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/AbstractC10020ny4.java com/view/AbstractC11252rI.java com/view/AbstractC13237wY.java com/view/AbstractC13321wm.java com/view/AbstractC13682xk.java com/view/AbstractC1467Fb4.java com/view/AbstractC2219Jx4.java com/view/AbstractC3164Pz.java com/view/AbstractC4415Xz4.java com/view/AbstractC4510Yp3.java com/view/AbstractC7001fy4.java com/view/AbstractC8905kz2.java com/view/AbstractC9224lq2.java com/view/AbstractC9230lr2.java com/view/AbstractC9994nu2.java com/view/AbstractServiceC12088tX0.java com/view/B14.java com/view/BinderC12068tT4.java com/view/BinderC12357uF4.java com/view/BinderC13676xj.java com/view/BinderC8986lC4.java com/view/C0711Ak1.java com/view/C0761As4.java com/view/C0770Au1.java com/view/C0797Ay4.java com/view/C10000nv2.java com/view/C10002nv4.java com/view/C1017Cf0.java com/view/C10273oe4.java com/view/C10329oo0.java com/view/C10373ov2.java com/view/C10445p71.java com/view/C10549pP.java com/view/C10560pQ4.java com/view/C10698pn4.java com/view/C10721pr3.java com/view/C10735pu.java com/view/C10764py4.java com/view/C10832qA.java com/view/C10963qV4.java com/view/C11135qy2.java com/view/C11137qy4.java com/view/C11188r71.java com/view/C11196r83.java com/view/C11295rP0.java com/view/C11443rn4.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/C11528s14.java com/view/C11604sE2.java com/view/C11672sP4.java com/view/C11711sW1.java com/view/C11726sY4.java com/view/C11924t54.java com/view/C1207Dk1.java com/view/C12110ta4.java com/view/C12224tt4.java com/view/C12322uA.java com/view/C12456uW1.java com/view/C12504ue1.java com/view/C12718v92.java com/view/C12798vM4.java com/view/C12855vW1.java com/view/C13099wA4.java com/view/C13125wF0.java com/view/C13351wr.java com/view/C13519xI4.java com/view/C13587xU0.java com/view/C13621xZ4.java com/view/C13684xk1.java com/view/C13727xr2.java com/view/C13739xt2.java com/view/C13839yA.java com/view/C13981yX3.java com/view/C1399Eq2.java com/view/C14112yt2.java com/view/C1550Fp3.java com/view/C1604Fy4.java com/view/C1695Go0.java com/view/C1732Gu1.java com/view/C1854Ho4.java com/view/C1964Ih0.java com/view/C2096Jd1.java com/view/C2107Jf0.java com/view/C2213Jw4.java com/view/C2258Ke1.java com/view/C2325Kp3.java com/view/C2351Ku.java com/view/C2392La4.java com/view/C2514Lv1.java com/view/C2652Ms2.java com/view/C2684Mx4.java com/view/C2811Nt.java com/view/C3057Ph0.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/C3076Pk1.java com/view/C3080Pl.java com/view/C3524Sh0.java
3	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/view/C3531Si1.java com/view/C3547Sl.java com/view/C3624Sx4.java com/view/C3646Tb2.java com/view/C3748Ts2.java com/view/C3753Tt1.java com/view/C3802Ub2.java com/view/C3902Us0.java com/view/C3930Uw4.java com/view/C3948Uz4.java com/view/C3959Vb2.java com/view/C3976Ve1.java com/view/C4016Vl.java com/view/C4066Vt1.java com/view/C4283Xd4.java com/view/C4531Yt1.java com/view/C4538Yu2.java com/view/C4582Zb2.java com/view/C4610Zg0.java com/view/C4694Zu2.java com/view/C4836aH4.java com/view/C4943aZ3.java com/view/C4960ac2.java com/view/C4974ae4.java com/view/C4977af1.java com/view/C5027an3.java com/view/C5038ap2.java com/view/C5053as.java com/view/C5333bc2.java com/view/C5440bu1.java com/view/C5476c01.java com/view/C5605cL3.java com/view/C5672cW4.java com/view/C5706cc2.java com/view/C5755ck3.java com/view/C5784cp2.java com/view/C5908d54.java com/view/C5975dH.java com/view/C6118de4.java com/view/C6201ds.java com/view/C6211dt3.java com/view/C6246dz2.java com/view/C6339eE4.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/C6393eN4.java com/view/C6400eP.java com/view/C6462eZ1.java com/view/C6481ec2.java com/view/C6486ed1.java com/view/C6773fP.java com/view/C6921fn3.java com/view/C7203gW1.java com/view/C7343gt3.java com/view/C7615hY2.java com/view/C7656hf1.java com/view/C7989iY4.java com/view/C8025ie4.java com/view/C8223jB4.java com/view/C8366jZ3.java com/view/C8623kG1.java com/view/C8679kN4.java com/view/C8745kY4.java com/view/C8781ke4.java com/view/C8823kl4.java com/view/C8842kp.java com/view/C8849kq0.java com/view/C8881kv2.java com/view/C8954l72.java com/view/C9186lk0.java com/view/C9208ln4.java com/view/C9294m2.java com/view/C9334m83.java com/view/C9342mA.java com/view/C9425mN4.java com/view/C9618mu.java com/view/C9711n91.java com/view/C9954nn4.java com/view/CN4.java com/view/CP3.java com/view/D82.java com/view/DG.java com/view/DJ1.java com/view/E30.java com/view/E44.java com/view/ER4.java com/view/F01.java com/view/FA4.java com/view/FL4.java com/view/FN4.java com/view/FW4.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/FX4.java com/view/FZ3.java com/view/GB2.java com/view/GI2.java com/view/H82.java com/view/HF4.java com/view/HT4.java com/view/HandlerC13501xF4.java com/view/HandlerC13874yF4.java com/view/HandlerC5612cM4.java com/view/II4.java com/view/IP0.java com/view/InputConnectionC1316Ec3.java com/view/InputConnectionC1472Fc3.java com/view/J00.java com/view/JJ4.java com/view/JN4.java com/view/JO4.java com/view/KF4.java com/view/KY0.java com/view/KY4.java com/view/L43.java com/view/LM4.java com/view/LP.java com/view/LP2.java com/view/LY4.java com/view/LZ4.java com/view/LayoutInflaterFactory2C3475Rz.java com/view/MF4.java com/view/MO3.java com/view/MQ0.java com/view/MZ4.java com/view/MenuItemC3125Ps2.java com/view/P14.java com/view/PE4.java com/view/QA4.java com/view/QE2.java com/view/R11.java com/view/RK3.java com/view/RN4.java com/view/RO3.java com/view/RunnableC10424p34.java com/view/RunnableC5347be4.java com/view/SB.java com/view/SE4.java com/view/SF1.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/view/SZ.java com/view/ServiceConnectionC10105oC4.java com/view/T11.java com/view/T92.java com/view/TE4.java com/view/TR2.java com/view/TW4.java com/view/UH.java com/view/VV1.java com/view/VX4.java com/view/W14.java com/view/W30.java com/view/WF4.java com/view/X72.java com/view/XI4.java com/view/XM4.java com/view/XR3.java com/view/Y20.java com/view/YB4.java com/view/YV1.java com/view/ZC0.java com/view/ZE4.java com/view/ZV2.java com/view/ZX3.java
	App uses SQLite Database and execute raw			com/view/ft/debug/installbuild/frontend/DebugInstallBuildActivity.java com/salesforce/marketingcloud/storage/db/a.java com/salesforce/marketingcloud/storage/db/b.java com/salesforce/marketingcloud/storage/db/c.java com/salesforce/marketingcloud/storage/db/e.java com/salesforce/marketingcloud/storage/db/f.java com/salesforce/marketingcloud/storage/db/g.java com/salesforce/marketingcloud/storage/db/h.java com/salesforce/marketingcloud/storage/db/i.java com/salesforce/marketingcloud/storage/db/j.java com/salesforce/marketingcloud/storage/db/k.java com/salesforce/marketingcloud/storage/db/l.java com/salesforce/marketingcloud/storage/db/m.java com/salesforce/marketingcloud/storage/db/upgrades/a.java com/salesforce/marketingcloud/storage/db/upgrades/b.java com/salesforce/marketingcloud/storage/db/upgrades/c.java com/salesforce/marketingcloud/storage/db/upgrades/d.java com/salesforce/marketingcloud/storage/db/upgrades/e.

NO	ISSUE	SEVERITY	STANDARDS	FILES
4	SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/salesforce/marketingcloud/storage/db/upgrades/f.java com/salesforce/marketingcloud/storage/db/upgrades/g.java com/salesforce/marketingcloud/storage/db/upgrades/h.java com/salesforce/marketingcloud/storage/db/upgrades/i.java com/salesforce/marketingcloud/storage/db/upgrades/j.java com/salesforce/marketingcloud/storage/db/upgrades/k.java com/salesforce/marketingcloud/storage/db/upgrades/l.java com/view/BinderC12068tT4.java com/view/C10159oL4.java com/view/C12828vR4.java com/view/C1757Gy3.java com/view/C2759Nk1.java com/view/C4062Vs3.java com/view/C8283jL4.java com/view/VX4.java com/view/XI4.java com/view/y05.java
5	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	com/salesforce/marketingcloud/legacycrypto/OldSdkHash.java com/view/C12730vB2.java com/view/C6832fY4.java
6	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	com/appsflyer/internal/AFa1jSDK.java com/cyberfend/cyfsecurity/a.java com/view/AbstractC4735a1.java com/view/C10576pT2.java com/view/C12070tU0.java com/view/C3222Qi3.java com/view/C5656cU0.java com/view/C6832fY4.java com/view/E93.java com/view/F01.java com/view/HS4.java com/view/Q11.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
7	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	com/salesforce/marketingcloud/sfmcsdk/components/encryption/Encryptor.java com/salesforce/marketingcloud/sfmcsdk/components/encryption/SalesforceKeyGenerator.java com/view/C4066Vt1.java com/view/SF1.java
8	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/view/SD0.java
9	App can write to App Directory. Sensitive Information should be encrypted.	info	CWE: CWE-276: Incorrect Default Permissions OWASP MASVS: MSTG-STORAGE-14	com/view/FO3.java
10	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	com/view/DD4.java com/view/HI4.java com/view/L00.java
11	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	com/view/ft/settings/frontend/SettingsFragment.java
12	Insecure WebView Implementation. Execution of user controlled code in WebView is a critical Security Hole.	warning	CWE: CWE-749: Exposed Dangerous Method or Function OWASP Top 10: M1: Improper Platform Usage OWASP MASVS: MSTG-PLATFORM-7	com/cyberfend/cyfsecurity/CYFWebViewService.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libakamaibmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	armeabi-v7a/libakamaibmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libakamaibmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	x86_64/libakamaibmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	armeabi-v7a/libakamaibmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	arm64-v8a/libakamaibmp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00091	Retrieve data from broadcast	collection	com/appsflyer/internal/AFa1rSDK.java com/appsflyer/internal/AFa1uSDK.java com/salesforce/marketingcloud/alarms/b.java com/salesforce/marketingcloud/messages/push/a.java com/salesforce/marketingcloud/notifications/a.java com/salesforce/marketingcloud/sfmcsdk/components/behaviors/BehaviorManagerImpl.java com/view/C14337zU4.java com/view/ft/main/frontend/MainActivity.java net/openid/appauth/AuthorizationManagementActivity.java
00014	Read file into a stream and put it into a JSON object	file	com/appsflyer/internal/AFg1qSDK.java com/view/C10931qQ2.java com/view/C13366wt2.java com/view/C2889Of0.java com/view/C5258bQ.java

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	com/appsflyer/internal/AFc1rSDK.java com/appsflyer/internal/AFf1kSDK.java com/appsflyer/internal/AFg1qSDK.java com/salesforce/marketingcloud/storage/d.java com/salesforce/marketingcloud/tozny/AesCbcWithIntegrity$PrngFixes$LinuxPRNGSecureRandom.java com/salesforce/marketingcloud/util/c.java com/salesforce/marketingcloud/util/d.java com/salesforce/marketingcloud/util/e.java com/view/C10931qQ2.java com/view/C11443rn4.java com/view/C12730vB2.java com/view/C13090w91.java com/view/C13366wt2.java com/view/C2501Lt0.java com/view/C2889Of0.java com/view/C5258bQ.java com/view/C5453bw2.java com/view/C5476c01.java com/view/C6930fp0.java com/view/C8965l91.java com/view/C9766nI2.java com/view/C9911ng3.java com/view/DB2.java com/view/Q91.java com/view/SB.java com/view/ZV2.java

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/appsflyer/internal/AFa1rSDK.java com/appsflyer/internal/AFa1uSDK.java com/appsflyer/internal/AFb1tSDK.java com/appsflyer/internal/AFe1cSDK.java com/cyberfend/cyfsecurity/CYFWebViewService.java com/view/C10768pz2.java com/view/C14337zU4.java com/view/C4016Vl.java com/view/C4465Yi0.java com/view/C4687Zt1.java com/view/C5076aw.java com/view/C5147b72.java com/view/C6033dQ3.java com/view/C7737hs4.java com/view/C9793nN.java com/view/C9932nk0.java com/view/HS4.java com/view/J00.java com/view/VX4.java com/view/ft/accommodation/details/AccommodationDetailsActivity.java com/view/ft/debug/installbuild/frontend/DebugInstallBuildActivity.java com/view/ft/feedback/frontend/FeedbackDialogFragment.java net/openid/appauth/b.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/view/C4016Vl.java com/view/C4465Yi0.java com/view/C4687Zt1.java com/view/C9932nk0.java com/view/J00.java com/view/ft/accommodation/details/AccommodationDetailsActivity.java com/view/ft/debug/installbuild/frontend/DebugInstallBuildActivity.java com/view/ft/feedback/frontend/FeedbackDialogFragment.java

RULE ID	BEHAVIOUR	LABEL	FILES
00096	Connect to a URL and set request method	command network	com/appsflyer/internal/AFc1aSDK.java com/appsflyer/internal/AFd1fSDK.java com/salesforce/marketingcloud/media/q.java com/salesforce/marketingcloud/media/r.java com/salesforce/marketingcloud/sfmcsdk/components/http/NetworkManager.java com/view/C12070tU0.java com/view/C2096Jd1.java com/view/C5125b34.java com/view/C7511hH0.java com/view/LS.java com/view/R34.java
00089	Connect to a URL and receive input stream from the server	command network	com/appsflyer/internal/AFc1aSDK.java com/appsflyer/internal/AFd1fSDK.java com/salesforce/marketingcloud/media/q.java com/salesforce/marketingcloud/media/r.java com/salesforce/marketingcloud/sfmcsdk/components/http/NetworkManager.java com/view/C12070tU0.java com/view/C2096Jd1.java com/view/C5125b34.java com/view/IR4.java com/view/LS.java com/view/R34.java com/view/RunnableC5666cV4.java
00109	Connect to a URL and get the response code	network command	com/appsflyer/internal/AFc1aSDK.java com/appsflyer/internal/AFd1fSDK.java com/appsflyer/internal/AFf1xSDK.java com/salesforce/marketingcloud/sfmcsdk/components/http/NetworkManager.java com/view/C12070tU0.java com/view/C2096Jd1.java com/view/C5125b34.java com/view/IR4.java com/view/JN4.java com/view/LS.java com/view/R34.java com/view/RunnableC5666cV4.java com/view/WG4.java

RULE ID	BEHAVIOUR	LABEL	FILES
00016	Get location info of the device and put it to JSON object	location collection	com/salesforce/marketingcloud/messages/d.java
00022	Open a file from given absolute path of the file	file	com/appsflyer/internal/AFg1qSDK.java com/salesforce/marketingcloud/storage/d.java com/salesforce/marketingcloud/util/c.java com/view/C12730vB2.java com/view/C13366wt2.java com/view/C13534xL1.java com/view/C13835y91.java com/view/C14208z91.java com/view/C1483Fe2.java com/view/C3076Pk1.java com/view/C5453bw2.java com/view/C9711n91.java com/view/DB2.java com/view/F91.java com/view/ZV2.java
00009	Put data in cursor to JSON object	file	com/salesforce/marketingcloud/storage/db/a.java com/salesforce/marketingcloud/storage/db/d.java com/salesforce/marketingcloud/storage/db/f.java com/salesforce/marketingcloud/storage/db/m.java com/salesforce/marketingcloud/storage/db/upgrades/a.java com/salesforce/marketingcloud/storage/db/upgrades/l.java
00026	Method reflection	reflection	com/view/XO1.java com/view/YO1.java
00191	Get messages in the SMS inbox	sms	com/appsflyer/internal/AFj1lSDK.java com/appsflyer/internal/AFj1sSDK.java com/appsflyer/internal/AFj1uSDK.java com/appsflyer/internal/AFj1wSDK.java com/view/B14.java

RULE ID	BEHAVIOUR	LABEL	FILES
00036	Get resource file from res/raw directory	reflection	com/appsflyer/internal/AFa1uSDK.java com/appsflyer/internal/AFe1aSDK.java com/appsflyer/internal/AFj1sSDK.java com/appsflyer/internal/AFj1uSDK.java com/appsflyer/internal/AFj1zSDK.java com/salesforce/marketingcloud/media/q.java com/view/B14.java com/view/C4016Vl.java com/view/C4687Zt1.java com/view/C9932nk0.java com/view/J00.java
00121	Create a directory	file command	com/view/C9186lk0.java
00125	Check if the given file path exist	file	com/view/C9186lk0.java
00012	Read data and put it into a buffer stream	file	com/view/C5476c01.java
00202	Make a phone call	control	com/view/C4465Yi0.java com/view/ft/accommodation/details/AccommodationDetailsActivity.java
00203	Put a phone number into an intent	control	com/view/C4465Yi0.java com/view/ft/accommodation/details/AccommodationDetailsActivity.java
00030	Connect to the remote server through the given URL	network	com/salesforce/marketingcloud/media/q.java com/view/C7511hH0.java com/view/IR4.java com/view/RunnableC5666cV4.java
00094	Connect to a URL and read data from it	command network	com/view/IR4.java com/view/PD1.java com/view/RunnableC5666cV4.java
00108	Read the input stream from given URL	network command	com/view/IR4.java com/view/RunnableC5666cV4.java
00034	Query the current data network type	collection network	com/view/C9932nk0.java

RULE ID	BEHAVIOUR	LABEL	FILES
00192	Get messages in the SMS inbox	sms	com/appsflyer/internal/AFb1iSDK.java
00011	Query data from URI (SMS, CALLLOGS)	sms calllog collection	com/appsflyer/internal/AFb1iSDK.java com/appsflyer/internal/AFj1lSDK.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	com/appsflyer/internal/AFb1iSDK.java com/appsflyer/internal/AFj1lSDK.java
00074	Get IMSI and the ISO country code	collection telephony	com/view/C4831aH.java
00146	Get the network operator name and IMSI	telephony collection	com/view/C4831aH.java
00078	Get the network operator name	collection telephony	com/appsflyer/internal/AFi1pSDK.java com/view/C4831aH.java
00106	Get the currently formatted WiFi IP address	collection wifi	com/view/C4831aH.java
00130	Get the current WIFI information	wifi collection	com/view/C4831aH.java
00117	Get the IMSI and network operator name	telephony collection	com/view/C4831aH.java
00065	Get the country code of the SIM card provider	collection	com/view/C4831aH.java
00066	Query the ICCID number	collection	com/view/C4831aH.java
00134	Get the current WiFi IP address	wifi collection	com/view/C4831aH.java
00067	Query the IMSI number	collection	com/view/C4831aH.java
00084	Get the ISO country code and IMSI	collection telephony	com/view/C4831aH.java
00132	Query The ISO country code	telephony collection	com/view/C4831aH.java

RULE ID	BEHAVIOUR	LABEL	FILES
00024	Write file after Base64 decoding	reflection file	com/view/C1483Fe2.java
00147	Get the time of current location	collection location	com/view/C8823kl4.java
00075	Get location of the device	collection location	com/view/C8823kl4.java
00115	Get last known location of the device	collection location	com/view/C8823kl4.java
00162	Create InetSocketAddress object and connecting to it	socket	com/view/C5656cU0.java
00163	Create new Socket and connecting to it	socket	com/view/C5656cU0.java
00189	Get the content of a SMS message	sms	com/appsflyer/internal/AFj1lSDK.java
00188	Get the address of a SMS message	sms	com/appsflyer/internal/AFj1lSDK.java
00200	Query data from the contact list	collection contact	com/appsflyer/internal/AFj1lSDK.java
00201	Query data from the call log	collection calllog	com/appsflyer/internal/AFj1lSDK.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	com/view/C9294m2.java
00005	Get absolute path of file and put it to JSON object	file	com/appsflyer/internal/AFg1qSDK.java com/view/C13366wt2.java
00029	Initialize class object dynamically	reflection	com/view/F72.java
00079	Hide the current app's icon	evasion	com/view/AbstractC3164Pz.java
00153	Send binary data over HTTP	http	com/view/C5125b34.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
App talks to a Firebase database	info	The app talks to Firebase database at https://trv-member-sso.firebaseio.com
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/363634697571/namespaces/firebase:fetch?key=AIzaSyCywqj_Xjh8zzj5oaHfuIxUxeaG6iAp8nI. This is indicated by the response: The response code is 403

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	6/25	android.permission.INTERNET, android.permission.ACCESS_FINE_LOCATION, android.permission.ACCESS_COARSE_LOCATION, android.permission.ACCESS_WIFI_STATE, android.permission.ACCESS_NETWORK_STATE, android.permission.WAKE_LOCK
Other Common Permissions	3/44	com.google.android.gms.permission.AD_ID, com.google.android.c2dm.permission.RECEIVE, com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
svalidate-and-log.s	ok	No Geolocation information available.
goo.gl	ok	**IP:** 142.251.143.110 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.youzhan.com	ok	**IP:** 194.153.186.54 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
scdn-stestsettings.s	ok	No Geolocation information available.
cdn-hs-graphql-hkg.trivago.com	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.no	ok	**IP:** 2.19.124.150 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.se	ok	**IP:** 2.19.124.162 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.es	ok	**IP:** 2.19.124.153 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.it	ok	**IP:** 2.19.124.148 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.pe	ok	**IP:** 2.19.124.133 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
firebase-settings.crashlytics.com	ok	**IP:** 142.251.143.195 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
sregister.s	ok	No Geolocation information available.
www.trivago.pl	ok	**IP:** 2.19.124.153 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
simpression.s	ok	No Geolocation information available.
www.trivago.fi	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.no	ok	**IP:** 2.19.124.133 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.de	ok	**IP:** 2.19.124.161 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sonelink.s	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
www.example.com	ok	**IP:** 23.202.156.226 **Country:** United States of America **Region:** Virginia **City:** Manassas **Latitude:** 38.750950 **Longitude:** -77.475273 **View:** Google Map
www.trivago.com.tr	ok	**IP:** 2.19.124.151 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.de	ok	**IP:** 2.19.124.158 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
imgcy.trivago.com	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.pt	ok	**IP:** 2.19.124.133 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.rs	ok	**IP:** 2.19.124.142 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.es	ok	**IP:** 2.19.124.155 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.co.uk	ok	**IP:** 2.19.124.155 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.hk	ok	**IP:** 2.19.124.148 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
company.youzhan.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
www.trivago.com.ar	ok	**IP:** 2.19.124.150 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
goo.gle	ok	**IP:** 67.199.248.13 **Country:** United States of America **Region:** New York **City:** New York City **Latitude:** 40.739288 **Longitude:** -73.984955 **View:** Google Map
www.trivago.com.co	ok	**IP:** 2.19.124.161 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.com.ph	ok	**IP:** 2.19.124.132 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.si	ok	**IP:** 2.19.124.161 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.com.ec	ok	**IP:** 2.19.124.139 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
scdn-ssettings.s	ok	No Geolocation information available.
spia.s	ok	No Geolocation information available.
magazine.trivago	ok	No Geolocation information available.
www.trivago.ru	ok	**IP:** 2.19.124.142 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.sk	ok	**IP:** 2.19.124.141 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
trivago.co.kr	ok	**IP:** 2.19.124.153 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
ssdk-services.s	ok	No Geolocation information available.
magazine.trivago.se	ok	**IP:** 2.19.124.137 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sattr.s	ok	No Geolocation information available.
magazine.trivago.gr	ok	**IP:** 194.153.186.54 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
www.trivago.sg	ok	**IP:** 2.19.124.162 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.com	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
cdn-hs-graphql-stage.trivago.com	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.dk	ok	**IP:** 194.153.186.54 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map
mc4rc13vbt4qsbx4w3gyt8v6jpdy.device.marketingcloudapis.com	ok	**IP:** 13.111.7.85 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.788464 **Longitude:** -122.394608 **View:** Google Map
www.trivago.co.kr	ok	**IP:** 2.19.124.153 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
support.trivago.com	ok	**IP:** 216.198.54.6 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.773968 **Longitude:** -122.410446 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
magazine.trivago.com	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
mikepenz.com	ok	**IP:** 172.67.141.197 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
developer.android.com	ok	**IP:** 142.250.180.174 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.trivago.be	ok	**IP:** 2.19.124.154 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
android.googlesource.com	ok	**IP:** 173.194.69.82 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
youtrack.jetbrains.com	ok	**IP:** 63.33.88.220 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
pagead2.googlesyndication.com	ok	**IP:** 142.251.209.34 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.trivago.cl	ok	**IP:** 2.19.124.147 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.ae	ok	**IP:** 2.19.124.143 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.com.tw	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
cdn-hs-graphql-sfo.trivago.com	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
github.com	ok	**IP:** 140.82.121.4 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.trivago.jp	ok	**IP:** 2.19.124.148 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.google.com	ok	**IP:** 142.250.180.132 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.trivago.co.th	ok	**IP:** 2.19.124.144 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.com.my	ok	**IP:** 2.19.124.152 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.bg	ok	**IP:** 2.19.124.146 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.com.au	ok	**IP:** 2.19.124.145 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
cdn-hs-graphql-dca.trivago.com	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.at	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.cloudinary.com	ok	**IP:** 162.159.130.82 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.trivago.cz	ok	**IP:** 2.19.124.142 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.dk	ok	**IP:** 2.19.124.146 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sadrevenue.s	ok	No Geolocation information available.
www.trivago.hu	ok	**IP:** 2.19.124.149 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.in	ok	**IP:** 2.19.124.141 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.hr	ok	**IP:** 2.19.124.161 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.ch	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sars.s	ok	No Geolocation information available.
magazine.trivago.fr	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
magazine.trivago.fi	ok	**IP:** 2.19.124.143 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.ca	ok	**IP:** 2.19.124.135 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
app.igodigital.com	ok	**IP:** 34.204.4.97 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
xmlpull.org	ok	**IP:** 185.199.110.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
www.trivago.com.uy	ok	**IP:** 2.19.124.151 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
privacy-sandbox.appsflyersdk.com	ok	**IP:** 3.166.81.97 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.
stage.app.igodigital.com	ok	**IP:** 52.86.255.74 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
www.trivago.co.id	ok	**IP:** 2.19.124.163 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.com.br	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.com.br	ok	**IP:** 2.19.124.137 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sapp.s	ok	No Geolocation information available.
firebase.google.com	ok	**IP:** 142.250.180.174 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
issuetracker.google.com	ok	**IP:** 216.58.204.142 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
sdlsdk.s	ok	No Geolocation information available.
magazine.trivago.nl	ok	**IP:** 194.153.186.54 **Country:** Germany **Region:** Hessen **City:** Frankfurt am Main **Latitude:** 50.115520 **Longitude:** 8.684170 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
console.firebase.google.com	ok	**IP:** 142.250.180.174 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
magazine.trivago.com.ar	ok	**IP:** 2.19.124.158 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sinapps.s	ok	No Geolocation information available.
svalidate.s	ok	No Geolocation information available.
trivago.it	ok	**IP:** 2.19.124.136 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
cdn-hs-graphql-dus.trivago.com	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
app-measurement.com	ok	**IP:** 142.251.140.110 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
sconversions.s	ok	No Geolocation information available.
trivago.com	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sgcdsdk.s	ok	No Geolocation information available.
www.trivago.gr	ok	**IP:** 2.19.124.138 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.firebase.google.com	ok	No Geolocation information available.
www.trivago.co.za	ok	**IP:** 2.19.124.153 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.nl	ok	**IP:** 2.19.124.139 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
trv-member-sso.firebaseio.com	ok	**IP:** 34.120.206.254 **Country:** United States of America **Region:** Missouri **City:** Kansas City **Latitude:** 39.099731 **Longitude:** -94.578568 **View:** Google Map
www.trivago.pt	ok	**IP:** 2.19.124.136 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
google.com	ok	**IP:** 216.58.204.142 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
xml.org	ok	**IP:** 104.239.142.8 **Country:** United States of America **Region:** Texas **City:** Windcrest **Latitude:** 29.499678 **Longitude:** -98.399246 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.trivago.vn	ok	**IP:** 2.19.124.146 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
sviap.s	ok	No Geolocation information available.
www.trivago.ie	ok	**IP:** 2.19.124.139 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.com.mx	ok	**IP:** 2.19.124.152 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.it	ok	**IP:** 2.19.124.136 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
ns.adobe.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
www.trivago.co.nz	ok	**IP:** 2.19.124.160 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
auth.trivago.com	ok	**IP:** 2.19.124.134 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.com.tr	ok	**IP:** 2.19.124.139 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
magazine.trivago.com.mx	ok	**IP:** 2.19.124.139 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.googleadservices.com	ok	**IP:** 142.251.209.34 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
play.google.com	ok	**IP:** 142.250.180.174 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
accounts.google.com	ok	**IP:** 173.194.69.84 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.trivago.fr	ok	**IP:** 2.19.124.161 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
www.trivago.co.il	ok	**IP:** 2.19.124.154 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
plus.google.com	ok	**IP:** 142.250.180.174 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
salesforce-marketingcloud.github.io	ok	**IP:** 185.199.109.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
www.w3.org	ok	**IP:** 104.18.22.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.trivago.ro	ok	**IP:** 2.19.124.163 **Country:** Sweden **Region:** Stockholms lan **City:** Stockholm **Latitude:** 59.332581 **Longitude:** 18.064899 **View:** Google Map
firebasestorage.googleapis.com	ok	**IP:** 216.58.205.42 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
smonitorsdk.s	ok	No Geolocation information available.
slaunches.s	ok	No Geolocation information available.

EMAILS

EMAIL	FILE
mobile@trivago.com	com/view/C6673f81.java
u0013android@android.com0 u0013android@android.com	com/view/BinderC12834vS4.java
fdf_@nw.cgnh	com/view/C2681Mx1.java
trv@trivago.com	com/view/P50.java
fdf_@nw.gfjnbh	com/cyberfend/cyfsecurity/a.java
read@trivago.com	com/view/ft/debug/installbuild/frontend/DebugInstallBuildActivity.java
info@youzhan.com mobile@trivago.com	Android String Resource

TRACKERS

TRACKER	CATEGORIES	URL
AppsFlyer	Analytics	https://reports.exodus-privacy.eu.org/trackers/12
Google CrashLytics	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/27
Google Firebase Analytics	Analytics	https://reports.exodus-privacy.eu.org/trackers/49
Google Tag Manager	Analytics	https://reports.exodus-privacy.eu.org/trackers/105
Salesforce Marketing Cloud		https://reports.exodus-privacy.eu.org/trackers/220

HARDCODED SECRETS

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Slaptažodis"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parolă"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"child_key_example_1" : "child_key_example_1"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "סיסמה"
"google_crash_reporting_api_key" : "AIzaSyCywqj_Xjh8zzj5oaHfuIxUxeaG6iAp8nI"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Klucz"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Zaporka"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Tilgangsnøkkel"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Geslo"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parole"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "گذرواژه"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Sandi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Fjalëkalimi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "პაროლი"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Senha"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■"
"google_maps_key" : "AIzaSyBZgoSu03zHT9uoNInwR_QFh0skJ_eGh_8"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□□□□"
"google_auth_server_id" : "363634697571-lj09qn82grlkcma3sud1c11bo7srajd3.apps.googleusercontent.com"
"apps_flyer_development_key" : "m26Yetn6jW5T7nyF9N48nV"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "ລະຫັດຜ່ານ"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Toegangssleutel"
"child_key_example_3" : "child_key_example_3"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Nyckel"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Парола"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Jelszó"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passord"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Sarbide-gakoa"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Palavra-passe"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Գաղտնաբառ"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Сырсөз"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lozinka"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lösenord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Iphasiwedi"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Kod"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Wachtwoord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Heslo"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Pasahitza"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Avainkoodi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Лозинка"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passwort"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Hasło"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Անցաբառ"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Şifre"
"firebase_database_url" : "https://trv-member-sso.firebaseio.com"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"google_play_service_intent_key" : "market://details?id=%s"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Пароль"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□"
"com.google.firebase.crashlytics.mapping_file_id" : "a63b5b9c93ae4ff69235a7b8cb95692e"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "ภะแจผ่าบ"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Wagwoordsleutel"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Adgangskode"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"library_fastadapter_authorWebsite" : "http://mikepenz.com/"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■"
"google_play_service_disbaled_intent_key" : "https://play.google.com/store/apps/details?id=%s"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Aðgangsorð"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "گذرکلید"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contraseña"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parool"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■"
"google_api_key" : "AIzaSyCywqj_Xjh8zzj5oaHfuIxUxeaG6iAp8nI"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Salasana"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Pääsuvõti"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Aðgangslykill"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasinal"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasenya"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parol"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"child_key_example_2" : "child_key_example_2"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Wagwoord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Adgangsnøgle"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "[redacted]"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "[redacted]"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Nenosiri"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Azonosítókulcs"

POSSIBLE SECRETS
b3312fa7e23ee7e4988e056be3f82d19181d9c6efe8141120314088f5013875ac656398d8a2ed19d2a85c8edd3ec2aef
0010a8eca11e1565dc8b54edab9a8238
26b0e8f8c1395f07ab62be1b292c4cb400caa63d41a922cf5e47f1a7025e1f7d
ChNjb20uYW5kcm9pZC52ZW5kaW5nCiBjb20uZ29vZ2xlLmFuZHJvaWQuYXBwcy5tZWV0aW5ncwohY29tLmdvb2dsZS5hbmRyb2lkLmFwcHMubWVzc2FnaW5n
36864200e0eaf5284d884a0e77d31646
258EAFA5-E914-47DA-95CA-C5AB0DC85B11
68647976601306097149819007990813932172694353001433054093944634591855431833976560521225596406614545549772963113914808580371219879997166438125740282911150577151
a0784d7a4716f3feb4f64e7f4b39bf04
849f26e2-2df6-11e4-ab12-14109fdc48df
241037bb3d500e7f6956c6e392cb67b196b33caa93bb0754d77678c9b82987c7
2a043ee8eff9dc613e0194337bb7ca7bd123e05ef1b164a84bb0640c526e6f37
6b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296
156858211eb091affc28d29de12574f76b2b88ee6341d4d5fb0219f21c685ce2
69f098748877c10c8a7a6c9f437238bdbe67be60a451b342beb3a4e493fb0411
E3F9E1E0CF99D0E56A055BA65E241B3399F7CEA524326B0CDD6EC1327ED0FDC1
88308986b48bfe0efa8039ddbdadf39a16d7cb56ca5b08afe4b4156e1e72c247
af60eb711bd85bc1e4d3e0a462e074eea428a8

POSSIBLE SECRETS
96b9dfc5535b5289d9f46148fd928678dda2855ba9a40b36fa3769056519ce8c
a1f905d4f8bdb6aa6075e23f41cbca2cde77cf63638cfd6088700215f6eb9e02
aa87ca22be8b05378eb1c71ef320ad746e1d3b628ba79b9859f741e082542a385502f25dbf55296c3a545e3872760ab7
c7a6e96946496d81bc1be6d9fcf302c6b5e49e2c57e65f22b9b6903c26d38ffd
9caeeeade404cb54ece0fc997ca13e6601fd28de5436c0e07d80830406d36ed7
eec0cd775c15ad988a1f69290a36e2d69734eb42bb1d8caf6a22b2c096d95814
115792089210356248762697446949407573530086143415290314195533631308867097853951
21a3ab00468748902c31c2ab0cf25e0260270c22d6630aab1a3e11e0b24427a4
3BAF59A2E5331C30675FAB35FF5FFF0D116142D3D4664F1C3CB804068B40614F
FFE391E0EA186D0734ED601E4E70E3224B7309D48E2075BAC46D8C667EAE7212
3617de4a96262c6f5d9e98bf9292dc29f8f41dbd289a147ce9da3113b5f0b8c00a60b1ce1d7e819d7a431d7c90ea0e5f
4fe342e2fe1a7f9b8ee7eb4a7c0f9e162bce33576b315ececbb6406837bf51f5
bae8e37fc83441b16034566b
dc848ed8dcbef4feb7c7664e84f98f28c89bca2b2fe726cd05018ab764684b0d
5ac635d8aa3a93e7b3ebbd55769886bc651d06b0cc53b0f63bce3c3e27d2604b
72312c30b9dbb8f9a5e99a22d80c886a33e4e27dcbfe3d97780b7f0564c64beb
8f6d430dedcaff6f1e749658ad9e5ca71db95eff5f996cdc145ae041d6b9c5fd
11839296a789a3bc0045c8a5fb42c7d1bd998f54449579b446817afbd17273e662c97ee72995ef42640c550b9013fad0761353c7086a272c24088be94769fd16650

POSSIBLE SECRETS
f9f6ffc0d29aabb3ab1ed1e77465c89b4dd71e9620484c29d2352172ec188945
cad610ac85cc5abff9292db1728adfb5cedb623b4068226d729a33263fbf1fdc
c12569151c8827df12d4b95918e32fb9
a4f3a997de8a693484cf799520a9f5d4fcfd7ed3101454df03477332cb0ed555
31fbc07be5012359cfa4e6b31e6674e1ea74e6cc3dfa916208278596ad8810c2
ebf44cf248d98df99058021c4ca5e5fae3b86943b7f3504d7650e4ed9699144d
39402006196394479212279040100143613805079739270465446667946905279627659399113263569398956308152294913554433653942643
3d0c5a8c1351e05ef9d44b2d407576ef5dd01788b44f0ed6e1fa8f934157c5fc
470fa2b4ae81cd56ecbcda9735803434cec591fa
e4a2676773eab0186ca9ff6dd4ad581c21762913d4c0a073144b687775efe94e
913ba183a28e5f60ccdd15bdd8799535d8d67951e821f14c0b9f345cd47a2aac
25c0fd35fe9b2ae066bb03154e3c31b2f548f0b7a188cd7b6313dcd56fae722b
e0390393319ebc39fb2be77e29af85b74fddee0cd25399dfbe7bcf7fffe745a8
a6839e13444a9950b7741a6053fbc7c7517c4e8ffcbd2e71ac2d0fe3d6a4a523
68647976601306097149819007990813932172694353001433054093944634591855431833976553942450577463332171975329639963713633211138647686124403803403728088927070005449
6d0275317826fcd1ba176c29613fd441612aa0dc29d02e0d6291af5e22d4614a
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112319

POSSIBLE SECRETS
6d80abec69f72a38804d6de15f60ed596542a6209b93f60e5256bbff90a78089
42907ee9551b6960433fa59a8891cbb7708dbfcceb5c13e3a2c66b14501a5ec7
e4ee107331ba7787ab460e3279027406f80852e6b1a74f58c82615d93c410e73
4d787e59-cfc7-423a-b3f2-738acab4c3b2
F6389234-1024-481F-9173-37D9D7F5051F
FBA3AF4E7757D9016E953FB3EE4671CA2BD9AF725F9A53D52ED4A38EAAA08901
da0cfaa6187b3fe9085ccf3a5bb13773a8fd546aef7b6d65e70bf8cb30f4fb25
dca8397d39ed7c2452b6be032db0506f7344b0e3332ad551e27a8e09dffec3d7
574c08af-49ff-4a70-8d0f-57c2babff30f
d06209c1815d5c5c3ef451c5780ccf5a00365a2140675a5115eca7cce27da79e
c6858e06b70404e9cd9e3ecb662395b4429c648139053fb521f828af606b4d3dbaa14b5e77efe75928fe1dc127a2ffa8de3348b3c1856a429bf97e7e31c2e5bd66
025c23c7c75ea5ca72f802238b96c7f1
4675cf5696b40778acdeb8989afc8fdebeae23c4964c2353b851812a178214c2
80706c8e8b970e79b9a57237f424aed1a188822d70bfd937dbcdc30f037ebeeb
9bdd98074655b8748c75281140dd764af3e21e9ad773a6c6e95e341364834c26
ac9b1b0135b7013c6dc64783c098ca15679ff3c074e183c06aac8e88e85f775f
ab6ef38f405ff7fa45210eb45f33ce18ef806e66fa81f59bbe73aed2d3f04155
051953eb9618e1c9a1f929a21a0b68540eea2da725b99b315f3b8b489918ef109e156193951ec7e937b1652c0bd3bb1bf073573df883d2c34f1ef451fd46b503f00

POSSIBLE SECRETS
0a2b52074b13cbcd8a7666ed4724e477eba8db1442f91731dc868be7039cc7b2
84f8add05b73b7eabb620c99722bcc9892c85ca4bb30599deba992bd499e7929
58c3d724f661064231ae059f9cffd26145677d68a71504a60c033f3a87258ec0
115792089210356248762697446949407573529996955224135760342422259061068512044369
9e56dfe2-86c6-4563-a5a0-73bde22d5fb7
ac46e27b2282726920892687a7aa5e0f
808182838485868788898a8b8c8d8e8f909192939495969798999a9b9c9d9e9f
0b67fbbf2669200d119b375b087dd4968914da80bbdba7b57af0cbf4f2c57d9b
9c0494e3d34f06097bc5c60a8a2c05816ed2b4b4589737c60626aab4e4baed55

PLAYSTORE INFORMATION

Title: trivago: Compare hotel prices

Score: 4.453252 **Installs:** 100,000,000+ **Price:** 0 **Android Version Support:** **Category:** Travel & Local **Play Store URL:** com.trivago

Developer Details: trivago N.V., 6990042735476603793, None, https://www.trivago.com, mobile@trivago.com,

Release Date: Dec 3, 2010 **Privacy Policy:** Privacy link

Description:

The trivago app is the easy way to search and compare hotel prices from your favorite booking sites so you can find a hotel or accommodation in the location you want, with the amenities you need, and for a deal you'll feel amazing about. - Compare accommodation prices from major booking sites with one search - Get exclusive mobile rates on your phone or tablet - Get price drop alerts for your favorite hotels - Save favorite accommodations and compare them side-by-side - Read aggregated guest reviews from multiple booking sites - Search over 5 million properties in more than 190 countries and find amazing hotel deals No matter what type of traveler you are, or what type of budget you have, the trivago app makes your hotel search simpler than ever. Compare prices from hundreds of booking sites With trivago, you don't just search for hotel offers in your dream vacation destinations, you also get to compare prices from the major booking sites like Expedia, Hotels.com, Accor, ZenHotels, Booking.com, Trip.com, Priceline, TravelUp, Orbitz, HotelTonight, and more. With over 5 million hotels and other accommodations to choose from worldwide, finding the right stay at the right price doesn't get much easier than this. Mobile rates for deal-hunters on the go The trivago app features deals on hotels that you can only access on your mobile device — something all you deal-hunters out there won't want to miss out on. Just search for your hotel like you normally would, and keep an eye out for the "mobile rate"

badge to know when you've found a special deal. Get a heads-up when prices drop Have a trip coming up and want to try and book your stay for cheap? Now you can sign up for price drop alerts on the trivago app to stay on top of price changes for your favorite hotels. Instead of constant searching, you'll get notified as soon as prices drop so you can act fast and get an awesome deal. Save hotels and compare them side-by-side Whether your dream hotel is pet-friendly, has late-checkout, offers free cancellation, or includes a breakfast buffet, the trivago app makes it easy to save your favorite stays. When you feel like booking your trip, you can compare chosen hotels side-by-side to see how they match up before making your decision, so can always be confident you got the right stay at the right price. Real talk from real guests Along with always-updating price information, the trivago app aggregates guest ratings from major booking sites to give you the best understanding of real-world experiences at each hotel. The trivago rating index creates a combined score of available ratings so that you can see what other guests have to say, and always be ready to book your room with confidence. 5 million hotel beds and counting With over over 5 million properties in more than 190 countries, you can find the perfect stay for every trip on the trivago app. Find rooms at boutique hotels, luxury hotels, airport hotels, hostels, bed and breakfasts, lodges, vacation rentals, resorts, and everything in between with one simple search. Download trivago's free app today and start searching, comparing, and saving on your next adventure.

SCAN LOGS

Timestamp	Event	Error
2025-11-04 16:05:52	Generating Hashes	OK
2025-11-04 16:05:52	Extracting APK	OK
2025-11-04 16:05:52	Unzipping	OK
2025-11-04 16:05:52	Parsing APK with androguard	OK
2025-11-04 16:05:53	Extracting APK features using aapt/aapt2	OK
2025-11-04 16:05:53	Getting Hardcoded Certificates/Keystores	OK
2025-11-04 16:05:55	Parsing AndroidManifest.xml	OK
2025-11-04 16:05:56	Extracting Manifest Data	OK

2025-11-04 16:05:56	Manifest Analysis Started	OK
2025-11-04 16:05:56	Reading Network Security config from network_security_config.xml	OK
2025-11-04 16:05:56	Parsing Network Security config	OK
2025-11-04 16:05:56	Performing Static Analysis on: trivago (com.trivago)	OK
2025-11-04 16:05:57	Fetching Details from Play Store: com.trivago	OK
2025-11-04 16:05:57	Checking for Malware Permissions	OK
2025-11-04 16:05:57	Fetching icon path	OK
2025-11-04 16:05:57	Library Binary Analysis Started	OK
2025-11-04 16:05:57	Analyzing lib/x86_64/libakamaibmp.so	OK
2025-11-04 16:05:57	Analyzing lib/x86_64/libandroidx.graphics.path.so	OK
2025-11-04 16:05:57	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK
2025-11-04 16:05:57	Analyzing lib/armeabi-v7a/libakamaibmp.so	OK

2025-11-04 16:05:57	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2025-11-04 16:05:57	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2025-11-04 16:05:57	Analyzing lib/arm64-v8a/libakamaibmp.so	OK
2025-11-04 16:05:57	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-11-04 16:05:57	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2025-11-04 16:05:57	Analyzing lib/x86/libandroidx.graphics.path.so	OK
2025-11-04 16:05:57	Analyzing lib/x86/libdatastore_shared_counter.so	OK
2025-11-04 16:05:57	Analyzing apktool_out/lib/x86_64/libakamaibmp.so	OK
2025-11-04 16:05:57	Analyzing apktool_out/lib/x86_64/libandroidx.graphics.path.so	OK
2025-11-04 16:05:57	Analyzing apktool_out/lib/x86_64/libdatastore_shared_counter.so	OK
2025-11-04 16:05:57	Analyzing apktool_out/lib/armeabi-v7a/libakamaibmp.so	OK
2025-11-04 16:05:58	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK

2025-11-04 16:05:58	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2025-11-04 16:05:58	Analyzing apktool_out/lib/arm64-v8a/libakamaibmp.so	OK
2025-11-04 16:05:58	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-11-04 16:05:58	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2025-11-04 16:05:58	Analyzing apktool_out/lib/x86/libandroidx.graphics.path.so	OK
2025-11-04 16:05:58	Analyzing apktool_out/lib/x86/libdatastore_shared_counter.so	OK
2025-11-04 16:05:58	Reading Code Signing Certificate	OK
2025-11-04 16:05:58	Running APKiD 3.0.0	OK
2025-11-04 16:06:00	Detecting Trackers	OK
2025-11-04 16:06:02	Decompiling APK to Java with JADX	OK
2025-11-04 16:07:02	Converting DEX to Smali	OK
2025-11-04 16:07:02	Code Analysis Started on - java_source	OK

2025-11-04 16:07:10	Android SBOM Analysis Completed	OK
2025-11-04 16:07:28	Android SAST Completed	OK
2025-11-04 16:07:28	Android API Analysis Started	OK
2025-11-04 16:07:37	Android API Analysis Completed	OK
2025-11-04 16:07:37	Android Permission Mapping Started	OK
2025-11-04 16:07:50	Android Permission Mapping Completed	OK
2025-11-04 16:07:51	Android Behaviour Analysis Started	OK
2025-11-04 16:08:07	Android Behaviour Analysis Completed	OK
2025-11-04 16:08:07	Extracting Emails and URLs from Source Code	OK
2025-11-04 16:08:18	Email and URL Extraction Completed	OK
2025-11-04 16:08:18	Extracting String data from APK	OK
2025-11-04 16:08:19	Extracting String data from SO	OK

2025-11-04 16:08:19	Extracting String data from Code	OK
2025-11-04 16:08:19	Extracting String values and entropies from Code	OK
2025-11-04 16:08:25	Performing Malware check on extracted domains	OK
2025-11-04 16:08:34	Saving to Database	OK

Report Generated by - MobSF v4.4.3

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2025 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.