

Deliverable 1

Structural Aliasing Analysis in Time-Series Forecasting Using Chronos

Matteo Boniotti, Gianluca Brignoli and Federico Sabbadini *

June 1, 2026

This investigation formalizes the phenomenon of *structural aliasing* within patch-based time-series foundation models, focusing specifically on Amazon’s Chronos-Bolt framework. [1, 2] The project focuses on smart-grid load balancing.

Intended Audience

This analysis is directly intended for researchers and practitioners utilizing large language models within the Chronos family for time-series analysis, representation learning, and forecasting, as well as individuals interested in characterizing the fundamental limitations, structural boundaries, and latent capabilities of these architectures.

This study is also explicitly directed toward researchers, engineers, and practitioners working in the field of energy management and domains directly related to this described infrastructure.

Purpose and Scope

This project formalises and empirically validates the phenomenon of *structural aliasing* in patch-based time-series foundation models, using Amazon Chronos-Bolt-Tiny as the target architecture.

Chronos-Bolt-Tiny operates with a fixed patch size of $P = 16$, stride of $S = 16$ and context window of $T = 512$ tokens as default settings, and four encoder blocks followed by four decoder blocks terminating in a direct quantile projection head. [3]

This study aims to provide a comprehensive understanding of the relationships between raw signal characteristics and the latent representations learned by the model, systematically identifying the critical links between sampling frequency (f_s), patch size (P), and stride (S) in order to propose actionable solutions to mitigate the phenomenon.

Layer-resolved probing is executed sequentially across the intermediate hidden states of the encoder and decoder blocks, plus at the final output probability distribution level. By mapping representations across these specific layers, the project isolates where task-relevant signal attributes are preserved or compromised under architectural synchronization constraints.

Stride is systematically varied within the range of $S \in [8, 16]$ to explore the explicit impact of patch geometry on aliasing effects.

*This work is licensed under the Creative Commons Attribution 4.0 International License. Concurrently, all associated source code, probing scripts, and software artifacts generated throughout the project lifecycle are released under the open-source MIT license.

Copyright for any third-party material included in this work remains with its respective owners and must be respected accordingly.

During the preparation of this work, the authors used AI-based tools, including GPT-5.5, Gemini 3.1 Pro, Gemini 3.5 Flash, Sonnet 4.6, and Opus 4.7, to support language refinement and improve clarity. All generated or suggested content was carefully reviewed, revised where necessary, and validated by the authors, who assume full responsibility for the final content of this work.

The core objective is to challenge the baseline assumption that pre-trained temporal foundation models inherently preserve frequency attributes when processing Nyquist-compliant signals.

Domain Description

To ground this abstract architectural evaluation, the study utilizes a specific physical domain as an empirical reference layer. This reference setting models the solar energy produced by a photovoltaic array attached to an internal load, a local storage battery, and the national electricity grid. The explicit operational objective within this system is to evaluate production variations over short-term future horizons so that the system can dynamically modify the internal load, attach and detach the battery unit, with the aim of maintaining internal grid stability and enabling precise anomaly detection.

Within this infrastructure, a control AI agent is responsible for executing real-time tasks: dynamic load-balancing, battery dispatch, state-monitoring and active anomaly detection, and internal grid stability maintenance.

Significance and Impact

This subject is relevant because it explores an unexamined systemic vulnerability native to patch-based temporal foundation architectures. By systematically characterizing the conditions under which structural aliasing emerges, this work will provide critical insights into the fundamental limitations of these models, directly informing the design of more robust architectures and training paradigms.

For professionals operating within this domain, the analysis could expose how algorithmic data-deletion anomalies can propagate through automated distribution pipelines. By evaluating how hidden token-space representation collapse can deceive a load-balancing AI agent into executing misaligned control choices, this work could provide insights needed for high-reliability, fault-tolerant smart-grid deployments.

The impact of this project could extend beyond theoretical understanding, as it has direct implications for the reliability and safety of real-world applications that depend on accurate time-series forecasting and representation learning, particularly in high-stakes domains such as energy management.

Project Outline

At first the project will focus on the definition of the phenomenon, particularly:

- formal domain description through OWL2 ontology of the physical system (photovoltaic array, battery storage, national grid, internal load), signal (frequency, amplitude, timespan, phase) and signal patched representation (patch size, stride, sampling frequency);
- patch-based tokenization and patch aliasing formal definition as function of the patch size (P), stride (S) and sampling frequency (f_s);
- phase-locking condition formal definition;

Then, after defining a set of falsifiable hypotheses, including:

- the existence of frequency-dependent blind spots at harmonics of a patch-induced frequency;
- the dependence of the effect on temporal alignment;
- the impact of patch size, stride, and overlap.

The project will focus on the empirical validation of the phenomenon, through:

- use of a light implementation of TSMixup [1] to generate synthetic data by mixing different frequency sinusoidal signals;

- test of the model on simple sinusoidal signals and TSMixup generated ones to verify the presence of blind spots and phase-locking effects.

If previous analyses show evidence of aliasing in synthetic data, the project may analyze signals produced with KernelSynth [1] to test whether the phenomenon persists in more complex signals. If the phenomenon is verified on synthetic data, the project will then focus on the analysis of real-world data, through the use of the `Dataset-SolarTechLab.csv` dataset, which contains one-minute multivariate telemetry stream of a photovoltaic array. [4]

The project will focus on the analysis of the phenomenon, through MDL probing [5] after each decoder block to verify the presence, or absence, of frequency information in the hidden states. The analysis will be performed through the use of Bayesian statistics. Discussion of possible mitigation strategies, including stride reduction.

Finally, the project will include a formal risk assessment grounded in the NIST AI Risk Management Framework (AI RMF) to evaluate structural aliasing as a systematic vulnerability within cyber-physical energy systems. This analysis will outline plausible threat models and attack surfaces, and evaluate whether the proposed mitigation strategies effectively reduce residual exposure for the automated control AI agent. The risk assessment will be structured around the following key points:

- Context and Attack Surface: identify vulnerable points.
- Threat Modeling: define potential attacks.
- Consequences and Impact: assess system damage.
- Mitigation and Residual Exposure: evaluate remaining risks.

References

- [1] Abdul Fatir Ansari et al. *Chronos: Learning the Language of Time Series*. Nov. 4, 2024. DOI: 10.48550/arXiv.2403.07815. arXiv: 2403.07815 [cs.LG]. URL: <http://arxiv.org/abs/2403.07815> (visited on 05/13/2026). Pre-published.
- [2] Abdul Fatir Ansari et al. *Fast and Accurate Zero-Shot Forecasting with Chronos-Bolt and AutoGluon / Artificial Intelligence*. Dec. 2, 2024. URL: <https://aws.amazon.com/blogs/machine-learning/fast-and-accurate-zero-shot-forecasting-with-chronos-bolt-and-autogluon/> (visited on 05/13/2026).
- [3] *ChronosBoltPipeline / Amazon-Science/Chronos-Forecasting*. DeepWiki. URL: <https://deepwiki.com/amazon-science/chronos-forecasting/2.4-chronosboltpipeline> (visited on 05/13/2026).
- [4] Sonia Leva et al. *Photovoltaic Power and Weather Parameters*. IEEE DataPort, Sept. 23, 2020. DOI: 10.21227/42V0-JZ14. URL: <https://ieee-dataport.org/open-access/photovoltaic-power-and-weather-parameters> (visited on 06/01/2026).
- [5] Elena Voita and Ivan Titov. “Information-Theoretic Probing with Minimum Description Length”. In: *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. EMNLP 2020. Ed. by Bonnie Webber et al. Online: Association for Computational Linguistics, Nov. 2020, pp. 183–196. DOI: 10.18653/v1/2020.emnlp-main.14. URL: <https://aclanthology.org/2020.emnlp-main.14/> (visited on 05/13/2026).