Captures du code par service

Service : Agence

Interface : IAgenceService.java

IAgenceService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Agence;

import java.util.List;

public interface IAgenceService {
    Agence ajouterAgence(Agence agence);
    Agence modifierAgence(Agence agence);
    List<Agence> consulterAgences();
    Agence consulterAgenceById(Long idAgence);
    void supprimerAgenceById(Long idAgence);
}
```

Implémentation : IAgenceServiceImp.java

IAgenceServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Agence;
import tn.esprit.autoloc.autolocapi.repository.AgenceRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IAgenceServiceImp implements IAgenceService {

    private final AgenceRepository agenceRepository;

    @Override
    public Agence ajouterAgence(Agence agence) {
        return agenceRepository.save(agence);
    }

    @Override
    public Agence modifierAgence(Agence agence) {
        return agenceRepository.save(agence);
    }

    @Override
    public List<Agence> consulterAgences() {
        return agenceRepository.findAll();
    }

    @Override
    public Agence consulterAgenceById(Long idAgence) {
        return agenceRepository.findById(idAgence).orElse(null);
    }

    @Override
    public void supprimerAgenceById(Long idAgence) {
        agenceRepository.deleteById(idAgence);
    }
}
```

Service : Client

Interface : IClientService.java

IClientService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Client;

import java.util.List;

public interface IClientService {
    Client ajouterClient(Client client);
    Client modifierClient(Client client);
    List<Client> consulterClients();
    Client consulterClientById(Long idClient);
    void supprimerClientById(Long idClient);
}
```

Implémentation : IClientServiceImp.java

IClientServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Client;
import tn.esprit.autoloc.autolocapi.repository.ClientRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IClientServiceImp implements IClientService {

    private final ClientRepository clientRepository;

    @Override
    public Client ajouterClient(Client client) {
        return clientRepository.save(client);
    }

    @Override
    public Client modifierClient(Client client) {
        return clientRepository.save(client);
    }

    @Override
    public List<Client> consulterClients() {
        return clientRepository.findAll();
    }

    @Override
    public Client consulterClientById(Long idClient) {
        return clientRepository.findById(idClient).orElse(null);
    }

    @Override
    public void supprimerClientById(Long idClient) {
        clientRepository.deleteById(idClient);
    }
}
```

Service : Contrat

Interface : IContratService.java

IContratService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Contrat;

import java.util.List;

public interface IContratService {
    Contrat ajouterContrat(Contrat contrat);
    Contrat modifierContrat(Contrat contrat);
    List<Contrat> consulterContrats();
    Contrat consulterContratById(Long idContrat);
    void supprimerContratById(Long idContrat);
}
```

Implémentation : IContratServiceImp.java

IContratServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Contrat;
import tn.esprit.autoloc.autolocapi.repository.ContratRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IContratServiceImp implements IContratService {

    private final ContratRepository contratRepository;

    @Override
    public Contrat ajouterContrat(Contrat contrat) {
        return contratRepository.save(contrat);
    }

    @Override
    public Contrat modifierContrat(Contrat contrat) {
        return contratRepository.save(contrat);
    }

    @Override
    public List<Contrat> consulterContrats() {
        return contratRepository.findAll();
    }

    @Override
    public Contrat consulterContratById(Long idContrat) {
        return contratRepository.findById(idContrat).orElse(null);
    }

    @Override
    public void supprimerContratById(Long idContrat) {
        contratRepository.deleteById(idContrat);
    }
}
```

Service : Employe

Interface : IEmployeService.java

IEmployeService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Employe;

import java.util.List;

public interface IEmployeService {
    Employe ajouterEmploye(Employe employe);
    Employe modifierEmploye(Employe employe);
    List<Employe> consulterEmployes();
    Employe consulterEmployeById(Long idEmploye);
    void supprimerEmployeById(Long idEmploye);
}
```

Implémentation : IEmployeServiceImp.java

IEmployeServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Employe;
import tn.esprit.autoloc.autolocapi.repository.EmployeRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IEmployeServiceImp implements IEmployeService {

    private final EmployeRepository employeRepository;

    @Override
    public Employe ajouterEmploye(Employe employe) {
        return employeRepository.save(employe);
    }

    @Override
    public Employe modifierEmploye(Employe employe) {
        return employeRepository.save(employe);
    }

    @Override
    public List<Employe> consulterEmployes() {
        return employeRepository.findAll();
    }

    @Override
    public Employe consulterEmployeById(Long idEmploye) {
        return employeRepository.findById(idEmploye).orElse(null);
    }

    @Override
    public void supprimerEmployeById(Long idEmploye) {
        employeRepository.deleteById(idEmploye);
    }
}
```

Service : Equipement

Interface : IEquipementService.java

IEquipementService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Equipement;

import java.util.List;

public interface IEquipementService {
    Equipement ajouterEquipement(Equipement equipement);
    Equipement modifierEquipement(Equipement equipement);
    List<Equipement> consulterEquipements();
    Equipement consulterEquipementById(Long idEquipement);
    void supprimerEquipementById(Long idEquipement);
}
```

Implémentation : IEquipementServiceImp.java

IEquipementServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Equipement;
import tn.esprit.autoloc.autolocapi.repository.EquipementRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IEquipementServiceImp implements IEquipementService {

    private final EquipementRepository equipementRepository;

    @Override
    public Equipement ajouterEquipement(Equipement equipement) {
        return equipementRepository.save(equipement);
    }

    @Override
    public Equipement modifierEquipement(Equipement equipement) {
        return equipementRepository.save(equipement);
    }

    @Override
    public List<Equipement> consulterEquipements() {
        return equipementRepository.findAll();
    }

    @Override
    public Equipement consulterEquipementById(Long idEquipement) {
        return equipementRepository.findById(idEquipement).orElse(null);
    }

    @Override
    public void supprimerEquipementById(Long idEquipement) {
        equipementRepository.deleteById(idEquipement);
    }
}
```

Service : Maintenance

Interface : IMaintenanceService.java

IMaintenanceService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Maintenance;

import java.util.List;

public interface IMaintenanceService {
    Maintenance ajouterMaintenance(Maintenance maintenance);
    Maintenance modifierMaintenance(Maintenance maintenance);
    List<Maintenance> consulterMaintenances();
    Maintenance consulterMaintenanceById(Long idMaintenance);
    void supprimerMaintenanceById(Long idMaintenance);
}
```

Implémentation : IMaintenanceServiceImp.java

IMaintenanceServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Maintenance;
import tn.esprit.autoloc.autolocapi.repository.MaintenanceRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IMaintenanceServiceImp implements IMaintenanceService {

    private final MaintenanceRepository maintenanceRepository;

    @Override
    public Maintenance ajouterMaintenance(Maintenance maintenance) {
        return maintenanceRepository.save(maintenance);
    }

    @Override
    public Maintenance modifierMaintenance(Maintenance maintenance) {
        return maintenanceRepository.save(maintenance);
    }

    @Override
    public List<Maintenance> consulterMaintenances() {
        return maintenanceRepository.findAll();
    }

    @Override
    public Maintenance consulterMaintenanceById(Long idMaintenance) {
        return maintenanceRepository.findById(idMaintenance).orElse(null);
    }

    @Override
    public void supprimerMaintenanceById(Long idMaintenance) {
        maintenanceRepository.deleteById(idMaintenance);
    }
}
```

Service : Paiement

Interface : IPaiementService.java

IPaiementService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Paiement;

import java.util.List;

public interface IPaiementService {
    Paiement ajouterPaiement(Paiement paiement);
    Paiement modifierPaiement(Paiement paiement);
    List<Paiement> consulterPaiements();
    Paiement consulterPaiementById(Long idPaiement);
    void supprimerPaiementById(Long idPaiement);
}
```

Implémentation : IPaiementServiceImp.java

IPaiementServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Paiement;
import tn.esprit.autoloc.autolocapi.repository.PaiementRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IPaiementServiceImp implements IPaiementService {

    private final PaiementRepository paiementRepository;

    @Override
    public Paiement ajouterPaiement(Paiement paiement) {
        return paiementRepository.save(paiement);
    }

    @Override
    public Paiement modifierPaiement(Paiement paiement) {
        return paiementRepository.save(paiement);
    }

    @Override
    public List<Paiement> consulterPaiements() {
        return paiementRepository.findAll();
    }

    @Override
    public Paiement consulterPaiementById(Long idPaiement) {
        return paiementRepository.findById(idPaiement).orElse(null);
    }

    @Override
    public void supprimerPaiementById(Long idPaiement) {
        paiementRepository.deleteById(idPaiement);
    }
}
```

Service : Reservation

Interface : IReservationService.java

IReservationService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Reservation;

import java.util.List;

public interface IReservationService {
    Reservation ajouterReservation(Reservation reservation);
    Reservation modifierReservation(Reservation reservation);
    List<Reservation> consulterReservations();
    Reservation consulterReservationById(Long idReservation);
    void supprimerReservationById(Long idReservation);
}
```

Implémentation : IReservationServiceImp.java

IReservationServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Reservation;
import tn.esprit.autoloc.autolocapi.repository.ReservationRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IReservationServiceImp implements IReservationService {

    private final ReservationRepository reservationRepository;

    @Override
    public Reservation ajouterReservation(Reservation reservation) {
        return reservationRepository.save(reservation);
    }

    @Override
    public Reservation modifierReservation(Reservation reservation) {
        return reservationRepository.save(reservation);
    }

    @Override
    public List<Reservation> consulterReservations() {
        return reservationRepository.findAll();
    }

    @Override
    public Reservation consulterReservationById(Long idReservation) {
        return reservationRepository.findById(idReservation).orElse(null);
    }

    @Override
    public void supprimerReservationById(Long idReservation) {
        reservationRepository.deleteById(idReservation);
    }
}
```

Service : Vehicule

Interface : IVehiculeService.java

IVehiculeService.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import tn.esprit.autoloc.autolocapi.domain.Vehicule;

import java.util.List;

public interface IVehiculeService {
    Vehicule ajouterVehicule(Vehicule vehicule);
    Vehicule modifierVehicule(Vehicule vehicule);
    List<Vehicule> consulterVehicules();
    Vehicule consulterVehiculeById(Long idVehicule);
    void supprimerVehiculeById(Long idVehicule);
}
```

Implémentation : IVehiculeServiceImp.java

IVehiculeServiceImp.java – AutoLoc

```java
package tn.esprit.autoloc.autolocapi.service;

import lombok.AllArgsConstructor;
import org.springframework.stereotype.Service;
import tn.esprit.autoloc.autolocapi.domain.Vehicule;
import tn.esprit.autoloc.autolocapi.repository.VehiculeRepository;

import java.util.List;

@Service
@AllArgsConstructor
public class IVehiculeServiceImp implements IVehiculeService {

    private final VehiculeRepository vehiculeRepository;

    @Override
    public Vehicule ajouterVehicule(Vehicule vehicule) {
        return vehiculeRepository.save(vehicule);
    }

    @Override
    public Vehicule modifierVehicule(Vehicule vehicule) {
        return vehiculeRepository.save(vehicule);
    }

    @Override
    public List<Vehicule> consulterVehicules() {
        return vehiculeRepository.findAll();
    }

    @Override
    public Vehicule consulterVehiculeById(Long idVehicule) {
        return vehiculeRepository.findById(idVehicule).orElse(null);
    }

    @Override
    public void supprimerVehiculeById(Long idVehicule) {
        vehiculeRepository.deleteById(idVehicule);
    }
}
```