

# CodeAssistant 报告

(由自动审查与测试生成系统输出)

## Contents

|     |                |    |
|-----|----------------|----|
| 1   | 代码审查 (Review)  | 1  |
| 1.1 | 概览             | 1  |
| 1.2 | 严重性分布          | 1  |
| 1.3 | 工具分布           | 1  |
| 1.4 | DS 规则分布        | 1  |
| 1.5 | Top 20 问题      | 1  |
| 1.6 | 复杂度摘要          | 3  |
| 2   | 测试生成 (TestGen) | 47 |
| 2.1 | 指标             | 47 |
| 2.2 | 覆盖率报告          | 47 |

---

## 1 代码审查 (Review)

### 1.1 概览

- 问题总数: 22
- 高/中/低: 10 / 4 / 8
- 工具数: 4
- DS 规则命中总数: 1

### 1.2 严重性分布

- high: 10
- low: 8
- medium: 4

### 1.3 工具分布

- bandit: 10
- rule-plugin: 8
- ast-rule: 3
- ds-rule: 1

### 1.4 DS 规则分布

- DS\_PANDAS\_SETTINGWITHCOPY: 1

## 1.5 Top 20 问题

1. [medium] ast-rule BARE\_EXCEPT  
位置: `src/flask/app.py:1571`  
说明: 避免裸 `except:`, 应捕获明确异常类型。
2. [high] rule-plugin PY\_RESOURCE\_LEAK  
位置: `src/flask/app.py:444`  
说明: `open()` 调用应在 `with` 语句中使用以确保正确关闭
3. [high] rule-plugin PY\_RESOURCE\_LEAK  
位置: `src/flask/app.py:466`  
说明: `open()` 调用应在 `with` 语句中使用以确保正确关闭
4. [high] rule-plugin PY\_RESOURCE\_LEAK  
位置: `src/flask/app.py:442`  
说明: `open()` 调用应在 `with` 语句中使用以确保正确关闭
5. [high] rule-plugin PY\_RESOURCE\_LEAK  
位置: `src/flask/app.py:464`  
说明: `open()` 调用应在 `with` 语句中使用以确保正确关闭
6. [high] rule-plugin PY\_RESOURCE\_LEAK  
位置: `src/flask/blueprints.py:128`  
说明: `open()` 调用应在 `with` 语句中使用以确保正确关闭
7. [high] rule-plugin PY\_RESOURCE\_LEAK  
位置: `src/flask/blueprints.py:126`  
说明: `open()` 调用应在 `with` 语句中使用以确保正确关闭
8. [high] ast-rule BANNED\_CALL  
位置: `src/flask/cli.py:1023`  
说明: 禁止使用 `eval` (项目/领域规则), 建议安全替代或白名单。
9. [high] ast-rule BANNED\_CALL  
位置: `src/flask/config.py:209`  
说明: 禁止使用 `exec` (项目/领域规则), 建议安全替代或白名单。
10. [low] rule-plugin PY\_LOOP\_INVARIANT  
位置: `src/flask/config.py:358`  
说明: 考虑在循环外计算长度, 避免每次迭代都重新计算
11. [low] rule-plugin PY\_GLOBAL\_VARIABLE  
位置: `src/flask/testing.py:101`  
说明: 检测到全局变量 `'werkzeug_version'` 的使用; 考虑使用参数传递代替
12. [high] ds-rule DS\_PANDAS\_SETTINGWITHCOPY  
位置: `src/flask/sansio/scaffold.py:654`  
说明: Chained indexing may trigger SettingWithCopy; use `.loc/.iloc`.
13. [low] bandit B106  
位置: `D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/flaskr/_/_init/__.py:9`  
说明: Possible hardcoded password: `'dev'`

14. [low] bandit B101  
位置: D:/code\\_assistant/Git\\_repo/pallets\\_\\_flask/src/flask/app.py:351  
说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.
15. [medium] bandit B307  
位置: D:/code\\_assistant/Git\\_repo/pallets\\_\\_flask/src/flask/cli.py:1023  
说明: Use of possibly insecure function - consider using safer ast.literal\_eval.
16. [low] bandit B110  
位置: D:/code\\_assistant/Git\\_repo/pallets\\_\\_flask/src/flask/config.py:163  
说明: Try, Except, Pass detected.
17. [medium] bandit B102  
位置: D:/code\\_assistant/Git\\_repo/pallets\\_\\_flask/src/flask/config.py:209  
说明: Use of exec detected.
18. [low] bandit B101  
位置: D:/code\\_assistant/Git\\_repo/pallets\\_\\_flask/src/flask/debughelpers.py:59  
说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.
19. [medium] bandit B704  
位置: D:/code\\_assistant/Git\\_repo/pallets\\_\\_flask/src/flask/json/tag.py:188  
说明: Potential XSS with “markupsafe.Markup“ detected. Do not use “Markup“ on untrusted data.
20. [low] bandit B101  
位置: D:/code\\_assistant/Git\\_repo/pallets\\_\\_flask/src/flask/sansio/scaffold.py:705  
说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.

## 1.6 复杂度摘要

- 来源: Radon Cyclomatic Complexity (CC)
- 说明: 等级通常为 A (简单) 到 F (复杂), 括号内为复杂度分数

| 文件  | 类型 | 符号 (函数/方法)  | 等级 | 分数 |
|---|----|-------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/docs/conf.py                            | F  | github_link | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/docs/conf.py                            | F  | setup       | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/examples/celery/src/tasks\_app/tasks.py | F  | process     | A  | 2  |

(续下页)

| 文件   | 类型 | 符号（函数/方法）           | 等级 | 分数 |
|--|----|---------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/tasks.py         | F  | add                 | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/tasks.py         | F  | block               | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/views.py         | F  | result              | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/views.py         | F  | add                 | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/views.py         | F  | block               | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/views.py         | F  | process             | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/\_\_init\_\_.py  | F  | create_app          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/celery/src/task\_app/\_\_init\_\_.py  | F  | celery_init_app     | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/javascript/js\_example/views.py       | F  | index               | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/javascript/js\_example/views.py       | F  | add                 | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/javascript/tests/conftest.py          | F  | fixture_app         | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/javascript/tests/conftest.py          | F  | client              | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/javascript/tests/test\_js\_example.py | F  | test_add            | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/javascript/tests/test\_js\_example.py | F  | test_index          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/auth.py               | F  | register            | B  | 7  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/auth.py               | F  | login               | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/auth.py               | F  | load_logged_in_user | A  | 2  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）       | 等级 | 分数 |
|--|----|-----------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/auth.py         | F  | login_required  | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/auth.py         | F  | logout          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/blog.py         | F  | get_post        | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/blog.py         | F  | create          | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/blog.py         | F  | update          | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/blog.py         | F  | index           | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/blog.py         | F  | delete          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/db.py           | F  | get_db          | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/db.py           | F  | close_db        | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/db.py           | F  | init_db         | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/db.py           | F  | init_db_command | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/db.py           | F  | init_app        | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/flaskr/\_\_init\_\_.py | F  | create_app      | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/conftest.py      | C  | AuthActions     | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/conftest.py      | F  | app             | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/conftest.py      | F  | client          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/conftest.py      | F  | runner          | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                    | 等级 | 分数 |
|--|----|------------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/conftest.py  | F  | auth                         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/conftest.py  | M  | AuthActions.__init__         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/conftest.py  | M  | AuthActions.login            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/conftest.py  | M  | AuthActions.logout           | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_auth.py | F  | test_login                   | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_auth.py | F  | test_register                | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_auth.py | F  | test_register_validate_input | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_auth.py | F  | test_login_validate_input    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_auth.py | F  | test_logout                  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_index                   | B  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_author_required         | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_create                  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_update                  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_delete                  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_login_required          | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_exists_required         | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/examples/tutorial/tests/test_blog.py | F  | test_create_update_validate  | A  | 2  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                      | 等级 | 分数 |
|--|----|--------------------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/test\_db.py      | F  | test_get_close_db              | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/test\_db.py      | F  | test_init_db_command           | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/test\_factory.py | F  | test_config                    | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_flask/examples/tutorial/tests/test\_factory.py | F  | test_hello                     | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.make_response            | C  | 16 |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.url_for                  | C  | 13 |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.run                      | C  | 12 |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.__init_subclass__        | B  | 10 |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.preprocess_request       | B  | 8  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.create_url_adapter       | B  | 7  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.handle_user_exception    | B  | 7  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.handle_exception         | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.process_response         | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.wsgi_app                 | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | C  | Flask                          | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.raise_routing_exception  | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.update_template_context  | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.create_jinja_environment | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.handle_http_exception    | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.dispatch_request         | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.do_teardown_request      | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | F  | _make_timedelta                | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_flask/src/flask/app.py                         | M  | Flask.__init__                 | A  | 3  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                           | 等级 | 分数 |
|---|----|-------------------------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.get_send_file_max_age         | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.open_resource                 | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.full_dispatch_request         | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.finalize_request              | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.send_static_file              | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.open_instance_resource        | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.make_shell_context            | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.test_client                   | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.test_cli_runner               | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.ensure_sync                   | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.async_to_sync                 | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.do_teardown_appcontext        | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | F  | remove_ctx                          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | F  | add_ctx                             | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.log_exception                 | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.make_default_options_response |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.app_context                   | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.request_context               | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.test_request_context          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/app.py        | M  | Flask.__call__                      | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/blueprints.py | C  | Blueprint                           | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/blueprints.py | M  | Blueprint.get_send_file_max_age     |    | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/blueprints.py | M  | Blueprint.open_resource             | A  | 3  |

（续下页）



| 文件   | 类型 | 符号（函数/方法）                  | 等级 | 分数 |
|--|----|----------------------------|----|----|
| D:<br>/code\_assistant/Git\_repo/pallets<br>\\_flask/src/flask/blueprints.py | M  | Blueprint.send_static_file | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\\_flask/src/flask/blueprints.py | M  | Blueprint.__init__         | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | routes_command             | C  | 18 |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | find_app_by_string         | C  | 14 |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | load_dotenv                | C  | 13 |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | find_best_app              | C  | 12 |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | _validate_key              | B  | 10 |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | M  | ScriptInfo.load_app        | B  | 8  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | prepare_import             | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | shell_command              | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | C  | ScriptInfo                 | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | M  | CertParamType.convert      | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | locate_app                 | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | _env_file_callback         | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | show_server_banner         | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | run_command                | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | C  | FlaskGroup                 | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | M  | FlaskGroup.__init__        | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | M  | FlaskGroup.get_command     | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | M  | FlaskGroup.parse_args      | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | C  | CertParamType              | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | _set_debug                 | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | _called_with_wrong_args    | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_flask/src/flask/cli.py           | F  | get_version                | A  | 3  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                        | 等级 | 分数 |
|---|----|----------------------------------|----|----|
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | FlaskGroup._load_plugin_commands | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | FlaskGroup.list_commands         | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | FlaskGroup.make_context          | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | C  | SeparatedPathType                | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | F  | _set_app                         | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | C  | AppGroup                         | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | SeparatedPathType.convert        | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | F  | locate_app                       | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | F  | locate_app                       | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | F  | with_appcontext                  | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | F  | _path_is_ancestor                | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | F  | main                             | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | C  | NoAppException                   | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | ScriptInfo.__init__              | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | AppGroup.command                 | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | AppGroup.group                   | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/cli.py    | M  | CertParamType.__init__           | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.from_prefixed_env         | B  | 7  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | C  | Config                           | A  | 5  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.from_file                 | A  | 5  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.get_namespace             | A  | 5  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.from_pyfile               | A  | 4  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.from_object               | A  | 4  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.from_mapping              | A  | 4  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | ConfigAttribute.__get__          | A  | 3  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                    | 等级 | 分数 |
|---|----|------------------------------|----|----|
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.from_envvar           | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | C  | ConfigAttribute              | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.__init__              | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | ConfigAttribute.__init__     | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | ConfigAttribute.__get__      | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | ConfigAttribute.__get__      | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | ConfigAttribute.__set__      | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/config.py | M  | Config.__repr__              | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | AppContext.pop               | B  | 7  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | AppContext.session           | A  | 4  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | AppContext.push              | A  | 4  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | F  | after_this_request           | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | C  | AppContext                   | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | AppContext.__init__          | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | AppContext.match_request     | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | F  | copy_current_request_context | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | F  | has_request_context          | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | F  | __getattr__                  | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | C  | _AppCtxGlobals               | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | _AppCtxGlobals.__getattr__   | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | _AppCtxGlobals.__delattr__   | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | _AppCtxGlobals.pop           | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | _AppCtxGlobals.__repr__      | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | AppContext.request           | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/ctx.py    | M  | AppContext.__repr__          | A  | 2  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                         | 等级 | 分数 |
|---|----|-----------------------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | F  | has_app_context                   | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | _AppCtxGlobals.__setattr__        | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | _AppCtxGlobals.get                | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | _AppCtxGlobals.setdefault         | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | _AppCtxGlobals.__contains__       | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | _AppCtxGlobals.__iter__           | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | AppContext.from_envron            | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | AppContext.has_request            | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | AppContext.copy                   | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | AppContext.__enter__              | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/ctx.py          | M  | AppContext.__exit__               | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | F  | explain_template_loading_attempts |    | 13 |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | F  | _dump_loader_info                 | B  | 8  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | C  | FormDataRoutingRedirect           | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | C  | DebugFilesKeyError                | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | M  | DebugFilesKeyError.__init__       | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | M  | FormDataRoutingRedirect.__init__  | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | F  | attach_enctype_error_multidict    | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | C  | UnexpectedUnicodeError            | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/debughelpers.py | M  | DebugFilesKeyError.__str__        | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/globals.py      | F  | __setattr__                       | A  | 2  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                      | 等级 | 分数 |
|--|----|--------------------------------|----|----|
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/globals.py | C  | ProxyMixin                     | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/globals.py | M  | ProxyMixin._get_current_object | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/globals.py | C  | FlaskProxy                     | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/globals.py | C  | AppContextProxy                | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/globals.py | C  | _AppCtxGlobalsProxy            | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/globals.py | C  | RequestProxy                   | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/globals.py | C  | SessionMixinProxy              | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | get_root_path                  | B  | 10 |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | get_flashed_messages           | B  | 6  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | make_response                  | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | get_debug_flag                 | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | get_load_dotenv                | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | stream_with_context            | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | redirect                       | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | abort                          | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | _prepare_send_file_kwargs      | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | _split_blueprint_path          | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | stream_with_context            | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | stream_with_context            | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | url_for                        | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | get_template_attribute         | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | flash                          | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | send_file                      | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/helpers.py | F  | send_from_directory            | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/logging.py | F  | has_level_handler              | A  | 5  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）   | 等级 | 分数 |
|---|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/logging.py  | F  | create_logger                                       | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/logging.py  | F  | wsgi_errors_stream                                  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | C  | SecureCookieSessionInterface                        | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SecureCookieSessionInterface.save_session           | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SecureCookieSessionInterface.open_session           | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionInterface.should_set_cookie                  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SecureCookieSessionInterface.get_signing_serializer | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | C  | SessionMixin  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | C  | SecureCookieSession                                 | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | C  | NullSession   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | C  | SessionInterface                                    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionInterface.get_cookie_path                    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionInterface.get_expiration_time                | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | F  | _lazy_sha1  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionMixin.permanent                              | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionMixin.permanent                              | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SecureCookieSession.__init__                        | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SecureCookieSession.__getitem__                     | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SecureCookieSession.get                             | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SecureCookieSession.setdefault                      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | NullSession._fail                                   | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionInterface.make_null_session                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionInterface.is_null_session                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionInterface.get_cookie_name                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sessions.py | M  | SessionInterface.get_cookie_domain                  | A  | 1  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                                    | 等级 | 分数 |
|---|----|--|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sessions.py   | M  | SessionInterface.get_cookie_httponly         |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sessions.py   | M  | SessionInterface.get_cookie_secure           |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sessions.py   | M  | SessionInterface.get_cookie_samesite         |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sessions.py   | M  | SessionInterface.get_cookie_partitioned      |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sessions.py   | M  | SessionInterface.open_sessionA               |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sessions.py   | M  | SessionInterface.save_sessionA               |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | M  | DispatchingJinjaLoader._get_source_explained |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | M  | DispatchingJinjaLoader.list_templates        |    | 5  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | C  | DispatchingJinjaLoader                       | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | M  | DispatchingJinjaLoader._iter_loaders         |    | 4  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | C  | Environment                                  | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | M  | DispatchingJinjaLoader._get_source_fast      |    | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | F  | _default_template_ctx_processor              |    | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | M  | Environment.__init__                         | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | M  | DispatchingJinjaLoader.get_source            |    | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | F  | _render                                      | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | F  | render_template                              | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | F  | render_template_string                       | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/templating.py | F  | _stream                                      | A  | 1  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                              | 等级 | 分数 |
|---|----|--|----|----|
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/templating.py | F  | stream_template                        | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/templating.py | F  | stream_template_string                 | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/templating.py | M  | DispatchingJinjaLoader.__init__        | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | EnvironBuilder.__init__                | B  | 9  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskClient.open                       | B  | 7  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | C  | EnvironBuilder                         | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskClient.session_transaction        | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | C  | FlaskClient                            | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | C  | FlaskCliRunner                         | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskCliRunner.invoke                  | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | F  | _get_werkzeug_version                  | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskClient._copy_environ              | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskClient.__enter__                  | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | EnvironBuilder.json_dumps              | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskClient.__init__                   | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskClient._request_from_builder_args | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskClient.__exit__                   | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/testing.py      | M  | FlaskCliRunner.__init__                | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/views.py        | C  | MethodView                             | B  | 7  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/views.py        | M  | MethodView.__init_subclass__           | B  | 7  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/views.py        | C  | View                                   | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/views.py        | M  | View.as_view                           | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/views.py        | M  | MethodView.dispatch_request            | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets<br>ts\_\_flask/src/flask/views.py        | M  | View.dispatch_request                  | A  | 1  |

（续下页）



| 文件   | 类型 | 符号（函数/方法）                          | 等级 | 分数 |
|--|----|------------------------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request._load_form_data            | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.on_json_loading_failed     | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | C  | Request                            | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.max_content_length         | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.max_form_memory_size       | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.max_form_parts             | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.blueprint                  | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | C  | Response                           | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.endpoint                   | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.blueprints                 | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Response.max_cookie_size           | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.max_content_length         | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.max_form_memory_size       | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/wrappers.py      | M  | Request.max_form_parts             | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | JSONProvider._prepare_response_obj | B  | 7  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | F  | _default                           | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | DefaultJSONProvider.response       | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | C  | JSONProvider                       | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | C  | DefaultJSONProvider                | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | JSONProvider.__init__              | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | JSONProvider.dumps                 | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                        | 等级 | 分数 |
|--|----|----------------------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | JSONProvider.dump                | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | JSONProvider.loads               | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | JSONProvider.load                | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | JSONProvider.response            | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | DefaultJSONProvider.dumps        | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/provider.py | M  | DefaultJSONProvider.loads        | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | TaggedJSONSerializer.register    | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | TaggedJSONSerializer._untag_scan | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | TaggedJSONSerializer             | A  | 4  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | TagDict                          | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | TagDict.check                    | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | PassDict                         | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | PassList                         | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | TaggedJSONSerializer.tag         | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | TaggedJSONSerializer.untag       | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | JSONTag                          | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | PassDict.to_json                 | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | TagTuple                         | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | TagTuple.to_json                 | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | M  | PassList.to_json                 | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | TagBytes                         | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/json/tag.py      | C  | TagMarkup                        | A  | 2  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                     | 等级 | 分数 |
|---|----|-------------------------------|----|----|
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | C  | TagUUID                       | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | C  | TagDateTime                   | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TaggedJSONSerializer.__init__ | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | JSONTag.__init__              | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | JSONTag.check                 | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | JSONTag.to_json               | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | JSONTag.to_python             | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | JSONTag.tag                   | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagDict.to_json               | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagDict.to_python             | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | PassDict.check                | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagTuple.check                | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagTuple.to_python            | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | PassList.check                | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagBytes.check                | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagBytes.to_json              | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagBytes.to_python            | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagMarkup.check               | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagMarkup.to_json             | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagMarkup.to_python           | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagUUID.check                 | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagUUID.to_json               | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagUUID.to_python             | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagDateTime.check             | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/src/flask/json/tag.py | M  | TagDateTime.to_json           | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                  | 等级 | 分数 |
|--|----|----------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/tag.py    | M  | TagDateTime.to_python      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/tag.py    | M  | TaggedJSONSerializer.dumps | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/tag.py    | M  | TaggedJSONSerializer.loads | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/_init_.py | F  | dumps                      | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/_init_.py | F  | dump                       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/_init_.py | F  | loads                      | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/_init_.py | F  | load                       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/json/_init_.py | F  | jsonify                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App.add_url_rule           | C  | 13 |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App._find_error_handler    | B  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App.trap_http_exception    | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App.handle_url_build_error | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App.inject_url_defaults    | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | F  | _make_timedelta            | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | C  | App                        | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App.__init__               | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App.name                   | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/app.py  | M  | App._check_setup_finished  | A  | 2  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                      | 等级 | 分数 |
|---|----|--------------------------------|----|----|
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.make_config                | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.auto_find_instance_path    | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.select_jinja_autoescape    | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.debug                      | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.template_filter            | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.add_template_filter        | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.template_test              | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.add_template_test          | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.template_global            | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.add_template_global        | A  | 2  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.logger                     | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.jinja_env                  | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.create_jinja_environment   | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.make_aborter               | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.create_global_jinja_loader | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.debug                      | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py | M  | App.register_blueprint         | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                        | 等级 | 分数 |
|--|----|----------------------------------|----|----|
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.iter_blueprints              | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.template_filter              | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.template_filter              | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.template_test                | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.template_test                | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.template_global              | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.template_global              | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.teardown_appcontext          | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.shell_context_processor      | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.should_ignore_error          | A  | 1  |
| D:<br>/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/app.py    | M  | App.redirect                     | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.register               | D  | 23 |
| D:/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint._merge_blueprint_funcs |    | 6  |
| D:/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.add_url_rule           | B  | 6  |
| D:/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/blueprints.py | C  | BlueprintSetupState              | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/blueprints.py | M  | BlueprintSetupState.add_url_rule |    | 5  |
| D:/code\_assistant/Git\_repo/pallets<br>\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.__init__               | A  | 4  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                         | 等级 | 分数 |
|--|----|-----------------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | BlueprintSetupState.__init__      | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | C  | Blueprint                         | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint._check_setup_finished   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.register_blueprint      | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_filter     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_test       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_global     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.record                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.record_once             | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.make_setup_state        | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_filter     | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_filter     | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.add_app_template_filter | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_test       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_test       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.add_app_template_test   | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_global     | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                            | 等级 | 分数 |
|--|----|--------------------------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_template_global        | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.add_app_template_global    |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.before_app_request         | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.after_app_request          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.teardown_app_request       | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_context_processor      |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_errorhandler           | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_url_value_preprocessor |    | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/blueprints.py | M  | Blueprint.app_url_defaults           | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | F  | _find_package_path                   | B  | 10 |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | M  | Scaffold._get_exc_class_and_code     |    | 6  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | F  | find_package                         | A  | 5  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | M  | Scaffold.static_url_path             | A  | 3  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | F  | _endpoint_from_view_func             | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | C  | Scaffold                             | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | M  | Scaffold.__init__                    | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py   | M  | Scaffold.static_folder               | A  | 2  |

（续下页）



| 文件   | 类型 | 符号（函数/方法）                      | 等级 | 分数 |
|--|----|--------------------------------|----|----|
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.static_folder         | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.static_url_path       | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.jinja_loader          | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold._method_route         | A  | 2  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | F  | setupmethod                    | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.__repr__              | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold._check_setup_finished | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.has_static_folder     | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.get                   | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.post                  | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.put                   | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.delete                | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.patch                 | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.route                 | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.add_url_rule          | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.endpoint              | A  | 1  |
| D:/code\_assistant/Git\_repo/pallets\_\_flask/src/flask/sansio/scaffold.py | M  | Scaffold.before_request        | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                                      | 等级 | 分数 |
|--|----|--|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/scaffold.py | M  | Scaffold.after_request                         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/scaffold.py | M  | Scaffold.teardown_request                      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/scaffold.py | M  | Scaffold.context_processor                     | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/scaffold.py | M  | Scaffold.url_value_preprocessor                | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/scaffold.py | M  | Scaffold.url_defaults                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/scaffold.py | M  | Scaffold.errorhandler                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/src/flask/sansio/scaffold.py | M  | Scaffold.register_error_handler                | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | _standard_os_environ                           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | leak_detector                                  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | test_apps                                      | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | _reset_os_environ                              | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | app  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | app_ctx  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | req_ctx  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | client   | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | modules_tmp_path                               | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | modules_tmp_path_prefix                        | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | site_packages                                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/conftest.py            | F  | purge_module                                   | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py         | F  | test_app_ctx_globals_methods                   | B  | 10 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py         | F  | test_app_tearing_down_with_unhandled_exception | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py         | F  | test_context_refcounts                         | A  | 4  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）   | 等级 | 分数 |
|--|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_request_context_means_app_context                    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_app_context_provides_current_app                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_app_tearing_down_with_previous_exception             | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_app_tearing_down_with_handled_exception_by_exception | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_clean_pop  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_basic_url_generation                                 | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_app_tearing_down                                     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_app_tearing_down_with_handled_exception_by_appctx    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_custom_app_ctx_globals_class                         | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_url_generation_requires_server_name                  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_appctx.py | F  | test_url_generation_without_context_fails                 | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | F  | test_async_before_after_request                           | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | F  | test_async_route  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | F  | test_async_error_handler                                  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | C  | AsyncView   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | C  | AsyncMethodView   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | F  | _async_app  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | C  | AppError  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | C  | BlueprintError  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | M  | AsyncView.dispatch_request                                | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | M  | AsyncMethodView.get                                       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_async.py  | M  | AsyncMethodView.post                                      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py  | F  | test_response_types                                       | D  | 27 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py  | F  | test_make_response  | C  | 14 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py  | F  | test_session_using_session_settings                       | A  | 13 |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                                 | 等级 | 分数 |
|---|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_provide_automatic_options            | C  | 12 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_url_mapping                          | C  | 12 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_special_types                | C  | 11 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_request_dispatching                  | B  | 10 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_make_response_with_response_instance | C  | 10 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_server_name_subdomain                | B  | 9  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_expiration                   | B  | 8  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_trap_bad_request_key_error           | C  | 8  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_error_handling                       | B  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_route_decorator_custom_endpoint      | C  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_server_name_matching                 | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_max_cookie_size                      | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_response_type_errors                 | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_get_method_on_g                      | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_using_samesite_attribute     | C  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_secret_key_fallbacks         | C  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_flashes                              | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_request_processing                   | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_teardown_request_handler             | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_teardown_request_handler_debug_mode  | C  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_teardown_request_handler_error       | C  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_http_error_subclass_handling         | C  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_error_handler_after_processor_error  | C  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_build_error_handler                  | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_files                         | A  | 4  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                               | 等级 | 分数 |
|---|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_url_processors                     | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_g_iteration_protocol               | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_app_freed_on_zero_refcount         | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_options_work                       | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_provide_automatic_options_attr     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_werkzeug_routing                   | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_endpoint_decorator                 | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session                            | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_stored_last                | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_refresh_vary               | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_request_preprocessing_early_return | B  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_after_request_processing           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_before_after_request_order         | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_error_handling_processing          | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_before_request_and_routing_errors  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_errorhandler_precedence            | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_enctype_debug_helper               | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_jsonify_no_prettyprint             | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_url_generation                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_url_path                    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_url_path_with_ending_slash  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_route_with_host_matching    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_request_locals                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_exception_propagation              | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_inject_blueprint_url_defaults      | A  | 3  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                            | 等级 | 分数 |
|---|----|--------------------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_no_setup_after_first_request    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_routing_redirect_debugging      | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_subdomain_basic_support         | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_subdomain_matching_other_name   | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_multi_route_rules               | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_multi_route_class_views         | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_options_on_multiple_rules       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_method_route                    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_path                    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_session_using_application_root  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_missing_session                 | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_user_error_handling             | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_jsonify_mimetype                | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_json_dump_dataclass             | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_jsonify_args_and_kwargs_check   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_url_empty_path           | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_url_empty_path_default   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_folder_with_pathlib_path | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_static_folder_with_ending_slash | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_nonascii_pathinfo               | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_subdomain_matching              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_subdomain_matching_with_ports   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_run_defaults                    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_run_server_port                 | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py | F  | test_method_route_no_methods         | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）   | 等级 | 分数 |
|--|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_disallow_string_for_allowed_methods                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_session_cookie_setting                               | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_session_vary_cookie                                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_extended_flashing                                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_baseexception_error_handling                         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_trapping_of_all_http_exceptions                      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_build_error_handler_reraise                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_url_for_passes_special_values_to_build_error_handler | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_werkzeug_passthrough_errors                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_basic.py      | F  | test_run_from_config                                      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_global                                      | C  | 18 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_filter                                      | C  | 13 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_test  | C  | 13 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_templates_and_static                                 | C  | 11 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_nested_blueprint                                     | B  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_blueprint_renaming                                   | B  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_route_decorator_custom_endpoint                      | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_app_request_processing                               | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_blueprint_url_defaults                               | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_context_processing                                   | A  | 5  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                                   | 等级 | 分数 |
|--|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_blueprint_specific_error_handling      | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_filter                    | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_filter_with_name              | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_filter_with_name          | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_test                      | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_test_with_name                | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_test_with_name            | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_request_processing                     | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_blueprint_specific_user_error_handling | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_blueprint_app_error_handling           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_blueprint_url_processors               | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_default_static_max_age                 | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_empty_url_defaults                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_endpoint_decorator                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_app_url_processors                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_nested_callback_order                  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_child_and_parent_subdomain             | A  | 3  |

（续下页）



| 文件   | 类型 | 符号（函数/方法）                                       | 等级 | 分数 |
|--|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_blueprint_prefix_slash                     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_templates_list                             | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_dotted_names_from_app                      | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_filter_with_template              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_filter_after_route_with_template  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_filter_with_template          | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_filter_with_name_and_template     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_filter_with_name_and_template | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_test_with_template                | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_test_after_route_with_template    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_test_with_template            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_template_test_with_name_and_template       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_add_template_test_with_name_and_template   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_nesting_url_prefixes                       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_nesting_subdomains                         | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_dotted_name_not_allowed                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_empty_name_not_allowed                     | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                                      | 等级 | 分数 |
|--|----|--|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_route_decorator_custom_endpoint_with_dots |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_unique_blueprint_names                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_blueprints.py | F  | test_self_registration                         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_find_best_app                             | C  | 12 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_scriptinfo                                | C  | 11 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_load_dotenv                               | B  | 10 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_appgroup_app_context                      | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_no_command_echo_loading_error             |    | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_help_echo_loading_error                   | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_help_echo_exception                       | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_cli_blueprints                            | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_get_version                               | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_dotenv_path                               | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_prepare_import                            | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_with_appcontext                           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_flaskgroup_app_context                    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_flaskgroup_debug                          | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | F  | test_run_cert_path                             | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | C  | TestRoutes                                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | M  | TestRoutes.expect_order                        | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | M  | TestRoutes.test_sort                           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | M  | TestRoutes.test_all_methods                    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | M  | TestRoutes.test_no_routes                      | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_cli.py        | M  | TestRoutes.test_subdomain                      | A  | 3  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                       | 等级 | 分数 |
|---|----|---------------------------------|----|----|
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | M  | TestRoutes.test_host            | A  | 3  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_cli_name                   | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_locate_app                 | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_locate_app_suppress_raise  | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_app_cli_has_app_context    | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_flaskgroup_nested          | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | dotenv_not_available            | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_dotenv_optional            | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_disable_dotenv_from_env    | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_run_cert_adhoc             | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_run_cert_import            | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_cli_empty                  | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_run_exclude_patterns       | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | M  | TestRoutes.test_simple          | A  | 2  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | runner                          | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_locate_app_raises          | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | F  | test_run_cert_no_ssl            | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | M  | TestRoutes.app                  | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_cli.py    | M  | TestRoutes.invoke               | A  | 1  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_config.py | F  | test_get_namespace              | C  | 13 |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_config.py | F  | test_from_prefixed_env          | B  | 8  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_config.py | F  | test_from_prefixed_env_nested   | A  | 5  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_config.py | F  | common_object_test              | A  | 4  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_config.py | F  | test_config_from_envvar         | A  | 4  |
| D:/code\_assistant/Git\_repo/palle<br>ts\_\_flask/tests/test\_config.py | F  | test_config_from_envvar_missing | A  | 4  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）  | 等级 | 分数 |
|--|----|--|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_missing                              | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_missing_file                         | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_from_prefixed_env_custom_prefix             | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_custom_config_class                         | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_session_lifetime                            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_from_pyfile_weird_encoding                  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_from_pyfile                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_from_object                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_from_file_json                       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_from_file_toml                       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_from_mapping                         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_config.py     | F  | test_config_from_class                           | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_converters.py | F  | test_custom_converters                           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_converters.py | F  | test_context_available                           | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | M  | TestSendfile.test_static_file                    | B  | 8  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | C  | TestSendfile                                     | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | M  | TestHelpers.test_make_response                   | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | C  | TestHelpers                                      | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | M  | TestSendfile.test_send_file                      | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | M  | TestUrlFor.test_url_for_with_alternating_schemes | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | M  | TestUrlFor.test_url_with_method                  | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | F  | test_redirect_no_app                             | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | C  | TestUrlFor                                       | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py    | C  | TestNoImports                                    | A  | 3  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）  | 等级 | 分数 |
|---|----|--|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | C  | TestStreaming  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestStreaming.test_streaming_with_context_and_custom   |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestStreaming.test_async_view                          | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | F  | test_app_aborter_class                                 | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | F  | test_open_resource                                     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | F  | test_open_resource_with_encoding                       |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | C  | FakePath   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | C  | PyBytesIO  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestSendfile.test_send_from_directory                  |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestUrlFor.test_url_for_with_anchor                    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestUrlFor.test_url_for_with_scheme                    |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestUrlFor.test_url_for_with_scheme_not_external       |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestUrlFor.test_url_for_with_self                      |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestNoImports.test_name_with_import_error              |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestStreaming.test_streaming_with_context              |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestStreaming.test_streaming_with_context_as_decorator |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestStreaming.test_stream_keeps_session                |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | TestHelpers.test_get_debug_flag                        |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | F  | test_redirect_with_app                                 | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | F  | test_abort_no_app                                      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | F  | test_abort_with_app                                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | F  | test_open_resource_exceptions                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | FakePath.__init__                                      | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | FakePath.__fspath__                                    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py | M  | PyBytesIO.__init__                                     | A  | 1  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                        | 等级 | 分数 |
|---|----|----------------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_helpers.py         | M  | PyBytesIO.__getattr__            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_instance_config.py | F  | test_explicit_instance_paths     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_instance_config.py | F  | test_uninstalled_module_paths    | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_instance_config.py | F  | test_uninstalled_package_paths   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_instance_config.py | F  | test_uninstalled_namespace_paths | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_instance_config.py | F  | test_installed_module_paths      | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_instance_config.py | F  | test_installed_package_paths     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_instance_config.py | F  | test_prefix_package_paths        | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_json_key_sorting            | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_jsonify_dicts               | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_jsonify_arrays              | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_bad_request_debug_message   | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_jsonify_basic_types         | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_jsonify_uuid_types          | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_json_bad_requests           | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_json_custom_mimetypes       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_json_as_unicode             | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_json_dump_to_file           | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_jsonify_datetime            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_jsonify_aware_datetimes     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_json_decimal                | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_json.py            | F  | test_json_attr                   | A  | 2  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                | 等级 | 分数 |
|---|----|--------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | F  | test_tojson_filter       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | F  | test_json_customization  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | F  | _has_encoding            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | F  | test_html_method         | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | C  | FixedOffset              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | M  | FixedOffset.__init__     | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | M  | FixedOffset.utcoffset    | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | M  | FixedOffset.tzname       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | M  | FixedOffset.dst          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json.py       | F  | test_duplicate_tag       | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json\\_tag.py | F  | test_tag_order           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json\\_tag.py | F  | test_dump_load_unchanged | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json\\_tag.py | F  | test_custom_tag          | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_json\\_tag.py | F  | test_tag_interface       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_logging.py    | F  | test_has_level_handler   | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_logging.py    | F  | test_log_view_exception  | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_logging.py    | F  | test_logger              | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_logging.py    | F  | test_wsgi_errors_stream  | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_logging.py    | F  | test_logger_debug        | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_logging.py    | F  | test_existing_handler    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_logging.py    | F  | reset_logging            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/test\\_regression.py | F  | test_aborting            | A  | 5  |

（续下页）

| 文件  | 类型 | 符号 (函数/方法)   | 等级 | 分数 |
|---|----|--|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_context_test  | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_session_dynamic_cookie_name                         |    | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_teardown_with_previous_exception                    |    | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_teardown_with_handled_exception                     |    | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_context_binding                                     | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_session_error_pops_context                          |    | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | C  | TestGreenletContextCopying                               | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_teardown_on_pop                                     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_proper_test_request_context                         |    | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | M  | TestGreenletContextCopying.test_greenlet_context_copying |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | M  | TestGreenletContextCopying.test_greenlet_context_copying |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_manual_context_binding                              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_bad_environ_raises_bad_request                      |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_environ_for_valid_idna_completes                    |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_reqctx.py            | F  | test_normal_environ_completes                            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_request.py           | F  | test_limit_config  | C  | 13 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_request.py           | F  | test_trusted_hosts_config                                | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_request.py           | F  | test_max_content_length                                  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_session_interface.py | F  | test_open_session_with_endpoint                          |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_signals.py           | F  | test_before_render_template                              | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_signals.py           | F  | test_template_rendered                                   | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_signals.py           | F  | test_request_exception_signal                            | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_signals.py           | F  | test_flash_signal  | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_signals.py           | F  | test_appcontext_tearing_down_signal                      |    | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_signals.py           | F  | test_request_signals                                     | A  | 3  |

(续下页)



| 文件  | 类型 | 符号（函数/方法）                               | 等级 | 分数 |
|---|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_signals.py     | F  | test_appcontext_signals                 | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_subclassing.py | F  | test_suppressed_exception_logging       | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_add_template_global                | C  | 17 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_template_filter                    | C  | 13 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_template_test                      | C  | 13 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_templates_auto_reload              | C  | 12 |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_add_template_filter                | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_template_filter_with_name          | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_add_template_filter_with_name      | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_add_template_test                  | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_template_test_with_name            | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_add_template_test_with_name        | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_escaping_without_template_filename | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_templates_auto_reload_debug_run    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_template_loader_debugging          | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_context_processing                 | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_templating.py  | F  | test_original_win                       | A  | 2  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                                       | 等级 | 分数 |
|---|----|---|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_simple_stream                              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_request_less_rendering                     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_standard_context                           | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_escaping                                   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_no_escaping                                | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_macros                                     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_template_filter_with_template              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_add_template_filter_with_template          | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_template_filter_with_name_and_template     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_add_template_filter_with_name_and_template | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_template_test_with_template                | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_add_template_test_with_template            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_template_test_with_name_and_template       | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_add_template_test_with_name_and_template   | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_custom_template_loader                     | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_iterable_loader                            | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_templating.py | F  | test_custom_jinja_env                           | A  | 2  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                                  | 等级 | 分数 |
|---|----|--|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_test_client_context_bind              | B  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_session_transactions                  | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_json_request_and_response             | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_path_is_url                           | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_blueprint_with_subdomain              | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_full_url_request                      | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_environ_defaults_from_config          | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_environ_defaults                      | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_environ_base_default                  | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_environ_base_modified                 | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_client_open_environ                   | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_specify_url_scheme                    | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_redirect_session                      | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_session_transactions_keep_context     | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_reuse_client                          | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_client_json_no_app_context            | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_subdomain                             | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_nosubdomain                           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_cli_runner_class                      | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_cli_invoke                            | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_environbuilder_json_dump              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_session_transactions_no_null_sessions | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_cli_custom_obj                        | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_client_pop_all_preserved              | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_testing.py | F  | test_session_transaction_needs_cookies     | A  | 1  |

（续下页）

| 文件   | 类型 | 符号 (函数/方法)                                     | 等级 | 分数 |
|--|----|--|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | F  | test_error_handler_no_match                    | B  | 7  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | F  | test_default_error_handler                     | B  | 6  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | M  | TestGenericHandlers.test_handler_class_or_code |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | M  | TestGenericHandlers.test_handler_generic       |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | F  | test_error_handler_subclass                    | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | F  | test_error_handler_http_subclass               |    | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | C  | TestGenericHandlers                            | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | M  | TestGenericHandlers.test_handler_generic_http  |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | F  | test_error_handler_blueprint                   | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | M  | TestGenericHandlers.report_error               |    | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_user/_error_handler.py | M  | TestGenericHandlers.app                        | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | common_test                                    | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_implicit_head                             | A  | 5  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_view_provide_automatic_options_attr       |    |    |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_explicit_head                             | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_methods_var_inheritance                   | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_multiple_inheritance                      | A  | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_remove_method_from_parent                 |    | 4  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_view_decorators                           | A  | 3  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test/_views.py               | F  | test_init_once                                 | A  | 3  |

(续下页)

| 文件   | 类型 | 符号（函数/方法）              | 等级 | 分数 |
|--|----|------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_views.py                                  | F  | test_view_inheritance  | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_views.py                                  | F  | test_basic_view        | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_views.py                                  | F  | test_method_based_view | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_views.py                                  | F  | test_view_patching     | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_views.py                                  | F  | test_endpoint_override | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/blueprintapp/apps/admin/_init_.py    | F  | index                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/blueprintapp/apps/admin/_init_.py    | F  | index2                 | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/blueprintapp/apps/frontend/_init_.py | F  | index                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/blueprintapp/apps/frontend/_init_.py | F  | missing_template       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/cliapp/factory.py                    | F  | create_app             | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/cliapp/factory.py                    | F  | create_app2            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/cliapp/factory.py                    | F  | no_app                 | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/test_apps/helloworld/hello.py                  | F  | hello                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type_check/typing_app_decorators.py            | F  | after_sync             | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type_check/typing_app_decorators.py            | F  | after_async            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type_check/typing_app_decorators.py            | F  | before_sync            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type_check/typing_app_decorators.py            | F  | before_async           | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type_check/typing_app_decorators.py            | F  | teardown_sync          | A  | 1  |

（续下页）

| 文件   | 类型 | 符号（函数/方法）                  | 等级 | 分数 |
|--|----|----------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_app/_decorators.py | F  | teardown_async             | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_error/_handler.py  | F  | handle_400                 | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_error/_handler.py  | F  | handle_custom              | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_error/_handler.py  | F  | handle_accept_base         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_error/_handler.py  | F  | handle_multiple            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_generator_expression | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_iterator             | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | C  | RenderTemplateView         | A  | 2  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_str                  | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_bytes                | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_json                 | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_json_dict            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_json_list            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | typed_dict                 | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | hello_generator            | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | tuple_status               | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets/_flask/tests/type/_check/typing/_route.py           | F  | tuple_status_enum          | A  | 1  |

（续下页）

| 文件  | 类型 | 符号（函数/方法）                           | 等级 | 分数 |
|---|----|-------------------------------------|----|----|
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/type/_check/typing/_route.py | F  | tuple_headers                       | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/type/_check/typing/_route.py | F  | return_template                     | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/type/_check/typing/_route.py | F  | return_template_stream              | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/type/_check/typing/_route.py | F  | async_route                         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/type/_check/typing/_route.py | C  | StatusJSON                          | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/type/_check/typing/_route.py | M  | RenderTemplateView.__init__         | A  | 1  |
| D:/code/_assistant/Git/_repo/pallets\\_flask/tests/type/_check/typing/_route.py | M  | RenderTemplateView.dispatch_request | A  | 1  |

## 2 测试生成（TestGen）

### 2.1 指标

- 写入测试文件数：18
- 覆盖函数数：80
- 输出目录：D:/code/\_assistant/Git/\_repo/pallets\\\_flask/reports/pallets\\\_flask/generated/\_tests

### 2.2 覆盖率报告

| Name                            | Stmts | Miss | Cover | Missing |
|---------------------------------|-------|------|-------|---------|
| tests/conftest.py               | 72    | 72   | 0%    | 1-129   |
| tests/test/_appctx.py           | 142   | 142  | 0%    | 1-210   |
| tests/test/_async.py            | 100   | 100  | 0%    | 1-145   |
| tests/test/_basic.py            | 1317  | 1317 | 0%    | 1-1944  |
| tests/test/_blueprints.py       | 750   | 750  | 0%    | 1-1127  |
| tests/test/_cli.py              | 429   | 429  | 0%    | 3-702   |
| tests/test/_config.py           | 166   | 166  | 0%    | 1-250   |
| tests/test/_converters.py       | 29    | 29   | 0%    | 1-42    |
| tests/test/_helpers.py          | 237   | 237  | 0%    | 1-383   |
| tests/test/_instance/_config.py | 56    | 56   | 0%    | 1-109   |
| tests/test/_json.py             | 173   | 173  | 0%    | 1-346   |
| tests/test/_json/_tag.py        | 50    | 50   | 0%    | 1-86    |

（续下页）

| Name                                | Stmts | Miss | Cover | Missing |
|-------------------------------------|-------|------|-------|---------|
| tests/test\_logging.py              | 69    | 69   | 0%    | 1-98    |
| tests/test\_regression.py           | 21    | 21   | 0%    | 1-30    |
| tests/test\_reqctx.py               | 216   | 216  | 0%    | 1-326   |
| tests/test\_request.py              | 50    | 50   | 0%    | 1-70    |
| tests/test\_session\_interface.py   | 17    | 17   | 0%    | 1-28    |
| tests/test\_signals.py              | 126   | 126  | 0%    | 1-181   |
| tests/test\_subclassing.py          | 15    | 15   | 0%    | 1-21    |
| tests/test\_templating.py           | 339   | 339  | 0%    | 1-532   |
| tests/test\_testing.py              | 266   | 266  | 0%    | 1-385   |
| tests/test\_user\_error\_handler.py | 203   | 203  | 0%    | 1-295   |
| tests/test\_views.py                | 177   | 177  | 0%    | 1-260   |
| <b>TOTAL</b>                        | 5020  | 5020 | 0%    |         |