

CodeAssistant 报告

(由自动审查与测试生成系统输出)

Contents

1	代码审查 (Review)	1
1.1	概览	1
1.2	严重性分布	1
1.3	工具分布	1
1.4	Top 20 问题	2
1.5	复杂度摘要	3
2	测试生成 (TestGen)	43
2.1	指标	43
2.2	覆盖率报告	43

1 代码审查 (Review)

1.1 概览

- 问题总数: 25
- 高/中/低: 7 / 3 / 15
- 工具数: 4
- DS 规则命中总数: 0

1.2 严重性分布

- low: 15
- high: 7
- medium: 3

1.3 工具分布

- bandit: 14
- rule-plugin: 7
- pip-audit: 3
- ast-rule: 1

1.4 Top 20 问题

1. **[high] ast-rule BANNED_CALL**
位置: `setup.py:79`
说明: 禁止使用 `exec` (项目/领域规则), 建议安全替代或白名单。
2. **[low] rule-plugin PY_LOOP_INVARIANT**
位置: `src/requests/models.py:178`
说明: 考虑在循环外计算长度, 避免每次迭代都重新计算
3. **[low] rule-plugin PY_LOOP_INVARIANT**
位置: `src/requests/models.py:180`
说明: 考虑在循环外计算长度, 避免每次迭代都重新计算
4. **[low] rule-plugin PY_LOOP_INVARIANT**
位置: `src/requests/sessions.py:190`
说明: 考虑在循环外计算长度, 避免每次迭代都重新计算
5. **[low] rule-plugin PY_GLOBAL_VARIABLE**
位置: `src/requests/status_codes.py:120`
说明: 检测到全局变量 `'__doc__'` 的使用; 考虑使用参数传递代替
6. **[low] rule-plugin PY_LOOP_INVARIANT**
位置: `src/requests/utils.py:586`
说明: 考虑在循环外计算长度, 避免每次迭代都重新计算
7. **[low] rule-plugin PY_LOOP_INVARIANT**
位置: `src/requests/utils.py:643`
说明: 考虑在循环外计算长度, 避免每次迭代都重新计算
8. **[low] rule-plugin PY_LOOP_INVARIANT**
位置: `src/requests/utils.py:645`
说明: 考虑在循环外计算长度, 避免每次迭代都重新计算
9. **[low] bandit B605**
位置: `D:/code/_assistant/Git/_repo/kennethreitz/_requests/setup.py:57`
说明: Starting a process with a shell: Seems safe, but may be changed in the future, consider rewriting without shell
10. **[medium] bandit B607**
位置: `D:/code/_assistant/Git/_repo/kennethreitz/_requests/setup.py:57`
说明: Starting a process with a partial executable path
11. **[low] bandit B605**
位置: `D:/code/_assistant/Git/_repo/kennethreitz/_requests/setup.py:58`
说明: Starting a process with a shell: Seems safe, but may be changed in the future, consider rewriting without shell
12. **[medium] bandit B607**
位置: `D:/code/_assistant/Git/_repo/kennethreitz/_requests/setup.py:58`
说明: Starting a process with a partial executable path

13. [medium] bandit B102

位置: D:/code_assistant/Git_repo/kennethreitz_requests/setup.py:79

说明: Use of exec detected.

14. [low] bandit B101

位置: D:/code_assistant/Git_repo/kennethreitz_requests/src/requests/_init_.py:60

说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.

15. [low] bandit B101

位置: D:/code_assistant/Git_repo/kennethreitz_requests/src/requests/_init_.py:70

说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.

16. [low] bandit B101

位置: D:/code_assistant/Git_repo/kennethreitz_requests/src/requests/_init_.py:72

说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.

17. [low] bandit B101

位置: D:/code_assistant/Git_repo/kennethreitz_requests/src/requests/_init_.py:79

说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.

18. [low] bandit B101

位置: D:/code_assistant/Git_repo/kennethreitz_requests/src/requests/_init_.py:84

说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.

19. [low] bandit B101

位置: D:/code_assistant/Git_repo/kennethreitz_requests/src/requests/_internal_utils.py:45

说明: Use of assert detected. The enclosed code will be removed when compiling to optimised byte code.

20. [high] bandit B324

位置: D:/code_assistant/Git_repo/kennethreitz_requests/src/requests/auth.py:148

说明: Use of weak MD5 hash for security. Consider usedforsecurity=False

1.5 复杂度摘要

- 来源: Radon Cyclomatic Complexity (CC)
- 说明: 等级通常为 A (简单) 到 F (复杂), 括号内为复杂度分数

文件	类型	符号（函数/方法）	等级	分数
D:/code_assistant/Git_repo/kenne threitz_requests/setup.py	C	PyTest	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/setup.py	M	PyTest.initialize_options	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/setup.py	M	PyTest.finalize_options	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/setup.py	M	PyTest.run_tests	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/docs/_themes/ flask_theme_support.py	C	FlaskyStyle	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.send	C	19
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.cert_verify	C	14
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	F	_urllib3_request_context	B	6
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.request_url	B	6
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	C	HTTPAdapter	A	5
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter._get_connection	A	4
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.proxy_manager_for	A	3
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.get_connection	A	3
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	C	BaseAdapter	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.__init__	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.__getstate__	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.__setstate__	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.build_response	A	2

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.close	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.proxy_headers	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	F	SOCKSProxyManager	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	M	BaseAdapter.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	M	BaseAdapter.send	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	M	BaseAdapter.close	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.init_poolmanager	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a dapters.py	M	HTTPAdapter.add_headers	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	request	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	get	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	options	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	head	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	post	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	put	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	patch	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a pi.py	F	delete	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPDigestAuth.build_digest_header		19

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	F	_basic_auth_str	A	5
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	C	HTTPDigestAuth	A	5
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPDigestAuth.handle_401	A	5
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPDigestAuth.__call__	A	3
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	C	AuthBase	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	C	HTTPBasicAuth	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	C	HTTPProxyAuth	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPDigestAuth.init_per_thread_state	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPDigestAuth.handle_redirect	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	AuthBase.__call__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPBasicAuth.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPBasicAuth.__eq__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPBasicAuth.__ne__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPBasicAuth.__call__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPProxyAuth.__call__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPDigestAuth.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/a uth.py	M	HTTPDigestAuth.__eq__	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/a uth.py	M	HTTPDigestAuth.__ne__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar._find_no_duplicates	A	9
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	remove_cookie_by_name	B	8
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	cookiejar_from_dict	B	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar._find	B	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	merge_cookies	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.get_dict	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	morsel_to_cookie	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	_copy_cookie_jar	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.multiple_domains	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.set_cookie	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	extract_cookies_to_jar	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	C	RequestsCookieJar	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.set	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.list_domains	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.list_paths	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.update	A	3

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	create_cookie	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	C	MockRequest	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.get_full_url	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.has_header	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	C	MockResponse	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.get	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.iterkeys	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.itervalues	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.iteritems	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.__contains__	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.__setstate__	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	F	get_cookie_header	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.get_type	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.get_host	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.get_origin_req_host	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.is_unverifiable	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.get_header	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.add_header	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.add_unredirected_header	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.get_new_headers	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.unverifiable	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.origin_req_host	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockRequest.host	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockResponse.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockResponse.info	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	MockResponse.getheaders	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	C	CookieConflictError	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.keys	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.values	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.items	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.__getitem__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.__setitem__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/c ookies.py	M	RequestsCookieJar.__delitem__	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/c ookies.py	M	RequestsCookieJar.__getstate_A		1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/c ookies.py	M	RequestsCookieJar.copy	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/c ookies.py	M	RequestsCookieJar.get_policy	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	RequestException	A	5
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	M	RequestException.__init__	A	4
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	JSONDecodeError	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	InvalidJSONError	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	M	JSONDecodeError.__init__	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	M	JSONDecodeError.__reduce__	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	HTTPError	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	ConnectionError	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	ProxyError	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	SSLError	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	Timeout	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	ConnectTimeout	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	ReadTimeout	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/e xceptions.py	C	URLRequired	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	TooManyRedirects	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	MissingSchema	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	InvalidSchema	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	InvalidURL	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	InvalidHeader	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	InvalidProxyURL	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	ChunkedEncodingError	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	ContentDecodingError	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	StreamConsumedError	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	RetryError	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	UnrewindableBodyError	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	RequestsWarning	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	FileModeWarning	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/e xceptions.py	C	RequestsDependencyWarning	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/h elp.py	F	_implementation	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/h elp.py	F	info	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/h elp.py	F	main	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/h ooks.py	F	dispatch_hook	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/h ooks.py	F	default_hooks	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	RequestEncodingMixin._encode_files		21
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_url	C	17
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_body	C	17
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	C	RequestEncodingMixin	C	13
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	RequestEncodingMixin._encode_params		11
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.iter_lines	B	9
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.json	B	8
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Request.__init__	B	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.iter_content	B	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	RequestHooksMixin.register_hook		6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_auth	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.content	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.raise_for_status	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	C	RequestHooksMixin	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	C	PreparedRequest	A	5

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_content_length	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	C	Request	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	C	Response	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.text	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.links	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	RequestEncodingMixin.path_url	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_headers	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_cookies	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_hooks	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__getstate__	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.close	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	RequestHooksMixin.deregister_hook	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.copy	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare_method	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest._get_idna_encoded_host	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__setstate__	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.ok	A	2

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.is_redirect	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.is_permanent_redirec	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Request.__repr__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Request.prepare	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.prepare	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	PreparedRequest.__repr__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__enter__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__exit__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__repr__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__bool__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__nonzero__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.__iter__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.next	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/m odels.py	M	Response.apparent_encoding	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/s essions.py	M	SessionRedirectMixin.resolve_redirects	A	15

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.send	C	11
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	SessionRedirectMixin.should_strip_auth	B	10
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	F	merge_setting	B	8
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	C	SessionRedirectMixin	B	8
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.merge_environment_settings	B	8
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	SessionRedirectMixin.rebuild_method	B	7
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	SessionRedirectMixin.rebuild_proxies	B	6
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.prepare_request	B	6
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	F	merge_hooks	A	5
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	SessionRedirectMixin.rebuild_auth	B	5
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.request	A	4
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.mount	A	4
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	C	Session	A	3
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.get_adapter	A	3
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	SessionRedirectMixin.get_redirect_target	B	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.close	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.__getstate__	A	2

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.__setstate__	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	F	session	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.__init__	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.__enter__	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.__exit__	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.get	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.options	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.head	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.post	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.put	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.patch	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s essions.py	M	Session.delete	A	1
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s tatus_codes.py	F	_init	B	6
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s tructures.py	C	CaseInsensitiveDict	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__init__	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__iter__	A	2
D:/code_assistant/Git_repo/kenne threitz_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.lower_items	A	2

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__eq__	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	C	LookupDict	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__setitem__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__getitem__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__delitem__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__len__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.copy	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	CaseInsensitiveDict.__repr__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	LookupDict.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	LookupDict.__repr__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	LookupDict.__getitem__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/s tructures.py	M	LookupDict.get	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/u tils.py	F	super_len	C	17
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/u tils.py	F	should_bypass_proxies	C	17
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/u tils.py	F	get_netrc_auth	C	13
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/u tils.py	F	guess_json_utf	C	11
D:/code/_assistant/Git/_repo/kenne threitz/_requests/src/requests/u tils.py	F	proxy_bypass_registry	B	9

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	extract_zipped_paths	B	8
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	unquote_unreserved	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	is_valid_cidr	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	parse_header_links	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	guess_filename	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	unquote_header_value	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	get_encoding_from_headers	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	stream_decode_response_unicode	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	select_proxy	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	resolve_proxies	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	prepend_scheme_if_needed	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	_validate_header_part	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	to_key_val_list	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	parse_dict_header	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	_parse_content_type_header	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	iter_slices	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	get_unicode_from_response	A	4

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	set_environ	A	4
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	rewind_body	A	4
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	from_key_val_list	A	3
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	parse_list_header	A	3
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	proxy_bypass	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	dict_to_sequence	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	atomic_open	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	dict_from_cookiejar	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	requote_uri	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	is_ipv4_address	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	get_environ_proxies	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	get_auth_from_url	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	urldefragauth	A	2
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	add_dict_to_cookiejar	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	get_encodings_from_content	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	address_in_network	A	1
D:/code/_assistant/Git/_repo/kenne threitz_requests/src/requests/u tils.py	F	dotted_netmask	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	default_user_agent	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	default_headers	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/u tils.py	F	check_header_validity	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/_ _internal/_utils.py	F	unicode_is_ascii	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/_ _internal/_utils.py	F	to_native_string	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/_ _/_init/_/_py	F	check_compatibility	B	10
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/src/requests/_ _/_init/_/_py	F	_check_cryptography	A	3
D: /code/_assistant/Git/_repo/kenneth reitz/_/_requests/tests/compat.py	F	u	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/conftest .py	F	prepare_url	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/conftest .py	F	httpbin	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/conftest .py	F	httpbin_secure	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/conftest .py	F	nosan_server	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ad apters.py	F	test_request_url_trims_leading_path_separators	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_he lp.py	F	test_system_ssl	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_he lp.py	F	test_idna_without_version_attribute	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_he lp.py	F	test_idna_with_version_attribute	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_he lp.py	C	VersionedPackage	A	2

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_he lp.py	M	VersionedPackage.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ho oks.py	F	test_hooks	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ho oks.py	F	test_default_hooks	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ho oks.py	F	hook	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_redirect_rfc1808_to_non_ascii_location	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_fragment_not_sent_with_request	A	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_fragment_update_on_redirect	A	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_digestauth_401_count_reset_on_redirect	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_json_decode_compatibility_for_alt_utf_encodings	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_chunked_upload	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_chunked_upload_uses_only_specified_host_header	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_chunked_upload_doesnt_skip_host_header	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_digestauth_401_only_sent_once	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_digestauth_only_on_4xx	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_use_proxy_from_environment	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	echo_response_handler	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_chunked_encoding_error	A	1

（续下页）

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_lo wlevel.py	F	test_conflicting_content_lengths	1	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_pa ckages.py	F	test_can_access_urllib3_attribute	1	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_pa ckages.py	F	test_can_access_idna_attribute	1	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_pa ckages.py	F	test_can_access_chardet_attribute	1	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_custom_redirect_mixin	8	8
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookieslib_cookiejar_on_redirect	7	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_headers_preserve_order	7	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_https_warnings	7	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_status_code_425	7	7
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	F	test_requests_are_updated_each_time	6	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_302_TOO_MANY_REDIRECTS	6	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_302_TOO_MANY_REDIRECTS_WITH_PROXY	6	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_transfer_encoding_removal_on_redirect	6	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_parameters	6	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_prepared_request_with_hook_is_pickled	6	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_transport_adapter_ordering	6	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_should_strip_auth_https_upgrade	6	6

(续下页)

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_Contains	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_307_ALLOW_REDIRECT_POST	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_307_ALLOW_REDIRECT_POST_WITH_	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_301_changes_post5_to_get	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_301_doesnt_change_head_to_get	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_302_changes_post5_to_get	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_302_doesnt_change_head_to_get	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_303_changes_post5_to_get	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_303_doesnt_change_head_to_get	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_basicauth_with_netrc	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_DIGEST_HTTP_A200_OK_GET	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_DIGESTAUTH_WRONG_HTTP_401_GET	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_POSTBIN_SEEKED_OBJECT5_WITH_NO_ITER	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_as_dict_keeps_5len	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_prepared_request_is_pickleable	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_prepared_request_with_file_is_pick	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_error	A	5

（续下页）

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_manual_redirect_with_partial_body	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_rewind_body	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_rewind_partially_read_body	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_get	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_update	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_equality	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	F	test_prepared_copy	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_302_ALLOW_REDIRECT_GET	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_and_body_removal_on_redirect	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_fragment_maintained_on_redirect	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_requests_in_history_are_not_overridden	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_history_is_always_a_list	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_BASICAUTH_TUPLE_HTTP_200_OK_GET	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_DIGEST_AUTH_RETURNS_COOKIE	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_DIGEST_STREAM	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_POSTBIN_GET_APOST_FILES	A	5
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_POSTBIN_GET_APOST_FILES_WITH_DATA	A	5

(续下页)

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_unicode_method_name_with_request_o		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_as_dict_keeps_4_items		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_duplicate_names_different_d		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_request_and_response_are_pickleabl		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_fixes_1329	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_session_get_adapter_prefix_matchin		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_with_subclass_4_types		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_json_param_post_content_type_works		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_chunked_upload_does_not_set_conten		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	C	TestCaseInsensitiveDict	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_init		4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_fixes_649		4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_preserve_key_case		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_preserve_last_key_case		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestTimeout.test_connect_timeout		4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_json_decode_compatibility		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_different_connection_pool_for		

(续下页)

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	F	test_proxy_env_vars_override_default	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	F	test_urllib3_pool_connection_closed	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	C	TestRequests	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_basic_building	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_override_content_length	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_200_OK_GET_WITH_PARAMS	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_removed_on_expire	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_persists_via_api	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_request_cookie_override_session_cookie	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_generic_cookiejar_works	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_DIGEST_AUTH_ASETS_SESSION_COOKIES	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_DIGESTAUTH_QUOTES_QOP_VALUE	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_invalid_files_input	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_invalid_ssl_certificate_files	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_urlencoded_get_query_multivalued_params	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_unicode_multipart_post_fieldnames	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_custom_content_type	A	3

(续下页)

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_session_hooks_are_used_with_no_req	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_session_hooks_are_overridden_by_re	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_prepared_from_session	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_as_dict_keys	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_as_dict_values	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_as_dict_items	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_decode_unicode	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_chunk_size_type	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_uppercase_scheme_redirect	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_keys_are_native	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_validation	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_nonhttp_schemes_dont_check_URLs	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_auth_is_stripped_on_http_downgrade	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_rewind_body_no_seek	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_rewind_body_failed_seek	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_rewind_body_failed_tell	3	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_basic_auth_str_is_always_native	3	

(续下页)

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_requests_history_is_saved		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_iter_lines		3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_context_manager		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_unconsumed_session_response_closes		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_iter_lines_reentrant		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_without_release_conn		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_empty_stream_with_auth_does_not_se		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_stream_with_auth_does_not_set_tran		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_docstring_example		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_getitem		3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_delitem		3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_setdefault		3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_lower_items		3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_copy		3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	C	TestMorselToCookieExpires	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	C	TestMorselToCookieMaxAge	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	C	TestTimeout	A	3

(续下页)

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestTimeout.test_stream_timeout	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	C	TestPreparingURLs	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_different_connection_pool_for	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_different_connection_pool_for	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_different_connection_pool_for	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	F	test_json_encodes_as_bytes	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	F	test_data_argument_accepts_tuples	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	F	test_json_decode_errors_are_serializable_deserializable	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_no_content_length	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_no_body_content_length	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_empty_content_length	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_path_is_not_double_encoded	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_params_are_added_before_fragment	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_params_original_order_is_preserved	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_params_bytes_are_encoded	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_binary_put	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_whitespaces_are_removed_from_url	A	2

(续下页)

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_mixed_case_scheme_acceptable	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_200_OK_GET_ALTERNATIVE	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_200_OK_GET_WITH_MIXED_PARAMS	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_set_cookie_on_301	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_sent_on_redirect	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_quote_wrapped	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_request_cookies_not_persisted	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_param_cookiejar_works	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_headers_on_session_with_None_are_not_stored	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_user_agent_transfers	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_200_OK_HEAD	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_HTTP_200_OK_PUT	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_set_basicauth	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_basicauth_encodes_byte_strings	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_proxy_authorization_preserved_on_redirect	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_proxy_authorization_not_appended_twice	1	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_post_with_custom_mapping	1	

(续下页)

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_request_ok_set	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_status_raising	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_invalid_certificate_path	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_env_cert_bundles	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_http_with_certificate	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_form_encoded_post_query_multivalued	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_different_encodings_dont_break_pos	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_unicode_multipart_post	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_unicode_method_name	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_non_prepared_request_error	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_prepared_request_hook	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_prepare_request_with_bytestring_un	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_request_with_bytestring_host	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_links	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_policy_copy	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_time_elapsed_blank	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_empty_response_has_content_none	A	2

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_is_iterable	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_reason_unicode	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_reason_unicode_fallback	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_session_pickling	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_session_get_adapter_prefix_matching	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_session_get_adapter_prefix_matching	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_remove_is_case_insensitive	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_params_are_merged_case_sensitive	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_long_authinfo_in_url	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_value_not_str	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_can_send_objects_with_files	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_can_send_file_object_with_non_str	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_autoset_header_values_are_native	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_content_length_for_bytes_data	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_content_length_for_string_data_count	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_auth_is_retained_for_redirect_on_host	2	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_should_strip_auth_host_change	2	

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_should_strip_auth_http_downgrade	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_should_strip_auth_port_change	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_should_strip_auth_default_port	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_prepare_body_position_non_stream	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_json_param_post_should_not_override	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_proxy_auth	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_proxy_auth_empty_pass	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_response_json_when_content_is_None	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_len	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_update_retains_unchanges	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestCaseInsensitiveDict.test_iter	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestMorselToCookieExpires.test_expired_valid_str	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestMorselToCookieExpires.test_expired_none	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestMorselToCookieMaxAge.test_max_age_valid_int	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestTimeout.test_invalid_timeout	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestTimeout.test_none_timeout	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestTimeout.test_read_timeout	A	2

（续下页）

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestTimeout.test_total_timeout_connect	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestTimeout.test_encoded_methods	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	C	RedirectSession	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	RedirectSession.build_response	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestPreparingURLs.test_preparing_url	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestPreparingURLs.test_url_mutation	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestPreparingURLs.test_parameters_for_nonstandard_scheme	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestPreparingURLs.test_json_decode_persists_doc_attr	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	F	test_urllib3_retries	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_entry_points	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_invalid_url	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_errors	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_proxy_error	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_proxy_error_on_bad_url	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_respect_proxy_env_on_send_self_pre	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_respect_proxy_env_on_send_session	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_re quests.py	M	TestRequests.test_respect_proxy_env_on_send_with_red	A	1

(续下页)

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_respect_proxy_env_on_get	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_respect_proxy_env_on_request	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_conflicting_post_params	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_decompress_gzip	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_unicode_getA	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_unicode_header_name	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_pyopenssl_redirect	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_certificate_failure	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_hook_receives_request_arguments	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cookie_duplicate_names_raises_cookie	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_iter_content_wraps_exceptions	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_cannot_send_unprepared_requests	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_no_return_chars	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_header_no_leading_space	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests._patch_adapter_gzipped_redirect	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_redirect_with_wrong_gzipped_header	A	
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_re quests.py	M	TestRequests.test_session_close_proxy_clear	A	

（续下页）

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	TestMorselToCookieExpires.test_	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	TestMorselToCookieMaxAge.test_	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	RedirectSession.__init__	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	RedirectSession.send	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	RedirectSession._build_raw	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_preparing_	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_redirecting_to_	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_re quests.py	M	TestPreparingURLs.test_post_json_nan	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	C	TestCaseInsensitiveDict	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.test_copy	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	C	TestLookupDict	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.test_list	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.test_getitem	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.test_delitem	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.test_lower_items	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.test_repr	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.test_instance_equality	A	2

(续下页)

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestLookupDict.test_repr	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestLookupDict.test_getitem	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestLookupDict.test_get	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestCaseInsensitiveDict.setup	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_st ructures.py	M	TestLookupDict.setup	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_text_response	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_basic_response	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	C	TestTestServer	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_multiple_requests	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_request_recovery	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_basic	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_requests_after_timeout_are_not_r	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_request_recovery_with_bigger_tim	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_server_finishes_on_error	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_server_finishes_when_no_connecti	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_server_closes	A	1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test/_te stserver.py	M	TestTestServer.test_basic_waiting_server	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_iter_slices	B	6
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestGuessFilename	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestExtractZippedPaths	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestExtractZippedPaths.test_zipped_paths_extracted	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_add_dict_to_cookiejar	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_should_bypass_proxies_with_registry	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_set_environ	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestSuperLen	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_io_streams	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_file	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_with_tell	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestToKeyValList	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestUnquoteHeaderValue	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestGetEnvironProxies	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestIsIPv4Address	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestIsValidCIDR	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestAddressInNetwork	A	3

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGuessFilename.test_guess_filename_valid		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestContentEncodingDetection	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestContentEncodingDetection.test_pragmas		
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	C	TestGuessJSONUTF	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_get_auth_from_url	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_requote_uri_with_unquoted_percents	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_unquote_unreserved	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_dotted_netmask	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_select_proxies	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_parse_dict_header	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test__parse_content_type_header		2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_get_encoding_from_headers	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_parse_header_links	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_prepend_scheme_if_needed	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_to_native_string	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_urldefragauth	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_should_bypass_proxies	A	2

（续下页）

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_unicode_is_ascii	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_should_bypass_proxies_no_proxy	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_should_bypass_proxies_with_registry_bad_values	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_set_environ_raises_exception	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	F	test_should_bypass_proxies_with_registry_ProxyOverride	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_correctly_calculates_len	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_handles_files_raising_we	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_tell_ioerror	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_string	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_tarfile_member	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_with_len_2	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_with_no_len	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_with_fileno	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestSuperLen.test_super_len_with_no_matches	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestToKeyValList.test_valid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestUnquoteHeaderValue.test_valid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestUnquoteHeaderValue.test_is_filename	A	2

(续下页)

文件	类型	符号 (函数/方法)	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGetEnvironProxies.test_bypass	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGetEnvironProxies.test_not_bypass	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGetEnvironProxies.test_bypass_no_proxy_keyword	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGetEnvironProxies.test_not_bypass_no_proxy_keyword	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestIsValidIPv4Address.test_valid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestIsValidIPv4Address.test_invalid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestIsValidCIDR.test_valid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestIsValidCIDR.test_invalid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestAddressInNetwork.test_valid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestAddressInNetwork.test_invalid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGuessFilename.test_guess_filename_invalid	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestExtractZippedPaths.test_unzipped_paths_unchanged	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestExtractZippedPaths.test_invalid_unzip_path	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestContentEncodingDetection.test_none	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestContentEncodingDetection.test_precedence	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGuessJSONUTF.test_encoded	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_/_requests/tests/test/_ut ils.py	M	TestGuessJSONUTF.test_bad_utf_like_encoding	A	2

(续下页)

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_utils.py	M	TestGuessJSONUTF.test_guess_by_bom	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_utils.py	F	test_should_bypass_proxies_pass_only_hostname		
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_utils.py	M	TestToKeyValList.test_invalidA		1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/test_utils.py	M	TestGetEnvironProxies.no_proxyA		1
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/utls.py	F	override_environ	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	F	consume_socket_content	A	4
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	C	Server	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server._handle_requests	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server._accept_connection	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server.__exit__	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	C	TLSSTServer	A	3
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server.__init__	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server.run	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server._close_server_sock_ignore_errors	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server.__enter__	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	TLSSTServer.__init__	A	2
D:/code/_assistant/Git/_repo/kenne threitz/_requests/tests/testserver/server.py	M	Server.text_response_server	A	1

（续下页）

文件	类型	符号（函数/方法）	等级	分数
D:/code/_assistant/Git/_repo/kennethreitz/_requests/tests/testserver/server.py	M	Server.basic_response_server	A	1
D:/code/_assistant/Git/_repo/kennethreitz/_requests/tests/testserver/server.py	M	Server._create_socket_and_bind	A	1
D:/code/_assistant/Git/_repo/kennethreitz/_requests/tests/testserver/server.py	M	TLSSTServer._create_socket_and_bind	A	1

2 测试生成（TestGen）

2.1 指标

- 写入测试文件数：8
- 覆盖函数数：63
- 输出目录：D:/code/_assistant/Git/_repo/kennethreitz/_requests/reports/kennethreitz/_requests/generated/_tests

2.2 覆盖率报告

Name	Stmts	Miss	Cover	Missing
N/A	0	0	0%	