

Flatland

Ryan Kepler Murphy

October 12, 2023

Contents

1	Introduction	3
1.1	Problem Background	3
1.2	Related works	3
1.2.1	Vehicle Scheduling Problem	3
1.2.2	Vehicle Rescheduling Problem	3
1.2.3	Multi-agent pathfinding	4
2	Approaches	5
2.1	Which methods have been used?	5
2.2	What is answer set programming?	5
3	Building Blocks	6
3.1	Environment	6
3.1.1	Track Types and Transitions	6
3.1.2	Points of Interest	6
3.2	Agents	7
3.2.1	Actions	7
3.2.2	Starting and Ending Positions	7
3.2.3	Conflicts and Speed Profiles	8

1 Introduction

1.1 Problem Background

The Flatland framework seeks to address the problem of automated train scheduling and rescheduling, a major challenge for modern railway systems. It does so by providing a simplified two-dimensional grid world environment to allow for fast experimentation of new approaches to this problem [?].

1.2 Related works

The Flatland problem exists at the intersection of several well-explored problems. In essence, it is a vehicle rescheduling problem—derived from the vehicle scheduling problem. It is also a multi-agent pathfinding problem. An understanding of how each of these problems influences Flatland is a critical piece of finding ideal methods of producing solutions.

1.2.1 Vehicle Scheduling Problem

The vehicle scheduling problem (VSP) is a classical optimization problem in the field of operational planning of public transportation systems, consisting of assigning vehicles to trips, in such a way that each trip is associated to one vehicle and a cost function is minimized [?]. This problem has been a topic of operational research for decades, but is not the primary focus of Flatland, as each instance provides a set of agents with pairs of starting and ending positions. Since the agents come pre-assigned to the origin and destination, the importance of assigning vehicles to trips is shifted to actively determining their paths. However, since Flatland randomly inflicts breakdowns upon its fleet, the task effectively transforms into a vehicle rescheduling problem.

1.2.2 Vehicle Rescheduling Problem

The vehicle rescheduling problem (VRSP) is an extension of the VSP and arises when a previously-scheduled trip is disrupted due to interruptions such as a traffic collision, a medical emergency, or a vehicle breakdown [?]. Trips in the Flatland environment may be disrupted by randomly-assigned vehicle breakdowns, each of which stops a train in its current location for an unforeseen duration. Ideally, scheduled trips that are affected by a breakdown should be rescheduled in such a way that there are minimal impacts to the original plan.

1.2.3 Multi-agent pathfinding

Multi-agent pathfinding (MAPF) is a planning problem in which agents in a shared environment must find routes to their respective destinations without incurring collisions [?].

2 Approaches

Alcrowd hosts a global competition in which participants submit crafted approaches to scenarios in the Flatland environment, which are scored and compared against one another. The variety of submissions highlights the diverse nature of approaches taken to solve the problem Flatland presents.

2.1 Which methods have been used?

- Reinforcement learning
- Deep learning
- Previous winners

2.2 What is answer set programming?

- Definition
- How can it help in this case?

3 Building Blocks

Flatland comprises a set of components that are fundamental to its ability to simulate real-world railway scenarios. In the forefront are the environment and the agents, which form the basis of modeling how trains traverse a physical network.

Further components include the scope of observation, the presence of breakdowns, and pre-determined timetables. However, these are not considered within the scope of this research.

3.1 Environment

An environment in Flatland is a grid that consists of cells that are either empty or contain tracks. A track may belong to one of nine types, and may be rotated in increments of 90° . Cells must be arranged in such a way that they form a cohesive network, even if the resulting network is simplistic. Each cell may only be occupied by a single agent at any given time step. [Transitions are symmetrical]

3.1.1 Track Types and Transitions

Flatland documentation considers seven track types, however, two of them have alternative representations that this paper recognizes as individual types, bringing the total to nine. There is also a separate designation for an empty cell.

The various rail types can be grouped into two categories: non-switches and switches. Non-switches include tracks such as straight tracks, curved tracks, and dead ends. [They do not allow the course of the path to change.] Conversely, switches represent a decision point, as they force agents to make a choice. A switch will never present more than two options.

Each rail type determines the possible transitions for the agents, meaning which neighboring cells are accessible positions following a single move. Crucially, neighboring cells that are accessible from one location, may in some cases not be accessible had the train approached this same location from another direction. For this reason, recording both the position and orientation of each agents at every time step is necessary for determining its legal paths. A diagram explaining this quality is shown in Figure ??.

3.1.2 Points of Interest

[Stations and cities]

3.2 Agents

Agents in Flatland represent the trains of a railway network. They can choose from a set of actions, are given starting locations and specified destinations, must avoid collisions and other conflicts with agents present throughout the environment, and have various speed profiles. The terms agent and train are used interchangeably.

3.2.1 Actions

Within the environment, agents follow a series of actions. Since Flatland is a discrete time simulation, the duration of each action conforms to a constant amount of time. At each time step, agents must choose from one of the following five actions:

1. **MOVE_FORWARD**: this action moves the train forward, provided there is a legal transition that allows this; this is also the appropriate action along curved track with no switch
2. **MOVE_LEFT**: this action moves the train along a switch to the left, provided there is a legal transition that allows this
3. **MOVE_RIGHT**: this action moves the train along a switch to the right, provided there is a legal transition that allows this
4. **STOP_MOVING**: this action stops the train, resulting in its remaining in the current cell
5. **DO_NOTHING**: this action compels the train to adhere to a continuation of its previous action; the one exception is that while stopped in a dead end, this reverses the direction of the train

So long as a valid action has been selected, the position and orientation of the agent will be updated in the following time step.

3.2.2 Starting and Ending Positions

Each agent is given a starting position and orientation, as well as a destination. The goal for a single agent is to traverse the environment by choosing valid actions along legal paths that lead the agent from its starting position to its destination.

For simplicity, trains are not recognized by the environment until they are actively underway. This prevents trains who have not yet begun their

journeys from occupying space on the tracks and preventing the passage of other trains. Likewise, once a train reaches its destination, it is no longer recognized as actively being present in the environment. The track space therefore becomes free once the train has completed its journey.

3.2.3 Conflicts and Speed Profiles

Consistent with core tenets of any MAPF problem, any two trains must avoid a collision with each other. Agents, as with trains in real life, may not physically pass through one another. This prevents one train from overtaking a stopped train on the same set of tracks; it also prevents two trains facing each other from swapping positions.

Furthermore, agents in Flatland may have different speeds, depending on their train types, such as passenger trains or freight trains. This speed profile determines how quickly agents are capable of traversing the environment, and ultimately influences how they interact with one another. [This means] that a train cannot travel faster than another train traveling immediately before it.