
langgraph

Multi Agents with LangGraph

Patterns, Communication and Deep Agents

ARI520 · THREE DAYS · HANDS-ON



SpiralTrain
developer courses

SpiralTrain
developer courses

General Course Remarks

- Course times
- Drinks
- Meals
- Toilettes
- Smoking
- Mobile Phones
- Manual
- Software

Everything should be made as simple as possible, but not simpler

Albert Einstein

Ja, was ich hier geschrieben habe, macht im Einzelnen überhaupt nicht den Anspruch auf Neuheit; und darum gebe ich auch keine Quellen an, weil es mir gleichgültig ist, ob das was ich gedacht habe, vor mir schon ein anderer gedacht hat.

Ludwig Wittgenstein

SpiralTrain
developer courses

Lab Environment

- **Labs run as Jupyter notebooks on the classroom laptop :**
  - `uv sync` installs the pinned stack from `uv.lock`
  - `.env` holds the course key ; no notebook contains it
  - `uv run jupyter lab` from the repository root
- **The course model is `gpt-6-luna` through OpenRouter ; no local model is needed**
- **Google Colab runs the same notebooks as a fallback**
- **`check_setup.py` confirms the stack and the key in under a minute**

From LLM to Agent

From LLM to Agent

Introduction to LangGraph

Graph Fundamentals

State Management

Building Agents

Multi-Agent Patterns

Agent Communication

Advanced Workflows

Deep Agents

Production Deployment

Real-World Applications

Comet Arcade

What is an LLM?

Tokens

The Next Token

Sampling and Temperature

A Model Call

No Memory Between Calls

What is Context?

The Context Window

What Context Costs

System Prompt

What is Tool Calling?

Tool Definitions

What is an Agent?

The Agent Loop

Tokens Across a Run

How an Agent Stops

Agents and Workflows

What is a Harness?

Solo Agent and Full Harness

Context Engineering

Compaction

Verification

Objective Metric and Optimizer

Four Ways a Loop Breaks

The Outer Loop


Why Several Agents?

Summary : From LLM to Agent

SpiralTrain developer courses

Comet Arcade

- **Comet Arcade is a made-up game studio whose crew are AI programs called agents**
  - Producer, Designer, Artist, Coder and Tester
  - A person, the Publisher, approves each release
- **Its running project is Comet Snake**
  - Snake in space : eat stars, dodge comets
  - Every fifth star speeds the game up
  - One web page, in one HTML file
  - Its art files are assets, such as the comet sprite `CS-SPR-03`, a small picture
- **A ready-made kit holds the drawing, the keyboard controls and the tests ; the crew adds the rules, the colours and the game logic**



SpiralTrain developer courses

What is an LLM?

- **A large language model is a program trained on a huge amount of text :**
  - Given text, it predicts what comes next, one piece at a time
  - A reply is a prediction and can be wrong even when it sounds confident
- **ChatGPT is an application built around such a model :**
  - The application draws the chat window and keeps the conversation
  - The model turns text into more text
- **The course reaches the model `gpt-6-luna` through OpenRouter :**
  - OpenRouter is a service that forwards requests to the companies that run models, called providers

SpiralTrain developer courses

Tokens

- **A token is the piece of text a model reads and writes :**
  - A common word is often one token, a long or rare word several
  - As a rule of thumb, about 4 characters of English make one token
- **Prices and size limits are counted in tokens**

text	tokens	pieces
`the`	1	`the`
`star`	1	`star`
`CS-SPR-03`	5	`CS` , `-SP` , `R` , `-` , `03`
`Comet`	2	`Com` , `et`
`kometenstaart`	4	`kom` , `eten` , `sta` , `art`

demo01 · tokens

SpiralTrain developer courses

Text Becomes Tokens

Is	sprite	CS	-SP	R	-	03	of
3031	36767	15903	115754	49	12	3659	328

Com	et	Snake	final	,	and	does	it
1390	292	86554	1721	11	326	2226	480

pass	the	contrast	rule	?
1853	290	20663	10652	30

77	14	21
CHARACTERS	WORDS	TOKENS

Rare text costs more tokens : the sprite id is 5 tokens and the word Comet 2. Prices and size limits are counted in tokens.

demo01 · tokens

SpiralTrain developer courses

The Next Token

- **A model writes one token at a time :**
  - It gives every token it knows a probability
  - One token is drawn from those probabilities
  - The drawn token joins the text, and the step repeats
- **A special end token or a length limit stops the writing**
- **The same prompt can give a different reply each time :**
  - Five tries with one prompt gave three different replies

demo02 · next-token

One Token at a Time

PROMPT

Complete in a few words : The snake stopped because the comet

REPLY SO FAR

The snake stopped because the comet passed.

FIVE MORE CALLS, SAME PROMPT

The snake stopped because the comet passed overhead.

blocked its path.

The snake stopped because the comet passed.

Five more tries with one prompt gave three different replies. Code around a model has to expect that.

SpiralTrain developer courses


Sampling and Temperature

- **Sampling draws the next token from the probabilities**
- **Temperature changes the odds before the draw :**
  - A low temperature favours the likeliest token
  - A high temperature gives rarer tokens a chance
- **`gpt-6-luna` ignores `temperature` through OpenRouter ; code computes this table from the first token of demo02**

```
def with_temperature(probs, temperature):
    scaled = {t: math.log(p) / temperature for t, p in probs.items()}
    total = sum(math.exp(s) for s in scaled.values())
    return {t: round(100 * math.exp(s) / total) for t, s in scaled.items()}
```

temperature	`blocked`	`The`	`got`	`was`
0.2	59 %	41 %	0 %	0 %
1	45 %	42 %	9 %	4 %
2	37 %	35 %	16 %	11 %

Temperature and the Odds



Code on the laptop computed this table, because gpt-6-luna ignores temperature through OpenRouter. Luna's replies still vary per call.

SpiralTrain developer courses


A Model Call

- **A model call is one request and one reply :**
  - The application sends text and settings
  - The provider runs the model and returns text and a token count
- **`make_llm` is the course helper that connects to the model ; `invoke` makes the call**

```
llm = make_llm(max_tokens=40)
reply = llm.invoke("In five words, describe snake in space.")
print(reply.content)
print(reply.usage_metadata)
```

```
Serpent slithers silently among stars.
{'input_tokens': 15, 'output_tokens': 13, 'total_tokens': 28, ...}
```

One Request and One Reply



15
INPUT TOKENS

13
OUTPUT TOKENS

28
TOTAL TOKENS

$0.000008
AT LIST PRICE

The reply returns with a token count : 15 tokens read and 13 written, $0.000008 at list price.

No Memory Between Calls

- **Each call is independent :**
  - The model keeps nothing after it replies
- **A chat application keeps the conversation and resends it with every call :**
  - The application holds the memory of a chat
  - Each call is larger than the last, because it includes all the earlier messages

messages sent	input tokens	reply
1	22	noted
3	46	noted
5	78	Your asset ID is CS-SPR-03, and it is too dark.

demo03 · no-memory

Resending the Conversation

APPLICATION · ONE REQUEST

My sprite is CS-SPR-03. Reply with one word : noted.

noted

It is too dark. Reply with one word : noted.

noted

Which asset id did I give you, and what is wrong with it? Reply in one sentence.



Model

keeps nothing between calls

Your asset ID is CS-SPR-03, and it is too dark.

INPUT TOKENS **78**

Call 3 sends five messages : 78 input tokens. The application holds the memory.

demo03 · no-memory

SpiralTrain developer courses

What is Context?

- **Context is everything the model can see on this call :**
  - The model sees nothing else
  - The model can use a file, a database or an earlier call only after the application puts it in the context

in the context	Comet Arcade example
Instructions	`You are the studio assistant of Comet Arcade.`
Tool descriptions, the actions on offer	`game_info` , `assets_for_game`
Conversation so far	`Which asset is at fault?`
Tool results, what those actions returned	`{"asset_id": "CS-SPR-03", "colour": "#3a4a7a"}`

The Context Window

- **The context window is the limit on how much fits in one call :**
  - Instructions, tools, history, tool results and the reply share it
- **`gpt-6-luna` has a window of 1,050,000 tokens, and one reply can use up to 128,000 of them**
- **Quality can drop well before the limit :**
  - Answers get less accurate as the context grows ; Anthropic calls this context rot

What Fills the Window

CONTEXT WINDOW OF GPT-6-LUNA

1,050,000 tokens

demo05 run, 0.1 % of the window



- **19** system prompt
- **195** tool definitions
- **48** the task
- **253** model replies and tool calls
- **523** tool results

Tool results are the largest part : 523 of 1,038 tokens, counted locally. Long tool results fill a window first.

SpiralTrain developer courses

What Context Costs

- **A provider bills every token of every call :**
  - `gpt-6-luna` costs $0.10 per million input tokens and $0.50 per million output tokens
  - Input means all the context, sent again on each call

what	tokens	at list price
One question answered in 4 calls, demo05	1,900 in, 167 out	$0.000273
One crew run that builds Comet Snake	about 2,860 in, 1,620 out	about $0.001
One crew run with no cap on its replies, 5 calls	71,934 in, 68,338 out	$0.041
One call with a full window	1,050,000 in	$0.105

SpiralTrain developer courses

System Prompt

- **The system prompt holds standing instructions from the application :**
  - It goes ahead of the conversation on every call
  - The user does not type it
- **One model plays every crew member ; the system prompts differ :**

crew member	opening of the system prompt
Designer	`Turn the brief into rules. Pick the one twist from the menu ...`
Artist	`You pick the colours and draw sprites for a space game.`
Coder	`You write the pure game logic of a one-file canvas game.`
Tester	`File one short bug per failed test ... Do not write the fix.`

- **A brief is the request for a game ; a twist is one extra rule from a menu of 4**

SpiralTrain developer courses


What is Tool Calling?

- **A model on its own can only write text**
- **Tool calling lets it ask the application to act :**
  - The model writes a request in a fixed format
  - The application runs the request
  - The result goes back to the model in a new call
- **The model never runs anything itself**
- **A tool is a piece of code the application offers, such as one that reads a database or runs the game's tests**

demo04 · tool-call-by-hand

SpiralTrain developer courses

A Tool Call Round Trip



The reply has no tool call, which ends the exchange. Two model calls produced one answer.

demo04 · tool-call-by-hand

SpiralTrain developer courses

Tool Definitions

- **A tool definition tells the model what a tool does and what it takes :**
  - The model picks a tool by its name and description
  - The model never sees the body of the function


```
@tool
def game_info(title: str) -> str:
    """Look up a Comet Arcade game by its title or id. Returns id, title, genre, status and
pitch."""
```

- **`@tool` comes from LangChain, a Python library for model applications, and builds the definition from the function :**

```
{"name": "game_info",
 "description": "Look up a Comet Arcade game by its title or id. Returns id, title, ...",
 "parameters": {"properties": {"title": {"type": "string"}}, "required": ["title"]}}
```

SpiralTrain developer courses

From Chatbot to Agent



The loop has no fixed length. The model reacting to each result makes this an agent, however few or many the tool calls.

SpiralTrain developer courses

What is an Agent?

- **An agent is a model calling tools in a loop until the task is done :**
  - The model chooses the next step from what the last step returned
- **A question for the studio assistant :**
  - `Playtesters lose Comet Snake to comets they cannot see. Which asset is at fault?`
  - The agent looks up the game, then its assets, then the style guide
  - It names the comet sprite `CS-SPR-03` and the fix, the colour `#ff6b5e`

SpiralTrain developer courses


The Agent Loop

- **Every pass through the loop has three steps :**
  - The model reads the context and chooses what to do
  - The application runs the tool the model asked for
  - The result joins the context
- **The loop ends when the model replies without a tool call, or when a cap, a fixed limit, stops it**
- **The loop is a few lines of code, a Python `while` loop that repeats until told to stop :**
  - The model supplies the decisions
  - The code around it runs the tools and resends the messages

demo05 · agent-loop-by-hand

SpiralTrain developer courses

One Lap at a Time



TASK

Playtesters lose Comet Snake to comets they cannot see. Which asset is at fault, and what should the Artist change?

PASSES

1. `game_info` — Comet Snake is CS-01, an arcade game
2. `assets_for_game` — 7 assets, among them comet CS-SPR-03
3. `search_design_docs` — Contrast rule : at least 4.5 to 1
4. `no tool call` — answer, and the loop ends

The model replies without a tool call, and the loop ends : CS-SPR-03 is at fault, change it to #ff6b5e.

The Loop as a `while` Statement

```python
messages = [system, task]
while True:
    reply = model.invoke(messages)
    messages.append(reply)
    if not reply.tool_calls:
        break
    for call in reply.tool_calls:
        result = by_name[call["name"]].invoke(call["args"])
        messages.append(ToolMessage(result, tool_call_id=call["id"]))
print(reply.content)
```


MESSAGES

`call 4 reads 832 tokens`

system	You are the studio assistant of …
human	Playtesters lose Comet Snake to …
ai	call game_info
tool	{"game_id": "CS-01", …
ai	call assets_for_game
tool	[{"asset_id": "CS-SPR-01", …
ai	call search_design_docs
tool	# Comet Arcade style guide …
ai	The comet sprite (CS-SPR-03) is at fault …

The list now holds nine messages. Four model calls produced one answer.

Resending the Context Each Call



BILLED INPUT SO FAR

1,900

call 1	+ 200
call 2	+ 283
call 3	+ 585
call 4	+ 832

new on this call
sent again

The last call read about 830 tokens, and the run billed about 1,900. The striped blocks were paid for more than once.

SpiralTrain developer courses

Tokens Across a Run

- **Two numbers describe a run :**
  - Context is what one call reads
  - Billed input is the sum over all the calls
- **Billed input grows much faster than context, because each call is billed for the whole context again**


run	calls	context of the last call	billed input
demo05, one question	4	about 830	about 1,900
`Can Comet Snake ship?`	14	2,444	18,139

- **The longer run billed 7 times its last context**

demo05b · the-bill

SpiralTrain developer courses

Tokens Over Fourteen Calls



The last call read 2,444 tokens, and the run billed 18,139 : 7 times the last context. Calls cost more as a run grows.

SpiralTrain developer courses


How an Agent Stops

- **A model reply without a tool call ends the loop**
- **A `while` loop has no other exit ; the code around it adds caps :**
  - A cap on turns, the passes through the loop, stops a run that never finishes
  - A cap on tokens stops one long reply
- **A person can pause a run and decide**
- **A build that stops at the cap with failing tests does not ship**

```
llm = make_llm(max_tokens=8000)
for turn in range(10):
    reply = model.invoke(messages)
```

SpiralTrain developer courses

Four Ways Out of the Loop



A person can pause a run. The run stays saved until the answer comes, and it goes on from there.

SpiralTrain developer courses


Agents and Workflows

- **A workflow follows a path fixed in code :**
  - After the Designer comes the Artist, after the Artist the Coder
  - The model fills in each step
- **An agent chooses its own path :**
  - The Producer decides who works next, from the last result
- **Both finish a game that passes its tests on the course model :**


pattern	runs passed	model calls	seconds, median
Workflow, fixed path	20 of 20	3	18.4
Agent, Producer with the crew as tools	8 of 8	6	25.9

Fixed Path and Chosen Path

WORKFLOW · PATH FIXED IN CODE



AGENT · PATH CHOSEN BY THE MODEL



Both built a passing game. With a known path, the agent spent twice the calls on the same result.

SpiralTrain developer courses

What is a Harness?


- **Agent = Model + Harness**
- **A harness is**

```
every piece of code, configuration, and execution logic that isn't the model itself
```

- **The model decides ; the harness acts :**
  - It runs the tools and keeps the files
  - It trims the context
  - It runs the tests and stops the loop
- **Three harnesses around a model : ChatGPT, the coding tool Claude Code, and Deep Agents from LangChain**

SpiralTrain developer courses

Harness Layers Around the Model



System prompt
You are the Tester at Comet Arcade.

Tools
game_info, run_tests, play_bot

Infrastructure
files, QuickJS to run the game, a browser

Orchestration
the crew graph, handoffs, a model per job

Hooks and caps
cap on attempts, max_tokens, compaction

Agent = Model + Harness

Agent = Model + Harness. Everything outside the blue box is the harness, which takes most of the engineering.

SpiralTrain developer courses

Solo Agent and Full Harness

- **Anthropic gave one model the same task twice : build a retro game maker**
- **The harness split the work over a planner, a generator and an evaluator :**
  - The evaluator clicked through the running app

	solo agent	full harness
time	20 minutes	6 hours
cost	$9	$200
result	`the actual game was broken`	`I was actually able to move my entity and play the game`

- **The harness cost over 20 times as much, and only its game played**

SpiralTrain developer courses

Context Engineering

- Context engineering decides what goes into the window at each step and what stays out
- Each crew member reads only what its job needs :

crew member	reads	input tokens
Artist	the game title and the extra object	404
Designer	the brief and the twist menu	574
Tester	the test report and the code	1,426
Coder	the rules and the logic block of the kit	1,702

- Tools return short answers, because large tool results fill a window fastest

SpiralTrain developer courses

Compaction

- **A long run fills the window with old tool results**
- **Compaction replaces the older messages with a summary :**
  - Writing the summary takes one more model call
  - The run goes on from the summary
- **Details can be lost :**
  - Facts that must survive go into a file or the crew’s shared project board
- **The harness runs compaction ; the model only writes the summary**


Compaction in a Run

WHAT THE NEXT CALL READS

system, tools, task

summary ids of done work, facts, what is left

bug_details
bug_details
bug_details
builds_for_game
playtests_for_game
search_design_docs
search_design_docs



Without compaction the same task ended at 2,444 tokens and billed 18,139. With compaction : 1,885 and 16,003.


SpiralTrain developer courses

Verification

- **A model stops when the work looks done**
- **Verification lets the agent find out whether it is done :**
  - The agent runs something that says pass or fail
  - It reads the result and tries again
  - A checker other than the writer decides
- **An agent can work unattended for as long as something else can tell it what is wrong**
- **At Comet Arcade the verdict comes from real tests and a bot :**
  - The model only writes the bug report

SpiralTrain developer courses

A Verification Loop



21 of 21 rule tests pass


66.0 stars, bot average

The harness runs the new build. 21 of 21 rule tests pass, and the loop exits with a playable game.

SpiralTrain developer courses


Giving the Loop Senses

Run it
QuickJS runs the game logic with no browser




20 of 21 rule tests pass

Play it
A bot plays five games



bot : 66.0 stars on average

Look at it
Chromium opens the file and takes a screenshot



score 13, no page errors

Count it
The provider reports tokens and cost



6,390 input tokens, $0.002067

Agent
CONTEXT

- the code it wrote
- 20 of 21 rule tests pass
- bot : 66.0 stars on average
- score 13, no page errors
- 6,390 input tokens, $0.002067

Tokens and cost per game are a sense too. Each check a person does by hand is a sense the loop still lacks.

SpiralTrain developer courses

Objective Metric and Optimizer

- **A loop that improves work has three parts :**

part	what it is	at Comet Arcade
Objective	the goal	`eat stars, dodge comets, every fifth star speeds up`
Metric	a number that stands in for the goal	rule tests and the bot’s score
Optimizer	what takes the next step	the Coder reads the bugs and changes the code

- **The metric only approximates the goal and can be gamed :**
  - A bot could score well by exploiting a bug
- **Writing down each failure lets the next attempt read it**

SpiralTrain developer courses

Four Ways a Loop Breaks

failure	what happens	at Comet Arcade
Blind	the loop cannot see the result	tests passed on a blank page
Wrong proxy	the metric drifts from the goal	a bot that scores by exploiting a bug
Stuck	no attempt gets closer	the Coder chased a wrong diagnosis for 3 attempts
Model limit	the model cannot take the step	narrow the task, or use a stronger model


- **Improving the loop comes before trying another prompt**

SpiralTrain developer courses

The Outer Loop

- **The agent loop sits inside a larger loop with a person at both ends :**
  - Intent : a person states the goal and why
  - Agent loop : the agent works and checks
  - Evidence : the agent passes on its results and the proof
  - Checks : automatic tests that the agent cannot change
  - Review : a person accepts the work or sends it back
- **A failure in the outer loop calls for a better loop :**
  - Better checks, a better rule or a better tool

Outer Loop at Comet Arcade




After the same bug came back in later runs, the rules got a section on the order of a step. First-try passes went from 9 of 12 to 20 of 20.

SpiralTrain developer courses

Why Several Agents?

- **One agent holds everything in one window, and the context grows with every job**
- **Several agents split the work :**
  - Each reads only the context its job needs
  - The writer and the checker stay separate
  - Work can run side by side
- **A second agent costs calls and coordination :**
  - Start with one agent, and add another when a measurement says so
- **The Comet Arcade crew is the course’s running example of this split**

One Window or a Crew



The crew finishes a real, playable game, at the cost of more calls and more coordination. A second agent has to be worth that cost.

SpiralTrain developer courses

Summary : From LLM to Agent

- An LLM predicts the next token and keeps nothing between calls
- Context is everything the model sees on one call, and every call bills all of it
- A tool call is a request ; the application runs it
- An agent is a model calling tools in a loop, and the loop grows the context
- A harness is everything around the model : tools, files, caps, compaction and checks
- Verification lets an agent find out whether the work is done
- A person sets the intent and reviews the result ; each failure leads to a better check, rule or tool

demo01 · tokens

demo02 · next-token

demo03 · no-memory

demo04 · tool-call-by-hand

demo05 · agent-loop-by-hand

Introduction to LangGraph

From LLM to Agent

Introduction to LangGraph

Graph Fundamentals

State Management

Building Agents

Multi-Agent Patterns

Agent Communication

Advanced Workflows

Deep Agents

Production Deployment

Real-World Applications

A Crew of Thirty Agents

Ten Thousand Agents on Navier-Stokes

How the Swarm Was Organised

Status of the Proof

A Compiler from Sixteen Agents

A Browser from Hundreds of Agents

A Game Maker from Three Agents

A Research Team of Agents

Recursive Language Models

The Bill for a Swarm

Patterns Behind the Examples

Comet Arcade

How Far the Crew Gets

What is LangGraph?

What the Runtime Adds

Runtime and Harness Layers

Agent Frameworks Overview

Framework Capabilities

LangGraph Control Flow

Model APIs and Agent Runtimes

Why Multi-Agent?

Context Engineering

One Agent with More Tools

When One Agent is Enough

How Multi-Agent Systems Fail

Graph-Based Architecture

Conditional Routing

A First Graph

A First Multi-Agent System

A StateGraph by Hand

create_agent

create_deep_agent

Three Levels Compared

Agents versus Workflows

What Survived in 2026

The firstmate Orchestrator

The Service Desk Case

The Capstone in Five Stages


The Three Days

Summary : Introduction to LangGraph

SpiralTrain developer courses

A Crew of Thirty Agents


- **A personal setup, October 2026, built on `firstmate`, an open-source project :**
  - About 30 agents running on Grok, an AI model, each with a single job
  - One agent, the first mate, takes every request and passes it to the right agent
- **The jobs include :**
  - Dutch bookkeeping and taxes against a bunq account
  - An inbox over Gmail and Outlook, Home Assistant, a Tesla
  - The admin of goldmary.eu, the owner's bookkeeping app
  - A seller and a buyer, side by side
- **The agents share one computer and one set of browser logins**
- **"nothing gets sent without my ok"**



Ten Thousand Agents on Navier-Stokes

- **OpenAI proposed a solution to a Millennium Prize Problem, a famous open problem in mathematics, on 8 September 2026 :**
  - The Navier-Stokes equations describe how fluids move
  - The claim : a fluid at rest, pushed by a smooth force, reaches a point in finite time where the equations break down
- **Found by a system of coordinating agents on an unreleased internal model :**
  - On the order of 10,000 concurrent agents in the group that found it
  - 88 hours to the proof, then 17 hours to rewrite it in Lean, a language in which a program checks every step
  - 2.7 million messages and about 130 billion output tokens
- **Not confirmed and not refuted on 30 October 2026**
- **OpenAI does not claim the prize**

The Swarm in Groups



Lean is a language a program can check. 17 hours turned the proof into Lean, and a preprint of 6 October says the two do not match.

How the Swarm Was Organised

- **Agents worked in groups and messaged only within their own group**
- **Separate groups received different variants of the problem :**
  - Some aimed at a proof of smoothness, others at a blowup
- **Codex merged the most useful findings of each group into new prompts**
- **Agents moved to Navier-Stokes after about 100 agents resolved a related Euler problem**
- **The model was replaced by a further-trained version during the run**
- **Lean checked the final proof :**
  - The proof checker accepts no step that does not follow
  - Lean checks the formal statement, and a preprint of 6 October says it differs from the written proof

Status of the Proof

date	what happened
8 September	OpenAI publishes the proof and a Lean formalisation
11 September	Clay Mathematics Institute : the review is "deliberately unhurried"
6 October	A preprint argues that the Lean proof does not match the written proof
27 October	King’s College London : this "does not yet establish that OpenAI’s original proof is incorrect"
30 October	Clay lists Navier-Stokes under Active ; only Poincaré is Solved

- **Lean is a language in which a program checks every step of a proof**
- **The checker tests only the Lean text it receives ; the translation from the paper needs its own check**

SpiralTrain developer courses

A Compiler from Sixteen Agents

- **Anthropic, February 2026 : 16 agents wrote a C compiler in Rust :**
  - A compiler turns source code into a program a computer can run
  - About 100,000 lines that build Linux 6.9 on x86, ARM and RISC-V
  - Nearly 2,000 sessions over two weeks, just under $20,000
- **Each agent has its own container, a sealed work area, and its own copy of one shared repository**
- **An agent claims a task by writing a lock file ; git, the version control tool, rejects a second claim**
- **Tests steer the crew : "the task verifier is nearly perfect, otherwise Claude will solve the wrong problem"**
- **Limits remain : GCC, an existing compiler, still does the 16-bit step of booting Linux, and the demo used its assembler and linker**

SpiralTrain developer courses

A Browser from Hundreds of Agents

- **Cursor, January 2026 : "Hundreds of workers run concurrently" on one branch of the code :**
  - "close to a week" of work
  - "over 1 million lines of code across 1,000 files"
- **Three roles keep them apart :**
  - Planners explore the code and create tasks
  - Workers finish one task each
  - A judge decides whether another cycle runs
- **A setup with no roles failed first : "Twenty agents would slow down to the effective throughput of two or three"**
- **The project’s README says "Not recommended for production use"**

SpiralTrain developer courses

A Game Maker from Three Agents

- **Anthropic, March 2026 : one prompt for a retro game maker, run by one agent and by a harness of three**
- **The three agents :**
  - The planner turns the short prompt into a full product spec
  - The generator builds the app in short rounds, called sprints
  - The evaluator tests the running app with Playwright, a tool that drives a browser
- **The evaluator’s brief : "click through the running application the way a user would"**
- **One failed check fails the sprint, and detailed feedback goes back to the generator**

One Prompt in Two Runs

THE PROMPT "Create a 2D retro game maker with features including a level editor ..."

SOLO


one agent

"the actual game was broken"

FULL HARNESS

planner → generator → evaluator

"I was actually able to move my entity and play the game"



The harness took 6 hours and $200, over 20 times the cost, and the game plays. The author reports rough physics and a working core.

A Research Team of Agents

- **Anthropic, June 2025 : a lead agent starts helper agents, called subagents, in parallel :**
  - 90.2 % better than a single agent on the Opus 4 model, on Anthropic’s internal evaluation
- **The cost, from the same report :**
  - Agents use about 4 times the tokens of a chat ; multi-agent systems about 15 times
  - Token use alone explained 80 % of the differences in performance
- **A poor fit, from the same report :**
  - Tasks where every agent needs the same context
  - Most coding tasks, which have fewer parallel parts than research

Recursive Language Models

- **A model that treats a long input as an environment to explore in code :**
  - The input is in a Python REPL instead of the prompt
  - The model writes code that splits it and calls fresh copies of itself on the parts
  - Only the sub-calls use tools ; the root model sees their results
- **Zhang, Kraska and Khattab (MIT, December 2025) report inputs about two orders of magnitude beyond the context window**
- **Prime Intellect called it the paradigm of 2026**
- **Alex Zhang describes it as a harness whose only tool is code**
- **Deep Agents implements the idea as dynamic subagents**

SpiralTrain developer courses

The Bill for a Swarm

- **Every extra agent reads context and writes messages**
- **The bill for a large group of agents, a swarm, runs from a tenth of a cent to millions of dollars :**
  - One Comet Snake build : 3 model calls, about $0.001
  - The C compiler : just under $20,000
- **Measured in this course on the two-part question of module 05, with `gpt-6-luna` :**
  - A single agent answered in 2 model calls ; each multi-agent pattern needed 4 to 6
  - A Deep Agent read 28 times the input tokens of the single agent
- **Alex Zhang, an MIT researcher, suspects most of a large swarm's work is wasted**
- **Cognition, maker of the Devin coding agent, reports that several reviewers on one change work, and several writers on one change still fail (April 2026)**
- **The LangChain docs say a single agent with the right tools often does as well**

SpiralTrain developer courses

Patterns Behind the Examples

example	what happens	module
a first mate and its crew	one agent passes work to the others	05
groups that message only internally	teams with their own channel	05, 06
proof and disproof groups	two sides work on one problem	05
Codex merging each group’s findings	one agent combines parallel results	05, 06
planners, workers and a judge	a boss, a pool and a stop decision	05
a seller and a buyer for one owner	two agents with opposite goals	06
"nothing gets sent without my ok"	a person approves the action	07
Lean, tests, an evaluator	a checker other than the writer	05, 07
a model that splits its input and calls copies of itself	agents started from code	08

Comet Arcade

- **The crew of module 00 builds Comet Snake, one HTML file that opens in any browser**

crew member	job
Producer	takes the brief, assigns the work, decides when the game ships
Designer	picks a twist from the menu and copies its rules
Artist	picks colours and draws sprites
Coder	writes the game logic
Tester	reports the bugs that real tests and a bot find
Publisher	a person who approves a release

The Crew Builds Comet Snake

project board — attempts 2

BRIEF Playtesters love Comet Snake but rage-quit when one comet ends a long run. Give them one way to survive.

RULES twist : shield

- Every fourth star places a shield
- The head on a shield : shield true
- A comet hit uses up the shield
- A second hit ends the game

THEME

TESTS 21 of 21

bot : 66 stars, best 80

BUG LIST · 1 · FIXED

Self-collision is not detected when the head lands on the body.

```
if (!state.over) {
  // The tail has already been removed when the snake did not grow, so
  // every remaining segment after the head is a body cell to check.
  if (state.snake.slice(1).some(segment => same(segment, head))) {
    state.over = true;
    state.reason = 'self';
```



5 model calls

6,390 tokens in

2,976 tokens out

40.5 s wall time

$0.002 at list price

The finished game, running on this slide : the crew's rules and colours, played by the kit's bot.

SpiralTrain developer courses

How Far the Crew Gets


- **The current kit passes 20 of 20 runs, and all 20 play in a browser**
- **One run takes 3 model calls and about 19 seconds**
- **The kit does much of the work :**
  - It holds the page, the drawing, the keyboard, the bot and the tests
  - The Designer picks 1 of 4 twists from a menu
  - The Coder writes 132 to 165 lines of game logic
- **The verdict comes from real tests and a real bot, and the model writes the bug report**
- **A twist off the menu has no tests**
- **Tests prove the rules ; only opening the file proves that it plays :**
  - Without the kit, 8 of 8 whole files passed the tests and 1 of 8 was a blank page

SpiralTrain developer courses

What is LangGraph?

- LangGraph is a Python library that runs a program drawn as a graph of boxes and arrows
- A node is one box : one step of work, such as a lookup, a model call or a whole agent
- An edge is one arrow : after the Designer finishes, an edge starts the Coder
- State is the data every node shares : the crew’s project board
- One graph can mix fixed steps with model decisions
- LangChain agents and Deep Agents run on LangGraph

One Run Through a Graph




The second attempt passes all 21 tests, and the same conditional edge now leads to ship.

SpiralTrain developer courses

What the Runtime Adds

- **A long agent run can crash, wait for a person or take minutes to finish**
- **LangGraph is the runtime, the software that runs the graph and looks after it through these three cases :**
  - Checkpoints : after every step the project board is saved, so a crash at the Tester restarts at the Tester
  - Interrupts : the run stops at the Publisher until a person approves the release
  - Streaming : each step and the model’s words appear while the run continues
- **Module 03 teaches checkpoints, and module 07 teaches interrupts**

A Crash and a Pause



CHECKPOINTER : ONE SAVED BOARD PER STEP

step 1 step 2 step 3 step 4 step 5


THE PUBLISHER, A PERSON

Release Comet Snake ?

```
Command(resume="yes")
```

The Publisher answers yes. The run continues from the pause, and Comet Snake ships.

Three Layers Under One Crew



Each layer runs on the one below : create_agent and create_deep_agent both return a LangGraph graph. Higher means more ready-made, lower means more control.

Runtime and Harness Layers

layer	provides	package
runtime	state, checkpoints, interrupts, streaming	LangGraph 1.2.17
framework	model interfaces, tools, agent loop, middleware	LangChain 1.4.6
harness	filesystem, delegation, context management	Deep Agents 0.7.30

- **A framework supplies building blocks ; the application assembles them**
- **A harness supplies a ready agent with tools and instructions around its loop**
- **The runtime leaves the most control to the application ; the harness the least**

Agent Frameworks Overview

- **Provider-led SDKs integrate with their ecosystems :**
  - OpenAI Agents SDK, Google ADK and Claude Agent SDK
  - Support for other models varies by SDK and feature
- **Model-agnostic frameworks work across providers :**
  - LangChain, CrewAI and Pydantic AI
  - LangGraph exposes the graph runtime directly
- **Microsoft Agent Framework succeeds AutoGen and Semantic Kernel**
- **Two requirements decide the choice :**
  - Who controls the flow, the code or the model
  - Where the agent runs and who operates it

Framework Capabilities

package	PyPI, 30 October 2026	main abstraction
CrewAI	1.15.33	agents, crews, tasks and flows
OpenAI Agents SDK	0.24.0	agent loop, tools and handoffs
Google ADK	2.13.0	agents and workflow composition
Microsoft Agent Framework	1.23.0	agents and graph workflows
Claude Agent SDK	0.2.175	Claude Code harness as an SDK
Pydantic AI	2.63.0	typed dependencies and validated output

- **LangGraph needs no agent loop ; a graph of plain Python functions runs as it is**

LangGraph Control Flow

- **LangGraph starts from state and transitions :**
  - A node runs a function, a model call or a whole agent
  - The arrows are drawn in advance : when only one leaves the Designer, the Coder always comes next
- **Agent SDKs start from an agent loop and its tools**
- **Other frameworks add explicit flows next to the loop :**
  - CrewAI provides Flows
  - ADK and Microsoft Agent Framework provide workflow composition
- `create_agent` **supplies a standard loop for an agent that needs no custom graph**

Model APIs and Agent Runtimes

interface	who runs the tool loop	role
Chat Completions	application	course OpenRouter model endpoint
Responses API	application, with hosted tools available	OpenAI model interface
Agents SDK	SDK in the application	agent loop, handoffs and tracing
Managed Deep Agents	provider-hosted harness	hosted sessions and execution

- **OpenAI-compatible names an API shape ; each provider supports its own subset**
- **A model only requests a tool call ; the runtime executes it and returns the result**
- **LangGraph keeps the application's state between model calls**

SpiralTrain developer courses

Why Multi-Agent?


- **Module 00 gave the first reasons : each agent reads less, and the writer stays apart from the checker**
- **Separate teams can own separate agents**
- **The LangChain docs add three reasons to split :**
  - Too many tools lead the model to pick the wrong one
  - Specialised knowledge takes up much of the context
  - Steps in a fixed order unlock tools in stages, such as a release tool after the tests pass

SpiralTrain developer courses

Context Engineering

- **Context engineering decides which information each agent sees**
- **The multi-agent patterns of module 05 differ in that choice :**
  - Subagents : a helper agent sees only the task the Producer wrote for it
  - Handoffs : one agent passes the work and the conversation to the next
  - Skills : one agent loads a pack of instructions when it needs them
  - Router : a dispatcher sends each agent the part of the input meant for it
- **Modules 05 and 06 compare calls and tokens across patterns**

What Each Crew Member Sees



The Coder's second attempt also gets the report and the bug notes : 2,284 input tokens. No crew member saw the whole board.

SpiralTrain developer courses

One Agent with More Tools

- **One agent with the right tools is the baseline every split is measured against**
- **Every model call includes every tool description**
- **An experiment keeps 9 studio tools and 6 questions, and adds 51 tools that return no records :**
  - Input tokens per call grow from 564 at 9 tools to 1,672 at 60
  - The fact check passes 6 of 6 at 9, 20, 40 and 60 tools
  - No added tool is called in the saved run


demo01 · one-agent-limits

The Tool List Grows

SENT TO THE MODEL ON EVERY CALL — 60 tools

list_games	daily_players	press_contacts	accessibility_options
game_info	session_length	trailer_status	save_file_format
assets_for_game	retention_curve	screenshot_library	cloud_save_usage
asset_info	crash_analytics	event_calendar	server_status
bugs_for_game	leaderboard_top	booth_plan	patch_notes
bug_details	achievement_list	localisation_status	release_calendar
builds_for_game	achievement_rates	translator_list	team_directory
playtests_for_game	player_reviews	font_library	meeting_notes
search_design_docs	forum_threads	music_tracks	office_calendar
storefront_page	forum_moderation	sound_library	hardware_inventory
store_price	discord_mentions	voice_actors	license_keys
store_discounts	social_posts	controller_support	backup_status
wishlist_count	newsletter_drafts	platform_rules	build_server_queue
sales_by_region	streamer_list	platform_submissions	competitor_games
refund_rate	press_kit	age_ratings	genre_trends

INPUT TOKENS PER CALL, AVERAGE



6 of 6 at every size

0 detours

At every size the agent answered 6 of 6, in 14 to 16 calls, and never called another system's tool. Here the long list cost tokens and nothing else.

When One Agent is Enough

- **The LangChain docs warn before they teach the patterns :**
  - "a single agent with the right (sometimes dynamic) tools and prompt can often achieve similar results"
- **One agent suits a task whose context fits and whose tools it picks correctly**
- **An agent can load a tool only when a step needs it, which keeps its list short**
- **A fixed process fits a workflow with model calls only where judgment is needed**
- **A second agent adds model calls : 2 for one agent, 4 to 6 per pattern in the module 05 experiment**
- **A split needs a measured failure that one agent cannot fix**

How Multi-Agent Systems Fail

- **MAST (Cemri et al., UC Berkeley, 2025) studies more than 1,600 traces from 7 frameworks**
- **14 failure modes in three categories :**
  - System design issues, such as step repetition or a missed termination condition
  - Inter-agent misalignment, such as information withholding or reasoning-action mismatch
  - Task verification, such as premature termination or incorrect verification
- **Cognition, April 2026, "writes stay single-threaded" :**
  - Extra agents review or advise ; one agent acts
  - "Our original observations still hold today for parallel-writer swarms"
- **Modules 05 to 07 cover each category through loops, handoffs and judges**

SpiralTrain developer courses


Graph-Based Architecture

- A `StateGraph` runs steps over one shared state, such as a build and its test result
- Each node receives the state and returns the keys it changed
- `add_edge` sets a fixed next step
- `add_conditional_edges` lets a function choose the next step from the state
- A cycle lets a step run again, such as the Coder after a failed test
- `compile` turns the definition into a graph that runs
- `START` and `END` mark the entry and the exit

Conditional Routing

- A routing function reads the state and returns the next node's name
- `Literal` in the return type names the possible targets
- The graph diagram shows a dashed edge to each possible target

```
def route(state: Build) -> Literal["ship", "back_to_coder"]:
    return "ship" if state["passed"] else "back_to_coder"
```



SpiralTrain developer courses

A First Graph

```
builder = StateGraph(Build)
builder.add_node("assemble", assemble)
builder.add_node("test", test)
builder.add_node("ship", lambda state: {"verdict": "ship"})
builder.add_node("back_to_coder", lambda state: {"verdict": "back to the Coder"})
builder.add_edge(START, "assemble")
builder.add_edge("assemble", "test")
builder.add_conditional_edges("test", route)
builder.add_edge("ship", END)
builder.add_edge("back_to_coder", END)
graph = builder.compile()
```

- The graph calls no model. It puts a build in the kit, runs the real tests and picks the next node
- Three real builds : the plain kit, 10 of 19 tests ; the first attempt, 20 of 21 ; the fix, 21 of 21

demo02 · first-look

SpiralTrain developer courses

A First Multi-Agent System

- **The Producer is one agent, and the crew members are its tools :**
  - `ask_designer`, `ask_artist` and `ask_coder` each make one model call in a fresh conversation
  - `run_game_tests` runs plain code : the tests and the bot
- **Each crew member receives only what the Producer passes in**
- **The code stays on the board, so the Producer never reads it**
- **The saved run takes 8 model calls and passes 21 of 21 tests**
- **The last cell shows the game in the notebook, and the file opens in any browser**

`demo02b · first-multi-agent`

SpiralTrain developer courses

A StateGraph by Hand

- **A `StateGraph` is a LangGraph graph written by hand, here for one bug question :**
  - A model extracts the bug id
  - Python looks up the bug, the game and the latest build
  - A model writes the answer from those facts
- **State stores the bug id, the facts and the answer**
- **Code decides which lookups run and in what order**
- **The saved run makes 2 model calls, one to extract and one to answer**

demo03 · three-levels

SpiralTrain developer courses

create_agent

- `create_agent` builds a tool-calling loop on LangGraph
- The model receives the prompt and the tool descriptions
- Each tool result goes back to the model for its next step
- The model decides which lookups to run and when to answer
- The bug question is the same as in the graph by hand, and the lookups are now tools
- The saved run takes 3 model calls against 2 for the graph by hand
- The result is a LangGraph graph, so its nodes and edges can be listed

demo03b · create-agent

SpiralTrain developer courses

create_deep_agent

- `create_deep_agent` **adds a harness around the agent loop :**
  - Filesystem tools move large results out of the context
  - A general-purpose subagent, a helper agent, takes on delegated work
  - Summarisation shortens a long conversation history
- **The prompt and tools stay the same**
- **Built-in tools and instructions raise input tokens from 1,433 to 4,797 on the bug question**
- **Todo planning is opt-in in version 0.7.30**

demo03c · deep-agent

Who Picks the Next Step

THE TASK BUG-104 is open on Comet Snake. How serious is it, and how many tests does the latest build pass ?

StateGraph by hand

the code picks every step

extract look_up answer

243

2 model calls · input tokens

create_agent

the model picks the steps

bug_details game_info builds_for_game

1,433

3 model calls · input tokens

create_deep_agent

the model picks, inside a harness

bug_details builds_for_game file tools, subagent, longer instructions

4,797

2 model calls · input tokens

create_deep_agent adds its harness. It picked two tools in 2 calls, and every call includes the harness tools and instructions : 4,797 input tokens.

Three Levels Compared

level	who picks the steps	calls	input tokens	expected facts
`StateGraph` by hand	the code	2	243	pass
`create_agent`	the model	3	1,433	pass
`create_deep_agent`	the model, inside a harness	2	4,797	pass

- One run each on `gpt-6-luna`, 30 October 2026, on the BUG-104 question
- All three report a major bug and 19 passing tests
- The Deep Agent used none of its harness tools on this question
- Module 08 compares the harness on a longer task

SpiralTrain developer courses

Agents versus Workflows

- **Module 00 told the two apart : a workflow follows a path in code, and an agent chooses its next step**
- **Here both receive the same four playtester reports :**
  - A fixed workflow gives no answer to a report without a bug id, and passes it to the Producer
  - An agent can search the bugs and assets instead
- **Production systems often combine fixed steps with agent steps**

demo04 · workflow-or-agent

Four Reports on Two Paths

REPORTS

BUG-104
shield does nothing

BUG-105
sound plays twice

BUG-202
blocked slide counts

no id
comets I cannot see

WORKFLOW : THE PATH IS IN THE CODE

parse — look_up — write_note

escalate no id

AGENT : THE MODEL PICKS THE PATH

model — tools

BUG-104	**4 calls**	1,942 in
BUG-105	**3 calls**	1,634 in
BUG-202	**3 calls**	1,546 in
no id	**4 calls**	1,919 in

WORKFLOW
3 calls
557 in
3 of 4 answered

AGENT
14 calls
7,041 in
4 of 4 answered

The agent answered four of four, in 14 model calls and 7,041 input tokens. The workflow answered three, in 3 calls and 557 tokens. Each is a single run.

What Survived in 2026

- **Anthropic's research system and `firstmate` both use an orchestrator with isolated workers :**
  - One agent is responsible for the task and combines results
  - Each worker receives a bounded brief and its own context
- **`firstmate` implements this design around coding harnesses :**
  - Each task has its own git worktree and session
  - A watcher wakes the orchestrator on events
  - Briefs and state persist in files
- **Each worker's result still goes through review before it is merged**

The firstmate Orchestrator

- `firstmate` supplies instructions, skills, scripts and persistent state for coding harnesses
- The MIT-licensed project supports Claude Code, Codex and Pi

`firstmate`	in this course
a first mate dispatching to crewmates	subagents behind one orchestrator, module 05
one git worktree and session per task	context isolation and backends, module 08
a watcher that wakes the first mate on events	event systems and async subagents, modules 06 and 09
briefs and state files on disk	checkpointers and the `Store`, module 03
merges escalated to the human	interrupts and approval flows, module 07

- Yair reports using `firstmate` for his coding fleet

The Service Desk Case

- **Aurelia Imaging Systems is a fictional imaging-equipment manufacturer**
- **The capstone, the final project of the course, builds a service desk over its supplied data :**
  - Manuals and service bulletins
  - Parts, equipment and service records in SQLite
  - Tickets and an evaluation set
- **Specialist agents handle manuals, parts and scheduling**
- **Part orders pause for approval**
- **Three made-up worlds run through the course :**
  - Modules 00 to 04 : Comet Arcade, the game studio
  - Modules 05 to 10 : Veenhaven Bus, 10 buses at 5 depots
  - Capstone : Aurelia Imaging Systems

The Capstone in Five Stages

stage	after	Aurelia service desk
1	module 03	triage, which sorts a ticket, a `service.db` lookup and an answer ; state that survives a restart
2	module 05	specialists for parts, manuals and scheduling behind a supervisor, an agent that assigns the work
3	module 07	diagnoses side by side with a judge ; the manuals agent over A2A, a protocol between agents ; part-order approval inside a subagent
4	module 08	the same desk as a Deep Agent, compared with stage 3
5	module 09	running the desk as a service with `langgraph dev`, a background diagnosis subagent and evaluation per agent

- **Evaluation compares answer quality, model calls and tokens as the desk gains capabilities**

SpiralTrain developer courses

The Three Days

day	modules	builds
Monday	01 to 04	graphs, state and single agents in plain LangGraph
Tuesday	05 to 07	the multi-agent patterns, communication between agents, control
Wednesday	08 to 10	the same system as a Deep Agent, then served, evaluated and applied

- **Three ideas run through every module :**
  - Multi-agent is context engineering
  - One agent first ; add an agent when a measurement says so
  - Build each pattern by hand, then use the harness

SpiralTrain
developer courses

Summary : Introduction to LangGraph

- Crews of agents have built compilers, browsers and game makers ; their results still need a checker
- LangGraph runs a program as nodes, edges and shared state
- LangChain supplies ready-made agents ; Deep Agents adds a harness
- A workflow follows a path set in code ; an agent picks its next step from the last result
- Multi-agent design decides what each agent sees
- One agent sets the baseline for quality and cost
- A measurement decides whether a second agent is worth its cost

Graph Fundamentals

From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications

Why LangGraph?
LangChain vs. LangGraph
Thinking in LangGraph
Directed Graphs
DAGs and Cycles
State Machines
Model Transitions
LangGraph Concepts
Node Functions
StateGraph Nodes and Edges
Hello LangGraph
START and END
Conditional Edges

Routing with path_map
Loops and Cycles
GraphRecursionError
Command
Fan-out and Fan-in
Parallel Branches and Send
Deferred Nodes
Compiling a Graph
Visualising a Graph
Functional API
Graph API or Functional API
A Model in a Node
Summary : Graph Fundamentals

SpiralTrain developer courses

Why LangGraph?

- **In the agent loop of module 00 the model picks every next step**
- **A game build needs some of those steps fixed :**
  - After the Designer finishes, the Coder starts
  - When tests fail, the build goes back to the Coder
  - When tests pass, the game ships
- **LangGraph writes those steps as code :**
  - Each step is a function, called a node
  - A project board passes from node to node and holds the work so far
- `create_agent` **from module 01 builds such a graph, and so do Deep Agents**

LangChain vs. LangGraph

- **LCEL is LangChain's pipe syntax : `prompt | model | parser`, one straight line**

Concern	LCEL runnables	LangGraph
Composition	Sequences, parallel calls and branches	Nodes and edges over state
State	Values passed between runnables	Explicit state returned from nodes
Repetition	Application code or custom runnables	Cycles and conditional edges
State updates	Application-managed values	Explicit updates returned from nodes

- **`create_agent` returns a compiled LangGraph graph**
- **A graph of its own suits logic specific to the application, such as a fix loop**

Thinking in LangGraph

- **Designing a graph starts from the process, with one question for each part :**

Part	Question	Comet Snake
Node	What are the steps?	Designer, Coder, Tester
State	What must every step see?	The project board : brief, rules, code, bugs
Edge	What runs after what?	After the Designer, the Coder
Conditional edge	What gets decided on the way?	Tests fail : back to the Coder
Control point	Where does a mistake cost most?	The Publisher approves a release

- **A step that needs judgment calls a model, such as writing the game logic**
- **A step with a fixed answer is a plain function, such as running the tests**

SpiralTrain developer courses

A Graph Drawn from Code

```
builder = StateGraph(Board)

builder.add_node("designer", designer)

builder.add_node("coder", coder)

builder.add_node("tester", tester)


builder.add_edge(START, "designer")

builder.add_edge("designer", "coder")

builder.add_edge("coder", "tester")

builder.add_edge("tester", END)
```

```
graph = builder.compile()
```



`compile` checks the drawing and returns a graph that can run. The dot follows the only path through it.

SpiralTrain developer courses

Directed Graphs

- **A directed graph is a set of steps joined by one-way arrows :**
  - A step is a node, such as `designer` or `coder`
  - An arrow is an edge : after `designer` comes `coder`
- **A run enters at `START`, goes `designer`, `coder`, `tester`, and stops at `END`**
- **An arrow back to an earlier node makes a loop, called a cycle : from `tester` back to `coder`**

SpiralTrain developer courses

DAGs and Cycles

- A path is one route through a graph, such as `designer`, `coder`, `tester`
- DAG stands for directed acyclic graph : no path leads back to an earlier node
- A graph with only that path is a DAG
- An edge from `tester` back to `coder` adds a cycle
- Graph theory calls a node a vertex, and LangGraph uses node
- LangGraph accepts both shapes, and a recursion limit stops a cycle that never ends

SpiralTrain developer courses

State Machines

- **A state machine describes a process as states and transitions :**
  - A state records where the build stands, such as `tests fail`
  - A transition moves the build on and selects the next step
- **A plain node applies a fixed transition, such as `tests pass` to `shipped`**
- **A model can choose a transition when the next step needs judgment**
- **Demo01 b prints one build as it moves through its states :**
  - `build 1`, `tests fail`, `build 2`, `tests pass`, `shipped`, after 2 attempts
  - A build that never passes stops at 3 attempts, with `tests fail`

SpiralTrain developer courses

Model Transitions

- A plain node changes the board the same way on every run
- A model node supplies a judgment, such as whether a brief is an arcade game or a puzzle
- A routing function maps that label to a node, such as `puzzle`
- The other steps stay plain functions

LangGraph Concepts

Term	Meaning	Comet Arcade
State	The data of one run, in named fields called keys	The project board
Node	A function that reads the state and returns updates	`coder` writes `code`
Edge	An arrow : which node starts when this one finishes	After `designer` , `coder`
Conditional edge	A function that reads the board and picks the next node	Tests fail : `coder`
`START` , `END`	Where a run enters and where it stops	`START` to `designer`
Builder	The graph while it is being defined ; `compile` makes it runnable	`builder = StateGraph(Board)`

SpiralTrain developer courses

Node Functions

```
def coder(board: Board) -> dict:
    return {"code": "game.html"}
```

- A node receives the current state as its input
- A node returns only the keys it changed ; LangGraph writes them onto the board
- The keys it leaves out stay as they were
- One graph can be a node inside another graph

The Project Board




```
PROJECT BOARD
brief     one way to survive
rules     twist : shield
code      148 lines of logic
bugs      ["self-hit"]
attempts  1
```

`LAST BOARD` three nodes wrote to it, and no node read the bug

Only one arrow leaves the Tester, so this run stops at `END`, with the bug still on the board.

SpiralTrain developer courses

StateGraph Nodes and Edges

- `StateGraph` **builds a graph around a state schema, the list of keys on the board :**
  - `add_node` adds a step : a function or a whole graph
  - `add_edge` adds an arrow : after `designer`, always `coder`
  - `add_conditional_edges` adds a decision : a function picks the next node
- `compile` **checks the definition and returns a graph that can run**
- **A compiled graph exposes** `invoke` **and** `stream` **:**
  - `invoke` takes the first board and returns the last one
  - `stream` returns results while the run goes on

demo02 · nodes-and-edges

SpiralTrain developer courses

Hello LangGraph

```python
from typing import TypedDict
from langgraph.graph import END, START, StateGraph

class Board(TypedDict):
    brief: str
    rules: str

def designer(board: Board) -> dict:
    return {"rules": f"rules for {board['brief']}"}

builder = StateGraph(Board)
builder.add_node("designer", designer)
builder.add_edge(START, "designer")
builder.add_edge("designer", END)
graph = builder.compile()
print(graph.invoke({"brief": "snake in space", "rules": ""}))
```


- `Board` lists the keys of the state, and `invoke` runs the graph once

Adding a Second Node

```
def designer(board: Board) -> dict:
    return {"rules": f"rules for {board['brief']}"}

def coder(board: Board) -> dict:
    return {"code": f"game from {board['rules']}"}

builder = StateGraph(Board)
builder.add_node("designer", designer)
builder.add_node("coder", coder)
builder.add_edge(START, "designer")
builder.add_edge("designer", "coder")
builder.add_edge("coder", END)
```



Two edges change, and the Coder runs after the Designer.

SpiralTrain developer courses

START and END

- `START` and `END` are two fixed names from `langgraph.graph`
- `add_edge(START, "designer")` makes the Designer the first node of every run
- `add_edge("tester", END)` stops the run after the Tester
- A graph with no edge from `START` fails at `compile` : `Graph must have an entrypoint`
- `set_entry_point` and `set_finish_point` are older equivalents ; the docs use `add_edge`

demo02b · start-end-entry

SpiralTrain developer courses

Conditional Edges


- A routing function reads the board and returns the name of the next node :

```
def route(board: Board) -> Literal["ship", "coder"]:
    return "coder" if board["bugs"] else "ship"

builder.add_conditional_edges("tester", route)
```

- LangGraph calls `route` when `tester` has finished
- The returned text is the name of a node, as `"ship"` is here
- `Literal` in the return type lists the allowed values, so the graph drawing can show each route

Tests Decide the Branch



RUN_TESTS, BUILD 2

21 of 21 rule tests pass

bot : 66.0 stars on average, best score 80

ROUTING FUNCTION

```
def route(board: Board) -> Literal["ship", "coder"]:
    return "coder" if board["bugs"] else "ship"
```

RETURNS `"ship"`

The same `route` reads an empty list and returns `"ship"`. A different board takes the other branch.

SpiralTrain developer courses

Routing with path_map

- `path_map` maps route labels to graph node names :

```
builder.add_conditional_edges(
    "tester",
    lambda board: board["tests"],
    {"pass": "ship", "fail": "coder"},
)
```

- A dictionary maps labels to destinations
- A list declares possible destinations when labels match node names
- A label missing from the map, such as `"flaky"`, raises `KeyError`

demo03b · path-map

SpiralTrain developer courses

Loops and Cycles

- A cycle sends the build back to an earlier node : tests fail, back to the Coder
- The router decides whether to go round again, and it reads a cap from the board :


```
def route(board: Build) -> Literal["ship", "coder", "__end__"]:
    if board["status"] == "tests pass":
        return "ship"
    if board["attempts"] >= 3:
        return END
    return "coder"
```

- Returning `END`, the text `"__end__"`, leaves the graph, so a build at the cap never ships

demo01b · fix-loop

SpiralTrain developer courses

The Fix Loop



RUN 2, SEED 12

3 attempts

cap


1	tests fail
2	tests fail
3	tests fail more-comets, bot-score

The router returns `END`. The run stops with its failing tests, and the build never reaches `ship`.

Reading the Fix Loop

```python
def route(board: Build) -> Literal["ship", "coder", "__end__"]:
    if board["status"] == "tests pass":
        return "ship"
    if board["attempts"] >= 3:
        return END
    return "coder"

loop = StateGraph(Build)
loop.add_node("coder", coder)
loop.add_node("tester", tester)
loop.add_node("ship", ship)
loop.add_edge(START, "coder")
loop.add_edge("coder", "tester")
loop.add_conditional_edges("tester", route)
loop.add_edge("ship", END)
```



The back edge has no `add_edge`. It exists only in a return value.

SpiralTrain developer courses


GraphRecursionError

- **LangGraph counts the steps of every run and stops at a limit :**
  - The default is 10,007 steps on LangGraph 1.2.17
  - `create_agent` and `create_deep_agent` set 9,999
- **Passing the limit stops the run with a `GraphRecursionError`**
- **A node with an edge back to itself runs until that error**
- **`recursion_limit` sets the limit for one run : `invoke(board, {"recursion_limit": 40})`**
- **A loop around a model needs a cap of its own, or the limit arrives after thousands of model calls**

demo03c · recursion-limit

SpiralTrain developer courses

A Loop with No Exit



STEPS IN ONE RUN

10,007

GraphRecursionError
Recursion limit of 10007 reached without hitting a stop condition

3 attempts, then the router returned `END`

The fix loop reads a cap from the board. A build that never passes stopped after 3 attempts.

SpiralTrain developer courses

Command

- A node can return a `Command` to write to the state and pick the next node in one step :

```
from typing import Literal
from langgraph.types import Command

def triage(state: Bug) -> Command[Literal["coder", "artist"]]:
    target = "artist" if state["kind"] == "sprite" else "coder"
    return Command(update={"assigned": target}, goto=target)
```

- `update` holds the keys to write ; `goto` names the next node
- A node returning `Command` needs no conditional edge
- The `Command[Literal[...]]` return type adds its edges to the drawing

demo04 · command-and-send

SpiralTrain developer courses

Fan-out and Fan-in


- Fan-out : one node starts several nodes at the same time
- Fan-in : those nodes meet at one node, called the join
- The join below waits for both Testers :

```
builder.add_edge(["rule_tester", "bot_tester"], "gate")
```

- Two nodes that write one key need a reducer, a function that combines the writes :

```
bugs: Annotated[list, operator.add]
```

Three Designers and a Join





```
builder.add_edge(["designer_a", "designer_b", "designer_c"], "producer")
pitches: Annotated[list, operator.add]
```

The Producer runs once, picks `shield` and sends one board on to the Coder.

SpiralTrain developer courses

Supersteps



LOG ON THE BOARD — 8 entries

designer_a | designer_b | designer_c | producer | coder | rule_tester | bot_tester | gate

5 supersteps | 8 nodes | 1.5 s, one node takes 0.3 s

---

8 nodes, each waiting 0.3 seconds, took 1.5 seconds : 5 rounds, one after the other.

demo04d · supersteps

SpiralTrain developer courses

Parallel Branches and Send

- `Send` creates branches at run time, each with its own input :


```
from langgraph.types import Send

def fan_out(state):
    return [Send("tester", {"level": level}) for level in state["levels"]]
```

- A level here is one seed, a start number : `init(seed)` lays out a different game per seed
- A `collect` node sums up the reports as `3 levels tested`
- Map-reduce : many runs of one node, then one step that combines the results

demo04b · send-map-reduce

One Tester per Level



THIS RUN

PROJECT BOARD

levels	[1, 2, 3, 4, 5]
summary	5 levels tested

level 1: 56 stars

level 2: 66 stars

level 3: 65 stars

level 4: 80 stars

level 5: 63 stars

The drawing on the left has not moved. The list on the board set the number of testers.

SpiralTrain developer courses

Deferred Nodes


- **A deferred node waits until the other scheduled work is complete**

```
builder.add_node("splice", splice, defer=True)
```

- **One branch runs `artist`, the other `coder` then `reviewer`; both lead to `splice`:**
  - Plain: `splice` runs twice, first seeing 2 entries, then 4
  - Deferred: `splice` runs once, after `reviewer`, and sees 3
- **Without `defer`, a node behind uneven branches runs once per arriving branch**

demo04c · deferred-nodes

Uneven Branches



Superstep 3 : the plain `splice` runs a second time. The deferred one runs once, with no other work left, and sees the work of all three.

SpiralTrain developer courses

Compiling a Graph

- `compile` checks the builder and returns a graph that can run
- `compile` rejects an edge to a missing node : `Found edge ending at unknown node`
- A checkpointer is attached at compile time ; it saves the board after every step
- Options for one run, such as `recursion_limit`, go into each `invoke`
- One compiled graph runs many times : demo04 b ran one graph on 3 levels, then on 5

SpiralTrain developer courses

Visualising a Graph

- A compiled graph returns a Mermaid description, a text format for diagrams :

```
print(graph.get_graph().draw_mermaid())
```

- A Markdown viewer that knows Mermaid draws the text as a diagram
- The text comes from the graph itself, so the drawing matches the code
- No network service is needed

Functional API

- The Functional API expresses a workflow with decorated functions :

```python
from langgraph.func import entrypoint, task

@task
def normalise(text: str) -> str:
    return text.strip().title()

@entrypoint()
def workflow(text: str) -> str:
    return normalise(text).result()
```

- Tasks can run in parallel and return values to the entrypoint

demo05b · functional-api

SpiralTrain developer courses

Graph API or Functional API

- **Graph API :**
  - Explicit nodes and edges can be drawn and inspected
  - Branches and loops appear directly in the graph definition
- **Functional API :**
  - Ordinary Python control flow expresses the sequence
  - Tasks mark work that can run and resume independently
- **Both APIs use the LangGraph runtime**
- **A task can call a compiled graph**

SpiralTrain developer courses

A Model in a Node

- **A model call is one node among plain functions :**
  - `classify` asks the model whether a brief is an arcade game or a puzzle
  - A routing function sends the brief to the `arcade` or the `puzzle` node
- **The model’s reply can vary between runs**
- **Every other step runs the same way each time**

demo06 · a-model-in-a-node

SpiralTrain developer courses

Summary : Graph Fundamentals

- A directed graph is nodes joined by one-way edges, from `START` to `END`
- The project board is the state : each node returns the keys it changed
- `StateGraph` builds the graph : a fixed edge always leads to one node, a conditional edge lets a function choose
- A fix loop is a cycle, and a cap on the board ends it
- Nodes whose turn has come run together in one round, a superstep, and a join waits for all of them
- `Send` creates branches at run time from what is on the board
- `compile` checks the builder and returns a graph that can run and draw itself

State Management

From LLM to Agent

Introduction to LangGraph

Graph Fundamentals

State Management

Building Agents

Multi-Agent Patterns

Agent Communication

Advanced Workflows

Deep Agents

Production Deployment

Real-World Applications

What is State?

TypedDict State

Dataclass State

Pydantic State

Input and Output Schemas

Private State

Reducers

Merging State Updates

MessagesState

add_messages

Custom Reducers

Overwriting a Reduced Key

Concurrent Updates

Checkpointers and Persistence

Durability Modes

Threads

SqliteSaver

PostgreSQL Checkpoint Storage

Restoring Saved State

Inspecting Thread State

State History

Time Travel

Forking a Checkpoint

DeltaChannel

Long-Term Memory

Streaming Modes

Debugging State

The v2 Stream Format

v3 Event Projections

Summary : State Management

SpiralTrain developer courses


What is State?

- State is one dictionary, a set of named values called keys, that a graph passes from node to node
- Comet Arcade keeps it as the project board of a game :

key	holds	written by
`brief`	what the game must do	the input
`rules`	the rules of the game	Designer
`code`	the game logic	Coder
`bugs`	what the tests found	Tester
`attempts`	builds tried so far	Coder

- Each node gets the whole board and returns only the keys it changed ; the model inside sees only what the node passes to it

The Project Board



The tests run on the new code : 21 of 21 rule tests pass. All three crew members worked from one board.

SpiralTrain developer courses

TypedDict State

- A state schema lists the keys of the board and the type of each
- `TypedDict` describes a dictionary with named keys

```
class Board(TypedDict):
    brief: str
    rules: str
    code: str
    bugs: list[str]
    attempts: int

def designer(board: Board):
    return {"rules": "Eat stars. Dodge comets."}
```

- The Designer returns one key ; the other four keep their values
- Python does not check these types at run time : a wrong type passes

demo01 · typed-dict

SpiralTrain developer courses

Dataclass State

- A dataclass gives a key a default, so the input can leave that key out
- Nodes read `board.attempts` and still return a dictionary

```
@dataclass
class BoardDefaults:
    brief: str
    attempts: int = 0

def count_attempt(board: BoardDefaults):
    return {"attempts": board.attempts + 1}
```

- Dataclass annotations do not enforce the types either

SpiralTrain developer courses

Pydantic State

- Pydantic checks a value when a node receives it
- Here `le=3` rejects a fourth attempt

```
class CheckedBoard(BaseModel):
    brief: str
    attempts: int = Field(ge=0, le=3)

def next_attempt(board: CheckedBoard):
    return {"attempts": board.attempts + 1}
```

- A bad write fails at the next node that reads it
- A bad last write passes : no node reads it, and `invoke` returns a plain dictionary
- Validation adds run-time work compared with `TypedDict`

SpiralTrain developer courses

Input and Output Schemas

- **A graph can hide its working keys from the caller :**
  - `input_schema` lists the keys a caller passes in
  - `output_schema` lists the keys `invoke` returns

```
public = StateGraph(
    InternalBoard,
    input_schema=BriefIn,
    output_schema=VerdictOut,
)
```

- **The caller sends a brief and receives only a verdict**
- **The checkpoints still hold every key, `code` included**

SpiralTrain developer courses

Private State

- A private key passes a note between two nodes and stays outside the public schema
- The node that reads the note declares the key in the type of its argument


```
class Scratch(TypedDict):
    scratch: str

def tester(board: Scratch):
    return {"verdict": "retest : " + board["scratch"]}
```

- `scratch` stays out of the `invoke` result
- `scratch` still appears in checkpoints and in streamed output
- Hiding a key from the output gives no access control

demo01d · private-state

Keys at the Edge of a Graph



The checkpoint saved all four keys, and streaming can show them. The filter changes what `invoke` returns and protects nothing.

SpiralTrain developer courses


Reducers

- **A reducer decides what happens when a node writes a key that already has a value :**
  - Without a reducer the new value replaces the old one
  - With a reducer a function combines the old value and the new one
- `Annotated` **attaches the function to the key**

```
class Collect(TypedDict):
    bugs: Annotated[list[str], operator.add]
    status: str
```

- `operator.add` **joins the saved list and the incoming list into one longer list**
- **A node returns only its new bugs**
- **A node that returns the whole list again adds every bug a second time**

Append and Overwrite



A node that returns the whole list goes through the same reducer. Every bug is now on the list twice.

SpiralTrain developer courses

Merging State Updates

- Each key has its own reducer, or none :

key	reducer	saved	update	result
`status`	none	`"rules done"`	`"bot done"`	`"bot done"`
`bugs`	`operator.add`	`["self-hit"]`	`["bot-score"]`	`["self-hit", "bot-score"]`

- The list keeps the reports of two testers, even when the reports disagree
- Deciding which report is right takes a judge or a review

SpiralTrain developer courses

MessagesState

- A chat model needs the whole conversation on every call, so the board holds a list of messages
- `MessagesState` is a ready schema with one key, `messages`, and its reducer `add_messages`
- A subclass adds extra keys, such as `game`

```python
from langgraph.graph import MessagesState

class CrewState(MessagesState):
    game: str
```

- A node returns only its new message, and the reducer keeps the earlier ones
- `game` has no reducer, so a write replaces it

SpiralTrain developer courses

add_messages


- `add_messages` **matches messages by id :**
  - A new id appends the message
  - An existing id replaces that message
  - `RemoveMessage(id=...)` deletes it

```
history = add_messages(history, [
    AIMessage("Coder started", id="reply")
])
history = add_messages(history, [RemoveMessage(id="brief")])
```

- **A message without an id gets a new one, so it appends**
- **Message dictionaries and role-content tuples become message objects**

demo02 · add-messages

Messages on the Board



`RemoveMessage` deletes the matching entry, and the list closes up. The next model call receives this list.

SpiralTrain developer courses

Custom Reducers

- A custom reducer is a function of the current value and the incoming update
- Its return value becomes the next value of the key

```
def merge_bugs(current: list[str], incoming: list[str]):
    return sorted(set(current) | set(incoming))

class Bugs(TypedDict):
    bugs: Annotated[list[str], merge_bugs]
```

- Set union keeps one copy of a bug that two testers both report
- Sorting gives a stable order
- A reducer returns a new value and leaves its arguments unchanged

demo02b · custom-reducers

Overwriting a Reduced Key

- An ordinary update to `bugs` passes through the reducer, so an empty list clears nothing
- A new build needs an empty list : `Overwrite` skips the reducer

```
from langgraph.types import Overwrite

reset.add_node("clear", lambda state: {
    "bugs": Overwrite(value=[])
})
```

- Two `Overwrite` values for one key in one step raise `InvalidUpdateError`
- An `Overwrite` drops other branches' ordinary writes to that key in the same step, with no error

demo02c · overwriting

SpiralTrain developer courses

Concurrent Updates


- **Nodes scheduled together run in one superstep, one round of the graph :**
  - Each reads the board as it stood when the round began
  - Their updates land on the board when all of them have finished
- **Two writes to one key without a reducer raise `InvalidUpdateError`**

```
parallel.add_edge(START, "rule_tester")
parallel.add_edge(START, "bot_tester")
```

- **A reducer lets both testers add to one bug list**
- **Separate keys suit branches that produce different results**
- **Picking the right bug from the list is a later step**

demo02d · concurrent-updates

Two Testers in One Step



The next step reads the whole list. The reducer kept both bugs ; a later node decides what they mean.

Checkpointers and Persistence


- **Without a checkpointer the board is gone when `invoke` returns**
- **A checkpointer saves the board after every step. One save is a checkpoint :**
  - The value of every key
  - The nodes that run next
  - An id and details such as the step number
- **Saves let a graph remember between calls, wait for a person and survive a restart**

```
from langgraph.checkpoint.memory import InMemorySaver

graph = builder.compile(checkpointer=InMemorySaver())
```

- **`InMemorySaver` keeps saves in memory and loses them when the process ends**

A Crash at the Tester



`invoke(None, config)` runs the Tester and saves the result. The Designer and the Coder do not run again, so their model calls are not paid twice.

SpiralTrain developer courses

Durability Modes

- `durability` on `invoke` sets when each save is written
- A hard kill of the process during the Tester, on a three-node graph with SQLite :

`durability`	a save is written	saves left of 4	resumes at
`"sync"`	before the next step starts	4	Tester
`"async"`, the default	in the background	4 after 50 ms ; 1 at once	Tester ; restart
`"exit"`	when the run ends	0	restart

- A model call takes seconds, so the default keeps up in a normal run
- `"exit"` leaves no history for time travel

SpiralTrain developer courses

Threads

- A thread is the history of one game : its own line of saved boards
- `thread_id` names the thread. The same id loads that board before the new input
- A new id starts with an empty board


```
snake = {"configurable": {"thread_id": "comet-snake"}}
slide = {"configurable": {"thread_id": "star-slide"}}
first = {"messages": [("user", "The twist of Comet Snake is shields.")]}
question = {"messages": [("user", "Which twist did I mention?")]}

graph.invoke(first, snake)
graph.invoke(question, snake)
graph.invoke(question, slide)
```

- A thread id gives no access control ; the application decides who may read a thread
- One user can own many threads

demo03 · threads

One Thread per Game



One graph can serve both games, and neither board can leak into the other. A thread id gives no access control : the application decides who may use an id.

SpiralTrain developer courses

SqliteSaver

- `SqliteSaver`, from `langgraph-checkpoint-sqlite`, writes saves to a file
- The file is kept after the process ends, so a new process finds the board again
- The `with` block opens and closes the connection

```
from langgraph.checkpoint.sqlite import SqliteSaver

with SqliteSaver.from_conn_string(str(database)) as saver:
    crew = builder.compile(checkpointer=saver)
    crew.invoke(inputs, config)
```

- Every graph call that uses the saver belongs inside the `with` block
- SQLite suits local development and small applications

demo03b · sqlite-saver

PostgreSQL Checkpoint Storage

- `langgraph-checkpoint-postgres` **provides a PostgreSQL backend**
- **Several application processes can share one PostgreSQL checkpoint store**
- **Production operation includes :**
  - Connection management and schema setup
  - Backups and checkpoint retention
  - Access controls for thread data
- **The checkpointer saves execution state within a thread**
- **Cross-thread application memory uses a Store**

Restoring Saved State

- A new process compiles the same graph on the same file
- `get_state` shows the saved board ; `next` names the node that was due
- `invoke(None, config)` runs that node and continues to the end

```
with SqliteSaver.from_conn_string(str(database)) as saver:
    crew = builder.compile(checkpointer=saver)
    print(crew.get_state(config).next)    # ('tester',)
    crew.invoke(None, config)
```

- The config has the same thread id, and the graph code must still match the save
- New input in place of `None` applies a new update

Inspecting Thread State

- `get_state` returns a `StateSnapshot`, one saved board, and runs no node

```
snapshot = graph.get_state(snake)
print(snapshot.values)
print(snapshot.next)
print(snapshot.config["configurable"]["checkpoint_id"])
```

- `values` holds the saved keys
- `next` names the nodes due next ; an empty `next` means the run finished
- A config with a `checkpoint_id` selects an older save

SpiralTrain developer courses

State History

- `get_state_history` lists the saves of a thread, newest first
- Each snapshot has its own config and points to its parent save

```
history = list(graph.get_state_history(config))
for snapshot in history:
    print(snapshot.metadata["step"], snapshot.next)

before_coder = next(
    snapshot for snapshot in history
    if snapshot.next == ("coder",)
)
```

- The config of a snapshot selects the point to go back to

demo04 · state-history

SpiralTrain developer courses

Time Travel

- Time travel runs a graph again from an older save
- Replay passes `None` and the config of that save

```
replayed = graph.invoke(None, before_coder.config)
```

- The nodes before the save keep their saved results
- The nodes after it run again : the Coder is a new model call, and the code can differ
- A node with an effect outside the graph repeats that effect : a replayed release ships twice
- A save with an empty `next` has nothing to replay

demo04b · replay

SpiralTrain developer courses

Forking a Checkpoint

- A fork changes one value at an older save and runs on from there
- `update_state` writes a new checkpoint next to the old one
- `as_node` says which node the change counts as, and so what runs next


```
forked = graph.update_state(
    before_coder.config, {"twist": "shield"}, as_node="producer")
alternative = graph.invoke(None, forked)
```

- Updates pass through the same reducers as node updates
- The original save stays, and the old timeline can still be read
- A fork does not recall a game that the old timeline already released

demo04c · forking

SpiralTrain developer courses

Rolling Back a Build



Two timelines on one thread. The golden build can still be read, and anything it did outside the graph, such as a release, stays done.

Time Travel in Code

```
history = list(graph.get_state_history(config))
before_coder = next(snapshot for snapshot in history
                    if snapshot.next == ("coder",))
forked = graph.update_state(before_coder.config, {"twist": "shield"},
                            as_node="producer")
alternative = graph.invoke(None, forked)
```

List the saves of the thread, newest first.
Find the save where the Coder is the next node.
Write the new twist as a new save, as if the Producer had picked it.
Run on from the new save : the Coder and the Tester run again.

DeltaChannel

- `DeltaChannel` is beta in LangGraph 1.2.17
- Between full snapshots, LangGraph rebuilds a growing value from the saved writes
- A delta reducer receives the accumulated value and a batch of writes

```
def merge_batches(current, writes):
    return current + [item for batch in writes for item in batch]

class LongThread(TypedDict):
    entries: Annotated[list[str], DeltaChannel(merge_batches)]
```

- Reducers must be deterministic and give one result however the writes are batched
- A full snapshot is stored every 1,000 updates (`snapshot_frequency`) or 5,000 supersteps
- Delta storage does not shorten the model's context

SpiralTrain developer courses

Long-Term Memory

- A checkpoint belongs to one thread, so a new game starts on an empty board
- A Store keeps data across threads, such as the studio style guide
- A namespace, a path of labels, groups documents ; a key names one document

```
store = InMemoryStore()
style = ("studio", "comet-arcade", "style")
store.put(style, "danger", {"text": "Danger is warm : use #ff6b5e."})
print(store.get(style, "danger").value)
```

- `put` with the same namespace and key replaces the document ; `delete` removes it
- `search` returns up to 10 items (`limit`) under a namespace prefix
- Labels cannot contain `.` , so an e-mail address used as a user id needs encoding first
- A node reaches the Store through `runtime.store` , and the application picks the namespaces it may read

demo05 · the-store

Short-Term and Long-Term Memory



The danger sprite of Moon Miner comes out in the studio colour. In the demo the model replied `#ff6b5e` on both games.

SpiralTrain developer courses


Streaming Modes

- `stream` **returns what a run produces while it runs**
- `stream_mode` **chooses what comes out :**
  - `updates` : the name of a node and the keys it returned
  - `values` : the whole board after each step
  - `messages` : the model's reply, token by token
  - `custom` : anything a node sends through `get_stream_writer`

```
for part in graph.stream(inputs, config,
                         stream_mode=["values", "updates"], version="v2"):
    print(part["type"], part["data"])
```

demo06 · stream-modes

One Run in Stream Modes



`updates` shows who wrote what. `values` shows the resulting board. `messages` gives a person something to read while the run goes on.

SpiralTrain developer courses

Debugging State

- `debug` **combines checkpoint and task events :**
  - Checkpoint values and scheduled work
  - Task starts and completions, including results and errors
- `checkpoints` **and** `tasks` **select those events separately**
- **Checkpoint events require a checkpointer**
- `updates` **shows which node wrote a value**
- `values` **shows the result after reducers merged updates**
- **Studio shows the graph and its state in a visual interface**

The v2 Stream Format

- `stream(..., version="v2")` emits every part in one dictionary format
- `type` names the stream mode ; `data` holds its payload
- `ns` identifies the graph namespace

```
for part in graph.stream(inputs, config,
                         stream_mode=["custom", "updates"], version="v2"):
    print(part["type"], part["ns"], part["data"])
```

- Root graph events use an empty namespace tuple
- Values events also contain interrupt information
- The default v1 format varies with modes and subgraph settings

v3 Event Projections

- `stream_events(..., version="v3")` **returns a** `GraphRunStream`
- **Experimental on 1.2.17 ; the docs recommend it for new application code**
- **Projections select typed views of one run :**
  - `values` yields state snapshots
  - `messages`, `lifecycle` and `subgraphs` expose other views

```
run = small_graph.stream_events({"attempts": 0}, version="v3")
for state in run.values:
    print(state)
print(run.output)
```

- **Iteration drives the synchronous run without a background thread**
- **v3 sets stream modes and subgraph streaming itself, so** `stream_events` **takes neither as an argument**

SpiralTrain developer courses

Summary : State Management

- The board is one dictionary ; a schema names its keys and a node returns only what it changed
- A reducer combines a new write with the saved value ; without one the write replaces it
- Parallel writes to one key need a reducer or separate keys
- A checkpointer saves the board after every step, so a crash at the Tester restarts at the Tester
- A thread keeps one game’s saves apart from every other game
- Time travel reruns from an older save ; a fork changes a value there and leaves the old timeline in place
- A Store keeps memory across threads, such as the studio style guide
- Stream modes show who wrote what while the run goes on

exercise02 · State for Two Agents

Building Agents


From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications

Tool-Calling Agents
Models and Messages
Defining Tools
Agent Single Pass
Agent Loop
ToolNode
tools_condition
ReAct Agent
create_agent
An Agent as a Node
Custom Agent Logic
Custom Agent State
A Crew as Tools
Middleware Hooks
Writing Logging Middleware
Failure Modes of an Agent
Fault Tolerance
Node Run Timeout
Node Idle Timeout
Node Error Handler
Tool Errors
Model Fallback
Model Call Limit
Tool Call Limit
LangSmith Tracing
Testing Strategies
Unit Tests with a Fake Model
Testing Memory
Running pytest
Best Practices
Summary : Building Agents

Tool-Calling Agents

- **Module 00 wrote an agent as a `while` loop around a model :**
  - The model reads the messages and the tool list, then asks for a tool or answers
  - Python runs the tool and adds the result to the messages
  - A reply without a tool call ends the loop
- **A graph runs the same loop, one node per job :**
  - A crash in the tool step restarts at the tool step, from the saved state
  - Checkpoints from module 03 and the human approval of module 07 work on the loop without new code
- **One question runs through this module, the one from module 00 :**
  - Playtesters lose Comet Snake to comets they cannot see. Which asset is at fault?

From Loop to Graph



Calls 2 and 3 fetch the assets and the style guide. Call 4 reads about 830 tokens, asks for no tool and ends the run.

Models and Messages

- **A chat model accepts a list of messages and returns an `AIMessage`**
- **Module 00 used four kinds of message :**
  - `SystemMessage` holds the standing instructions
  - `HumanMessage` holds the request
  - `AIMessage` holds the model's text and any `tool_calls`
  - `ToolMessage` holds a result, linked to its request by `tool_call_id`
- **`llm.bind_tools(tools)` sends the tool descriptions with every call**
- **Binding runs nothing : the reply only asks for a tool**

```
bound = llm.bind_tools(tools)
message = bound.invoke([("human", "What genre is Comet Snake?")])
print(message.content, message.tool_calls)
```

SpiralTrain developer courses

Defining Tools


- `@tool` turns a Python function into the description the model reads :
  - The function name becomes the tool name
  - Type hints describe the arguments
  - The docstring tells the model when to use it
- The `?` in the SQL keeps a title from being read as SQL
- A tool returns `Unknown game` when no game matches, so the model has nothing to guess

```
@tool
def game_info(title: str) -> str:
    """Look up a Comet Arcade game by its title."""
    with sqlite3.connect(DB) as conn:
        row = conn.execute(
            "SELECT game_id, genre, status FROM games WHERE title = ?",
            (title,)).fetchone()
    return json.dumps(dict(zip(["game_id", "genre", "status"], row))) if row else "Unknown game"
```

SpiralTrain developer courses

Agent Single Pass

- **A graph with no way back gives the model one chance to choose tools**
- **The lookups of the Comet Snake question depend on each other :**
  - `game_info` returns the game id, `CS-01`
  - `assets_for_game` needs that id
  - The style guide search comes after the assets
- **The saved run calls `game_info`, then has to answer**
- **Its answer names the asset and style guide lookups as missing**



SpiralTrain developer courses

Agent Loop

- An edge from `tools` back to `agent` gives the model a turn after each result
- The model reads each result before it picks the next tool
- A routing function reads the last message :
  - Tool calls present : go to `tools`
  - No tool calls : end the graph
- The saved run of the loop makes 4 model calls, as the `while` loop did, and names the comet sprite, `CS-SPR-03`

```
loop.add_node("agent", call_model)
loop.add_node("tools", run_tools)
loop.add_edge(START, "agent")
loop.add_conditional_edges("agent", route)
loop.add_edge("tools", "agent")
result = loop.compile().invoke(question, {"recursion_limit": 16})
```

demo01 · react-as-a-graph

SpiralTrain developer courses

ToolNode

- `ToolNode` **is the** `run_tools` **function of the loop, ready-made :**
  - Finds the registered tool for each call in the last message
  - Checks the arguments against the tool's description
  - Returns one `ToolMessage`, the message type for a tool result, per call, with the same call id
- **Several calls in one reply can run in parallel**
- **A tool can return a** `Command` **to update custom state or route the graph**
- **An exception, Python's signal for an error, stops the run unless a handler catches it**

```
from langgraph.prebuilt import ToolNode

builder.add_node("tools", ToolNode(tools))
```

SpiralTrain developer courses

tools_condition

- `tools_condition` **is the** `route` **function of the loop, ready-made :**
  - Tool calls in the last message : returns `"tools"`
  - No tool calls : returns `"__end__"`
- **The default route expects a node named** `tools`
- **A path map sends the route to a node with another name**


```python
from langgraph.prebuilt import tools_condition

builder.add_conditional_edges("agent", tools_condition)
builder.add_edge("tools", "agent")
graph = builder.compile()
```

demo01b · toolnode-and-tools-condition

SpiralTrain developer courses

Routing a Tool Call




The run ends with 4 model calls. Neither prebuilt part ever looks at the text of the answer.

SpiralTrain developer courses

ReAct Agent

- **ReAct is the 2022 paper behind this loop : reason, act, observe, repeat**
- **A tool-calling agent follows the same order :**
  - The model selects a tool
  - The tool returns an observation
  - The model uses the observation in its next decision
- **The graph records each action and observation as messages**
- **A custom node can force an order, such as the game lookup before the assets**



SpiralTrain developer courses

create_agent


- `create_agent` **builds the loop from a model and a tool list :**
  - A node named `model` chooses tools or answers
  - A node named `tools` runs them
  - Middleware, extra code the application supplies, runs around both
- **The result is a compiled LangGraph graph**
- `invoke` **returns the final state, with every message**

```
from langchain.agents import create_agent

agent = create_agent(llm, tools=tools,
    system_prompt="You are the studio assistant of Comet Arcade. Use the tools.")
result = agent.invoke(question, {"recursion_limit": 16})
print(result["messages"][-1].content)
print(list(agent.get_graph().nodes))
```

demo02 · create-agent

One Loop in Three Forms



Each step adds its tool result to the context, and every call pays for all of it again : about 1,900 input tokens for one question.

SpiralTrain developer courses

An Agent as a Node

- A compiled agent can be one node of a larger graph
- Keys the parent and the agent share, such as `messages`, pass in and out
- The parent decides what happens around the agent :
  - The `handover` node always runs after the agent answers
  - It writes the note for the Artist, with no model involved
- An agent with different keys needs a small function that translates between the two

```
parent = StateGraph(StudioState)
parent.add_node("studio_agent", agent)
parent.add_node("handover", handover)
parent.add_edge(START, "studio_agent")
parent.add_edge("studio_agent", "handover")
parent.add_edge("handover", END)
```

demo02b · agent-as-a-node

SpiralTrain developer courses

Custom Agent Logic

- **A custom model node decides the prompt and the messages the model sees**
- **A prompt states the goal and the allowed moves :**
  - Look up the game before its assets
  - Report a missing record as missing
  - Leave the release decision to the Publisher
- **An edge guarantees a step ; a prompt only asks for it :**
  - The prompt asks for the game lookup first
  - Only an edge makes the lookup happen every time

```
def call_model(state: MessagesState):
    return {"messages": [bound.invoke([prompt, *state["messages"]])]}
```

SpiralTrain developer courses

Custom Agent State

- `AgentState` **holds the messages, and a subclass can add fields :**
  - `game_id` , the game this team works on
  - `model_calls` , a counter that middleware updates
- **Middleware reads and updates those fields**
- `ToolRuntime` **passes state to a tool, and the model never sees that argument**

```
class GameState(AgentState):
    game_id: str
    model_calls: NotRequired[int]

game_agent = create_agent(llm, tools=[open_bugs],
    state_schema=GameState, middleware=[game_prompt, count_calls])
```

demo02c · custom-agent-state

A Crew as Tools


- **The Producer of module 01 is one `create_agent` :**
  - `ask_designer` and `ask_coder` each make one fresh model call
  - `run_game_tests` runs the rule tests and the bot, with no model
- **8 of 8 measured runs finished a game that passed its tests, in 6 model calls**

```
@tool
def ask_designer(brief: str) -> str:
    """Send a brief to the Designer. Returns the chosen twist and its rules."""
    reply = crew_llm.invoke([SystemMessage(DESIGNER), HumanMessage(brief)])
    return reply.content

producer = create_agent(crew_llm, tools=[ask_designer, ask_coder, run_game_tests],
                        system_prompt=PRODUCER)
```

demo02d · a-crew-as-tools

The Producer at Work



6 model calls : 4 for the Producer, 2 for the crew. The Producer stops at 644 tokens, because the code never entered its context.

SpiralTrain developer courses


Middleware Hooks

- Middleware is code that runs at fixed points of the agent loop, called hooks

hook	runs
`before_agent`	once, before the loop
`before_model`	before each model call
`wrap_model_call`	around each model call
`after_model`	after each model call
`wrap_tool_call`	around each tool call
`after_agent`	once, after the loop

- A `before` or `after` hook can read the state and return updates
- A `wrap` hook decides whether the call happens at all

Hooks Around the Model Call



demo03 log

```
agent: start
model input messages: 1
requested tools: ['game_info']
tool: game_info {'title': 'Comet Snake'}
result: {"game_id": "CS-01", "title": "Comet Snake", ...
model input messages: 3
... two more laps ...
requested tools: []
agent: end
```

`after_agent` fires once. Six hooks, and the two nodes of the agent never changed.

Writing Logging Middleware

- A middleware class can print at every model turn
- A decorated wrapper can print tool arguments and results
- The saved log shows `game_info`, `assets_for_game`, `search_design_docs`, in order
- A tool argument can contain personal data, so check what a log keeps
- Each hook adds graph steps : a `recursion_limit` of 16 stopped this agent, so it gets 30

```
class Logger(AgentMiddleware):
    def before_model(self, state, runtime):
        print("model input messages:", len(state["messages"]))

@wrap_tool_call
def log_tool(request, handler):
    print("tool:", request.tool_call["name"], request.tool_call["args"])
    result = handler(request)
    print("result:", result.content[:100])
    return result
```

demo03 · middleware-hooks

Failure Modes of an Agent

what goes wrong	Comet Arcade example	what handles it
A node crashes	The asset store drops the connection	`RetryPolicy`, `error_handler`
A tool crashes	The playtest server times out	`ToolErrorMiddleware`
The model is down	The provider refuses every call	`ModelFallbackMiddleware`
The loop never ends	`build_status` keeps saying `still building`	`ModelCallLimitMiddleware`

- **A retry suits a failure that passes by itself**
- **A tool error goes to the model as a message, so the model can report it**
- **A limit stops a run that no error would ever stop**

SpiralTrain developer courses

Fault Tolerance

- A retry policy runs a failed node again
- `max_attempts` includes the first attempt
- `retry_on` selects the exceptions worth a retry
- The retries come first ; the node error handler runs after the last one fails
- The demo node fails twice and fetches the sprites on attempt 3
- A retried upload must not publish the build twice

```
from langgraph.types import RetryPolicy

builder.add_node("fetch_sprites", fetch_sprites, retry_policy=RetryPolicy(
    max_attempts=3, initial_interval=0.01,
    jitter=False, retry_on=ConnectionError))
```

demo04 · node-failures

SpiralTrain developer courses

Node Run Timeout

- Node `timeout` limits one async attempt
- A number sets a run timeout in seconds
- `TimeoutPolicy.run_timeout` caps the wall-clock time of the attempt
- Progress does not extend the run limit
- A timeout raises `NodeTimeoutError` and drops the writes of that attempt
- Compiling a graph rejects a timeout on a synchronous node

```
await timed(slow_fetch, TimeoutPolicy(run_timeout=0.08))
```

SpiralTrain developer courses

Node Idle Timeout

- `idle_timeout` limits the time without visible progress
- The refresh policy selects what counts as progress :
  - `auto` accepts graph and LangChain callback progress
  - `heartbeat` accepts explicit `runtime.heartbeat()` calls
- A heartbeat refreshes the idle limit and leaves the run limit alone
- With both limits set, the first one reached cancels the attempt

```
await timed(progressing_fetch,
    TimeoutPolicy(run_timeout=0.08, idle_timeout=0.08,
                  refresh_on="heartbeat"))
```

demo04b · node-timeout

SpiralTrain developer courses

Node Error Handler

- `error_handler` runs after the retries are used up, or when no retry applies
- The handler receives the state and a typed `NodeError` :
  - `error.node` names the failed node
  - `error.error` holds the exception
- A returned `Command` updates state and picks the next node
- The demo builds with placeholder sprites when the asset store stays down
- An error raised by the handler fails the run

```
def on_error(state: BuildState, error: NodeError) -> Command:
    return Command(update={"status": "placeholder sprites"},
                   goto="placeholders")

builder.add_node("fetch_sprites", unavailable,
    error_handler=on_error, retry_policy=RetryPolicy(max_attempts=2,
        retry_on=ConnectionError, initial_interval=0.01, jitter=False))
```

demo04c · error-handler

SpiralTrain developer courses


Tool Errors

- **An exception inside a tool stops the whole agent**
- **`ToolErrorMiddleware` turns chosen exceptions into an error `ToolMessage`:**
  - Text returned by `on_error` goes to the model as the tool result
  - `None` returned by `on_error` lets the exception through
- **The model reads the error and reports it in its answer**
- **`ToolNode` handles wrong tool arguments before this middleware is reached**

```
def on_error(exc, request):
    if isinstance(exc, TimeoutError):
        return "Playtest server unavailable. Do not guess a score. Ask for a manual playtest."
    return None

safe = create_agent(llm, tools=[live_playtests],
                    middleware=[ToolErrorMiddleware(on_error)])
```

A Tool Error Reaches the Model



The model reports the outage and invents no score. The error text told it not to guess.

SpiralTrain developer courses


Model Fallback

- `ModelFallbackMiddleware` tries the next model when a model call raises
- `create_agent` receives the primary model ; the middleware receives the fallbacks in order
- The primary is tried again on every turn of the loop
- If every model fails, the last exception reaches the caller
- A fallback needs tool calling and the same request settings as the primary

```
agent = create_agent(primary, tools=tools,
    middleware=[ModelFallbackMiddleware(llm)],
    system_prompt="You are the studio assistant of Comet Arcade. Use the tools.")
out = agent.invoke(question, {"recursion_limit": 16})
```

demo05b · model-fallback

A Fallback Model Takes Over



turns of the loop

1	primary failed luna : game_info	2	primary failed luna : assets_for_game	3	primary failed luna : search_design_docs	4	primary failed luna : answer

A fallback catches exceptions only. If the last model raises too, the exception reaches the caller, and a wrong answer passes straight through.

SpiralTrain developer courses

Model Call Limit


- `ModelCallLimitMiddleware` **counts model calls :**
  - `run_limit` applies to one invocation
  - `thread_limit` adds up over a thread, in saved state
- `exit_behavior="end"` **stops with a limit message**
- `exit_behavior="error"` **raises an exception**
- `create_agent` **has no call limit of its own : its step budget is 9,999 graph steps**

```
middleware = ModelCallLimitMiddleware(run_limit=1, exit_behavior="end")
agent = create_agent(repeated_lookup(), tools=[game_info],
                     middleware=[middleware])
```

demo05c · call-limits


demo05d · runaway-agent

Stopping a Runaway Agent



1,098
tokens, stopped by the limit, with a message

3,926
tokens, stopped by an exception, with no answer



About twice the calls cost more than three times the tokens. `create_agent` alone allows 9,999 graph steps.

Tool Call Limit

- `ToolCallLimitMiddleware` **counts tool calls per run or per thread**
- `tool_name` **limits the counter to one tool**
- **The exit behaviour decides what happens at the limit :**
  - `continue` returns an error for the blocked call and the agent runs on
  - `end` stops the agent
  - `error` raises an exception
- **With** `continue` **, an agent can keep asking for the blocked tool, so a model call limit is still needed**

```
middleware = ToolCallLimitMiddleware(tool_name="game_info",
                                     run_limit=1, exit_behavior="end")
```

SpiralTrain developer courses

LangSmith Tracing

- LangSmith is LangChain's service for storing and viewing traces
- A trace records one run as a tree of model and tool calls :
  - Inputs, outputs and errors
  - Timing and the token counts the provider reports
- `tracing_context` switches tracing on for one block of code
- Traces go to the EU region set in `LANGSMITH_ENDPOINT`
- A project name groups related traces
- A tracing failure prints a line, and the agent still answers

```
with tracing_context(enabled=True, client=client, project_name=PROJECT):
    out = agent.invoke(question)
client.flush()
```

demo06 · tracing-with-langsmith

SpiralTrain developer courses

Testing Strategies

layer	model	what it proves
Unit test	none	A tool or a middleware does its job
Scripted agent test	fake	The graph runs the tool and passes the result on
Evaluation	real	The model picks a suitable tool on questions with known answers
Monitoring	real	Failures on live traffic, outside those questions

- **A scripted tool call proves the wiring, and says nothing about the model's choice**
- **A failure in production becomes a new test**

SpiralTrain developer courses

Unit Tests with a Fake Model

- `GenericFakeChatModel` returns scripted messages, with no API call
- An agent passes its tools to the model through `bind_tools`, so the fake needs its own version
- A scripted tool call runs the real tool and the real agent wiring
- A scripted final answer proves nothing about how a model reads the result

```
class FakeToolModel(GenericFakeChatModel):
    def bind_tools(self, tools, **kwargs):
        return self

fake = FakeToolModel(messages=iter([
    call("CS-SPR-03"), AIMessage("CS-SPR-03 is still a draft.")]))
```

SpiralTrain developer courses

Testing Memory

- `InMemorySaver` keeps graph state within a process
- A thread id selects the conversation
- A memory test reads the saved state and ignores the scripted answer text :
  - The earlier tool result is in the saved history
  - A different thread starts without that history
- A new agent and saver per test keep the tests apart
- A production database needs its own integration tests

```
config = {"configurable": {"thread_id": "first"}}
saved = agent.get_state(config).values["messages"]
assert any(m.type == "tool" and m.content == "draft" for m in saved)
```

SpiralTrain developer courses

Running pytest

- **pytest, Python's usual test runner, runs a test file without the notebook**
- **The tests check what can be observed :**
  - Tool result content and call id
  - `Unknown asset` for an asset that does not exist
  - Saved history and thread isolation
- `check_returncode` **fails the cell when a test fails**

```
run = subprocess.run([sys.executable, "-B", "-m", "pytest", "-p",
                      "no:cacheprovider", "-q", str(test_path)],
                     capture_output=True, text=True)
print(run.stdout)
run.check_returncode()
```

demo07b · pytest

SpiralTrain developer courses

Best Practices

- One agent with a short tool list comes first
- An edge guarantees a step ; a prompt only asks for it
- A tool returns `Unknown asset`, so the model has nothing to guess
- Every agent gets a model call limit and every crew model a `max_tokens`
- Retries are for short outages of operations that are safe to repeat
- Traces show the path ; tokens per call show what the path costs
- A scripted test proves the wiring ; an evaluation tests the model’s choices
- A human makes the release decision : the Publisher, in module 07

SpiralTrain developer courses

Summary : Building Agents

- An agent is the `while` loop of module 00, drawn as two nodes and a conditional edge
- `ToolNode` and `tools_condition` replace the hand-written tool step and router
- `create_agent` builds the same loop, and it can be a node or call a crew as tools
- Middleware adds code before, after and around each model and tool call
- A tool error goes to the model, a fallback replaces a failing model, a limit stops a runaway loop
- Traces show what ran ; scripted tests check the wiring
- Real-model evaluations judge the model’s choices and answers

Multi-Agent Patterns

From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications

Multi-Agent Concepts
Examples in This Module
Agent Roles and Responsibilities
Choosing a Pattern
Pattern Capabilities
Documentation Call Counts

Subagents
Subagent Context
Writing a Task Description
Manager-Worker
A Supervisor Node
Hierarchical Teams

Router
Router Code
Delegation and Handoff
Handoffs
Fixed Handoffs
Handoff Middleware
Skills

Specialized Agents
Custom Workflow
Sequential Pattern
Parallel Agents
Orchestration in Code
Collaborative Agents

Maker-Checker
Checkers Written in Code
Debate with a Judge
Generate and Filter

Orchestration Shapes
Evaluating the Boundaries
Supervisor and Swarm Packages

The Earlier Pattern Probe
What Each Pattern Costs
Folding Subagents Back
When One Agent Is Enough
When a Crew Earns Its Cost
Summary : Multi-Agent Patterns

SpiralTrain developer courses

Multi-Agent Concepts

- **A multi-agent system splits one job across agents, each with its own context :**
  - The context is everything a model can see on one call
  - The Artist reads the asset list, the Tester reads the bug list
  - The Producer reads only what those two report back
- **Multi-agent design decides what each agent sees and what comes back**
- **Three measured problems justify another agent :**
  - With too many tools, the model picks the wrong one
  - Instructions for different specialities clash in one prompt
  - Tool output crowds the request out of the context
- **One agent comes first, as the baseline for calls, tokens, seconds and quality**
- **Each pattern is built from LangGraph nodes before a harness hides it**

SpiralTrain developer courses

Examples in This Module

- **Pictures and explanations use the Comet Arcade crew ; the demos use Veenhaven Bus, a made-up bus maintenance company**
- **Both ask one question that needs two specialists :**

	Comet Arcade	Veenhaven Bus demos
Question	Sprite status and open blocker	Part stock and error guidance
Main agent	Producer	Coordinator
First specialist	Artist, `assets_for_game`	Parts worker, `part_stock`
Second specialist	Tester, `bugs_for_game`	Manuals worker, `fault_guidance`
Key identifiers	CS-01, CS-SPR-03, BUG-101	CE-CF-02, F-CE-110

- **Code on the slides comes from the demo notebooks**
- **Each number is labelled with the example it was measured on**

SpiralTrain developer courses

Agent Roles and Responsibilities

- **Each agent gets one job, stated in its prompt :**
  - The Artist answers questions on sprites from the asset list
  - The Tester answers questions on bugs from the bug list
  - The Producer delegates and writes the final answer
- **Each agent gets only the tools its job needs**
- **A role prompt states the scope and when to stop**
- **A tool description tells the Producer when to call each specialist**
- **A delegated task includes the identifiers and says when the work is done**
- **A fact missing from the answer is traced to the worker’s reply first, then to the Producer’s summary**
- **A different model per role needs an evaluation that shows the gain**

SpiralTrain developer courses

Choosing a Pattern

- **The LangChain documentation names five patterns :**

Pattern	Control	Suitable task
Subagents	Main agent calls workers as tools	Specialist work that needs its own context
Handoffs	Active agent passes the conversation on	A conversation that moves through stages
Skills	One agent loads instructions when needed	Many specialities in one conversation
Router	A classify step sends work to specialists	Input that falls into clear categories
Custom workflow	The graph fixes the order in code	A process with known steps and rules

- **One pattern can sit inside another, such as a router or a subagent in a workflow node**
- **A subagent and a skill can both serve the Tester’s job ; only the subagent gets its own context**

SpiralTrain developer courses

Pattern Capabilities

- LangChain’s documentation rates the patterns by capability :

Pattern	Separate teams	Parallel	Multi-hop	User interaction
Subagents	High	High	High	Low
Handoffs	Unrated	Unrated	High	High
Skills	High	Medium	High	High
Router	Medium	High	Unrated	Medium

- Separate teams means different groups can own and change each part
- Multi-hop means one request passes through several specialists in turn
- A custom workflow gets its capabilities from the graph the developer writes
- A rating says nothing about answer quality or cost on a given question

Documentation Call Counts

- LangChain illustrates these calls and processed tokens :

Pattern	One request	Repeat turn	Three domains
Subagents	4 calls	4 calls	5 calls, about 9K tokens
Handoffs	3 calls	2 calls	7+ calls, about 14K+ tokens
Skills	3 calls	2 calls	3 calls, about 15K tokens
Router	3 calls	3 calls	5 calls, about 9K tokens

- A repeat turn is cheaper when the active agent or the loaded skill stays in place
- Loaded instructions remain in every later call to the same agent
- The counts come from LangChain’s own examples ; measured counts follow in demo09

SpiralTrain developer courses

Subagents

- A subagent is an agent wrapped as a tool : the main agent calls it and receives text
- Each worker’s model and tool loop is its own LangGraph graph
- demo01 on Veenhaven Bus, with a parts worker as the tool :

```
workers = specialists(llm)


@tool
def call_parts(question: str) -> str:
    """Ask the parts specialist about stock and location."""
    result = workers["parts"].invoke(ask(question), LIMIT)
    return last_text(result)

coordinator = agent_by_hand(llm, [call_parts, call_manuals],
    "Delegate both data questions, then answer briefly.")
```

- The main agent sees the worker’s final answer as a tool result and none of its tool calls

demo01 · subagents

A Subagent at Work



The Producer answers from two sentences. Its last call reads 284 tokens ; the Artist's last call read 408. Saved run, Comet Arcade.

SpiralTrain developer courses

Subagent Context

- **The Artist starts with two things : its prompt and the task**
- **Everything it reads stays in its own message list**
- **The Producer keeps the task and the reply**
- **A fact crosses the boundary only in the task or in the reply :**
  - A task without game id CS-01 sends the Artist to the wrong asset list
  - A reply without the status leaves the Producer guessing
- **Each call to a worker starts empty ; it keeps nothing from its last task**

demo01b · subagent-context

SpiralTrain developer courses

Writing a Task Description

- **The Producer knows a worker only from its tool name and description**
- **The worker knows the request only from the task text**
- **A task description states :**
  - The objective, with identifiers such as CS-01 and CS-SPR-03
  - The expected output, such as the status on one line
  - The tools and sources to use
  - The boundaries, such as no design advice
- **Veenhaven Bus, demo01 c, one need and two tasks :**
  - "Is the cooling fan for this bus in stock?" sends `part_stock` the argument `cooling fan` and returns no count
  - The specified task returns "6 at Rietpoort"

SpiralTrain developer courses

Manager-Worker

- A manager owns splitting the job and writing the final answer
- Workers own one bounded task each and return findings
- The Producer is a manager ; the Artist and the Tester are workers
- Workers can be tools of an agent or nodes of a graph
- Code sets which workers exist and how many rounds the manager gets
- The manager decides whether a finding needs more work
- A lookup with known inputs, such as the status of CS-SPR-03, stays an ordinary function

SpiralTrain developer courses

A Supervisor Node


- A supervisor node picks an unfinished worker and writes its task
- The worker receives that task in a separate context
- After each worker, an edge leads back to the supervisor
- Findings are stored per worker ; code caps the loop at two worker rounds
- demo02 on Veenhaven Bus :

```
graph.add_edge(START, "supervisor")
for name in workers:
    graph.add_node(name, worker(name))
    graph.add_edge(name, "supervisor")
graph.add_conditional_edges("supervisor", lambda s: s["next"],
                            ["parts", "manuals", "finish"])
graph.add_edge("finish", END)
```

demo02 · supervisors

SpiralTrain developer courses

A Supervisor Loop



With both findings in the state the supervisor picks finish. A supervisor that picks finish too early leaves a fact out.

SpiralTrain developer courses


Hierarchical Teams

- In a hierarchy one team sits inside another, and a manager manages managers
- The Studio Head reads the Producer’s report ; the Producer reads the crew’s replies
- Each level adds a context boundary and a model call :
  - Comet Arcade, 7 calls against 6 for the team alone
  - Veenhaven Bus, demo02 b, 8 calls against 7
- A fact can be lost at either report
- demo02 b, the outer manager calls the compiled team as one node :

```
def manage(state):
    report = team.invoke(team_input(state["question"]), LIMIT)
    return {"report": report["answer"]}

manager.add_node("maintenance_team", manage)
manager.add_edge("maintenance_team", "manager")
```

Reports Through Two Levels



The extra level costs one more call : 7 against 6 here, 8 against 7 in the Veenhaven Bus demo. The level adds no fact, and its report can lose one.


SpiralTrain developer courses

Router

- A router is a classify step at the entry of the graph
- The classifier picks the specialists and writes each one’s task
- Dispatch starts only the selected branches
- A final node combines the answers
- A brief about puzzle games reaches the puzzle team alone ; a brief about both reaches both teams
- A follow-up needs a surrounding conversation or a checkpointer, because classification runs once per request

demo03 · router

A Router Fan-Out



Combine answers for both : seven calls. The first, looser prompt sent the puzzle brief to both teams in 3 of 4 runs, so the classifier needs its own test.

Router Code

- `Send` gives each selected branch its own input
- demo03 b on Veenhaven Bus :

```
def dispatch(state):
    return [Send(r["agent"], {"question": r["query"]})
            for r in state["routes"]]

class RouterState(TypedDict):
    question: str
    routes: list[dict]
    answers: Annotated[list[str], operator.add]
    final: str

graph.add_conditional_edges("classify", dispatch,
                            ["parts", "manuals"])
```


- Each branch appends one answer through the reducer on `answers`
- The combining node runs after every selected branch has finished

Delegation and Handoff

Property	Delegation	Handoff
Caller	Waits for the task result	Passes on the active role
Worker output	Returns to the caller	Continues the conversation
Typical context	One bounded task	The conversation so far
Control	Caller chooses the next action	Active agent chooses it

- A status lookup for the comet sprite suits delegation
- Choosing a twist with the Designer and then planning the build with the Coder suits a handoff
- Either choice still has to settle how much history the receiver gets

Passing the Baton



Five calls. Everything the Designer read stays in the message list, so each later call reads it again : 698 tokens. Saved run, Comet Arcade.


SpiralTrain developer courses

Handoffs

- A transfer is a tool call that changes the active agent through `Command.PARENT`
- The documented example forwards only the last assistant message
- The page says the example assumes no parallel tool calls
- Veenhaven Bus, demo04 a, shows two faults in that transfer :
  - A stock result from the same turn is dropped, and the provider rejects the history
  - An earlier lookup is lost, and the receiver reports stock unavailable
- Both faults repeat on Comet Arcade with a seeded history and a live model

demo04 · handoffs

What a Transfer Can Lose



ONE RUN OF THREE, THE ARTIST ANSWERS

The comet sprite is in draft status. I've handed off the open-bug question to the tester.

The fix protects the history. The agent still decides : in 1 of 3 runs the Tester passed the baton straight back, and half the answer was lost.

SpiralTrain developer courses

Fixed Handoffs

- **The transfer tool refuses a turn that holds other tool calls :**
  - Every other call in the turn still gets its result
  - The model transfers alone on its next turn
- **The tool enforces the rule because OpenRouter drops `parallel_tool_calls=False` for the course model**
- **The transfer forwards the full history and a matching receipt**

```
messages = runtime.state["messages"]
if len(messages[-1].tool_calls) > 1:
    return "Transfer refused : call the transfer on its own, after the other tool results."
return Command(goto=target, graph=Command.PARENT, update={
    "active_agent": target, "messages": [*messages,
        ToolMessage("Transferred to " + target,
                    tool_call_id=runtime.tool_call_id)]})
```

demo04b · handoffs-fixed

SpiralTrain developer courses

Handoff Middleware

- One agent keeps the conversation and the active step in state
- `record_bus` in demo04 c validates the fleet number and updates the step
- Middleware picks the prompt and the tools for each model call :

```
@wrap_model_call
def apply_step(request, handler):
    if request.state.get("current_step", "triage") == "triage":
        return handler(request.override(
            system_prompt="Collect the fleet number.",
            tools=[record_bus]))
    return handler(request.override(
        system_prompt="Answer using the tools.",
        tools=[part_stock, fault_guidance]))
```

- A checkpointer keeps the step across user turns

demo04c · handoffs-one-agent

SpiralTrain developer courses

Skills

- A skill is a pack of instructions that the agent loads into its own history
- The prompt holds only the names and descriptions of the packs
- demo05 on Veenhaven Bus :

```
@tool
def load_skill(name: str) -> str:
    """Load task instructions. Names: parts or manuals."""
    return SKILLS.get(name, "Unknown skill.")

skilled = agent_by_hand(llm,
    [load_skill, part_stock, fault_guidance],
    "Load each matching skill before using its tools.")
```

- The same agent keeps control, and later calls read the loaded pack
- The prompt asks for the skill first, and nothing stops a tool call without it
- Agent Skills is an open standard at the Agentic AI Foundation since October 2026

demo05 · skills

A Skill Loaded When Needed

SpiralTrain developer courses

MODEL CALLS 6

decides next

Studio assistant
1,036 tokens read

ANSWER, TURN 3
Replacing the comet list after spawning a comet throws away the newly spawned comet.

prompt : 3 pack names
human : open bugs of CS-01?
ai : bugs_for_game, then a reply
human : head through body?
ai : load_skill(canvas-games)
tool : canvas-games pack, 293 tokens
ai : tail removed twice
human : lost comet?
ai : load_skill, a second time
tool : the same pack again
ai : comet list replaced

Skill packs
files, not in context

style-guide
testing
canvas-games

The pack stays in the history, and every later call reads it. A follow-up could reuse it, yet in 2 of 3 runs Luna loaded it again.

SpiralTrain developer courses

Specialized Agents


- **Specialisation can use a subagent or a skill**
- **A subagent isolates its work :**
  - The worker keeps its own tool calls
  - The caller receives a short result
- **A skill keeps the work in the conversation :**
  - Follow-ups can reuse the loaded pack and the findings
  - Every later call reads all of it again
- **Input tokens on one question, subagents against skills :**
  - Veenhaven Bus, demo09 : 942 against 1,139, with 435 for a single agent
  - Comet Arcade : 1,341 against 3,920, with 789 for a single agent

SpiralTrain developer courses

Custom Workflow

- A custom workflow is a LangGraph graph that mixes agent steps with ordinary code
- The developer fixes the order of the steps in edges
- Model steps handle writing and judgement : the Designer picks a twist, the Coder writes the logic
- Code steps handle known rules : the tests run, a gate reads the result
- A workflow node can hold a subagent, a router or a handoff
- Each node’s input and update can be inspected in the state

The Crew as a Workflow



The tests pass, so the gate sends the build to the Publisher, a human, through interrupt. Five model calls, in an order that no model chose.

Sequential Pattern

- demo06 on Veenhaven Bus : a customer ticket is classified, gets a priority, gets a reply
- Structured output restricts the model to the permitted labels
- A lookup table sets the priority without a model

```
def prioritise(state):
    return {"priority": {
        "complaint": "high", "question": "normal", "praise": "low"
    }[state["category"]]}

graph.add_edge(START, "categorise")
graph.add_edge("categorise", "prioritise")
graph.add_edge("prioritise", "respond")
graph.add_edge("respond", END)
```

- The prompt forbids a repair date ; the saved reply gives none

SpiralTrain developer courses

Parallel Agents


- A rule tester and a bot tester can run at once because neither needs the other’s result
- Separate state keys keep their results apart
- demo06 b on Veenhaven Bus :

```
graph.add_edge(START, "parts")
graph.add_edge(START, "manuals")
graph.add_edge(["parts", "manuals"], "compose")
graph.add_edge("compose", END)
```

- The join edge waits for both branches
- `Send` and a reducer do the same for a number of branches known only at run time
- A parallel run saves no tokens, because tokens add up across the branches
- At 0.4 requests per second the parallel graph takes 11.9 seconds and the sequential one 13.5

demo06b · workflows-parallel

Shared and Isolated Context



input tokens and seconds, 5 calls each, median of 3 runs

sequential, shared	1,467	10.2 s
sequential, isolated	1,034	10.3 s
parallel, isolated	1,050	10.1 s

The join edge starts the gate when both are done, and a reducer merges the findings. Time did not fall, because the rate limiter spaces every call.

Orchestration in Code

- When the identifiers are known, no model has to choose a tool
- Code runs both lookups, and one model call writes the answer
- One call against five for the sequential agents : Veenhaven Bus, demo06 c, and Comet Arcade alike
- demo06 c :

```
def fetch(state):
    return {
        "stock": part_stock.invoke({"part": "CE-CF-02"}),
        "guidance": fault_guidance.invoke({"error_code": "F-CE-110"})
    }

graph.add_edge(START, "fetch")
graph.add_edge("fetch", "compose")
graph.add_edge("compose", END)
```

- Code guarantees the lookups run ; the written answer still needs checking

SpiralTrain developer courses

Collaborative Agents

- Collaborative agents work on one result together
- Maker-checker separates writing from reviewing : the Coder writes, the Tester reviews
- Debate gives a judge two proposals, such as the shield twist or the clock twist
- Generate and filter keeps only the candidates that pass the tests
- Every shape needs the same evidence : the rules, the tests, the data
- Code sets the completion rule and the cap on attempts
- The test result decides, because two models that agree can both be wrong

SpiralTrain developer courses

Maker-Checker

- A maker writes, a checker returns approval and specific feedback
- A rejected draft returns to the maker with that feedback
- demo07 on Veenhaven Bus, a parts note from database evidence :

```
graph.add_edge(START, "make")
graph.add_edge("make", "check")
graph.add_conditional_edges("check", lambda s:
    END if s["approved"] or s["rounds"] >= 2 else "make",
    ["make", END])
```

- Reaching the cap can leave the draft unapproved
- The saved model checker approves a correct note ; the code checker rejects it for lacking the digit 0
- A model checker costs a call : 2 calls against 1 for the code checker in demo07

demo07 · maker-checker

SpiralTrain developer courses

Checkers Written in Code

- Code can check any fact that a query can return
- The Comet Arcade tests are such a checker : they run the game, and the Coder reads what failed
- A check returns specific findings, and the maker receives them on the next attempt
- demo07 b on Veenhaven Bus starts from a draft that marks CE-DA-03 available ; its stock is 0
- A format rule can reject a correct paraphrase
- A pass proves only what the check tests :
  - Comet Arcade, no kit : 8 of 8 whole-file games passed the tests, and 1 was a blank page
  - The tests read the logic and never opened the page
- Findings still open at the cap stay visible

demo07b · checker-in-code

SpiralTrain developer courses

Debate with a Judge

- Two agents argue different actions, such as adding a shield or adding a clock
- Both receive the same evidence
- A judge reads the proposals and the evidence, then returns a choice and a reason
- demo08 on Veenhaven Bus, inspect the fan or replace it :
  - Six fans in stock do not justify a replacement
  - The manual replaces the fan only below 80 percent airflow
  - The saved judge selects inspection and keeps the airflow condition
- The judge’s extra call changed no decision, because both saved proposals already put inspection first

demo08 · debate-and-selection

Generate and Filter

- Independent calls write several candidates, such as three twist pitches
- Code checks each candidate, and a rejected one keeps its findings
- Selection applies a fixed rule ; demo08 b on Veenhaven Bus keeps the shortest passing parts note
- A stable label breaks ties between equal candidates
- When no candidate passes, the run returns an explicit failure
- More candidates add calls and tokens without guaranteeing a pass

```
return [Send("generate", {"task": style}) for style in
        ["Compact bullets.", "A compact table."]]
```

demo08b · generate-and-filter

Orchestration Shapes

- **Named shapes describe how work runs and how a result is picked :**

Shape	At Comet Arcade
Classify and act	Send a brief to the right team
Fan-out and synthesise	Combine the Artist’s and the Tester’s findings
Adversarial verification	A second Tester challenges a passing build
Generate and filter	Keep the twist pitches that pass the checks
Tournament	Compare surviving pitches in rounds
Loop until done	Fix until tests pass or attempts run out

- **Code defines coverage, joins and the stopping rule**
- **Module 08 covers Deep Agents, which package delegation and context management**

SpiralTrain developer courses

Evaluating the Boundaries

- **Each boundary gets its own check :**
  - The specialist’s answer against the asset list
  - The delegated task for game id CS-01 and the sprite asked for
  - The reply for facts lost on the way back
  - The final answer against the whole request
- **The comparison always includes one agent with both tools**
- **A keyword check passes a sentence that contradicts itself**
- **Failures are read before a prompt changes or an agent is added**

Supervisor and Swarm Packages

- **Two earlier prebuilt packages supplied multi-agent graphs :**
  - `langgraph-supervisor` centralised worker coordination
  - `langgraph-swarm` switched between active agents
- **Older tutorials and applications still contain them**
- **Neither package has had a release in 11 months**
- **The documented patterns give the same control choices :**
  - A supervisor uses agents as tools or worker nodes
  - A swarm-style transfer uses handoffs and an active-agent key
- **Both shapes need only nodes, conditional edges and `Command`**

The Earlier Pattern Probe

- Luna medians on a small in-memory bus fixture, 13 October 2026 :

Pattern	Correct	Calls	Input	Output	Seconds
Single agent	3/3	2	399	96	6.7
Subagents	3/3	6	781	204	20.3
Handoffs, fixes applied	2/3	4	1,165	99	13.5
Skills	3/3	4	1,036	131	14.6
Router	3/3	6	622	184	20.6
Custom workflow	3/3	5	472	129	17.0
Deep Agent, module 08	3/3	6	11,044	214	20.6

- Seconds include rate limiting at 0.3 requests per second

What Each Pattern Costs

- Luna medians on the Veenhaven Bus records, 26 October 2026 :


Pattern	Correct	Calls	Input	Output	Seconds
Single agent	3/3	2	435	120	5.3
Subagents	3/3	6	942	260	15.4
Handoffs, fixes applied	3/3	4	947	121	10.2
Skills	3/3	4	1,139	159	10.2
Router	3/3	6	825	246	15.2
Custom workflow	3/3	5	632	181	12.8
Code lookups	3/3	1	129	47	2.6

- Seconds include the shared limiter at 0.4 requests per second
- Code lookups use the known part number and error code

demo09 · what-each-pattern-costs

Measured Cost per Pattern

Comet Arcade : the comet sprite and the open blocker



The two cheapest stay the same : code, then one agent. Handoffs got 2 of 3 right here ; every other row got 3 of 3.

Folding Subagents Back


- **Anthropic reported in October 2026 that one agent with skills often beat both one large prompt and a set of subagents**
- **Subagents stay where one loop measurably fails :**
  - Context bloat degrades the single loop
  - Parallel tasks need fresh contexts that are discarded afterwards
  - The single agent picks the wrong tools, or its instructions conflict
- **A subagent that stays is called as a tool and returns a compact result**
- **Migration moves one subagent at a time and runs an end-to-end eval more than once**
- **demo09 agrees on its question : 2 calls for one agent, 4 to 6 for each pattern**

SpiralTrain developer courses

When One Agent Is Enough

- **One agent is enough while it passes the test on the real job**
- **LangChain : "a single agent with the right (sometimes dynamic) tools and prompt can often achieve similar results"**
- **Comet Arcade, one question, three runs each :**
  - Single agent : 2 calls, 3 of 3 right
  - Every multi-agent pattern : 5 to 6 calls
- **A fixed order needs no manager :**
  - Plain graph building a game : 3 model calls, 20 of 20 runs pass
  - Same crew under a Producer agent : 6 calls, 8 of 8 pass
- **A failure that can be shown justifies another agent : wrong tool, clashing instructions, a crowded context**

Which Pattern for Which Job



calls : median on one Comet Arcade question, three runs

A canvas rule is needed now and then, in the same conversation, so one agent loads a skill pack when the question comes up.

When a Crew Earns Its Cost

- **Anthropic built a retro game maker twice, published 24 March 2026 :**
  - One agent : about 20 minutes, $9, and "the actual game was broken"
  - Planner, generator and evaluator : about 6 hours, $200, and a game that played
- **The evaluator clicks through the running app and grades each sprint**
- **The separate checker found what the builder did not see**
- **The harness cost over 20 times as much, and only a working game justified that**
- **The Comet Arcade crew keeps a checker for the same reason : the Tester’s tests run the game**

SpiralTrain developer courses

Summary : Multi-Agent Patterns

- Multi-agent design controls what each agent sees and what comes back
- One agent is the baseline for any architecture decision
- Subagents isolate work ; skills keep it in one conversation
- Supervisors and managers coordinate bounded tasks
- A hierarchy adds another context boundary and another report
- Routers classify and dispatch ; handoffs pass the conversation on
- Workflows fix the order in code, and joins wait for parallel branches
- Collaborative patterns need evidence, checks and a cap
- Code handles known steps and deterministic checks
- Calls, tokens, seconds and answer quality decide the trade-off

Agent Communication

From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications

Message Passing
Shared State
Full History
Agent Context
Handoffs
Parent Message Update
Shared Keys
Transformed Input and Output
Communication Protocols

The Agentic AI Foundation
Agent Protocol

What is MCP?
MCP for Tools
Served Agents
What is A2A?
Agent Cards
A2A Tasks
Two Agents over A2A
Event Systems

Subgraph Streaming

v3 Projections
Custom Events

State Broadcasting
Synchronization
Conflict Resolution
Conflicting Writes
Voting
Judge and Tie-Break
Seller and Buyer
Least Privilege


Summary : Agent Communication

SpiralTrain developer courses

Message Passing

- **Agents move facts in two ways :**
  - A direct message goes to one named agent and holds only what that agent needs
  - A shared board holds every key, and every agent can read all of it
- **The Designer can message the rules to the Coder, while the Testers write on the project board**
- **A direct message names its sender, its recipient and a correlation id, a code that ties a reply to its request**
- **Inside one Python process a message is a plain object and crosses no network**

Board or Direct Message



The Coder answers with a question. The correlation id 7f3 ties that reply to the message it answers.

Shared State

- The project board is the shared state of a graph, a set of keys every node can read
- The rule Tester and the bot Tester run side by side and both report to the board
- The gate starts only after both have finished :

```
builder.add_edge("coder", "rule_tester")
builder.add_edge("coder", "bot_tester")
builder.add_edge(["rule_tester", "bot_tester"], "gate")
```

- Bus depot demo : `parts` writes stock, `manuals` writes the error guidance, and the report reads both

SpiralTrain developer courses

Full History

- Full history gives the next agent every message the caller holds
- A Coder given the whole chat reads the brief, the pitches that lost and every old bug report
- Each new message makes the next call larger
- A later agent can repeat a lookup that already sits in that history
- Bus depot demo : the receiver held the stock note, and its saved answer still left out the stock count

SpiralTrain developer courses

Agent Context

- **Four choices for what the next agent receives :**
  - Full history : every message so far
  - Task only : one selected payload, such as the rules
  - Fork : a copy of the history plus a new task
  - Summary : the agent works apart and returns selected facts
- **Task only leaves earlier facts out on purpose**
- **A returned summary can drop a condition the caller needed**

`demo01b · full-history-task-or-summary`

What Each Agent Sees

SpiralTrain developer courses


THE PRODUCER HOLDS

- brief
- pitch : golden
- pitch : shield
- the 8 rules
- bug report
- summary : 7 colours chosen

THE ARTIST SEES ON THIS CALL

- the 8 rules

INPUT TOKENS, BUS DEPOT DEMO



Summary : the Artist works apart and returns one short message. Any condition it leaves out is lost to the Producer.

SpiralTrain developer courses

Handoffs

- A handoff passes control to another agent, such as from the Designer to the Coder
- A subgraph is a graph used as one node of a larger graph
- A Designer inside a subgraph reaches the Coder in the parent graph with `Command` :

```
def handoff(state):
    return Command(
        goto="coder",
        graph=Command.PARENT,
        update={"messages": state["messages"]},
    )
```

- `Command.PARENT` targets the closest parent graph, and `goto` names a node there
- Bus depot demo : a child graph hands over to `manuals`

demo02 · subgraph-communication

SpiralTrain developer courses

Parent Message Update

- `add_messages` merges the child's messages into the parent's list by id
- The Coder's list then holds the Designer's notes
- Bus depot demo : the receiver's list held the stock note, and the written answer still omitted it
- A handoff made by a tool call must answer that call with a `ToolMessage`
- The module 05 transfer tool refuses a call made beside other tools
- Neither rule applies to this node transfer, which has no pending tool call

SpiralTrain developer courses

Shared Keys

- A subgraph added as a node shares every key that appears in both schemas
- The Artist's subgraph returns `colours` to the parent
- `working_note` exists only on the child schema
- The parent result does not contain `working_note`
- Bus depot demo : `part_no` and `stock` cross, `working_note` stays behind

demo02b · shared-keys

Transformed Input and Output

- A wrapper node translates when parent and child use different keys :

```
def mapped_art(state):
    child_input = {"game": state["title"]}
    child_output = art_graph.invoke(child_input)
    return {"palette": child_output["colours"]}
```

- The child input has no `publisher` field
- Leaving a field out of model input does not hide logs or credentials
- Bus depot demo : `mapped_parts` sends `part_no` and leaves out `requester`


Communication Protocols

- The mechanism depends on what separates the two sides :

Boundary	Mechanism
One process	Tool call, shared keys, `Command`
Async subagent	Agent Protocol
Two servers	A2A JSON-RPC
Tools	MCP

- MCP when the caller treats an agent as a tool ; A2A when it needs tasks and a `contextId`
- In-process agents can access the same process credentials
- Separate servers can use separate storage and credentials

Where Each Protocol Sits



Credentials depend on the boxes. Agents in one process can reach the same credentials ; separate servers can hold their own.

The Agentic AI Foundation

- **The Agentic AI Foundation, AAIF, operates under the Linux Foundation and hosts agent standards**
- **Four standards in this course are now hosted there :**
  - MCP : how an agent reaches tools and data
  - A2A : how an agent reaches another agent, since 27 August 2026
  - Agent Skills : folders of instructions an agent loads when needed, since 22 October 2026
  - AGENTS.md : a file that tells coding agents how to work in a repository
- **Neutral governance keeps a protocol out of the control of a single vendor**
- **AAIF hosts 10 projects, among them goose, Open Responses and OpenSandbox**

SpiralTrain developer courses

Agent Protocol

- Agent Protocol is the HTTP API for threads and runs on an Agent Server
- `POST /runs/wait` starts a run and returns its final state
- Async subagents, which work in the background on another server, use these tools :
  - `start_async_task` and `check_async_task`
  - `update_async_task`, `cancel_async_task`, `list_async_tasks`
- Deep Agents adds those tools to the agent, and the Agent Server answers their HTTP requests

SpiralTrain developer courses

What is MCP?

- MCP, the Model Context Protocol, is an open standard for offering tools to any agent
- An MCP server wraps something useful, such as an asset store, behind one fixed set of requests
- An MCP client sits in the agent’s application and asks the server what it offers
- The model receives each tool as a name, a description and an input schema
- The tool’s code and credentials stay with the server

SpiralTrain developer courses

MCP for Tools

- `langchain.mcp` turns the tools of an MCP server into tools for an agent :

```
async with MCPAdapter(asset_store) as adapter:
    mcp_tools = await adapter.list_tools()
    agent = create_agent(llm, tools=mcp_tools)
```

- An in-memory FastMCP server needs no port and no process
- Adapted tools are async only, so the agent runs with `ainvoke`
- Agent Server also serves each assistant as an MCP tool at `/mcp`
- The installed `mcp` package implements revision 2026-07-28, which is stateless : no sessions and no `initialize` handshake
- Bus depot demo : `part_stock` over MCP reports CE-DA-03 as stock 0 at Rietpoort

demo03c · mcp-tools

MCP Discovery and Call



REQUESTS SO FAR `server/discover` `tools/list` `tools/call`

The result returns to the model as a tool message, and the loop goes on. The model cannot tell where the tool ran.

Served Agents

- `langgraph dev` **runs a graph on a local web server, the Agent Server, so another process can call it**
- `POST /runs/wait` **accepts the graph id, such as** `parts`
- **Bus depot demo, saved runs :**
  - The echo server runs with the LangSmith variables removed
  - The parts server sends metadata to the configured EU endpoint
  - Both Studio banners use `smith.langchain.com`

SpiralTrain developer courses

What is A2A?

- **A2A, the Agent2Agent protocol, is an open standard for giving a task to an agent in another system**
- **An outside QA studio can test Comet Snake while its own agents and prompts stay private**
- **Three objects make up the exchange :**
  - Agent card : a public JSON document that says what the agent can do and where to reach it
  - Task : one piece of work, with an id and a status
  - Artifact : a result the task produced
- **A `contextId` ties several tasks into one conversation**
- **Requests use JSON-RPC, a plain format for calling a named method over HTTP**

SpiralTrain developer courses

Agent Cards

- The card tells a caller what one assistant does and where to send tasks
- The installed server identifies an assistant by UUID, a long generated id :

```
GET /.well-known/agent-card.json?assistant_id=<uuid>
POST /a2a/<uuid>
```

- The server rejects a graph name with "must be a UUID"
- `POST /assistants/search` returns the UUID for that graph id
- Default assistant UUIDs derive from the graph id with `uuid5`
- A2A requires a `messages` key in the input schema
- This card has no security schemes and no signature, both defined in A2A 1.0


demo03b · agent-card

SpiralTrain developer courses

A2A Tasks

- **Bus depot demo : the completed `SendMessage` response has `result.task` :**
  - `status.state` is `TASK_STATE_COMPLETED`
  - Artifacts hold the assistant text
- **`GetTask` returns the task directly, with history and no artifacts**
- **On Agent Server, `contextId` is the thread id and must be a UUID**
- **`historyScope` is an Agent Server option beside the A2A 1.0 `historyLength`**
- **Responses still contain the A2A 0.3 field `kind`**
- **`SubscribeToTask` returns -32601, method not found, although the card sets streaming**
- **`message/send`, the older method, unwraps the task and lowercases the state**

The Life of an A2A Task



FAILED, CANCELED and REJECTED are the other final states. The next request starts a new task with the same contextId.

Two Agents over A2A

- Bus depot demo : two processes on ports 2124 and 2125 with separate storage
- The coordinator looks up the specialist UUID and posts `SendMessage` :

```
{"jsonrpc": "2.0", "id": "<uuid>", "method": "SendMessage",
 "params": {"message": {"role": "ROLE_USER", "messageId": "<uuid>",
   "contextId": "<thread uuid>", "parts": [{"text": "Report CE-CF-02 stock."}]},
   "configuration": {"historyScope": "task"}}}
```

- Each server allocates its own task id
- A follow-up sends a new message with the same `contextId`

demo04 · two-agents-over-a2a

Event Systems

- A stream shows a run while it happens, one event after each step
- `updates` mode delivers the values a node returned
- A namespace names the subgraph that produced an event, such as `bot_tester`
- A custom event reports progress to whoever watches the stream
- A custom event leaves the project board unchanged

Subgraph Streaming

- `version="v2"` yields a dict with `type`, `ns` and `data`

```
for part in graph.stream(
    {"game": "Comet Snake"},
    stream_mode="updates",
    subgraphs=True,
    version="v2",
):
    print(part["ns"], part["data"])
```

- A non-empty `ns` marks an event from inside the child
- The parent update contains the keys the child returned

SpiralTrain developer courses

v3 Projections

- `stream_events(version="v3")` **returns a** `GraphRunStream`
- **A projection is one view of that stream, such as the values**
- **The caller drives the run by iterating a projection**
- `run.subgraphs` **yields a handle as each child starts**
- **Each child handle exposes a** `values` **projection**
- **v3 is experimental in langgraph 1.2.17**

SpiralTrain developer courses

Custom Events

- `get_stream_writer` publishes a value beside the state update

```
writer = get_stream_writer()
writer({"event": "playtest-started", "game": state["game"]})
return {"score": score}
```

- The stream asks for `custom` and `updates`
- The custom payload is not written into state
- Bus depot demo : `lookup-started` and `lookup-finished`

demo05b · custom-events


SpiralTrain developer courses

State Broadcasting

- A broadcast publishes one value for every reader
- The Producer writes a snapshot of the brief on a shared key
- Designer, Coder and Artist each read that key in the next step
- Each returns its own note, and `operator.add` collects the notes
- All three read the value from before their step, so none sees another’s note
- Bus depot demo : seller and buyer both read stock 6 at Rietpoort

demo05c · broadcast-channel

A Broadcast to the Crew



A later write changes the key. The readers of the finished step keep v1, and the next readers receive v2.

Synchronization

- A join lists the nodes it waits for :

```
builder.add_edge(["rule_tester", "bot_tester"], "gate")
```

- `defer=True` holds a node until the other pending nodes finish :

```
builder.add_node("gate", gate, defer=True)
builder.add_edge("rule_tester", "gate")
builder.add_edge("bot_tester", "gate")
```

- Without `defer`, separate edges run the gate after the first Tester alone
- The gate raises unless both Testers reported

SpiralTrain developer courses

Conflict Resolution

- One owner can run agents with opposing goals
- Yair’s crew post puts a seller bot beside a buyer bot
- Yair calls the pair "a conflict of interest i’ve chosen to ignore"
- Those bots share one computer and the same browser logins
- A studio has the same shape : one Tester says hold the build, the other says ship it
- A few lines of code pick the winner with the same rule on every run

SpiralTrain developer courses

Conflicting Writes

- Two nodes may write the same key in one step
- A plain key accepts one value per step
- A second value raises `InvalidUpdateError`
- A list with `operator.add` keeps both verdicts
- Both verdicts stay on the board until a later step settles them
- Bus depot demo : `seller` proposes sell, `buyer` proposes retain

demo06 · conflicts

SpiralTrain developer courses

Voting

- Separate agents vote on one proposal, each in its own model call
- Each vote keeps the role, the choice and the reason
- Code counts the votes afterwards, such as 2 ship and 1 hold
- Voters that read the same evidence can repeat the same mistake
- Bus depot demo : selling 4 of 6 fans breaks a reserve of 4, and the saved vote was 3 retain, 0 sell

demo06b · voting

SpiralTrain developer courses

Judge and Tie-Break

- One hold vote and one ship vote make a tie
- A judge is an agent that records a decision and a reason
- Code settles it : the majority wins, and a tie holds the build

```
chosen = "ship" if counts["ship"] > counts["hold"] else "hold"
if chosen == "ship" and failed_tests > 0:
    return "hold", "failing test"
```

- A failing test overrides a majority for ship
- Bus depot demo : a tie retains stock, and code overrides two sell votes that break the reserve


demo06c · judge-and-tie-break

Conflict Between Two Testers

rule Tester
20 of 21 tests pass
`FAIL self-hit`

Producer

bot Tester
66.0 stars on average
`best score 80`



hold : a failing test

`bug report to the Coder`

One rule overrides the count : a failing test holds the build. The bug report goes back to the Coder.

SpiralTrain developer courses

Seller and Buyer

- **Bus depot demo, two agents and one stock of parts :**
  - The seller proposes a quantity to release
  - The buyer proposes a quantity to keep
- **Settlement keeps at least the reserve**
- **Retention is the greater of the reserve and the buyer’s quantity**
- **The sale is capped by the seller’s quantity and the remaining surplus**
- **The result records `external_action` as false**
- **Saved run : buyer 4, seller 2, settled as sell 2, retain 4**


SpiralTrain developer courses

Least Privilege

- Least privilege : each agent holds only the keys its own job needs
- Shared browser logins expose the same authenticated services to every agent
- `ToolRuntime` passes the principal, the identity of the caller, to the tool
- `context_schema=Principal` tells `create_agent` the shape of that trusted context
- The published tool schema contains `quantity` only, so the model cannot claim another identity
- `authorise` refuses when the seller’s agent tries to draft a purchase

demo07b · least-privilege-per-agent

Which Agent Holds Which Key



The release key stays with the Publisher, a person. A prompt injected into one agent reaches one key at most.

SpiralTrain developer courses

Summary : Agent Communication

- A direct message reaches one agent ; a shared board reaches them all
- Handoffs cross graphs with `Command` and `Command.PARENT`
- Agent Protocol and A2A connect agents across processes
- MCP lets an agent discover and call tools in memory or at `/mcp`
- MCP, A2A, Agent Skills and AGENTS.md are all hosted by one neutral body, the AAIF
- A stream shows a run live, with events from subgraphs and custom progress events
- State broadcasting publishes one snapshot for every reader
- Conflict resolution keeps both writes, then applies a vote, a judge or a tie rule
- A list edge or `defer=True` makes a node wait until both branches finish
- Least privilege gives each agent its own credentials and tools

exercise05 · Two Agents over A2A

exercise06 · Buyer and Seller

p. 313

Advanced Workflows

From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications

Advanced Workflows
Human-in-the-Loop
The interrupt Function
Resuming with Command
Approval States
Approve, Edit and Reject
Several Interrupts in One Step
Interrupts in Subgraphs
Interrupts in Subagents
Human-in-the-Loop Middleware
Gating Agent Actions
Per-Call Approval
Two Layers of Approval
Loop Detection in Graphs
A Watchdog Node
Repeated Tool Calls
Retry Strategies and Backoff
Fallback Chains
Subgraphs and Composition
Conditional Branching at Scale
Durable Execution
Resuming After a Crash
Graceful Workflow Drain
Summary : Advanced Workflows

SpiralTrain
developer courses

Advanced Workflows


- **A workflow can pause for a human decision :**
  - The Publisher approves a release before it goes out
  - The pause also works inside a subgraph or a subagent tool
- **A workflow can bound its own loops :**
  - A watchdog node stops a fix loop that makes no progress
  - A guard blocks a repeated tool call
- **A workflow can recover from failure :**
  - Retries with backoff around a call to a remote asset store
  - A fallback chain from live data to a cached copy to a person
  - Resume from a checkpoint after a crash or a drain
- **Each team can own one subgraph of a larger workflow**

SpiralTrain developer courses

Human-in-the-Loop

- **An agent loop can act on a wrong conclusion :**
  - Publish a build that plays badly
  - Replace the released game without sign-off
- **A human-in-the-loop workflow pauses before such an action :**
  - The Publisher, a person, sees the proposed release
  - The checkpointer stores the paused state with no time limit
  - An in-memory saver loses the pause when the process restarts
- **The graph continues only when the Publisher supplies a decision**

A Run Paused for the Publisher



The run moves on to release. With "no" it would stop here, and released stays False.

SpiralTrain developer courses

The interrupt Function

- `interrupt(payload)` **pauses the graph inside a node :**

```
from langgraph.types import interrupt

def publisher(state: Board):
    answer = interrupt({"notes": state["notes"], "options": ["approve", "edit", "reject"]})
    return {"action": answer["action"]}
```

- **A pause requires a checkpointer to store the thread state and the payload**
- `invoke(..., version="v2")` **returns the payload in** `out.interrupts[0].value`
- **Plain** `invoke` **returns a dict with the payload under** `"__interrupt__"`
- `out.value` **holds the state**
- `graph.get_state(cfg).next` **names the paused node**

demo01 · interrupts

SpiralTrain developer courses

Resuming with Command

- `Command(resume=value)` **continues the paused thread :**

```
from langgraph.types import Command

graph.invoke(Command(resume={"action": "approve"}), cfg, version="v2")
```

- **The paused node runs again from its first line :**
  - `interrupt(...)` now returns the resume value
  - Statements before `interrupt(...)` execute a second time
- **Side effects belong after the `interrupt(...)` call**

SpiralTrain developer courses

Re-entering the Paused Node

```
def publisher(state):

    answer = interrupt("Release this build?")

    notify_team(state["notes"])

    return {"released": answer == "yes"}
```

2
NODE ENTRIES

1
NOTES SENT


The fix : side effects go after the interrupt. The note then goes out once, after the approval.

SpiralTrain developer courses

Approval States

- **The Publisher’s choice picks the next state :**
  - Approve releases the notes unchanged
  - Edit replaces the notes, then releases
  - Reject returns feedback to the Coder
- **The run is in one of these states :**
  - Running : a node is working
  - Pending : the run waits at `interrupt`, and no process is needed
  - Resumed : `Command(resume=...)` has delivered the answer
  - Released : the build went out

Approve or Reject a Build



The new build passes the gate and reaches the Publisher again. The cycle runs until the answer is approve or edit.

SpiralTrain developer courses

Approve, Edit and Reject

- The Publisher node routes on the decision :

```
def publisher(state: Board) -> Command[Literal["release", "coder"]]:
    answer = interrupt({"notes": state["notes"], "options": ["approve", "edit", "reject"]})
    if answer["action"] == "approve":
        return Command(goto="release")
    if answer["action"] == "edit":
        return Command(update={"notes": answer["text"]}, goto="release")
    if answer["action"] == "reject":
        return Command(update={"feedback": answer["text"]}, goto="coder")
```

- `Command(update=..., goto=...)` updates state and routes in one return
- Edit replaces the notes without a model call
- Reject passes the Publisher’s notes to `coder` for a rewrite

demo01b · approve-edit-reject

SpiralTrain developer courses

Several Interrupts in One Step

- **Two `interrupt` calls in one node pause one after the other :**
  - LangGraph matches resume values to calls by their order
  - The order of the calls must not change between runs
- **Parallel nodes can pause in the same step :**
  - `out.interrupts` holds one `Interrupt` per node, each with its own `id`
  - The resume value maps each `id` to its reply :

```
replies = {item.id: f"approved {item.value['check']}" for item in out.interrupts}
checks.invoke(Command(resume=replies), check_cfg, version="v2")
```

- **One `id` per resume also works**
- **Finished siblings do not run again**

demo01c · several-interrupts

SpiralTrain developer courses

Interrupts in Subgraphs

- A child graph compiles without a checkpointer and mounts as a node
- The parent’s checkpointer stores the child’s state
- An interrupt in the child reaches the parent caller :
  - `parent.invoke(...)` returns it in `out.interrupts`
  - `parent.get_state(cfg, subgraphs=True)` shows the paused child node
- Resuming the parent thread delivers the reply to the child
- A release team subgraph can ask the Publisher while the crew waits above it

demo02 · interrupts-in-multi-agent

SpiralTrain developer courses

Interrupts in Subagents

- **A subagent tool can invoke a child graph that pauses :**
  - The Producer calls the release specialist as a tool
  - The child graph reaches `interrupt` and the pause reaches the Producer
  - The Producer's graph is paused in its `tools` node
- **Resuming the Producer runs the tool function again :**
  - Code before the child invocation executes a second time
  - The child receives the reply and the tool returns its `ToolMessage`
- **Bus depot demo : two executions of the tool function for one tool call**

`demo02b · in-a-subagent`

SpiralTrain developer courses

Human-in-the-Loop Middleware

- `HumanInTheLoopMiddleware` **names the tools that need approval :**

```
from langchain.agents.middleware import HumanInTheLoopMiddleware

policy = HumanInTheLoopMiddleware(interrupt_on={
    "publish_build": {"allowed_decisions": ["approve", "edit", "reject"]}
})
agent = create_agent(llm, tools=[publish_build], middleware=[policy],
                     checkpointer=InMemorySaver())
```

- **A call to a listed tool pauses before the tool runs**
- **Tools missing from** `interrupt_on` **run without a pause**

Gating Agent Actions

- **The interrupt payload holds `action_requests` and `review_configs`**
- **Each action request has the tool `name` and the model's `args`**
- **`Command(resume={"decisions": [...]})` returns one decision per request**
- **Each decision has a type :**
  - `approve` runs the tool with the model's arguments
  - `edit` runs it with `edited_action["args"]`, such as another version number
  - `reject` returns an error `ToolMessage` and the tool does not run
  - `respond` returns the reviewer's text as the tool result, without running the tool
- **Bus depot demo : quantity 2 on approve, quantity 1 after the edit, nothing on reject**

SpiralTrain developer courses

Per-Call Approval

- **LangChain 1.4.6 adds `interrupt_mode="per_call"` :**

```
gate = HumanInTheLoopMiddleware(interrupt_on={"publish_build": True},
                                interrupt_mode="per_call")
```

- **Batched mode raises one interrupt per model turn ; nothing runs until every decision arrives**
- **Per-call mode raises one interrupt per gated call :**
  - The resume maps each interrupt `id` to one decision
  - An invalid answer raises `ValidationError` and is not saved
  - An approved call runs while the others still wait

demo03b · per-call-approval

SpiralTrain developer courses

Two Layers of Approval

- **The prompt shapes what the model proposes :**
  - A system prompt can say "After rejection, stop without retrying"
  - A prompt can ask the model to propose before a hard-to-reverse action
- **`interrupt_on` makes the pause mandatory :**
  - The middleware gates the tool, whatever the prompt says
  - A scripted model with no prompt still pauses on every gated call
- **Each layer covers a gap in the other :**
  - The gate cannot keep a model from retrying a rejected action
  - The prompt cannot stop a call the model makes anyway

SpiralTrain developer courses

Loop Detection in Graphs

- **A cycle in a graph can run without making progress :**
  - The Coder chases a wrong diagnosis while the same test keeps failing
  - Two agents keep reversing each other’s changes
- **`recursion_limit` caps the supersteps, the rounds of node execution, in one run :**
  - Exceeding it raises `GraphRecursionError`
  - The run ends in an error, with no route to a person
- **A progress check in graph state stops a stalled run earlier**

SpiralTrain developer courses


A Watchdog Node

- A watchdog node counts rounds that bring no new evidence :

```
def watchdog(state: FixLoop):
    stalled = state["stalled"] + 1 if state["failing"] == state["previous"] else 0
    stop = stalled >= 2 or state["attempts"] >= 4
    return {"previous": state["failing"], "stalled": stalled,
            "status": "ask the Producer" if stop else "continue"}
```

- The watchdog runs after each round of the fix loop
- Two rounds on the same failing test, or four attempts, send the run to the Producer
- The run stops before it reaches `recursion_limit`
- Bus depot demo : the watchdog routed a stalled diagnosis to manual review on turn 2

A Watchdog in the Fix Loop



The run leaves the loop with a clear reason. A build that fails does not ship, and a person looks at it.

SpiralTrain developer courses

Repeated Tool Calls

- A model can repeat the same tool call on consecutive turns
- A signature `(name, sorted_args)` identifies a repeated call
- A guard node checks each call before it reaches the database :
  - The first read runs and stores its signature in `state["seen"]`
  - A repeat returns an error `ToolMessage` and does not run
- A repeat goes to a `stop` node, which ends the run with a manual-review error

demo04b · repeated-tool-calls

SpiralTrain developer courses

Retry Strategies and Backoff

- `RetryPolicy` **from module 04 retries a node on a transient exception, a failure that may pass by itself :**
  - Retry a timeout or an unavailable asset store
  - Fail a validation error at once ; `retry_on` selects the exceptions
- **Backoff spaces the attempts :**
  - `initial_interval` sets the first wait
  - `backoff_factor` multiplies the wait after each failure
  - `max_interval` caps the wait
  - `jitter` adds a random offset so workers do not retry in step
- **Inside** `create_agent` **,** `ToolRetryMiddleware` **retries a failing tool call**

demo05 · retries-and-fallbacks

Backoff between Attempts



jitter adds a random offset to each wait, so the attempts spread out over time.

SpiralTrain developer courses

Fallback Chains

- `with_fallbacks` **tries each runnable in turn on a listed exception :**

```
chain = RunnableLambda(live).with_fallbacks(
    [RunnableLambda(snapshot), RunnableLambda(manual)],
    exceptions_to_handle=(ConnectionError, LookupError)
)
```

- **Each tier has less authority than the one before :**
  - `live` reads the asset store and may clear a sprite for release
  - `snapshot` reads a cached copy and marks the answer as possibly stale
  - `manual` asks a person to check
- **A fallback answer states its source and clears nothing for release**
- **In a graph, module 04's `error_handler` with `Command(goto=...)` gives the same tiers**

demo05b · fallback-chain

SpiralTrain developer courses

Subgraphs and Composition

- **A subgraph lets one team build and test one stage :**
  - The design team owns the pitch workflow
  - The test team owns the rule and bot workflow
- **A compiled child graph mounts as a node in the parent :**
  - Keys in both schemas pass between parent and child
  - A wrapper function maps state when the child has its own schema
- **Each child graph can be tested and traced on its own**
- **Bus depot demo : a lookup workflow and a report workflow**

demo06 · composition-and-durability

SpiralTrain developer courses

Conditional Branching at Scale

- **A studio with many teams needs many branches :**
  - An `if/elif` chain in a router grows with every team
  - A routing table keeps the rules apart from the nodes
- `add_conditional_edges` **maps each team to a node via** `path_map` **:**

```
routes = {"puzzle": "puzzle_team", "arcade": "arcade_team", "racing": "racing_team"}
path_map = {name: name for name in set(routes.values()) | {"manual"}}
branching.add_conditional_edges("classify", lambda s: s["team"], path_map)
```

- **An unknown genre routes to the** `manual` **queue**
- **Bus depot demo :** `F-CE-110` **routes to** `electric`


demo06b · branching-at-scale

SpiralTrain developer courses

Durable Execution

- **Durable execution saves the project board after every step**
- **A crash at the Tester restarts at the Tester**
- `durability` **sets when the save is written :**
  - `"async"`, the default : while the next step runs
  - `"sync"` : before the next step starts
  - `"exit"` : only when the run ends
- **A crash during the Tester leaves the boards saved after Designer and Coder on disk**
- **Their model calls are not paid twice, because Designer and Coder do not run again**

A Crash at the Tester



The run continues to the gate. A checkpoint cannot undo a write to the outside world made before the crash.

SpiralTrain developer courses

Resuming After a Crash

- **A checkpointer preserves completed work before a node crashes :**

```
with SqliteSaver.from_conn_string("studio-checkpoints.sqlite") as saver:
    running = durable_builder().compile(checkpointer=saver)
    # Node 'coder' succeeds, node 'tester' raises RuntimeError
    running.invoke(initial, crash_cfg, durability="sync")

with SqliteSaver.from_conn_string("studio-checkpoints.sqlite") as saver:
    restarted = durable_builder().compile(checkpointer=saver)
    recovered = restarted.invoke(None, crash_cfg, durability="sync")
```

- `invoke(None, cfg)` **runs only** `tester` **; the Coder's work is not repeated**
- **Bus depot demo :** `prepare` **and** `finish`

demo06c · resuming-after-a-crash

SpiralTrain developer courses

Graceful Workflow Drain

- **A killed worker can stop in the middle of a node**
- **A drain stops a run between nodes, for instance before a deploy**
- **`RunControl` from `langgraph.runtime` provides it :**
  - A signal handler or a node calls `request_drain(reason)`
  - The running node finishes and its checkpoint is saved
  - The run raises `GraphDrained` before the next node starts
- **`invoke(None, cfg)` on a new worker runs the remaining nodes**

SpiralTrain developer courses

Summary : Advanced Workflows

- `interrupt` pauses a node ; `Command(resume=...)` supplies the decision
- A paused node runs again from its first line on resume
- Interrupts in subgraphs and subagent tools reach the parent caller
- `HumanInTheLoopMiddleware` pauses calls to the tools it lists, per turn or per call
- A watchdog node stops a stalled run ; a guard blocks a repeated call
- `RetryPolicy` retries with backoff ; `with_fallbacks` falls back by tier
- Subgraphs compose workflows ; a routing table maps each team to a node
- After a crash or a drain, `invoke(None, cfg)` restarts at the first unfinished node

exercise07 · Approval in a Subagent

Deep Agents

From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications

What is an agent harness?
A harness on a game maker
Framework, runtime, harness
The agent loop
A todo list
Files in state
A task tool
create_deep_agent
The default prompt
Planning with write_todos
The virtual filesystem
Offloading large results
State backend
Filesystem backend
Store backend
Composite backend
Permissions
The interpreter
Interpreter wiring
Interpreter limits
A local shell
Symlinks and middleware overrides
Memory in AGENTS.md
Skills
Tools bound to skills
Dict subagents
CompiledSubAgent
Fork mode
Fork cost on one question
The general-purpose subagent
Dynamic subagents
A fan-out script
Recursive language models
RLM harness families
Orchestration shapes
Telling an orchestrator when to delegate
A cap on delegation
Delegation measured on gpt-6-luna
interrupt_on
Summarisation
Context limits
State across context windows
Profiles
Deep Agents and the patterns
The Claude Agent SDK
Codex
Managed Deep Agents v0.10
The Academy course
Summary : Deep Agents


SpiralTrain developer courses

What is an agent harness?

- **An agent is a model calling tools in a loop until the task is done**
- **A harness is all the code around that loop :**
  - It runs the tools, keeps the files, trims the context and stops the run
  - The model still chooses the next tool call
- `create_agent` **from module 04 is a small harness on the LangGraph runtime**
- **Deep Agents is a larger harness on** `create_agent` **:**
  - It adds a todo list, files, subagents, skills, memory and context limits
  - The caller still supplies the task, the tools and the permissions

SpiralTrain developer courses

What a harness adds



All of this is the harness. The model in the middle still chooses every tool call.

A harness on a game maker

	Solo agent	Planner, generator, evaluator
Time	20 minutes	6 hours
Cost	$9	$200
Result	Entities appear, nothing responds to input	The entity moves and the game plays

- **Anthropic built a retro game maker both ways :**
  - The planner turns a prompt of a few sentences into a full spec
  - The generator builds the app
  - The evaluator clicks through the running app with Playwright and grades it
- **The harness run still had a flaw : a large wall blocked the character**

Framework, runtime, harness

- **Three layers sit under one Deep Agent :**
  - LangGraph, the runtime : runs the steps, saves checkpoints, keeps the store
  - LangChain, the framework : the model interface, tools and agent middleware
  - Deep Agents, the harness : files, the `task` tool and the rules for context
- **Middleware is code that runs around each model call or tool call**
- **The middleware stack implements the patterns of module 05**
- **The course pins `deepagents` 0.7.30, on `langchain` 1.4.6 and `langgraph` 1.2.17**

SpiralTrain developer courses

A long build at Comet Arcade


```
producer = create_deep_agent(
    model=llm, tools=[run_game_tests, bot_tick_log],
    subagents=[coder, artist],
    memory=["/AGENTS.md"], skills=["/skills/"],
    middleware=[TodoListMiddleware()],
    name="producer", system_prompt=PRODUCER)
```



- The Producer takes one brief and plans the build
- The Artist writes a theme, the Coder writes the logic
- The harness runs real tests and a bot, and the model reads the result
- 6 of 6 builds passed on `openai/gpt-6-luna`, 20 to 31 model calls, about $0.02 each

SpiralTrain developer courses

The build call by call



Every call sends the context again. The 28 calls add up to 165,307 input tokens, about $0.02 at list price, in 92 seconds.

SpiralTrain developer courses

The agent loop

```
plain = create_agent(llm, tools=[part_stock])
result = plain.invoke(ask(STOCK_TASK), LIMIT)
```

- **The notebooks of this module run on Veenhaven Bus, a bus company with a parts store and service manuals**
- **The model asks for a tool, our code runs it, and the model reads the result**
- **One stock lookup in demo01, on `openai/gpt-6-luna` :**
  - `part_stock` ran once
  - 2 model calls, 194 input tokens, 45 output tokens
  - The answer named 6 fans at Rietpoort
- **The callback recorded 0 malformed tool calls**

SpiralTrain developer courses

A todo list

```
planned = create_agent(
    llm, tools=[part_stock], middleware=[TodoListMiddleware()])
```

- `TodoListMiddleware` **adds the tool** `write_todos`
- **Each call sends the full list, and every item has a status**
- **The Veenhaven stock lookup in demo01b :**
  - The agent wrote one item, called `part_stock`, then marked it completed
  - The middleware does not enforce that order
- **The list costs context on this small lookup :**
  - 4 calls and 5502 input tokens with the list
  - 2 calls and 194 input tokens without it

A todo list in a long build

SpiralTrain developer courses

PENDING

IN_PROGRESS

COMPLETED

- [x] Read twist rules and choose a survival-focused twist
- [x] Have the artist create the game theme
- [x] Have the coder implement gameplay with the selected twist
- [x] Run twist tests and fix failures if needed
- [x] Playtest bot games and save three ending summaries

MODEL CALL **27** `bot_tick_log` `read_file × 3` `grep × 3` `/build/playtest.md`

All five are ticked. A tick is the agent's own claim ; the test report is the evidence.

SpiralTrain developer courses

Files in state

```
class ScratchState(AgentState):
    files: Annotated[dict[str, str], merge_files]
```

- `files` is one more key in the graph state
- A reducer that merges dicts lets two tools write without losing a file
- `write_note` returns a short confirmation :
  - The note goes under `files`
  - The message list keeps only the confirmation
- The Veenhaven lookup in demo01c saved `/stock.md` and answered 6 fans at Rietpoort
- 3 model calls, 4160 input tokens, 0 malformed tool calls

SpiralTrain developer courses

A task tool

```python
@tool
def task(description: str) -> str:
    """Delegate a self-contained Veenhaven Bus parts lookup to the parts worker."""
    result = worker.invoke(ask(description), LIMIT)
    return answer(result)
```

- The worker is a second `create_agent` with its own message list
- The parent receives one sentence
- In demo01d the worker has `part_stock`, and the parent has `task` and `write_note`
- The worker's tool results stay in the worker's messages
- 5 model calls, 4450 input tokens, 0 malformed tool calls

SpiralTrain developer courses

create_deep_agent

```
packaged = create_deep_agent(model=llm, tools=[part_stock],
    system_prompt="Use the parts tool. Save a short finding in /stock.md, then answer.")
```

- **One call builds the parts of demo01 and more**
- **Default tools in 0.7.30 :**
  - Files : `ls` , `read_file` , `write_file` , `edit_file` , `delete` , `glob` , `grep`
  - Shell and delegation : `execute` and `task`
- **The Veenhaven lookup in demo02 :**
  - `part_stock` , then `write_file` for `/stock.md`
  - 3 model calls, 6269 input tokens, 88 output tokens

SpiralTrain developer courses

The default prompt

- `write_todos` **is absent until** `TodoListMiddleware` **is passed**
- **Without** `system_prompt` **and a harness profile, our own prompt text is empty :**
  - `BASE_AGENT_PROMPT` has been deprecated since 0.7.0
  - Tool schemas and middleware fragments still reach the model
- **A harness profile is a set of defaults for one model name**
- **In demo02 the one-line prompt asks for the file :**
  - No `todos` key was written
  - The callback recorded 0 malformed tool calls

SpiralTrain developer courses

Planning with write_todos

```
planner = create_deep_agent(
    model=llm, tools=[part_stock], middleware=[TodoListMiddleware()])
```

- **Planning is opt-in on this pin**
- **Three Codex harness profiles are the built-in exception :**
  - `openai:gpt-5.1-codex` , `openai:gpt-5.2-codex` , `openai:gpt-5.3-codex`
  - Each profile adds `TodoListMiddleware` because its prompt mentions todos
- `openai/gpt-6-luna` **matches no harness profile, so the demo passes the middleware itself**
- **Only the tool result confirms a completed item**
- **The Veenhaven lookup in demo02b : 4 calls, 13282 input tokens, 0 malformed tool calls**

The virtual filesystem

```
inputs = {**ask("Read /manual.md and report the first action for F-CE-110."),
          "files": {"/manual.md": create_file_data(page)}}
```

- The agent sees paths and file tools, and a backend decides where the bytes are stored
- The default backend keeps files in the graph state and writes nothing to disk
- The notebook directory has no `manual.md` after the read
- `read_file` takes `offset` and `limit` to read a window of lines
- The seeded page in demo03 is the Veenhaven CE-12 error-code manual

SpiralTrain developer courses

Offloading large results

- A tool result over 20000 tokens moves to a file ; tokens are counted as characters divided by 4
- The model receives the path and a short preview
- The Veenhaven demo lowers `tool_token_limit_before_evict` to 600 :
  - 31 manuals are 18795 characters on disk
  - The tool result was 19626 characters and went to `/large_tool_results/`
  - The model saw the path and a preview, then reported 2 sources
- That answer is wrong because the preview is too short to count the files

demo03b · offloading-large-results

A large result moves to a file

CONTEXT OF THE NEXT MODEL CALL

FILES OF THIS RUN, IN THE GRAPH STATE


/AGENTS.md

/kit/rules.md logic.js theme.json twists.md

/build/logic.js theme.json

/large_tool_results/call_Hh… 289,213 characters

1091 game 2 tick 195 head 22,2 dir down	1092 game 2 tick 196 head 23,2 dir right
1121 game 2 tick 225 head 13,11 dir down	1976 game 2 over : score 66, self
3004 game 3 over : score 65, self	896 game 1 over : score 56, self



SECOND CALL, INPUT TOKENS



One run of a shorter log, with this limit and with eviction off : the next call holds 2,516 tokens, or 73,810.

SpiralTrain developer courses

State backend

```
state_agent = create_deep_agent(
    model=llm, backend=StateBackend(), checkpointer=InMemorySaver())
```

- `StateBackend` is the default
- Files for a thread are stored in that thread's graph state
- The checkpointer returns them on the next turn of the same thread
- A second `thread_id` starts with no files
- `InMemorySaver` loses its data when the process ends

demo04 · backends

SpiralTrain developer courses

Filesystem backend

```
disk = FilesystemBackend(root_dir=disk_root, virtual_mode=True)
```

- `virtual_mode=True` **maps** `/note.md` **to a file under** `root_dir`
- **A path containing** `..`**, or one that resolves outside the root, raises** `ValueError` **:**
  - `..` gives `Path traversal not allowed`
  - An absolute host path gives `... outside root directory`
- `~/x` **is an ordinary name under the root, and reads as not found**
- **These rules cover the file tools ; a shell command is outside them, as demo05 shows**

Store backend

```
shared = StoreBackend(
    store=store, namespace=lambda _runtime: ("veen-service", "user-a"))
```

- A store keeps a file after its conversation ends, and other threads can read it
- This pin requires the `namespace` callback, which names the folder in the store
- Later invokes under one namespace see the files
- A second namespace reads the same path as missing
- `InMemoryStore` keeps the rows until the process exits
- A durable store would keep them across processes ; this demo starts none

demo04c · store

SpiralTrain developer courses


Composite backend

```
mixed = CompositeBackend(
    default=StateBackend(), routes={"/memory/": shared})
```

- One agent uses several backends, and the path of each file selects one
- The longest matching prefix selects the backend
- `/memory/policy.md` is stored on the route as `/policy.md`
- A path with no matching prefix stays on the default, here state
- The file tools apply `permissions` ; a direct backend call skips them

demo04d · composite

A path chooses the backend



The read of /memory/style.md reaches the store : "Danger is warm." The style guide is kept after the game.

SpiralTrain developer courses

Permissions

```
rules = [
    FilesystemPermission(operations=["write"], paths=["/reports/**"], mode="allow"),
    FilesystemPermission(operations=["write"], paths=["/**"], mode="deny"),
]
```

- The rules are read from the top, and the first match wins
- `mode` is `allow`, `deny` or `interrupt`
- An operation is `read` or `write`
- No matching rule means the call proceeds
- A subagent inherits the list, or replaces it with its own `permissions`

demo05 · permissions-and-execution

The first matching rule

WRITE
/build/logic.js

RULES, READ FROM THE TOP

```
operations=["write"]
paths=["/**"]
```
deny

```
operations=["write"]
paths=["/build/**"]
```
allow

deny

Swap the two rules and the same write is denied. The order of the list decides.

The interpreter

```
analyst = create_deep_agent(model=llm, middleware=[interpreter])
```

- `CodeInterpreterMiddleware` **adds one tool,** `eval` **: the model writes JavaScript and QuickJS runs it**
- **Rows load into the script through an allowed tool, and only the result returns to the model**
- **The Veenhaven ticket question in demo05b :**
  - The script filtered and summed the rows of depot D01
  - The result was 4 tickets and 7.5 hours, and a Python check agreed
- **QuickJS has no built-in host filesystem, network, process or clock API**
- **An exposed tool still runs with the host's permissions**
- **Interpreters are a beta feature**

Interpreter wiring

```
from langchain_quickjs import CodeInterpreterMiddleware
interpreter = CodeInterpreterMiddleware(
    ptc=[ticket_rows], subagents=False, mode="turn",
    memory_limit=16 * 1024 * 1024, timeout=2,
    max_ptc_calls=2, max_result_chars=1200)
```

- PTC, programmatic tool calling : a script calls a Python tool as `tools.ticketRows({})`
- `ptc` is the list of tools a script may call
- The import is from `langchain_quickjs`
- The raw rows reach the script without passing through a parent tool message

SpiralTrain developer courses

Interpreter limits

- **Limits apply to different parts of the run :**
  - `memory_limit` bounds the QuickJS heap
  - `timeout` counts VM execution time ; host calls can take longer
  - `max_ptc_calls` caps `tools.*` calls in one `eval`
  - `max_result_chars` truncates result and console output separately
- **REPL state persists by `mode` :**
  - `thread` across turns, `turn` within one turn, `call` for one invocation
- **PTC calls bypass per-tool parent approval :**
  - Gate `eval` or put approval in the called agent

SpiralTrain developer courses

A local shell

```
local = LocalShellBackend(
    root_dir=SHELL, virtual_mode=True, inherit_env=False)
```

- `execute` runs the host shell with `root_dir` as the working directory
- `virtual_mode` confines the file tools to that directory, and `execute` can still read and write outside it
- In demo05c the command `echo veenhaven` returned `veenhaven`, exit code 0
- `inherit_env=False` keeps the process environment, and its keys, out of the command
- `SHELL` is `notebooks/08-deep-agents/workspace/shell/`, gitignored with the rest of `workspace/`

demo05c · a-local-shell

SpiralTrain developer courses

Symlinks and middleware overrides

- **Since 0.7.25 a rule is matched against the path and its symlink target :**
  - Before, `FilesystemBackend` followed a symlink after the check
  - A link to a denied file could be read
- **`permissions=` goes to the harness's own `FilesystemMiddleware`**
- **A `FilesystemMiddleware` in `middleware=` replaces it by name :**
  - On 0.7.30 the replacement has no rules
  - The denied read returned `SECRET EXPORT`
  - Passing `_permissions=rules` to the replacement restored the deny
- **0.7.31 copies the rules over and needs `langchain-core` 1.7**

demo05d · an-override-and-its-rules

SpiralTrain developer courses

Memory in AGENTS.md

```
agent = create_deep_agent(model=llm, memory=["/AGENTS.md"])
```

- `AGENTS.md` holds standing rules for a project, in plain Markdown
- Each path is loaded at the start of the run and appended to the system prompt
- HTML comments are removed before the text goes in
- Several sources are joined in the order given
- Skill bodies stay out of that prompt until a skill is read or pinned
- The Veenhaven demo seeds one rule, the vest rule, and the answer names it

demo06 · memory-and-skills

SpiralTrain developer courses

Skills

```
name: safety-briefing
description: Use when asked for safety rules before a depot visit.
```

- A skill is a folder of instructions the agent loads when a task needs them
- `skills=["/skills/"]` scans child folders for `SKILL.md`
- The prompt receives the name and the description
- The instructions stay in the file until `read_file`
- `name` must match the folder : lower case, digits and single hyphens, at most 64 characters
- When two sources share a name, the later source wins
- Agent Skills is an open standard that more than 70 agent platforms have integrated

Memory and skills loading

SpiralTrain developer courses

ONE MODEL REQUEST

system prompt

You are the Coder at Comet Arcade ...

A game is one HTML file. Every game has a dark background and one warm danger colour. A comet is red or orange, never blue or grey.

`canvas-game` Use when writing or fixing the logic block of a canvas game.

tools

`read_file` `write_file` `edit_file` `play_bot`

messages

description of the job

Common mistakes : Removing the tail twice before the self hit check ...

BACKEND FILES

`/AGENTS.md`

195 characters

Studio rules for every run.

`/skills/canvas-game/SKILL.md`

1,057 characters

name, description

body : pure logic, state, common mistakes

A skill can also hold back a tool. With metadata.include_tools the tool joins the request once the skill is read.

SpiralTrain developer courses

Tools bound to skills

- **The 7 October 2026 skills change is in this pin :**
  - `metadata.include_tools` is a space-separated list of tool names
  - Those tools are passed to `SkillsMiddleware`
  - A listed tool stays off the model request until the skill is read or named in `pinned_skills`
- **`pinned_skills` on `invoke` appends each skill body, then clears the list**
- **Set `skills_metadata` to `None` and the next run reads the files again**

```
metadata:
  include_tools: order_fan
```

SpiralTrain developer courses

Dict subagents

```
parts = {"name": "parts", "description": "Looks up stock and location for one part number.",
         "system_prompt": "Use part_stock. Return the stock and location.", "tools": [part_stock]}
team = create_deep_agent(model=llm, subagents=[parts])  # the demo adds a system_prompt
```

- **A subagent is a dict : a name, a description, a prompt and tools**
- **The parent calls `task` with `description` and `subagent_type`**
- **The default `mode` is `isolated`, where the worker starts from the description alone**
- **A `general-purpose` subagent is added when the caller did not pass that name :**
  - It is offered the parent's tools
  - A harness profile can set `GeneralPurposeSubagentProfile(enabled=False)`

demo07 · subagents

SpiralTrain developer courses

A subagent with a clean context

Producer 6,516

- brief
- write_todos
- twists.md
- write_todos
- task artist
- write_todos
- task coder : one sentence

17,977 tokens in the worker

+187 in the parent

SHARED FILES `/kit/rules.md` `/kit/logic.js` `/skills/canvas-game/SKILL.md` `/build/logic.js`

The Coder spent 17,977 input tokens over 4 calls. The Producer's next call grew by 187.

SpiralTrain developer courses

CompiledSubAgent

```
compiled = {"name": "manuals-graph",
            "description": "A compiled agent for one bus error code.",
            "runnable": manuals_graph}
```

- A finished graph can be a worker without a rewrite
- `runnable` is any graph whose state includes `messages`
- The harness does not wrap it in filesystem, skills or summarisation middleware
- The parent receives the last assistant text, or `structured_response` as JSON when it is set
- `interrupt_on` from the parent is not copied onto this runnable

demo07b · compiled-subagent

SpiralTrain developer courses

Fork mode

```
forked = {"name": "manuals-fork",
          "description": "Continues this conversation and looks up the error already named.",
          "system_prompt": "Use fault_guidance on the error code in the conversation. Return the
first action.",
          "tools": [fault_guidance], "mode": "fork"}
```

- `mode="fork"` is experimental in 0.7.30
- The worker receives the parent messages, then the task description
- Its `system_prompt` is appended to the prompt it inherited
- A fork cannot declare `skills`, and a `task` call from a fork is refused

demo07c · fork-mode

Fork cost on one question

- **The same Veenhaven question went to a compiled worker and to this fork :**
  - Fork 8761 input tokens, compiled 4516, parent plus worker
  - The gap is the inherited history
- **Told to leave out the error code, the parent still put F-CE-110 in the description**
- **Both answers were to check the traction cooling fan**

The general-purpose subagent

- The built-in name is `general-purpose`
- The pin’s description offers research, file search and multi-step tasks
- It is inserted when no subagent uses that name
- `enabled=False` on `GeneralPurposeSubagentProfile` stops the insertion
- With no synchronous subagent left, `create_deep_agent` does not register `task`
- Async subagents use a different middleware and stay available either way

SpiralTrain developer courses

Dynamic subagents

- In a fan-out one task splits into many workers at once
- With dynamic subagents the agent writes that fan-out itself :
  - The workers are the subagents we configured
  - The model writes the JavaScript that dispatches them and combines the results
- The top-level `task` in a script takes a description and a `subagentType`
- Like the interpreter, this feature is in beta
- A Python loop in the application does the same with the count fixed by our code

demo08 · dynamic-subagents

SpiralTrain developer courses

An agent-written fan-out

```
const twists = ["golden", "wormhole", "shield", "clock"];
const results = await Promise.all(twists.map((twist) => task({
  description: `Create one ... twist named "${twist}"`,
  subagentType: "designer",
  responseSchema: { twist: string, pitch: string }
})));
JSON.stringify(results);
```

[...]

GOLDEN	Chase the golden fruit ...
WORMHOLE	Slither through a wormhole ...
SHIELD	Grab a shield ...
CLOCK	Race the clock ...

eval QuickJS runs the script

Producer tool messages : `eval`

The Producer receives one tool message from eval, with four pitches. 6 model calls, 16,577 input tokens, on Comet Arcade.

A fan-out script

```
const codes = ["F-CE-110", "F-CE-305"];
const schema = {type: "object", properties: {
  error_code: {type: "string"}, action: {type: "string"}
}, required: ["error_code", "action"]};
const found = await Promise.all(codes.map(code => task({
  description: "First action for " + code,
  subagentType: "manuals",
  responseSchema: schema
})));
JSON.stringify(found)
```

- `responseSchema` **returns structured values for dict subagents**
- `max_subagent_concurrency=2` **caps simultaneous dispatches per REPL**


SpiralTrain developer courses

Recursive language models

- **A recursive language model, or RLM, handles an input too long for one prompt :**
  - The input stays in a code environment as a variable
  - The root model writes code that looks at it and calls a model on the pieces
  - A piece that is still too long can be split again
- **Zhang, Kraska and Khattab, MIT CSAIL, arXiv 2512.24601**
- **On its tasks, the paper reports inputs on the order of 100 times the context window**
- **Dynamic subagents have the same shape : the script calls `task` on each piece**

demo08b · splitting-a-long-input


An oversized input split in code



The root reads the findings and answers. The logs themselves never entered its context.

SpiralTrain developer courses

Splitting manuals that fit in one prompt



These manuals fit in one prompt, so splitting them costs tokens. Splitting helps when an input is longer than the window.

SpiralTrain developer courses

RLM harness families

- **Zhang later describes two harness families :**
  - One keeps the trajectory in the prompt
  - One orchestrates with code and sub-calls
- **QuickJS loads the chunks through PTC and calls the same model as a reader :**
  - The root writes the dispatch script and receives compact findings
  - The complete chunks stay out of the root’s model requests
- **The largest Veenhaven root call was 5244 input tokens and the largest reader 2058**
- **This run shows one level of the idea, on a small corpus**

SpiralTrain developer courses

Orchestration shapes

- **Many units of work and a count known at run time fit a loop in code :**
  - Classify and act : one label selects one specialist
  - Fan-out and synthesise : one call per unit, then one combined answer
  - Adversarial verification : a second pass challenges the first
  - Generate and filter : keep the candidates that pass a check
  - Tournament : compare candidates and keep a winner
  - Loop until done : repeat until a condition, with an explicit cap
- **A handful of fixed roles stays a dict of subagents**

SpiralTrain developer courses

Telling an orchestrator when to delegate

- **An orchestrator can delegate too much, and every worker costs model calls**
- **Anthropic’s guidance for Claude Opus 5 offers two controls :**
  - A delegation policy in the prompt
  - A deterministic cap on how many agents launch
- **The policy is vendor text for Claude, quoted in the demo :**

```
Delegate to a subagent only for large tasks that are genuinely
independent and parallelizable [...] If one subagent can complete
the task, use one rather than several, and keep spawn counts low.
```

demo08c · delegation-policy

SpiralTrain developer courses

A cap on delegation

```
ToolCallLimitMiddleware(tool_name="task", run_limit=2)
```

- `ToolCallLimitMiddleware` counts the calls to one tool in a run
- demo08c allows 1 `task` call, demo08d allows 2
- A blocked call returns an error message, and the run continues
- The cap covers the parent's `task` calls ; it does not count inside a worker

SpiralTrain developer courses

Delegation measured on gpt-6-luna

Desk	Arm	`task` calls	Model calls	Input tokens	Complete
With bus tools	Any of the four, cap 1	0	2	4403 to 4555	3/3
Specialists only	None	2	6	11582	3/3
Specialists only	Policy	2	6	11669	2/3
Specialists only	Cap of 2	2	6	11557	2/3
Specialists only	Both	2	6	11633	2/3

- Veenhaven Bus desk, medians of three runs
- With bus tools the policy adds 152 input tokens and changes no median call count
- The largest run without controls : 5 `task` calls, 12 model calls, 21795 input tokens
- The cap held the largest capped run to 7 calls, and its blocked lookups left the stock out

`demo08d · delegation-with-specialists-only`

SpiralTrain developer courses

interrupt_on

```
gated = create_deep_agent(
    model=llm, interrupt_on={"write_file": True}, checkpointer=InMemorySaver())
gated.invoke(Command(resume={"decisions": [{"type": "approve"}]}), config, version="v2")
```

- The run stops before the named tool and waits for a human
- `HumanInTheLoopMiddleware` inside the harness makes that pause
- A decision is `approve`, `edit`, `reject` or `respond`
- The graph needs a checkpointer, and resume continues the same thread
- A dict subagent inherits the map unless it sets `interrupt_on` itself
- A `CompiledSubAgent` does not inherit it
- `FilesystemPermission` with `mode="interrupt"` builds the same pause for matching paths

demo09 · control

SpiralTrain developer courses

Summarisation

- **A long run can fill the context window, the limit on what one call can hold**
- **The default stack replaces old messages with a summary for the model :**
  - The old messages go to `/conversation_history/{session}.md`
  - `state["messages"]` keeps the original log
- **This model publishes no profile, so the default trigger is 170000 tokens and the last 6 messages stay**
- **The Veenhaven demo sets a trigger of 3 messages so one lookup crosses it**
- `compact_conversation` **comes from** `SummarizationToolMiddleware`**, which the default stack does not add**

demo09b · summarisation

Old messages move out of the request

NEXT MODEL REQUEST

- summary of messages 1 to 8
- tool · message 9
- ai · message 10
- tool · message 11
- ai · message 12
- tool · message 13
- ai · message 14

/CONVERSATION_HISTORY/SESSION.MD

message 1 | message 2 | message 3 | message 4

message 5 | message 6 | message 7 | message 8

STATE["MESSAGES"]



all 14, unchanged

state["messages"] keeps the original log. Only the request to the model is shorter, and the summary can lose details.

SpiralTrain developer courses

Context limits

- **Three mechanisms run before a full summary :**
  - A tool result over 20000 tokens is evicted to the filesystem
  - A human message over 50000 tokens is evicted the same way
  - Old `write_file` and `edit_file` arguments can be clipped at a lower threshold
- **The summary call uses the agent model**
- **Fraction triggers apply when `max_input_tokens` is on the model profile**
- **`openai/gpt-6-luna`, constructed as `ChatOpenAI` for this course, has `profile is None`**

SpiralTrain developer courses

State across context windows

- **A task longer than one context window keeps its state outside the window :**
  - Structured status, such as a test list, goes in a JSON file
  - Free-text progress notes go in a second file
  - Messages and graph state go in the checkpointer
- **Deep Agents has a place for each :**
  - File tools write to a backend ; a store or disk backend keeps files after the thread ends
  - `memory=["/AGENTS.md"]` reloads standing rules at the start of every run
  - Summarisation writes the old messages to a file
- **A fresh start is a new `thread_id` with a prompt that names the files to read first**
- **Anthropic’s guidance for Claude says a fresh window that re-reads the files can beat compaction, its name for summarisation**

SpiralTrain developer courses

Profiles

- **Profiles are a beta API in two registries :**
  - A provider profile changes how `resolve_model` builds the chat model
  - A harness profile changes prompts, tool visibility and extra middleware after that
- **Built-in harness keys include the three Codex specs and Claude Haiku 4.5, Sonnet 4.6 and Opus 4.7**
- **Lookup for our instance uses provider `openai` and identifier `openai/gpt-6-luna`**
- **With no matching key, the profile is empty :**
  - There is no base prompt and no system-prompt suffix
  - There are no excluded tools and no extra middleware
- **A deployment registers a profile to opt this model into planning or a shorter `task` list**

Deep Agents and the patterns

Harness feature	Module 05 pattern
`write_todos`	One agent ; the plan is state
Skills, `include_tools`	Skills, with tools scoped to the file
`task`, isolated	Subagents
`mode="fork"`	The worker sees the parent history
`CompiledSubAgent`	A custom workflow behind one tool
Fan-out in Python	A custom workflow ; the loop is code
`interrupt_on`	An approval gate on a tool

- **Each feature packages a pattern built by hand on Tuesday**
- **demo10 compares both builders on one Veenhaven desk question**

demo10 · deep-agent-or-graph

Graph against Deep Agent

Lines of builder code



Model calls



Input tokens



`both complete` 6 fans at Rietpoort ; check the traction cooling fan

Both answered 6 fans at Rietpoort and the cooling-fan check, and both completeness checks passed.

The Claude Agent SDK

- The Agent SDK runs Claude Code’s agent loop in the application’s process
- The library includes file tools, a shell, subagents, skills, memory, permissions, sessions, hooks and MCP
- Python and TypeScript are the supported libraries
- The Client SDK calls the Claude API, and the application writes the tool loop
- Managed Agents run a hosted harness, with a cloud sandbox or a self-hosted sandbox
- This course runs the Deep Agents harness in-process, on LangGraph, with the course model

SpiralTrain developer courses

Codex

- **The Codex SDK starts and resumes a local Codex thread**
- **TypeScript package `@openai/codex-sdk` requires Node.js 18 or later**
- **Python package `openai-codex` talks to the local app server over JSON-RPC**
- **`thread.run` continues the thread ; a thread id resumes an older one**
- **Sandbox presets on the Python SDK :**
  - `read_only` reads files
  - `workspace_write` writes inside the workspace and configured roots
  - `full_access` runs without those filesystem restrictions
- **Deep Agents keeps the loop in-process and takes the model the caller built**

SpiralTrain developer courses

Managed Deep Agents v0.10

- **Managed Deep Agents runs this harness as a hosted service on LangSmith Cloud, in public beta**
- **Version 0.10, 29 October 2026, adds two features :**
  - Browser use : `browser_handoff` gives the user the window for a sign-in and keeps the password out of messages and traces
  - Async subagents : `"async": True` runs a worker on its own thread, and the parent keeps talking until it reports back
- **Version 0.10 removes `connectors.mcp()` , the `connectors/` layout and the sandbox `scope` option ; MCP servers go in `tools/mcp.py`**
- **The Plus plan is $39 per seat per month with 1 free small serverless deployment**
- **Deployment is not on the Developer plan**

SpiralTrain developer courses

The Academy course

- Introduction to Deep Agents, from LangChain Academy, is a free follow-up
- Six modules cover building, the execution environment, context, delegation, a capstone with async subagents and local deployment, and Managed Deep Agents
- The public repo at `github.com/langchain-ai/lca-deepagents` has no licence
- This course keeps its own wording and its own examples, Comet Arcade and Veenhaven Bus
- Their code pin is `deepagents` 0.7.0 ; this course is on 0.7.30

SpiralTrain developer courses

Summary : Deep Agents

- A harness packages a todo list, files, skills, memory, subagents and context limits on `create_agent`
- Version 0.7 leaves the base prompt and `write_todos` to the caller, unless a profile adds them
- A large tool result moves to a file, and the model keeps a path and a preview
- File tools, permission rules and `LocalShellBackend` are the execution environment in this pin
- Skills load when needed ; `include_tools` hides a tool until the skill is in context
- Isolated subagents see the task ; fork mode also sees the parent messages
- A long input can be split in code ; `interrupt_on` and summarisation bound a long run

exercise08 · A Deep Agent

exercise09 · Offload and Measure

p. 408

Production Deployment


From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications

Production Agent Services
LangGraph API
Agent Server Resources
langgraph.json
langgraph dev and Studio
Threads and Runs in Practice
Streaming to Clients
Stream Modes and Subgraphs
Double-Texting and Concurrency
Persistence Backends
Checkpoint Storage and TTLs
DeltaChannel
Async Subagents
Async Task Lifecycle
Co-deployed Graphs
Firstmate Orchestration
A2A on Agent Server
Deployment Options
Managed Deep Agents
Scaling Strategies
Evaluating a Multi-Agent System
What the Comet Arcade Evals Found
Limits of the Evidence
Final Answer Evaluation
Trajectory Match
Trajectory Match Modes
Trajectory Judge
Specialist and System Evaluation
pass@k and pass^k
A LangSmith Experiment
Monitoring
Cost Optimisation
Budget Stops
Error Return Channel
Summary : Production Deployment

Production Agent Services

- **A notebook serves one person, and its memory ends with the kernel**
- **A service has more duties :**
  - Any program can start a build over HTTP
  - The project board is still there after the server restarts
  - A score shows whether a change made the crew better
  - A budget stops a run that spends too much
- **Agent Server is the program that serves LangGraph graphs and Deep Agents over HTTP**
- **The Comet Arcade crew runs on it in this module ; demos 01 to 08 serve Veenhaven Bus graphs**

From Laptop to Agent Server



The client code stays. Its URL changes, and a second worker takes more runs at once.

SpiralTrain developer courses

LangGraph API

- **An API is a set of URLs that a program can call. Agent Server offers the LangGraph API**
- **Its three resources :**
  - Assistant : a graph with its default settings, such as the `crew` graph
  - Thread : one saved project board, kept across runs
  - Run : one execution of an assistant on a thread
- **`langgraph dev`, a self-hosted server and LangSmith Deployment offer the same API**
- **Clients call it through the `langgraph-sdk` package**
- **Studio is a web page that calls this API and draws the graph**

Agent Server Resources

- An assistant binds a `graph_id` from `langgraph.json` to runtime defaults
- A thread holds checkpointed state across runs
- A run applies input to an assistant on a thread, and returns a status and results
- Background runs support join, cancel and stream
- Follow-ups reuse the same thread id, so earlier messages stay available

SpiralTrain developer courses

langgraph.json

- One project file tells the server which graphs to load. For the Comet Arcade crew :

```
{
  "dependencies": ["."],
  "graphs": {
    "crew": "./crew.py:crew"
  },
  "env": "../../../.env"
}
```

- `crew` is the name clients use ; `./crew.py:crew` is the compiled graph in that file
- The server adds its own checkpointer, so the graph compiles without one
- demo01 registers three Veenhaven Bus graphs the same way

langgraph dev and Studio

- One command serves the project on the laptop :

```
uv run langgraph dev --no-browser --port 2134
```

- Studio opens against that address and draws the crew as a graph
- EU accounts add `--studio-url https://eu.smith.langchain.com`
- `/ok` answers once the server is ready for its first client
- `--n-jobs-per-worker` sets how many runs can work at once

demo01b · langgraph-dev-and-studio

SpiralTrain developer courses

Threads and Runs in Practice

- `assistants.search` **lists the served graphs**
- `threads.create` **opens a thread and returns its id**
- `runs.wait` **starts a run and returns when it finishes**
- `threads.get_state` **reads the saved board ;** `runs.list` **lists the runs on a thread**
- **A second run on the same thread sees what the first one saved :**
  - In demo01, on the Veenhaven Bus stock graph, a follow-up recalls part CE-CF-02 without a new lookup


`demo01c · threads-and-runs`

SpiralTrain developer courses

Streaming to Clients

- A build takes about 25 seconds, and a client can show progress during that time
- Server-sent events keep one HTTP response open and deliver each event as it happens
- A stream mode selects the events :
  - `updates` : what each node wrote when it finished
  - `messages` or `messages-tuple` : model text, piece by piece, with the node that wrote it
  - `values` : the full state after each step

Streaming a Build



After 25.3 seconds the Tester reports, and runs.wait returns. Both clients took the same time, and one could show progress.

SpiralTrain developer courses

Stream Modes and Subgraphs

- `langgraph_node` names the node that produced each message chunk
- Tool results arrive as message events too
- Clients keep AI chunks from the `model` node for text shown to a user
- `stream_subgraphs=True` adds events from nested graphs
- A list of stream modes requests tokens and node updates together
- `threads.get_state` reads the saved state after the stream ends

SpiralTrain developer courses

Double-Texting and Concurrency

- **Double-texting : a second request arrives while a run is busy on that thread**
- `multitask_strategy` **chooses what happens :**
  - `reject` returns HTTP 409 and the first run continues
  - `enqueue` lets the first run finish, then starts the second ; it is the default
  - `interrupt` halts the first run and keeps its progress
  - `rollback` halts the first run and reverts its progress
- **Provider quotas and worker capacity both limit how many runs can work at once**

demo02b · double-texting

Persistence Backends

- Production Agent Server keeps thread checkpoints in a database
- PostgreSQL is the default production checkpoint backend
- Local `langgraph dev` keeps development files under `.langgraph_api`
- How long threads are kept follows product and compliance requirements
- A Store holds memory across threads, such as the studio style guide

Checkpoint Storage and TTLs

- Shared checkpoint storage lets several worker processes serve one thread
- A TTL, a time to live, deletes expired threads or prunes older checkpoints
- Backups and access controls apply to thread data as to any customer store
- Development storage is kept across a local restart and is not a production database

demo02c · persistence-across-restarts

DeltaChannel

- `DeltaChannel` is beta in LangGraph 1.2.17
- A list that grows by a reducer, such as the bug list, is expensive to save whole at every step
- Checkpoints store each write, with a full snapshot at intervals
- Replay applies earlier writes to rebuild the list
- Reducers must be deterministic and give the same result however writes are batched


SpiralTrain developer courses

Async Subagents

- An async subagent is a graph that works in the background while its parent keeps going
- The Producer can start a long bot test, answer the Publisher and collect the score later
- `AsyncSubAgent` adds these tools to the parent :
  - `start_async_task` , `check_async_task` , `update_async_task`
  - `cancel_async_task` , `list_async_tasks`
- A target graph on the same server omits `url` ; a remote one passes `url` and `headers`

demo03 · async-subagents

A Background Bot Test



demo03 on Veenhaven Bus ended like this : one task finished with success, one was stopped with cancel_async_task, and list_async_tasks showed both.

Async Task Lifecycle

- `start_async_task` launches a background run and returns a task id
- `check_async_task` reads current status and results
- `update_async_task` interrupts the current run and starts a new run on its thread
- `cancel_async_task` stops a held or running task
- `list_async_tasks` reports tracked tasks, optionally filtered by status
- The task id is the worker's thread id ; `runs.join(task_id, run_id)` waits on it
- Updates keep the task id and replace the run id

Co-deployed Graphs

- Supervisor and worker graphs share one `langgraph.json`
- The supervisor is a Deep Agent with an `AsyncSubAgent` entry
- The worker is a compiled graph with a `messages` key
- The parent addresses the worker by `graph_id`
- In demo03 the Veenhaven Bus supervisor delegates stock research to the `researcher` graph

SpiralTrain developer courses

Firstmate Orchestration

- `firstmate` coordinates coding agents through processes and files
- One first mate dispatches each task to a crewmate in its own git worktree
- The first mate watches, steers and cancels those tasks
- State sits on disk, and a watcher wakes the first mate on events
- Separate worktrees keep each agent’s changes apart

SpiralTrain developer courses

A2A on Agent Server

- Every assistant exposes `/a2a/{assistant_id}`, where `assistant_id` is a UUID
- The agent card is at `/.well-known/agent-card.json?assistant_id=...`
- The binding is A2A v1.0 JSON-RPC, with send, stream, get, cancel and list tasks
- `contextId` identifies the Agent Server thread ; state needs a `messages` key
- `assistants.search` resolves graph names to assistant UUIDs
- Task history returns tool results to the caller as a `data` part
- MCP, A2A, Agent Skills and AGENTS.md all belong to one neutral body, the Agentic AI Foundation

demo04 · a2a-on-agent-server

Deployment Options

- **LangSmith Deployment lists four kinds of hosting :**
  - Cloud : LangChain hosts the control plane, the data plane and the databases
  - Hybrid : LangChain’s control plane, Agent Servers in your infrastructure
  - Self-hosted with control plane : both planes in your infrastructure
  - Standalone server : Agent Server containers without a control plane
- **The control plane creates and updates servers ; the data plane runs them**
- **All four run the same Agent Server from the same `langgraph.json`**
- **Operations ownership, region and compliance decide the choice**

SpiralTrain developer courses

Managed Deep Agents

- A hosted runtime in LangSmith runs the open-source Deep Agents harness
- Public beta at launch ; launch hosting was US only
- Version 0.10 of 29 October 2026 adds browser use and async subagents
- An agent is a folder :
  - `agent.py` : model and configuration, required
  - `instructions.md` , `skills/` , `tools/` , `middleware/`
  - Optional `sandbox/` , `memory.py` , `channels/` , `schedules/` , `evals/`
- CLI `mda` from the `managed-deepagents` package : `init` , `dev` , `evals` , `deploy`
- LangChain pricing, 30 October 2026 : Plus is $39 per seat per month with 1 free small serverless deployment

SpiralTrain developer courses

Scaling Strategies

- API processes keep no state of their own and share threads through PostgreSQL
- Long runs belong in workers, and clients poll or subscribe
- Local concurrency uses `--n-jobs-per-worker`
- Production concurrency uses `N_JOBS_PER_WORKER`
- Provider quotas limit model requests across all workers
- More workers add run capacity up to database and provider limits

SpiralTrain developer courses

Evaluating a Multi-Agent System

- **An eval runs the agent on fixed cases and scores the result, so two versions can be compared**
- **Four levels, from the outside in :**
  - Final response : is the answer right and complete
  - Single step : did the model pick the right tool and arguments
  - Trajectory : which tools were called, in which order
  - Multi-turn : did the conversation reach its goal
- **A score per crew member shows which one failed**
- **Correct specialist results do not prove the final answer : the last step can drop a fact**

The Eval Loop


Designer | Artist | Coder

RULE TESTS · QUICKJS

21 of 21

BOT · 5 GAMES

66.0 stars



Kit v3 spells out the order of a step in rules.md : 20 of 20. The same model, with better rules.

SpiralTrain developer courses

What the Comet Arcade Evals Found

kit	what changed	runs	pass
v1	first version	16	15
v2	stricter `star-grows` test ; the Coder sees the raw report	16	14
v3	`rules.md` spells out the order of a step	20	20

- A pass means every rule test passed and the bot ate at least 10 stars on average over 5 games
- Every run is counted, the failed ones too
- Each failure was traced to a cause, and each cause led to a change in the kit
- All three builds that failed stopped at the cap of 3 attempts ; none shipped

SpiralTrain developer courses

Limits of the Evidence

- **Tests prove the rules, and only opening the file proves it plays :**
  - Without the kit, 8 of 8 whole files passed the tests and 7 of 8 ran in a browser
  - The eighth called `init(0xC0MET)`, a pun that is no number, and showed a blank page
- **A model’s explanation of a bug is a guess :**
  - One Tester blamed `freeCell` and the Coder chased it for 3 attempts until the cap stopped the run
- **20 of 20 still allows a true pass rate of 86 %**
- **The same seed does not reproduce a run : seed 13 needed the fix loop once and passed first try on a repeat**
- **These numbers say nothing about a twist off the menu, which has no tests**

SpiralTrain developer courses

Final Answer Evaluation

- A final-answer eval checks facts in the reply against a trusted source
- Code scorers compare the required facts with tool results
- Text checks miss false claims and reject valid rewordings
- demo05 takes the expected stock and depot of a Veenhaven Bus part from the database

demo05 · evaluating-agents

SpiralTrain developer courses

Trajectory Match

- **A trajectory is the list of tool calls and results in one run**
- **`agentevals` compares a live trajectory with a reference trajectory**
- **`strict` needs the same messages in the same roles, and `unordered` needs the same tool calls**
- **Arguments must match exactly by default**
- **A strict reference needs the tool result and the answer as well as the call :**
  - In demo05b on the Veenhaven Bus stock graph, strict fails a short reference and passes the full one

`demo05b · trajectory-match`

Trajectory Match Modes

- **Four match modes on 0.0.9 :**
  - `strict` : same message roles and matching calls per message
  - `unordered` : same tool-call coverage across messages
  - `subset` : outputs introduce no calls beyond the reference
  - `superset` : outputs include at least the reference calls
- **Strict matching ignores prose and call order within one message**
- `tool_args_match_mode` **is** `exact` **by default, or** `ignore` **,** `subset` **,** `superset`

SpiralTrain developer courses

Trajectory Judge

- A judge is a second model that grades a run against a rubric, a written list of criteria
- `create_trajectory_llm_as_judge` gives it the task, tool calls, results and answer
- It returns a score and a short justification in `comment`
- Check a judge against human labels before it can block a release
- A judge has model biases, so read the justifications on a sample

demo05c · trajectory-judge

SpiralTrain developer courses

Specialist and System Evaluation

- **Each specialist gets its own rubric. On the Veenhaven Bus graphs in demo05d :**
  - Parts must keep the count and depot
  - Manuals must keep the action and condition
- **A negative control proves the judge can say no : a count changed from 6 to 9 failed 3 of 3 trials**
- **A system eval checks every required fact in the combined answer**
- **A failure then points at tool coverage, specialist quality or a fact lost in synthesis**

demo05d · each-agent

SpiralTrain developer courses

pass@k and pass^k

- An agent varies from run to run, so one run is one sample
- Run each case k times :
  - pass@k : at least one of the k trials passes
  - pass^k : all k trials pass
- pass@k suits a tool that a person can retry ; pass^k suits an agent that must work every time
- demo05e, Veenhaven Bus, 4 cases of 3 trials : each case passed all trials or none, so pass@3 = pass^3 = 3/4
- Anthropic’s example : 75 % per trial gives pass^3 of about 42 % when trials are independent

demo05e · pass-at-k

Rolling pass@k and pass^k



kit v3 20 of 20 · pass@5 4 of 4 · pass^5 4 of 4

Kit v3 ran 5 trials on each case and passed 20 of 20, so pass^5 is 4 of 4. That still allows a true rate of 86 %.

SpiralTrain developer courses

A LangSmith Experiment

- LangSmith keeps a dataset of cases and the score of every run against it
- The trainer experiment writes a Veenhaven Bus dataset to EU LangSmith
- Code evaluators score a stock fact and `part_stock` coverage
- Account or permission failures are reported, and the local agent still runs
- Online evaluators reuse the same rubrics on sampled production traces


demo06 · a-langsmith-experiment

SpiralTrain developer courses

Monitoring

- A trace is the record of one run : every model call, tool call, result and failure
- LangSmith Trajectories show one timeline across a parent and its subagents
- Online evals score a sample of production runs automatically
- Dashboards track cost per run, latency, error rate and judge scores
- Alerts fire when a quality score falls ; a sample can miss a failure

Reading a Trace



RUN_TESTS · SENT

The new game file

RUN_TESTS · RETURNED

```
21 of 21 rule tests pass ; bot 66.0 stars
```

no tokens

Reading the costs : two Coder calls took 78 % of the money. A cheaper model or a smaller prompt would save the most here.

SpiralTrain developer courses

Cost Optimisation

- **Each crew member can have its own model and its own token budget**
- **A compact handoff reduces input tokens :**
  - In demo07 a Veenhaven Bus synthesis read 138 tokens from a transcript and 50 from a summary
- **Provider prompt caching reuses a long stable start of a prompt :**
  - Instructions and tools go first, changing content last
  - Eligibility and retention depend on routing and the provider
  - OpenAI lists Luna cache writes at 25 % above input, so a prefix saves money from its first cached read
- **A cached prompt still sends a request and gets a new reply**
- **Usage reports separate input, cached input and output tokens**

`demo07 · cost`

`demo07b · prompt-caching`

p. 447

What a Game Costs



Then one run without max_tokens. The axis has to stretch : run 106 alone cost about as much as 45 normal builds.

SpiralTrain developer courses


Budget Stops

- **A guard is a limit in code that the model cannot override :**
  - `max_tokens` ends one reply. On Luna a cap of 200 ended a reply at 200 tokens
  - `ModelCallLimitMiddleware` ends a `create_agent` loop after a number of model calls
  - A gate ends the graph on attempts or on money spent :

```
def gate(board):
    if board["passed"]:
        return "publisher"
    if board["attempts"] >= 3 or board["spent"] >= 0.01:
        return END
    return "coder"
```

- **A reply cut by `max_tokens` is incomplete, so treat `finish_reason` `length` as a failure**

The Budget Stop



The budget stop : the gate returns END and the run stops, on the first attempt, before more money goes out.

SpiralTrain developer courses

Error Return Channel

- Prompt injection : text in a tool result that the model obeys as if it were an instruction
- Tool errors go back to the agent so it can recover, and error text can contain an injected instruction
- Fixed error codes keep untrusted text out of the reply
- demo08 changes one defence at a time on a Veenhaven Bus report tool :
  - A fixed code with the export tool kept
  - Then no export tool, and a prompt that treats codes as data
- Application code validates the stock lookup outside the agent

demo08 · injection-through-an-error

SpiralTrain developer courses

Summary : Production Deployment

- Agent Server serves assistants, threads and runs from `langgraph.json`
- The same graph runs on a laptop and in production, and the board is kept across a restart
- Clients stream events and read saved thread state
- Async subagents work in the background ; A2A exposes assistants to other systems
- Evals score final answers, trajectories and each crew member
- pass@k and pass^k report repeated trials ; a trace shows why one failed
- Token counts guide handoffs and caching, and guards stop a run in code
- Tool error text can inject an instruction, so error messages are untrusted input

exercise10 · Evaluating a System of Agents

exercise11 · An Async Subagent on a Server

Real-World Applications

From LLM to Agent
Introduction to LangGraph
Graph Fundamentals
State Management
Building Agents
Multi-Agent Patterns
Agent Communication
Advanced Workflows
Deep Agents
Production Deployment
Real-World Applications
Research Automation
Research Evidence
Customer Support
Handoffs in Support
Code Review
Pipeline Checkers
Data Analysis
Content Pipelines
Coding Agent Fleets
A Personal Crew
Firstmate Patterns
Harness or Graph
Navier-Stokes Swarm
Fermat Formalisation
The Research Team Revisited
Recursive Language Models Revisited
Multi-Agent Cost
The Capstone Desk
Summary : Real-World Applications

SpiralTrain developer courses

Research Automation

- **A research agent turns an open question into a report with sources :**
  - It plans sub-questions, retrieves evidence and combines the findings
  - Notes and drafts go into files as the context grows
- **The Deep Agents deep-research tutorial is the current reference ; `open_deep_research` showed the shape and is now archived**
- **Independent sub-questions run as parallel workers, each with its own sources, as in module 05**
- **A sub-question that needs another’s answer runs after it : in demo01 the Veenhaven Bus manual search uses the fault code found in the tickets**

Research Evidence

- **Every claim in a report needs a source that can be traced :**
  - Record the file or URL beside each finding
  - Report conflicting evidence and missing coverage
- **Files hold research notes and drafts outside the conversation, as in module 08**
- **A provenance check confirms that a source was retrieved ; a person checks that it supports the claim**

SpiralTrain developer courses

Customer Support

- **A service agent routes a request, looks up policy and resolves or escalates :**
  - Specialists hold different tools and authority
  - Irreversible actions pause for approval
- **Handoffs pass the request between specialists, as in module 05**
- **Refunds, orders and account changes wait at approval gates from module 07**

demo02 · customer-support

Handoffs in Support

- **A handoff changes the active specialist and passes on the task :**
  - The next agent needs the request and the earlier tool results
  - Parallel tool calls can leave an unanswered call after the transfer
- **Shared state keeps the request and useful tool results across transfers, as in modules 05 and 06**
- **Each specialist returns only its new records, and the handoff appends them once**
- **Evaluation checks complete answers and valid tool histories**

SpiralTrain developer courses

Code Review

- **Reviewers look at the same change for different risks :**
  - In demo03 one reviews correctness and one database safety, in parallel
  - Each reports every finding with a severity
- **A severity filter in code decides what reaches the judge, and the judge merges duplicates**
- **A checker in code confirms the seeded defects are among the accepted findings, and rejects an empty review**
- **Parallel review with a judge is the exploration pattern from module 05**

demo03 · code-review

SpiralTrain developer courses

Pipeline Checkers

- `no-mistakes` **places a pipeline of checks before changes reach** `origin` **:**
  - Stages run review, test, documentation, lint, push, pull request and CI
  - Mechanical fixes apply automatically, and changes to intent wait for approval
- **Defined pass conditions make it a maker-checker workflow from module 05**
- **Human approval controls consequential changes, as in module 07**

SpiralTrain developer courses

Data Analysis

- **An analytics agent turns a question into a query and an explanation :**
  - The SQL query, returned rows and explanation stay visible together
  - The database connection allows reading only
- `PRAGMA query_only` **makes SQLite reject writes on the connection**
- **A code check compares every number in the explanation with the returned rows, as in the checker pattern from module 05**
- **The Deep Agents data-analysis tutorial gives an agent CSV files and a sandbox from module 08**

SpiralTrain developer courses

Content Pipelines

- **A content pipeline turns source material into reviewed output :**
  - In demo04b it retrieves an approved Veenhaven Bus procedure
  - It drafts a bulletin and checks the required details before editorial review
- **Retrieval, drafting and validation form a fixed workflow from module 05**
- **An editor approves publication ; in a served pipeline the gate is an interrupt from module 07**

demo04b · content-pipeline

SpiralTrain developer courses

Coding Agent Fleets

- **A fleet gives each coding task its own worktree, a separate checkout of the repository :**
  - One orchestrator dispatches work and receives events
  - Each worker has a brief, a session and a checkout it can write to
- **Isolated subagents return findings to the orchestrator, as in modules 05 and 06**
- **Merge decisions use the approval flow from module 07**
- **Tests written by a coding agent need the same review as its code :**
  - An agent can hard-code values that pass only the given tests
  - A prompt can forbid it, and a reviewer or a held-out test catches it
- **firstmate supports macOS and Linux**

demo05 · firstmate

A Personal Crew

- **Monday’s first example : Yair deployed about 30 single-job bots behind one first mate :**
  - Bots cover taxes, vehicle status, portfolio, inbox and app administration
  - One first mate routes each request to the right bot
- **"they all share one computer with the same browser logins, and nothing gets sent without my ok"**
- **The course now has a name for each part :**
  - Single-job workers with short tool lists behind one orchestrator : module 05
  - A seller and a buyer for one owner : conflict resolution, module 06
  - "my ok" : an approval gate, module 07
  - Shared logins : the case for per-agent credentials, module 08

Firstmate Patterns

firstmate component	course pattern
first mate and crewmates	orchestrator with isolated subagents, module 05
task worktree and session	context isolation and backend, module 08
watcher and event files	event driven execution, module 06
durable briefs and state	checkpointer and `Store`, modules 03 and 06
merge escalation	interrupt and approval, module 07

- **Files and processes do the coordinating and saving that modules 05 to 08 do with graphs**

SpiralTrain developer courses

Harness or Graph

- **A coding harness fits work tied to a repository and long-lived sessions :**
  - Git worktrees, shell tools, watchers and files are its runtime
  - The model works on existing files and developer tools directly
- **A graph fits application-owned state and explicit transitions :**
  - Typed schemas, reducers and checkpointers define the boundaries
  - Conditional edges, loops and interrupts control the flow
- **Both can coordinate isolated workers, as in modules 05 and 08**
- **The choice depends on whether the application or the coding session controls state and the next step**


SpiralTrain developer courses

Navier-Stokes Swarm

- **Monday’s second example : OpenAI reports a coordinated search on an internal model :**
  - Groups explored different problem variants and proof or disproof directions
  - The winning group had on the order of 10,000 concurrent agents
  - Codex later shared findings between groups, and the model was updated during the run
- **OpenAI reports a Lean formalisation : GPT-6 Astra wrote the Lean proof in 17 more hours**
- **Clay says the process is "deliberately unhurried"**
- **A preprint says the Lean proof does not match the written proof ; neither shows the result wrong**
- **Module 05 has the same two roles : workers explore in parallel, and a checker judges the result**

SpiralTrain developer courses

What a Proof Checker Checks



A checker tests what it was given, so check the translation too : a second reader of the proof, a browser for the game.

Fermat Formalisation

- **Anthropic reports formalising an existing proof of Fermat's Last Theorem :**
  - Dozens of parallel agents proved 30,300 theorems over 11 days
  - The final development used 29,500 proved theorems across 13 million lines of Lean
  - Lean's type checker rejected invalid proof steps mechanically
- **Early attempts failed when agents lost track of the project's state**
- **A shared graph of theorem dependencies coordinates the parallel work, as in modules 05 and 06**

SpiralTrain developer courses

The Research Team Revisited

- **Monday’s third example : Anthropic’s lead agent with parallel research subagents**
- **The result stands, from June 2025 :**
  - 90.2 % better than a single Opus 4 agent on an internal research evaluation
  - About 15 times the tokens of a chat
- **The research agent of demo01 has the same shape : plan, workers, synthesis**
- **Anthropic’s advice of 22 October 2026 goes the other way for some work : fold a subagent back into the main loop when it adds little**
- **OpenAI’s mouse-brain run is a rare test at fixed resources : over 700 references with many agents, 11 with one**

SpiralTrain developer courses

Recursive Language Models Revisited

- Monday’s fourth example : a model that explores a long input in code
- The input stays in a Python REPL, and the model calls fresh copies of itself on parts
- Module 08 ran one level of the idea in demo08b, on 31 Veenhaven Bus manuals :
  - The root model writes a dispatch script, and readers get the chunks
  - The complete chunks stay out of the root’s requests
- Those manuals fit in one call, so the split cost more : 15,635 input tokens against 5,121
- The method pays off on inputs too long for one call, which the paper reports at about 100 times the window

SpiralTrain developer courses

Multi-Agent Cost

- **Monday’s last example : the bill for a swarm**
- **Multi-agent systems spend far more tokens than a chat :**
  - Anthropic measured about 15 times the tokens of a chat for its research system
  - Token usage alone explained 80 % of the variance in its BrowseComp results
- **OpenAI reports about 130 billion output tokens for Navier-Stokes ; Anthropic about six billion for Fermat**
- **swyx cited an estimate of about $40 million at public prices ; OpenAI reports no bill**
- **Alex Zhang stated "95% of the swarm is entirely useless", and hedged at once that OpenAI’s setup may differ ; no source measures the waste**
- **A single-agent baseline, as in modules 05 and 09, tests whether more workers justify their cost**

SpiralTrain developer courses

Opening Examples and Patterns



Six of the nine patterns ran on Comet Arcade in this course. The same parts build the examples from Monday.

SpiralTrain developer courses

One Shape at Every Scale




About ten orders of magnitude. The larger runs share one shape : someone makes, and something other than the maker checks.

The Capstone Desk

- **The Aurelia service desk compares a graph with a Deep Agent on one dataset :**
  - Stage 3 builds routed diagnosis, a judge, A2A communication and approval in a subagent
  - Stage 4 builds a Deep Agent with skills for procedures and specialists as subagents
- **Modules 05 to 08 supply the graph patterns, skills and subagents of both stages**
- **Stage 4 compares both designs on fact screens, tokens and counted code lines**
- **Stage 5 scores the served Deep Agent on eight cases, an injection among them**

SpiralTrain developer courses

What You Can Build Now




A crew that plans, builds, checks itself, asks before it ships and reports what it cost. It works on research, support, code and data as well.

SpiralTrain developer courses

Summary : Real-World Applications

- Research agents split questions, retrieve evidence and cite findings
- Support agents hand off the task and pause before consequential actions
- Reviewers report every finding with a severity ; code filters them, a judge merges them and a checker confirms the result
- Analysis and content pipelines keep queries and sources visible, and check figures in code
- Coding fleets use isolated workers, durable state and events
- Lean and code checks reject invalid model output mechanically. A checker tests what it was given, so check the translation too
- Multi-agent runs cost many times the tokens of a chat, so compare quality and cost with a simpler baseline

The Finished Comet Snake



5 model calls, 40.5 seconds, $0.002. Your turn : click the game and take the arrow keys, then build your own.