Multi Agents with LangGraph

COURSE EXERCISES

Exercise 0 : Lab Setup 3

Exercise 01 : Graphs and Loops 5

Exercise 02 : State for Two Agents 7

Exercise 03 : An Agent with Tests 9

Exercise 04 : A Multi-Agent Visit Planner 11

Exercise 05 : Two Agents over A2A 13

Exercise 06 : Buyer and Seller 16

Exercise 07 : Approval in a Subagent 18

Exercise 08 : A Deep Agent 20

Exercise 09 : Offload and Measure 22

Exercise 10 : Evaluating a System of Agents 24

Exercise 11 : An Async Subagent on a Server 26

Capstone : Aurelia Service Desk 28

---

footer: Introduction to LangGraph

Exercise 0 : Lab Setup

Open a terminal in the repository root on the classroom laptop. The trainer has installed `uv`, the repository and its packages ; you add the course key, run the check and start Jupyter.

Step 1 : Key

Copy `.env.example` to `.env` and paste the OpenRouter key from the trainer after `COURSE_API_KEY=` :

```
Copy-Item .env.example .env
notepad .env
```

Leave the other values as they are. Never paste a key into a notebook ; `.env` is ignored by git.

Step 2 : Check

```
uv run python check_setup.py
```

Does it report `7 of 7 checks passed` ? An authentication failure on every line means the key is missing or wrong. A missing package means `uv sync --group server` has to run first. Tell the trainer either way.

Step 3 : Notebooks

```
uv run jupyter lab
```

Open `notebooks/` and run the setup cell of the notebook the trainer names. Keep this terminal open.

If time permits

- Run `uv tree --depth 1` and compare the `langgraph` version with the one the check printed
- Find the line in `check_setup.py` that switches reasoning off for the course model
- Find the second model the check calls besides `COURSE_MODEL`

---

footer: Graph Fundamentals

Exercise 01 : Graphs and Loops

Open `exercises/exercise01-graphs-and-loops.ipynb` and run the setup cell. You route Aurelia service tickets through four small graphs by replacing the `____` blanks ; the solution is `solutions/exercise01-graphs-and-loops.ipynb` .

Worked examples to revisit : `demo02 · nodes-and-edges` , `demo03 · routing` , `demo04 · command-and-send` , `demo06 · a-model-in-a-node` .

Made up, not from work. The Aurelia tickets and sites are fictional.

Step 1 : Linear graph

Add the `stamp` node and its three edges : `START` to `normalise` , `normalise` to `stamp` , `stamp` to `END` . Run the cell on the messy T-1001 slip ring ticket, then the check.

What happens if you remove the edge to `END` and compile again?

Step 2 : Router

`prioritise` asks the model for `high` or `low` . Complete `route` so a high ticket goes to `page_engineer` and a low ticket to `queue` , and connect it to `prioritise` with the missing `router` method.

Which route did the stopped gantry get, and which the fan procedure request? Why does `route` declare its return type as `Literal["page_engineer", "queue"]` ?

Step 3 : Loop

`shorten` rewrites the Kanaalzicht gantry ticket in fewer words. Complete `again` : end when the text is at most 60 characters or after three attempts, otherwise return `"shorten"` .

Read the printed lengths. Which condition ended the loop, and what would `again` do on this ticket without the attempt cap?

Step 4 : Command

`triage` already knows the priority. Return a `Command` that stores `target` on `assigned` and goes to `target`.

Which node ran for the high ticket, and what does `assigned` hold?

If time permits

- Print `router_graph.get_graph().draw_mermaid()` and compare it with the router slide
- Give the loop in Step 3 a `recursion_limit` of 2 and read the error
- Fan out with `Send`, one branch per site from S01 to S04, and collect the site ids

---

footer: State Management

Exercise 02 : State for Two Agents

Open `exercises/exercise02-state-for-two-agents.ipynb` and run the setup cell. You run a triage node and a parts node in parallel on Aurelia ticket T-1001 by replacing the `____` blanks ; the solution is `solutions/exercise02-state-for-two-agents.ipynb`.

Worked examples to revisit : `demo01 · state-schemas`, `demo02 · reducers`, `demo03 · checkpointers`, `demo04 · history-and-time-travel`.

Made up, not from work. The Aurelia tickets and `service.db` are fictional.

Step 1 : Shared key

Run the cell that reads T-1001 from `tickets.csv`. Add the two edges from `START` to `triage` and `parts`, then run the check cell. Both nodes write `note`.

Which error does the check catch, and what does its first line say about `note` ?

Step 2 : Reducer

Give `findings` in `Shared` a list type with a reducer that appends. Run both nodes again.

Which findings does the result keep, and which keys did each node read?

Step 3 : Private key

`lookup` writes `stock_note`, the stock line for the slip ring brush kit. Type `stock_note` in `PartsView`, and choose the `output_schema` that leaves it out of the result.

Which keys does the invoke result contain? Where does `stock_note` still appear, and which keys did triage read?

Step 4 : History

Compile `desk` again with a checkpointer, give `cfg` a thread id, and list the thread's state history.

How many checkpoints does the thread keep, and which step has an empty `next`?

If time permits

- Open a second thread id on `saved` and compare `get_state` on both
- Replace `InMemorySaver` with `SqliteSaver` and open the same thread again
- Fork the checkpoint before `parts` with `update_state` and change `stock_note`

---

footer: Building Agents

Exercise 03 : An Agent with Tests

Open `exercises/exercise03-an-agent-with-tests.ipynb` and run the setup cell. You build a stock agent on Aurelia's `service.db`, test it with a scripted model under pytest and run it once on the course model ; the solution is `solutions/exercise03-an-agent-with-tests.ipynb`.

Worked examples to revisit : `demo02 · create-agent`, `demo05 · agent-failures`, `demo07 · testing-agents`.

Made up, not from work. The Aurelia parts and stock are fictional.

Step 1 : Tool

Complete the query in `part_stock` so it reads `stock` from `parts` for one `part_no`. The function already returns `Unknown part` when no row comes back.

What does the tool return for `CT-SR-03` and for `UNKNOWN` ?

Step 2 : Scripted model

`GenericFakeChatModel.bind_tools` raises `NotImplementedError`. Make `FakeToolModel.bind_tools` return the model itself, then run the scripted `part_stock` call and final answer.

Which message carries the tool result, and what is its `tool_call_id` ?

Step 3 : Pytest

Fill the middleware in `test_run_limit_stops_the_second_call` with a `ModelCallLimitMiddleware` that allows one model call and ends the run. Write the module and run pytest.

How many tests pass? The script has two tool calls ; how many tool results does the limit let through?

Step 4 : Live run

Run the same tool on `llm` with `run_limit=4` and ask for the stock of `CT-SR-03`.

How many model calls did the live run make, and did it reach an answer before the limit?

If time permits

- Add `ToolCallLimitMiddleware` on `part_stock` and script a second call
- Give the live agent a checkpointer, run two thread ids and compare `get_state`
- Change `run_limit` to 1 on the live agent and read the limit message

---

footer: Multi-Agent Patterns

Exercise 04 : A Multi-Agent Visit Planner

Open `exercises/exercise04-a-multi-agent-visit-planner.ipynb` and run the setup cell. You plan an engineer's visit to Aurelia site S04 with a parts agent, a manuals agent and a code checker, then compare it with one agent ; the solution is `solutions/exercise04-a-multi-agent-visit-planner.ipynb`.

Worked examples to revisit : `demo01 · subagents`, `demo03 · router`, `demo07 · maker-checker`, `demo09 · what-each-pattern-costs`.

Made up, not from work. The Aurelia sites, devices and manuals are fictional.

Step 1 : Tools

Run the two cells. They define `run_sql` and `search_manuals` and list the devices at S04.

What does `run_sql` return for `DELETE FROM devices` ?

Step 2 : Checker

Write `check_plan(plan, site_id)`. It returns a list of problems, empty when the plan passes :

- Every device at the site appears in the plan by serial number
- Every part number that `PART` matches exists in `parts`
- A part with stock 0 has "out of stock" on the same line

Error codes such as `E-MR-202` do not match `PART`. The test cell must pass before you go on.

Which three problems does `BAD` have?

Step 3 : Router

Complete `manuals_question` from `state["devices"]`, `dispatch` with one `Send` to `parts` and one to `manuals`, and `after_check` : `"assemble"` while problems remain and `rounds` is under 2, otherwise `END`. Replace the blank line with an edge from both specialists to `assemble`.

Which nodes does `dispatch` send to, and what does `after_check` return once `rounds` reaches 2?

Step 4 : Cost

Run the planner for S04, then the single agent with both tools on the same task. The metrics lines print calls and tokens for each.

How many model calls and tokens did each design use? Did the checker pass the planner's plan?

If time permits

- Plan site S01 with `run_planner`
- Add a fourth check : every CT-400 on firmware below 5.2 gets the 12-month fan interval
- Replace the router with a handoff. Disable parallel tool calls, and forward the full worker history with the transfer receipt, as in `demo04 · handoffs`

---

marp: true theme: spiraltrain size: 16:10 paginate: true footer: Agent Communication

Exercise 05 : Two Agents over A2A

Open `exercises/exercise05-two-agents-over-a2a.ipynb` and run the setup cell. You serve an Aurelia parts agent and a service desk agent on two local Agent Servers and let the desk call the parts agent over A2A by replacing the `____` blanks ; the solution is `solutions/exercise05-two-agents-over-a2a.ipynb` .

Worked examples to revisit : `demo03 · served-agents` , `demo04 · two-agents-over-a2a` .

Made up, not from work. The Aurelia parts and stock are fictional.

Step 1 : Graph sources

In `coordinator_source` , fill the assistant id key from `/assistants/search` , the JSON-RPC method and the `contextId` . Run the cell that writes both sources into `parts` and `desk` runtime folders.

Which of the two sources opens `service.db` , and how does the desk get its stock facts?

Step 2 : Agent cards

Fill the `assistant_id` parameter of the card request and run the cell. It starts the parts agent on port 2125 and the desk on 2124.

Which id appears at the end of each card's `url` : the graph name or a UUID?

Step 3 : First task

Fill the context constructor, the method and the result key, then send the CT-400 visit request to the desk. The cell prints the desk's stored remote exchange.

Which part do the two task ids share, and which part differs?

Step 4 : Same context

Send the follow-up with the saved `context` and no task id. Fill the method that fetches the new task by id.

Which keys does `GetTask` return, and where is the answer text? How long is the history with `historyScope="task"` and without it?

Step 5 : Shutdown

Run the final cell. It stops both servers and prints the calls and tokens from both sides. Call `stop_servers()` at once if a cell fails while a server runs.

Are ports 2124 and 2125 released?

If time permits

- Send a third question through the desk with the same context and compare both histories
- Call the parts agent with `message/send` and compare its response shape with `SendMessage`
- Send a context that is not a UUID and read the JSON-RPC error ; no model call is made

---

marp: true theme: spiraltrain size: 16:10 paginate: true footer: Agent Communication

Exercise 06 : Buyer and Seller

Open `exercises/exercise06-buyer-and-seller.ipynb` and run the setup cell. You let an Aurelia procurement agent and a parts seller agent negotiate three helium compressor filters, each under a private price policy, by replacing the `____` blanks ; the solution is `solutions/exercise06-buyer-and-seller.ipynb`.

Worked examples to revisit : `demo06 · conflicts`, `demo07 · buyer-and-seller`.

Made up, not from work. The Aurelia stock and both price policies are fictional.

Step 1 : Private policies

Complete `read_policy` : raise `PermissionError` unless the principal's role is `owner` and its scope is `expected_scope[owner]`. Run the two policy checks.

Which values in `ORDER` come from `service.db`, and which values live only in `BUYER` or `SELLER`?

Step 2 : Scoped agents

Give `buyer` and `seller` each its own policy tool. `ToolRuntime` passes the principal as context.

What does the printed tool schema of `buyer_policy` contain, and can the model name a role through it?

Step 3 : Settlement

In `settle`, fill the condition that sends non-overlapping prices to review and the midpoint price. Join `buyer` and `seller` into `settle`, then run the three fixture checks.

Why does `proposals` need a reducer when both agents write it in the same step?

Step 4 : Negotiation

Run the two rounds. Only the public prices of round 1 go into round 2.

What were the opening offers, and what did round 2 settle on? Which rule would keep a crossed result in review?

Step 5 : Access denial

Read the seller policy with the buyer principal. The cell then tries a seller role with the buyer's scope. Run the metrics cell.

Which message does the denial print, and does it come from the prompt or from `read_policy` ?

If time permits

- Raise the seller floor above the buyer ceiling and confirm the result stays in review
- Replace the midpoint rule with a model judge, then check its output against both policies
- Add a delivery deadline to each private policy and share only the proposed delivery date

---

marp: true theme: spiraltrain size: 16:10 paginate: true footer: Advanced Workflows

Exercise 07 : Approval in a Subagent

Open `exercises/exercise07-approval-in-a-subagent.ipynb` and run the setup cell. You build an Aurelia supervisor whose parts subagent pauses for a person's approval before it records a spare parts order, by replacing the `____` blanks ; the solution is `solutions/exercise07-approval-in-a-subagent.ipynb` .

Worked examples to revisit : `demo01 · interrupts` , `demo02 · interrupts-in-multi-agent` .

Made up, not from work. The Aurelia parts, prices and orders are fictional.

Step 1 : Order policy

Complete `reviewer` : the manager above 10,000 EUR, the lead otherwise. Complete the quantity bound in `validated_order` : positive and within stock.

Which reviewer does each of the three requests get? What does `A-edit` cost at quantity 1?

Step 2 : Parts subagent

In `review_order` , call `interrupt` and match the `reject` , `edit` and `approve` actions. An edit reads its new quantity from the decision.

Which statements in `review_order` run before `interrupt` , and will they run again on resume?

Step 3 : Supervisor tool

Invoke `parts_subagent` inside `parts_specialist` , and give the supervisor an in-memory checkpointer.

Why does only the supervisor get a checkpointer, and not `parts_subagent` ?

Step 4 : Top-level pause

Run the three requests, each in its own supervisor thread.

What does `get_state(cfg).next` show for each thread, and is any order in `ORDERS` yet?

Step 5 : Decisions

Fill the decisions : approve the helium filters, edit the fan order to quantity 1, and reject the detector module. Resume each saved supervisor thread with its decision.

Why do `tool_entries` and `review_entries` reach 2 for every order while `ORDERS` holds each approved order once?

If time permits

- Edit an order to quantity 0 or above stock and read the validation error
- Print the supervisor state history and find the checkpoint with the pending approval
- Add a second review by the manager after the lead approves an expensive order

---

footer: Deep Agents

Exercise 08 : A Deep Agent

Open `exercises/exercise08-a-deep-agent.ipynb` and run the setup cell. You build an Aurelia briefing agent with a manuals backend, a skill and a parts subagent by replacing the `____` blanks ; the solution is `solutions/exercise08-a-deep-agent.ipynb` .

Worked examples to revisit : `demo02b · write-todos` , `demo04d · composite` , `demo06b · skills` , `demo07 · subagents` .

Made up, not from work. The Aurelia manuals, parts and stock are fictional.

Step 1 : Manuals backend

Run the cell that defines `part_stock` , `disk` and `backend` , then the check. Read the sample from the CT-400 error-code manual and the `disk.ls("/")` listing.

How many manuals does `PAGES` contain?

Step 2 : Skill

Complete the front matter and body in `SKILL_MD` for `error-briefing` . Tell the agent to read the Aurelia manuals, state the error's meaning and first action, and keep the briefing to three bullets. Run the skill-text check.

Which directory does the printed skill tell the agent to read?

Step 3 : Parts subagent

Complete `name` , `description` , `system_prompt` and `tools` in `parts` for stock lookups through `part_stock` . Keep `parts_llm` as its model and run the check.

Which name and description does the cell print for the subagent?

Step 4 : Briefing

Fill `backend`, `middleware`, `skills` and `subagents` in `create_deep_agent`. Use the objects from the earlier cells, add planning with `TodoListMiddleware`, and point skills at `/skills/`. Run the supplied E-CT-110 and CT-FN-02 request, then the check. Read `todos`, `files` and `seen_by_parts` alongside the answer.

Does `seen_by_parts` contain the parent skill text or only the delegated stock request?

If time permits

- Change the skill so the briefing must name the depot as well, and run again
- Add a second dict subagent for manuals and move the parent's `/manuals/` reads into it
- Compare tokens with and without `TodoListMiddleware` on the same task

---

footer: Deep Agents

Exercise 09 : Offload and Measure

Open `exercises/exercise09-offload-and-measure.ipynb` and run the setup cell. This exercise is optional. You compare Aurelia manuals exports with and without offloading, then total ticket hours in QuickJS ; the solution is `solutions/exercise09-offload-and-measure.ipynb` .

Worked examples to revisit : `demo03b · offloading-large-results` , `demo05b · the-interpreter` .

Made up, not from work. The Aurelia manuals and tickets are fictional.

Step 1 : Raw export

Run the helpers and the `plain` agent with `all_manuals` , then the check. Read `raw_chars` , the model's answer and the metrics saved in `no_offload` .

How close is the model's estimated export size to `raw_chars` ?

Step 2 : Offloading

Fill `tool_token_limit_before_evict` in `FilesystemMiddleware` with a threshold low enough to offload the export. Keep `deny_reread` and `capture_tool_results` . Run `offloader` , then the check, and compare `captured` with `saved paths` .

What does the model receive in place of the full export?

Step 3 : QuickJS

Run `analyst` with `CodeInterpreterMiddleware` and the `ticket_rows` PTC tool on the supplied S01 request. Replace the final blank with an assertion that `computed` matches `expected` for `count` and `hours` , then run the check.

Which ticket count and hours total do the sandbox and Python report?

Step 4 : Measurements

Run the cell that prints `rows` as a table. Replace its final blank with assertions that `offload_tool_chars` is less than half of `raw_chars` and that `quickjs` recorded input tokens.

How do input tokens and tool-message characters compare between `no_offload` and `offload` ?

If time permits

- Raise the eviction limit until offloading stops, and find the threshold on this export
- Ask QuickJS for a breakdown by `error_code` at site `S03`
- Offload `ticket_rows` itself and compare with the interpreter path

---

footer: Production Deployment

Exercise 10 : Evaluating a System of Agents

Open `exercises/exercise10-evaluating-a-system-of-agents.ipynb` and run the setup cell. You score Aurelia's parts agent, manuals agent and desk on cases from `eval.jsonl` by replacing the `____` blanks ; the solution is `solutions/exercise10-evaluating-a-system-of-agents.ipynb` .

Worked examples to revisit : `demo05 · evaluating-agents` , `demo05b · trajectory-match` , `demo05d · each-agent` .

Made up, not from work. The Aurelia service records, manuals and evaluation cases are fictional.

Step 1 : Agents and cases

Run the cell that builds `parts_agent` , `manuals_agent` and `desk` . Read their tool lists and the case ids in `SELECTED` , then run the check.

Which six case ids does the cell select from `CASES` ?

Step 2 : Answer scores

Complete the message type, case conversion and tool-list blanks in `score_answer` . Check for at least one expected fact in the answer and every expected tool in the messages. Run all `SELECTED` cases through `desk` and read `desk_results` .

How many cases pass both `facts_ok` and `tools_ok` in your run?

Step 3 : Trajectory match

Run the live `man-01` comparison against `reference` . Fill `trajectory_match_mode` in the fixture loop to compare `strict` and `unordered` , keeping `tool_args_match_mode="ignore"` . Run the reordered-call

and one-call fixtures, then the check.

How do the two modes score the live messages, `reversed_calls` and `one`?

Step 4 : Per-agent scores

Fill the two agent blanks in `per_agent` with the specialist for `db_case` and the specialist for `man_case`. Run the mixed-case calls and compare each specialist's row with `desk_mix`, then run the check.

Which `mix-01` rows pass `facts_ok` but fail `tools_ok`?

If time permits

- Re-score the live `man-01` trajectory without `tool_args_match_mode="ignore"` and compare the argument checks
- Add `subset` and `superset` to the trajectory table
- Replace the fact check with a trajectory judge on one mixed case

---

footer: Production Deployment

Exercise 11 : An Async Subagent on a Server

Open `exercises/exercise11-an-async-subagent-on-a-server.ipynb` and run the setup cell. You serve an Aurelia supervisor and diagnosis worker, then start and collect an async task by replacing the `____` blanks ; the solution is `solutions/exercise11-an-async-subagent-on-a-server.ipynb` .

Worked examples to revisit : `demo03 · async-subagents` .

Made up, not from work. The Aurelia diagnoses, manuals and stock are fictional.

Step 1 : Graph sources

Run the cell that writes `course_runtime.py` , `graphs.py` and `langgraph.json` , then the file check. Read the printed graph configuration.

Which graph ids does `langgraph.json` expose?

Step 2 : Agent Server

Run the server helpers. Fill the port blanks in `start_server` and `connect` to match the supplied `/ok` request. Run the startup cell and the assistant check.

Which assistants does the server list?

Step 3 : Task lifecycle

Run `supervise` to start the E-CT-110 and CT-FN-02 diagnosis, check `task_id` and list the tasks. Expect the worker to hold for about two minutes before its model call so the first check sees `running` . Replace the final blank with assertions that `first_status` has the expected status and `used` includes all three requested lifecycle tools.

Which lifecycle tool names does `used` contain after the list request?

Step 4 : Task result

Run `client.runs.join` on the child run and expect to wait for the hold and diagnosis to finish. Check the task again through `supervise`. Replace the final blank with assertions on `status` and the returned diagnosis facts. Run the final cell to stop every process in `servers`; call `stop_server` on those processes at once if a cell fails while the server runs.

What first action and CT-FN-02 stock does the collected answer report?

If time permits

- Cancel a second delayed task before it finishes
- Steer the running task with `update_async_task` to look up UX-BT-02 instead
- Restart the server in the same folder and read whether the thread still lists the task

---

marp: true theme: spiraltrain size: 16:10 paginate: true footer: Real-World Applications

Capstone : Aurelia Service Desk

Open `exercises/capstone-stage1.ipynb` and run the setup cell. Build a service desk for Aurelia Imaging Systems, a fictional maker of hospital imaging equipment. Find each stage's solution in `solutions/capstone-stageN.ipynb`.

Use the supplied data in `data/capstone/`, made up, not from work. Inspect `service.db`, `manuals/`, `tickets.csv` and `eval.jsonl`. Keep `untrusted/` out of the trusted manuals search.

Run the supplied previous-stage definitions at the start of each later notebook. A missed stage does not block the next one. Complete all numbered steps unless the trainer takes the stage 3 A2A cut. Items under `If time permits` are optional.

Keep `COURSE_RPS=0.08` and run one notebook at a time. Use the supplied server cells and run the final stop cell in stages 3 to 5, including after a failed cell. Keep the course key in `.env`.

Stage 1 : Graph workflow

Open `exercises/capstone-stage1.ipynb`. Add triage, database lookup, answers and checkpoints to Aurelia's desk after module 03 on Monday. Allow 45 to 60 minutes.

Step 1 : Triage

1. Complete the typed evidence field and the edge from lookup to answer.
2. Inspect the supplied triage expressions and read-only queries.
3. Run the lookup check and compare the ticket fields with the database result.

Which device field does triage extract before the database lookup?

Step 2 : Checkpoints

1. Compile the workflow with an in-memory checkpointer.
2. Run the three database questions.
3. Compare each returned answer with the saved state on its thread.

Does each saved answer match the returned answer?

Step 3 : Boundaries

1. Run the unknown-device and mixed-fault questions.
2. Read both answers beside the database evidence.

Which question needs a manual before Aurelia can identify a replacement part?

If time permits

- Add a site contract lookup
- Restore a checkpoint with `SqliteSaver`
- Inspect state history before the answer node

Stage 2 : Specialist supervisor

Open `exercises/capstone-stage2.ipynb` and run the supplied stage 1 definitions. Add parts, manuals and scheduling specialists behind Aurelia's supervisor after module 05 on Tuesday. Allow 45 to 60 minutes.

Step 1 : Specialists

1. Complete the manuals tool list and scheduling query parameters.
2. Inspect each specialist's tool schema.
3. Run the certification and trusted-manual checks.

Which engineers does the scheduling query return for MR-150?

Step 2 : Delegation

1. Complete the isolated parts invocation.
2. Build the supervisor with a checkpointer.
3. Follow the worker messages and returned summary when running the next cell.

How many messages does the parts worker's printed context contain?

Step 3 : Measurements

1. Run the same three questions through stage 1 and stage 2.
2. Compare the answers, calls, input tokens and output tokens.

Does stage 2 answer these database questions more accurately at the additional call cost?

If time permits

- Ask the mixed fault question and inspect both specialist summaries
- Add a ticket-history specialist
- Remove an unnecessary delegation and measure again

Stage 3 : Diagnosis and approval

Open `exercises/capstone-stage3.ipynb` and run the supplied stage 2 definitions. Add parallel diagnosis, a judge, a served manuals agent and order approval to Aurelia's desk after module 07 on Tuesday. Allow 60 to 75 minutes.

Step 1 : Manuals service

1. Run the export cell and inspect `GRAPH_SOURCE`.
2. Complete the A2A method and UUID context id.
3. Start the manuals server on port 2145 and read its agent card.

Does the printed assistant id match the graph name `manuals`?

On `langgraph-api` 0.16.0, use the assistant UUID resolved by `assistants.search` for the A2A endpoint and a fresh UUID for `contextId`.

Tuesday trainer cut

Skip the A2A part when the trainer takes this cut :

1. Run the server-helper cell to initialise the empty server list for cleanup.
2. Use the local manuals worker with `record_trace` in place of A2A.
3. Skip server startup and the remote-usage assertion.
4. Keep the three-finding check, parallel diagnosis and order approval.

Step 2 : Parallel diagnosis

1. Complete the fan-in edge to the judge.
2. Run the mixed fault question.
3. Compare all three findings with the judge's answer.

Which airflow condition does the judge retain before recommending CT-FN-02?

Step 3 : Order approval

1. Request a fan through the supervisor's order subagent.
2. Inspect the ledger while the top-level graph is interrupted.

3. Resume that supervisor on the same thread with approval.
4. Request another fan and reject it. Inspect the ledger again.

When does a simulated order enter the ledger?

Run the final server stop cell, including after the trainer cut.

If time permits

- Request a tube above 10000 EUR and inspect the service-manager rule
- Compare A2A with the in-process manuals worker
- Inspect the child checkpoint while approval waits

Stage 4 : Deep Agent desk

Open `exercises/capstone-stage4.ipynb` and run the supplied stage 3 definitions. Rebuild Aurelia's desk with procedure skills and specialist subagents after module 08 on Wednesday. Allow 60 to 75 minutes.

Step 1 : Procedure skills

1. Complete the virtual skills source and compiled specialist entry.
2. Read the diagnosis, scheduling and ordering procedures.
3. Run the harness configuration check.

Which procedure files are available to the desk?

Step 2 : Graph baseline

1. Start the stage 3 manuals server.
2. Run `db-01`, `db-03`, `db-04`, `man-01` and `mix-01` through the graph.

3. Read every answer beside its phrase screen, especially the MR-150 certification answer.

Does the passing `db-04` screen agree with the answer's claim about certification?

Step 3 : Harness comparison

1. Run the same five cases through the Deep Agent.
2. Compare answers, screens, calls, tokens and the printed code counts.
3. Inspect the worker traces for missing certification evidence.

Does the Deep Agent use fewer orchestration lines while consuming more input tokens?

Compare only the counted stage additions, which exclude shared tools and stage 4's reused approval code.

Step 4 : Approval transfer

1. Request a fan through the Deep Agent's orders subagent.
2. Inspect the top-level interrupt and reject the request.
3. Check the ledger and run the final server stop cell.

Does rejection leave the ledger empty?

If time permits

- Pin a procedure and compare `read_file` calls
- Inspect the general-purpose subagent's scope
- Add human-reviewed correctness labels beside the phrase screens

---

Stage 5 : Served evaluation

Open `exercises/capstone-stage5.ipynb` and run the supplied stage 4 definitions. Serve Aurelia's desk, launch async diagnosis and score answers and ticket costs after module 09 on Wednesday. Allow 60 to 75 minutes.

Step 1 : Graph exports

1. Inspect the service, dispatcher and diagnostician exports in `GRAPH_SOURCE`.
2. Complete the diagnostician registration.
3. Start the supplied server on port 2144 and check its graph ids.

Which three graphs does the server register?

Step 2 : Async diagnosis

1. Launch the long diagnosis with `start_async_task` and retain its task id.
2. Complete the SDK wait on the child run.
3. Ask the dispatcher to fetch fresh status with `check_async_task`.
4. Inspect the child's answer and usage.

Which status appears at launch and which appears after the dispatcher fetches the result?

Step 3 : Agent scores

1. Complete the trajectory coverage mode and run the same five cases through the served desk.
2. Compare specialist coverage, system coverage, phrase screens and final answers.

3. Inspect the printed arguments for `db-04` and `mix-01` against the database values.

Which two answers fail despite coverage scoring `True`?

Inspect the saved solution : all coverage scores are `True`, but two of five answers are wrong or incomplete after `lookup_parts(model="CT400")` instead of `CT-400` and `engineers(model="Aurelia MR-150", region="")` instead of canonical `MR-150`.

Step 4 : Ticket costs

1. Read the notebook's dated public OpenRouter price snapshot.
2. Complete the output-token rate lookup.
3. Calculate each ticket's cost from its measured input and output tokens.

Which of the five tickets has the highest estimated cost?

Treat the result as an uncached token list-price estimate, excluding infrastructure, retries, discounts and optional judge calls.

Run the final server stop cell.

If time permits

- Add argument validation for canonical model names and the optional region filter
- Judge one failed trajectory and compare a human correctness label
- Steer or cancel a second async task before its model call