FEITIAN

aR530 Developer Guide for iOS

Revision History:

Date	Revision	Description
20th, Jan, 2015	1.0	Release first version
April 16, 2015	1.1	Add get reader UID API
Jan 27, 2016	1.2	Add buzzer control API

Software Developer's Agreement

All Products of Feitian Technologies Co., Ltd. (Feitian) including, but not limited to, evaluation copies, diskettes, CD-ROMs, hardware and documentation, and all future orders, are subject to the terms of this Agreement.   If you do not agree with the terms herein, please return the evaluation package to us, postage and insurance prepaid, within seven days of their receipt, and we will reimburse you the cost of the Product, less freight and reasonable handling charges.

1. Allowable Use – You may merge and link the Software with other programs for the sole purpose of protecting those programs in accordance with the usage described in the Developer's Guide.   You may make archival copies of the Software.

2. Prohibited Use – The Software or hardware or any other part of the Product may not be copied, reengineered, disassembled, decompiled, revised, enhanced or otherwise modified, except as specifically allowed in item 1. You may not reverse engineer the Software or any part of the product or attempt to discover the Software's source code.   You may not use the magnetic or optical media included with the Product for the purposes of transferring or storing data that was not either an original part of the Product, or a Feitian provided enhancement or upgrade to the Product.

3. Warranty – Feitian warrants that the hardware and Software storage media are substantially free from significant defects of workmanship or materials for a time period of twelve (12) months from the date of delivery of the Product to you.

4. Breach of Warranty – In the event of breach of this warranty, Feitian's sole obligation is to replace or repair, at the discretion of Feitian, any Product free of charge.   Any replaced Product becomes the property of Feitian.

Warranty claims must be made in writing to Feitian during the warranty period and within fourteen (14) days after the observation of the defect.   All warranty claims must be accompanied by evidence of the defect that is deemed satisfactory by Feitian.   Any Products that you return to Feitian, or a Feitian authorized distributor, must be sent with freight and insurance prepaid.

EXCEPT AS STATED ABOVE, THERE IS NO OTHER WARRANTY OR REPRESENTATION OF THE PRODUCT, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

5. Limitation of Feitian's Liability – Feitian's entire liability to you or any other party for any cause whatsoever, whether in contract or in tort, including negligence, shall not exceed the price you paid for the unit of the Product that caused the damages or are the subject of, or indirectly related to the cause of action.   In no event shall Feitian be liable for any damages caused by your failure to meet your obligations, nor for any loss of data, profit or savings, or any other consequential and incidental damages, even if Feitian has been advised of the possibility of damages, or for any claim by you based on any third-party claim.

6. Termination – This Agreement shall terminate if you fail to comply with the terms herein. Items 2, 3, 4 and 5 shall survive any termination of this Agreement.

Contents

Chapter 1. Overview

This document describes how to develop application based on Feitian aR530, and the document has guide developers to using API to do operate with Feitian aR530.

We through four parts to describe aR530 SDK.

1.1 First part, describe application dynamic library and JAR file, to let developer have a basic concept.

1.2 Second part, we do explain all support APIs, and have to do each API means

1.3 Third part, the details of APIs

1.4 Describe the development process and notice items

Chapter 2. Development Overview

2.1 Describe static library

The aR530 SDK based on static library (**.a**) and header file (**.h**), the below chart listed related file:

File	Describe
libFTaR530.a	Support armv7/armv7s/arm64/i386/x86_64
Header file	\Include

To develop application, customer need to import above file and also import framework which related with libFTaR530.a

AVFoundation.framework

Foundation.framework

CoreAudio.framework

CoreMedia.framework

ExternalAccessory.framework

AudioToolbox.framework

MediaPlayer.framework

2.2 Describe operation APIs

Number	API name	Description	Status
initialization APIs			
1	SharedInstance	Get the aR530 operating handle	Implemented
2	setDeviceEventDelegate	To set current reader event, which is instance object	Implemented
Reader event APIs			

3	FtaR530DidConnected	Get reader plug in event	Implemented
4	FTaR530DidDisConnected	Get reader plug out event	Implemented
5	FTaR530GetInfoDidComplete	Get reader information event	Implemented
6	FTNFCDidComplete	Get the response data from card	Implemented
Get version			
7	getDeviceID	Get reader hardware id	Implemented
8	getFirmwareVersion	Get reader firmware version	Implemented
9	getLibVersion	Get the current lib version	Implemented
Contactless card functions (Type A/B and Felica)			
10	NFC_Card_Open	Connect to contactless card	Implemented
11	NFC_Card_Close	To disconnect the current card	Implemented
12	NFC_Card_Recognize	Get the current contactless card type (after NFC_Card_Open can call this API)	Implemented
13	NFC_Card_Transmit	Send APDU commands to card	Implemented
Mifare card functions			
14	Mifare_GeneralAuthenticate	To authentication the current card	Implemented
15	Mifare_ReadBinary	Read block data	Implemented
16	Mifare_UpdateBinary	Update block data	Implemented
17	Mifare_ClassicBlockInitial	To do initialization with the special block	Implemented
18	Mifare_ClassicReadValue	Read value from card	Implemented

19	Mifare_ClassicStoreBlock	Write value into block	Implemented
20	Mifare_ClassicIncrement	To increment value	Implemented
21	Mifare_ClassicDecrement	To decrement value	Implemented
Buzzer control			
22	playSound	Call disableconnectSound first, and after call this API to control buzzer	Implemented
23	disabbleConnectSound	Disable buzzer function	Implemented

Chapter 3. Definitions

3.01 Get operation handle of aR530

```
#include "FTaR530.h"
+(id)sharedInstance;
```

Please refer to aR530 demo code

3.02 Setting the current instance of the object

```
#include "FTaR530.h"
-(void)setDeviceEventDelegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

3.03 Get the reader insert event

```
#include "FTaR530.h"
-(void)FTaR530DidConnected;
```

Please refer to aR530 demo code

3.04 Get the reader plug out event

```
#include "FTaR530.h"
-(void)FTaR530DidDisConnected;
```

Please refer to aR530 demo code

3.05 Get the device information

```
#include "FTaR530.h"
/*@Name:            -(void)FTaR530GetInfoDIdComplete:(unsigned  char  *)retData
retDataLen:(unsigned  int)retDataLen    functionNum:(unsigned  int)functionNum
errCode:(unsigned int)errCode;
 *@Function:    This function will be callback when Get Firmware Version or Get Device
ID function completed.
 *@Parameter:   OUT:(1).(unsigned char *)retData:   return Data
 *              (2).(unsigned int)retDataLen:   return Data length
 *              (3).(unsigned int)functionNum:  The function number
 *               (4).(unsigned int)errCode:      The error code(0-sucess,other
value-error code)
 *
 */
-(void)FTaR530GetInfoDidComplete:(unsigned  char  *)retData  retDataLen:(unsigned
int)retDataLen     functionNum:(unsigned    int)functionNum    errCode:(unsigned
int)errCode;
```

Please refer to aR530 demo code

3.06 Get the response data from card

```
/*@Name:           -(void)FTNFCDidComplete:(nfc_card_t)cardHandle retData:(unsigned
char   *)retData    retDataLen:(unsigned    int)retDataLen    functionNum:(unsigned
int)funcNum errCode:(unsigned int)errCode;
 *@Function:    This function will be callback when NFC function completed.
 *@Parameter:   OUT:(1).(nfc_card_t)cardHandle:    the card's handle
 *              (2).(unsigned char *)retData:   return data
 *              (3).(unsigned int)retDataLen:   return data length
 *              (4).(unsigned int)funcNum:      The function number
 *              (5).unsigned int)errCode:       The error code(0-success, other
value-error code)
 */
-(void)FTNFCDidComplete:(nfc_card_t)cardHandle  retData:(unsigned  char  *)retData
retDataLen:(unsigned     int)retDataLen     functionNum:(unsigned     int)funcNum
errCode:(unsigned int)errCode;
```

Please refer to aR530 demo code

3.07 Ge the lib version

```
#include "FTaR530.h"
-(NSString *)getLibVersion;
```

Please refer to aR530 demo code

3.08 Get the reader device ID

```
#include "FTaR530.h"
/*@Name:        +(void)getDeviceID:(id<FTaR530Delegate>)delegate;
 *@Function:    Get device ID
 *@Parameter:   IN:(id<FTaR530Delegate>)delegate:
 */
-(void)getDeviceID:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code
To get the response data, need call below API:
    FTNFCDidComplete: retData: retDataLen: functionNum: errCode:
    FT_FUNCTION_NUM_GET_DEVICEID

3.09 get the firmware version

```
#include "FT_aR530.h"
/*@Name:        +(void)getFirmwareVersion:(id<FTaR530Delegate>)delegate;
 *@Function:    Get firmware version
 *@Parameter:   IN:(id<FTaR530Delegate>)delegate:
 */
-(void)getFirmwareVersion:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code
To get the response data, need call below API:
    FTNFCDidComplete: retData: retDataLen: functionNum: errCode:
    FT_FUNCTION_NUM_GET_FIRMWAREVERSION

3.10 Connect to contactless card

```
#include "FT_aR530.h"
/*@Name:        +(void)NFC_Card_Open:(id<FTaR530Delegate>)delegate
 *@Funciton:    Open the CardReader and Connect to SmartCard
 *@Parameter:   IN:(id<FTaR530Delegate>)delegate
 */
-(void)NFC_Card_Open:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_OPEN_CARD

3.11 To disconnect with the current connected card

```
#include "FT_aR530.h"
/*@Name:   +(void)NFC_Card_Close:(nfc_card_t)card
delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Close the CardReader and Disconnect with SmartCard
 *@Parameter:   IN:(1).(nfc_card_t)card: SmartCard's handle has been Opened
 *              (2).(id<FTaR530Delegate>)delegate
 */
-(void)NFC_Card_Close:(nfc_card_t)card delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_CLOSE_CARD

3.12 Get the contactless card type

```
#include "FT_aR530.h"
/*@Name:                       +(void)NFC_Card_Recognize:(nfc_card_t)card
delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Recognize the smartcard's type
 *@Parameter:   IN: (1).nfc_card_t card: the pointer SmartCard Handle
 *              (2).(id<FTaR530Delegate>)delegate
 */
```

```
-(void)NFC_Card_Recognize:(nfc_card_t)card
delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

FT_FUNCTION_NUM_RECOGNIZE

3.13 Send command to contactless card

```
/*@Name:   +(void)NFC_Card_Transmit:(nfc_card_t)card    sendBuf:(unsigned    char
*)sendBuf sendLen:(unsigned int)sendLen delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Transmit APDU to Smart Card
 *@Parameter:   IN: (1).nfc_card_t card: The pointer of smart card handle
 *              (2).(unsigned char *)sendBuf: Send buffer
 *              (3).(unsigned int)sendLen: Send buffer length
 *              (4).(id<FTaR530Delegate>)delegate
 */


-(void)NFC_Card_Transmit:(nfc_card_t)card    sendBuf:(unsigned    char    *)sendBuf
sendLen:(unsigned int)sendLen delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

FT_FUNCTION_NUM_TRANSMIT

3.14 To authentication with current block

```
/*@Name:   +(void) Mifare_GeneralAuthenticate:(nfc_card_t)card blockNum:(unsigned
char)blockNum keyType:(unsigned  char)keyType  key:(unsigned  char   *)key
delegate:(id<FTaR530Delegate>)delegate;
 *@Funciton:    Authentication the key of Block
 *@Parameter:   IN: (1).nfc_card_t card: the pointer of smartcard handle
 *              (2).(unsigned char)blockNum: block number
 *              (3).(unsigned char)keyType: key tyep(A or B)
 *              (4).(unsigned char *)key: Authentication key
 *              (5).(id<FTaR530Delegate>)delegate
 */
```

```
-(void)    Mifare_GeneralAuthenticate:(nfc_card_t)card    blockNum:(unsigned
char)blockNum    keyType:(unsigned    char)keyType    key:(unsigned    char    *)key
delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_AUTHENTICATE

3.15 To read block (removed in new SDK)

```
/*@Name:    +(void)Mifare_ReadBinary:(nfc_card_t)card         blockNum:(unsigned
char)blockNum size:(unsigned char)size delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Read the binary data of block
 *@Parameter:   IN: (1).nfc_card_t card: The Pointer of smart card handle
 *                  (2).(unsigned char)blockNum: The block number
 *                  (3).size:(unsigned char)size: the data length to read
 *                  (4).(id<FTaR530Delegate>)delegate
 */
-(void)Mifare_ReadBinary:(nfc_card_t)card   blockNum:(unsigned char)blockNum
size:(unsigned char)size delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_READ_BINARY

3.16 To update block(removed in new SDK)

```
/*@Name:    +(void)mifare_UpdateBinary:(nfc_card_t)card blockNum:(unsigned
char)blockNum  data:(unsigned char    *)data size:(unsigned char)size
delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Update the binary data of block
 *@Parameter:   IN: (1).nfc_card_t card: The pointer of smart card handle
 *                  (2).(unsigned char)blockNum: The block number
 *                  (3).(unsigned char *)data: data buffer
 *                  (4).(unsigned char)size: data buffer length
 *                  (5).(id<FTaR530Delegate>)delegate
 */
```

```
-(void)Mifare_UpdateBinary:(nfc_card_t)card    blockNum:(unsigned    char)blockNum
data:(unsigned       char      *)data       size:(unsigned       char)size
delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

> **FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:**
> **FT_FUNCTION_NUM_UPDATE_BINARY**

3.17 To do initialization with current block

```
/*@Name:                         +(void)Mifare_ClassicBlockInitial:(nfc_card_t)card
blockNum:(unsigned char)blockNum delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Initialize the value of block
 *@Parameter:   IN: (1).nfc_card_t card: The pointer of smart card handle
 *              (2).(unsigned char)blockNum: The block number
 *              (3).(id<FTaR530Delegate>)delegate
 */
-(void)Mifare_ClassicBlockInitial:(nfc_card_t)card           blockNum:(unsigned
char)blockNum delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

> **FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:**
> **FT_FUNCTION_NUM_INIT_BLOCK**

3.18 Read value

```
/*@Name:        +(void)Mifare_ClassicReadValue:(nfc_card_t)card blockNum:(unsigned
char)blockNum delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Read the value of block
 *@Parameter:   IN: (1).nfc_card_t card: The pointer of smart card handle
 *              (2).(unsigned char)blockNum:  The block number to read
 *              (3).(id<FTaR530Delegate>)delegate
 */
-(void)Mifare_ClassicReadValue:(nfc_card_t)card blockNum:(unsigned char)blockNum
delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

> **FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:**

FT_FUNCTION_NUM_READ_VALUE

3.19 To write value

```
/*@Name:                    +(void)Mifare_ClassicStoreBlock:(nfc_card_t)card
blockNum:(unsigned    char)blockNum    valueAmount:(unsigned    int)valueAmount
delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Store value to the block
 *@Parameter:   IN: (1).nfc_card_t card: The pointer of smart card handle
 *              (2).(unsigned char)blockNum:  The block number
 *              (3).(unsigned int)valueAmount:  The value to store
 *              (4).(id<FTaR530Delegate>)delegate
 */
-(void)Mifare_ClassicStoreBlock:(nfc_card_t)card blockNum:(unsigned char)blockNum
valueAmount:(unsigned int)valueAmount delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_STORE_BLOCK

3.20 To increment value

```
/*@Name:    +(void)Mifare_ClassicIncrement:(nfc_card_t)card blockNum:(unsigned
char)blockNum  valueAmount:(unsigned int)valueAmount
    delegate:(id<FTaR530Delegate>)delegate;
 *@Function:    Increment the value of block
 *@Parameter:   IN: (1).nfc_card_t card: The pointer of smart card handle
 *              (2).(unsigned char)blockNum: The block number
 *              (3).(unsigned int)valueAmount: The value to Increment
 *              (4).(id<FTaR530Delegate>)delegate
 */
-(void)Mifare_ClassicIncrement:(nfc_card_t)card blockNum:(unsigned char)blockNum
valueAmount:(unsigned int)valueAmount delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_INCREMENT

3.21 To decrement value

```
/*@Name:+(void)Mifare_ClassicDecrement:(nfc_card_t)card    blockNum:(unsigned
char)blockNum  valueAmount:(unsigned int)valueAmount
    delegate:(id<FTaR530Delegate>)delegate;
 *@Function:   Decrement the value of block
 *@Parameter:   IN: (1).nfc_card_t card: The pointer of smart card handle
 *              (2).(unsigned char)blockNum: The block number
 *              (3).(unsigned int)valueAmount: The value to Decrement
 *              (4).(id<FTaR530Delegate>)delegate
 */
-(void)Mifare_ClassicDecrement:(nfc_card_t)card blockNum:(unsigned  char)blockNum
valueAmount:(unsigned int)valueAmount delegate:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTaR530GetInfoDidComplete: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_DECREMENT

3.22 get the device UID

```
#include "FT_aR530.h"
/*@Name:       +(void)aR530_GetDeviceUID:(id<FTaR530Delegate>)delegate;
 *@Function:   Get device UID
 *@Parameter:   IN:(id<FTaR530Delegate>)delegate:
 */
- (void)getDeviceUID:(id<FTaR530Delegate>)delegate;
```

Please refer to aR530 demo code

To get the response data, need call below API:

    FTNFCDidComplete: retData: retDataLen: functionNum: errCode:

    FT_FUNCTION_NUM_GET_FIRMWAREVERSION

3.23 API using to control buzzer

```
#include "FT_aR530.h"
/*!
 @method playSound:
 @abstract Play a sound
 @param delegate IN:(id<FTaR530Delegate>)
*/
- (void)playSound:(id<FTaR530Delegate>)delegate;
```

More information, please refer to sample code

Notice, only 1.32 and above firmware support buzzer control, if your reader not 1.32, please update to latest firmware.

3.24 API using to disable buzzer

```
#include "FT_aR530.h"
/*!
 @method disabbleConnectSound:
 @abstract disabble connect sound
 @param delegate IN:(id<FTaR530Delegate>)
*/
- (void)disabbleConnectSound:(id<FTaR530Delegate>)delegate;
```

More information, please refer to sample code

Notice, only 1.32 and above firmware support buzzer control, if your reader not 1.32, please update to latest firmware.