

FEITIAN

aR530 Datasheet



2013-12

Contents

1.1 Title	1
1.2 Introduction	1
1.3 Feature	1
1.4 Hardware configuration	2
1.5 Specification	3

1.1 Title

FEITIANaR530

1.2 Introduction

FEITIAN aR530 is a NFC contactless reader specially engineered to accommodate a range of smart card applications. Developers use it as a platform to generate and deploy related products and services. Moreover, FEITIAN aR530 is a terminal unit which can be seamlessly integrated to all major systems of operation. Additional features such as the built-in inclusive support for different smart card interfaces has facilitated the wide scale and cross industry adoption of aR530.

aR530 suits customers where security concerns are the most salient and satisfies the demand for a flexible solution for ID authentication, e-commerce, e-payment, information security and access control.

1.3 Features

- General
 - 480mHa battery inside, operational more than 3h
 - Full battery charge within 3hours
 - 3.5mm standard headphone jack &MicroUSB
 - Low battery consumption
 - Micro-USB port for pass-through charging
- Contactless part
 - Support firmware encryption upgrade
 - Supports contactless smart cards compliant with ISO 14443 type A and type B, Mifare card, Felica
 - 1x Beeper and 4x lights for reader/card/battery status

1.4 Hardware configuration

Three lights available red/blue/yellow, each respectively indicates charge battery/low battery/card status.

Card status light –blue color light

Contents	Contents	Contents
1	No card	Light OFF
2	Card detected	Light ON

Low battery light – yellow color light

Number	Progress	Status
1	Full battery	Light OFF
2	Low battery	Light ON

Charge battery light – red color light

Number	Progress	Status
1	Charging completed	Light OFF
2	Charging	Light ON

1.5 Specification

Type	Comments	
Basic Parameters	Specification	Parameters
	Working Current	50-80mA
	Communication Rate	8000bps
	Supported Card Type	ISO 14443 standard Type A/B, Mifare, Felica, Mifare tag 1
	Working Temperature	0°C to 50°C (32 to 122°F)
	Storage Temperature	- 20°C to 70°C (-4 to 158°F)
	Operating Humidity	0 to 90%RH non-condensing
	Storage Humidity	0 to 90%RH non-condensing
	Size	59*50*12mm
	Port	3.5mm audio jack/Micro USB(Type B)
	Supported OS	Android 2.2+/iOS4.3+/Windows/Linux/Mac OS X (For PC platform OEM necessary)
	Certification	CE/FCC/RoHS
	Lights	Red/Yellow/Blue
Hardware Security	Support Card short circuit protection Support firmware upgrading	
Battery	Power	480mHa
	Charging time	3hours
	Max work time(full speed)	App 3 hours or 1700 readings
Custom items	Casing	OEM available
	Logo	Custom logo
	Firmware	OEM firmware available

1.6 Key Applications

Mobile payment (payment by NFC card)

Authentication, access control (Secure application login)

Access to digital information (Read schedules from start poster to NFC tag/ Read name card from NFC tag)

Ticketing (Store theater/attraction/event ticket on NFC card)