SkillPass: Technical Report

Final Version of the Product · An assessor-verified skills passport for informal artisans in Nigeria, with escrow job payments

Fejiro Obiku · BSc Software Engineering, African Leadership University · Supervisor: Tunde Isiaq Gbadamosi · October 2026 ·
Live: skillpasssss.vercel.app · Code: github.com/Fejiroobiku/skillpasssss · Video: youtu.be/U8pesWQt8CI

1. Scope alignment and feature validation

SkillPass is a full-stack web application: a React and TypeScript single-page app talks to a REST API (Node.js 22, Express 5) backed by PostgreSQL. Table 1 maps every module in the approved proposal (Table 6 of the proposal), plus the features added after supervisor feedback, to its current state. The roles are called Assessor and Artisan in the app (internally still trainer and apprentice). Screenshots are in docs/screenshots; paths are relative to the repository root.

Planned feature	Intended purpose	Current status	Evidence
Accounts and roles	Role-based access; assessors approved before issuing; each artisan linked to an assessor	Completed	routes/auth.js, middleware/auth.js; 13_register.jpg; tests: "authentication", "bootstrap"
Skill framework	Checklists per trade by level; assessors propose skills; Advanced skills need a co-signer	Completed	routes/skills.js, routes/admin.js; tests: "skills and trades"
Credential issuing	Assessor records an observed skill with live evidence; signed, timestamped, unique ID	Completed	routes/credentials.js, routes/evidence.js, lib/signing.js; 03_issue_credential.jpg; tests: "issuing a credential"
Skills passport	Shareable, printable record of verified skills	Completed	routes/passport.js (revocable link + QR); 05_apprentice_passport.jpg; tests: "public passport"
Public verification	Anyone checks a credential by ID, link or QR, no login	Completed	routes/verify.js; 01_verify_valid.jpg, 02_verify_revoked.jpg; tests: "public verification"
Integrity safeguards	Evidence first, co-signing, issuing limit, random audits, flag/revoke, trust score, append-only log	Completed	lib/scoring.js, lib/integrity.js, lib/auditChain.js; 09_review_queue.jpg, 10_audit_log.jpg; tests: "flags and disputes", "risk and misconduct"
Job referral and ratings	Rank verified artisans by skill and distance; employers and artisans rate each other	Partial	lib/matching.js, routes/jobs.js, routes/feedback.js; 07, 08 jpg. In-app alerts work; SMS in console mode until a Termii sender ID is approved
Job agreements and escrow (added 26 Oct)	Quotes split materials from workmanship; employer pays into escrow before work; release on confirmation; disputes decided by admin	Completed (test mode)	lib/escrow.js, lib/payments.js, routes/agreements.js; 14_employer_hires.jpg, 15, 16, 18 jpg; tests: agreements.test.js (18)
Terms of Service (added 26 Oct)	Plain-language terms in English and Pidgin, accepted at sign-up and before each job	Completed	src/data/terms.ts, lib/terms.js; 17_terms.jpg; tests: "Terms of Service"
Administration	Approve accounts, manage skills, review flags, audits and disputes	Completed	routes/admin.js, routes/agreements.js; 09, 11, 16 jpg; tests: "admin extras", "disputes"
Deployment and pilot	Hosted app; run the pilot with real users in Lagos	Partial	Live demo on Vercel + Render + Neon (README). The live pilot waits for ethics approval (submitted 23 Oct 2026)

Table 1. Planned features from the approved proposal and their current status.




Figure 1. Core features: an assessor issues a credential against the rubric (top left); public verification with signature check and QR code (top right); an employer's hires with money held in escrow (bottom left); an administrator deciding a job dispute from the photos and scope (bottom right).

Justified scope changes

Added after supervisor feedback (26 Oct 2026). My supervisor asked how price, materials and payment disputes between employers and artisans would work, and noted that the person checking a skill is not always the one who taught it. In response, jobs now carry quotes that separate materials from workmanship, payment is held in escrow with before/after photos and an administrator-decided dispute process, artisans also rate employers, a plain-language Terms of Service governs all of it, and the roles were renamed Assessor and Artisan.

Added after ethics feedback. SMS phone verification, email verification and password reset; Nigerian Pidgin; an offline upload queue; artisan-controlled passport links; a confidential report channel; consent withdrawal that removes personal data (NDPA 2023); a hash-chained audit log; and expiring signed evidence links.

Partial or deferred. Real SMS delivery is implemented (TermiiSmsChannel) but switched to console mode, because Nigerian networks require an approved sender ID for messages to reach Do-Not-Disturb numbers. Payments run in test mode (simulated, or Paystack with a test key); live money waits for ethics approval, as does the real pilot. NIN integration, native apps, blockchain anchoring and NSQ integration stay out of scope.

2. Technical functionality

Architecture. The frontend (src/) is organised by role (pages/trainer, apprentice, employer, admin, public) with shared components, an auth context and a typed API client. The backend (backend/src) separates HTTP routes (one file per area) from domain logic in lib/ (scoring, matching, signing, storage, messaging, payments, escrow, audit chain, privacy). It is deployed on Render, the frontend on Vercel and the database on Neon PostgreSQL. Every request body is validated with Zod; every protected route checks the JWT and the role on the server; database writes that must stay consistent run in transactions.




Figure 2. System architecture: the browser app talks to the REST API over HTTPS; domain logic lives in classes under backend/src/lib.

Core flow: issuing and verifying a credential. (1) The assessor gets a one-time challenge code (15 minutes). (2) The app records a live video showing it; the upload is checked by magic bytes, hashed with SHA-256 on the server and refused if that hash already backs another credential. (3) The assessor ticks the rubric and signs; the API locks the assessor row (SELECT … FOR UPDATE) so two requests cannot both slip under the daily limit, applies probation and co-sign rules, signs the credential with HMAC-SHA256 and logs it. (4) The artisan confirms; only then is it valid. (5) /verify/:id recomputes the signature and the live trust score.

Core flow: hiring with escrow. (1) The artisan quotes workmanship, plus materials if they buy them. (2) The employer offers an agreement with a written scope; both accept the job terms, and the Terms version is stored on the agreement. (3) The employer pays the full amount through the PaymentGateway; on confirmation the agreement moves to in progress and a materials payout is queued. (4) The artisan adds live before/after photos and marks the job done, which starts a review period (3 days). (5) The employer confirms, the period runs out (automatic release), or either side disputes, which freezes the money until an administrator splits it 0–100%. Database changes create pending payment rows inside one transaction; calls to the provider run after commit, so a slow or failed provider never leaves the data half-changed.

Testing with different inputs. The API returns specific, actionable errors and the UI shows them: wrong password or suspended account (401/403); an under-18 date of birth at sign-up (400, "SkillPass pilot participants must be 18 or older"); a reused challenge code (400); a duplicate evidence file (409, also written to the audit log); a credential beyond the daily limit (held for review); confirming someone else's credential (404); an unknown credential ID ("Not found" page); an edited or expired evidence link (403); a tampered credential signature ("Signature does not match"); a job offer without accepting the terms, paying before the artisan accepts, marking a job done without photos, a second open dispute, or a non-admin deciding one (400/403/409). All are covered by automated tests.

3. Testing strategies and results

Strategy	Why chosen	How conducted	Result and improvement made
Unit testing	The integrity logic (trust, risk, matching, signed links) must be exactly right and is easy to test in isolation	37 Node test-runner tests on the domain classes with fixed clocks and fake inputs, including the Paystack gateway against a fake network (kobo amounts, HMAC-SHA512 webhooks); no database	37/37 pass. Found a time-boundary edge in the signed-link test; fixed the test clock
Integration (API + DB)	Integrity rules depend on SQL, transactions and locks working together	100 tests run the Express app against a real PostgreSQL database, wiped and re-seeded per run, including the whole escrow flow, automatic release and disputes	100/100 pass. Found a seed notice that told an assessor about a pending audit; replaced it
End-to-end UI	Shows that real screens and the real API work together	24 Vitest + Testing Library tests render the app against the running API; Playwright walks every page and the full hiring flow	24/24 pass. Found a passport crash, phone-width overflow and a one-option trade dropdown; all fixed
Security	Evidence and records are sensitive; claims in the ethics application must hold	Forged, edited and expired evidence links; tampered signatures; audit-log tampering with triggers disabled; access across roles	All pass. Found that evidence was served by a permanent address; added expiring HMAC-signed links

Strategy	Why chosen	How conducted	Result and improvement made
Performance and compatibility	Users have low-cost Android phones on 3G/4G	Playwright + Chrome DevTools throttling (CPU and network); API load test; 4 screen sizes (Section 4)	Cut JavaScript by 44% and first-load time by 16–27% on a low-end phone (Section 4)

Table 2. Testing strategies. Totals: 161 automated tests (137 backend, 24 frontend), all passing; TypeScript and ESLint report 0 errors.

4. Performance and compatibility

Method. The production build was served with gzip, as Netlify or Vercel would, and each page was loaded with an empty cache 5 times per profile in Chromium, using Chrome DevTools Protocol throttling. Medians are reported. "Ready" is the time until the page's main content is visible.

Profile and page	Before: ready	After: ready	JS before → after	Change in ready time
Low-end Android (6× CPU, 3G): sign-in	2.69 s	1.96 s	243 → 135 KB	27% faster
Low-end Android: employer verifies a credential	3.23 s	2.54 s	243 → 135 KB	21% faster
Low-end Android: artisan passport (signed in)	4.18 s	3.50 s	243 → 146 KB	16% faster
Mid-range Android (4× CPU, 4G): sign-in	1.41 s	0.91 s	243 → 135 KB	35% faster
Desktop broadband: sign-in	0.44 s	0.43 s	243 → 135 KB	No real change

Table 3. Page performance before and after on-demand page loading (median of 5 cold loads). The gain is largest on slow phones and networks, where it matters for this pilot; on fast desktops the difference is negligible. JavaScript heap on the low-end verify page fell from 5.6 to 4.3 MB.

What changed and why. The first build shipped one 574 kB JavaScript bundle. Splitting every page into its own file reduced the download but, measured on 3G, made content appear later: the browser fetched the main file, then checked the account, and only then requested the page file. The final version keeps the public entry pages (sign-in, register, verify, passport) in the main bundle and, for a signed-in user, starts fetching their role's pages in parallel with the account check (src/pageLoaders.ts). The verify page, the target metric in the proposal (under 1 minute), is ready in 2.5 s on the slowest profile.

API under load. With 10 concurrent clients on a 2-core test machine: public verification took a median of 34 ms (p95 81 ms) at about 260 requests per second; an artisan's full data load 47 ms (p95 59 ms); the heaviest request, an administrator's data with live trust and risk for every assessor, 147 ms (p95 192 ms). There were no failures.

Compatibility. Every screen was checked at 360 px (low-end Android), 390 px (iPhone-size), 768 px (tablet) and 1366 px (laptop) for horizontal overflow; after fixes, none overflows (docs/screenshots/compat_*.jpg). Automated runs used Chromium, the engine behind Chrome, Edge and Opera, the browsers most common on Android in Nigeria. Firefox and Safari were not available in the test environment and are shown in the walkthrough video. The deployed demo runs on free tiers; the API sleeps when idle, so the first request after a pause takes up to a minute. The app targets modern evergreen browsers (ES2020, CSS custom properties) and needs no plug-ins; the camera uses the standard MediaRecorder API, and a browser that cannot record gets a clear message instead of a broken screen.




Figure 3. The public verification page at 1366, 768, 390 and 360 px wide: no horizontal scrolling, header kept on one line.

5. Code quality, OOP and algorithms

Object-oriented design

Class or module	OOP principle shown	Benefit
MessageChannel → HttpChannel → TermiiSmsChannel, ResendEmailChannel; ConsoleChannel (lib/messaging.js)	Abstraction (abstract base refuses direct use), inheritance, polymorphism: callers only call send()	Switch SMS or email provider in .env; adding Africa's Talking is one subclass. Tested with a fake fetch
PaymentGateway → PaystackGateway, SimulatedGateway (lib/payments.js)	Abstraction and polymorphism: routes call startCheckout(), confirm(), payout(), refund() without knowing the provider	Demo runs with no money; Paystack test mode is one setting; Flutterwave would be one subclass. Live keys are refused at start-up
RiskRule → FastIssuingRule, PassesEveryoneRule, ClusteredDayRule, PoorRatingsRule, OpenReportsRule; RiskAssessor (lib/scoring.js)	Strategy pattern, open/closed principle: new warning signs are added as classes without editing the assessor	Rules are tested one by one; a test injects a custom NightShiftRule to prove polymorphism
TrustScoreCalculator (lib/scoring.js)	Encapsulation: weights validated and frozen; constants named	Weights can be tuned during the pilot without touching the formula
JobMatcher (lib/matching.js)	Encapsulation of matching weights and the distance cap	Configurable per trade or city; validated inputs
EvidenceStore → LocalDiskStore; SignedUrlSigner (lib/storage.js, lib/signedUrls.js)	Abstraction with dependency injection; private methods (#mac) hide the key	A cloud store (Supabase) can replace disk storage with one subclass; links can't be forged
React components and contexts (src/components, src/contexts)	Composition, separation of concerns, reusable components (PassportView, ScoreRing, EvidenceCapture)	The same passport view serves artisan, assessor, employer and public pages; job parts (AgreementSteps, MoneyBreakdown, DisputeThread) serve employer, artisan and admin

Table 4. Object-oriented structure. The existing function names (computeTrust, rankMatches, sendSms…) remain as thin wrappers, so no route had to change.

Algorithms and technical problem-solving

- **Job matching:** haversine great-circle distance plus a weighted score (70% skills held, 30% closeness within 30 km), using Set look-ups, O(n·k + n log n) for n artisans and k skills.
- **Fraud signals:** one pass over time-sorted credentials finds pairs signed minutes apart, O(n log n); a hash map counts credentials per Lagos calendar day, O(n).
- **Unbiased random audits:** a Fisher–Yates shuffle driven by a cryptographic random source (crypto.randomInt) selects the audit sample, so every credential is equally likely to be picked and the choice cannot be predicted.
- **Tamper evidence:** each audit entry stores HMAC(previous hash, entry), forming a hash chain; verification walks the chain in O(n) and pinpoints the first broken link. Credentials and evidence links are HMAC-SHA256 signed and compared in constant time (timingSafeEqual) to resist timing attacks.
- **Escrow settlement:** a percentage split of held workmanship (artisan share rounded, remainder refunded, so no naira is lost); overdue reviews are released in one indexed sweep; Paystack webhooks are verified with HMAC-SHA512 in constant time and re-checked with Paystack before money is marked as received.
- **Data integrity under concurrency:** row-level locks and transactions enforce the daily issuing limit and probation rules even when two requests arrive at the same moment; a unique index on the evidence hash blocks reuse in O(1).
- **Weak-signal resilience:** an IndexedDB queue keeps failed uploads per user and retries them when the connection returns; each evidence link expiry is rounded to the minute so repeated loads hit the browser cache.

Quality practices

TypeScript strict checks and ESLint (0 errors); PascalCase classes, camelCase functions, files by feature; folders by responsibility; validation at every API boundary; start-up checks that refuse missing, reused or live-payment secrets; comments that explain why; about 30 descriptive commits; a README with setup, versions and structure. Next steps: 51 lint warnings, real SMS (sender ID pending), live payments and the pilot (ethics approval pending), and an EU-region database before real participants join.