

Lab 1 (50 pts)**TA: Mose Yoloye****Email: myoloye@scu.edu****Office Hours: Monday & Wednesday 1:15-2:15 EC 608C****Objectives: Learn**

- Learn the basics of logging into Oracle database
- Use SQLPLUS (Oracle's SQL interface) to create tables.
- Load the tables with values.
- Perform simple SQL queries to retrieve data from the tables.
- Execute SQL from a file.

Note: There are three files you will use for this lab: a) Lab1.doc b) load_data.php and c) staff.txt

Logging into Oracle

1. Open PuTTY and connect to Linux m/c.
Host Name: linux.dc.engr.scu.edu
Connection type: SSH
Click on Open button
2. Login to Linux m/c
Enter User name: 8 letters, 1 from your first name and 7 from your last name
Enter Password: Your student ID or other if you have changed it
3. Setup Oracle database
setup oracle
4. Logon to Oracle server
sqlplus <username>@db11g

Your Oracle username will be identical to your DC username, but the password is independent. (By default your password is set to your Access Card number with *ALL* the leading zeroes)

Now you are at SQL> prompt

To **change password**, at SQL prompt, run password as shown below
SQL> password

Check <http://wiki.helpme.engr.scu.edu/index.php/Oracle>

PART 1 (20 pts)

In this part, you will issue SQL statements from the command line.

Creating a Table (or two)

At SQL> prompt, **type the following lines to create a table called trial, with two attributes, tnum (an integer) and str (a string of 10 characters).**

```
CREATE TABLE trial (  
    tnum    int,  
    str     char(10)  
);
```

Note: SQL is NOT case-sensitive. You may enter text on one line or on several lines. If your command runs over several lines, you will be prompted with line numbers until you type the semicolon that ends any command.

Do you see the message, Table created, at SQL prompt? -----

Inserting Tuples

Now we need to add some data tuples into table, trial.

Type the following SQL statement:

```
INSERT INTO trial VALUES (1,'A test');
```

You should see the message, "1 row created".

Insert at least 2 more tuples with values of your choice.

Simple Queries to get data from the table

At the SQL prompt, **type the following statement, to retrieve all the rows in the table, trial.**

```
SELECT * FROM trial;
```

Do you see all the tuples you have entered in the table?

To retrieve only the values for the attribute, tnum, type the following SQL command:

```
SELECT tnum FROM trial;
```

Now, try to enter a duplicate tuple (1,'A test') into trial, with the statement:

```
INSERT INTO trial VALUES (1,'A test');
```

Did you succeed in adding a duplicate tuple?

Type the statement, SELECT * FROM trial;

You were able to add a duplicate tuple because we did not define a primary key on the table.

Let us create another table with a primary key.

```
CREATE TABLE test (  
    tnum    int,  
    str     char(10),  
    PRIMARY KEY(tnum)  
);
```

Add a tuple into test. Type the following SQL statement:

```
INSERT INTO test VALUES (1,'A test');
```

Now, try to enter a duplicate tuple (1,'A test') into test, with the statement:

```
INSERT INTO test VALUES (1,'A test');
```

Did you succeed in adding a duplicate row? -----

Getting Meta Information about your Database

The system keeps information about your database (the tables and constraints etc, that you have created) in certain system tables. You can retrieve the names of the tables that you have created from the system table, USER_TABLES. Type the following query:

```
SELECT TABLE_NAME
```

```
FROM USER_TABLES;
```

Do you see the tables (trial and test) that you have created so far?

*******PLEASE DEMO BEFORE MOVING ON TO THE NEXT STEP!*******

Removing your tables from the database

Now, remove the table, trial from the database with the statement,

```
DROP TABLE trial;
```

Now, execute the query to get the table names from USER_TABLES.

```
SELECT TABLE_NAME
```

```
FROM USER_TABLES;
```

What do you see?

Part 2 (10 pts)

Capturing and Recording your Session

One way to capture your SQL session is to use the spool command that SQLPLUS provides to save query results to a file. At the SQL> prompt, type spool <filename>. For example,

```
SQL> spool foo;
```

This will create a **foo.lst** file in the current directory and will capture all input and output during your session at SQLPLUS (until you exit SQL).

You can terminate the capture with the command, **spool off;**

*******Turn in the foo.lst file for submission. Terminate the session at the end of part 2.*******

In this part, you will learn to execute SQL commands from a script file.

Step 1: Create a folder structure called COEN178/labs/lab1.

Step 2: Create a text file called **data.sql**. This file will contain the SQL statements that you want to execute.

You have a couple of options to create the text file:

A) Using a text editor (gvim, for example), create the file and include the SQL statements.

B) At SQL prompt, you can type the command, edit <filename>. This will open up the default editor (vi, for example, in Unix environment) and you can type the SQL statements and save the file under COEN178/labs/lab1 directory. You can also set the editor of your choice as follows:

```
SQL> DEFINE _EDITOR = "vim"
```

```
SQL>edit data.sql
```

(This will open up the new file in the editor). Now type the following statements to insert values into the table test.

```
INSERT INTO test VALUES (10,' ten');
```

```
INSERT INTO test VALUES (11,' eleven');
```

You can type more statements to insert values of your choice.

Now, to execute the commands from the script file, data.sql as follows:

```
SQL> start <Path/filename>
```

or

```
SQL> @<Path/filename>.
```

For example,

```
SQL> start /home/<user>/COEN178/labs/lab1/data.sql
```

or

```
SQL> @/home/<user>/COEN178/labs/lab1/data.sql
```

Now, check if the data you have entered has been loaded into the table successfully, by issuing the SQL query, SELECT * from test;

Issuing operating system commands from SQL

You can issue host operating system commands from SQL as follows:

Assuming you are accessing Oracle on Unix systems, you can list the contents of the current directory as

SQL> host ls

To see your current directory,

SQL> host pwd

*******Turn off your spool here*******

Part 3 (20 pts)

Oracle SQL Datatypes, Reference: <http://www.ss64.com/orasyntax/datatypes.html>

You should capture the session (queries and output) into a file called, lab1_part3.lst.

Step 1:

Create a table called Staff_2010 as follows:

```
CREATE table Staff_2010 (Last VARCHAR(20),First VARCHAR(20),status
VARCHAR(20),salary NUMBER(10,2),salary_type VARCHAR(40),title
VARCHAR(200));
```

Step 2:

Load values into the table from a text file (staff.txt) using the PHP script file, **load_data.php.**

Move the provided load_data.php and staff.txt files into your webpages folder (cd /webpages/<your username>)

Make sure to change the username and password in the file

Execute the PHP script, load_data.php:

Change file permissions on the script file to -rwxrwxrwx. (chmod 777 load_data.php)

Open a browser and type the URL

http://linux.students.engr.scu.edu/~<username>/load_data.php

Step 3:

Type the command below from SQL prompt:

Select * from Staff_2010;

How many rows are retrieved from the table -----

Type the command below from SQL prompt:

Commit;

This will ensure the data you have entered will be in the table even if the system crashes.

Now you are ready to issue queries against the table **staff_2010**.

- Write a SQL query to show all lastnames from the table staff_2010.
- Write a SQL query to show all first names concatenated with last names (concatenation operator is ||) and the column in the result renamed as fullname, from the table staff_2010.