

1. Description

1.1. Project

Project Name	STM32_EMB
Board Name	NUCLEO-H743ZI2
Generated with:	STM32CubeMX 6.9.1
Date	09/16/2023


1.2. MCU

MCU Series	STM32H7
MCU Line	STM32H743/753
MCU name	STM32H743ZITx
MCU Package	LQFP144
MCU Pin number	144

1.3. Core(s) information

Core(s)	ARM Cortex-M7

2. Pinout Configuration



3. Pins Configuration


Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
6	VBAT	Power		
7	PC13	I/O	GPIO_EXTI13	BTN
8	PC14-OSC32_IN (OSC32_IN)	I/O	RCC_OSC32_IN	
9	PC15-OSC32_OUT (OSC32_OUT)	I/O	RCC_OSC32_OUT	
16	VSS	Power		
17	VDD	Power		
23	PH0-OSC_IN (PH0)	I/O	RCC_OSC_IN	
24	PH1-OSC_OUT (PH1) *	I/O	RCC_OSC_OUT	
25	NRST	Reset		
27	PC1	I/O	ETH_MDC	
30	VDD	Power		
31	VSSA	Power		
33	VDDA	Power		
35	PA1	I/O	ETH_REF_CLK	
36	PA2	I/O	ETH_MDIO	
38	VSS	Power		
39	VDD	Power		
43	PA7	I/O	ETH_CRS_DV	
44	PC4	I/O	ETH_RXD0	
45	PC5	I/O	ETH_RXD1	
46	PB0 **	I/O	GPIO_Output	LD1 [Green Led]
47	PB1	I/O	ADC1_INP5	
51	VSS	Power		
52	VDD	Power		
61	VSS	Power		
62	VDD	Power		
71	VCAP	Power		
72	VDD	Power		
74	PB13	I/O	ETH_TXD1	
75	PB14 **	I/O	GPIO_Output	LD3 [Red Led]
77	PD8	I/O	USART3_TX	STLINK_RX
78	PD9	I/O	USART3_RX	STLINK_TX
79	PD10 **	I/O	GPIO_Output	USB_OTG_FS_PWR_EN
83	VSS	Power		

Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
84	VDD	Power		
92	PG7	I/O	GPIO_EXTI7	USB_OTG_FS_OVCR
94	VSS	Power		
95	VDD33_USB	Power		
100	PA8	I/O	USB_OTG_FS_SOF	
101	PA9	I/O	USB_OTG_FS_VBUS	
103	PA11	I/O	USB_OTG_FS_DM	
104	PA12	I/O	USB_OTG_FS_DP	
106	VCAP	Power		
107	VSS	Power		
108	VDD	Power		
120	VSS	Power		
121	VDD	Power		
126	PG11	I/O	ETH_TX_EN	
128	PG13	I/O	ETH_TXD0	
130	VSS	Power		
131	VDD	Power		
138	воото	Boot		
142	PE1 **	I/O	GPIO_Output	LD2 [Yellow Led]
143	PDR_ON	Reset		
144	VDD	Power		

^{**} The pin is affected with an I/O function

^{*} The pin is affected with a peripheral function but no peripheral mode is activated

4. Clock Tree Configuration



Page 5

5. Software Project

5.1. Project Settings

Name	Value
Project Name	STM32_EMB
Project Folder	C:\Users\Felipe\STM32CubeIDE\workspace_1.0.2\STM32_EMB
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_H7 V1.11.1
Application Structure	Advanced
Generate Under Root	Yes
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power	No
consumption)	
Enable Full Assert	No

5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_DMA_Init	DMA
4	MX_USART3_UART_Init	USART3
5	MX_USB_OTG_FS_PCD_Init	USB_OTG_FS
6	MX_TIM3_Init	TIM3
7	MX_ETH_Init	ETH
8	MX_ADC1_Init	ADC1

1. Power Consumption Calculator report

1.1. Microcontroller Selection

Series	STM32H7
Line	STM32H743/753
мси	STM32H743ZITx
Datasheet	DS12110_Rev8

1.2. Parameter Selection

Temperature	25
Vdd	3.0

1.3. Battery Selection

Battery	Alkaline(9V)	
Capacity	625.0 mAh	
Self Discharge	0.3 %/month	
Nominal Voltage	9.0 V	
Max Cont Current	200.0 mA	
Max Pulse Current	0.0 mA	
Cells in series	1	
Cells in parallel	1	


1.4. Sequence

	1	
Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.0	3.0
Voltage Source	Battery	Battery
Range	VOS0: Scale0-High	SVOS5: System-Scale5
D1 Mode	DRUN/CRUN	DSTANDBY
D2 Mode	DRUN	DSTANDBY
D3 Mode	DRUN	DSTOP
Fetch Type	ITCM	NA
CPU Frequency	480 MHz	0 Hz
Clock Configuration	HSE BYP PLL	Flash-OFF
Clock Source Frequency	24 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	148 mA	150 μΑ
Duration	0.1 ms	0.9 ms
DMIPS	1027.0	0.0
Ta Max	105.46	124.98
Category	In DS Table	In DS Table

1.5. Results

Sequence Time	1 ms	Average Current	14.94 mA
Battery Life	1 day, 17 hours	Average DMIPS	1027.2001
	-	-	DMIPS

1.6. Chart



2. Peripherals and Middlewares Configuration

2.1. ADC1

IN5: IN5 Single-ended

2.1.1. Parameter Settings:

ADCs_Common_Settings:

Mode Independent mode

ADC_Settings:

Clock Prescaler Asynchronous clock mode divided by 2 *

Resolution * ADC 12-bit resolution *

Scan Conversion Mode Enabled

Continuous Conversion Mode Enabled *

Discontinuous Conversion Mode Disabled

End Of Conversion Selection End of single conversion

Overrun behaviour Overrun data preserved

Left Bit Shift No bit shift

Conversion Data Management Mode

DMA Circular Mode *

Low Power Auto Wait Disabled

ADC_Regular_ConversionMode:

Enable Regular Conversions Enable
Enable Regular Oversampling Disable
Number Of Conversion 10 *

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None Rank 1

Channel Channel 5
Sampling Time 1.5 Cycles
Offset Number No offset
Rank 2 *

ChannelChannel 5Sampling Time1.5 CyclesOffset NumberNo offset

Rank 3 *

Channel Channel 5
Sampling Time 1.5 Cycles
Offset Number No offset
Rank 4 *

Channel Channel 5
Sampling Time 1.5 Cycles

Offset Number No offset

Rank 5 *

Channel 5 Channel 1.5 Cycles Sampling Time No offset Offset Number Rank 6 *

Channel Channel 5 1.5 Cycles Sampling Time Offset Number No offset Rank

Channel Channel 5 Sampling Time 1.5 Cycles Offset Number No offset

7 *

Rank 8 *

Channel 5 Channel Sampling Time 1.5 Cycles Offset Number No offset Rank 9 *

Channel 5 Channel Sampling Time 1.5 Cycles No offset Offset Number Rank 10 *

Channel Channel 5 Sampling Time 1.5 Cycles No offset Offset Number

ADC_Injected_ConversionMode:

Disable **Enable Injected Conversions**

Analog Watchdog 1:

Enable Analog WatchDog1 Mode false

Analog Watchdog 2:

Enable Analog WatchDog2 Mode false

Analog Watchdog 3:

Enable Analog WatchDog3 Mode false

2.2. ETH

Mode: RMII

2.2.1. Parameter Settings:

General: Ethernet Configuration:

Warning The ETH can work only when RAM is pointing at 0x24000000

Ethernet MAC Address 00:80:E1:00:00:00

Tx Descriptor Length 4

First Tx Descriptor Address 0x30000200 *

Rx Descriptor Length 4

First Rx Descriptor Address 0x30000000 *

Rx Buffers Length 1524

2.3. RCC

High Speed Clock (HSE): BYPASS Clock Source Low Speed Clock (LSE): Crystal/Ceramic Resonator

2.3.1. Parameter Settings:

Power Parameters:

SupplySource PWR_LDO_SUPPLY

Power Regulator Voltage Scale 2 *

RCC Parameters:

TIM Prescaler Selection Disabled
HSE Startup Timout Value (ms) 100
LSE Startup Timout Value (ms) 5000
CSI Calibration Value 16
HSI Calibration Value 32

System Parameters:

VDD voltage (V) 3.3

Flash Latency(WS) 1 WS (2 CPU cycle)

Product revision rev.Y

PLL range Parameters:

PLL1 clock Input range

Between 8 and 16 MHz

PLL2 input frequency range

Between 8 and 16 MHz

PLL1 clock Output range

MEDIUM VCO range

PLL2 clock Output range

MEDIUM VCO range

2.4. SYS

Timebase Source: SysTick

2.5. TIM3

Clock Source: Internal Clock

2.5.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 6399 *

Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 1500 *

Internal Clock Division (CKD) No Division auto-reload preload Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection TRGO Reset (UG bit from TIMx_EGR)

2.6. USART3

Mode: Asynchronous

2.6.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples
Single Sample Disable
ClockPrescaler 1
Fifo Mode Disable

Txfifo Threshold 1 eighth full configuration Rxfifo Threshold 1 eighth full configuration

Advanced Features:

Auto Baudrate Disable TX Pin Active Level Inversion Disable **RX Pin Active Level Inversion** Disable Data Inversion Disable TX and RX Pins Swapping Disable Enable Overrun DMA on RX Error Enable MSB First Disable

2.7. USB_OTG_FS

Mode: Device_Only

Activate_VBUS: VBUS sensing

mode: Activate_SOF

2.7.1. Parameter Settings:

Speed Full Speed 12MBit/s

Enable internal IP DMA Disabled

Low power Disabled

Battery charging Enabled

Link Power Management Disabled

Use dedicated end point 1 interrupt Disabled

VBUS sensing Enabled

Signal start of frame Enabled

^{*} User modified value

3. System Configuration

3.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
ADC1	PB1	ADC1_INP5	Analog mode	No pull-up and no pull-down	n/a	
ETH	PC1	ETH_MDC	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA1	ETH_REF_CLK	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA2	ETH_MDIO	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA7	ETH_CRS_DV	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PC4	ETH_RXD0	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PC5	ETH_RXD1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PB13	ETH_TXD1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PG11	ETH_TX_EN	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PG13	ETH_TXD0	Alternate Function Push Pull	No pull-up and no pull-down	Low	
RCC	PC14- OSC32_IN (OSC32_IN)	RCC_OSC32_IN	n/a	n/a	n/a	
	PC15- OSC32_OU T	RCC_OSC32_O UT	n/a	n/a	n/a	
	PH0- OSC_IN (PH0)	RCC_OSC_IN	n/a	n/a	n/a	
USART3	PD8	USART3_TX	Alternate Function Push Pull	No pull-up and no pull-down	Low	STLINK_RX
	PD9	USART3_RX	Alternate Function Push Pull	No pull-up and no pull-down	Low	STLINK_TX
USB_OTG_ FS	PA8	USB_OTG_FS_ SOF	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA9	USB_OTG_FS_ VBUS	Input mode	No pull-up and no pull-down	n/a	
	PA11	USB_OTG_FS_ DM	Alternate Function Push Pull	No pull-up and no pull-down	Low	
	PA12	USB_OTG_FS_ DP	Alternate Function Push Pull	No pull-up and no pull-down	Low	
Single Mapped Signals	PH1- OSC_OUT (PH1)	RCC_OSC_OUT	n/a	n/a	n/a	
GPIO	PC13	GPIO_EXTI13	External Interrupt Mode with Falling edge trigger detection	No pull-up and no pull-down	n/a	BTN
	PB0	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD1 [Green Led]
	PB14	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD3 [Red Led]
	PD10	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	USB_OTG_FS_PWR_EN

IP	Pin	Signal	GPIO mode	GPIO pull/up pull	Max	User Label
				down	Speed	
	PG7	GPIO_EXTI7	External Interrupt Mode with Rising edge trigger detection	No pull-up and no pull-down	n/a	USB_OTG_FS_OVCR
	PE1	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD2 [Yellow Led]

3.2. DMA configuration

DMA request	Stream	Direction	Priority
ADC1	DMA2_Stream0	Peripheral To Memory	Low

ADC1: DMA2_Stream0 DMA request Settings:

Mode: Circular *
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable *
Peripheral Data Width: Word *
Memory Data Width: Word *

3.3. BDMA configuration

nothing configured in DMA service

3.4. MDMA configuration

nothing configured in DMA service

3.5. NVIC configuration

3.5.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority		
Non maskable interrupt	true	0	0		
Hard fault interrupt	true	0	0		
Memory management fault	true	0	0		
Pre-fetch fault, memory access fault	true	0	0		
Undefined instruction or illegal state	true	0	0		
System service call via SWI instruction	true	0	0		
Debug monitor	true	0	0		
Pendable request for system service	true	0	0		
System tick timer	true	0	0		
TIM3 global interrupt	true	0	0		
EXTI line[15:10] interrupts	true	0	0		
DMA2 stream0 global interrupt	true	0	0		
PVD and AVD interrupts through EXTI line 16	unused				
Flash global interrupt	unused				
RCC global interrupt	unused				
ADC1 and ADC2 global interrupts	unused				
EXTI line[9:5] interrupts	unused				
USART3 global interrupt	unused				
Ethernet global interrupt	unused				
Ethernet wake-up interrupt through EXTI line 86	unused				
FPU global interrupt	unused				
USB On The Go FS End Point 1 Out global interrupt	unused				
USB On The Go FS End Point 1 In global interrupt	unused				
USB On The Go FS global interrupt	unused				
HSEM1 global interrupt		unused			

3.5.2. NVIC Code generation


Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false

Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true
TIM3 global interrupt	false	true	true
EXTI line[15:10] interrupts	false	true	true
DMA2 stream0 global interrupt	false	true	true

^{*} User modified value

4. System Views


- 4.1. Category view
- 4.1.1. Current



Power Domain view

Category view

4.1.2. Without filters



4.2. Power Domain view

Category view Power Domain view



5. Docs & Resources

Type Link

BSDL files https://www.st.com/resource/en/bsdl_model/stm32h7_bsdl.zip

IBIS models https://www.st.com/resource/en/ibis_model/stm32h7_ibis.zip

System View https://www.st.com/resource/en/svd/stm32h7-svd.zip

Description

Presentations https://www.st.com/resource/en/product_presentation/microcontrollers_st

m32h7_series_product_overview.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_embedded_software_solutions.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_eval-

tools_portfolio.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_stm8_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_software_development_tools.pdf

Brochures https://www.st.com/resource/en/brochure/brstm32h7.pdf

Brochures https://www.st.com/resource/en/brochure/brstm32h7vl.pdf

Brochures https://www.st.com/resource/en/brochure/products-and-solutions-for-plcs-

and-smart-i-os.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Flyers https://www.st.com/resource/en/flyer/flpowerstbd.pdf

Application Notes https://www.st.com/resource/en/application_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2639-soldering-

recommendations-and-package-information-for-leadfree-ecopack-mcus-

- and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2834-how-to-get-the-best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2867-oscillator-design-guide-for-stm8afals-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4277-using-stm32-device-pwm-shutdown-features-for-motor-control-and-digital-power-conversion-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4539-hrtim-cookbook-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4635-minimization-of-power-consumption-using-lpuart-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-

- applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4839-level-1-cache-on-stm32f7-series-and-stm32h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4861-lcdtft-display-controller-ltdc-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4891-stm32h72x-stm32h73x-and-singlecore-stm32h74x75x-system-architecture-and-performance-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4936-migration-of-microcontroller-applications-from-stm32f7-series-to-stm32h743753-line-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4938-getting-started-with-stm32h74xig-and-stm32h75xig-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4990-getting-started-with-sigmadelta-digital-interface-on-applicable-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4996-hardware-jpeg-codec-peripheral-in-stm32f7677xxx-and-

- stm32h743534555475750a3b3b0xx-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5020-digital-camera-interface-dcmi-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5033-stm32cube-mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5036-thermal-management-guidelines-for-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5200-getting-started-with-stm32h7-series-sdmmc-host-controller-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5224-stm32-dmamux-the-dma-request-router-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5225-usb-typec-power-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5312-migration-from-revy-to-revv-for-stm32h743753-and-stm32h750-value-line-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5337-stm32h7-series-lifetime-estimates-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5354-getting-started-with-the-stm32h7-series-mcu-16bit-adc-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5405-fdcan-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5543-enhanced-methods-to-handle-spi-communication-on-stm32-devices-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5690-vrefbuf-peripheral-applications-and-trimming-technique-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4760-quadspi-

- interface-on-stm32-microcontrollers-and-microprocessors-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4899-stm32microcontroller-gpio-hardware-settings-and-lowpower-consumptionstmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5507-cyclic-redundancy-check-in-stm32h7-series-flash-memory-interface-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5612-esd-protection-of-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5293-migration-guide-from-stm32f7-series-to-stmh74x75x-stm32h72x73x-and-stmh7a37bx-devices-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-to-stm32-microcontrollers-security-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4838-introduction-to-memory-protection-unit-management-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5348-introduction-to-fdcan-peripherals-for-stm32-product-classes-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4230-random-number-generation-validation-using-nist-statistical-test-suite-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5342--errorcorrection-code-ecc-management-for-internal-memories-protection-onstm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4879-introduction-to-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an1202_freertos_guide-for related Tools freertos-guide-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an1602_semihosting_in for related Tools _truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an1801_stm32cubeprog for related Tools rammer_in_truestudio-installing-stm32cubeprogrammer-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/atollic_editing_keyboard

for related Tools _shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/iar_to_atollic_truestudio

for related Tools __migration_guide-truestudio-for-arm-migration-guide-iar-embedded-

& Software workbench-to-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/stm32cubemx_installatio

for related Tools n_in_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-for related Tools microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-

for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-for-for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-

& Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an4635-minimization-of-

for related Tools power-consumption-using-lpuart-for-stm32-microcontrollers-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32-

for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-

for related Tools hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

& Software stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-

for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4891-stm32h72x-for related Tools stm32h73x-and-singlecore-stm32h74x75x-system-architecture-and-

& Software performance-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5001-stm32cube-for related Tools expansion-package-for-stm32h7-series-mdma-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5014-stm32h7x3-for related Tools smart-power-management-expansion-package-for-stm32cube-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5033-stm32cube-for related Tools mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5426-migrating-

for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5534-stm32h735gdk-

for related Tools firmware-upgrade-for-atbased-emw3080-wifi-module-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4865-lowpower-timer-

for related Tools lptim-applicative-use-cases-on-stm32-mcus-and-mpus-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5698-adapting-thefor related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application note/an5450-stm32h7a37b3for related Tools lines-and-stm32h7b0-value-line-smart-power-management-expansion-

& Software package-for-stm32cube-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an4502-stm32-

for related Tools smbuspmbus-expansion-package-for-stm32cube-stmicroelectronics.pdf

& Software

Design Notes & https://www.st.com/resource/en/design_tip/dt0117-microphone-array-**Tips**

beamforming-in-the-pcm-and-pdm-domain-stmicroelectronics.pdf

Errata Sheets https://www.st.com/resource/en/errata_sheet/es0392-stm32h742xig-and-

stm32h743xig-device-limitations-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00387108.pdf

Programming https://www.st.com/resource/en/programming_manual/pm0253-stm32f7-

Manuals series-and-stm32h7-series-cortexm7-processor-programming-manual-

stmicroelectronics.pdf

https://www.st.com/resource/en/reference manual/rm0433-stm32h742-Reference Manuals stm32h743753-and-stm32h750-value-line-advanced-armbased-32bit-

mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1433-reference-device-

& Articles marking-schematics-for-stm32-microcontrollers-and-microprocessors-

stmicroelectronics.pdf