

# File operations and data parsing

## Presented by

Felix Hoffmann

@Felix11H

[felix11h.github.io/](https://felix11h.github.io/)

## Slides

Slideshare:

[tiny.cc/file-ops](https://tiny.cc/file-ops)

Source:

[tiny.cc/file-ops-github](https://tiny.cc/file-ops-github)

## References

- Python Files I/O at [tutorialspoint.com](https://tutorialspoint.com)
- [Dive into Python 3](#) by Mark Pilgrim
- Python Documentation on [match objects](#)
- Regex tutorial at [regexone.com](https://regexone.com)



This work is licensed under a [Creative Commons Attribution 4.0 International License](https://creativecommons.org/licenses/by/4.0/).

Load/Save data

Data parsing

os module

# File operations: Reading

Opening an existing file

```
>>> f = open("test.txt", "rb")  
>>> print f  
<open file 'test.txt', mode 'rb' at 0x...>
```

# File operations: Reading

Opening an existing file

```
>>> f = open("test.txt", "rb")  
>>> print f  
<open file 'test.txt', mode 'rb' at 0x...>
```

Reading it:

```
>>> f.read()  
'hello world'
```

# File operations: Reading

Opening an existing file

```
>>> f = open("test.txt", "rb")
>>> print f
<open file 'test.txt', mode 'rb' at 0x...>
```

Reading it:

```
>>> f.read()
'hello world'
```

Closing it:

```
>>> f.close()
>>> print f
<closed file 'test.txt', mode 'rb' at 0x...>
```

# File operations: Writing

Opening a (new) file

```
>>> f = open("new_test.txt", "wb")  
>>> print f  
<open file 'test.txt', mode 'wb' at 0x...>
```

# File operations: Writing

Opening a (new) file

```
>>> f = open("new_test.txt", "wb")
>>> print f
<open file 'test.txt', mode 'wb' at 0x...>
```

Writing to it:

```
>>> f.write("hello world, again")
>>> f.write("... and again")
>>> f.close()
```

# File operations: Writing

Opening a (new) file

```
>>> f = open("new_test.txt", "wb")
>>> print f
<open file 'test.txt', mode 'wb' at 0x...>
```

Writing to it:

```
>>> f.write("hello world, again")
>>> f.write("... and again")
>>> f.close()
```

⇒ Only after calling close() the changes appear in the file for editing elsewhere!



# File operations: Appending

Opening an existing file

```
>>> f = open("test.txt", "ab")  
>>> print f  
<open file 'test.txt', mode 'ab' at 0x...>
```

# File operations: Appending

Opening an existing file

```
>>> f = open("test.txt", "ab")
>>> print f
<open file 'test.txt', mode 'ab' at 0x...>
```

Appending to it:

```
>>> f.write("hello world, again")
>>> f.write("... and again")
>>> f.close()
```

# File operations: Appending

Opening an existing file

```
>>> f = open("test.txt", "ab")
>>> print f
<open file 'test.txt', mode 'ab' at 0x...>
```

Appending to it:

```
>>> f.write("hello world, again")
>>> f.write("... and again")
>>> f.close()
```

⇒ In append mode the **file pointer** is set to the end of the opened file.

## File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" %(i+1))
4 f.close()
```

# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" %(i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
```

# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" %(i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
'this is line 1 \n'
```

# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" %(i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
'this is line 1 \n'
>>> f.readline()
```

# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" % (i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
'this is line 1 \n'
>>> f.readline()
'this is line 2 \n'
```



# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" % (i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
'this is line 1 \n'
>>> f.readline()
'this is line 2 \n'
>>> f.read(14)
```

# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" % (i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
'this is line 1 \n'
>>> f.readline()
'this is line 2 \n'
>>> f.read(14)
'this is line 3'
```

# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" % (i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
'this is line 1 \n'
>>> f.readline()
'this is line 2 \n'
>>> f.read(14)
'this is line 3'
>>> f.read(2)
```

# File operations: More about file pointers

```
1 f = open("lines_test.txt", "wb")
2 for i in range(10):
3     f.write("this is line %d \n" % (i+1))
4 f.close()
```

Reading from the file:

```
>>> f = open("lines_test.txt", "rb")
>>> f.readline()
'this is line 1 \n'
>>> f.readline()
'this is line 2 \n'
>>> f.read(14)
'this is line 3'
>>> f.read(2)
' \n'
```

## File operations: More about file pointers

**`f.tell()`**

gives current position within file **`f`**

# File operations: More about file pointers

**`f.tell()`**

gives current position within file **`f`**

**`f.seek(x[, from])`**

change file pointer position within file **`f`**, where

from = 0      from beginning of file

from = 1      from current position

from = 2      from end of file

# File operations: More about file pointers

**f.tell()**

gives current position within file **f**

**f.seek(x[, from])**

change file pointer position within file **f**, where

from = 0      from beginning of file

from = 1      from current position

from = 2      from end of file

```
1 >>> f = open("lines_test.txt", "rb")
2 >>> f.tell()
3 0
4 >>> f.read(10)
5 'this is li'
6 >>> f.tell()
7 10
```

# File operations: More about file pointers

```
1 >>> f.seek(5)
2 >>> f.tell()
3 5
4 >>> f.seek(10,1)
5 >>> f.tell()
6 15
7 >>> f.seek(-10,2)
8 >>> f.tell()
9 151
10 >>> f.read()
11 ' line 10 \n'
```



## File operations: Other Modes

**rb+**      Opens the file for reading and writing. File pointer will be at the beginning of the file.

# File operations: Other Modes

- rb+** Opens the file for reading and writing. File pointer will be at the beginning of the file.
- wb+** Opens for reading and writing. Overwrites the existing file if the file exists, otherwise a new file is created.

# File operations: Other Modes

- |            |   |
|------------|---|
| <b>rb+</b> | Opens the file for reading and writing. File pointer will be at the beginning of the file.  |
| <b>wb+</b> | Opens for reading and writing. Overwrites the existing file if the file exists, otherwise a new file is created.  |
| <b>ab+</b> | Opens the file for appending and reading. The file pointer is at the end of the file if the file exists, otherwise a new file is created for reading and writing. |

# Saving Data: Python Pickle

Use pickle to save and retrieve more complex data types - lists, dictionaries and even class objects:

# Saving Data: Python Pickle

Use pickle to save and retrieve more complex data types - lists, dictionaries and even class objects:



©Dom Dada [CC BY-NC-ND 2.0](https://creativecommons.org/licenses/by-nc-nd/2.0/)

# Saving Data: Python Pickle

Use pickle to save and retrieve more complex data types - lists, dictionaries and even class objects:

```
1 >>> import pickle
2 >>> f = open('save_file.p', 'wb')
3 >>> ex_dict = {'hello': 'world'}
4 >>> pickle.dump(ex_dict, f)
5 >>> f.close()
```

# Saving Data: Python Pickle

Use pickle to save and retrieve more complex data types - lists, dictionaries and even class objects:

```
1 >>> import pickle
2 >>> f = open('save_file.p', 'wb')
3 >>> ex_dict = {'hello': 'world'}
4 >>> pickle.dump(ex_dict, f)
5 >>> f.close()
```

```
1 >>> import pickle
2 >>> f = open('save_file.p', 'rb')
3 >>> loadobj = pickle.load(f)
4 >>> print loadobj['hello']
5 world
```

# Best practice: With Statement

```
1 import pickle
2
3 ex_dict = {'hello': 'world'}
4
5 with open('save_file.p', 'wb') as f:
6     pickle.dump(ex_dict, f)
```



# Best practice: With Statement

```
1 import pickle
2
3 ex_dict = {'hello': 'world'}
4
5 with open('save_file.p', 'wb') as f:
6     pickle.dump(ex_dict, f)
```

```
1 import pickle
2
3 with open('save_file.p', 'rb') as f:
4     loadobj = pickle.load(f)
5
6 print loadobj['hello']
```

⇒ Use this!

Load/Save data

Data parsing

os module

# Need for parsing

Imagine that

Data files are  
generated by a third  
party (no control over  
the format)

# Need for parsing

Imagine that

Data files are  
generated by a third  
party (no control over  
the format)

& the data files need  
pre-processing

# Need for parsing

Imagine that

Data files are  
generated by a third  
party (no control over  
the format)

& the data files need  
pre-processing

⇒ Regular expressions  
provide a powerful  
and concise way to  
perform pattern  
match/search/replace  
over the data

# Need for parsing

Imagine that

Data files are  
generated by a third  
party (no control over  
the format)

& the data files need  
pre-processing

⇒ Regular expressions  
provide a powerful  
and concise way to  
perform pattern  
match/search/replace  
over the data



# Regular expressions - A case study

Formatting street names

```
>>> s = '100 NORTH MAIN ROAD'
```

# Regular expressions - A case study

## Formatting street names

```
>>> s = '100 NORTH MAIN ROAD'  
>>> s.replace('ROAD', 'RD.')
```



# Regular expressions - A case study

## Formatting street names

```
>>> s = '100 NORTH MAIN ROAD'  
>>> s.replace('ROAD', 'RD.')  
'100 NORTH MAIN RD.'
```

# Regular expressions - A case study

## Formatting street names

```
>>> s = '100 NORTH MAIN ROAD'
>>> s.replace('ROAD', 'RD.')
'100 NORTH MAIN RD.'
>>> s = '100 NORTH BROAD ROAD'
```

# Regular expressions - A case study

## Formatting street names

```
>>> s = '100 NORTH MAIN ROAD'
>>> s.replace('ROAD', 'RD.')
'100 NORTH MAIN RD.'
>>> s = '100 NORTH BROAD ROAD'
>>> s.replace('ROAD', 'RD.')
```

# Regular expressions - A case study

## Formatting street names

```
>>> s = '100 NORTH MAIN ROAD'
>>> s.replace('ROAD', 'RD.')
'100 NORTH MAIN RD.'
>>> s = '100 NORTH BROAD ROAD'
>>> s.replace('ROAD', 'RD.')
'100 NORTH BRD. RD.'
```

# Regular expressions - A case study

## Formatting street names

```
>>> s = '100 NORTH MAIN ROAD'
>>> s.replace('ROAD', 'RD.')
'100 NORTH MAIN RD.'
>>> s = '100 NORTH BROAD ROAD'
>>> s.replace('ROAD', 'RD.')
'100 NORTH BRD. RD.'
>>> s[:-4] + s[-4:].replace('ROAD', 'RD.')
'100 NORTH BROAD RD.'
```

## Better use regular expressions!

```
>>> import re
>>> re.sub(r'ROAD$', 'RD.', s)
'100 NORTH BROAD RD.'
```

# Pattern matching with regular expressions

<code>^</code>	Matches beginning of line/pattern
<code>\$</code>	Matches end of line/pattern
<code>.</code>	Matches any character except newline
<code>[..]</code>	Matches any single character in brackets
<code>[^..]</code>	Matches any single character not in brackets
<code>re*</code>	Matches 0 or more occurrences of the preceding expression
<code>re+</code>	Matches 1 or more occurrences of the preceding expression
<code>re?</code>	Matches 0 or 1 occurrence
<code>re{n}</code>	Match exactly n occurrences
<code>re{n,}</code>	Match n or more occurrences
<code>re{n,m}</code>	Match at least n and at most m

# Pattern matching with regular expressions

<b>^</b>	Matches beginning of line/pattern
<b>\$</b>	Matches end of line/pattern
<b>.</b>	Matches any character except newline
<b>[..]</b>	Matches any single character in brackets
<b>[^..]</b>	Matches any single character not in brackets
<b>re*</b>	Matches 0 or more occurrences of the preceding expression
<b>re+</b>	Matches 1 or more occurrences of the preceding expression
<b>re?</b>	Matches 0 or 1 occurrence
<b>re{n}</b>	Match exactly n occurrences
<b>re{n,}</b>	Match n or more occurrences
<b>re{n,m}</b>	Match at least n and at most m

⇒ Use cheatsheets, trainers, tutorials, builders, etc..

## re.search() & matches

```
>>> import re
>>> data = "I like python"
>>> m = re.search(r'python', data)
```



## re.search() & matches

```
>>> import re
>>> data = "I like python"
>>> m = re.search(r'python', data)
>>> print m
<_sre.SRE_Match object at 0x...>
```

## re.search() & matches

```
>>> import re
>>> data = "I like python"
>>> m = re.search(r'python', data)
>>> print m
<_sre.SRE_Match object at 0x...>
```

Important properties of the match object:

- group()** Return the string matched by the RE
- start()** Return the starting position of the match
- end()** Return the ending position of the match
- span()** Return a tuple containing the (start, end) positions of the match

## re.search() & matches

For example:

```
>>> import re
>>> data = "I like python"
>>> m = re.search(r'python', data)
```

## re.search() & matches

For example:

```
>>> import re
>>> data = "I like python"
>>> m = re.search(r'python', data)
>>> m.group()
'python'
```

## re.search() & matches

For example:

```
>>> import re
>>> data = "I like python"
>>> m = re.search(r'python', data)
>>> m.group()
'python'
>>> m.start()
7
```

# re.search() & matches

For example:

```
>>> import re
>>> data = "I like python"
>>> m = re.search(r'python', data)
>>> m.group()
'python'
>>> m.start()
7
>>> m.span()
(7, 13)
```

For a complete list of match object properties see for example the Python Documentation:

<https://docs.python.org/2/library/re.html#match-objects>

# re.findall()

```
>>> import re
>>> data = "Python is great. I like python"
>>> m = re.search(r'[pP]ython', data)
```

## re.findall()

```
>>> import re
>>> data = "Python is great. I like python"
>>> m = re.search(r'[pP]ython', data)
>>> m.group()
'Python'
```



## re.findall()

```
>>> import re
>>> data = "Python is great. I like python"
>>> m = re.search(r'[pP]ython', data)
>>> m.group()
'Python'
```

⇒ **re.search()** returns only the first match, use **re.findall()** instead:

## re.findall()

```
>>> import re
>>> data = "Python is great. I like python"
>>> m = re.search(r'[pP]ython', data)
>>> m.group()
'Python'
```

⇒ **re.search()** returns only the first match, use **re.findall()** instead:

```
>>> import re
>>> data = "Python is great. I like python"
>>> l = re.findall(r'[pP]ython', data)
```

## re.findall()

```
>>> import re
>>> data = "Python is great. I like python"
>>> m = re.search(r'[pP]ython', data)
>>> m.group()
'Python'
```

⇒ **re.search()** returns only the first match, use **re.findall()** instead:

```
>>> import re
>>> data = "Python is great. I like python"
>>> l = re.findall(r'[pP]ython', data)
>>> print l
['Python', 'python']
```

## re.findall()

```
>>> import re
>>> data = "Python is great. I like python"
>>> m = re.search(r'[pP]ython', data)
>>> m.group()
'Python'
```

⇒ **re.search()** returns only the first match, use **re.findall()** instead:

```
>>> import re
>>> data = "Python is great. I like python"
>>> l = re.findall(r'[pP]ython', data)
>>> print l
['Python', 'python']
```

⇒ Returns list instead of match object!

## re.findall() - Example

```
1 import re
2
3 with open("history.txt", "rb") as f:
4     text = f.read()
5
6 year_dates = re.findall(r'19[0-9]{2}', text)
```

# re.split()

Suppose the data stream has well-defined delimiter

```
>>> data = "x = 20"  
>>> re.split(r'=', data)  
['x ', ' 20']
```

# re.split()

Suppose the data stream has well-defined delimiter

```
>>> data = "x = 20"  
>>> re.split(r'=', data)  
['x ', ' 20']
```

```
>>> data = 'ftp://python.about.com'  
>>> re.split(r':/{1,3}', data)  
['ftp', 'python.about.com']
```

# re.split()

Suppose the data stream has well-defined delimiter

```
>>> data = "x = 20"  
>>> re.split(r'=', data)  
['x ', ' 20']
```

```
>>> data = 'ftp://python.about.com'  
>>> re.split(r':/{1,3}', data)  
['ftp', 'python.about.com']
```

```
>>> data = '25.657'  
>>> re.split(r'\.', data)  
['25', '657']
```



## re.sub()

Replace patterns by other patterns.

```
>>> data = "2004-959-559 # my phone number"  
>>> re.sub(r'#[.*]', '', data)  
'2004-959-559 '
```

# re.sub()

Replace patterns by other patterns.

```
>>> data = "2004-959-559 # my phone number"
>>> re.sub(r'#[.*]', '', data)
'2004-959-559 '
```

A more interesting example:

```
>>> data = "2004-959-559"
>>> re.sub(r'([0-9]*)-([0-9]*)-([0-9]*)',
>>>         r'\3-\2-\1', data)
```

# re.sub()

Replace patterns by other patterns.

```
>>> data = "2004-959-559 # my phone number"
>>> re.sub(r'#[.*]', '', data)
'2004-959-559 '
```

A more interesting example:

```
>>> data = "2004-959-559"
>>> re.sub(r'([0-9]*)-([0-9]*)-([0-9]*)',
>>>         r'\3-\2-\1', data)
'559-959-2004'
```

## re.sub()

Replace patterns by other patterns.

```
>>> data = "2004-959-559 # my phone number"
>>> re.sub(r'#[.*]', '', data)
'2004-959-559 '
```

A more interesting example:

```
>>> data = "2004-959-559"
>>> re.sub(r'([0-9]*)-([0-9]*)-([0-9]*)',
>>>        r'\3-\2-\1', data)
'559-959-2004'
```

⇒ Groups are captured in parenthesis and referenced in the replacement string by \1, \2, ...

Load/Save data

Data parsing

os module

# os module

Provides a way of using os dependent functionality:

<b>os.mkdir()</b>	Creates a directory (like mkdir)
<b>os.chmod()</b>	Change the permissions (like chmod)
<b>os.rename()</b>	Rename the old file name with the new file name.
<b>os.listdir()</b>	List the contents of the directory
<b>os.getcwd()</b>	Get the current working directory path
<b>os.path</b>	Submodule for useful functions on pathnames

# os module

Provides a way of using os dependent functionality:

<b>os.mkdir()</b>	Creates a directory (like mkdir)
<b>os.chmod()</b>	Change the permissions (like chmod)
<b>os.rename()</b>	Rename the old file name with the new file name.
<b>os.listdir()</b>	List the contents of the directory
<b>os.getcwd()</b>	Get the current working directory path
<b>os.path</b>	Submodule for useful functions on pathnames

For example, list all files in the current directory:

```
>>> from os import listdir
>>>
>>> for f in listdir("."):
>>>     print f
```

# *Have fun!*

## Presented by

Felix Hoffmann

@Felix11H

[felix11h.github.io/](https://felix11h.github.io/)

## Slides

Slideshare:

[tiny.cc/file-ops](https://tiny.cc/file-ops)

Source:

[tiny.cc/file-ops-github](https://tiny.cc/file-ops-github)

## References

- Python Files I/O at [tutorialspoint.com](https://tutorialspoint.com)
- [Dive into Python 3](#) by Mark Pilgrim
- Python Documentation on [match objects](#)
- Regex tutorial at [regexone.com](https://regexone.com)



This work is licensed under a [Creative Commons Attribution 4.0 International License](https://creativecommons.org/licenses/by/4.0/).