Routes

Routes define the URL structure and map HTTP methods to controller functions.

Route Organization

Routes are organized by domain module. Each route file imports its corresponding controller and applies middleware.

Public Ticket Routes

File: `backend/src/routes/publicTickets.js`

```
const express = require('express');
const router = express.Router();
const { createPublicTicket } = require('../controllers/ticketController');

router.post('/', createPublicTicket);

module.exports = router;
```

Authentication Routes

File: `backend/src/routes/auth.js`

```
const express = require('express');
const router = express.Router();
const authController = require('../controllers/authController');

router.post('/login', authController.login);
router.post('/logout', authController.logout);
router.get('/profile', require('../middleware/auth').authenticate,
authController.getProfile);

module.exports = router;
```

Ticket Routes

File: `backend/src/routes/tickets.js`

```
const express = require('express');
const router = express.Router();
const ticketController = require('../controllers/ticketController');
const { requireStaffOrAdmin } = require('../middleware/auth');
const { authenticate } = require('../middleware/auth');

router.get('/', authenticate, requireStaffOrAdmin, ticketController.getTickets);
router.get('/:id', authenticate, requireStaffOrAdmin, ticketController.getTicket);
router.put('/:id', authenticate, requireStaffOrAdmin, ticketController.updateTicket);
router.post('/:id/escalate', authenticate, requireStaffOrAdmin,
ticketController.escalateTicket);
router.post('/:id/comments', authenticate, requireStaffOrAdmin,
ticketController.addComment);
router.post('/:id/attachments', authenticate, requireStaffOrAdmin,
  upload.single('file'), ticketController.uploadAttachment);
```

```
module.exports = router;
```

Mounting Order in server.js

Routes are mounted in `backend/src/server.js`:

```
app.use('/api/auth', rateLimit({ windowMs: 15 * 60 * 1000, max: 30, keyPrefix: 'auth'
}), authRoutes);
app.use('/api/departments', departmentRoutes);
app.use('/api/users', userRoutes);
app.use('/api/notifications', require('./routes/notifications'));
app.use('/api/settings', require('./routes/settings'));
app.use('/api/views', require('./routes/views'));
app.use('/api/knowledge-base', require('./routes/knowledgeBase'));
app.use('/api/status-issues', require('./routes/statusIssues'));
app.use('/api/forms', require('./routes/forms'));
app.use('/api/operations', require('./routes/operations'));
app.use('/api/public/tickets', rateLimit(...), publicTicketRoutes);
app.use('/api/tickets/public', rateLimit(...), publicTicketRoutes);
app.use('/api/tickets', ticketRoutes);
```

> **Important:** Public ticket routes must be mounted before the general `/api/tickets` route to avoid path conflicts.

Route Patterns

Pattern	Example	Purpose
`GET /`	`GET /api/tickets`	List resources

Pattern	Example	Purpose
`GET /:id`	`GET /api/tickets/123`	Get single resource
`POST /`	`POST /api/tickets`	Create resource
`PUT /:id`	`PUT /api/tickets/123`	Update resource
`DELETE /:id`	`DELETE /api/tickets/123`	Delete resource
`POST /:id/action`	`POST /api/tickets/123/escalate`	Resource-specific action

Previous
« Controllers

Next
Services »

Copyright © 2026 KUCCPS. Built with Docusaurus.