Styling

The frontend uses Tailwind CSS with a custom design system for consistent branding and responsive design.

Tailwind Configuration

File: `frontend/tailwind.config.js`

The Tailwind configuration extends the default theme with:

- Custom brand colors
- Animation keyframes
- Extended font families
- Dark mode support

Design System

Brand Colors

Brand colors are configurable through `SystemSettings` and applied dynamically:

```
document.documentElement.style.setProperty('--brand-primary', settings.primaryColor ||
'#911414');
document.documentElement.style.setProperty('--brand-secondary', settings.secondaryColor
|| '#d20001');
```

Default Palette

Color	Hex	Usage
Primary	`#911414`	KUCCPS brand red, buttons, headers
Secondary	`#d20001`	Accent color, hover states
Dark	`#1f2937`	Dark mode backgrounds
Gray	`#6b7280`	Secondary text, borders

CSS Architecture

Global Styles (`index.css`)

```
@tailwind base;
@tailwind components;
@tailwind utilities;

@layer base {
  :root {
    --brand-primary: #911414;
```

```
    --brand-secondary: #d20001;
  }
}

@layer components {
  .btn-primary {
    @apply px-4 py-2 rounded-lg text-white font-medium;
    background-color: var(--brand-primary);
  }

  .card {
    @apply bg-white rounded-xl shadow-sm border border-gray-200 p-6;
  }
}
```

Animations (`styles/animations.css`)

Custom animations for:

- Fade in/out
- Slide in from bottom
- Spinner rotation
- Pulse effects for notifications

Responsive Design

The application uses a mobile-first approach with Tailwind responsive prefixes:

Breakpoint	Width	Target
`sm`	640px	Large phones
`md`	768px	Tablets
`lg`	1024px	Small laptops
`xl`	1280px	Desktops
`2xl`	1536px	Large screens

Theme Variants

Dark Mode

Enabled via `darkModeEnabled` in `SystemSettings`:

```
.theme-dark {
  background-color: #1f2937;
  color: #f9fafb;
}
```

High Contrast Mode

Enabled via `contrastMode` in `SystemSettings`:

```
.theme-high-contrast {
  filter: contrast(1.5);
}
```

PostCSS Pipeline

File: `postcss.config.js`

```
export default {
  plugins: {
    tailwindcss: {},
    autoprefixer: {},
  },
};
```

Autoprefixer automatically adds vendor prefixes for cross-browser compatibility.

Previous
« Routing

Next
Database Overview »

Getting Started

Architecture

API Reference

Community

GitHub

More

Deployment Guide

Troubleshooting

Copyright © 2026 KUCCPS. Built with Docusaurus.