API Overview

All API endpoints are prefixed with `/api`. Responses are JSON.

Base URL

```
http://localhost:5000/api
```

Response Format

Standard response envelope:

```
{
  "success": true,
  "message": "Optional message",
  "data": {}
}
```

Authentication

JWT Bearer Token

Protected routes require a JWT token in the `Authorization` header:

```
Authorization: Bearer <jwt-token>
```

Public API Key

Public ticket endpoints require an API key:

```
X-API-Key: <PUBLIC_TICKET_API_KEY>
```

Or as a bearer token depending on server configuration.

Rate Limiting

Scope	Window	Max Requests
Global	15 minutes	600
Auth	15 minutes	30
Public tickets	15 minutes	30

Status Codes

Code	Meaning
200	Success
201	Created
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
413	Payload Too Large
415	Unsupported Media Type
429	Too Many Requests
500	Server Error

Error Response Format

```
{
  "success": false,
  "message": "Error description"
```

```
}
```

Pagination

List endpoints support pagination via query parameters:

```
GET /api/tickets?page=1&limit=20
```

- `page`: Page number (default: 1)
- `limit`: Items per page (default: 20, max: 100)

Filtering

Many list endpoints support filtering:

```
GET /api/tickets?status=Open&priority=High&departmentId=uuid
```

Sorting

```
GET /api/tickets?sortBy=createdAt&sortOrder=desc
```

Previous
« Prisma Usage

Next
Authentication API »

Copyright © 2026 KUCCPS. Built with Docusaurus.