Authentication API

Base path: `/api/auth`

Login

```
POST /api/auth/login
```

Request

```
{
  "username": "admin",
  "password": "admin123"
}
```

Response

```
{
  "success": true,
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "user": {
```

```
    "id": "uuid",
    "email": "admin@example.com",
    "name": "System Administrator",
    "username": "admin",
    "role": "admin",
    "departmentId": "uuid",
    "department": {
      "id": "uuid",
      "name": "ICT"
    }
  }
}
```


Logout

```
POST /api/auth/logout
```

No request body required. Primarily for client-side token cleanup.

Profile

```
GET /api/auth/profile
```

Headers

```
Authorization: Bearer <jwt-token>
```

Response


```
{
  "success": true,
  "user": {
    "id": "uuid",
    "email": "admin@example.com",
    "name": "System Administrator",
    "username": "admin",
    "role": "admin",
    "departmentId": "uuid",
    "department": {
      "id": "uuid",
      "name": "ICT"
    }
  }
}
```


Previous

« API Overview

Next

Tickets API »

Architecture

API Reference

Community

GitHub

More

Deployment Guide

Troubleshooting

Copyright © 2026 KUCCPS. Built with Docusaurus.