Users API

Base path: `/api/users`

Get Users

```
GET /api/users
```

Headers

```
Authorization: Bearer <jwt-token>
```

Response

```
{
  "success": true,
  "users": [
    {
      "id": "uuid",
      "email": "admin@example.com",
      "name": "System Administrator",
```

```
      "username": "admin",
      "role": "admin",
      "ldapSync": false,
      "departmentId": "uuid",
      "department": {
        "id": "uuid",
        "name": "ICT"
      },
      "createdAt": "2026-08-14T09:00:00.000Z"
    }
  ]
}
```


Create User

```
POST /api/users
```

Headers

```
Authorization: Bearer <jwt-token>
```

Request Body


```
{
  "email": "newuser@example.com",
  "name": "New User",
  "username": "newuser",
  "password": "securePassword123",
  "role": "staff",
```

```
  "departmentId": "uuid"
}
```

Response

```
{
  "success": true,
  "message": "User created successfully",
  "user": { /* user object */ }
}
```

Update User

```
PUT /api/users/:id
```

Request Body

```
{
  "name": "Updated Name",
  "role": "admin",
  "departmentId": "uuid",
  "password": "newPassword123"
}
```

> Note: Password is optional. If provided, it will be hashed and updated.

Delete User

```
DELETE /api/users/:id
```

Response

```
{
  "success": true,
  "message": "User deleted successfully"
}
```

Sync from Active Directory

```
POST /api/users/sync/ad
```

Headers

```
Authorization: Bearer <jwt-token>
```

> Admin only.

Response

```
{
```

```
  "success": true,
  "message": "Users synced from Active Directory",
  "synced": 15
}
```

Previous
« Tickets API

Next
Departments API »

Troubleshooting

Copyright © 2026 KUCCPS. Built with Docusaurus.