# Notifications API

Base path: `/api/notifications`

All notification endpoints require JWT authentication.

## Get Notifications

```
GET /api/notifications
```

### Response


```
{
  "success": true,
  "notifications": [
    {
      "id": "uuid",
      "type": "sla_breach",
      "title": "SLA Breach Alert",
      "message": "Ticket TICK20260814-0001 has breached its SLA.",
      "isRead": false,
      "ticketId": "uuid",
      "ticketNumber": "TICK20260814-0001",
      "createdAt": "2026-08-14T09:00:00.000Z"
```

```
    }
  ]
}
```

# Mark All as Read

```
PUT /api/notifications/read/all
```

## Response

```
{
  "success": true,
  "message": "All notifications marked as read"
}
```

# Mark One as Read

```
PUT /api/notifications/:id/read
```

# Dismiss Notification

```
DELETE /api/notifications/:id
```

# Get Preferences

```
GET /api/notifications/preferences
```

## Response

```
{
  "success": true,
  "preferences": {
    "emailOnAssignment": true,
    "emailOnStatusChange": true,
    "emailOnNewComment": true,
    "dailyDigest": false,
    "escalationAlerts": true
  }
}
```

# Update Preferences

```
PUT /api/notifications/preferences
```

```
{
  "emailOnAssignment": true,
  "emailOnStatusChange": false,
  "emailOnNewComment": true,
  "dailyDigest": true,
  "escalationAlerts": true
```

```
}
```

# Send Test Email

```
POST /api/notifications/test
```

Sends a test notification email to the current user's email address.

```
{
  "success": true,
  "message": "Test email sent"
}
```

Previous
« Operations API

Next
Forms API »

Architecture

API Reference

**Community**

GitHub

**More**

Deployment Guide

Troubleshooting

Copyright © 2026 KUCCPS. Built with Docusaurus.