Supplementary Methods: Shared LSTM Forecasts in MPC–DWA for UAV Path Planning among Dynamic Obstacles

S1. Development controller and trust-weight calibration

This supplement documents the 3-s development configuration, Stage-1 trust-weight calibration and LSTM training (S1–S3); preserves the completed historical five-controller benchmark and earlier CV/Kalman studies (S4–S7); and reports the current 100-scene, seven-method exploratory evaluation (S8). Stage 1 comprised 4,320 development episodes and selected a trust-weight vector; these runs are separate from both the 7,500-run historical benchmark and the 2,100 planned exploratory episodes, and their selected weights were not applied to the historical benchmark. The historical benchmark used 1-s DWA screening and inherited weights listed with the development settings and identified explicitly in S4. Obstacle trajectories are exogenous: they are generated before a run and do not react to the UAV. The development and exploratory configurations use 3-s MPC and DWA horizons; in the shared-LSTM arm, the same time-aligned 30-step forecast reaches both layers. One-layer ablations send LSTM only to the named layer and use CV extrapolation in the other. DWA samples reachable controls and selects the command applied at the next 0.1-s update; MPC optimizes a 3-s control sequence and uses bounds from DWA's passing controls to constrain its first input. The three evidence sets are not pooled.

S1.1. MPC objective and first-control constraint

The route term measures squared distance from each predicted position to the direct start-to-goal line. The complete objective and its geometric definitions are

$$
\begin{aligned}
\mathbf{a} &= \mathbf{g} - \mathbf{s}, \\
\eta_{\mathbf{a}} &= \mathbf{a}^{\mathsf{T}}\mathbf{a} + 10^{-12}\,\mathrm{m}^2, \\
P_{\mathbf{a}} &= I_3 - \frac{\mathbf{a}\mathbf{a}^{\mathsf{T}}}{\eta_{\mathbf{a}}}, \\
\mathbf{e}^{\perp}_{t+k|t} &= P_{\mathbf{a}}(\mathbf{p}_{t+k|t} - \mathbf{s}), \\
J_{\mathrm{MPC}} &= w_p \sum_{k=0}^{N-1} \|\mathbf{p}_{t+k|t} - \mathbf{g}\|_2^2 \\
&\quad + w_u \sum_{k=1}^{N} \|\mathbf{u}_{t+k|t}\|_2^2 \\
&\quad + w_f \|\mathbf{p}_{t+N|t} - \mathbf{g}\|_2^2 \\
&\quad + w_{\Delta u} \sum_{k=2}^{N} \|\mathbf{u}_{t+k|t} - \mathbf{u}_{t+k-1|t}\|_2^2 \\
&\quad + w_r \sum_{k=1}^{N} \|\mathbf{e}^{\perp}_{t+k|t}\|_2^2 \\
&\quad + \sum_{k=1}^{H_{\mathrm{inj}}} \sum_{j=1}^{M} \left[w_o \max(0, -\hat{d}_{j,k})^2 + w_s \max(0, d_{\mathrm{soft}} - \hat{d}_{j,k})^2 \right], \\
\text{subject to} \quad & \mathbf{x}_{t|t} = \mathbf{x}_t, \\
& \mathbf{x}_{t+k|t} = f(\mathbf{x}_{t+k-1|t}, \mathbf{u}_{t+k|t}), \quad k = 1, \ldots, N, \\
& 0 \le v_{c,t+k|t} \le 2.0\ \mathrm{m\,s^{-1}}, \\
& |\omega_{\theta,t+k|t}| \le 0.8\ \mathrm{rad\,s^{-1}}, \quad |\omega_{\psi,t+k|t}| \le 0.8\ \mathrm{rad\,s^{-1}}, \quad k = 1, \ldots, N.
\end{aligned}
\tag{S1}
$$

Here $\mathbf{x}_t = [\mathbf{p}_t^{\mathsf{T}}, \theta_t, \psi_t, v_t]^{\mathsf{T}}$ is the current state in the implementation's position–pitch–yaw–speed order, and f is the discrete vehicle update defined in the main text; the constraints initialize the prediction and propagate each planned state. The vectors $\mathbf{s}$ and $\mathbf{g}$ are the start and goal, and $\mathbf{a} = \mathbf{g} - \mathbf{s}$ is the start-to-goal route vector. The scalar $\eta_{\mathbf{a}} = \mathbf{a}^{\mathsf{T}}\mathbf{a} + 10^{-12}\,\mathrm{m}^2$ is the squared route length with the implementation's numerical safeguard; $P_{\mathbf{a}} = I_3 - \mathbf{a}\mathbf{a}^{\mathsf{T}}/\eta_{\mathbf{a}}$ defines the corresponding regularized cross-track operator. Thus $\mathbf{e}^{\perp}_{t+k|t}$ is the regularized cross-track residual of predicted position $\mathbf{p}_{t+k|t}$ from the direct route, and I_3 is the 3-D identity. The index k denotes a prediction step, $N = 30$ is the MPC horizon, and $\mathbf{u}_{t+k|t}$ is the three-component command planned at time t for step $t + k$. The obstacle index is $j = 1, \ldots, M$; $H_{\mathrm{inj}} = 30$ is the number of forecast positions injected into MPC. The predicted signed clearance $\hat{d}_{j,k}$ is defined in the main text; $\hat{d}^{(b)}_{j,k}$ below is its candidate-specific counterpart. The soft margin $d_{\mathrm{soft}} = 0.35$ m is the desired MPC safety margin. Thus the seven weights multiply, in order, stage goal error, control effort, terminal goal error, direct-route deviation, command variation, predicted overlap and sub-margin clearance. The weights for stage position, control effort, terminal position, control smoothing, route deviation, obstacle overlap and the safety margin are 1, 10, 1, 50, 3, 20,000 and 12,000, respectively. The safety margin is 0.35 m. Main simulations use 30 prediction steps and a 0.1 s integration step. The code squares speed and angular-rate command values in their native units without cross-channel normalization, so this is a heuristic scalarization rather than a dimensionally homogeneous physical energy; the control weight supplies the numerical scale relative to position-based costs. In its soft penalty, MPC adds a $10^{-12}\,\mathrm{m}^2$ numerical smoothing term when evaluating distance; DWA gates and swept-collision checks use the exact norm. The route-weight ablation alone removes the direct-route preference; all primary results retain it.

When DWA retains candidates, their component-wise control extrema form the box for MPC's first input; the implementation expands each bound by 0.1 in its native command units before clipping to physical limits.

$$
\text{for } \mathcal{A}_t \neq \varnothing: \quad \mathcal{U}_t = \prod_{i=1}^{3} \left[\max\left(u_i^{\min}, \min_{b \in \mathcal{A}_t} u_{b,i} - \delta \right), \min\left(u_i^{\max}, \max_{b \in \mathcal{A}_t} u_{b,i} + \delta \right) \right], \qquad \delta = 0.1. \tag{S2}
$$

Here $\mathcal{A}_t$ is the nonempty set of DWA candidates that pass the gates defined below, $u_{b,i}$ is component i of candidate b, and $u_i^{\min}$ and $u_i^{\max}$ are the physical lower and upper limits for that component. The Cartesian product forms the three-dimensional control box $\mathcal{U}_t$. The implementation applies the same numerical expansion $\delta = 0.1$ separately in each of the three control coordinates, then clips each bound to that coordinate's physical limits; the controls have different physical units, so this is a code-specific heuristic margin rather than a common dimensional distance. When $\mathcal{A}_t$ is empty, no extrema or envelope are formed; MPC uses its ordinary physical bounds. The box constrains MPC but does not certify every command inside it. Only the first MPC control is constrained by this box. Let $\mathbf{u}_0 = \text{UPREV}$ denote the last control actually applied to the vehicle; the first rate bound therefore compares $\mathbf{u}_1$ with $\mathbf{u}_0$. The command components are speed v_c and pitch/yaw rates $\omega_\theta, \omega_\psi$; their hard bounds are shown above. Component i satisfies $|u_{k,i} - u_{k-1,i}| \le a_i \Delta t$ for $k = 1, \ldots, N$, where $\mathbf{a}_u = [a_1, a_2, a_3]^\mathsf{T}$ contains the speed, pitch-rate and yaw-rate acceleration limits. If no DWA candidate passes, the MPC solve uses its ordinary physical input bounds. Command speed, angular-rate and per-step rate-of-change limits remain active in either case; there are no separate hard state-box bounds. IPOPT uses at most 300 iterations and a stopping tolerance of 0.000001.

S1.2. Heuristic score, sampling and safety gates

The four normalized heuristic-score components measure predicted clearance, goal progress, agreement with the preceding MPC reference, and command smoothness. Their definitions are

$$
\begin{aligned}
d_{\min}^{\mathrm{MPC}} &= \min_{1\le j\le M,\, 1\le k\le N} \hat{d}_{j,k}, \\
d_0 &= \|\mathbf{p}_{\mathrm{ref},1|t-1} - \mathbf{g}\|_2, \quad d_N = \|\mathbf{p}_{\mathrm{ref},N|t-1} - \mathbf{g}\|_2, \\
\Delta_p &= \|\mathbf{p}_t - \mathbf{p}_{\mathrm{ref},1|t-1}\|_2, \qquad \Delta\mathbf{u}_k = \mathbf{u}_k - \mathbf{u}_{k-1}, \\
\mathrm{clip}_{[0,1]}(x) &= \max(0, \min(1, x)), \\
\tau_{\mathrm{sa}} &= \mathrm{clip}_{[0,1]}\left(\frac{d_{\min}^{\mathrm{MPC}} - d_{\mathrm{low}}}{d_{\mathrm{high}} - d_{\mathrm{low}}}\right), \\
\tau_g &= \begin{cases} 1, & d_0 < 10^{-6}\,\mathrm{m}, \\ \mathrm{clip}_{[0,1]}(1 - d_N/d_0), & \text{otherwise}, \end{cases} \\
\tau_{\mathrm{ref}} &= \exp[-\alpha_T \Delta_p], \\
\tau_{\mathrm{sm}} &= \mathrm{clip}_{[0,1]}\left[1 - \frac{1}{3(N-1)} \sum_{i=1}^{3} \sum_{k=2}^{N} \frac{|\Delta u_{k,i}|}{a_{u,i}\Delta t}\right], \\
\tau &= \sigma_s \tau_{\mathrm{sa}} + \sigma_g \tau_g + \sigma_t \tau_{\mathrm{ref}} + \sigma_m \tau_{\mathrm{sm}}, \qquad \sigma_s + \sigma_g + \sigma_t + \sigma_m = 1, \\
\mathbf{a}_u &= [1,\ 0.5,\ 0.5]^\mathsf{T}, \\
B &= \mathrm{round}[300(1 + \alpha e^{-\beta\tau})], \\
B_g &= \mathrm{round}(B\tau), \quad B_e = B - B_g.
\end{aligned}
\tag{S3}
$$

Here $d_{\min}^{\mathrm{MPC}}$ is the smallest predicted surface clearance along the MPC reference available before DWA sampling: the initial MPC solution at startup and the shifted previous solution thereafter. The same aligned reference and its control sequence supply the goal-progress, mismatch and smoothness scores. $d_{\mathrm{low}} = 1$ m and $d_{\mathrm{high}} = 5$ m are the lower and upper clearance anchors for the safety-trust normalization. The reference runs from $\mathbf{p}_{\mathrm{ref},1|t-1}$ to $\mathbf{p}_{\mathrm{ref},N|t-1}$; $d_0 = \|\mathbf{p}_{\mathrm{ref},1|t-1} - \mathbf{g}\|_2$ and $d_N = \|\mathbf{p}_{\mathrm{ref},N|t-1} - \mathbf{g}\|_2$. Thus τ_g measures the reference route's clipped fractional reduction in goal distance, not progress from the current measured position. The mismatch $\Delta_p = \|\mathbf{p}_t - \mathbf{p}_{\mathrm{ref},1|t-1}\|_2$ defines the reference-agreement score $\tau_{\mathrm{ref}} = \exp(-\alpha_T \Delta_p)$: a smaller mismatch gives a larger score. The index k runs over the $N = 30$ planned control steps, and i indexes desired speed, pitch rate and yaw rate.

In the MATLAB implementation, the same reference-tracking score is named τ_t; its subscript denotes tracking, not elapsed time.

The vector $\mathbf{a}_u = [1, 0.5, 0.5]^\mathsf{T}$ gives the componentwise acceleration limits for desired speed, pitch rate and yaw rate, with units m s^{-2}, rad s^{-2} and rad s^{-2}, respectively; $\Delta t = 0.1$ s is the control period. The subscript in σ_t labels the reference-tracking component, not elapsed time. The four dimensionless components τ_{sa}, τ_g, τ_{ref} and τ_{sm} quantify predicted safety, goal progress, reference agreement and command smoothness; their weighted sum is the heuristic sampling score τ. The score components are limited to the range from zero to one. The sampling rule divides the B randomly generated candidates between B_g MPC-guided actions and B_e uniformly distributed exploratory actions. Guided controls are drawn within 0.35 per control component of the clipped MPC command and clipped to the dynamic window. The clipped MPC command is also added, yielding one extra candidate. Their union is the candidate-control set $\mathcal{B}_t$. The dimensionless budget-gain coefficient is $\alpha = 1$, distinct from the reference-mismatch decay rate α_T. The four nonnegative trust coefficients were selected from a prespecified finite grid of six vectors using 48 development scenes and three matched sampling seeds. This Stage-1 design comprised $6 \times 5 \times 48 \times 3 = 4{,}320$ episodes, one for each candidate vector, integrated arm, scene and seed. The selection score gives equal weight to five trust-using integrated arms: CV-coupled MPC–DWA, LSTM to MPC only, LSTM to DWA only, shared LSTM, and latest-position hold. For each arm, collision-free arrival is the fraction of its 144 runs that reached the goal without swept contact; collisions and all non-arrivals remain failures. Stage 1 selected $[\sigma_s, \sigma_g, \sigma_t, \sigma_m] = [0.15, 0.15, 0.15, 0.55]$, with an equal-arm macro-average of 0.8042. At this selected vector, the development rates were 0.8958 for shared LSTM, 0.7431 for CV-coupled MPC–DWA, 0.8194 for LSTM-to-MPC-only, 0.8958 for LSTM-to-DWA-only, and 0.6667 for latest-position hold. These rates and the macro-average are descriptive results from the same development scenes used for selection, not held-out comparisons or evidence of generalization. A recovery audit revalidated all 4,320 existing records and recomputed the selection without generating simulations. The current 100-scene evaluation uses the selected vector, while these development outcomes remain descriptive and do not validate its performance. The historical 7,500-run benchmark used its inherited vector $[0.35, 0.30, 0.15, 0.20]$ and remains a separate 1-s DWA study (S4). The earlier 864-episode six-setting comparison used a different protocol and was not reused.

The reference-mismatch decay $\alpha_T = 3\,\mathrm{m}^{-1}$ and budget sensitivity $\beta = 3$ are fixed implementation settings; neither was selected by the 4,320 Stage-1 episodes. The planned 5,760-episode Stage-2 grid was not completed or independently verified, so it provides no basis for describing either setting as calibrated or Stage-2-selected. Stage-2 records and protocol are retained as historical audit material only and are excluded from the evidence used for the current paper's main conclusions. The score τ and its four component scores are dimensionless, α_T has units m^{-1} because it multiplies the position mismatch Δ_p in metres, and β is dimensionless.

The signed clearance for each sampled path and its minimum over all obstacles and forecast steps are defined below. A path is retained only if it passes the clearance, corridor and stopping-distance gates.

$$
\begin{aligned}
&H_D = \lceil T_D/\Delta t \rceil = 30, \qquad H_{\mathrm{eff}} = \min(H_D, H_{\mathrm{inj}}, N_{\mathrm{pred}}) = 30,\\
&\hat{d}^{(b)}_{j,k} = \|\mathbf{p}^{(b)}_{t+k|t} - \hat{\mathbf{o}}_{j,t+k|t}\|_2 - r_j - r_u,\\
&d^{(b)}_{\min} = \min_{1\le j\le M,\, 1\le k\le H_{\mathrm{eff}}} \hat{d}^{(b)}_{j,k},\\
&\mathcal{C}_b = 1 \iff \forall k = 1, \dots, H_{\mathrm{eff}}: \quad 0.5 \le z^{(b)}_{t+k|t} \le 9.5 \text{ m and } |z^{(b)}_{t+k|t} - z^{(b)}_{\mathrm{nom},k}| \le 3 \text{ m},\\
&\mathcal{A}_t = \left\{ b \in \mathcal{B}_t :\ d^{(b)}_{\min} > 0.25 \text{ m}, \quad \mathcal{C}_b = 1, \quad (v^{(b)}_{\mathrm{end}})^2 \le 2(1.0\ \mathrm{m\,s^{-2}}) d^{(b)}_{\min} \right\}.
\end{aligned}
\tag{S4}
$$

Here $T_D = 3$ s is the DWA candidate-rollout duration, H_D its number of simulated UAV states, $N_{\mathrm{pred}} = 30$ the network-output length and $H_{\mathrm{inj}} = 30$ the configured cap on usable forecast steps. Candidate b has predicted centre $\mathbf{p}^{(b)}_{t+k|t}$; its third coordinate $z^{(b)}_{t+k|t}$ is altitude. Obstacle j has predicted centre $\hat{\mathbf{o}}_{j,t+k|t}$ and radius r_j, while the UAV radius is r_u. Their surface clearance is $\hat{d}^{(b)}_{j,k}$ and its minimum is $d^{(b)}_{\min}$. The indicator $\mathcal{C}_b$ equals one only when every rollout point stays inside the absolute altitude band and within 3 m of $z^{(b)}_{\mathrm{nom},k}$, the altitude of the closest point on the finite start-to-goal segment to that predicted position; the segment projection is clipped to its endpoints. Finally, $v^{(b)}_{\mathrm{end}}$ is terminal candidate speed; its inequality is the stopping-distance gate using 1.0 m s^{-2} available deceleration. The candidate contains 30 future UAV states, so its clearance gate compares all 30 time-aligned UAV–obstacle state pairs at 0.1-s intervals; it does not minimize relative distance continuously between two predicted states. The reported collision-free-arrival endpoint is stricter: it independently audits the saved true UAV and obstacle paths by continuous piecewise-linear closest approach between consecutive simulator states. The 30-step sequence also enters the MPC objective. The corridor condition applies to every DWA rollout point; the nominal altitude is taken from the direct start-to-goal line at the path's clamped along-route position. The reachable dynamic window is updated from the previous control using the acceleration bounds.

The 30-step DWA gate checks discrete, time-aligned states; the separate continuous piecewise-linear swept-path audit is an evaluation rule, not a continuous-time safety guarantee.

S1.3. Candidate score

The score-to-weight mapping and normalized weights are

$$\begin{aligned} q &= [1+\exp(-8(\tau-0.5))]^{-1}, \\ (w'_p, w'_h, w'_v, w'_o) &= (0.10+0.20q,\ 0.08+0.14q,\ 0.12(1+q),\ 0.45-0.25q), \\ w_i^{\mathrm{DWA}} &= \frac{w'_i}{\sum_{r\in\{p,h,v,o\}} w'_r}. \end{aligned} \tag{S5}$$

The logistic map converts τ to q, which smoothly changes four unnormalized score coefficients w'_p, w'_h, w'_v and w'_o. Dividing each by their sum gives w_i^{DWA} for position, heading, velocity and obstacle clearance, respectively; the summation index r runs over those four components. The candidate scores compare the 30-step DWA rollout endpoint with the endpoint of the current 30-step MPC reference, reward useful speed and obstacle clearance, and penalize vertical deviation. In the definitions below, $\mathbf{p}_{b,D}$ and v_b are the DWA candidate endpoint and speed, whereas $\mathbf{p}_{\mathrm{MPC},N}$ and v_{MPC} are the final position and speed of the current MPC reference. The vectors $\mathbf{h}_b$ and $\mathbf{h}_{\mathrm{MPC}}$ are the corresponding unit heading vectors formed from terminal pitch and yaw. All component scores are dimensionless.

$$\begin{aligned} S_{p,b} &= \left(1+\frac{\|\mathbf{p}_{b,D}-\mathbf{p}_{\mathrm{MPC},N}\|_2}{1\,\mathrm{m}}\right)^{-1}, & S_{h,b} &= \tfrac{1}{2}(1+\mathbf{h}_b^{\mathsf{T}}\mathbf{h}_{\mathrm{MPC}}), \\ S_{v,b} &= \tfrac{1}{2}\left[\left(1+\frac{|v_b-v_{\mathrm{MPC}}|}{1\,\mathrm{m\,s^{-1}}}\right)^{-1}+\frac{v_b}{2\,\mathrm{m\,s^{-1}}}\right], & & \\ S_{o,b} &= \frac{\min(d_{\min}^{(b)}, 5\,\mathrm{m})}{5\,\mathrm{m}}, & S_{z,b} &= \left(1+\frac{\max_{1\le k\le H_D}|z_{b,k}-z_{\mathrm{nom},k}|}{1\,\mathrm{m}}\right)^{-1}, \\ S_b &= w_p^{\mathrm{DWA}}S_{p,b}+w_h^{\mathrm{DWA}}S_{h,b}+w_v^{\mathrm{DWA}}S_{v,b}+w_o^{\mathrm{DWA}}S_{o,b}+w_zS_{z,b}. & & \end{aligned} \tag{S6}$$

Here $S_{p,b}$, $S_{h,b}$, $S_{v,b}$, $S_{o,b}$ and $S_{z,b}$ are the position-agreement, heading-agreement, velocity, obstacle-clearance and vertical-corridor scores of candidate b. The value $z_{b,k}$ is its altitude at rollout step k, and $z_{\mathrm{nom},k}$ is the corresponding direct-route altitude. Their weighted total is S_b. The planner selects the retained candidate with the largest total score. The fixed coefficient is $w_z = 0.25$; it is added after the four normalized weights and is not renormalized with them.

S1.4. Executed cycle and fallback

The implemented top-to-bottom cycle is:

1. Read the current UAV state and the latest 10 obstacle observations.
2. Predict 30 future obstacle offsets with the causal LSTM; each offset is relative to the latest observed centre and is added directly, not cumulatively.
3. At startup, solve MPC from the current state with this forecast to initialize the reference route and control sequence, then compute the first trust score. At later updates, shift the preceding MPC solution forward before computing trust.
4. Align the MPC sequence and DWA rollouts over steps 1–30 of the same forecast; update the heuristic score using the available MPC reference and its first-point mismatch with the current position.
5. Sample score-guided DWA controls, roll each out for 3 s (30 steps at 0.1 s), and test those UAV states against all 30 forecast positions before applying the corridor and braking gates and scoring retained candidates.
6. If the normal safe set is nonempty, form its expanded first-control box and retain the top-scoring DWA command. Trigger lateral recentering when the selected rollout's minimum predicted clearance exceeds 1.0 m and the UAV's current horizontal cross-track offset from the start–goal line exceeds 0.5 m. Set yaw rate

to 0.8 times the wrapped heading error toward the goal, clipped to the physical yaw-rate limit. Recompute the rollout and reapply the normal clearance, corridor and braking gates; use the adjusted command only if all gates pass, otherwise revert to the original screened sample.

7. If the normal safe set is empty, augment the reachable samples with low-speed controls at the lower edge of the dynamic window, a reachable pitch-rate command toward level flight, and bounded yaw-rate choices. Roll out every emergency candidate against the same forecast.

8. Retain an emergency candidate only when its predicted surface clearance is strictly positive, the full rollout remains within the flight corridor, and terminal speed satisfies the configured stopping-distance condition. Rank retained emergency candidates by predicted clearance, breaking ties toward lower terminal speed.

9. Recompute and re-screen the final emergency command against all three emergency conditions. If no candidate passes, mark the trial as having no feasible emergency action and terminate before issuing an unchecked command. This fail-closed simulator branch records planning infeasibility; it does not model instantaneous physical braking.

10. Re-solve MPC from the current state with the current forecast. Use the normal safe-set box only when the normal safe set is nonempty.

11. Execute the screened DWA or emergency command for 0.1 s; update state and observation history, and repeat.

The emergency branch differs from the normal 0.25-m candidate gate: it permits smaller positive clearance when the predicted surfaces remain separated and the stopping-distance condition passes. The planner rechecks the exact selected command before execution. A trial also ends after at most 650 state updates, equivalent to 65 s. Goal arrival and an infeasible emergency-action stop terminate execution early; a detected collision is logged but does not itself stop the simulator. For the Stage-1 development episodes, goal arrival required final distance within the configured goal tolerance and no swept-path contact. The historical five-controller results retain the endpoint definition and audit used in their original run bundle.

S2. LSTM training and prediction evaluation

At each 0.1-s planning cycle, the predictor maps the latest 10 observations for each obstacle to 30 three-dimensional future offsets. Every offset is anchored independently to the latest observed centre; it is not added to the preceding forecast. Samples are separated by 0.1 s, so the first and last observations are 0.9 s apart. An observation contains position, velocity and heading encoded by its sine and cosine. In clean-observation evaluation, velocity and heading are simulator-provided obstacle states; heading is obstacle yaw, distinct from UAV yaw. In the separate noisy-input diagnostic, velocity is recomputed from perturbed positions while heading is unchanged. Table S1 separates the network architecture from the data split and optimizer settings so the complete training configuration is easy to reproduce.

The training set contains synthetic trajectories from eight motion families. The split is made by trajectory, so no trajectory appears in both training and validation. Training inputs include current and one-step-delayed histories; a noisy view adds independent 0.03-m position noise while future targets remain clean and anchored to the noisy last observation. For noisy views, velocity is recomputed from perturbed positions, whereas simulator-generated heading remains unchanged. Normalization uses training trajectories only. Validation trajectories support model selection and early stopping; the independent open-loop probe is reported below.

Validation trajectories are separate from training trajectories and support model selection and early stopping. A separate open-loop probe evaluates 12 independently generated synthetic compound switchback trajectories, with 14 forecast windows per trajectory. Each track combines repeated stop–go motion with piecewise turn-rate reversals; the compound test trajectories are held out from training. In each forecast window, ADE is the average three-dimensional centre-position error over the 30 predicted steps and FDE is the average error at the final step. Mean ADE/FDE are 0.626/1.254 m for LSTM, 0.865/1.544 m for constant velocity, 0.864/1.506 m for Kalman and 1.033/1.974 m for static positions. Paired trajectory-cluster bootstrap intervals for LSTM minus constant velocity are -0.259 to -0.218 m (ADE) and -0.350 to -0.228 m (FDE); for LSTM minus Kalman they are -0.275 to -0.201 m (ADE) and -0.331 to -0.173 m (FDE). The 20,000 bootstrap replicates resample the 12 trajectories, retaining all windows and paired method outcomes for each selected trajectory. These open-loop metrics quantify position-prediction accuracy; closed-loop planning performance is evaluated separately in S4.

Table S1: LSTM architecture and training configuration.

Parameter	Setting	Unit or definition
Input and network		
Input history	10 observations; first-to-last span 0.9 s	0.1-s interval
Input channels	Position, velocity, cosine heading, sine heading	8 values per observation
LSTM layer	96 hidden units; use final sequence output	96 units
Dropout	0.2	Fraction
Fully connected layer	96 units followed by ReLU	96 units
Regression output	90 displacement values	30 steps × 3 axes
Forecast output	30 offsets, each relative to the latest observed position	3 s
Data and optimization		
Synthetic training set	800 trajectories from eight motion families	Generated trajectories
Trajectory split	640 training; 160 validation	No shared trajectories
Noisy-history augmentation	Independent 0.03-m position noise; clean future targets	Training input
Optimizer	Adam; learning rate 0.001; batch size 128	Per training run
Training limit	180 epochs; validation every 50 iterations	Maximum
Regularization	L2 coefficient 0.0001; gradient threshold 1	As implemented
Early stopping	Patience 12; retain best validation-loss model	Validation set
Random seed	20260905	Training-data setup

Online ADE and FDE summarize diagnostic runs retained in the run-level CSV. Goal arrival is the primary closed-loop outcome; held-out switchback prediction results are available in the supplementary CSV records.

S3. Development simulation settings

Tables S2 and S3 give the 3-s configuration used for Stage-1 development and the current seven-method evaluation. In this configuration, the network returns 30 positions over 3 s, DWA checks each reachable 3-s candidate rollout against positions 1–30, and MPC optimizes a 3-s route using the same time-aligned positions. A selected DWA command is applied for one 0.1-s update. The historical five-controller benchmark used 1-s DWA screening and is reported separately in S4.

Table S2: Workspace, vehicle and timing settings for the separate 3-s development configuration.

Group	Parameter	Value	Unit or definition
Workspace			
Scene	Workspace dimensions	$20 \times 20 \times 10$	m (x, y, z)
Scene	UAV start	$(1, 1, 1)$	m
Scene	Goal	$(18, 18, 8)$	m
Flight envelope	Altitude band	0.5–9.5	m (z-axis)
Vehicle model			
Vehicle	Effective radius	0.3	m
Vehicle	Maximum speed	2.0	m s^{-1}
Vehicle	Maximum pitch and yaw rates	0.8	rad s^{-1}
Vehicle	Maximum linear acceleration	1.0	m s^{-2}
Vehicle	Maximum pitch and yaw acceleration	0.5	rad s^{-2}
Simulation time			
Integration	State-update interval	0.1	s
Vehicle response	Speed-response time constant	0.5	s
Trial	Maximum duration	650 updates	65 s

Table S3: MPC and DWA parameters for the separate 3-s development configuration; the historical 1-s benchmark weights are identified separately.

Planner	Parameter	Value and definition
Prediction and planning horizons		
MPC	Route horizon	30 steps (3 s)
DWA	Candidate rollout	30 steps (3 s); selected command applied for one 0.1-s update
DWA	Forecast available / used by screening	All 30 predicted positions, time-aligned to the 3-s rollout
MPC objective and solver		
MPC	Objective weights	$w_p, w_u, w_f, w_{\Delta u}, w_r, w_o, w_s =$ $1, 10, 1, 50, 3, 20{,}000, 12{,}000$; in the S1.1 objective order
MPC	Soft safety margin	$d_{\text{soft}} = 0.35$ m
IPOPT	Iteration cap; stopping tolerance	300; 10^{-6}
DWA sampling and score		
DWA	Base sample budget	$N_{\text{base}} = 300$ candidates
DWA	Adaptive stochastic sample budget	round$[300(1 + \alpha e^{-\beta\tau})]$ with fixed $\alpha = 1$; fraction τ guided, plus the clipped MPC command
DWA	Guided sampling half-width	0.35 in each native control unit; clipped to the dynamic window
DWA	Stage-1 development trust-score weights	$[0.15, 0.15, 0.15, 0.55]$; equal-arm development rate 0.8042
DWA	Historical benchmark trust-score weights (S4)	$[0.35, 0.30, 0.15, 0.20]$; inherited, not tuned on the 500 scenes
DWA	Safety-trust normalization anchors	$d_{\text{low}} = 1$ m; $d_{\text{high}} = 5$ m
DWA	Reference-mismatch decay, α_T	3 m^{-1} in Stage 1 and the historical benchmark
DWA	Budget sensitivity, β	3 in Stage 1 and the historical benchmark
DWA	Logistic weight mapping	Dimensionless slope 8; dimensionless midpoint 0.5 (fixed implementation heuristics)
DWA	Candidate rejection and braking gate	Clearance > 0.25 m; deceleration 1.0 m s^{-2}
DWA	Adaptive score-weight ranges	Position 0.10–0.30; heading 0.08–0.22; velocity base 0.12; obstacle 0.20–0.45
DWA	Vertical-corridor score coefficient	$w_z = 0.25$, additive and unnormalized (fixed implementation heuristic)

The historical five-controller scene bank was generated by `generate_random_eval_scenarios` with master seed 20261015; scene seeds increase by one from 20261015 to 20261514. Each scene contains 3–8 obstacles, with each obstacle independently assigned one of seven motion families at equal probability: straight, turn, sinusoidal speed, acceleration, hover–go, zigzag or waypoint following. The manifest records each scene seed, obstacle count and assigned family. Obstacle radii are uniform on 1.0–1.8 m. Initial centres are placed 2–5 m to alternating sides of the start–goal diagonal, at stations formed from evenly spaced values between 3.8 and 14.6 m plus Gaussian jitter with a standard deviation (SD) of 0.25 m, clipped to 3.2–15.2 m; initial height is uniform on 2.2–8.0 m. Initial speed is uniform on 0.8–1.6 m s^{-1}, vertical speed is Gaussian with mean 0 and SD 0.03 m s^{-1}, and heading is set to either diagonal direction with Gaussian noise (SD 0.15 rad). Maneuver parameters are sampled within the ranges in the accompanying `scene_generation_specification.md`; the exact generator, manifest and historical per-run records accompany this supplement. The 48 development scenes used for Stage 1 were a separate scene set.

The trust score weights safety, goal progress, reference tracking (current-position mismatch to the one-step-old MPC reference) and command smoothness. High trust concentrates fewer samples near the clipped MPC command; low trust increases full-window exploration. The command is added once, and all candidates pass the same corridor and clearance checks. The 0.35 guided-sampling half-width, logistic slope 8, midpoint 0.5 and vertical-score coefficient $w_z = 0.25$ are fixed implementation heuristics, held constant in every integrated arm that uses them and not selected using held-out outcomes. The sampling half-width is applied in each control's native units ($\mathrm{m\,s^{-1}}$ for speed and $\mathrm{rad\,s^{-1}}$ for pitch and yaw rates) before clipping to the dynamic window; slope and midpoint are dimensionless. The additive w_z term is distinct from the four trust weights and is not renormalized with them.

The historical two-method forecast-sharing runs used Windows 64-bit, MATLAB R2025a and CasADi 3.8.0 with the 1-s DWA rollout. Timing begins before obstacle prediction and ends after DWA screening, the MPC solve, state advancement and post-step logging; one-time solver setup is excluded. Table S4 summarizes both the mean and median over timed steps. Each method had 1,500 timed runs. The mean step times differ by 0.07 ms in this environment. These descriptive local measurements are specific to this 1-s historical implementation and do not characterize the 3-s development configuration.

Table S4: Historical descriptive computation time in the two-method, 1-s DWA forecast-sharing evaluation. Step time covers prediction, planning, state advancement and logging; initialization is excluded.

Method	Attempts	Timed runs	Mean (ms/step)	Median (ms/step)
DWA-only LSTM	1500	1500	100.23	95.9
Shared LSTM	1500	1500	100.30	95.7

S4. Controller definitions and historical comparisons

S4.1. Methods in the completed five-controller comparison

The historical comparison comprised a latest-position-hold MPC–DWA reconstruction, standalone DWA + LSTM, standalone MPC + LSTM, integrated MPC–DWA with LSTM supplied only to DWA, and integrated MPC–DWA with the same LSTM forecast supplied to both layers. All five methods used the same 500 obstacle scenes and three matched sampling seeds. The latest-position reconstruction holds obstacle positions at their most recent observations in both MPC and DWA; it is a project-local implementation, not an exact reproduction of the cited MPC–DWA algorithm or its reported experiments.

The 3,000 shared-versus-DWA-only episodes are the corresponding two-arm records within this 7,500-run five-controller benchmark; they are not an additional set of simulation episodes.

Standalone DWA receives the causal LSTM forecast and samples a fixed grid over dynamically reachable speed, pitch-rate and yaw-rate commands. It scores 1-s rollouts without an MPC route, trust score or MPC-guided samples, then screens retained actions with clearance, corridor and braking checks. Standalone MPC receives the same type of LSTM forecast and optimizes the 30-step route objective, but directly applies its first command without DWA sampling or action screening; obstacle safety remains a soft objective penalty. In the integrated DWA-only condition, MPC holds latest observed obstacle positions while DWA uses LSTM forecasts. In the shared condition, both layers use the same time-aligned LSTM sequence. DWA screens its first 10 steps (1 s), whereas MPC uses all 30 steps (3 s). The shared-versus-DWA-only contrast therefore isolates forecast access by

MPC within the tested integrated implementation; the independent controllers provide contextual, non-matched comparisons.

S4.2. Historical forecast-sharing comparison (1-s DWA rollout)

The earlier forecast-sharing comparison used the same 500 independently generated mixed-motion 3D scenes (scenario master seed 20261015) and three matched sampling seeds per scene, for 1,500 runs in each integrated condition. Its 500-scene target followed a paired normal-approximation calculation based on the earlier 48-scene estimate (2.08 percentage points; scene-level SD, 15.99 percentage points), targeting 80% power at a two-sided 5% level. The trained predictor, vehicle model, planner objective, safety checks, sampler and stopping rules were fixed. The predictor returned the same 30-step (3-s) LSTM sequence in both conditions. DWA screened each 10-step (1-s) reachable action against forecast steps 1–10; MPC planned for 30 steps and, in the shared arm, used the full sequence. In the DWA-only arm MPC instead held obstacles at their latest observed positions. This contrast isolates MPC's access to the learned forecast. It differs from the 3-s development configuration described in S1–S3. The historical 48-scene experiment used a different DWA horizon and is reported separately. All scenes and attempts are included; the frozen design and analysis rule are in the earlier confirmatory protocol.

These earlier runs used clean, current-time simulator obstacle positions: observation noise and delay were both set to zero. Noisy and delayed histories were used in training augmentation and the separate S5 sensing diagnostic. The executed settings are documented in `confirmatory_protocol_clarification.md`. The endpoint was arrival within 0.5 m without collision, checked by closest approach along piecewise-linear motion between states. Runs not terminated earlier were classified as maximum-step non-arrivals after 650 updates (65 s). The paired contrast is shared LSTM minus DWA-only LSTM. We resampled the 500 complete scenes, retaining all three matched seeds and both methods, for 20,000 bootstrap replicates (MATLAB Twister seed 20261015). The prespecified criterion was a 95% interval entirely above zero; intervals for secondary outcomes are unadjusted.

Table S5: Historical mutually exclusive run outcomes (1,500 runs per method). Categories are assigned in order: safe arrival, any collision, collision-free infeasible stop, collision-free solver-only failure, then maximum-step non-arrival. Each column sums to 1,500.

Outcome	Shared forecast (MPC and DWA)	DWA-only forecast (DWA receives it)
Reached goal without collision, runs (%)	**936/1,500 (62.4%)**	**836/1,500 (55.7%)**
Collision recorded	0	2
No collision; infeasible-action stop	366	453
No collision/stop; solver-only failure	0	0
No collision/stop/solver; 650-step non-arrival	198	209

Two shared-arm runs recorded an MPC solve failure before later ending in the infeasible-stop category; the exclusive priority above prevents double counting. The complete event flags and the derived accounting are supplied in `five_method_run_audit.csv` and `five_method_terminal_outcomes.csv`.

Historical result. Sharing produced 100 more collision-free goal arrivals (936/1,500, 62.4%, versus 836/1,500, 55.7%; paired difference +6.7 percentage points, 95% scene-cluster CI +4.2 to +9.2). It favored sharing in 72 scenes, favored DWA-only in 24, and tied in 404 (three seeds per scene).

The run-level minimum surface clearance averaged 1.245 ± 1.085 m with sharing and 1.187 ± 1.046 m with DWA-only prediction; the paired difference was +0.058 m (95% scene-cluster CI +0.027 to +0.090; unadjusted secondary interval).

Distance travelled per run averaged 21.144 m with sharing and 19.743 m with DWA-only prediction; the paired difference was +1.401 m (95% scene-cluster bootstrap CI +0.931 to +1.906; unadjusted secondary interval). This average includes successful and incomplete runs, so it combines route geometry with distance travelled before termination and is not interpreted as the cost of a detour.

The earlier 48-scene, six-forecast-setting experiment is reported separately because it used a different DWA rollout.

S4.3. Historical five-controller architecture comparison

The integrated controllers in this 7,500-run benchmark used inherited trust weights $[0.35, 0.30, 0.15, 0.20]$. The later Stage-1 development selection $[0.15, 0.15, 0.15, 0.55]$ was not applied to these runs. This earlier comparison's latest-position MPC–DWA, standalone DWA and standalone MPC arms reused the exact 500 scenes, obstacle tracks, plant settings and sampling seeds 1–3 from its confirmatory bundle. The coupled MPC–DWA arms and standalone DWA used 1-s DWA rollouts; MPC retained a 30-step horizon. The two standalone arms were regenerated in a versioned fairness rerun: standalone DWA used the integrated planner's strictly positive emergency-clearance rule, while its 0.25-m normal gate and all corridor and braking checks were unchanged; standalone MPC code and parameters were unchanged. The four LSTM-guided arms use the same frozen predictor; the latest-position baseline does not call it. Together the five arms contain 7,500 trials, 1,500 per controller.

The historical trust weights and the later Stage-1 development selection are distinct, as specified in S1.2. The earlier v08 standalone-DWA record reports 1,146/1,500 collision-free arrivals (76.4%) with no collision runs; the versioned emergency-screen rerun used here reports 1,236/1,500 (82.4%). These results come from distinct implementations and are retained separately, not pooled or substituted for one another. Parameters were not tuned on these evaluation outcomes.

Analysis resampled all three paired seeds within each of the 500 scenes for 20,000 scene-cluster bootstrap replicates. The shared-minus-latest-position contrast was frozen before the direct baseline run, and the shared-minus-DWA-only interval remains the original confirmatory contrast in that earlier protocol. Standalone-controller intervals are secondary and unadjusted for multiplicity. For the secondary `MedianPlanningStep_ms` contrast, each scene contributes the median of its three run-level mean step times, and the reported point estimate is the mean paired difference across 500 scenes; this estimand differs from the descriptive method-level median over all 1,500 run-level mean step times in Table S6. These five-controller results are separate from the 3-s development configuration.

Table S6: Earlier five matched controllers evaluated on 500 scenes with three seeds per scene. Collision-free arrival was the principal outcome within that comparison; mean minimum clearance is calculated per run from continuous swept paths. Planning time is descriptive and is not used to rank architectures because timing boundaries differ.

Controller	Collision-free goal arrival	Collision runs	Mean minimum gap (m)	Median step time (ms)
MPC–DWA, latest-position-hold	33/1,500 (2.2%)	624 (41.6%)	0.532	79.5
Standalone DWA + LSTM	1,236/1,500 (82.4%)	0 (0%)	1.515	5.9
Standalone MPC + LSTM	1,428/1,500 (95.2%)	36 (2.4%)	0.674	29.7
Integrated MPC–DWA, DWA-only LSTM	836/1,500 (55.7%)	2 (0.13%)	1.187	95.9
Integrated MPC–DWA, shared LSTM	936/1,500 (62.4%)	0 (0%)	1.245	95.7

Table S7: Exhaustive mutually exclusive terminal accounting for the five-controller comparison. Priority is safe arrival, any collision, collision-free infeasible-action stop, collision-free solver-failure termination, then collision-free 650-step non-arrival. Every row sums to 1,500.

Controller	Safe	Collision	Infeasible	Solver	650-step
MPC–DWA, latest-position-hold	33	624	143	0	700
Standalone DWA + LSTM	1,236	0	264	0	0
Standalone MPC + LSTM	1,428	36	0	9	27
Integrated MPC–DWA, DWA-only LSTM	836	2	453	0	209
Integrated MPC–DWA, shared LSTM	936	0	366	0	198

The accounting is derived from the saved run flags without rerunning the simulator and is archived in `five_method_terminal_outcomes.csv`. Collision is assigned before other failure flags because collision-free arrival is the primary endpoint; an integrated run can record an MPC solve failure and later stop infeasibly, so event totals outside this table may overlap.

Shared LSTM produced 903 more collision-free arrivals than latest-position MPC–DWA (936/1,500 versus

33/1,500), a paired increase of +60.2 percentage points (95% scene-cluster CI +56.2 to +64.2). Collision incidence fell from 624/1,500 (41.6%) to zero; the paired collision-rate difference was -41.6 points (95% CI -45.5 to -37.5). Mean swept minimum clearance increased by 0.712 m (95% CI +0.643 to +0.784). Descriptive median planning-time values were 79.5 ms for latest-position MPC–DWA and 95.7 ms for shared LSTM; the timing boundaries differed, so these values are not interpreted as a comparative efficiency effect. These results quantify historical outcomes for the reconstructed coupled architecture.

The shared controller's collision-free arrival was lower than standalone DWA by 20.0 percentage points (95% paired scene-cluster CI, -24.8 to -15.1) and lower than standalone MPC by 32.8 points (-37.1 to -28.5). Standalone MPC reached the goal more often but had 36 swept-collision runs; shared LSTM had no collisions and a larger mean minimum gap. Standalone DWA also had no collisions, a larger mean minimum gap and higher arrival. The shared method is therefore the best tested coupled MPC–DWA variant, whereas standalone MPC has the highest overall arrival rate.

S5. Single-scene sensing-pressure check

The sensing diagnostic evaluates one repeated-encounter scene with three matched seeds under four conditions: clean observations, 0.05-m position noise, one-step observation delay, and their combination. Obstacle paths and controller settings are fixed; these runs are separate from the 500-scene comparison in S4. In noisy conditions, noise affects positions only, velocity is recomputed from noisy positions, and heading ψ remains the simulator-provided value, corresponding to an ideal heading observation. Table S8 reports terminal outcomes, sampled clearance and forecast error. These four conditions are descriptive diagnostics of this single scene, not population-level or full-state sensor-noise robustness evidence.

Table S8: Shared-LSTM outcomes under four sensing conditions in one repeated-encounter scene. Each condition has three matched seeds. Clearance is the per-run minimum sampled at 0.1-s post-action states; ADE and FDE are the mean and standard deviation across seeds. Terminal counts and metric summaries are descriptive, not population estimates.

Condition	Goals ($n/3$)	Collision runs ($n/3$)	Infeasible stops ($n/3$)	Clearance mean ± SD (m)	ADE / FDE mean ± SD (m)
Clean	0/3	0/3	3/3	0.924 ± 0.674	0.560 ± 0.027 / 1.302 ± 0.035
0.05-m position noise	0/3	0/3	3/3	1.142 ± 0.340	0.667 ± 0.019 / 1.480 ± 0.036
One-step observation delay	0/3	0/3	3/3	1.388 ± 0.005	0.610 ± 0.000 / 1.397 ± 0.000
Noise and delay	0/3	0/3	3/3	1.023 ± 0.422	0.697 ± 0.018 / 1.523 ± 0.048

All 12 shared-LSTM runs ended in a fail-closed stop before reaching the goal; none recorded a collision. Under this obstacle trajectory, the planner found no feasible emergency action. Clearance and ADE/FDE are descriptive means and standard deviations across three seeds. The four-method summary is in `sensing_summary_revised.csv`; run-level records are in `sensing_revised.csv`.

S6. Earlier baseline comparisons retained separately

Earlier baseline experiments compare static-position, constant-velocity (CV) and Kalman forecasts; their original figures and analysis records are retained in this section. Because these studies used different scenes and a different DWA action-rollout setting, they are reported separately from the historical 500-scene estimate and the current seven-method exploratory evaluation.

S6.1. Early 16-scene baseline pilot

This historical pilot used four fixed scenes and 12 random scenes, each with three matched seeds; it is retained separately from the Stage-1 development calibration, the historical 500-scene benchmark and the current seven-method exploratory evaluation. In the fixed suite, goal arrivals were 10/12 for static positions, 9/12 for CV, 9/12 for Kalman and 12/12 for shared LSTM. In the random suite, arrivals were 26/36, 33/36, 33/36 and 36/36, respectively. The scene-cluster estimate for the random-suite shared-LSTM minus CV difference was +8.3 percentage points (95% CI, 0.0 to 25.0), spanning zero. The earlier four-panel results figure is retained in Fig. S1; its panels include random-scene success and clearance, forecast error and a single-scene interface/horizon ablation.




Figure S1: Retained historical results figure from the earlier random-scene comparison (36 runs per method). It shows Static, CV, Kalman and shared LSTM, with separate forecast-error and single-scene interface/horizon panels. This pilot is reported separately and not pooled with the historical 500-scene benchmark or the seven-method exploratory evaluation.

S6.2. Earlier 48-scene, six-setting comparison

The subsequent historical benchmark tested Static, CV, Kalman, MPC-only LSTM, DWA-only LSTM and shared LSTM in 48 scenes with three matched seeds per setting (144 runs per method; 864 attempts). Table S9 reports method-level goal and failure outcomes; Fig. S2 shows scene-cluster intervals and paired contrasts. The shared-LSTM versus CV contrast was the prespecified primary comparison in that study: 125/144 goal arrivals (86.8%) versus 103/144 (71.5%), a paired difference of +15.28 percentage points (95% scene-cluster bootstrap CI, +6.25 to +25.69). The shared-versus-DWA-only difference was +2.08 percentage points (95% CI, -1.39 to +6.94). Its DWA rollout differed from the 1-s rollout in the historical five-controller benchmark and the 3-s development configuration, so these estimates remain separate historical evidence.

Table S9: Run-level outcomes in the earlier 48-scene six-setting comparison, with 144 attempts per method. Clearance is the mean ± standard deviation of each run's minimum. Collision, infeasible-stop and solver-failure counts are separately audited flags and may co-occur.

Method	Goals, $n/144$ (%)	Collisions	Infeasible stops	Solver failures	Minimum clearance, mean ± SD (m)
Static	97/144 (67.4%)	24	44	0	1.038 ± 1.121
CV	103/144 (71.5%)	0	39	0	1.400 ± 1.105
Kalman	106/144 (73.6%)	0	36	1	1.335 ± 1.079
MPC-only LSTM	109/144 (75.7%)	23	34	0	1.035 ± 1.095
DWA-only LSTM	122/144 (84.7%)	0	22	0	1.465 ± 1.029
Shared LSTM	125/144 (86.8%)	0	19	0	1.425 ± 0.980

Figure S2 displays all six goal-arrival rates and the paired shared-LSTM contrasts. The CV contrast was prespecified in that benchmark; the remaining paired intervals are secondary and unadjusted. The complete run audit, scene-cluster outcomes, bootstrap contrasts, scenario manifest and protocol are retained in the separate historical 48-scene folder and the reproducibility archive.




Figure S2: Earlier six-setting comparison across 48 scenes. (a) Goal-arrival rates, with 95% scene-cluster intervals and counts. (b) Paired success-rate differences (shared LSTM minus each baseline); the vertical line marks zero. The CV contrast was prespecified in that study; other intervals are unadjusted. These estimates are separate from the historical 500-scene benchmark and the current seven-method exploratory evaluation.

The former main-text scene-2 route comparison is also retained as a historical illustration. It compares CV, Kalman, DWA-only LSTM and shared LSTM on the same prescribed obstacle tracks; these paths are separate from the new standalone-controller evaluation.




Figure S3: Historical four-method 3-D route example from scene 2 and DWA sampling seed 1. Panels (a)–(d) show CV, Kalman, DWA-only LSTM and shared LSTM under the same prescribed obstacle tracks. The green triangle marks the start, the red star the goal, and the open circle CV's recorded early-stop endpoint. In this example, CV stopped before the goal; the other three methods reached the goal, and all four routes were collision-free under the swept-path test. Each route contains only its saved states through the recorded terminal point; none is extended or interpolated. Obstacle tracks show scene context and are not time-aligned with route durations. This single historical example illustrates route geometry, not aggregate performance, and is reported separately from the historical five-controller benchmark and current seven-method evaluation.

S7. Representative routes from the earlier five-controller comparison

Fig. S4 shows the historical scene 404, seed 2 example for the reconstructed latest-position MPC–DWA baseline and four LSTM-guided controllers under identical obstacle tracks. The reconstructed baseline collides at step 224 (minimum swept clearance, −0.0603 m). Standalone DWA + LSTM stops after 20 steps, 22.06 m from the goal, following an infeasible action set. Standalone MPC + LSTM collides at step 262; although its final state is 0.49 m from the goal, its minimum swept clearance is −0.236 m. In the integrated DWA-only-LSTM run, no safe candidate or feasible emergency action remains after 220 steps, leaving the UAV 16.23 m from the goal. Only integrated shared LSTM reaches without collision, after 253 steps with 0.583 m minimum swept clearance. Each overlaid route contains only recorded states through its terminal step. In the figure, × indicates a swept collision somewhere along a run, not its terminal point; square and circle markers denote a stop and collision-free arrival,

respectively. This selected scene is illustrative; aggregate outcomes are tabulated separately in Table S6. It is one case from the historical five-controller comparison, not an estimate of overall performance.




Figure S4: Historical five-controller 3-D route overlay from scene 404, seed 2 in a 20 m × 20 m × 10 m workspace. The five overlaid routes are reconstructed MPC–DWA with latest-position-hold (collision, step 224), standalone DWA + LSTM (stopped, step 20), standalone MPC + LSTM (collision, step 262), integrated MPC–DWA with LSTM supplied only to DWA (stopped, step 220), and integrated MPC–DWA with shared LSTM (collision-free goal arrival, step 253). Each trajectory ends at its logged terminal state. The triangle and star mark the common start and goal; squares denote stops, circles denote collision-free arrival, and × denotes a swept collision somewhere along that run, not at the marker. Dashed lines show the in-workspace portions of the same three obstacle tracks. This route-only illustration has no aggregate-rate panel; aggregate outcomes are tabulated separately in Table S6.

S8. Seven-method exploratory evaluation

S8.1. Frozen design and outcome definitions

This limited-scope evaluation compares seven matched controller arms on 100 newly generated, unique-content-hashed scenes, with sampling seeds 1–3 shared across all methods (300 episodes per arm; 2,100 planned episodes total). The arms are standalone DWA with CV prediction, standalone MPC with CV prediction, coupled MPC–DWA with CV in both layers, coupled MPC–DWA with LSTM supplied to MPC only, coupled MPC–DWA with LSTM supplied to DWA only, coupled MPC–DWA with the same LSTM forecast supplied to both layers, and a project-local latest-position-hold MPC–DWA reconstruction. The last arm is an architectural reconstruction, not an exact reproduction of the cited method. All arms use 0.1-s updates, a 30-step (3-s) MPC horizon and, unlike the historical five-controller benchmark, a 30-step DWA screening horizon. The trust vector was selected in the separate 4,320-episode Stage-1 development sweep; $\alpha_T = 3\,\mathrm{m}^{-1}$ and $\beta = 3$ were fixed implementation settings. The interrupted Stage-2 calibration did not select these settings and contributes no outcomes to this comparison.

The evaluation is exploratory and was defined by an internal scope amendment, not an external preregistration. Its primary outcome is collision-free goal arrival: the terminal position must lie within the recorded goal tolerance and the complete trajectory must have no swept-path contact. Continuous contact is recomputed from piecewise-linear relative motion between adjacent saved states; clearance at or below zero counts as contact. All attempted episodes and their terminal categories are retained. For each method, the three seeds are averaged within each scene; absolute rates use 20,000 scene-cluster bootstrap resamples, and the six shared-LSTM-minus-comparator primary contrasts use centered max-$|t|$ simultaneous 95% intervals. There is no post-hoc weighted composite. Any

inferential superiority claim requires the shared-LSTM arm to have the highest observed primary rate and all six simultaneous interval lower bounds above zero.

Secondary outcomes follow the frozen multidimensional comparison contract: swept-contact incidence and minimum swept clearance use all episodes; path length and time to goal use collision-free arrivals only and report their denominator; planning latency is summarized descriptively under the shared simulator conditions and is not presented as onboard flight latency. Failure categories are mutually exclusive: swept contact, collision-free arrival, no-contact infeasible stop, no-contact timeout, or other non-arrival. Figure 2 shows a post hoc route example (scene 72, seed 2). Shared LSTM and standalone DWA arrived safely; standalone MPC reached the goal tolerance after swept contact, position-hold MPC–DWA collided before arrival, and the other three methods stopped without contact. All six comparator paths span at least 5 s. This example is descriptive. Supplementary Fig. S5 preserves the only matched set in which shared LSTM alone arrived safely and all other methods had GoalArrival = 0 (scene 79, seed 2). The original scene-1/seed-1 routes remain archived.




Figure S5: Unique shared-LSTM safe-arrival example from scene 79, seed 2. Among 300 matched sets, this was the only set in which shared LSTM reached the goal without swept contact and all six other methods had GoalArrival = 0. One comparator had swept contact; five stopped without contact. Paths contain only saved positions through each recorded terminal state, with no smoothing, interpolation or extension. Method-specific colors, line styles and route-point marker shapes aid identification. This outcome-selected illustration is descriptive; all population-level comparisons use the complete evaluation.

S8.2. Seven-method outcomes

The run-level outcomes, denominators, clustered intervals, paired contrasts, secondary distributions and failure-category counts are archived with the v13 evidence package. These results are presented only after all 2,100

episode keys pass integrity and coverage checks; they are not pooled with the earlier 500-scene benchmark or the 4,320-episode development set.

S9. Reproducibility files

The reproducibility materials distinguish the 100-scene seven-method exploratory evaluation from the completed historical five-controller benchmark and the separate 4,320-episode Stage-1 development calibration. Scene identifiers, seeds and motion families are recorded in each scenario manifest; their SHA-256 values are listed in the audit records:

`10D86F1D0BA1146B9777C82A63AFCFB526DA9E309C961D4B5B1A849C4D9BCCF1`

The v13 evidence archive contains the manuscript sources, figures, bilingual reader, historical run-level records, Stage-1 recovered episode table, seven-method exploratory aggregates and their integrity manifests. Original episode MAT checkpoints remain unchanged in the project results directory and are not duplicated in the archive; their SHA-256 hashes are included. The incomplete Stage-2 calibration remains excluded from outcome claims. These experiments use prescribed obstacle tracks; no real-flight result or public data DOI is claimed here.

Table S10: Artifacts documenting the reported historical benchmark and separate Stage-1 development calibration. The two evidence sets are not pooled.

Artifact	Purpose	Expected content
`scenario_manifest.csv`	Historical assignment of scene identifiers, seeds and motion families	500 historical scenes
`five_method_run_audit.csv`	Historical run-level joined audit	7,500 historical rows
`five_method_terminal_outcomes.csv`	Historical mutually exclusive terminal accounting used in Table S7	5 controllers; 1,500 each
`five_method_summary.csv`	Historical controller-level arrival, collision, clearance and timing summaries	5 controllers
`five_method_paired_bootstrap.csv`	Historical shared-minus-comparator scene-cluster intervals	20,000 resamples
`five_method_absolute_bootstrap.csv`	Historical absolute scene-cluster intervals for each controller	20,000 resamples
`confirmatory_protocol_clarification.md`	Historical shared-versus-DWA-only design and stopping rule	500 scenes; 3 seeds; 1-s DWA
`original_mpc_dwa_baseline_protocol.md`	Protocol for the historical project-local latest-position reconstruction	1,500 historical runs
`v12a_stage1_recovery_audit_20261014.md`	Independent validation and selection record for Stage 1	4,320 existing episodes; 0 new simulations
`pooled_development_raw.csv`	Stage-1 recovered run-level outcomes	4,320 rows
`pooled_episode_sha256.csv`	Hashes linking the outcomes to preserved MAT checkpoints	4,320 hashes
`pooled_calibration_artifact_sha256.csv`	Stage-1 calibration artifact integrity register	8 files
`reproducibility_package.zip`	Current unified v13 source, data and audit archive	SHA-256 sidecar
`scripts/`	Versioned simulation, recovery and analysis code	Historical and development workflows

S10. Verified outcomes from the 100-scene exploratory evaluation

All 2,100 planned episodes passed integrity checks. Table S11 reports collision-free arrivals and swept contacts for seven arms (300 episodes per arm); Table S12 gives the six paired shared-LSTM contrasts.

Table S11: Observed collision-free goal arrivals and swept contacts in the verified 100-scene exploratory evaluation. Each arm has 300 episodes (100 scenes with three matched seeds).

Method	Collision-free arrivals, $n/300$ (%)	Swept contacts, $n/300$
Standalone DWA (CV)	234/300 (78.0%)	0/300
Standalone MPC (CV)	276/300 (92.0%)	15/300
Coupled MPC–DWA (CV in both layers)	204/300 (68.0%)	0/300
MPC–DWA (LSTM to MPC only)	219/300 (73.0%)	0/300
MPC–DWA (LSTM to DWA only)	224/300 (74.7%)	0/300
MPC–DWA (shared LSTM)	221/300 (73.7%)	0/300
Reconstructed MPC–DWA (latest-position hold)	172/300 (57.3%)	50/300

For paired inference, the three seeds were averaged within each scene; 20,000 scene-cluster bootstrap replicates and a centered max-$|t|$ critical value of 2.59005 gave simultaneous 95% intervals. Differences are in percentage points (pp), with positive values favoring shared LSTM for collision-free arrival.

Table S12: Shared-LSTM minus comparator differences in collision-free goal-arrival rate. Intervals are simultaneous 95% scene-cluster bootstrap intervals across the six comparisons.

Comparator	Difference (pp)	Simultaneous 95% CI (pp)
Standalone DWA (CV)	-4.3	$[-16.8,\ 8.1]$
Standalone MPC (CV)	-18.3	$[-29.6,\ -7.0]$
Coupled MPC–DWA (CV)	$+5.7$	$[-3.4,\ 14.7]$
MPC–DWA (LSTM to MPC only)	$+0.7$	$[-9.0,\ 10.3]$
MPC–DWA (LSTM to DWA only)	-1.0	$[-4.8,\ 2.8]$
Reconstructed MPC–DWA (latest-position hold)	$+16.3$	$[5.1,\ 27.6]$

Among the six contrasts, shared LSTM exceeded the latest-position-hold reconstruction, while standalone MPC-CV exceeded shared LSTM; the other four intervals included zero.

Integrity: all 2,100 planned keys appear once. One invalid-sidecar scene-58/seed-2 attempt was preserved but excluded; raw results, logs and hashes remain archived. No planned key fails. Historical 500-scene, 4,320-development, CV/Kalman and scene-404 records remain separate and were not pooled.