Math Book Template

Felix Benning

2025-06-12

Table of contents

O.	vervi	ew		1
	H5P	integration demo \dots		1
1	Usage guide			
	1.1	H5P Integration		3
	1.2	Global LaTeX Macros		4
	1.3	Mathematical equations		5
		1.3.1 Equations in LaTeX		6
		1.3.2 Equations in Quarto		7
		1.3.3 Aligned-Overset		10
		1.3.4 Theorem environments		11
	1.4	Publishing the book as a website		12
2	$\mathbf{U}\mathbf{se}$	ful extensions		13
3	Det	ails		14
	3.1	Global LaTeX Macros		14
References				15

Overview

This is a template for a Quarto math book or lecture script. Quarto¹ is a framework to render Markdown documents into html and via LaTeX into pdf. The reason you may want to target html is immediately illustrated if you read the web version of this documentation. For example, try to hover over the footnote on "Quarto", or over the following equation reference Equation 1.

This interactivity is something that is impossible with pdf. And since LaTeX can only really target pdf this is a problem. However LaTeX is really good at equations and other academic features that make it difficult to replace. Quarto provides these features.

- 1. It has bibliographic reference management that can generate citations e.g. Knuth [1] based on the cite keys in bibtex .bibtex and biblatex .bib files. Try to hover over the citation!
- 2. It has machinery to cross-reference figures, tables, sections, theorems, etc.
- 3. And most importantly for maths, it is integrated with the mathjax JavaScript library that can render LaTeX equations on websites, like this one for example:

$$\mathbb{N} \subset \mathbb{Z} \subset \mathbb{Q} \subset \mathbb{R} \subset \mathbb{C} \tag{1}$$

H5P integration demo

H5P's default multiple choice example (source).

To learn more about Quarto books visit https://quarto.org/docs/books.

¹Quarto is a language agnostic the successor to R Markdown, both of which are built on the universal document converter Pandoc. R Markdown allowed for R code snippets to be included in a markdown document which were executed before display. Quarto also allows this for Python and JavaScript.

Chapter 1

Usage guide

- 1. Install Quarto, LaTeX and R¹.
- 2. To use this template type the following into a terminal

quarto use template FelixBenning/math-book

i Add to existing project

You can also use quarto add FelixBenning/math-book to add this template to an existing quarto project. However to use the global macros feature (Section 1.2) you need to manually copy the file _macro_processing.yml into your root directory.

3. Update the configuration in the file _quarto.yml marked with a TODO (e.g. title, author, site-url, etc.)

For the standard features refer to Quarto's documentation we will focus on the features specific or at least important to this template.



In the web version of this documentation, try to click on the GitHub symbol \bigcirc next to the title in the top left. If you read it on a smaller device you may first need to open the left sidebar. This will lead you to the GitHub repository of this template. Next to it is a button to download the pdf version.

If your device is wide enough for the Table of Contents to be displayed on

 $^{^{1}}$ required for the global macro feature Section 1.2

the right, you can click on "O View source" to be directed straight to the .qmd file that produced this chapter. This way you can see how certain features are used by example.

There is also an "Q Edit this page" button. If someone finds a spelling error for example this allows them to suggest an edit. Note that if they do not have access to the GitHub repository they cannot change it directly.

H5P Integration 1.1

This template includes the tunapanda/h5p-standalone project and thereby supports the addition of H5P files without the need for a separate H5P server. H5P files (with the .h5p file extension may be added as follows):

- 1. Change the .h5p file extension to a .zip extension
- 2. unzip the zip file and place the resulting folder (referred to as my-h5p-folder in the following) into the folder assets/h5p-content/ of the Quarto project.
- 3. In Quarto markdown file where you want to add the h5p content add the following

```
::: {#my-h5p-folder .h5p}
```

or alternatively

```
<div id="my-h5p-folder" class="h5p"></div>
```

🛕 Possible issue: Missing libraries

Historically, every H5P file with the extension .h5p used to include the H5P libraries necessary to make the content work. More recently, these libraries are not always included (see this GitHub issue). In this case the my-h5p-folder does not include folders of the form H5P.AdvancedText, H5P.Audio, H5P.Blanks, etc. But without these libraries the content does not work.

To make it work, simply copy these libraries from an older h5p file into this folder (e.g. from the multiple-choice example of this template)



A Possible issue: 404 files not found

If your book is in the GitHub repository my-repo and published with GitHub Pages, then the base url is something like https://username.github.io/my-repo/ (if you did not configure a custom domain). Locally the base repository is localhost however. To ensure H5P works when deployed and when testing locally, the code in h5p-collector.qmd uses a heuristic based on the book.site-url configuration in the _quarto.yml file to find the h5p files. So make sure this configuration is set correctly!

1.2 Global LaTeX Macros

A very important feature for LaTeX users is the possibility to define custom macros. For example the following custom macros

```
\newcommand{\real}{\mathbb{R}}
\newcommand{\complex}{\mathbb{C}}}
```

can be used to produce $\mathbb{R} \subset \mathbb{C}$ from \real \subset \complex.

i What is the benefit of macros?

The notation for the natural numbers $\mathbb{N} = \{1, 2, 3, \dots\}$ requires "Blackboard letters" for example. Those can be achieved using the command \mathbb - specifically \mathbb{N}. A custom macro may be defined as follows in LaTeX

```
\newcommand{\nat}{\mathbb{N}}
```

Observe that such custom macros may not only be used to abbreviate commands, e.g. \n instead of \m to produce \mathbb{N} , but it can also be used to create semantic placeholders for symbols that can be changed later. For example one may initially choose the letter η to denote a step size before realizing that this letter is needed for something else. If a \stepsize macro is used it is trivial to replace

```
\newcommand{\stepsize}{\eta}
```

by a different letter, say h.

```
\newcommand{\stepsize}{h}
```

An update to the command immediately updates every occurrence of \stepsize.

These macro definitions can be placed into a global macros.tex file and annotated with LaTeX comments. This file will be automatically included in the LaTeX target and therefore the pdf.

Unfortunately the macros cannot be automatically included in the html target. To make sure macros also work for the html target it is necessary to add the following line to the start of any .qmd chapter file.

{{< include _macro_processing.qmd >}}

Important

This templates includes the <code>_macro_processing.qmd</code> file in the root directory. If this template is added to an existing project, this file must be manually added to the root of the project.

Details about this design can be found in Section 3.1 and also in this GitHub discussion. The Quarto developers may add a better mechanism in the future.

1.3 Mathematical equations

To understand how Quarto deals with mathematical equations it is necessary to understand how equations are handled in LaTeX and html (i.e. the JavaScript libraries mathjax or KaTeX). Readers that understand equations in Quarto and their limitations may want to skip to Section 1.3.3 where the aligned-overset feature is discussed that is special to this template.

LaTeX is built on TeX which simply toggles between 'normal mode' and 'math mode' using dollar signs e.g. $e^{i\gamma} + 1 = 0$ renders as: $e^{i\pi} + 1 = 0$. For display equations TeX allows for the use of double dollar signs, e.g.

$$f'(x) = \lim_{h \to 0} \frac{f(x+h) - f(x)}{h}$$

which is rendered like this

$$f'(x) = \lim_{h \to 0} \frac{f(x+h) - f(x)}{h}.$$

JavaScript libraries like mathjax or katex only implement math mode and generally scan for this dollar syntax in an html page to process it. However, at least mathjax can also be configured to work with the more advanced equation environments provided by LaTeX.

1.3.1 Equations in LaTeX

However LaTeX built more sophisticated display equation environments on top of this simple toggle and it is therefore not recommended to use these primitive TeX macros for display equations in LaTeX. Instead of \$\$ math \$\$ LaTeX authors are encouraged to use the syntax

```
\begin{environment}
    math
\end{environment}
```

Here the word environment is replaced by one of the following:

1. equation results in a numbered display equation, equation* in an unnumbered display equation.

```
Note

\[...\] is an alias for the equation∗ environment.
```

In contrast to the primitive TeX syntax (\$\$... \$\$), LaTeX equations adjusts the spacing of the equation depending on the length of the sentence before and after the equation. If the line before the equation only contains a single word, the equation is packed tighter since there is already a lot of white space to the right of this word.

2. align is a numbered display equation environment that allows the user to set alignment points with & letters. For example

```
\begin{align}
    (a + b)^2
    &= (a + b)(a + b) \\
    &= a^2 + ab + ba + b^2 \\
    &= a^2 + 2ab + b^2
\end{align}
```

which is roughly² rendered as

$$(a+b)^2 = (a+b)(a+b)$$
 (1)

$$=a^2 + ab + ba + b^2 \tag{2}$$

$$= a^2 + 2ab + b^2 (3)$$

²due to the issues with equation numbering in quarto explained in Section 1.3.2 every line was manually tagged using \tag here instead of automatically numbered.

The align* environment is again the un-numbered pendant which results in

$$(a+b)^{2} = (a+b)(a+b)$$

$$= a^{2} + ab + ba + b^{2}$$

$$= a^{2} + 2ab + b^{2}$$

3. alignat (or alignat*) works similar to align (or align*), but allows for multiple alignment columns.

1.3.2 Equations in Quarto

Quarto essentially only allows the dollar sign syntax. However, the display equations using double dollar signs (\$\$... \$\$) are converted to LaTeX equation environments when targeting pdf via LaTeX. More specifically, un-annotated equations are converted to un-numbered equation* environments while a 'tagged equation'

```
f'(x) = \lim_{h \to 0} \frac{f(x+h) - f(x)}{h}
$$ {#eq-differentiation}
```

is converted into a numbered equation

```
\label{eq-differentiation} $$ \ell(x) = \lim_{h \to 0} \frac{f(x+h) - f(x)}{h} \end{equation}
```

rendered in html as

$$f'(x) = \lim_{h \to 0} \frac{f(x+h) - f(x)}{h}$$
 (1.1)

The key @eq-differentiation can be used to produce a link (Equation 1.1).

Unfortunately Quarto does not support aligned equations using the align environment. However it is possible to use the aligned environment inside of math mode; similarly the alignedat environment can be used in math mode in place of alignat.

To produce an aligned equation one can therefore use the syntax

```
$$
\begin{aligned}
    (a + b)^2
    &= (a + b)(a + b) \\
    &= a^2 + ab + ba + b^2 \\
    &= a^2 + 2ab + b^2
```

```
\end{aligned}
$$ {#eq-aligned-demo}
```

This renders as

$$(a+b)^{2} = (a+b)(a+b)$$

$$= a^{2} + ab + ba + b^{2}$$

$$= a^{2} + 2ab + b^{2}$$
(1.2)

Observe that the 'Quarto-way' to tag equations only allows for one label per equation which is different from line-by-line numbering that LaTeX provides with the align environment. This is an unsolved issue at the moment.

There are two possible **workarounds**. The first workaround I strongly recommend against, under the assumption that:

- You want to reference equations from different chapters.
- You want to keep the equation preview on hover in html.

I recommend the second workaround if you are willing to duplicate the equation for the few cases you actually need to reference particular lines in aligned equations. This assumes that:

• Aligned equations explain how to get from the first element to the last. Afterwards the steps in the middle can generally be forgotten. So in the vast majority of cases it is unnecessary to label individual lines.

i Workaround 1: Ignore Quarto

Recall that mathjax can deal with LaTeX equation environments? Instead of the dollar syntax you can simply place naked \begin{...} \end{...} tags into your .qmd files. This will be correctly rendered by mathjax in html and will correctly be converted into LaTeX. But there are caveats. The first caveat can be fixed: mathjax does not treat equation differently from equation* by default and omits equation numbers altogether by default. This setting can be changed and Mathjax is already configured to behave like LaTeX in this template (this is not the default of Quarto). But since the mathjax equation numbering is independent of Quartos, the numbering is going to be incorrect if you use both. For this reason some authors recommend never using the Quarto syntax and only relying on mathjax for equation numbering. To do so simply use the \label{eq-name} and \ref{eq-name} tags you may know from LaTeX. However,

 mathjax cannot see anything beyond the current html page. In particular it cannot see the equations in other chapters, which makes it impossible to reference equations from other chapters with this approach.

- 2. The hover-over (e.g. Equation 1.2) Quarto provides will be broken
- 3. mathjax does not know the chapter it is in, so it cannot easily use the format (1.3) where 1 refers to the chapter and 3 means it is the third equation of this chapter. The tagformat of mathjax can however be changed and this template implements a heuristic to find the correct chapter number (assumes there is only one top level heading per .qmd file).

i Workaround 2: Case-by-case treatment

Typically, you do not need to reference individual lines in an equation. The following workaround works well if you only need this in a handful of places and only reference these individual equations within the same chapter. It works by duplicating the equation and providing a version for the html target separately for a version for the pdf (i.e. LaTeX target). It looks like this:

$$a = b \tag{1.3}$$

$$=c (1.4)$$

This is achieved using the following code that introduces a case-by-case treatment of the output

```
::: {.content-visible when-format="html"}
$$
    \begin{align}
        a \&= b \setminus tag\{a\} \setminus 
        &=c \tag{b}
    \end{align}
$$ {#eq-test}
:::
::: {.content-visible when-format="pdf"}
    \begin{align}
        a &= b \left(eq-a\right)
        &=c \label{eq-b}
    \end{align}
:::
`<` Text before you want to reference the equation. `>`
Equation reference:
[@eq-test (a)]{.content-visible when-format="html"}
[Equation \ref{eq-a}]{.content-visible when-format="pdf"}
```

Note that \begin{align} is invalid syntax inside the math environment for LaTeX but it is accepted by mathjax. This allows double tags for the html target. In LaTeX you cannot have these duplicate tags, but you can use the fact that Quarto converts equation references into the LaTeX reference system and LaTeX will then take all labels into consideration and the numbering simply works. Check both outputs!

1.3.3 Aligned-Overset

A LaTeX package I love is aligned-overset. To understand what it does let me first explain the command \overset with the following demo

$$x \stackrel{\text{due to b}}{=} y$$
.

This demo is produced by the code

```
$$
    x \overset{\text{due to b}}{=} y.
$$
```

The command \overset{over}{under} essentially places the first input over the second input. It is therefore a wonderful tool for explaining equation steps. In an aligned environment however this typically breaks alignment because the entire 'stack' is left-aligned if the alignment symbol & is placed before. And the explanation is usually longer than the =, like here

$$x_0 = x_1$$

$$\stackrel{\text{due to b}}{=} x_2$$

$$= x_3.$$

aligned-overset allows the placement of the alignment symbol & between the {over} and {under} of \overset, i.e.

```
\overset{over}&{under}
```

and aligns the stack only on the under part. With this feature it is possible to align the equations above like so

$$x_0 = x_1$$

$$\stackrel{\text{due to b}}{=} x_2$$

$$= x_3$$

By default mathjax does not implement the aligned-overset package and therefore does not allow this placement of the alignment symbol &. However, a mathjax maintainer (Davide P. Cervone) showed me how to configure mathjax to allow this placement (see this GitHub issue). This is why the equation above works. However his solution only correctly adjusts the white-space to the right and may result in overlaps on the left, e.g.

$$x^2 \stackrel{\text{due to b}}{=} y$$

$$= z$$

Nevertheless for all equations, except for the first, this is a good solution and works out of the box with this template.

1.3.4 Theorem environments

Theorem 1.1 (Demo Theorem). Quarto provides certain theorem environments out of the box (see documentation)

proof name. Usage

```
::: {#thm-demo name="Demo Theorem"}
content
:::
::: {.proof name="proof name"}
content
```

:::

Theorem 1.2 (Links work). See Theorem 1.1

Lemma 1.1. Different types of theorems however do not use the same numbering. There is no such thing as theorem groups as in LaTeX amsmath.

1.4 Publishing the book as a website

Quarto documents many ways to publish a Quarto book as a website, the way I recommend uses Github pages and the command quarto publish. This is a direct link to this part of the documentation.

Chapter 2

Useful extensions

You may find the following quarto extensions useful

- 1. Callouty Theorems wraps Theorems and Proofs into a callout block of your choosing (in particular proofs can be made collapsible)
- 2. Latex Environment wraps quarto divs into a LaTeX environment of your choosing.
- 3. Quarto TikZ A filter that renders PGF/TikZ diagrams in HTML as SVG.
- 4. **honeypot** Add hidden instructions to HTML homework assignments to help detect cheating by unauthorized LLM usage.

Chapter 3

Details

3.1 Global LaTeX Macros

References

[1] Donald E. Knuth. "Literate Programming". In: $Comput.\ J.\ 27.2$ (May 1984), pp. 97–111. ISSN: $0010\text{-}4620.\ DOI:\ 10.1093/\text{comjnl}/27.2.97.\ URL:\ https://doi.org/10.1093/comjnl/27.2.97.$