Time Is the Baseline to Beat: Lead Time over a Timer as the Test for VLA Failure Monitors

Author Names Omitted for Anonymous Review. Paper-ID [add your ID here]

***Abstract*—Runtime failure monitors for vision-language-action (VLA) policies are often evaluated under success-terminated, time-limited protocols, where a failed episode is one that reaches its time limit. There, elapsed time is a strong failure signal: on RoboCasa365, a timer calibrated at a 5% false-positive rate (FPR) flags every failure, and a model that sees only elapsed time separates failures as well as one that reads the policy. Without a duration-only comparator, even timeliness metrics cannot show what a monitor adds. We measure how much earlier than a per-task timer a monitor alarms at the same target FPR, and fuse the two by an OR rule whose split-conformal calibration bounds the FPR for a path fixed independently of the calibration successes. On 760 test rollouts of one VLA on 38 tasks, at matched false alarms, three-seed ensembles of the SAFE failure score and of the sequence detector Hide-and-Seek warn earlier than the timer by 0.015 and 0.056 of the time limit, neither clearly above zero (0.030 and 0.071 at the same target). Input ablations that see only elapsed time or another rollout's features add none at matched false alarms. On unseen tasks, where no per-task timer exists, Hide-and-Seek still adds 0.051 over a global timer at matched false alarms (0.127 at the same target), SAFE about as much as random noise. The ordering holds on recorded rollouts of a second VLA, and on FIPER's benchmark FIPER does warn earlier than a timer. Stage 2 tests the second VLA on new rollouts and whether earlier alarms raise success through retry.**

I. Introduction

Vision-language-action (VLA) policies [13, 5] fail often enough that a deployed robot must notice when an attempt is going wrong. Runtime monitors map the policy's hidden state to a failure score [8], or score how unusual its embeddings or actions are relative to successful rollouts [30, 24]. They are compared with each other on ROC-AUC, balanced accuracy and, increasingly, timeliness [24, 22], but rarely with what the robot knows for free: how long the attempt has been running.

Under success-terminated, time-limited protocols such as those of RoboCasa365 [20] and LIBERO [15], an episode ends at the first success or at a fixed time limit, so a failure is, by construction, an episode that ran out of time. In RoboCasa365 every one of our failed rollouts ran to its limit, and on our validation set a timer at 90% of the limit flags all of them at 4.7% FPR. Elapsed time also explains separation: Hide-and-Seek's LSTM trained on zero inputs, which sees only elapsed time, matches the ROC-AUC of the same LSTM trained on the policy's features (0.888 against 0.878). On such benchmarks, a monitor can add only one thing over a timer: an earlier alarm at the same false-alarm rate (Fig. 1), whose value Stage 2 tests by acting on it.




Fig. 1. In success-terminated, time-limited benchmarks every failed rollout runs to its time limit H_k, so a per-task timer that alarms once an attempt outlasts the task's successes flags all failures. A monitor helps only if it alarms *earlier*. We fuse any monitor with the timer (first alarm wins), calibrate both at a 5% false-alarm target, and measure the extra warning over the timer (the fused timer can be looser than P's). Example: a failed XR-1 *OpenCabinet* rollout, monitor score from SAFE.

We therefore evaluate monitors by their *warning lead* over a per-task timer that alarms once an attempt has run longer than the task's successful attempts usually take. We hypothesize that the policy's internal state carries warning that elapsed time does not: fused with this timer, a learned failure score should raise the mean lead at the same FPR, and the gain should vanish when the score cannot see the rollout. Our contributions are:

- **A duration-only comparator for timeliness metrics:** warning lead over a timer at matched FPR, on known and unseen tasks, with input ablations that separate rollout-specific evidence from learned elapsed time (Sec. III, IV).
- **Time-aware fusion:** an OR rule that fuses any monitor with a timer, whose split-conformal calibration bounds the FPR in finite samples for a path fixed independently of the calibration successes (Proposition 1).
- **An evaluation on 38 RoboCasa365 tasks.** As three-seed ensembles at matched false alarms, SAFE adds 0.015 of the time limit over the per-task timer and Hide-and-Seek [22] 0.056, neither clearly above zero; input ablations suggest that Hide-and-Seek's warning develops during the rollout (Sec. VI). On XR-1's unseen tasks, Hide-and-Seek keeps the largest gain; the ordering holds on a second VLA, and on FIPER's benchmark FIPER does warn earlier than a timer.

Most failures we annotated had reached no irreversible state

by the limit, which is why lead, not recall, is the quantity to report.

II. Related Work

Failure detection from policy internals. SAFE learns a failure score from a VLA's last-layer features and thresholds it with a functional conformal band [8]; we reuse its implementation. Follow-ups change the training data [23], labels [22, 18], or policy [26]. FIPER notes that accumulated scores flag failures mostly because failed rollouts are longer [24], and ActProbe feeds the normalized timestep to its model [11], but none reports an elapsed-time detector. SAFE identifies the duration shortcut and removes it by evaluating rollouts at equal length (its App. B.5) and, on its real robots, by running every rollout to a fixed horizon [8]. These controls suit fixed-horizon evaluation; under success-terminated execution, duration is a shortcut [7] for offline metrics but legitimate online evidence, much as time limits make the remaining time part of the agent's state in reinforcement learning [21].

Action-space and success-only detectors. STAC [1] and VLA-FAIL [25] compare overlapping action chunks, and ActProbe [11] feeds chunk consistency, magnitude and the normalized timestep to a task-conditioned LSTM, beating internal-feature baselines on RoboCasa. FAIL-Detect [30] and FIPER [24] score inputs, outputs or embeddings against successful rollouts only. FIPER alarms when two conformal scores *both* exceed their thresholds, which suppresses false alarms; we alarm when *either* crosses, as the two signals catch failures at different times. CheckVLA [17], the closest work on our benchmark, verifies each action chunk with a world model on RoboCasa365. Neither FIPER nor CheckVLA compares against elapsed time.

Time, calibration and intervention. FIPER argues that late detection is not enough [24] and Hide-and-Seek weights accuracy by time [22]. Our lead is one minus FIPER's detection time and, when failures run to the limit, determines Hide-and-Seek's TWA at equal FPR (Sec. VI-A): the metric is not new, the duration-only comparator is. Lead at a fixed false-alarm budget is the accuracy–earliness trade-off of early time-series classification [29]. Split-conformal thresholds give finite-sample false-positive control under exchangeability [3]; our two-signal OR rule (Sec. IV-D) is an instance of nested conformal prediction [9], and Learn-then-Test [4] could choose its path from data with a guarantee. RESCUE [2] finds that, with strong policies, good detection scores do not guarantee lower intervention cost, and CheckVLA couples detection to repair; an earlier alarm matters only if acting on it raises success.

III. Problem Setup

Time. The simulator runs *control steps* at RoboCasa's default 20 Hz. The policy executes each 16-step action chunk in full, so *policy inferences* $t = 1, 2, \ldots$ (0.8 s each) are our clock, and a monitor decides only at an inference. Task k's limit of N_k control steps is $H_k = \lceil N_k/16 \rceil$ inferences (29 to 272, or 22.5 to 217.5 s). Every fraction of time (t/H_k, c, ℓ) is a fraction of H_k.

Monitoring. A monitor watches a rollout of a known task k and decides at each inference t whether to alarm, using only the policy features so far, t, the task and H_k. The first alarm is at T (in inferences). FPR is the fraction of successful rollouts with any alarm. A rollout of length L ends at success or at H_k. For a failure ($L = H_k$) the *warning lead* is $\ell = (L - T)/H_k$, one minus the normalized detection time of [24], with $\ell = 0$ for a missed failure; an alarm at the final inference counts with $\ell = 0$. The mean lead $\bar{\ell}$ over failures combines recall and earliness. Detectors are compared at thresholds set on a calibration set for FPR $\leq \alpha = 0.05$ (the *same target*), and, since the realized test FPRs differ, also at *matched* false alarms: the comparator timer is set to the fused detector's number of test false alarms.

IV. Method

A. Monitor scores

Policy score. At each inference we take the final-layer action-token hidden state of the policy's action head (1,024 dimensions). The SAFE MLP [8] (or, as a variant, SAFE's LSTM head) maps the features so far to a failure score $u_t^{(j)}$ for each of three training seeds j; as in SAFE, the MLP's score sums its per-inference outputs. With per-task location $m_k^{(j)}$ and scale $\sigma_k^{(j)}$ estimated on training rollouts, the policy score is

$$s_t = \frac{1}{3}\sum_{j=1}^{3} \frac{\max_{t' \leq t} u_{t'}^{(j)} - m_k^{(j)}}{\sigma_k^{(j)}}. \tag{1}$$

The running maximum makes s_t monotone, so it does not change once a threshold is crossed. On unseen tasks, $m^{(j)}$ and $\sigma^{(j)}$ are pooled over training tasks. Success-only alternatives (Mahalanobis [14], kNN [27], PCA-KMeans [16] and RND [6, 10]) are fitted on training successes and aggregated the same way.

Sequence score and input ablations. Hide-and-Seek [22] trains an LSTM with rollout labels only (in our implementation, on a 128-dimensional PCA of the same hidden state): a margin loss pushes each failure's peak score above every success's, and an onset loss acts within failures. A recurrent model can learn how long each task takes, so we retrain it unchanged on ablated inputs: *zero input*, so it sees only elapsed time; *shuffle*, a random same-task rollout's features at the same inference, so it also sees the task's typical trajectory; and *first step*, the rollout's own first-inference features, repeated, so it also sees the initial scene. Unlike the original methods, which threshold with time-varying conformal bands [8, 22], we threshold every score at a constant level on its running maximum (Sec. IV-D).

B. Time baselines

The *global timer* G alarms once $t \geq c\,H_k$, with one fraction $c \in (0, 1]$ for all tasks. The *per-task timer* P uses $c_k = \min(1, \rho_k + \delta)$, where ρ_k is the 95th percentile of task k's training success durations (as fractions of H_k) and the




Fig. 2. Time-aware fusion: the earlier of a monitor alarm and a timer alarm wins. Split-conformal calibration on successes sets both thresholds along one path; for a path fixed independently of them, a new success alarms with probability at most α (Proposition 1).

shared margin δ is set by Proposition 1. P needs successful rollouts of each task, but no failures and no policy features.

C. OR-fusion

The fused monitor (Fig. 2) alarms at

$$T = \min\{\, t : s_t > \tau_s \text{ or } t \geq c_k H_k \,\}, \tag{2}$$

with $c_k = c$ for G. Neither signal is restricted in time: the score may alarm early, and, once calibration certifies a usable point (Sec. IV-D), the timer alarms on every failure by $c_k H_k$. Any lead gain over the timer comes from failures on which the score crosses first.

D. Calibration with a finite-sample FPR guarantee

A successful rollout i of task k_i and length L_i (in inferences) raises a false alarm under $(\tau_s, c_1, \ldots, c_K)$ if and only if $M_i = \max_{t \leq L_i} s_t > \tau_s$ or $d_i = L_i / H_{k_i} \geq c_{k_i}$. Fix in advance a finite grid Λ and a path $\gamma(\lambda) = (\tau_s(\lambda), c_1(\lambda), \ldots, c_K(\lambda))$, $\lambda \in \Lambda$, with every coordinate nondecreasing and $c_k \leq 1$, so that a larger λ is more conservative and the alarm sets are nested. For each calibration success define

$$V_i = \min\{\lambda \in \Lambda : M_i \leq \tau_s(\lambda) \text{ and } d_i < c_{k_i}(\lambda)\}, \tag{3}$$

the least conservative point on the path at which rollout i stays silent, and $V_i = \infty$ if none is (e.g. a success lasting the whole limit). Because the alarm sets are nested, rollout i is silent at $\lambda \in \Lambda$ exactly when $\lambda \geq V_i$.

Proposition 1: Let n calibration successes and a new successful rollout be exchangeable, and let the path γ not depend on the calibration successes. Set $\hat{\lambda} = V_{(r)}$, the r-th smallest V_i with $r = \lceil (n+1)(1-\alpha) \rceil$, or $\hat{\lambda} = \infty$ if $r > n$. If $\hat{\lambda} = \infty$, the calibration rule cannot certify a usable point at the target and the monitor is disabled: it raises no alarm. Otherwise it runs at $\gamma(\hat{\lambda})$. Then, over calibration draws, $\Pr(\text{monitor enabled and false alarm on the new success}) \leq \alpha$.

Proof: An enabled monitor alarms on the new success if and only if $V_{n+1} > \hat{\lambda}$, and a disabled one ($\hat{\lambda} = \infty$) never does, so the event is $\{V_{n+1} > V_{(r)}\}$ with $V_{(r)} = \infty$ for $r > n$. By exchangeability, the rank of V_{n+1} among $V_1, \ldots, V_{n+1}$ is uniform, so $\Pr(V_{n+1} > V_{(r)}) \leq 1 - r/(n+1) \leq \alpha$: the split-conformal quantile lemma [3]. ∎

The path may use any data except calibration successes, such as development rollouts or calibration *failures*. The guarantee is per trajectory and marginal over tasks and calibration draws, not a cap on a finite test set or on each task (on the test set, one task had 4 of 10 successes alarmed); a per-task version needs 19 calibration successes per task.

Adaptive and fixed paths. Our Stage 1 results use *adaptive-path calibration*: every detector fused with P uses the path $\delta = \lambda$, $\tau_s = a + b\lambda$, with (a, b) the grid point of largest mean lead on calibration failures, each point placed at its own $\hat{\lambda}$. This choice also uses the calibration successes, so Proposition 1 bounds each candidate path, not the chosen one; over 200 re-splits of the successes, the choice raised the expected test FPR from 0.047 (P) to about 0.055. A *fixed path*, chosen independently of the calibration successes, restores the bound: chosen on the validation set, it gives Hide-and-Seek + P 0.072 at 0.061 FPR (0.057 matched, uncertain) and SAFE + P 0.007 (0.039 matched: its 16 false alarms against P's 21 make matching tighten P). Stage 2 uses fixed paths only (Sec. VII).

V. Hypotheses

Early warning (H1). At a 5% calibration target, OR-fusing a policy-internal score with the per-task timer P increases the mean warning lead over P alone, also at matched false alarms.

Policy evidence (H2). At matched FPR, policy scores fused with P lead more than scores without rollout-specific information: random noise, or features or scores resampled from other rollouts of the task.

Second policy (H3). On a second VLA, RLDX-1 [12], SAFE-LSTM + P and Hide-and-Seek + P also lead P, including at matched false alarms.

Value of earlier warning (H4). Within a budget of $1.25\,H_k$, resetting and retrying when Hide-and-Seek + P alarms yields a higher success rate than resetting when P alarms.

Sec. VI tests H1 and H2; Stage 2 addresses H3 and H4 (Sec. VII).

VI. Experiments

A. Setup

Policy and tasks. We use the released Xiaomi-Robotics-1 (XR-1) RoboCasa365 checkpoint [28] on the 38 official RoboCasa365 tasks [19, 20] whose published success lies between 5 and 45 of 50 (10 atomic and 28 composite tasks).

Data. Disjoint sets of rollouts serve one purpose each. A *training set* (1,824 rollouts) fits every learned detector and P's ρ_k. A *validation set* (380 successes and 380 failures, 10 per class per task), with its own, smaller calibration set (3 successes and 3 failures per task), was used to develop the timers and the fused detectors. A *test set* of the same size, with new seeds, and a new calibration set of 10 successes and 10 failures per task served the tests of H1 and H2.

Unseen tasks. Each task is held out once (4 folds): monitors are retrained and thresholds calibrated without it, with OOD references and score normalization pooled over the other tasks. P needs the task's own successes, so the comparator is G.

TABLE I

STANDALONE FAILURE DETECTION WITH XR-1 (TEST SET, 380 + 380 ROLLOUTS) AT THRESHOLDS CALIBRATED FOR 5% FPR, CONSTANT ON EACH SCORE'S RUNNING MAXIMUM. SINGLE MODELS: MEAN ± STD ACROSS 3 TRAINING SEEDS; **BOLD**/UNDERLINE: BEST/SECOND BEST.

		Policy: XR-1 (Success Rate: 55.6%)			
		Seen tasks		Unseen tasks	
	Method	bACC↑	TWA↑	bACC↑	TWA↑
OOD	Mahalanobis	$0.818^{\pm 0.001}$	$0.582^{\pm 0.001}$	$0.726^{\pm 0.000}$	$0.543^{\pm 0.000}$
	Cosine k-NN	$0.788^{\pm 0.000}$	$0.577^{\pm 0.000}$	$0.729^{\pm 0.000}$	$0.544^{\pm 0.000}$
	PCA-KMeans	$0.796^{\pm 0.001}$	$0.578^{\pm 0.001}$	$0.728^{\pm 0.001}$	$0.542^{\pm 0.001}$
	RND	$0.793^{\pm 0.002}$	$0.572^{\pm 0.001}$	$0.728^{\pm 0.001}$	$0.547^{\pm 0.001}$
Class.	SAFE-MLP	$0.763^{\pm 0.003}$	$0.582^{\pm 0.011}$	$0.713^{\pm 0.003}$	$0.541^{\pm 0.001}$
	SAFE-LSTM	$0.610^{\pm 0.012}$	$0.547^{\pm 0.007}$	$0.686^{\pm 0.021}$	$\underline{0.560}^{\pm 0.013}$
	Hide-and-Seek	$0.742^{\pm 0.033}$	$\mathbf{0.599}^{\pm 0.005}$	$\underline{0.790}^{\pm 0.002}$	$\mathbf{0.595}^{\pm 0.005}$
Time	Global timer G*	**0.988**	0.550	**0.988**	0.551
	Per-task timer P*	$\underline{0.972}$	$\underline{0.585}$	–	–

*Deterministic. P needs the task's own successful rollouts.

(Hide-and-Seek's evaluation [22] uses random 7/3 task splits instead.)

Baselines. We compare three families (Table I). *OOD detectors*, fitted on successful rollouts only: Mahalanobis distance [14], cosine k-NN [27], PCA-KMeans [16] and RND [10]. *Failure classifiers*, trained with rollout labels: SAFE-MLP and SAFE-LSTM [8] and Hide-and-Seek [22]. *Elapsed time*, with no policy access: G and P. Token-uncertainty baselines need discrete action tokens and STAC [1] overlapping chunks, which XR-1 does not produce. Act-Probe [11], reduced to its magnitude feature, never alarms on unseen tasks, so we omit it.

Metrics. Following [24, 22], at thresholds calibrated for FPR ≤ 0.05 we report test FPR, balanced accuracy (bACC; equal to weighted accuracy on our balanced sets), time-weighted accuracy $\mathrm{TWA} = \frac{1}{2}(\bar{\ell} + 1 - \mathrm{FPR})$ and detection time $\mathrm{DT} = 1 - \bar{\ell}$, a miss counting as 1 (FIPER averages DT over detected failures only). As in [22], each learned detector is trained with 3 random seeds, and tables give the mean ± std of single models across these training seeds. For H1 and H2 we use *three-seed ensembles*, which average the 3 models' scores (Table III); the input ablations are ensembled the same way. Matching sets P's margin on the test set itself, which favors the timer. For the two central matched gains, 95% bootstrap CIs resample the test set's tasks, then failures within each task (2,000 resamples, paired across methods). They are conditional on the fitted thresholds and the matched timer, so they exclude calibration and matching uncertainty.

B. Results on XR-1

Standalone detection. On their own (Table I), learned detectors catch at most 69% of seen-task failures at 5% FPR; the two timers, which never read the policy, catch all of them (bACC 0.97 and 0.99, against at most 0.82), and P (DT 0.775) alarms earlier than every learned detector except Hide-and-Seek (0.754). On unseen tasks, Hide-and-Seek and SAFE-LSTM exceed the global timer's TWA.

SAFE and Hide-and-Seek (H1, H2). Fused with P, the SAFE and Hide-and-Seek ensembles warn 0.015 (95% CI $[-0.007, 0.041]$) and 0.056 ($[-0.014, 0.120]$) of the time limit earlier than P at matched false alarms, and 0.030 and 0.071 at the same target, where random and within-task resampled scores gain at most 0.009 and 0.012 (Table III, Fig. 3b). Hide-and-Seek's advantage over SAFE (0.041) is uncertain. A single Hide-and-Seek model gains only 0.039 ± 0.006 (Table II): averaging seeds leaves its ROC-AUC near 0.89 but lets it alarm before the timer on more failures (21% to 57%; matched gains 0.036, 0.065, 0.056 for one to three models). SAFE-MLP's per-inference outputs exceed 0.9 on 85% of success and 92% of failure steps, so its summed score mostly counts inferences;

TABLE II

WARNING LEAD ON THE TEST SETS. MONITORS ARE OR-FUSED AT A 5% FPR TARGET WITH P ON SEEN TASKS AND G ON UNSEEN TASKS, USING ADAPTIVE-PATH CALIBRATION (SEC. IV-D; NOT COVERED BY PROPOSITION 1). $\Delta\bar{\ell}$: GAIN IN MEAN LEAD OVER THAT TIMER. SINGLE MODELS: MEAN ± STD ACROSS 3 TRAINING SEEDS.

		Policy: XR-1 (Success Rate: 55.6%; 380 + 380 test rollouts)					
		Seen tasks + P			Unseen tasks + G		
	Method	FPR↓	$\Delta\bar{\ell}$ ↑	TWA↑	FPR↓	$\Delta\bar{\ell}$ ↑	TWA↑
Time	Timer G	0.024	−0.102	0.550	0.024	–	0.551
	Timer P	0.055	–	0.585	–	–	–
OOD	Mahalanobis	0.055	$\underline{0.034}^{\pm 0.000}$	$\underline{0.602}^{\pm 0.000}$	0.073	$0.044^{\pm 0.001}$	$0.549^{\pm 0.001}$
	Cosine k-NN	0.058	$0.021^{\pm 0.000}$	$0.594^{\pm 0.000}$	0.079	$0.053^{\pm 0.000}$	$0.550^{\pm 0.000}$
	PCA-KMeans	0.060	$0.022^{\pm 0.001}$	$0.594^{\pm 0.000}$	0.071	$0.053^{\pm 0.001}$	$0.554^{\pm 0.000}$
	RND	0.060	$0.021^{\pm 0.001}$	$0.593^{\pm 0.000}$	0.073	$0.050^{\pm 0.001}$	$0.551^{\pm 0.000}$
Cl.	SAFE-MLP	0.058	$0.024^{\pm 0.015}$	$0.596^{\pm 0.006}$	0.053	$0.028^{\pm 0.009}$	$0.551^{\pm 0.005}$
	SAFE-LSTM	0.059	$0.031^{\pm 0.013}$	$0.599^{\pm 0.005}$	0.040	$\underline{0.058}^{\pm 0.020}$	$\underline{0.572}^{\pm 0.009}$
	Hide&Seek	0.055	$\mathbf{0.039}^{\pm 0.006}$	$\mathbf{0.605}^{\pm 0.005}$	0.059	$\mathbf{0.122}^{\pm 0.005}$	$\mathbf{0.595}^{\pm 0.004}$
Abl.	First step	0.055	$0.001^{\pm 0.001}$	$0.586^{\pm 0.001}$	0.027	$0.002^{\pm 0.003}$	$0.550^{\pm 0.001}$
	Zero input	0.062	$0.013^{\pm 0.003}$	$0.588^{\pm 0.000}$	0.037	$0.020^{\pm 0.008}$	$0.554^{\pm 0.005}$
	Shuffle	0.058	$0.005^{\pm 0.001}$	$0.586^{\pm 0.002}$	–	–	–
		Policy: RLDX-1 (Success Rate: 56.2%; 100 + 100 recorded test rollouts)					
		Seen tasks + P			Unseen tasks + G		
	Method	FPR↓	$\Delta\bar{\ell}$ ↑	TWA↑	FPR↓	$\Delta\bar{\ell}$ ↑	TWA↑
Time	Timer G	0.010	−0.239	0.511	0.000	–	0.513
	Timer P	0.030	–	0.621	–	–	–
OOD	Mahalanobis	0.040	$0.030^{\pm 0.000}$	$0.631^{\pm 0.000}$	0.030	$0.112^{\pm 0.000}$	$0.554^{\pm 0.000}$
	Cosine k-NN	0.050	$0.005^{\pm 0.000}$	$0.613^{\pm 0.000}$	0.010	$0.112^{\pm 0.000}$	$\underline{0.564}^{\pm 0.000}$
	PCA-KMeans	0.047	$0.029^{\pm 0.004}$	$0.627^{\pm 0.001}$	0.040	$\underline{0.115}^{\pm 0.004}$	$0.550^{\pm 0.002}$
	RND	0.040	$0.015^{\pm 0.007}$	$0.623^{\pm 0.010}$	0.037	$0.099^{\pm 0.013}$	$0.544^{\pm 0.011}$
Class.	SAFE-MLP	0.053	$0.008^{\pm 0.012}$	$0.613^{\pm 0.007}$	0.070	$0.044^{\pm 0.000}$	$0.500^{\pm 0.000}$
	SAFE-LSTM	0.033	$\underline{0.036}^{\pm 0.003}$	$\underline{0.637}^{\pm 0.003}$	0.067	$0.101^{\pm 0.006}$	$0.530^{\pm 0.000}$
	Hide&Seek	0.050	$\mathbf{0.074}^{\pm 0.030}$	$\mathbf{0.648}^{\pm 0.004}$	0.057	$\mathbf{0.196}^{\pm 0.013}$	$\mathbf{0.583}^{\pm 0.021}$
Abl.	First step	0.050	$-0.004^{\pm 0.014}$	$0.609^{\pm 0.005}$	0.090	$0.038^{\pm 0.025}$	$0.487^{\pm 0.012}$
	Zero input	0.037	$0.012^{\pm 0.010}$	$0.623^{\pm 0.002}$	0.023	$0.010^{\pm 0.024}$	$0.506^{\pm 0.008}$
	Shuffle	0.030	$0.007^{\pm 0.005}$	$0.624^{\pm 0.002}$	–	–	–

Mean lead of the timers: XR-1 P 0.225, G 0.123 (seen) and 0.126 (unseen); RLDX-1 P 0.271, G 0.032 and 0.026. Unseen FPRs can exceed 0.05, as thresholds are set on the seen tasks.

TABLE III

H1 AND H2: THREE-SEED ENSEMBLES + P, XR-1 TEST SET. FA: FALSE ALARMS; P ALONE: 21 FA, LEAD 0.225.

Monitor + P	FA (of 380)	$\Delta\bar{\ell}$, same target	$\Delta\bar{\ell}$, matched FA
SAFE-MLP	23	0.030	0.015
Hide-and-Seek	23	**0.071**	**0.056**
Mahalanobis (one model)	21	0.034	0.030
Hide-and-Seek, first step	21	0.001	−0.003
Hide-and-Seek, zero input	23	0.012	−0.003
Hide-and-Seek, shuffle	24	0.011	−0.011




Fig. 3. Gain over the per-task timer P (XR-1, test set). (a) Atomic tasks gain about four times as much as composite ones (Hide-and-Seek: 0.160 vs. 0.039). (b) At matched false alarms, Hide-and-Seek's point estimates are positive from 2% to 10%; its ablations never exceed 0.01.

their running mean, free of elapsed time, adds nothing over P.

Where the gain comes from. SAFE-MLP, Hide-and-Seek and the four OOD scores all gain more on the 10 atomic tasks (0.045 to 0.160) than on the 28 composite ones (0.008 to 0.039; Fig. 3a). Hide-and-Seek + P alarms later than P on 16 tasks, where its looser timer margin spends the false-alarm budget on the score, and five tasks carry 78% of its gain. In seconds, Hide-and-Seek + P warns 2.6 s earlier than P on average (matched: 5.0 s on atomic, 0 s on composite tasks).

Stronger comparators and nulls. A timer whose per-task margins maximize mean lead under a pooled false-alarm budget, chosen as adaptively as the fused path, does not beat P at matched false alarms (-0.008); Hide-and-Seek + P gains 0.063 over it. Both scores beat all 100 noise and within-task resampled fusions at matched false alarms. With the methods' own time-varying bands [8, 22], fused matched gains are 0.068 (Hide-and-Seek) and 0.006 (SAFE). Matched gains stay uncertain when calibration is also resampled. With episodes truncated at 0.8 or 0.9 of the limit, Hide-and-Seek's matched gain stays positive (0.062, 0.110). P is a realistic timer, not the best possible one: per-task cutoffs tuned on the test successes themselves would lead P by 0.16, more than either monitor.

Is the extra warning learned elapsed time? The zero-input ablation separates failures as well as Hide-and-Seek (Sec. I), yet no ablation gains over P at matched false alarms (Table III): the warning appears to develop during the rollout.

C. Transfer and irreversibility

Unseen tasks (Tables I and II). With no rollout of the task, as in SAFE's setting [8], Hide-and-Seek keeps the largest gain over G on XR-1: 0.127 as an ensemble (zero-input ablation: 0.033), 0.11 more than SAFE. SAFE's ensemble (0.017) gains no more than random scores (up to 0.019), and -0.079 matched (Hide-and-Seek: 0.051). Once 1 to 5 successes of the new task exist, a per-task timer can be built, and Hide-and-Seek still adds 0.088 to 0.099 over it (SAFE about 0.01).

Second policy. On recorded RLDX-1 rollouts [12] (Table II, bottom), all failures again ran to the limit. As ensembles, SAFE-LSTM + P gains 0.034 and Hide-and-Seek + P 0.083 (0.052 matched), both on atomic tasks only. On unseen tasks, Hide-and-Seek again gains most over G (lead only 0.026).

FIPER's benchmark. In FIPER's released rollouts [24] (five tasks, two on a real robot), length alone gives ROC-AUC 0.92–1.00 in four tasks. In FIPER's code (results reproduced), the timer has the best balanced accuracy (0.81 against 0.78; FPR 0.09 against 0.35), yet at its own FPR FIPER warns 0.146 earlier: the test credits early warning wherever it occurs.

When do failures become irreversible? An annotator blind to alarms marked the point of no return (the first state from which the task could not be completed without outside help) on 48 test failures: 38 (79%), mostly slow or near-successful, reached none before the limit (a second annotator agreed on 11 of 12). On the other 10, P alarmed before it on none, SAFE + P and Hide-and-Seek + P on two each.

VII. Stage 2: Planned Experiments

Second policy (E1). We test H3 on new RLDX-1 rollouts: fresh calibration and test sets of 20 successes and 20 failures for each of its 20 tasks (about 2,500 rollouts). The detectors (SAFE-LSTM, as SAFE's MLP head adds no lead on the recorded rollouts, and Hide-and-Seek), H_k, ρ_k and each fused path are fixed on the existing rollouts, so only $\hat{\lambda}$ is set on new successes and Proposition 1 applies. A gain over P counts as early warning if its 97.5% CI (Bonferroni over two detectors) is above zero at the same target and at matched false alarms, it beats 38 of 39 random and resampled fusions, and test false alarms stay within an exact binomial bound (at most 39 of 400); simulated power is at least 0.94.

Reset and retry (E2). We evaluate H4 in closed loop on 1,000 RLDX-1 scenes (50 per task) with a shared budget of $1.25\,H_k$. Each scene runs once without reset to $1.25\,H_k$ (the no-reset outcome); each monitor's arm branches from this run at its first alarm, restores the initial simulator state and retries with a seed that differs from the first attempt's but is shared by all monitors, with latency charged to the budget. We report the paired success-rate difference between Hide-and-Seek + P and P resets with a 95% CI, plus reset against no reset, unnecessary resets, and a time-only reset with per-task cutoffs that maximize success on the recorded rollouts (in simulation, within 0.01 of P). Simulations put it at about $+0.01$ (half-width 0.02), so E2 estimates H4 rather than tests it; in a pilot, only 4% of failures succeeded if left running.

Further analyses (E3). Action-only and multi-sample monitors, and lead from the point of no return.

VIII. Conclusion and Limitations

At matched false alarms, policy monitors add an uncertain 0.015 to 0.056 of the time limit over a per-task timer, so early warning (H1) is not yet established; Stage 2 tests it further. **Limitations.** Alarms were recorded in simulation (free resets), not acted on, and lead runs to the time limit, not to irreversibility. Hide-and-Seek reused SAFE's test set, but its comparison with P, ablations and nulls had written rules before it was scored there (matched: descriptive only); other analyses came after scoring. Monitors assume a known task, a time limit and a success check.

References

[1] Christopher Agia et al. Unpacking failure modes of generative policies: Runtime monitoring of consistency and progress. In *Conference on Robot Learning (CoRL)*, volume 270 of *PMLR*, 2024.

[2] David Ahmedt-Aristizabal et al. RESCUE: Is this alarm worth acting on? Counterfactual evaluation of VLA runtime monitors, 2026. arXiv:2610.13516.

[3] Anastasios N. Angelopoulos and Stephen Bates. A gentle introduction to conformal prediction and distribution-free uncertainty quantification, 2021. arXiv:2107.07511.

[4] Anastasios N. Angelopoulos et al. Learn then test: Calibrating predictive algorithms to achieve risk control. *Annals of Applied Statistics*, 2025. arXiv:2110.01052.

[5] Kevin Black et al. π_0: A vision-language-action flow model for general robot control. In *Robotics: Science and Systems (RSS)*, 2025.

[6] Yuri Burda et al. Exploration by random network distillation. In *International Conference on Learning Representations (ICLR)*, 2019.

[7] Robert Geirhos et al. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020.

[8] Qiao Gu et al. SAFE: Multitask failure detection for vision-language-action models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025.

[9] Chirag Gupta, Arun K. Kuchibhotla, and Aaditya Ramdas. Nested conformal prediction and quantile out-of-bag ensemble methods. *Pattern Recognition*, 127:108496, 2022.

[10] Nantian He et al. ReDiffuser: Reliable decision-making using a diffuser with confidence estimation. In *International Conference on Machine Learning (ICML)*, volume 235 of *PMLR*, pages 17921–17933, 2024.

[11] Bingjia Huang et al. ActProbe: Action-space probe for early failure detection of generative robot policies, 2026. arXiv:2606.08508.

[12] Dongyoung Kim et al. RLDX-1 technical report, 2026. arXiv:2605.03269.

[13] Moo Jin Kim et al. OpenVLA: An open-source vision-language-action model. In *Conference on Robot Learning (CoRL)*, 2024.

[14] Kimin Lee et al. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

[15] Bo Liu et al. LIBERO: Benchmarking knowledge transfer for lifelong robot learning. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2023.

[16] Huihan Liu et al. Multi-task interactive robot fleet learning with visual world models. In *Conference on Robot Learning (CoRL)*, volume 270 of *PMLR*, 2024.

[17] Yushan Liu et al. CheckVLA: Execution-time verification with action-conditioned world model for long-horizon mobile manipulation, 2026. arXiv:2607.26789.

[18] Jie Ma, Zongxi Liu, and Yi Zhu. FailureSpot: Label-efficient timestamp-level failure detection for vision-language-action models, 2026. arXiv:2609.04277.

[19] Soroush Nasiriany et al. RoboCasa: Large-scale simulation of everyday tasks for generalist robots. In *Robotics: Science and Systems (RSS)*, 2024.

[20] Soroush Nasiriany et al. RoboCasa365: A large-scale simulation framework for training and benchmarking generalist robots. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2603.04356.

[21] Fabio Pardo, Arash Tavakoli, Vitaly Levdik, and Petar Kormushev. Time limits in reinforcement learning. In *International Conference on Machine Learning (ICML)*, volume 80 of *PMLR*, pages 4045–4054, 2018.

[22] Seongheon Park et al. Hide-and-seek in trajectories: Discovering failure signals for VLA runtime monitoring. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2026. arXiv:2605.30834.

[23] Harshitha Rajaprakash et al. SAFECAST: Robust failure detection for VLA policies with contrast-set training and calibration, 2026. arXiv:2608.04246.

[24] Ralf Römer et al. Failure prediction at runtime for generative robot policies. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025.

[25] Florian Seligmann et al. VLA-FAIL: Efficient task failure detection for finetuned vision-language-action models. In *Conference on Robot Learning (CoRL)*, 2026.

[26] Michael Soddy et al. Predictable before action, resistant to correction: Failure signals in vision-language-action models. In *NeurIPS Workshop on From Pretrained Representations to Acting Agents (PTA)*, 2026.

[27] Yiyou Sun et al. Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning (ICML)*, 2022.

[28] Xiaomi Robotics Team. Xiaomi-Robotics-1: Scaling vision-language-action models with over 100K hours of real-world trajectories, 2026. arXiv:2607.15330.

[29] Zhengzheng Xing, Jian Pei, and Philip S. Yu. Early classification on time series. *Knowledge and Information Systems*, 31(1):105–127, 2012. doi: 10.1007/s10115-011-0400-x.

[30] Chen Xu et al. Can we detect failures without failure data? Uncertainty-aware runtime failure detection for imitation learning policies. In *Robotics: Science and Systems (RSS)*, 2025.