

Doki UML_10112025

10.11.2025

```
classDiagram
    class DialogManager {
        +DialogContext context
        +BaseStoryNode currentNode
        +void Start()
        +void PlayCurrent()
        +void AdvanceTo(BaseStoryNode next)
        +void CompleteNode()
        +void SwitchGame() // teleport / hide UI
    }

    class DialogContext {
        +TMP_Text speakerText
        +TMP_Text dialogText
        +Image charImage
        +Image backgroundImage
        +Image charFrame
        +WritingAnimation writing
        +void SetSpeaker(string)
        +void SetLine(string)
        +void SetSprites(Sprite c, Sprite b)
        +void setFrameColor(Color)
    }

    class BaseStoryNode {
        <<ScriptableObject>>
        +string nodeName
        +TeleportLocationAsset teleportLocation
        +bool canTeleport
        +virtual void Play(DialogContext ctx, DialogManager runner)
    }
```

```

class DialogueNode {
    <<ScriptableObject>>
    +string whostalking
    +string[] dialogText
    +Sprite character_img
    +Sprite background_img
    +CharacterColor emotionColor
    +ReactionAnimation reactionAnimation    // small sprite animation
    +override void Play(ctx, runner)
}

class ChoiceNode {
    <<ScriptableObject>>
    +string prompt
    +string[] options
    +override void Play(ctx, runner)
}

class AnimationNode {
    <<ScriptableObject>>
    +Sprite animationSprite
    +float duration
    +override void Play(ctx, runner)
}

class CharacterColor {
    <<ScriptableObject>>
    +Color uiColor
}

class ReactionAnimation {
    <<ScriptableObject>>
    +string triggerName
    +float duration
}

```

```
BaseStoryNode <|-- DialogueNode
BaseStoryNode <|-- ChoiceNode
BaseStoryNode <|-- AnimationNode

DialogManager --> BaseStoryNode : runs
BaseStoryNode --> DialogManager : calls Fns on runner
DialogueNode --> CharacterColor : uses
DialogueNode --> ReactionAnimation : uses
DialogManager --> DialogContext : owns
```

Flow

📄 Doki_UML 10112025