

# Introduction to Formal Methods

## Chapter 09: SAT-Based Bounded Model Checking

Roberto Sebastiani

DISI, Università di Trento, Italy – [roberto.sebastiani@unitn.it](mailto:roberto.sebastiani@unitn.it)

URL: <http://disi.unitn.it/rseba/DIDATTICA/fm2018/>

Teaching assistant: **Patrick Trentin** – [patrick.trentin@unitn.it](mailto:patrick.trentin@unitn.it)

CDLM in Informatica, academic year 2017-2018

last update: Tuesday 20<sup>th</sup> February, 2018, 08:54

Copyright notice: *some material (text, figures) displayed in these slides is courtesy of M. Benerecetti, A. Cimatti, P. Pandya, M. Pistore, M. Roveri, and S. Tonetta, who detain its copyright. Some examples displayed in these slides are taken from [Clarke, Grunberg & Peled, "Model Checking", MIT Press], and their copyright is detained by the authors. All the other material is copyrighted by Roberto Sebastiani. Every commercial use of this material is strictly forbidden by the copyright laws without the authorization of the authors. No copy of these slides can be displayed in public without containing this copyright notice.*

# Outline

- 1 Motivations
- 2 Background on SAT Solving
- 3 Bounded Model Checking: an example
- 4 Bounded Model Checking
- 5 Computing upper bounds for  $k$
- 6 Inductive reasoning on invariants (aka “K-Induction”)
- 7 Exercises

# Outline

- 1 Motivations
- 2 Background on SAT Solving
- 3 Bounded Model Checking: an example
- 4 Bounded Model Checking
- 5 Computing upper bounds for  $k$
- 6 Inductive reasoning on invariants (aka “K-Induction”)
- 7 Exercises

# SAT-based Bounded Model Checking

- Key problems with BDD's:
  - they can explode in space
  - an expert user can make the difference (e.g. reordering, algorithms)
- A possible alternative:
  - Propositional Satisfiability Checking (SAT)
  - SAT technology is very advanced
- Advantages:
  - reduced memory requirements
  - limited sensitivity: one good setting, does not require expert users
  - much higher capacity (more variables) than BDD based techniques

# SAT-based Bounded Model Checking

- Key problems with BDD's:
  - they can explode in space
  - an expert user can make the difference (e.g. reordering, algorithms)
- A possible alternative:
  - Propositional Satisfiability Checking (SAT)
  - SAT technology is very advanced
- Advantages:
  - reduced memory requirements
  - limited sensitivity: one good setting, does not require expert users
  - much higher capacity (more variables) than BDD based techniques

# SAT-based Bounded Model Checking

- Key problems with BDD's:
  - they can explode in space
  - an expert user can make the difference (e.g. reordering, algorithms)
- A possible alternative:
  - Propositional Satisfiability Checking (SAT)
  - SAT technology is very advanced
- Advantages:
  - reduced memory requirements
  - limited sensitivity: one good setting, does not require expert users
  - much higher capacity (more variables) than BDD based techniques

# SAT-based Bounded Model Checking [cont.]

## Key ideas:

- look for counter-example paths of increasing length  $k$   
 $\Rightarrow$  oriented to finding bugs
- for each  $k$ , builds a Boolean formula that is satisfiable iff there is a counter-example of length  $k$ 
  - can be expressed using  $k \cdot |S|$  variables
  - formula construction is not subject to state explosion
- satisfiability of the Boolean formulas is checked using a **SAT procedure**
  - can manage complex formulae on several 100K variables
  - returns satisfying assignment (i.e., a counter-example)

# SAT-based Bounded Model Checking [cont.]

Key ideas:

- look for counter-example paths of increasing length  $k$   
⇒ oriented to finding bugs
- for each  $k$ , builds a Boolean formula that is satisfiable iff there is a counter-example of length  $k$ 
  - can be expressed using  $k \cdot |S|$  variables
  - formula construction is not subject to state explosion
- satisfiability of the Boolean formulas is checked using a SAT procedure
  - can manage complex formulae on several 100K variables
  - returns satisfying assignment (i.e., a counter-example)



# SAT-based Bounded Model Checking [cont.]

Key ideas:

- look for counter-example paths of increasing length  $k$   
⇒ oriented to finding bugs
- for each  $k$ , builds a Boolean formula that is satisfiable iff there is a counter-example of length  $k$ 
  - can be expressed using  $k \cdot |S|$  variables
  - formula construction is not subject to state explosion
- satisfiability of the Boolean formulas is checked using a SAT procedure
  - can manage complex formulae on several 100K variables
  - returns satisfying assignment (i.e., a counter-example)

# SAT-based Bounded Model Checking [cont.]

Key ideas:

- look for counter-example paths of increasing length  $k$   
⇒ oriented to finding bugs
- for each  $k$ , builds a Boolean formula that is satisfiable iff there is a counter-example of length  $k$ 
  - can be expressed using  $k \cdot |S|$  variables
  - formula construction is not subject to state explosion
- satisfiability of the Boolean formulas is checked using a SAT procedure
  - can manage complex formulae on several 100K variables
  - returns satisfying assignment (i.e., a counter-example)

# SAT-based Bounded Model Checking [cont.]

Key ideas:

- look for counter-example paths of increasing length  $k$   
⇒ oriented to finding bugs
- for each  $k$ , builds a Boolean formula that is satisfiable iff there is a counter-example of length  $k$ 
  - can be expressed using  $k \cdot |S|$  variables
  - formula construction is not subject to state explosion
- satisfiability of the Boolean formulas is checked using a **SAT procedure**
  - can manage complex formulae on several 100K variables
  - returns satisfying assignment (i.e., a counter-example)

# Outline

- 1 Motivations
- 2 Background on SAT Solving**
- 3 Bounded Model Checking: an example
- 4 Bounded Model Checking
- 5 Computing upper bounds for  $k$
- 6 Inductive reasoning on invariants (aka “K-Induction”)
- 7 Exercises

# DPLL

- Davis-Putnam-Longeman-Loveland procedure (DPLL)
- Tries to build recursively an assignment  $\mu$  satisfying  $\varphi$ ;
- At each recursive step assigns a truth value to (all instances of) **one atom**.
- Performs **deterministic choices** first.

# DPLL Algorithm

```

function  $DPLL(\varphi, \mu)$ 
  if  $\varphi = \top$                                 /* base      */
    then return True;
  if  $\varphi = \perp$                               /* backtrack */
    then return False;
  if {a unit clause ( $l$ ) occurs in  $\varphi$ }         /* unit      */
    then return  $DPLL(assign(l, \varphi), \mu \wedge l)$ ;
  (...)
   $l := choose\_literal(\varphi);$                   /* split     */
  return  $DPLL(assign(l, \varphi), \mu \wedge l)$  or
          $DPLL(assign(\neg l, \varphi), \mu \wedge \neg l);$ 

```

# “Classic” chronological backtracking

- variable assignments (literals) stored in a stack
- each variable assignments labeled as “unit”, “open”, “closed”
- when a conflict is encountered, the stack is popped up to the most recent open assignment /
- / is toggled, is labeled as “closed”, and the search proceeds.

# Classic chronological backtracking – example

$$c_1 : \neg A_1 \vee A_2$$

$$c_2 : \neg A_1 \vee A_3 \vee A_9$$

$$c_3 : \neg A_2 \vee \neg A_3 \vee A_4$$

$$c_4 : \neg A_4 \vee A_5 \vee A_{10}$$

$$c_5 : \neg A_4 \vee A_6 \vee A_{11}$$

$$c_6 : \neg A_5 \vee \neg A_6$$

$$c_7 : A_1 \vee A_7 \vee \neg A_{12}$$

$$c_8 : A_1 \vee A_8$$

$$c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$$

...



# Classic chronological backtracking – example

$$c_1 : \neg A_1 \vee A_2$$

$$c_2 : \neg A_1 \vee A_3 \vee A_9$$

$$c_3 : \neg A_2 \vee \neg A_3 \vee A_4$$

$$c_4 : \neg A_4 \vee A_5 \vee A_{10}$$

$$c_5 : \neg A_4 \vee A_6 \vee A_{11}$$


$$c_6 : \neg A_5 \vee \neg A_6$$

$$c_7 : A_1 \vee A_7 \vee \neg A_{12}$$

$$c_8 : A_1 \vee A_8$$

$$c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$$

...



$\{..., \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots\}$

(initial assignment)

# Classic chronological backtracking – example

$C_1 : \neg A_1 \vee A_2$   
 $C_2 : \neg A_1 \vee A_3 \vee A_9$   
 $C_3 : \neg A_2 \vee \neg A_3 \vee A_4$   
 $C_4 : \neg A_4 \vee A_5 \vee A_{10}$   
 $C_5 : \neg A_4 \vee A_6 \vee A_{11}$   
 $C_6 : \neg A_5 \vee \neg A_6$   
 $C_7 : A_1 \vee A_7 \vee \neg A_{12} \quad \checkmark$   
 $C_8 : A_1 \vee A_8 \quad \checkmark$   
 $C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$

...




$\{..., \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, ..., A_1\}$

... (branch on  $A_1$ )

# Classic chronological backtracking – example


$C_1 : \neg A_1 \vee A_2 \quad \checkmark$   
 $C_2 : \neg A_1 \vee A_3 \vee A_9 \quad \checkmark$   
 $C_3 : \neg A_2 \vee \neg A_3 \vee A_4$   
 $C_4 : \neg A_4 \vee A_5 \vee A_{10}$   
 $C_5 : \neg A_4 \vee A_6 \vee A_{11}$   
 $C_6 : \neg A_5 \vee \neg A_6$   
 $C_7 : A_1 \vee A_7 \vee \neg A_{12} \quad \checkmark$   
 $C_8 : A_1 \vee A_8 \quad \checkmark$   
 $C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 ...



$\{ \dots, \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots, A_1, A_2, A_3 \}$   
 (unit  $A_2, A_3$ )

# Classic chronological backtracking – example


$C_1 : \neg A_1 \vee A_2 \quad \checkmark$   
 $C_2 : \neg A_1 \vee A_3 \vee A_9 \quad \checkmark$   
 $C_3 : \neg A_2 \vee \neg A_3 \vee A_4 \quad \checkmark$   
 $C_4 : \neg A_4 \vee A_5 \vee A_{10}$   
 $C_5 : \neg A_4 \vee A_6 \vee A_{11}$   
 $C_6 : \neg A_5 \vee \neg A_6$   
 $C_7 : A_1 \vee A_7 \vee \neg A_{12} \quad \checkmark$   
 $C_8 : A_1 \vee A_8 \quad \checkmark$   
 $C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 ...



$\{..., \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, ..., A_1, A_2, A_3, A_4\}$   
 (unit  $A_4$ )

# Classic chronological backtracking – example

$C_1 : \neg A_1 \vee A_2$  ✓  
 $C_2 : \neg A_1 \vee A_3 \vee A_9$  ✓  
 $C_3 : \neg A_2 \vee \neg A_3 \vee A_4$  ✓  
 $C_4 : \neg A_4 \vee A_5 \vee A_{10}$  ✓  
 $C_5 : \neg A_4 \vee A_6 \vee A_{11}$  ✓  
 $C_6 : \neg A_5 \vee \neg A_6$  ✗  
 $C_7 : A_1 \vee A_7 \vee \neg A_{12}$  ✓  
 $C_8 : A_1 \vee A_8$  ✓  
 $C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 ...



$\{ \dots, \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots, A_1, A_2, A_3, A_4, A_5, A_6 \}$   
 (unit  $A_5, A_6$ )  $\Rightarrow$  conflict

# Classic chronological backtracking – example

$$c_1 : \neg A_1 \vee A_2$$

$$c_2 : \neg A_1 \vee A_3 \vee A_9$$

$$c_3 : \neg A_2 \vee \neg A_3 \vee A_4$$

$$c_4 : \neg A_4 \vee A_5 \vee A_{10}$$

$$c_5 : \neg A_4 \vee A_6 \vee A_{11}$$

$$c_6 : \neg A_5 \vee \neg A_6$$

$$c_7 : A_1 \vee A_7 \vee \neg A_{12}$$


$$c_8 : A_1 \vee A_8$$

$$c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$$

...

$$\{..., \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots\}$$

$\Rightarrow$  backtrack up to  $A_1$



# Classic chronological backtracking – example

$$c_1 : \neg A_1 \vee A_2 \quad \checkmark$$

$$c_2 : \neg A_1 \vee A_3 \vee A_9 \quad \checkmark$$

$$c_3 : \neg A_2 \vee \neg A_3 \vee A_4$$

$$c_4 : \neg A_4 \vee A_5 \vee A_{10}$$

$$c_5 : \neg A_4 \vee A_6 \vee A_{11}$$

$$c_6 : \neg A_5 \vee \neg A_6$$

$$c_7 : A_1 \vee A_7 \vee \neg A_{12}$$


$$c_8 : A_1 \vee A_8$$

$$c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$$

...


$$\{ \dots, \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots, \neg A_1 \}$$

(unit  $\neg A_1$ )



# Classic chronological backtracking – example

- $c_1 : \neg A_1 \vee A_2$  ✓  
 $c_2 : \neg A_1 \vee A_3 \vee A_9$  ✓  
 $c_3 : \neg A_2 \vee \neg A_3 \vee A_4$   
 $c_4 : \neg A_4 \vee A_5 \vee A_{10}$   
 $c_5 : \neg A_4 \vee A_6 \vee A_{11}$   
 $c_6 : \neg A_5 \vee \neg A_6$   
 $c_7 : A_1 \vee A_7 \vee \neg A_{12}$  ✓  
 $c_8 : A_1 \vee A_8$  ✓  
 $c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$  ✗  
 ...




$\{ \dots, \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots, \neg A_1, A_7, A_8 \}$   
 (unit  $A_7, A_8$ )  $\implies$  conflict



# Classic chronological backtracking – example

$c_1 : \neg A_1 \vee A_2$   
 $c_2 : \neg A_1 \vee A_3 \vee A_9$   
 $c_3 : \neg A_2 \vee \neg A_3 \vee A_4$   
 $c_4 : \neg A_4 \vee A_5 \vee A_{10}$   
 $c_5 : \neg A_4 \vee A_6 \vee A_{11}$   
 $c_6 : \neg A_5 \vee \neg A_6$   
 $c_7 : A_1 \vee A_7 \vee \neg A_{12}$   
 $c_8 : A_1 \vee A_8$   
 $c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 ...



$\{..., \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots\}$


$\Rightarrow$  backtrack to the most recent open branching point

# Classic chronological backtracking – example

$c_1 : \neg A_1 \vee A_2$   
 $c_2 : \neg A_1 \vee A_3 \vee A_9$   
 $c_3 : \neg A_2 \vee \neg A_3 \vee A_4$   
 $c_4 : \neg A_4 \vee A_5 \vee A_{10}$   
 $c_5 : \neg A_4 \vee A_6 \vee A_{11}$   
 $c_6 : \neg A_5 \vee \neg A_6$   
 $c_7 : A_1 \vee A_7 \vee \neg A_{12}$   
 $c_8 : A_1 \vee A_8$   
 $c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 ...

$\{ \dots, \neg A_9, \neg A_{10}, \neg A_{11}, A_{12}, A_{13}, \dots \}$

$\Rightarrow$  lots of useless search before backtracking up to  $A_{13}$ !



# Classic chronological backtracking: drawbacks

- often the branch heuristic delays the “right” choice
- chronological backtracking always backtracks to the most recent branching point, even though a higher backtrack could be possible  
⇒ lots of useless search!

# Modern DPLL implementations

## [Silva & Sakallah '96, Moskewicz et al. '01]

### Conflict-Driven Clause-Learning (CDCL) DPLL solvers:

- Non-recursive: stack-based representation of data structures
- Efficient data structures for doing and undoing assignments
- Perform **conflict-driven backtracking (backjumping)** and learning
- May perform search restarts
- Reason on total assignments

**Dramatically efficient:** solve industrial-derived problems with  $\approx 10^7$  Boolean variables and  $\approx 10^7 - 10^8$  clauses

# Conflict-directed backtracking (backjumping) and learning

- Idea: when a branch  $\mu$  fails,
  - (i) **conflict analysis**: reveal the sub-assignment  $\eta \subseteq \mu$  causing the failure (**conflict set  $\eta$** ):
    - find  $\eta \subseteq \mu$  by generating the conflict clause  $C \stackrel{\text{def}}{=} \neg\eta$  via resolution from the falsified clause  
(e.g. , via the **1<sup>st</sup>UIP strategy**)
  - (ii) **learning**: add the conflict clause  $C$  to the clause set
  - (iii) **backjumping**: **backtrack to the highest branching point s.t. the stack contains all-but-one literals in  $\eta$ , and then unit-propagate the unassigned literal on  $C$**
- may jump back up much more than one decision level in the stack  
 $\implies$  **may avoid lots of redundant search!!**.

# State-of-the-art backjumping and learning: intuitions

- **Backjumping:** climb up to many decision levels in the stack
  - intuition: “go back to the oldest decision where you’d have done something different if only you had known  $C$ ”  
⇒ may avoid lots of redundant search
- **Learning:** in future branches, when all-but-one literals in  $\eta$  are assigned, the remaining literal is assigned to false by unit-propagation:
  - intuition: “when you’re about to repeat the mistake, do the opposite of the last step”  
⇒ avoid finding the same conflict again


# State-of-the-art backjumping and learning: intuitions

- **Backjumping:** climb up to many decision levels in the stack
  - intuition: “go back to the oldest decision where you’d have done something different if only you had known  $C$ ”  
⇒ may avoid lots of redundant search
- **Learning:** in future branches, when all-but-one literals in  $\eta$  are assigned, the remaining literal is assigned to false by unit-propagation:
  - intuition: “when you’re about to repeat the mistake, do the opposite of the last step”  
⇒ avoid finding the same conflict again

# Stack-based representation of a truth assignment $\mu$

- stack partitioned into **decision levels**:
  - one **decision literal**
  - its **implied literals**
  - each implied literal tagged with the clause causing its unit-propagation (**antecedent clause**)
- equivalent to an **implication graph**:
  - a node without incoming edges represent a **decision literal**
  - the graph contains  $l_1 \xrightarrow{c} l, \dots, l_n \xrightarrow{c} l$  iff  $c \stackrel{\text{def}}{=} \bigvee_{j=1}^n \neg l_j \vee l$  is the antecedent clause of  $l$



representation of the dependencies  
between literals in  $\mu$





# Implication graph - example

- $C_1 : \neg A_1 \vee A_2$  ✓  
 $C_2 : \neg A_1 \vee A_3 \vee A_9$  ✓  
 $C_3 : \neg A_2 \vee \neg A_3 \vee A_4$  ✓  
 $C_4 : \neg A_4 \vee A_5 \vee A_{10}$  ✓  
 $C_5 : \neg A_4 \vee A_6 \vee A_{11}$  ✓  
 $C_6 : \neg A_5 \vee \neg A_6$  ✗  
 $C_7 : A_1 \vee A_7 \vee \neg A_{12}$  ✓  
 $C_8 : A_1 \vee A_8$  ✓  
 $C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$  ✓  
 ...



## Building a conflict set/clause by resolution

1.  $C :=$  conflicting clause
2. repeat
  - (i) resolve current clause  $C$  with the antecedent clause of the last unit-propagated literal  $l$  in  $C$until  $C$  verifies some given termination criteria  
(e.g., until  $C$  contains only decision literals)

$$\begin{array}{c}
\frac{\neg A_1 \vee A_2}{\neg A_1 \vee A_9 \vee A_{10} \vee A_{11}} \quad (A_2) \\
\frac{\neg A_1 \vee A_3 \vee A_9 \quad \neg A_2 \vee \neg A_1 \vee A_9 \vee A_{10} \vee A_{11}}{\neg A_2 \vee \neg A_3 \vee A_4} \quad (A_3) \\
\frac{\neg A_2 \vee \neg A_3 \vee A_4 \quad \neg A_4 \vee A_5 \vee A_{10}}{\neg A_4 \vee A_6 \vee A_{11}} \quad (A_4) \\
\frac{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_4 \vee \neg A_5 \vee A_{11}}{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_5 \vee \neg A_6} \quad (A_5) \\
\frac{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_5 \vee \neg A_6}{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_5 \vee \neg A_6} \quad (A_6)
\end{array}$$

Idea: “Undo” unit-propagations.

## Building a conflict set/clause by resolution

1.  $C :=$  conflicting clause
2. repeat
  - (i) resolve current clause  $C$  with the antecedent clause of the last unit-propagated literal  $l$  in  $C$until  $C$  verifies some given termination criteria  
(e.g., until  $C$  contains only decision literals)

$$\begin{array}{c}
\frac{\neg A_1 \vee A_2}{\neg A_1 \vee A_9 \vee A_{10} \vee A_{11}} \quad (A_2) \\
\frac{\neg A_1 \vee A_3 \vee A_9 \quad \neg A_2 \vee \neg A_1 \vee A_9 \vee A_{10} \vee A_{11}}{\neg A_2 \vee \neg A_3 \vee A_4} \quad (A_3) \\
\frac{\neg A_2 \vee \neg A_3 \vee A_4 \quad \neg A_4 \vee A_5 \vee A_{10}}{\neg A_4 \vee A_6 \vee A_{11}} \quad (A_4) \\
\frac{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_4 \vee \neg A_5 \vee A_{11}}{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_5 \vee \neg A_6} \quad (A_5) \\
\frac{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_5 \vee \neg A_6}{\neg A_4 \vee A_6 \vee A_{11} \quad \neg A_5 \vee \neg A_6} \quad (A_6)
\end{array}$$

Idea: “Undo” unit-propagations.

# State-of-the-art in backjumping & learning



## First Unique Implication Point (1st UIP) strategy:

- corresponds to consider the first clause encountered containing one literal of the current level (1st UIP).

$$\begin{array}{c}
 \neg A_4 \vee A_5 \vee A_{10} \\
 \hline
 \underbrace{\neg A_4}_{1st\ UIP} \vee A_{10} \vee A_{11} \\
 \hline
 \neg A_4 \vee A_6 \vee A_{11} \quad \overbrace{\neg A_5 \vee \neg A_6}^{Conflicting\ cl.} \\
 \hline
 \neg A_4 \vee \neg A_5 \vee A_{11} \quad (A_5) \\
 \hline
 (A_6)
 \end{array}$$

# 1st UIP strategy – example

- $C_1 : \neg A_1 \vee A_2$  ✓  
 $C_2 : \neg A_1 \vee A_3 \vee A_9$  ✓  
 $C_3 : \neg A_2 \vee \neg A_3 \vee A_4$  ✓  
 $C_4 : \neg A_4 \vee A_5 \vee A_{10}$  ✓  
 $C_5 : \neg A_4 \vee A_6 \vee A_{11}$  ✓  
 $C_6 : \neg A_5 \vee \neg A_6$  ✗  
 $C_7 : A_1 \vee A_7 \vee \neg A_{12}$  ✓  
 $C_8 : A_1 \vee A_8$  ✓  
 $C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 ...



$\Rightarrow$  Conflict set:  $\{\neg A_{10}, \neg A_{11}, A_4\}$ , learn  $c_{10} := A_{10} \vee A_{11} \vee \neg A_4$

# 1st UIP strategy and backjumping



- The added conflict clause states the reason for the conflict
- The procedure backtracks to the most recent decision level of the variables in the conflict clause which are not the UIP.
- then the conflict clause forces the negation of the UIP by unit propagation.

E.g.:  $c_{10} := A_{10} \vee A_{11} \vee \neg A_4$

$\implies$  backtrack to  $A_{11}$ , then assign  $\neg A_4$

## 1st UIP strategy – example (7)

- $C_1 : \neg A_1 \vee A_2$  ✓  
 $C_2 : \neg A_1 \vee A_3 \vee A_9$  ✓  
 $C_3 : \neg A_2 \vee \neg A_3 \vee A_4$  ✓  
 $C_4 : \neg A_4 \vee A_5 \vee A_{10}$  ✓  
 $C_5 : \neg A_4 \vee A_6 \vee A_{11}$  ✓  
 $C_6 : \neg A_5 \vee \neg A_6$  ✗  
 $C_7 : A_1 \vee A_7 \vee \neg A_{12}$  ✓  
 $C_8 : A_1 \vee A_8$  ✓  
 $C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 ...



$\Rightarrow$  Conflict set:  $\{\neg A_{10}, \neg A_{11}, A_4\}$ , learn  $c_{10} := A_{10} \vee A_{11} \vee \neg A_4$

## 1st UIP strategy – example (8)

$$c_1 : \neg A_1 \vee A_2$$

$$c_2 : \neg A_1 \vee A_3 \vee A_9$$

$$c_3 : \neg A_2 \vee \neg A_3 \vee A_4$$

$$c_4 : \neg A_4 \vee A_5 \vee A_{10}$$

$$c_5 : \neg A_4 \vee A_6 \vee A_{11}$$

$$c_6 : \neg A_5 \vee \neg A_6$$


$$c_7 : A_1 \vee A_7 \vee \neg A_{12}$$

$$c_8 : A_1 \vee A_8$$

$$c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$$

$$c_{10} : A_{10} \vee A_{11} \vee \neg A_4$$

...




$\Rightarrow$  backtrack up to  $A_{11} \Rightarrow \{\dots, \neg A_9, \neg A_{10}, \neg A_{11}\}$



## 1st UIP strategy – example (9)

$c_1 : \neg A_1 \vee A_2$   
 $c_2 : \neg A_1 \vee A_3 \vee A_9$   
 $c_3 : \neg A_2 \vee \neg A_3 \vee A_4$   
 $c_4 : \neg A_4 \vee A_5 \vee A_{10} \quad \checkmark$   
 $c_5 : \neg A_4 \vee A_6 \vee A_{11} \quad \checkmark$   
 $c_6 : \neg A_5 \vee \neg A_6$   
 $c_7 : A_1 \vee A_7 \vee \neg A_{12}$   
 $c_8 : A_1 \vee A_8$   
 $c_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13}$   
 $c_{10} : A_{10} \vee A_{11} \vee \neg A_4 \quad \checkmark$   
 ...



$\Rightarrow$  unit propagate  $\neg A_4 \Rightarrow \{..., \neg A_9, \neg A_{10}, \neg A_{11}, A_4\}...$

# Learning – example

$$C_1 : \neg A_1 \vee A_2$$

$$C_2 : \neg A_1 \vee A_3 \vee A_9$$

$$C_3 : \neg A_2 \vee \neg A_3 \vee A_4$$

$$C_4 : \neg A_4 \vee A_5 \vee A_{10}$$

$$C_5 : \neg A_4 \vee A_6 \vee A_{11}$$

$$C_6 : \neg A_5 \vee \neg A_6$$

$$C_7 : A_1 \vee A_7 \vee \neg A_{12}$$

$$C_8 : A_1 \vee A_8$$



$$C_9 : \neg A_7 \vee \neg A_8 \vee \neg A_{13} \quad \checkmark$$

$$C_{10} : A_9 \vee A_{10} \vee A_{11} \vee \neg A_1 \quad \checkmark$$

$$C_{11} : A_9 \vee A_{10} \vee A_{11} \vee \neg A_{12} \vee \neg A_{13} \quad \checkmark$$

...

$$\Rightarrow \text{Unit: } \{\neg A_1, \neg A_{13}\}$$



## Remark: the “quality” of conflict sets

- Different ideas of “good” conflict set
  - Backjumping: if causes the highest backjump (“local” role)
  - Learning: if causes the maximum pruning (“global” role)
- Many different strategies implemented

# Drawbacks of Learning

- Prunes drastically the search.
- Problem: may cause a blowup in space
  - ⇒ techniques to drop learned clauses when necessary
    - according to their size
    - according to their activity.

## Definition

A clause is currently **active** if it occurs in the current implication graph (i.e., it is the antecedent clause of a literal in the current assignment).

## Property

In order to guarantee correctness, completeness & termination of a CDCL solver, it suffices to keep each clause until it is active.

⇒ **CDCL solvers require polynomial space**

# Drawbacks of Learning

- Prunes drastically the search.
- Problem: may cause a blowup in space
  - ⇒ techniques to drop learned clauses when necessary
    - according to their size
    - according to their **activity**.

## Definition

A clause is currently **active** if it occurs in the current implication graph (i.e., it is the antecedent clause of a literal in the current assignment).

## Property

In order to guarantee correctness, completeness & termination of a CDCL solver, it suffices to keep each clause until it is active.

⇒ **CDCL solvers require polynomial space**

# Drawbacks of Learning

- Prunes drastically the search.
- Problem: may cause a blowup in space
  - ⇒ techniques to drop learned clauses when necessary
    - according to their size
    - according to their **activity**.

## Definition

A clause is currently **active** if it occurs in the current implication graph (i.e., it is the antecedent clause of a literal in the current assignment).

## Property

In order to guarantee correctness, completeness & termination of a CDCL solver, it suffices to keep each clause until it is active.

⇒ **CDCL solvers require polynomial space**

# Drawbacks of Learning

- Prunes drastically the search.
- Problem: may cause a blowup in space
  - ⇒ techniques to drop learned clauses when necessary
    - according to their size
    - according to their **activity**.

## Definition

A clause is currently **active** if it occurs in the current implication graph (i.e., it is the antecedent clause of a literal in the current assignment).

## Property

In order to guarantee correctness, completeness & termination of a CDCL solver, it suffices to keep each clause until it is active.

⇒ **CDCL solvers require polynomial space**

# Many applications of SAT Solvers


- Many successful applications of SAT:
  - Boolean circuits
  - (Bounded) Planning
  - (Bounded) Model Checking
  - Cryptography
  - Scheduling
  - ...
- All NP-complete problem can be (polynomially) converted to SAT.
- Key issue: find an efficient encoding.




# Outline

- 1 Motivations
- 2 Background on SAT Solving
- 3 Bounded Model Checking: an example**
- 4 Bounded Model Checking
- 5 Computing upper bounds for  $k$
- 6 Inductive reasoning on invariants (aka “K-Induction”)
- 7 Exercises

# Bounded Model Checking: Example




- LTL Formula:  $\mathbf{G}(p \rightarrow \mathbf{F}q)$
- Negated Formula (violation):  $\mathbf{F}(p \wedge \mathbf{G}\neg q)$
- $k = 0$ :




- No counter-example found.

# Bounded Model Checking: Example




- LTL Formula:  $\mathbf{G}(p \rightarrow \mathbf{F}q)$
- Negated Formula (violation):  $\mathbf{F}(p \wedge \mathbf{G}\neg q)$
- $k = 1$ :




- No counter-example found.

# Bounded Model Checking: Example




- LTL Formula:  $\mathbf{G}(p \rightarrow \mathbf{F}q)$
- Negated Formula (violation):  $\mathbf{F}(p \wedge \mathbf{G}\neg q)$
- $k = 2$ :




- No counter-example found.

# Bounded Model Checking: Example



- LTL Formula:  $\mathbf{G}(p \rightarrow \mathbf{F}q)$
- Negated Formula (violation):  $\mathbf{F}(p \wedge \mathbf{G}\neg q)$
- $k = 3$ :



- The 2nd trace is a counter-example!

# Outline

- 1 Motivations
- 2 Background on SAT Solving
- 3 Bounded Model Checking: an example
- 4 Bounded Model Checking**
- 5 Computing upper bounds for  $k$
- 6 Inductive reasoning on invariants (aka “K-Induction”)
- 7 Exercises

# The problem [Biere et al, 1999]

## Ingredients:

- A **system** written as a Kripke structure  $M := \langle S, I, T, \mathcal{L} \rangle$
- A **property**  $f$  written as a **LTL formula**:
- an integer  $k \geq 0$  (**bound**)

## Problem

Is there a (possibly-partial) execution path  $\pi$  of  $M$  of length  $k$  satisfying the temporal property  $f$ ?

- the check is repeated for increasing values of  $k = 1, 2, 3, \dots$

# The problem [Biere et al, 1999]

## Ingredients:

- A **system** written as a Kripke structure  $M := \langle S, I, T, \mathcal{L} \rangle$
- A **property**  $f$  written as a **LTL formula**:
- an integer  $k \geq 0$  (**bound**)

## Problem

Is there a (possibly-partial) execution path  $\pi$  of  $M$  of length  $k$  satisfying the temporal property  $f$ ?

- the check is repeated for increasing values of  $k = 1, 2, 3, \dots$



# The problem [Biere et al, 1999]

## Ingredients:

- A **system** written as a Kripke structure  $M := \langle S, I, T, \mathcal{L} \rangle$
- A **property**  $f$  written as a **LTL formula**:
- an integer  $k \geq 0$  (**bound**)

## Problem

Is there a (possibly-partial) execution path  $\pi$  of  $M$  of length  $k$  satisfying the temporal property  $f$ ?

- the check is repeated for increasing values of  $k = 1, 2, 3, \dots$

# The encoding

Equivalent to the satisfiability problem of a Boolean formula  $[[M, f]]_k$  defined as follows:

$$[[M, f]]_k := [[M]]_k \wedge [[f]]_k \quad (1)$$

$$[[M]]_k := I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}), \quad (2)$$

$$[[f]]_k := (\neg \bigvee_{l=0}^k R(s^k, s^l) \wedge [[f]]_k^0) \vee \bigvee_{l=0}^k (R(s^k, s^l) \wedge {}_l[[f]]_k^0), \quad (3)$$

- the vector  $s$  of propositional variables is replicated  $k+1$  times  
 $s^0, s^1, \dots, s^k$
- $[[M]]_k$  encodes the fact that the  $k$ -path is an execution of  $M$
- $[[f]]_k$  encodes the fact that the  $k$ -path satisfies  $f$

# The encoding

Equivalent to the satisfiability problem of a Boolean formula  $[[M, f]]_k$  defined as follows:

$$[[M, f]]_k := [[M]]_k \wedge [[f]]_k \quad (1)$$

$$[[M]]_k := I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}), \quad (2)$$

$$[[f]]_k := (\neg \bigvee_{l=0}^k R(s^k, s^l) \wedge [[f]]_k^0) \vee \bigvee_{l=0}^k (R(s^k, s^l) \wedge {}_l[[f]]_k^0), \quad (3)$$

- the vector  $s$  of propositional variables is replicated  $k+1$  times  $s^0, s^1, \dots, s^k$
- $[[M]]_k$  encodes the fact that the  $k$ -path is an execution of  $M$
- $[[f]]_k$  encodes the fact that the  $k$ -path satisfies  $f$

# The encoding

Equivalent to the satisfiability problem of a Boolean formula  $[[M, f]]_k$  defined as follows:

$$[[M, f]]_k := [[M]]_k \wedge [[f]]_k \quad (1)$$

$$[[M]]_k := I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}), \quad (2)$$

$$[[f]]_k := (\neg \bigvee_{l=0}^k R(s^k, s^l) \wedge [[f]]_k^0) \vee \bigvee_{l=0}^k (R(s^k, s^l) \wedge {}_l[[f]]_k^0), \quad (3)$$

- the vector  $\mathbf{s}$  of propositional variables is replicated  $k+1$  times  $s^0, s^1, \dots, s^k$
- $[[M]]_k$  encodes the fact that the  $k$ -path is an execution of  $M$
- $[[f]]_k$  encodes the fact that the  $k$ -path satisfies  $f$

# The encoding

Equivalent to the satisfiability problem of a Boolean formula  $[[M, f]]_k$  defined as follows:

$$[[M, f]]_k := [[M]]_k \wedge [[f]]_k \quad (1)$$

$$[[M]]_k := I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}), \quad (2)$$

$$[[f]]_k := (\neg \bigvee_{l=0}^k R(s^k, s^l) \wedge [[f]]_k^0) \vee \bigvee_{l=0}^k (R(s^k, s^l) \wedge {}_l[[f]]_k^0), \quad (3)$$

- the vector  $s$  of propositional variables is replicated  $k+1$  times  $s^0, s^1, \dots, s^k$
- $[[M]]_k$  encodes the fact that the  $k$ -path is an execution of  $M$
- $[[f]]_k$  encodes the fact that the  $k$ -path satisfies  $f$

# The Encoding [cont.]

In general, the encoding for a formula  $f$  with  $k$  steps,  $[[f]]_k$  is the disjunction of

- the constraints needed to express a model without loopback:

$$(\neg(\bigvee_{l=0}^k R(s^k, s^l)) \wedge [[f]]_k^0)$$

- $[[f]]_k^i, i \in [0, k]$ : encodes the fact that  $f$  holds in  $s^i$  under the assumption that  $s^0, \dots, s^k$  is a no-loopback path
- the constraints needed to express a given loopback, for all possible points of loopback:
 
$$\bigvee_{l=0}^k (R(s^k, s^l) \wedge {}_l[[f]]_k^0)$$
  - ${}_l[[f]]_k^0, i \in [0, k]$ : encodes the fact that  $f$  holds in  $s^i$  under the assumption that  $s^0, \dots, s^k$  is a path with a loopback from  $s^k$  to  $s^l$

# The Encoding [cont.]

In general, the encoding for a formula  $f$  with  $k$  steps,  $[[f]]_k$  is the disjunction of

- the constraints needed to express a model without loopback:

$$(\neg(\bigvee_{l=0}^k R(s^k, s^l)) \wedge [[f]]_k^0)$$



- $[[f]]_k^i, i \in [0, k]$ : encodes the fact that  $f$  holds in  $s^i$  under the assumption that  $s^0, \dots, s^k$  is a no-loopback path
- the constraints needed to express a given loopback, for all possible points of loopback:
 
$$\bigvee_{l=0}^k (R(s^k, s^l) \wedge {}_l[[f]]_k^0)$$
  - ${}_l[[f]]_k^0, i \in [0, k]$ : encodes the fact that  $f$  holds in  $s^i$  under the assumption that  $s^0, \dots, s^k$  is a path with a loopback from  $s^k$  to  $s^l$

# The Encoding [cont.]

In general, the encoding for a formula  $f$  with  $k$  steps,  $[[f]]_k$  is the disjunction of


- the constraints needed to express a model without loopback:

$$(\neg(\bigvee_{l=0}^k R(s^k, s^l)) \wedge [[f]]_k^0)$$



- $[[f]]_k^i, i \in [0, k]$ : encodes the fact that  $f$  holds in  $s^i$  under the assumption that  $s^0, \dots, s^k$  is a no-loopback path
- the constraints needed to express a given loopback, for all possible points of loopback:

$$\bigvee_{l=0}^k (R(s^k, s^l) \wedge {}_l[[f]]_k^0)$$



- ${}_l[[f]]_k^0, l \in [0, k]$ : encodes the fact that  $f$  holds in  $s^l$  under the assumption that  $s^0, \dots, s^k$  is a path with a loopback from  $s^k$  to  $s^l$



# The encoding of $[[f]]_k^i$ and ${}_i[[f]]_k^i$

$f$	$[[f]]_k^i$	${}_i[[f]]_k^i$
$p$	$p_i$	$p_i$
$\neg p$	$\neg p_i$	$\neg p_i$
$h \wedge g$	$[[h]]_k^i \wedge [[g]]_k^i$	${}_i[[h]]_k^i \wedge {}_i[[g]]_k^i$
$h \vee g$	$[[h]]_k^i \vee [[g]]_k^i$	${}_i[[h]]_k^i \vee {}_i[[g]]_k^i$
$\mathbf{X}g$	$\begin{array}{ll} [[g]]_k^{i+1} & \text{if } i < k \\ \perp & \text{otherwise.} \end{array}$	$\begin{array}{ll} {}_i[[g]]_k^{i+1} & \text{if } i < k \\ {}_i[[g]]_k^i & \text{otherwise.} \end{array}$
$\mathbf{G}g$	$\perp$	$\bigwedge_{j=\min(i,l)}^k {}_i[[g]]_k^j$
$\mathbf{F}g$	$\bigvee_{j=i}^k [[g]]_k^j$	$\bigvee_{j=\min(i,l)}^k {}_i[[g]]_k^j$
$h\mathbf{U}g$	$\bigvee_{j=i}^k \left( [[g]]_k^j \wedge \bigwedge_{n=i}^{j-1} [[h]]_k^n \right)$	$\begin{aligned} & \bigvee_{j=i}^k \left( {}_i[[g]]_k^j \wedge \bigwedge_{n=i}^{j-1} {}_i[[h]]_k^n \right) \vee \\ & \bigvee_{j=l}^{i-1} \left( {}_i[[g]]_k^j \wedge \bigwedge_{n=i}^k {}_i[[h]]_k^n \wedge \bigwedge_{n=l}^{j-1} {}_i[[h]]_k^n \right) \end{aligned}$
$h\mathbf{R}g$	$\bigvee_{j=i}^k \left( [[h]]_k^j \wedge \bigwedge_{n=i}^j [[g]]_k^n \right)$	$\begin{aligned} & \bigwedge_{j=\min(i,l)}^k {}_i[[g]]_k^j \vee \\ & \bigvee_{j=i}^k \left( {}_i[[h]]_k^j \wedge \bigwedge_{n=i}^j {}_i[[g]]_k^n \right) \vee \\ & \bigvee_{j=l}^{i-1} \left( {}_i[[h]]_k^j \wedge \bigwedge_{n=i}^k {}_i[[g]]_k^n \wedge \bigwedge_{n=l}^j {}_i[[g]]_k^n \right) \end{aligned}$

## Example: $Fp$ (reachability)

- $f := Fp$ , s.t.  $p$  Boolean:  
is there a reachable state in which  $p$  holds?
- a finite path can show that the property holds
- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{j=0}^k p^j$$

### Note

if done for increasing value of  $k$ , then it suffices that  $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} \left( R(s^i, s^{i+1}) \wedge \neg p^i \right) \wedge p^k$$

## Example: $\mathbf{F}p$ (reachability)

- $f := \mathbf{F}p$ , s.t.  $p$  Boolean:  
is there a reachable state in which  $p$  holds?
- a finite path can show that the property holds
- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{j=0}^k p^j$$


### Note

if done for increasing value of  $k$ , then it suffices that  $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} \left( R(s^i, s^{i+1}) \wedge \neg p^i \right) \wedge p^k$$

## Example: $Fp$ (reachability)

- $f := Fp$ , s.t.  $p$  Boolean:  
is there a reachable state in which  $p$  holds?
- a finite path can show that the property holds
- $[[M, f]]_k$  is:




### Note

if done for increasing value of  $k$ , then it suffices that  $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} \left( R(s^i, s^{i+1}) \wedge \neg p^i \right) \wedge p^k$$

## Example: $Fp$ (reachability)

- $f := Fp$ , s.t.  $p$  Boolean:  
is there a reachable state in which  $p$  holds?
- a finite path can show that the property holds
- $[[M, f]]_k$  is:



### Note

if done for increasing value of  $k$ , then it suffices that  $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} \left( R(s^i, s^{i+1}) \wedge \neg p^i \right) \wedge p^k$$

# Example: $\mathbf{G}p$

- $f := \mathbf{G}p$ , s.t.  $p$  Boolean: is there a path where  $p$  holds forever?
- We need to produce an infinite behaviour, with a finite number of transitions
- We can do it by imposing that the path loops back

- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{l=0}^k R(s^k, s^l) \wedge \bigwedge_{j=0}^k p^j$$

## Example: $\mathbf{G}p$


- $f := \mathbf{G}p$ , s.t.  $p$  Boolean: **is there a path where  $p$  holds forever?**
- We need to produce an infinite behaviour, with a finite number of transitions
- We can do it by imposing that the path loops back

- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{l=0}^k R(s^k, s^l) \wedge \bigwedge_{j=0}^k p^j$$

# Example: $Gp$

- $f := Gp$ , s.t.  $p$  Boolean: is there a path where  $p$  holds forever?
- We need to produce an infinite behaviour, with a finite number of transitions
- We can do it by imposing that the path loops back




- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{l=0}^k R(s^k, s^l) \wedge \bigwedge_{j=0}^k p^j$$



# Example: $\mathbf{G}p$

- $f := \mathbf{G}p$ , s.t.  $p$  Boolean: is there a path where  $p$  holds forever?
- We need to produce an infinite behaviour, with a finite number of transitions
- We can do it by imposing that the path loops back



- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{l=0}^k R(s^k, s^l) \wedge \bigwedge_{j=0}^k p^j$$

## Example: $\mathbf{GF}q$ (fair states)


- $f := \mathbf{GF}q$ , s.t.  $q$  Boolean: does  $q$  hold infinitely often?
- Again, we need to produce an infinite behaviour, with a finite number of transitions

- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{l=0}^k \left( R(s^k, s^l) \wedge \bigvee_{j=l}^k q^j \right)$$

# Example: $\mathbf{GF}q$ (fair states)

- $f := \mathbf{GF}q$ , s.t.  $q$  Boolean: does  $q$  hold infinitely often?
- Again, we need to produce an infinite behaviour, with a finite number of transitions




- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{l=0}^k \left( R(s^k, s^l) \wedge \bigvee_{j=l}^k q^j \right)$$

# Example: $\mathbf{GF}q$ (fair states)

- $f := \mathbf{GF}q$ , s.t.  $q$  Boolean: does  $q$  hold infinitely often?
- Again, we need to produce an infinite behaviour, with a finite number of transitions



- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{l=0}^k \left( R(s^k, s^l) \wedge \bigvee_{j=l}^k q^j \right)$$

## Example: $\mathbf{GF}q \wedge \mathbf{F}p$ (fair reachability)


- $f := \mathbf{GF}q \wedge \mathbf{F}p$ , s.t.  $p, q$  Boolean: provided that  $q$  holds infinitely often, is there a reachable state in which  $p$  holds?
- Again, we need to produce an infinite behaviour, with a finite number of transitions

- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{j=0}^k p_j \wedge \bigvee_{l=0}^k \left( R(s^k, s^l) \wedge \bigvee_{j=l}^k q^j \right)$$

## Example: $\mathbf{GF}q \wedge \mathbf{F}p$ (fair reachability)

- $f := \mathbf{GF}q \wedge \mathbf{F}p$ , s.t.  $p, q$  Boolean: provided that  $q$  holds infinitely often, is there a reachable state in which  $p$  holds?
- Again, we need to produce an infinite behaviour, with a finite number of transitions




- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{j=0}^k p_j \wedge \bigvee_{l=0}^k \left( R(s^k, s^l) \wedge \bigvee_{j=l}^k q^j \right)$$

## Example: $\mathbf{GF}q \wedge \mathbf{F}p$ (fair reachability)

- $f := \mathbf{GF}q \wedge \mathbf{F}p$ , s.t.  $p, q$  Boolean: provided that  $q$  holds infinitely often, is there a reachable state in which  $p$  holds?
- Again, we need to produce an infinite behaviour, with a finite number of transitions



- $[[M, f]]_k$  is:

$$I(s^0) \wedge \bigwedge_{i=0}^{k-1} R(s^i, s^{i+1}) \wedge \bigvee_{j=0}^k p_j \wedge \bigvee_{l=0}^k \left( R(s^k, s^l) \wedge \bigvee_{j=l}^k q^j \right)$$

# Example: a bugged 3-bit shift register

- System  $M$ :

- $I(x) := \top$  (arbitrary initial state)
- Correct  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0)$
- Bugged  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 1)$

- Property: **AF** $(\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$

- BMC Problem: exists an execution  $\pi$  of  $\mathcal{M}$  of length  $k$  s.t.  
 $\pi \models \mathbf{G}((x[0] \vee x[1] \vee x[2]))?$



# Example: a bugged 3-bit shift register

- System  $M$ :
  - $I(x) := \top$  (arbitrary initial state)
  - Correct  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0)$
  - Bugged  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 1)$
- Property:  $\mathbf{AF}(\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
- BMC Problem: exists an execution  $\pi$  of  $\mathcal{M}$  of length  $k$  s.t.  
 $\pi \models \mathbf{G}((x[0] \vee x[1] \vee x[2]))?$

# Example: a bugged 3-bit shift register

- System  $M$ :
  - $I(x) := \top$  (arbitrary initial state)
  - Correct  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0)$
  - Bugged  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 1)$
- Property:  $\mathbf{AF}(\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
- BMC Problem: exists an execution  $\pi$  of  $\mathcal{M}$  of length  $k$  s.t.  
 $\pi \models \mathbf{G}((x[0] \vee x[1] \vee x[2]))?$

# Example: a bugged 3-bit shift register

- System  $M$ :
  - $I(x) := \top$  (arbitrary initial state)
  - Correct  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0)$
  - Bugged  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 1)$
- Property:  $\mathbf{AF}(\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
- BMC Problem: exists an execution  $\pi$  of  $\mathcal{M}$  of length  $k$  s.t.  
 $\pi \models \mathbf{G}((x[0] \vee x[1] \vee x[2]))?$

# Example: a bugged 3-bit shift register


- System  $M$ :
  - $I(x) := \top$  (arbitrary initial state)
  - Correct  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0)$
  - Bugged  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 1)$
- Property: **AF** $(\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
- BMC Problem: exists an execution  $\pi$  of  $\mathcal{M}$  of length  $k$  s.t.  
 $\pi \models \mathbf{G}((x[0] \vee x[1] \vee x[2]))?$

# Example: a bugged 3-bit shift register

- System  $M$ :
  - $I(x) := \top$  (arbitrary initial state)
  - Correct  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0)$
  - Bugged  $R$ :  $R(x, x') := (x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 1)$
- Property: **AF** $(\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
- BMC Problem: exists an execution  $\pi$  of  $\mathcal{M}$  of length  $k$  s.t.  
 $\pi \models \mathbf{G}((x[0] \vee x[1] \vee x[2]))?$

# Example: a bugged 3-bit shift register [cont.]


$k = 2$ :



$$\begin{aligned}
 & [[M]]_2 : \left( \begin{aligned} & (x_1[0] \leftrightarrow x_0[1]) \wedge (x_1[1] \leftrightarrow x_0[2]) \wedge (x_1[2] \leftrightarrow 1) \wedge \\ & (x_2[0] \leftrightarrow x_1[1]) \wedge (x_2[1] \leftrightarrow x_1[2]) \wedge (x_2[2] \leftrightarrow 1) \end{aligned} \right) \wedge \\
 & \bigvee_{i=0}^2 L_i : \left( \begin{aligned} & ((x_0[0] \leftrightarrow x_2[1]) \wedge (x_0[1] \leftrightarrow x_2[2]) \wedge (x_0[2] \leftrightarrow 1)) \vee \\ & ((x_1[0] \leftrightarrow x_2[1]) \wedge (x_1[1] \leftrightarrow x_2[2]) \wedge (x_1[2] \leftrightarrow 1)) \vee \\ & ((x_2[0] \leftrightarrow x_2[1]) \wedge (x_2[1] \leftrightarrow x_2[2]) \wedge (x_2[2] \leftrightarrow 1)) \end{aligned} \right) \wedge \\
 & \bigwedge_{i=0}^2 (x \neq 0) : \left( \begin{aligned} & (x_0[0] \vee x_0[1] \vee x_0[2]) \wedge \\ & (x_1[0] \vee x_1[1] \vee x_1[2]) \wedge \\ & (x_2[0] \vee x_2[1] \vee x_2[2]) \end{aligned} \right) \\
 & \implies \text{SAT: } x_i[j] := 1 \ \forall i, j
 \end{aligned}$$

# Example: a bugged 3-bit shift register [cont.]


$k = 2$ :



$$\begin{aligned}
 [[M]]_2 : & \left( (x_1[0] \leftrightarrow x_0[1]) \wedge (x_1[1] \leftrightarrow x_0[2]) \wedge (x_1[2] \leftrightarrow 1) \wedge \right. \\
 & \left. (x_2[0] \leftrightarrow x_1[1]) \wedge (x_2[1] \leftrightarrow x_1[2]) \wedge (x_2[2] \leftrightarrow 1) \right) \wedge \\
 \bigvee_{l=0}^2 L_l : & \left( ((x_0[0] \leftrightarrow x_2[1]) \wedge (x_0[1] \leftrightarrow x_2[2]) \wedge (x_0[2] \leftrightarrow 1)) \vee \right. \\
 & ((x_1[0] \leftrightarrow x_2[1]) \wedge (x_1[1] \leftrightarrow x_2[2]) \wedge (x_1[2] \leftrightarrow 1)) \vee \\
 & ((x_2[0] \leftrightarrow x_2[1]) \wedge (x_2[1] \leftrightarrow x_2[2]) \wedge (x_2[2] \leftrightarrow 1)) \left. \right) \wedge \\
 \bigwedge_{i=0}^2 (x \neq 0) : & \left( \begin{aligned} & (x_0[0] \vee x_0[1] \vee x_0[2]) \wedge \\ & (x_1[0] \vee x_1[1] \vee x_1[2]) \wedge \\ & (x_2[0] \vee x_2[1] \vee x_2[2]) \end{aligned} \right) \\
 \Rightarrow \text{SAT: } & x_i[j] := 1 \forall i, j
 \end{aligned}$$

# Example: a bugged 3-bit shift register [cont.]

$k = 2$ :



$$\begin{aligned}
 &[[M]]_2 : \left( \begin{aligned} &(x_1[0] \leftrightarrow x_0[1]) \wedge (x_1[1] \leftrightarrow x_0[2]) \wedge (x_1[2] \leftrightarrow 1) \wedge \\ &(x_2[0] \leftrightarrow x_1[1]) \wedge (x_2[1] \leftrightarrow x_1[2]) \wedge (x_2[2] \leftrightarrow 1) \end{aligned} \right) \wedge \\
 &\bigvee_{l=0}^2 L_l : \left( \begin{aligned} &((x_0[0] \leftrightarrow x_2[1]) \wedge (x_0[1] \leftrightarrow x_2[2]) \wedge (x_0[2] \leftrightarrow 1)) \vee \\ &((x_1[0] \leftrightarrow x_2[1]) \wedge (x_1[1] \leftrightarrow x_2[2]) \wedge (x_1[2] \leftrightarrow 1)) \vee \\ &((x_2[0] \leftrightarrow x_2[1]) \wedge (x_2[1] \leftrightarrow x_2[2]) \wedge (x_2[2] \leftrightarrow 1)) \end{aligned} \right) \wedge \\
 &\bigwedge_{i=0}^2 (x \neq 0) : \left( \begin{aligned} &(x_0[0] \vee x_0[1] \vee x_0[2]) \wedge \\ &(x_1[0] \vee x_1[1] \vee x_1[2]) \wedge \\ &(x_2[0] \vee x_2[1] \vee x_2[2]) \end{aligned} \right) \\
 &\implies \text{SAT: } x_i[j] := 1 \ \forall i, j
 \end{aligned}$$



# Bounded Model Checking: summary

- **incomplete technique:**
  - if you find all formulas unsatisfiable, it tells you nothing
  - computing the maximum  $k$  (diameter) possible but extremely hard
- **very efficient** for some problems (typically debugging)
- lots of enhancements
- current symbolic model checkers embed a SAT based BMC tool

# Bounded Model Checking: summary

- **incomplete technique:**
  - if you find all formulas unsatisfiable, it tells you nothing
  - computing the maximum  $k$  (diameter) possible but extremely hard
- **very efficient** for some problems (typically debugging)
- lots of enhancements
- current symbolic model checkers embed a SAT based BMC tool

# Bounded Model Checking: summary

- **incomplete technique:**
  - if you find all formulas unsatisfiable, it tells you nothing
  - computing the maximum  $k$  (diameter) possible but extremely hard
- **very efficient** for some problems (typically debugging)
- lots of enhancements
- current symbolic model checkers embed a SAT based BMC tool

# Bounded Model Checking: summary

- **incomplete technique:**
  - if you find all formulas unsatisfiable, it tells you nothing
  - computing the maximum  $k$  (diameter) possible but extremely hard
- **very efficient** for some problems (typically debugging)
- lots of enhancements
- current symbolic model checkers embed a SAT based BMC tool

# Efficiency Issues in Bounded Model Checking

- Caching different problems:
  - can we exploit the similarities between problems at  $k$  and  $k + 1$ ?
- Simplification of encodings
  - Reduced Boolean Circuits (RBC)
  - Boolean Expression Diagrams (BED)
  - And-Inverter Graphs (AIG)
  - Simplification based on Binary-Clauses Reasoning
- When can we stop increasing the bound  $k$  if we don't find violations?

# Efficiency Issues in Bounded Model Checking

- Caching different problems:
  - can we exploit the similarities between problems at  $k$  and  $k + 1$ ?
- Simplification of encodings
  - Reduced Boolean Circuits (RBC)
  - Boolean Expression Diagrams (BED)
  - And-Inverter Graphs (AIG)
  - Simplification based on Binary-Clauses Reasoning
- When can we stop increasing the bound  $k$  if we don't find violations?

# Efficiency Issues in Bounded Model Checking

- Caching different problems:
  - can we exploit the similarities between problems at  $k$  and  $k + 1$ ?
- Simplification of encodings
  - Reduced Boolean Circuits (RBC)
  - Boolean Expression Diagrams (BED)
  - And-Inverter Graphs (AIG)
  - Simplification based on Binary-Clauses Reasoning
- When can we stop increasing the bound  $k$  if we don't find violations?

# Outline

- 1 Motivations
- 2 Background on SAT Solving
- 3 Bounded Model Checking: an example
- 4 Bounded Model Checking
- 5 Computing upper bounds for  $k$**
- 6 Inductive reasoning on invariants (aka “K-Induction”)
- 7 Exercises



# Basic bounds for $k$

## Theorem [Biere et al. TACAS 1999]

Let  $f$  be a LTL formula.  $M \models \mathbf{E}f \iff M \models_k \mathbf{E}f$  for some  $k \leq |M| \cdot 2^{|f|}$ .

- $|M| \cdot 2^{|f|}$  is always a bound of  $k$ .
  - $|M|$  huge!
- $\implies$  not so easy to compute in a symbolic setting.

$\implies$  need to find better bounds!

# Basic bounds for $k$

## Theorem [Biere et al. TACAS 1999]

Let  $f$  be a LTL formula.  $M \models \mathbf{E}f \iff M \models_k \mathbf{E}f$  for some  $k \leq |M| \cdot 2^{|f|}$ .

- $|M| \cdot 2^{|f|}$  is always a bound of  $k$ .
  - $|M|$  huge!
  - $\implies$  not so easy to compute in a symbolic setting.
- $\implies$  need to find better bounds!

## Other bounds for $k$

### ACTL & ECTL

- **ACTL** is a subset of CTL in which “**A...**” (resp. “**E...**”) sub-formulas occur only positively (resp. negatively) in each formula.  
e.g. **AG**( $p \rightarrow$  **AGAF** $q$ )
- **ECTL** is a subset of CTL in which “**E...**” (resp. “**A...**”) sub-formulas occur only positively (resp. negatively) in each formula.  
e.g. **EF**( $p \wedge$  **EFEG** $\neg q$ )
- ECTL is the dual subset of ACTL:  $\phi \in ECTL \iff \neg\phi \in ACTL$ .
- Many frequently-used LTL properties  $\neg f$  have equivalent ACTL representations  $\neg f'$  (e.g. **G**( $p \rightarrow$  **GF** $q$ ) wrt. **AG**( $p \rightarrow$  **AGAF** $q$ )):

$$M \not\models_{LTL} \neg f \Leftrightarrow M \not\models_{CTL^*} \mathbf{A}\neg f \Leftrightarrow M \not\models_{CTL^*} \mathbf{A}\neg f' \Leftrightarrow M \models_{CTL^*} \mathbf{E}f'$$

Theorem [Biere et al. TACAS 1999]

Let  $f$  be an ECTL formula.  $M \models \mathbf{E}f \iff M \models_k \mathbf{E}f$  for some  $k \leq |M|$ .

## Other bounds for $k$

### ACTL & ECTL

- **ACTL** is a subset of CTL in which “**A...**” (resp. “**E...**”) sub-formulas occur only positively (resp. negatively) in each formula.  
e.g. **AG**( $p \rightarrow$  **AGAF** $q$ )
- **ECTL** is a subset of CTL in which “**E...**” (resp. “**A...**”) sub-formulas occur only positively (resp. negatively) in each formula.  
e.g. **EF**( $p \wedge$  **EFEG** $\neg q$ )
- ECTL is the dual subset of ACTL:  $\phi \in ECTL \iff \neg\phi \in ACTL$ .
- Many frequently-used LTL properties  $\neg f$  have equivalent ACTL representations  $\neg f'$  (e.g. **G**( $p \rightarrow$  **GF** $q$ ) wrt. **AG**( $p \rightarrow$  **AGAF** $q$ )):

$$M \not\models_{LTL} \neg f \Leftrightarrow M \not\models_{CTL^*} \mathbf{A}\neg f \Leftrightarrow M \not\models_{CTL^*} \mathbf{A}\neg f' \Leftrightarrow M \models_{CTL^*} \mathbf{E}f'$$

### Theorem [Biere et al. TACAS 1999]

Let  $f$  be an ECTL formula.  $M \models \mathbf{E}f \iff M \models_k \mathbf{E}f$  for some  $k \leq |M|$ .

# Other bounds for $k$ (cont)

## Theorem [Biere et al. TACAS 1999]

Let  $p$  be a Boolean formula and  $d$  be the **diameter** of  $M$ . Then  $M \models \mathbf{EF}p \iff M \models_k \mathbf{EF}p$  for some  $k \leq d$ .

## Theorem [Biere et al. TACAS 1999]

Let  $f$  be an ECTL formula and  $d$  be the **recurrence diameter** of  $M$ . Then  $M \models \mathbf{Ef} \iff M \models_k \mathbf{Ef}$  for some  $k \leq d$ .

# The diameter

## Definition: diameter

Given  $M$ , the **diameter** of  $M$  is the smallest integer  $d$  s.t. for every path  $s_0, \dots, s_{d+1}$  there exist a path  $t_0, \dots, t_l$  s.t.  $l \leq d$ ,  $t_0 = s_0$  and  $t_l = s_{d+1}$ .

- Intuition: if  $u$  is reachable from  $v$ , then there is a path from  $v$  to  $u$  of length  $d$  or less.

⇒ it is the maximum distance between two states in  $M$ .


# The diameter

## Definition: diameter

Given  $M$ , the **diameter** of  $M$  is the smallest integer  $d$  s.t. for every path  $s_0, \dots, s_{d+1}$  there exist a path  $t_0, \dots, t_l$  s.t.  $l \leq d$ ,  $t_0 = s_0$  and  $t_l = s_{d+1}$ .

- Intuition: if  $u$  is reachable from  $v$ , then there is a path from  $v$  to  $u$  of length  $d$  or less.

⇒ it is the maximum distance between two states in  $M$ .




# The diameter

## Definition: diameter

Given  $M$ , the **diameter** of  $M$  is the smallest integer  $d$  s.t. for every path  $s_0, \dots, s_{d+1}$  there exist a path  $t_0, \dots, t_l$  s.t.  $l \leq d$ ,  $t_0 = s_0$  and  $t_l = s_{d+1}$ .

- Intuition: if  $u$  is reachable from  $v$ , then there is a path from  $v$  to  $u$  of length  $d$  or less.

⇒ it is the maximum distance between two states in  $M$ .





# The diameter: computation

- $d$  is the smallest integer  $d$  which makes the following formula true:

$$\forall s_0, \dots, s_{d+1}. \exists t_0, \dots, t_d. \\ \underbrace{\bigwedge_{i=0}^d T(s_i, s_{i+1})}_{s_0, \dots, s_{d+1} \text{ is a path}} \rightarrow \underbrace{\left( t_0 = s_0 \wedge \bigwedge_{i=0}^{d-1} T(t_i, t_{i+1}) \wedge \bigvee_{i=0}^d t_i = s_{d+1} \right)}_{t_0, \dots, t_i \text{ is another path from } s_0 \text{ to } s_{d+1} \text{ for some } i}$$

- Quantified Boolean formula (QBF): much harder than NP-complete!

# The diameter: computation

- $d$  is the smallest integer  $d$  which makes the following formula true:


$$\forall s_0, \dots, s_{d+1}. \exists t_0, \dots, t_d. \\ \underbrace{\bigwedge_{i=0}^d T(s_i, s_{i+1})}_{s_0, \dots, s_{d+1} \text{ is a path}} \rightarrow \underbrace{\left( t_0 = s_0 \wedge \bigwedge_{i=0}^{d-1} T(t_i, t_{i+1}) \wedge \bigvee_{i=0}^d t_i = s_{d+1} \right)}_{t_0, \dots, t_i \text{ is another path from } s_0 \text{ to } s_{d+1} \text{ for some } i}$$

- Quantified Boolean formula (QBF): much harder than NP-complete!

# The recurrence diameter

## Definition: recurrence diameter

Given  $M$ , the **recurrence diameter** of  $M$  is the smallest integer  $d$  s.t. for every path  $s_0, \dots, s_{d+1}$  there exist  $j \leq d$  s.t.  $s_{d+1} = s_j$ .




- Intuition: the maximum length of a non-loop path

# The recurrence diameter

## Definition: recurrence diameter

Given  $M$ , the **recurrence diameter** of  $M$  is the smallest integer  $d$  s.t. for every path  $s_0, \dots, s_{d+1}$  there exist  $j \leq d$  s.t.  $s_{d+1} = s_j$ .



- Intuition: **the maximum length of a non-loop path**

# The recurrence diameter: computation

- $d$  is the smallest integer  $d$  which makes the following formula true:

$$\forall s_0, \dots, s_{d+1}. \underbrace{\bigwedge_{i=0}^d T(s_i, s_{i+1})}_{s_0, \dots, s_{d+1} \text{ is a path}} \rightarrow \underbrace{\bigvee_{i=0}^d s_i = s_{d+1}}_{s_0, \dots, s_{d+1} \text{ contains a cycle}}$$

- Validity problem: coNP-complete (solvable by SAT).
- Possibly much longer than the diameter!

# The recurrence diameter: computation

- $d$  is the smallest integer  $d$  which makes the following formula true:

$$\forall s_0, \dots, s_{d+1}. \underbrace{\bigwedge_{i=0}^d T(s_i, s_{i+1})}_{s_0, \dots, s_{d+1} \text{ is a path}} \rightarrow \underbrace{\bigvee_{i=0}^d s_i = s_{d+1}}_{s_0, \dots, s_{d+1} \text{ contains a cycle}}$$


- Validity problem: coNP-complete (solvable by SAT).
- Possibly much longer than the diameter!

# The recurrence diameter: computation

- $d$  is the smallest integer  $d$  which makes the following formula true:

$$\forall s_0, \dots, s_{d+1} \cdot \underbrace{\bigwedge_{i=0}^d T(s_i, s_{i+1})}_{s_0, \dots, s_{d+1} \text{ is a path}} \rightarrow \underbrace{\bigvee_{i=0}^d s_i = s_{d+1}}_{s_0, \dots, s_{d+1} \text{ contains a cycle}}$$

- Validity problem: coNP-complete (solvable by SAT).
- Possibly much longer than the diameter!



# Outline

- 1 Motivations
- 2 Background on SAT Solving
- 3 Bounded Model Checking: an example
- 4 Bounded Model Checking
- 5 Computing upper bounds for  $k$
- 6 Inductive reasoning on invariants (aka "K-Induction")**
- 7 Exercises



# Inductive Reasoning on Invariants

Invariant: "**AG***Good*", *Good* being a Boolean formula

- (i) If all the initial states are good,
  - (ii) and if from good states we only go to good states
- ⇒ then we can conclude that the system is correct for all reachable states.

# Inductive Reasoning on Invariants

Invariant: "**AG***Good*", *Good* being a Boolean formula

- (i) If all the initial states are good,
  - (ii) and if from good states we only go to good states
- ⇒ then we can conclude that the system is correct for all reachable states.

# Inductive Reasoning on Invariants

Invariant: "**AG***Good*", *Good* being a Boolean formula

- (i) If all the initial states are good,
- (ii) and if from good states we only go to good states

⇒ then we can conclude that the system is correct for all reachable states.

# Inductive Reasoning on Invariants

Invariant: "**AG***Good*", *Good* being a Boolean formula

- (i) If all the initial states are good,
  - (ii) and if from good states we only go to good states
- ⇒ then we can conclude that the system is correct for all reachable states.

# SAT-based Inductive Reasoning on Invariants

(i) If all the initial states are good

- $I(s^0) \rightarrow \text{Good}(s^0)$  is valid (i.e. its negation is unsatisfiable)

(ii) if from good states we only go to good states

- $(\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \rightarrow \text{Good}(s^{k+1})$  is valid  
(i.e. its negation is unsatisfiable)

then we can conclude that the system is correct for all reachable states.

⇒ Check for the (un)satisfiability of the Boolean formulas:

$$\begin{aligned} & (I(s^0) \wedge \neg \text{Good}(s^0)); \\ & (\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \wedge \neg \text{Good}(s^{k+1}) \end{aligned}$$

# SAT-based Inductive Reasoning on Invariants

(i) If all the initial states are good

- $I(s^0) \rightarrow \text{Good}(s^0)$  is valid (i.e. its negation is unsatisfiable)

(ii) if from good states we only go to good states

- $(\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \rightarrow \text{Good}(s^{k+1})$  is valid  
(i.e. its negation is unsatisfiable)

then we can conclude that the **system is correct for all reachable states**.

⇒ Check for the (un)satisfiability of the Boolean formulas:

$$\begin{aligned} & (I(s^0) \wedge \neg \text{Good}(s^0)); \\ & (\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \wedge \neg \text{Good}(s^{k+1}) \end{aligned}$$

# SAT-based Inductive Reasoning on Invariants

(i) If all the initial states are good

- $I(s^0) \rightarrow \text{Good}(s^0)$  is valid (i.e. its negation is unsatisfiable)

(ii) if from good states we only go to good states

- $(\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \rightarrow \text{Good}(s^{k+1})$  is valid  
(i.e. its negation is unsatisfiable)


then we can conclude that the **system is correct for all reachable states**.

⇒ Check for the (un)satisfiability of the Boolean formulas:

$$\begin{aligned} & (I(s^0) \wedge \neg \text{Good}(s^0)); \\ & (\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \wedge \neg \text{Good}(s^{k+1}) \end{aligned}$$

# Strengthening of Invariants


- Problem: Induction may fail because of unreachable states:
  - if  $(Good(s^k) \wedge R(s^k, s^{k+1})) \rightarrow Good(s^{k+1})$  is not valid, this does not mean that the property does not hold
  - both  $s^k$  and  $s^{k+1}$  might be unreachable






# Strengthening of Invariants

- Problem: Induction may fail because of unreachable states:
  - if  $(Good(s^k) \wedge R(s^k, s^{k+1})) \rightarrow Good(s^{k+1})$  is not valid, this does not mean that the property does not hold
  - both  $s^k$  and  $s^{k+1}$  might be unreachable



# Strengthening of Invariants

- Problem: Induction may fail because of unreachable states:
  - if  $(Good(s^k) \wedge R(s^k, s^{k+1})) \rightarrow Good(s^{k+1})$  is not valid, this does not mean that the property does not hold
  - both  $s^k$  and  $s^{k+1}$  might be unreachable




# Strengthening of Invariants [cont.]

Solution:

- increase the depth of induction

$$(Good(s^k) \wedge R(s^k, s^{k+1}) \wedge Good(s^{k+1}) \wedge R(s^{k+1}, s^{k+2})) \rightarrow Good(s^{k+2})$$




- force loop freedom with  $\neg(s^i = s^j)$  for every  $i \neq j$

# Strengthening of Invariants [cont.]

Solution:

- increase the depth of induction

$$(Good(s^k) \wedge R(s^k, s^{k+1}) \wedge Good(s^{k+1}) \wedge R(s^{k+1}, s^{k+2})) \rightarrow Good(s^{k+2})$$



- force loop freedom with  $\neg(s^i = s^j)$  for every  $i \neq j$

# Strengthening of Invariants [cont.]

⇒ Check for the unsatisfiability of the Boolean formulas:

$$\begin{aligned}
 &I(s^0) \wedge \neg \text{Good}(s^0); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \wedge \neg \text{Good}(s^{k+1}) \wedge \neg(s^k = s^{k+1}); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1}) \wedge \text{Good}(s^{k+1}) \wedge R(s^{k+1}, s^{k+2})) \wedge \neg \text{Good}(s^{k+2}) \\
 &\wedge \neg(s^k = s^{k+1}) \wedge \neg(s^k = s^{k+2}) \wedge \neg(s^{k+1} = s^{k+2}); \\
 &\dots
 \end{aligned}$$

- repeat for increasing values of the gap 1, 2, 3, 4, ...
- **intuition**: increasingly tighten the constraint for “spurious” counterexamples: a spurious counterexample must be a chain  $s_{k-n}, \dots, s_k$  of **unreachable** and **different** states s.t.  $\neg \text{Good}(s_k)$  and  $T(s_i, s_{i+1}), \forall i$ .
- dual to bounded model checking

# Strengthening of Invariants [cont.]

⇒ Check for the unsatisfiability of the Boolean formulas:

$$\begin{aligned}
 &I(s^0) \wedge \neg \text{Good}(s^0); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \wedge \neg \text{Good}(s^{k+1}) \wedge \neg(s^k = s^{k+1}); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1}) \wedge \text{Good}(s^{k+1}) \wedge R(s^{k+1}, s^{k+2})) \wedge \neg \text{Good}(s^{k+2}) \\
 &\wedge \neg(s^k = s^{k+1}) \wedge \neg(s^k = s^{k+2}) \wedge \neg(s^{k+1} = s^{k+2}); \\
 &\dots
 \end{aligned}$$

- repeat for increasing values of the gap 1, 2, 3, 4, ....
- **intuition**: increasingly tighten the constraint for “spurious” counterexamples: a spurious counterexample must be a chain  $s_{k-n}, \dots, s_k$  of **unreachable** and **different** states s.t.  $\neg \text{Good}(s_k)$  and  $T(s_i, s_{i+1}), \forall i$ .
- dual to bounded model checking

# Strengthening of Invariants [cont.]

⇒ Check for the unsatisfiability of the Boolean formulas:

$$\begin{aligned}
 &I(s^0) \wedge \neg \text{Good}(s^0); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \wedge \neg \text{Good}(s^{k+1}) \wedge \neg(s^k = s^{k+1}); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1}) \wedge \text{Good}(s^{k+1}) \wedge R(s^{k+1}, s^{k+2})) \wedge \neg \text{Good}(s^{k+2}) \\
 &\wedge \neg(s^k = s^{k+1}) \wedge \neg(s^k = s^{k+2}) \wedge \neg(s^{k+1} = s^{k+2}); \\
 &\dots
 \end{aligned}$$

- repeat for increasing values of the gap 1, 2, 3, 4, ...
- **intuition**: increasingly tighten the constraint for “spurious” counterexamples: a spurious counterexample must be a chain  $s_{k-n}, \dots, s_k$  of **unreachable** and **different** states s.t.  $\neg \text{Good}(s_k)$  and  $T(s_i, s_{i+1}), \forall i$ .
- dual to bounded model checking

# Strengthening of Invariants [cont.]

⇒ Check for the unsatisfiability of the Boolean formulas:

$$\begin{aligned}
 &I(s^0) \wedge \neg \text{Good}(s^0); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1})) \wedge \neg \text{Good}(s^{k+1}) \wedge \neg(s^k = s^{k+1}); \\
 &(\text{Good}(s^k) \wedge R(s^k, s^{k+1}) \wedge \text{Good}(s^{k+1}) \wedge R(s^{k+1}, s^{k+2})) \wedge \neg \text{Good}(s^{k+2}) \\
 &\wedge \neg(s^k = s^{k+1}) \wedge \neg(s^k = s^{k+2}) \wedge \neg(s^{k+1} = s^{k+2}); \\
 &\dots
 \end{aligned}$$

- repeat for increasing values of the gap 1, 2, 3, 4, ...
- **intuition**: increasingly tighten the constraint for “spurious” counterexamples: a spurious counterexample must be a chain  $s_{k-n}, \dots, s_k$  of **unreachable** and **different** states s.t.  $\neg \text{Good}(s_k)$  and  $T(s_i, s_{i+1}), \forall i$ .
- dual to bounded model checking



# Example: a correct 3-bit shift register

- System  $M$ :

- $I(x) := (\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
- $R(x, x') := ((x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0))$

- Property:  $\mathbf{AG} \neg x[0]$

# Example: a correct 3-bit shift register

- System  $M$ :
  - $I(x) := (\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
  - $R(x, x') := ((x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0))$
- Property:  $\mathbf{AG} \neg x[0]$

# Example: a correct 3-bit shift register

- System  $M$ :
  - $I(x) := (\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
  - $R(x, x') := ((x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0))$
- Property:  $\text{AG} \neg x[0]$

## Example: a correct 3-bit shift register

- System  $M$ :
  - $I(x) := (\neg x[0] \wedge \neg x[1] \wedge \neg x[2])$
  - $R(x, x') := ((x'[0] \leftrightarrow x[1]) \wedge (x'[1] \leftrightarrow x[2]) \wedge (x'[2] \leftrightarrow 0))$
- Property: **AG** $\neg x[0]$

## Example: a correct 3-bit shift register [cont.]

● Init:  $((\neg x^0[0] \wedge \neg x^0[1] \wedge \neg x^0[2]) \wedge x^0[0]) \implies \text{unsat}$

● Step 1:

$$\left( \begin{array}{l} (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0))) \\ \wedge x^{k+1}[0] \end{array} \right) \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2]))$$

$\implies$  (partly by unit-propagation)

$$\text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & x^k[1], & x^k[2], \\ x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \end{array} \right\}$$

$\implies$  not proved

### Remark

Both  $\{\neg x^k[0], x^k[1], x^k[2]\}$  and  $\{x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2]\}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

- Init:  $((\neg x^0[0] \wedge \neg x^0[1] \wedge \neg x^0[2]) \wedge x^0[0]) \implies \text{unsat}$
- Step 1:

$$\left( \begin{array}{l} (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0))) \\ \wedge x^{k+1}[0] \end{array} \right) \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2]))$$

$\implies$  (partly by unit-propagation)

$$\text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & x^k[1], & x^k[2], \\ x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \end{array} \right\}$$

$\implies$  not proved

### Remark

Both  $\{\neg x^k[0], x^k[1], x^k[2]\}$  and  $\{x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2]\}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

- Init:  $((\neg x^0[0] \wedge \neg x^0[1] \wedge \neg x^0[2]) \wedge x^0[0]) \implies \text{unsat}$
- Step 1:

$$\left( \begin{array}{l} (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0))) \\ \wedge x^{k+1}[0] \end{array} \right) \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2]))$$

$\implies$  (partly by unit-propagation)

$$\text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & x^k[1], & x^k[2], \\ x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \end{array} \right\}$$

$\implies$  not proved

### Remark

Both  $\{\neg x^k[0], x^k[1], x^k[2]\}$  and  $\{x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2]\}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

- Init:  $((\neg x^0[0] \wedge \neg x^0[1] \wedge \neg x^0[2]) \wedge x^0[0]) \implies \text{unsat}$
- Step 1:

$$\left( \begin{array}{l} (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0))) \\ \wedge x^{k+1}[0] \end{array} \right) \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2]))$$

$\implies$  (partly by unit-propagation)

$$\text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & x^k[1], & x^k[2], \\ x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \end{array} \right\}$$

$\implies$  not proved

### Remark

Both  $\{\neg x^k[0], x^k[1], x^k[2]\}$  and  $\{x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2]\}$  are non-reachable.



## Example: a correct 3-bit shift register [cont.]

- Init:  $((\neg x^0[0] \wedge \neg x^0[1] \wedge \neg x^0[2]) \wedge x^0[0]) \implies \text{unsat}$
- Step 1:

$$\left( \begin{array}{l} (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0))) \\ \wedge x^{k+1}[0] \end{array} \right) \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2]))$$

$\implies$  (partly by unit-propagation)

$$\text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & x^k[1], & x^k[2], \\ x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \end{array} \right\}$$

$\implies$  not proved

### Remark

Both  $\{\neg x^k[0], x^k[1], x^k[2]\}$  and  $\{x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2]\}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

### • Step 2:

$$\begin{aligned}
 & \left( \begin{aligned} & (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0)) \wedge \\ & \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \end{aligned} \right) \\
 & \wedge x^{k+2}[0] \\
 & \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2]))
 \end{aligned}$$

$$\Rightarrow \text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & \neg x^k[1], & x^k[2] \\ \neg x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \\ x^{k+2}[0], & \neg x^{k+2}[1], & \neg x^{k+2}[2] \end{array} \right\}$$

$\Rightarrow$  not proved

### Remark

$\{ \neg x^k[0], \neg x^k[1], x^k[2] \}$ ,  $\{ \neg x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2] \}$ , and  $\{ x^{k+2}[0], \neg x^{k+2}[1], \neg x^{k+2}[2] \}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

### • Step 2:

$$\left( \begin{array}{l} (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0)) \wedge \\ \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \wedge \\ ) \wedge x^{k+2}[0] \end{array} \right)$$

$$\wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2]))$$

$$\wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2]))$$

$$\wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2]))$$

$$\Rightarrow \text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & \neg x^k[1], & x^k[2] \\ \neg x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \\ x^{k+2}[0], & \neg x^{k+2}[1], & \neg x^{k+2}[2] \end{array} \right\}$$

$\Rightarrow$  not proved

### Remark

$\{ \neg x^k[0], \neg x^k[1], x^k[2] \}$ ,  $\{ \neg x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2] \}$ , and  $\{ x^{k+2}[0], \neg x^{k+2}[1], \neg x^{k+2}[2] \}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

### • Step 2:

$$\left( \begin{array}{l} (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0)) \wedge \\ \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \wedge \\ ) \wedge x^{k+2}[0] \end{array} \right)$$

$$\wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2]))$$

$$\wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2]))$$

$$\wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2]))$$

$$\Rightarrow \text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & \neg x^k[1], & x^k[2] \\ \neg x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \\ x^{k+2}[0], & \neg x^{k+2}[1], & \neg x^{k+2}[2] \end{array} \right\}$$

$\Rightarrow$  not proved

### Remark

$\{ \neg x^k[0], \neg x^k[1], x^k[2] \}$ ,  $\{ \neg x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2] \}$ , and  $\{ x^{k+2}[0], \neg x^{k+2}[1], \neg x^{k+2}[2] \}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

### • Step 2:

$$\begin{aligned}
 & \left( \begin{aligned} & (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0)) \wedge \\ & \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \end{aligned} \right) \\
 & \wedge x^{k+2}[0] \\
 & \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2]))
 \end{aligned}$$

$$\Rightarrow \text{sat: } \left\{ \begin{array}{lll} \neg x^k[0], & \neg x^k[1], & x^k[2] \\ \neg x^{k+1}[0], & x^{k+1}[1], & \neg x^{k+1}[2] \\ x^{k+2}[0], & \neg x^{k+2}[1], & \neg x^{k+2}[2] \end{array} \right\}$$

$\Rightarrow$  not proved

### Remark

$\{ \neg x^k[0], \neg x^k[1], x^k[2] \}$ ,  $\{ \neg x^{k+1}[0], x^{k+1}[1], \neg x^{k+1}[2] \}$ , and  $\{ x^{k+2}[0], \neg x^{k+2}[1], \neg x^{k+2}[2] \}$  are non-reachable.

## Example: a correct 3-bit shift register [cont.]

### • Step 3:

$$\begin{aligned}
 & \left( \begin{aligned}
 & (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0))) \wedge \\
 & \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \wedge \\
 & \neg x^{k+2}[0] \wedge ((x^{k+3}[0] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[2]) \wedge (x^{k+3}[2] \leftrightarrow 0)) \\
 & ) \wedge x^{k+3}[0]
 \end{aligned} \right) \\
 & \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^k[0]) \wedge (x^{k+3}[1] \leftrightarrow x^k[1]) \wedge (x^{k+3}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+2}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+2}[2]))
 \end{aligned}$$

$\Rightarrow$  (unit-propagation)  $\{x^{k+3}[0], x^{k+2}[1], x^{k+1}[2]\}$

$\Rightarrow$  unsat

$\Rightarrow$  proved!

# Example: a correct 3-bit shift register [cont.]

## • Step 3:

$$\begin{aligned}
 & \left( \begin{aligned}
 & (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0)) \wedge \\
 & \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \wedge \\
 & \neg x^{k+2}[0] \wedge ((x^{k+3}[0] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[2]) \wedge (x^{k+3}[2] \leftrightarrow 0)) \\
 & ) \wedge x^{k+3}[0]
 \end{aligned} \right) \\
 & \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^k[0]) \wedge (x^{k+3}[1] \leftrightarrow x^k[1]) \wedge (x^{k+3}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+2}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+2}[2]))
 \end{aligned}$$

$\Rightarrow$  (unit-propagation)  $\{x^{k+3}[0], x^{k+2}[1], x^{k+1}[2]\}$

$\Rightarrow$  unsat

$\Rightarrow$  proved!

## Example: a correct 3-bit shift register [cont.]

### • Step 3:

$$\begin{aligned}
 & \left( \begin{aligned}
 & (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0)) \wedge \\
 & \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \wedge \\
 & \neg x^{k+2}[0] \wedge ((x^{k+3}[0] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[2]) \wedge (x^{k+3}[2] \leftrightarrow 0)) \\
 & ) \wedge x^{k+3}[0]
 \end{aligned} \right) \\
 & \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^k[0]) \wedge (x^{k+3}[1] \leftrightarrow x^k[1]) \wedge (x^{k+3}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+2}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+2}[2]))
 \end{aligned}$$

$\Rightarrow$  (unit-propagation)  $\{x^{k+3}[0], x^{k+2}[1], x^{k+1}[2]\}$

$\Rightarrow$  unsat

$\Rightarrow$  proved!



# Example: a correct 3-bit shift register [cont.]

## ● Step 3:

$$\begin{aligned}
 & \left( \begin{aligned}
 & (\neg x^k[0] \wedge ((x^{k+1}[0] \leftrightarrow x^k[1]) \wedge (x^{k+1}[1] \leftrightarrow x^k[2]) \wedge (x^{k+1}[2] \leftrightarrow 0))) \wedge \\
 & \neg x^{k+1}[0] \wedge ((x^{k+2}[0] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[2]) \wedge (x^{k+2}[2] \leftrightarrow 0)) \wedge \\
 & \neg x^{k+2}[0] \wedge ((x^{k+3}[0] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[2]) \wedge (x^{k+3}[2] \leftrightarrow 0)) \\
 & ) \wedge x^{k+3}[0]
 \end{aligned} \right) \\
 & \wedge \neg((x^{k+1}[0] \leftrightarrow x^k[0]) \wedge (x^{k+1}[1] \leftrightarrow x^k[1]) \wedge (x^{k+1}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^k[0]) \wedge (x^{k+2}[1] \leftrightarrow x^k[1]) \wedge (x^{k+2}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^k[0]) \wedge (x^{k+3}[1] \leftrightarrow x^k[1]) \wedge (x^{k+3}[2] \leftrightarrow x^k[2])) \\
 & \wedge \neg((x^{k+2}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+2}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+2}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+1}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+1}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+1}[2])) \\
 & \wedge \neg((x^{k+3}[0] \leftrightarrow x^{k+2}[0]) \wedge (x^{k+3}[1] \leftrightarrow x^{k+2}[1]) \wedge (x^{k+3}[2] \leftrightarrow x^{k+2}[2]))
 \end{aligned}$$

⇒ (unit-propagation)  $\{x^{k+3}[0], x^{k+2}[1], x^{k+1}[2]\}$

⇒ unsat

⇒ **proved!**

# Mixed BMC & Inductive reasoning [Sheeran et al. 2000]

$$\begin{aligned}
 Base_n &:= I(\mathbf{s}_0) \wedge \bigwedge_{i=0}^{n-1} (R(\mathbf{s}_i, \mathbf{s}_{i+1}) \wedge \varphi(\mathbf{s}_i)) \wedge \neg\varphi(\mathbf{s}_n) \\
 Step_n &:= \bigwedge_{i=0}^n (R(\mathbf{s}_i, \mathbf{s}_{i+1}) \wedge \varphi(\mathbf{s}_i)) \wedge \neg\varphi(\mathbf{s}_{n+1}) \\
 Unique_n &:= \bigwedge_{0 \leq i \leq j \leq n} \neg(\mathbf{s}_i = \mathbf{s}_{j+1})
 \end{aligned}$$

## Algorithm

```

1.  function CHECK_PROPERTY ( $I, R, \varphi$ )
2.      for  $n := 0, 1, 2, 3, \dots$  do
3.          if (DPLL( $Base_n$ ) == SAT)
4.              then return PROPERTY_VIOLATED;
5.          else if (DPLL( $Step_n \wedge Unique_n$ ) == UNSAT)
6.              then return PROPERTY_VERIFIED;
7.      end for;
  
```

⇒ reuses previous search if DPLL is incremental!!

# Mixed BMC & Inductive reasoning [Sheeran et al. 2000]

$$\begin{aligned}
 Base_n &:= I(\mathbf{s}_0) \wedge \bigwedge_{i=0}^{n-1} (R(\mathbf{s}_i, \mathbf{s}_{i+1}) \wedge \varphi(\mathbf{s}_i)) \wedge \neg \varphi(\mathbf{s}_n) \\
 Step_n &:= \bigwedge_{i=0}^n (R(\mathbf{s}_i, \mathbf{s}_{i+1}) \wedge \varphi(\mathbf{s}_i)) \wedge \neg \varphi(\mathbf{s}_{n+1}) \\
 Unique_n &:= \bigwedge_{0 \leq i \leq j \leq n} \neg(\mathbf{s}_i = \mathbf{s}_{j+1})
 \end{aligned}$$

## Algorithm

```

1.  function CHECK_PROPERTY ( $I, R, \varphi$ )
2.      for  $n := 0, 1, 2, 3, \dots$  do
3.          if (DPLL( $Base_n$ ) == SAT)
4.              then return PROPERTY_VIOLATED;
5.          else if (DPLL( $Step_n \wedge Unique_n$ ) == UNSAT)
6.              then return PROPERTY_VERIFIED;
7.      end for;
  
```

⇒ reuses previous search if DPLL is incremental!!

# Mixed BMC & Inductive reasoning [Sheeran et al. 2000]

$$\begin{aligned}
 Base_n &:= I(\mathbf{s}_0) \wedge \bigwedge_{i=0}^{n-1} (R(\mathbf{s}_i, \mathbf{s}_{i+1}) \wedge \varphi(\mathbf{s}_i)) \wedge \neg \varphi(\mathbf{s}_n) \\
 Step_n &:= \bigwedge_{i=0}^n (R(\mathbf{s}_i, \mathbf{s}_{i+1}) \wedge \varphi(\mathbf{s}_i)) \wedge \neg \varphi(\mathbf{s}_{n+1}) \\
 Unique_n &:= \bigwedge_{0 \leq i \leq j \leq n} \neg(\mathbf{s}_i = \mathbf{s}_{j+1})
 \end{aligned}$$

## Algorithm

```

1.  function CHECK_PROPERTY ( $I, R, \varphi$ )
2.      for  $n := 0, 1, 2, 3, \dots$  do
3.          if (DPLL( $Base_n$ ) == SAT)
4.              then return PROPERTY_VIOLATED;
5.          else if (DPLL( $Step_n \wedge Unique_n$ ) == UNSAT)
6.              then return PROPERTY_VERIFIED;
7.      end for;
  
```

⇒ reuses previous search if DPLL is incremental!!

# Other Successful SAT-based (UNbounded) MC Techniques

- Counter-example guided abstraction refinement (CEGAR)  
[Clarke et al. CAV 2002]
- Interpolant-based MC  
[Mc Millan, TACAS 2005]
- IC3/PDR  
[Bradley, VMCAI 2011]
- ...

For a survey see e.g.

[Amla et al., CHARME 2005, Prasad et al. STTT 2005].


# Outline

- 1 Motivations
- 2 Background on SAT Solving
- 3 Bounded Model Checking: an example
- 4 Bounded Model Checking
- 5 Computing upper bounds for  $k$
- 6 Inductive reasoning on invariants (aka “K-Induction”)
- 7 Exercises**


## Ex: CDCL SAT Solving

Which of the following figures may correspond to a modern DPLL 1st-UIP backjumping step?


(a)



(b)




(c)




# Ex: CDCL SAT Solving

Which of the following figures may correspond to a modern DPLL 1st-UIP backjumping step?


(a)



(b)



(c)



[ Solution: The correct answer is (a). (b) represents standard chronological backtracking, whilst (c) is nonsense. ]



## Ex: Bounded Model Checking

Given the symbolic representation of a FSM  $M$ , expressed in terms of the two Boolean formulas:  $I(x, y) \stackrel{\text{def}}{=} \neg(x \vee \neg y)$ ,  $T(x, y, x', y') \stackrel{\text{def}}{=} (x' \leftrightarrow (x \leftrightarrow \neg y)) \wedge (y' \leftrightarrow \neg y)$ , and the LTL property:  $\varphi \stackrel{\text{def}}{=} \neg \mathbf{F}(x \wedge y)$ ,

1. Write a Boolean formula whose solutions (if any) represent executions of  $M$  of length 2 which violate  $\varphi$ .

[ Solution: The question corresponds to the Bounded Model Checking problem  $M \models_2 \mathbf{E F} f$ , s.t.  $f(x, y) \stackrel{\text{def}}{=} (x \wedge y)$ . Thus we have:

$$\begin{array}{ll}
 \neg(x_0 \vee \neg y_0) & \wedge \quad // I(x_0, y_0) \wedge \\
 (x_1 \leftrightarrow (x_0 \leftrightarrow \neg y_0)) \wedge (y_1 \leftrightarrow \neg y_0) & \wedge \quad // T(x_0, y_0, x_1, y_1) \wedge \\
 (x_2 \leftrightarrow (x_1 \leftrightarrow \neg y_1)) \wedge (y_2 \leftrightarrow \neg y_1) & \wedge \quad // T(x_1, y_1, x_2, y_2) \wedge \\
 ((x_0 \wedge y_0) & \vee \quad // (f(x_0, y_0) \vee \\
 (x_1 \wedge y_1) & \vee \quad // f(x_1, y_1) \vee \\
 (x_2 \wedge y_2)) & // f(x_2, y_2))
 \end{array}$$

2. Is there a solution? If yes, find the corresponding execution; if no, show why.

[ Solution: Yes:  $\{\neg x_0, y_0, x_1, \neg y_1, x_2, y_2\}$ , corresponding to the execution:  
 $(0, 1) \rightarrow (1, 0) \rightarrow (1, 1)$  ]

## Ex: Bounded Model Checking

Given the symbolic representation of a FSM  $M$ , expressed in terms of the two Boolean formulas:  $I(x, y) \stackrel{\text{def}}{=} \neg(x \vee \neg y)$ ,  $T(x, y, x', y') \stackrel{\text{def}}{=} (x' \leftrightarrow (x \leftrightarrow \neg y)) \wedge (y' \leftrightarrow \neg y)$ , and the LTL property:  $\varphi \stackrel{\text{def}}{=} \neg \mathbf{F}(x \wedge y)$ ,

1. Write a Boolean formula whose solutions (if any) represent executions of  $M$  of length 2 which violate  $\varphi$ .

[ Solution: The question corresponds to the Bounded Model Checking problem  $M \models_2 \mathbf{E F} f$ , s.t.  $f(x, y) \stackrel{\text{def}}{=} (x \wedge y)$ . Thus we have:

$$\begin{array}{ll}
 \neg(x_0 \vee \neg y_0) & \wedge \quad // I(x_0, y_0) \wedge \\
 (x_1 \leftrightarrow (x_0 \leftrightarrow \neg y_0)) \wedge (y_1 \leftrightarrow \neg y_0) & \wedge \quad // T(x_0, y_0, x_1, y_1) \wedge \\
 (x_2 \leftrightarrow (x_1 \leftrightarrow \neg y_1)) \wedge (y_2 \leftrightarrow \neg y_1) & \wedge \quad // T(x_1, y_1, x_2, y_2) \wedge \\
 ((x_0 \wedge y_0) & \vee \quad // (f(x_0, y_0) \vee \\
 (x_1 \wedge y_1) & \vee \quad // f(x_1, y_1) \vee \\
 (x_2 \wedge y_2)) & // f(x_2, y_2))
 \end{array}$$

]

2. Is there a solution? If yes, find the corresponding execution; if no, show why.

[ Solution: Yes:  $\{\neg x_0, y_0, x_1, \neg y_1, x_2, y_2\}$ , corresponding to the execution:  
 $(0, 1) \rightarrow (1, 0) \rightarrow (1, 1)$  ]

## Ex: Bounded Model Checking

Given the symbolic representation of a FSM  $M$ , expressed in terms of the two Boolean formulas:  $I(x, y) \stackrel{\text{def}}{=} \neg(x \vee \neg y)$ ,  $T(x, y, x', y') \stackrel{\text{def}}{=} (x' \leftrightarrow (x \leftrightarrow \neg y)) \wedge (y' \leftrightarrow \neg y)$ , and the LTL property:  $\varphi \stackrel{\text{def}}{=} \neg \mathbf{F}(x \wedge y)$ ,

1. Write a Boolean formula whose solutions (if any) represent executions of  $M$  of length 2 which violate  $\varphi$ .

[ Solution: The question corresponds to the Bounded Model Checking problem

$M \models_2 \mathbf{E F} f$ , s.t.  $f(x, y) \stackrel{\text{def}}{=} (x \wedge y)$ . Thus we have:

$$\begin{array}{ll}
 \neg(x_0 \vee \neg y_0) & \wedge \quad // I(x_0, y_0) \wedge \\
 (x_1 \leftrightarrow (x_0 \leftrightarrow \neg y_0)) \wedge (y_1 \leftrightarrow \neg y_0) & \wedge \quad // T(x_0, y_0, x_1, y_1) \wedge \\
 (x_2 \leftrightarrow (x_1 \leftrightarrow \neg y_1)) \wedge (y_2 \leftrightarrow \neg y_1) & \wedge \quad // T(x_1, y_1, x_2, y_2) \wedge \\
 ((x_0 \wedge y_0) & \vee \quad // (f(x_0, y_0) \vee \\
 (x_1 \wedge y_1) & \vee \quad // f(x_1, y_1) \vee \\
 (x_2 \wedge y_2)) & // f(x_2, y_2))
 \end{array}$$

]

2. Is there a solution? If yes, find the corresponding execution; if no, show why.

[ Solution: Yes:  $\{\neg x_0, y_0, x_1, \neg y_1, x_2, y_2\}$ , corresponding to the execution:

$(0, 1) \rightarrow (1, 0) \rightarrow (1, 1)$  ]

# Ex: Bounded Model Checking

Given the symbolic representation of a FSM  $M$ , expressed in terms of the two Boolean formulas:  $I(x, y) \stackrel{\text{def}}{=} \neg(x \vee \neg y)$ ,  $T(x, y, x', y') \stackrel{\text{def}}{=} (x' \leftrightarrow (x \leftrightarrow \neg y)) \wedge (y' \leftrightarrow \neg y)$ , and the LTL property:  $\varphi \stackrel{\text{def}}{=} \neg \mathbf{F}(x \wedge y)$ ,

1. Write a Boolean formula whose solutions (if any) represent executions of  $M$  of length 2 which violate  $\varphi$ .

[ Solution: The question corresponds to the Bounded Model Checking problem

$M \models_2 \mathbf{E F} f$ , s.t.  $f(x, y) \stackrel{\text{def}}{=} (x \wedge y)$ . Thus we have:

$$\begin{array}{ll}
 \neg(x_0 \vee \neg y_0) & \wedge \quad // I(x_0, y_0) \wedge \\
 (x_1 \leftrightarrow (x_0 \leftrightarrow \neg y_0)) \wedge (y_1 \leftrightarrow \neg y_0) & \wedge \quad // T(x_0, y_0, x_1, y_1) \wedge \\
 (x_2 \leftrightarrow (x_1 \leftrightarrow \neg y_1)) \wedge (y_2 \leftrightarrow \neg y_1) & \wedge \quad // T(x_1, y_1, x_2, y_2) \wedge \\
 ((x_0 \wedge y_0) & \vee \quad // (f(x_0, y_0) \vee \\
 (x_1 \wedge y_1) & \vee \quad // f(x_1, y_1) \vee \\
 (x_2 \wedge y_2)) & // f(x_2, y_2))
 \end{array}$$

]

2. Is there a solution? If yes, find the corresponding execution; if no, show why.

[ Solution: Yes:  $\{\neg x_0, y_0, x_1, \neg y_1, x_2, y_2\}$ , corresponding to the execution:

$(0, 1) \rightarrow (1, 0) \rightarrow (1, 1)$  ]

## Ex: Bounded Model Checking

Given the symbolic representation of a FSM  $M$ , expressed in terms of the two Boolean formulas:  $I(x, y) \stackrel{\text{def}}{=} \neg(x \vee \neg y)$ ,  $T(x, y, x', y') \stackrel{\text{def}}{=} (x' \leftrightarrow (x \leftrightarrow \neg y)) \wedge (y' \leftrightarrow \neg y)$ , and the LTL property:  $\varphi \stackrel{\text{def}}{=} \neg \mathbf{F}(x \wedge y)$ ,

1. Write a Boolean formula whose solutions (if any) represent executions of  $M$  of length 2 which violate  $\varphi$ .

[ Solution: The question corresponds to the Bounded Model Checking problem

$M \models_2 \mathbf{E F} f$ , s.t.  $f(x, y) \stackrel{\text{def}}{=} (x \wedge y)$ . Thus we have:

$$\begin{array}{ll}
 \neg(x_0 \vee \neg y_0) & \wedge \quad // \quad I(x_0, y_0) \wedge \\
 (x_1 \leftrightarrow (x_0 \leftrightarrow \neg y_0)) \wedge (y_1 \leftrightarrow \neg y_0) & \wedge \quad // \quad T(x_0, y_0, x_1, y_1) \wedge \\
 (x_2 \leftrightarrow (x_1 \leftrightarrow \neg y_1)) \wedge (y_2 \leftrightarrow \neg y_1) & \wedge \quad // \quad T(x_1, y_1, x_2, y_2) \wedge \\
 ((x_0 \wedge y_0) & \vee \quad // \quad (f(x_0, y_0) \vee \\
 (x_1 \wedge y_1) & \vee \quad // \quad f(x_1, y_1) \vee \\
 (x_2 \wedge y_2)) & // \quad f(x_2, y_2))
 \end{array}$$

]

2. Is there a solution? If yes, find the corresponding execution; if no, show why.

[ Solution: Yes:  $\{\neg x_0, y_0, x_1, \neg y_1, x_2, y_2\}$ , corresponding to the execution:

$(0, 1) \rightarrow (1, 0) \rightarrow (1, 1)$  ]

# Ex: Bounded Model Checking

3. From the solutions to question #1 and #2 we can conclude that:

- (a)  $M \models \varphi$
- (b)  $M \not\models \varphi$
- (c) we can conclude nothing.

[ Solution: b) ]

4. What are the diameter and the recurrence diameter of this system?

[ Solution:

# Ex: Bounded Model Checking

3. From the solutions to question #1 and #2 we can conclude that:

- (a)  $M \models \varphi$
- (b)  $M \not\models \varphi$
- (c) we can conclude nothing.

[ Solution: b ) ]

4. What are the diameter and the recurrence diameter of this system?

[ Solution:

# Ex: Bounded Model Checking

3. From the solutions to question #1 and #2 we can conclude that:

- (a)  $M \models \varphi$
- (b)  $M \not\models \varphi$
- (c) we can conclude nothing.

[ Solution: b) ]

4. What are the diameter and the recurrence diameter of this system?

[ Solution:



# Ex: Bounded Model Checking

3. From the solutions to question #1 and #2 we can conclude that:

(a)  $M \models \varphi$

(b)  $M \not\models \varphi$

(c) we can conclude nothing.

[ Solution: b) ]

4. What are the diameter and the recurrence diameter of this system?

[ Solution:

]

# Ex: Bounded Model Checking

3. From the solutions to question #1 and #2 we can conclude that:

- (a)  $M \models \varphi$
- (b)  $M \not\models \varphi$
- (c) we can conclude nothing.

[ Solution: b) ]

4. What are the diameter and the recurrence diameter of this system?

[ Solution:

]

# Ex: Bounded Model Checking


3. From the solutions to question #1 and #2 we can conclude that:

- (a)  $M \models \varphi$
- (b)  $M \not\models \varphi$
- (c) we can conclude nothing.

[ Solution: b) ]

4. What are the diameter and the recurrence diameter of this system?

[ Solution:



]