

Captura de archivos ignorados

The screenshot shows the Visual Studio Code interface. The Explorer sidebar on the left displays the file structure of a project named 'PreEntrega2_TorresFelipe'. The file list includes '.vs', 'css', 'Fonts', 'html', 'images', '.gitignore', 'index.html', 'Pruebalgnorados', and 'readme.md'. The '.gitignore' file is selected, and its content is displayed in the main editor area. The content of the '.gitignore' file is:

```
.gitignore
1 PruebaIgnorados
```

The terminal window at the bottom shows the output of a git push command. The output indicates that the push was successful and provides a link to create a pull request on GitHub.

```
$ git push origin PreEntregable2_V1
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0
remote:
remote: Create a pull request for 'PreEntregable2_V1' on GitHub by visiting:
remote:   https://github.com/Felo550/CorcheaAcademy/pull/new/PreEntregable2_V1
remote:
To https://github.com/Felo550/CorcheaAcademy.git
 * [new branch]      PreEntregable2_V1 -> PreEntregable2_V1

filip@FELOPC MINGW64 /f/CursosVirtuales/CODERHOUSE_FullStack Developer/PreEntrega2_TorresFelipe (master)
$
```

The status bar at the bottom right shows the current line and column (Ln 1, Col 16), the encoding (UTF-8), the line ending (CRLF), and the file type (Ignore).

Captura de diferentes Branchs (rojo:local /Azul: github)

The screenshot shows the Visual Studio Code interface with a dark theme. The Explorer sidebar on the left shows the file structure of a project named 'PREENTREGA2_TORRESFEL...'. The main editor area displays the 'index.html' file. A 'Select a branch or tag to checkout' dialog is open in the center, showing the following options:

- + Create new branch...
- + Create new branch from...
- 🔗 Checkout detached...
- 🔗 master 8b6fb918 (red arrow pointing left)
- 🔗 PreEntregable2_V1 e1adf3e8 (red arrow pointing left)
- 🔗 origin/master Remote branch at 8b6fb918 (blue arrow pointing right)
- 🔗 origin/PreEntregable2_V1 Remote branch at e1adf3e8 (blue arrow pointing right)

The terminal window at the bottom shows the output of a 'git push' command:

```
$ git push origin PreEntregable2_V1
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0
remote:
remote: Create a pull request for 'PreEntregable2_V1' on GitHub by visiting:
remote:   https://github.com/Felo550/CorcheaAcademy/pull/new/PreEntregable2_V1
remote:
To https://github.com/Felo550/CorcheaAcademy.git
 * [new branch]      PreEntregable2_V1 -> PreEntregable2_V1

filiip@FELOPC MINGW64 /f/CursosVirtuales/CODERHOUSE_FullStack Developer/PreEntrega2_TorresFelipe (master)
$
```

The status bar at the bottom indicates the current branch is 'master' and the file encoding is UTF-8.



