

# An introduction to femtolisp

(Content not checked for grammar and spelling errors)

Eduardo Costa

Vernon Sipple



# Preface

Femto is a tiny Emacs clone, originally derived from a minimalist editor called Atto. Although built upon the C Atto codebase, Femto can be customized using the femtolisp Scheme dialect.

The fundamental paradigm of Emacs is that it rests on a small core, but can be extended and customized through the Lisp programming language.

Instead of requiring from the programmer a compile, build, test and fix cycle — Lisp offers a Read, Eval, Print Loop (REPL).

1. **Read.** The REPL reads a symbolic expression such as `(+ 42 13 4)` from a text terminal. The symbolic expression — `sexpr` — always has the form: `(operation  $a_1$   $a_2 \dots a_n$ )`, where  $a_1, a_2 \dots a_n$  are the arguments of the operation.
2. **Eval.** The compiler translates the symbolic expression to machine language, then executes the generated code and calculates the corresponding value.
3. **Print.** The value produced in step 2 is printed.
4. **Loop.** The REPL returns to step 1.

Since Lisp is usually compiled, it is much faster than interpreted languages. However, to facilitate portability, femtolisp does not generate native code, but compiles symbolic expressions to a virtual machine language. As a consequence of this choice, femtolisp is not as fast as other Lisp dialects, such as sbcl and Racket. Notwithstanding, it is about four times faster than Python and forty times faster than Tiny Scheme.

The REPL approach enables fast prototyping of extensions as each idea can be tested individually on the command line inside the editor with an immediate result check.

For historical reasons, the reference GNU Emacs implementation uses a specialised version of lisp known as elisp. However, the elisp dialect is not standard lisp, being used only by the GNU Emacs editor and its derivatives.

Femtolisp was chosen as the extension language for FemtoEmacs for the following reasons:

1. Femtolisp is open source.
2. Femtolisp is small and written in C.
3. After loading the `r5rs.scm` library provided in the femtoemacs distribution, the user can bridge the syntactic gap between femtolisp and Scheme. In the majority of situations, the `r5rs.scm` library is compatible with the standard Scheme dialect. This means that one can use classical Scheme tutorials to learn how to configure and customize femtoemacs. The Structure and Interpretation of Computer Programs is the most popular of these tutorials. Of course, you can use the content of the present text to the same effect.
4. Femtolisp is fast.

# Chapter 1

## Shell

Nia, a Greek young woman, has an account on a well known social network. She visits her friends' postings on a daily basis, and when she finds an interesting picture or video, she presses the *Like*-button. However, when she needs to discuss her upcoming holidays on the Saba Island with her Argentinian boyfriend, she uses the live chat box. After all, hitting buttons and icons offers only a very limited interaction tool, and does not produce a highly detailed level of information that permits the answering of questions and making of statements.

Using a chat service needs to be very easy and fun, otherwise all those teenage friends of Nia's would be doing something else. I am telling you this, because there are two ways of commanding a computer. The first is called Graphical User Interface (GUI) and consists of moving the cursor with a mouse or other pointing device and clicking over a menu option or an icon, such as the *Like* button. As previously mentioned, a Graphical User Interface often does not generate adequate information for making a request to the computer. In addition, finding the right object to press can become difficult in a labyrinth of menu options.

The other method of interacting with the computer is known as Shell and is similar to a chat with one's own machine.

In your computer, there is a giant program, called the operating system, which controls all peripherals that the machine uses to stay connected with the external world: pointing devices, keyboard, video terminal, robots, cameras, solid state drives, pen drives, and other peripherals.

In a Shell interface, Nia issues written instructions that the operating system answers by fulfilling the assigned tasks. The language that Nia uses to chat with the operating system is called *Bourne-again shell*, or *bash* for short. This language has commands to go through folders, browser files, create new directories, copy objects from one place to the other, configure

the machine, install applications, change the permissions of a file, create groups to organize users and devices, etc. When accessing the operating system through a text-based terminal, a shell language is the main way of executing programs and doing work on a computer.

The shell interface derives its name from the fact that it acts like a shell surrounding all other programs being run, and controlling everything the machine performs.

To make a long story short, it is much faster to complete tasks using a shell than with graphical applications, icons, menus and mouse. Another benefit of the shell is that you can gain access to many more commands and scripts than with a Graphical User Interface.

In order not to scare off the feeble-minded, many operating systems hide access to the text terminal. In some distribution of Linux, you need to maintain the `[Alt]` key down, then press the `[F2]` key to open a dialog box, where you must type the name of the terminal you want to open. If you are really lucky, you may find the icon of the terminal on the toolbar.



If the way of opening the text terminal is not obvious, you should ask for help from a student majoring in Computer Science. You can teach her Russian, Sanskrit, Javanese or Ancient Greek, as a compensation for the time that she will spend explaining how to start a terminal in OS X or Linux. If you are afraid of paying for a few minutes of tutorial about the Bourne-again shell with hundred hours of classes on Russian, don't worry! The CS major will give up after barely starting the section on the alphabet. After all, Philology is much more difficult than Computer Engineering. For details, read the tale "The man who could speak Javanese" by Lima Barreto.

**The prompt.** The shell prompt is where one types commands. The prompt has different aspects, depending on the configuration of the terminal. In Nia's machine, it looks something like this:

```
~$ _
```

Files are stored in folders. Typically, the prompt shows the folder where the user is currently working.

The main duty of the operating system is to maintain the contents of the mass storage devices in a tree structure of files and folders. Folders are also called *directories*, and like physical folders or cabinets, they organize files.

A folder can be put inside another folder. In a given machine, there is a folder reserved for duties carried out by the administrator. This special folder is called home or personal directory.

Besides the administrator, a machine can have other rightful users, each with a personal folder. For instance, Nia's folder on her Mac OS X has the `/Users/nia` path. You will learn a more formal definition of path later on.

**pwd #** The `pwd` command informs the user's position in the file tree. A folder can be placed inside another folder. For example, in a Macintosh, Nia's home folder is inside the `/Users` directory.

One uses a path to identify a nest of folders. In a path, a subfolder is separated from the parent folder by a slash bar. If one needs to know the current folder, there is the `pwd` command.

```
~$ pwd          # shows the current folder. Enter
/Users/nia
```

When Nia issues a command, she may add comments to it, so her boyfriend that does not know Bourne-again shell (bash) can understand what is going on and learn something in the process. Comments are prefixed with the `#` hash char, as you can see in the above chat. Therefore, when the computer sees a `#` hash char, it ignores everything to the end of the line.

**mkdir wrk #** creates a `wrk` folder inside the current directory, where `wrk` can be replaced with any other name. For instance, if Nia is inside her home directory, `mkdir wrk` creates a folder with the `/Users/nia/wrk` path.

**cd wrk #** One can use the `cd <folder name>` commands to enter the named folder. The `cd ..` command takes Nia to the parent of the current directory. Thanks to the `cd` command, one can navigate through the tree of folders and directories.

**Tab.** If you want to go to a given directory, type part of the directory path, and then press Tab. The shell will complete the folder name for you.

**Home directory.** One can use a `~` tilde to represent the home directory. For instance, `cd ~` will send Nia to her personal folder. The `cd $HOME` has the same effect, i.e., it places Nia inside her personal directory.

**echo #** One can use the `echo` command to print something. Therefore, `echo $HOME` prints the contents of the `HOME` environment variable on the terminal.

Environment variables store the terminal configuration. For instance, the `HOME` variable contains the user's personal directory identifier. One needs to prefix the environment variable with the `$` char to access its contents. Therefore, `echo $HOME` displays the contents of the `HOME` variable.

The instruction `echo "Work Space" > readme.txt` creates a `readme.txt` text file and writes the "Work Space" string there. If the `readme.txt` file exists, this command supersedes it.

The command `echo "Shell practice" >> readme.txt` appends a string to a text file. It does not erase the previous content of the `readme.txt` file. Of course, you should replace the string or the file name, as necessity dictates.

Below you will find an extended example of a chat between Nia and the OS X operating system.

```
~$ mkdir wrk      # creates a work space folder      Enter
~$ cd wrk        # transfers action to the wrk file  Enter
~/wrk$ echo "* Work space" > readme.txt              Enter
~/wrk$ echo "This folder is used" >> readme.txt      Enter
~/wrk$ echo "to practice the bash" >> readme.txt    Enter
~/wrk$ echo "commands and queries." >> readme.txt   Enter
~/wrk$ ls        # list files in current folder.    Enter
readme.txt
~/wrk$ cat readme.txt # shows the file contents.    Enter

* Work space
This folder is used
to practice the bash
commands and queries.
```

**ls #** By convention, a file name has two parts, the id and the extension. The id is separated from the extension by a dot. The `ls` command lists all files and subfolders present in the current folder. The `ls *.txt` prints only files with the `.txt` extension.

**Wild card.** The `*.txt` pattern is called wild card. In a wild card, the `*` asterix matches any sequence of chars, while the `?` interrogation mark matches a single char.



**ls -lia \*.txt** # prints detailed information about the .txt files, like date of creation, size, etc.

```
~/wrk$ ls -la 
```

```
total 8
drwxr-xr-x    3 edu500ac  staff    102 Sep 18 16:29 .
drwxr-xr-x+ 321 edu500ac  staff   10914 Sep 18 14:40 ..
-rw-r--r--    1 edu500ac  staff     74 Sep 18 16:30 readme.txt
```

Files starting with a dot are called hidden files, due to the fact that the **ls** command does not normally show them. All the same, the **ls -a** option includes the hidden files in the listing.

In the preceding examples, the first character in each list entry is either a dash (-) or the letter d. A dash (-) indicates that the file is a regular file. The letter d indicates that the entry is a folder. A special file type that might appear in a **ls -la** command is the symlink. It begins with a lowercase l, and points to another location in the file system. Directly after the file classification comes the permissions, represented by the following letters:

- r – read permission.
- w – write permission.
- x – execute permission.

**cp readme.txt lire.txt** # makes a copy of a file. You can copy a whole directory with the **-rf** options, as shown below.

```
~/wrk$ ls
readme.txt
~/wrk$ cp readme.txt lire.fr
~/wrk$ ls
lire.fr  readme.txt
~/wrk$ cd ..
~$ cp -rf wrk wsp
~$ cd wsp/
~/wsp$ ls
lire.fr  readme.txt
```

**rm lire.txt #** removes a file. The **-rf** option removes a whole folder.

```
~/wsp$ ls
lire.frreadme.txt
~/wsp$ rm lire.fr
~/wsp$ ls
readme.txt
~/wsp$ cd ..
~$ ls wrk
lire.frreadme.txt
~$ rm -rf wrk
~$ ls wrk
ls: wrk: No such file or directory
```

**mv wsp wrp #** changes the name of a file or folder, or even permits the moving of a file or folder to another location.

```
~$ mv wsp wrk
~$ cd wrk
~/wrk$ ls
readme.txt
~/wrk$ mv readme.txt read.me
~/wrk$ ls
read.me
~/wrk$ cp read.me wrk-readme.txt
~/wrk$ ls
read.mewrk-readme.txt
~/wrk$ mv wrk-readme.txt ~/Documents/
~/wrk$ ls
read.me
~/wrk$ cat ~/Documents/wrk-readme.txt
Work space
This folder is used
to practice the bash
commands and queries.
```

**Copy to pen drive.** In most Linux distributions, the pen drive is seen as a folder inside the **/media/nia/** directory, where you should replace **nia** with your user name. In the Macintosh, the pen drive appears at the **/Volume/** folder. The commands **cp**, **rm** and **ls** see the pen drive as a normal folder.

## 1.1 Package managers

A package manager is a tool that works with core libraries to handle, even though poorly, the installation and removal of software. Each operating system has its own package manager. Even if you stick to a single operating system, you will have to deal with many package managers and different philosophies concerning software installation.

I will teach you how to use three installation tools: apt-get, homebrew and git clone. However, this tutorial will not completely cover the many subtleties involved while you make your machine usable. You will really need the help of that girl who is majoring in Computer Engineering. Tell her that, if she teaches you how to configure apt-get install, you will teach her the ancient Javanese script.

## 1.2 ncurses

In the jargon of tech-oriented people, a person who uses computers is called *user*, but engineers prefer the term *looser*, as the latter is an affectionate way of calling those individuals who need to work with a computer, but in fact have no skills. By the way, *looser* is a loser who can't spell "loser".

Computers need a tool to make communication with users possible. That tool is called User Interface, or UI for short. There are two kinds of User Interface.

In this chapter, you are learning how to use a text terminal. Therefore, you already know, what a text based User Interface or UI is. After all, you are operating the shell, and the shell is a User Interface.

A graphical user interface allows people to interact with computers through graphical icons and visual indicators, instead of typed commands or keyboard shortcuts. GUIs were introduced when vendors perceived that non tech-savvy customers have difficulty in dealing with modern digital machines, that require a formal language for accepting commands.

Considering that people frequently converse with each other through the Chat Box, you could type commands in a text box of a Graphical User Interface. However, a text terminal offers sharper and crisp characters through the use of a specialized User Interface called ncurses. You will find ncurses at the following address:

<http://ftp.gnu.org/gnu/ncurses/>

The distribution package is called archive, since it contains many files stored together in a compact way, that you will need to decompress and extract.

A popular tool for decompressing an archive is `gunzip` that accepts files with the `*.gz` extension. Extraction is performed by the `tar` application.

```
~$ tar xfvz ncurses-6.0.tar.gz
```

The `z` option calls `gunzip` to decompress the `ncurses-6.0.tar.gz` archive into an `ncurses-6.0.tar` file. The `x` option indicates that you want to extract the component files of the `ncurses-6.0.tar` intermediate file and place them into the `ncurses-6.0/` directory.

The Macintosh differs from Linux machines in that, when you perform the download of the `ncurses-6.0.tar.gz` archive, the Apple operating system decompresses the distribution automatically, so that you will end up with the tar file in the `~/Downloads` folder. Then you can transfer it to your home directory and perform the extraction without the need for the `z` option.

```
~$ cd ~ # makes sure that you are in the home folder
~$ cp ~/Downloads/ncurses-6.0.tar .
~$ tar xfv ncurses-6.0.tar
```

The `tar` tool creates an `ncurses-6.0` folder containing all files of the program that implement the ncurses text based User Interface.

The `ncurses-6.0` directory contains many files in the C computer language. In order to become usable, these files must be compiled into a set of libraries containing instructions written in a language that the computer understands. You do not need any knowledge of C to perform the translation to machine language. All instructions in the batch job for performing the compilation are written in `Makefile`. However, `Makefile` on its own is not sufficient. For the operation to be successful, the system needs also to know which computer you are using. The `configure` contains the program that analyzes your hardware.

```
~$ cd ncurses-6.0/
~/ncurses-6.0$ ./configure --enable-widec
~/ncurses-6.0$ make
~/ncurses-6.0$ sudo make install
```

The second line of the above listing configures `ncurses`, i.e., discovers details about your machine. The `--enable-widec` option customizes the text terminal for chars with diacritics, so you can write words like *café* and *façade*.

The second line of the ncurses installation listing compiles the User Interface. The third line performs the very installation.

The installation requires that the system copy files to the `/usr/local/` folder. However, you must give special permission for this operation to be

performed, otherwise the possibility remains open for a virus to make similar copies in critical folders. The `sudo` command informs the machine that you are a superuser. To avoid being tricked by a virus or an unauthorized user, the machine asks for the password, and if you type it correctly, the system installs ncurses.

## 1.3 Linux.

Use `apt-get` to install the latest version of `libncursesw5-dev`. Since repositories are usually old, download a recent distribution of ncurses, and build it:

```
~$ sudo apt-get install libncursesw5-dev
~$ wget http://ftp.gnu.org/gnu/ncurses/ncurses-6.0.tar.gz
~$ tar xfvz ncurses-6.0.tar.gz
~$ cd ncurses-6.0/
~/ncurses-6.0$ ./configure --enable-widec
~/ncurses-6.0$ make
~/ncurses-6.0$ sudo make install
```

After installing ncursesw, you need to clone the sources for the editor. Here is how to perform this job:

```
~$ git clone https://github.com/FemtoEmacs/Femto-Emacs
```

After cloning the editor, enter the source directory and make the files.

```
~/Femto-Emacs$ cd ~/Femto-Emacs/
~/Femto-Emacs$ make
```

Installation is achieved by copying the compiled files to `/usr/local/bin/` and the customization files to your home directory.

```
~/Femto-Emacs/femto$ sudo cp femto /usr/local/bin/
~/Femto-Emacs/femto$ sudo cp femto.boot /usr/local/bin/
~/Femto-Emacs/femto$ cp init.lsp $HOME/
~/Femto-Emacs/femto$ cp aliases.scm $HOME/
```

I have to say this again: An installation task has so many details that, unless you are an engineer yourself, ask for help from a computer expert.

## 1.4 MAC OS-X.

In order to install programs that depend on resources present in a text terminal, you need to install the `libncursesw.a` library. You can use your browser to download it. Immediately after the download is complete, it will be placed in the `~/Downloads/` folder.

It is advisable to transfer it to your home directory or, even better, to a source folder. Let us assume that Nia has chosen the home directory as her installation folder.

```
~$ cp ~/Download\ncurses-6.0.tar.gz .
```

Remember that the dot indicates the current directory. For instance, the `./femto` command means: execute the `femto` file present in the current directory. The fact is that Unix and Unix like systems are unable to find a command, except when it is installed in a pre-defined search path or when the file path is completely specified.

Unpack and make the distribution archive as shown below:

```
~$ tar xfvz ncurses-6.0.tar.gz
~$ cd ncurses-6.0/
~/ncurses-6.0$ ./configure --enable-widc
~/ncurses-6.0$ make
~/ncurses-6.0$ sudo make install
```

Femto assumes that `libncursesw.a` resides in the following folder:

```
/usr/local/lib/libncursesw.a
```

Therefore, copy the `libncursesw.a` file to `/usr/local/lib/` as shown below:

```
~/ $ cd ncurses-6.0
~/ncurses-6.0$ cd lib
~/ncurses-6.0/lib$ sudo cp libncursesw.a /usr/local/lib/
```

After installing `libncursesw`, enter the folder `Femto-Emacs/` and build the editor for Macintosh:

```
~/ $ cd ~/Femto-Emacs/
~/Femto-Emacs$ make -f Makefile.macosx
```

## Chapter 2

### The man who knew Javanese

In a doughnut shop the other day, I was telling my friend Castro how I tricked respectable members of the community not only to make a living, but also rise to a higher social position.

For instance, while I was living in Manaus, I had to hide my professional degree to win over the clients' trust. People, who never would come to a physician's practice or lawyer firm, flocked to my wizard and fortune teller's office. So, I was telling him this story.

My friend listened to me in silence, enraptured by my words, appreciating the account of picaresque adventures, that seemed as though they had been extracted from the Story of Gil Blas. During a conversational pause, after both drying our glasses, he remarked randomly:

"You've been living an extremely funny life, Castelo!"

"It's the only kind of life worth living...I could not imagine myself having a single occupation. It is extremely boring to go to work in the morning, come back in the evening, read the paper on the sitting room armchair, and go to bed at eleven fifteen. Don't you think? In fact, I can't imagine how I have been able to stand my job at the Consulate!"

"Yes, the existence in the civil service must be tedious. But that's not what amazes me. I wonder how have you been able to pass through so many adventures here, in this monotonous and bureaucratic Brazil."

"You will be surprized, my dear Castro, to learn that even here, in this country, one can write quite interesting pages on a memoir. Believe it or not, I was even a teacher of Javanese!"

"When was that? Here, after you retired from your job at the Consulate?"

"No, it was a long time ago. What's more, I got my job at the Consulate as a consequence of my teaching duties."

"That story I want to hear! In the mean time, let us have a few more drinks?"

“Yes, I accept another glass of beer.”

We sent for another bottle, filled our glasses and I continued:

“I had just arrived in Rio and I was literally broke. My life was consumed fleeing from one boarding house to the other on rent day, without idea of how to earn a living.

Of course, I didn’t have money to pay for breakfast. Even so, I was in a café, but only to read through the job openings section of the newspaper left on a table for the customers’ convenience. Then, I came across the following advertisement:

“Needed: A JAVANESE TEACHER. Interviews at, etc.”

So, I told myself: “This certainly is a position where you won’t find many applicants. If only I could comprehend a few words of Javanese, I’d apply.”

I left the coffee shop in a waking dream, where imagined myself in a brave new world, as a Javanese teacher, earning more than just a decent living, driving my car, without unhappy meetings with debt collectors.

When I awoke from my daydream, I found myself in front of the public library. I went in and gave my cap to a person that looked like an attendant, since I knew about the custom of the upper class to leave their hats at the hat stand. I did not have a hat, so I left my cap. Of course, I never saw my cap again.

I didn’t really know what book I was going to ask for. In any case, this was irrelevant, because my name was nationally blacklisted, since I never returned the books to the highschool library. Nevertheless, I climbed the stairs to browse an Encyclopedia, volume J and look up the entry on Java and the Javanese dialect. In a few minutes, I knew that Java was a big island of the Greater Sunda Islands, at the time a Dutch colony.

I also learned that Javanese is an agglutinative language of the Malayo-Polynesian family. It has a noteworthy literature written in characters derived from the old Hindu alphabet. The Javanese alphabet is a modern variant of the Kawi script, a Brahmic script developed in Java around the ninth century. In the past, it was widely used in religious literature, which was written on palm-leaves. This kind of manuscript came to be known as lontar. The Encyclopedia gave a list of books for further reading and I had no doubt of what I needed to do, and consulted one of them. I made a copy of the alphabet and its phonetic transcription and left. I wandered the streets walking aimlessly chewing over the letters as they were gum.

Hieroglyphs danced in my head. From time to time, I would look at my notes. Then I would go into Tijuca park, and wrote those strange looking characters with a stick in the sand to keep them vividly in my memory and accustom my hands in writing them.

I would enter my building late at night in an attempt to avoid coming



across the landlord, who could ask for the rent. Even in my bedroom I kept chewing over my Malayan A-B-C. My determination was such that I knew it all by heart with the sunrise. I convinced myself that Malay was the easiest language in the world, and that Javanese was as close to Malay as Portuguese to Spanish, which simply is not true. The reality is that Malay is not so easy, and it is as far from Javanese as English from German.

I tried to leave home as early in the morning as possible to avoid my landlord. But to my dismay, it was not early enough, for I couldn't escape meeting the man in charge of asking for the room rent.

"Mr. Castelo, when are you going to pay your rent bill?"

I answered him with the most heart filled hope:

"Soon... Wait just a little longer... Be patient... I will be appointed as a Javanese teacher and..." At that moment, the man cut in into my stuttering excuses.

"What in hell is that, Mr. Castelo?"

I enjoyed the amusement and proceeded to invest in the man's patriotism:

"It's a language from the distant reaches of Timor. Do you know where it is?"

Oh, simple minded fellow! The man forgot all about my overdue bill and told me in a strong accent from Portugal:

"I am not sure, Mr. Castelo. If I remember rightly, Portugal has or had a colony with that name close to Macau. But do you really know such a thing, Mr. Castelo?"

Incentivated by this initial result from my Javanese studies, I started to fulfil the requisite of the advertisement. I decided to offer my services as a teacher of that transoceanic idiom. I composed the letter of acceptance, then I went to the newspaper office to left the document there. With that, I returned to the library to resume my Javanese studies. I didn't make any progress that day. In fact, I felt that the alphabet was the only knowledge required from a Javanese teacher. Perhaps, I was overly indulged with the bibliography and history of the language that I was going to teach.

Two days later I received an answer to my correspondence, in which was stated that I should go to the residence of a certain Dr. Manuel Feliciano Soares Albernaz, Baron of Jacuecanga, Conde de Bonfim street. I can't recall the house number. Remember that I was extremely focused on Malayan studies to register the details for history, as for example the house number. But don't be fooled into thinking that my lack of memory for particularities, such as house numbers or names of historical figures, renders the story as a figment of my imagination. More than one scholar told me that the name of a certain Prince Kalunga is Aji Saka. There you are.

Besides the alphabet, I knew the names of a few authors. I also could

say, “How are you?”, and knew a few grammar rules. All this knowledge was supported on around twenty words.

You can’t imagine how hard I tried to get the money for the bus fare! Javanese is easier than loaning money, you can be sure. Failing to raise the necessary funds for the trip from one neighborhood to the other, I walked. Of course, I arrived in a state of dripping sweat. With a motherly affection, the old mango trees standing in front of the baron’s house received, harbored and cooled me down with the fresh air of shade. It was the first time in all my life that I felt sympathy for Nature.

The house was huge, but ill kept. However, it was that way more from despondency and weariness of living than from its owner’s poverty. The walls hadn’t been painted for years, and what was left of their coats was peeling away. The eaves around the edges of the roof were made up of old fashioned tiles, some of which were missing, creating an effect of decaying false teeth. In the garden, the flatsedge and other weeds had expelled the begonias. However, the more resistant crotons continued to bloom with their purplish leaves.

I knocked. It was awhile before an aged African Negro came to the door. His white beard and hair gave him an appearance of fatigue and suffering.

In the parlor there was a row of gold framed portraits, which showed bearded gentlemen and profiles of sweet ladies holding huge fans and dresses that looked like balloons ready to ascend in the air. From among the many items, to which the dust gave more antiquity and respect, what impressed me most was a big, beautiful, porcelain vase from China or India, I never learned to differentiate their origins. Anyway, the purity of the material, its fragility, the naiveté of its contour and its dim lustre that appeared to be as the moonlight suggested to me that the artwork was fashioned by the hands of a dreaming child for the enchantment of old men’s disillusioned eyes.

As I described above, I was inspecting the furniture, while waiting for the master of the house. He delayed quite a long time. Then, he came. Full of respect, I watched the elderly man approach haltingly, a large handkerchief in his hand, inhaling an old fashioned peppermint essence venerably.

Although I wasn’t sure he was my pupil to be, I felt that it would have been wicked to deceive the aged gentleman, whose ancient aspect made me think of something august, sacred. I hesitated for a moment. Should I invent an excuse and leave? But finally decided to wait and see.

“I am,” I said to break the ice, “The Javanese teacher you asked for.”

“Sit down,” answered the old gentleman. “Are you from Rio?”

“No, Sir. I’m from Canavieiras.”

“What?” He said. “Speak louder, my hearing is impaired.”

“I am from Canavieiras,” I repeated putting emphasis upon each word.

“Where did you go to school?”

“In the city of Salvador, in the great state of Bahia.”

“And where did you learn Javanese?” he asked with that dodgedness so common among the elderly.

I was not expecting for such a question, but I made up a lie about a Javanese father, who had come to Bahia on a freighter. Liking what he saw, my phony father decided to settle there in Canavieiras as a fisherman. He married, prospered and taught me Javanese.

“Did he believe you?” asked my friend who up to that moment had remained silent. “And your features?”

“I’m not very different from a Javanese” I contested. “With my thick, straight, black hair and tanned skin, I could very well pass for a Indonesian halfbreed. You know very well that among us there are all kinds of nationalities – Indians, Malayans, Tahitians, Madagascans, Guanches<sup>1</sup> and even Goths. Our people are an amalgamation of races and types to make the whole world envy us.”

“O.K.” My friend agreed. “Please, go on.”

“The old gentleman,” I resumed, “listened intently and examined my physique for a long while. Then he concluded that I was indeed the son of a Malayan, and asked me softly:

“Well, do you really want to teach me Javanese?”

The answer came unwittingly: “Yes.”

“You must be astounded,” added the Baron of Jacuecanga, “that I, at my age, should still have a wont for learning.”

“I’m not surprized at all. There have been noteworthy examples of late learners, as Socrates, who started flute at seventy.”

“What I really want, Mr...?”

“Castelo,” I supplied.

“What I really want, Mr. Castelo, is to fulfill a family pledge. I don’t know whether you realize that I’m the grandson of State Secretary Albernaz, the same man who accompanied Peter, the first emperor of Brazil, into exile, after his abdication. When he came back from London, the Secretary brought with him a book written in a strange language, onto which he bestowed great value.

The old volume had been given to my grandfather by an Indian or a Siamese sailor in return for what received favor I do not know.

Before he died, my grandfather called my father to his deathbed and told him the story that follows.

---

<sup>1</sup>Guanches were the Berber aboriginal inhabitants of the Canary Islands.

“Son, do you see this book here, written in Javanese? Well, the person who gave it to me believed that it would bring its owner happiness and deliverance from evil. I don’t know whether you should believe in such a legend or not. In any case, keep the book, and if the good omens prophesized by the oriental wiseman come true, teach your son to read it, so that our family line should prosper.”

“My father,” proceeded the old baron, “didn’t take the story to heart. Nevertheless, he maintained the book in safe keeping. When he lay sick and suspected that the end of his life was near<sup>2</sup>, he gave it to me repeating the dying words of his own father.”

In the beginning, I paid little attention to the book. I threw it in a corner, and got on with life. I even forgot it existed. Lately, so many misfortunes have befallen me, that I remembered the old family heirloom. I must read and understand the book, if I want to preserve my last days from witnessing the total ruin of my posterity. Of course, to read the book, I need to master the Javanese language. There you have all of it.”

He became silent. I noticed his eyes glistened with tears. He wiped them discreetly and asked me if I would care to see the book. I gave a yes. He summoned the maid, passed her the instructions to find and fetch the book, while he told me how he had lost all his children, nephews and nieces. Only one married daughter remained alive. From her numerous offspring, only one son survived, a weak and infirm boy.

The book arrived, an old, large volume, presented in quarto bound in leather and printed in huge letters on yellowed paper.

Since the title page was missing, I was unable to determine the date of publication. Fortunately, the preface was written in English. There I read that the book contained the stories of a Prince Kalunga, a renowned writer.

I explained this entirety to the baron. Ignorant of the fact that I arrived at this deliverance of knowledge from the English preface, he was very impressed with my erudition on Javanese culture. I browsed the pages with the look of someone familiar with that language that most people would not be able to tell apart from Sanskrit or Hindi.

Before parting company, the baron and I agreed upon my fees and the class schedules. To fulfill my part in the contract, I should teach my old pupil to read the book in a year.

A few days later, I gave the gentleman the first private lesson, but the old man was not diligent, not even at my level of interest. At the end of the class, he could not distinguish one character of the abugida from the other,

---

<sup>2</sup>Before the Scholar among my readers accuse me of plagiarism, I avow that I am fluent in Ancient Greek, and the first book I read in my life was the Anabasis.

or trace the five first letters of the hanacaraka sequence.

Traditionally, the Javanese syllabary is taught through a poem of 4 verses narrating the myth of Aji Saka.

ᮊ ᮓ ᮒ ᮑ ᮓ ᮓ – There were two messengers

ᮓ ᮓ ᮒ ᮓ ᮓ ᮓ – with mutual hatred.

ᮓ ᮓ ᮒ ᮓ ᮓ ᮓ – One was as mighty as the other.

ᮓ ᮓ ᮓ ᮓ ᮓ ᮓ – Here are the corpses.

In the poem, each syllable is written with a different letter. After learning the first verse, the student has learned five letters. Five more letters are presented in each subsequent verse.

It took a whole month for the Baron of Jacuecanga to learn the first and second verse. What is worse, only one day was enough for him to forget everything. So, both teacher and student started a long cycle of learning and forgetting.

I think that the Baron's daughter and her husband didn't know anything about the book until they become curious of my activities in their home. When I explained the matter to them, they took it lightly. They laughed about the behavior of their elderly relative, said that he probably had dementia, and that learning languages could slow the progress of the disease.

You won't believe it, my dear Castro, but the son-in-law came to admire and respect the teacher of Javanese. He kept saying: "It is amazing how my father-in-law's tutor could grasp a culture so different from our own! Yet, he is so young. If I were as knowledgeable as he, I would be a scholar at Cambridge or at the Sorbonne.

The husband of Mrs. Maria da Gloria, that was the name of the Baron's daughter, was a judge, a powerful and well connected man. Even so, he never tired of showing his admiration for my knowledge of Javanese.

The Baron also seemed happy with me. But after two months he gave up learning the language. Instead of reading the book himself, he concluded that it would be enough to understand its contents in order to fulfill the pledge he made to his dying father. Certainly, the powerful spiritual forces behind the book would not be opposed to the humble request for the services of a translator. He would hear my rendition of the story of Aji Saka, avoiding the effort that his old brain was not in shape to bear.

You are certainly aware that even today I don't know Javanese. But as every learned man in this country, I had heard the story of King Aji Saka,

or Prince Kalunga, as Brazilians prefer to call the hero. In my rural village, at night, in my room illuminated by candles and kerosene lamps, my mother used to read a translation of the Indonesian legend into Latin until I would fall asleep. Therefore, it was not very difficult to patch together memories from my childhood, fill the gaps, and present the result to the old man as coming directly from the book. He would hear those myths in ecstasy, as though an angel were providing the rendition. And my reputation increased among the members of the Baron's family and its circle of acquaintances. The Baron raised my salary, and I started living an easy life.

An unexpected fact contributed to my prestige. The Baron received an inheritance from a Portuguese relative that he didn't even know existed. Of course, he assigned the happy event to the Javanese book. I myself almost believed that this was so.

As time went by, I stopped myself from feeling remorse and guilty due to my deceiving the naive man and his family. In any case, I was terrified at the prospect of coming across some horrible person that could speak the Javanese dialect. My terror increased when the Baron wrote a letter to the Viscount of Caruru suggesting my name for an international affairs career. I advanced every kind of objection to the idea. "I am very ugly, uncouth and gaunt. My knowledge of French is faulty. I am not elegant. I don't know the protocols."

He insisted: "Physical aspect doesn't matter, young man. Go ahead! Everybody speaks French, German and English. But only you know Javanese."

So, I went to the interview with the Viscount, who sent me to the Ministry of Foreign Affairs with more than one recommendation letter. After all, everybody wanted to have the honor of giving me a recommendation letter. I was a huge success when I arrived at the office of the director of fucking nothing<sup>3</sup>.

The director called all the department heads: "Look at this! The man knows Javaness. What a prodigy!"

The heads of various departments introduced me to clerks and amanuensis. One of these lesser officials of the Ministry gave me a look with more envy and hatred than admiration. But everybody else kept saying: "Do you really know Javanese? Is it difficult? I believe that nobody else speaks that language here."

The clerk who had looked at me with undeserved hatred approached the group of admirers and interrupted the applauses with a cold comment: "That is true, nobody knows Malay or Indonesian here. But I speak Kanak,

---

<sup>3</sup>A literal translation of the Portuguese acronym for ASPONE – Assessor de Porra Nenhuma.

a language of the New Caledonia. Do you know Kanak?

I told him I didn't and proceeded to the Minister's office.

The high authority got up, adjusted the glasses on his nose, and asked point blank: "So, do you speak Javanese?" My answer was a loud *yes*. He wanted to know where I learned the language. I told him about my Javanese father. The Minister was sincere and direct. "You can't go into the Diplomatic Service. Brazilian Diplomats must be blond with blue eyes. Of course, there is the affirmative action for blacks and indians. But although your skin is dark, you cannot apply, since you are Javanese, not Indian. We could send you to a consulate in Asia or Oceania, but I am afraid that there is no opening now. However, if a position appears, you will get it. Meanwhile, you will be attached directly to my Ministry. By the way, I want you to go to Basel sometime next year, in order to represent our country in a congress of Linguistics. Read the books of Hove-Iacque, Max Müller, and other good authors in the field."

Can you follow me? I didn't know Javanese and could barely ask for lunch in French or English, but have a good job, and would represent my country in a meeting of scholars!

The old Baron came to pass, and the book went to his son-in-law, with the intention that it be given to his grandson when the boy come to age. The deceased Baron also left me a sum in his will.

I cannot say that I didn't try to learn the Malayo-Polynesian languages, but to no avail. The effort of learning those languages is way out of my reach. Besides this, I had more pressing business to take care of: Eating well, dressing elegantly, and reading Comics.

Anyway, even if you don't read much, it is advisable to have shelves of books and many volumes of journals in your office. Therefore, I subscribed to the *Revue Anthropologique et Linguistique*, the *Proceeding of the English Oceanic Association*, and the *Archivio Glottologico Italiano*. Of course, subscribing to those scholarly journals without reading them did add anything to my learning of languages.

Yet, my reputation did not stop increasing. People who I met on the street would greet me with the comment:

"There goes the man who knows Javanese."

In book stores, grammarians often would consult me about the position of pronouns in the dialect spoken on the island of Sonda. Scholars sent me letters from all over the world and newspapers would write articles about me. On an occasion, I had to refuse a group of well to do young students who wanted to learn Javanese at any cost.

Do you remember that commerce paper where I found the advertisement? The editor asked me to write an article on the classical and modern Javanese

literature. I obliged.

“How could you, since you avow to be ignorant of the language, let alone the literature?” asked Castro.

“That was not very difficult. I started with a detailed description of the island of Java. Dictionaries and geography textbooks provided me with the necessary information. Then, I quoted American, German and French authors.”

“Did anybody ever put your knowledge in question?” My friend asked.

“Never, although I was almost caught out on a particular occasion. The police arrested an individual, a sailor, a brown fellow who spoke a strange language. They called a number of different interpreters, but to no avail. Finally the police got in touch with me, the Javanese scholar, with all the respect my position deserved. I delayed in attending the request, but in the end I could no longer escape the compromise. Fortunately, the man had been released, thanks to the intervention by the Dutch consul to whom the sailor could explain his case through the use of half a dozen or so Dutch words. The sailor was indeed Javanese.”

The moment finally arrived for my attending the congress. So, there I was on my way to Europe. It was marvelous! I attended to the opening ceremony and the invited paper presentations. The organizers registered me in the Tupi-Guarani section. After a couple of days at going from presentation to presentation, I concluded that the whole thing was not for me, and left for Paris. Before taking the train, however, I was careful enough to convince a journalist to publish my portrait and a short article about me. Thus, I had a way to prove that I was in Basel, not in Paris.

Eventually, I returned to Basel for the closing ceremony. The organizers of the congress assumed that my absence was due to their mistake of assigning me to the Guarani section. I accepted the apology, but I still was not able to write that treatise on Javanese that I promised them.

After the congress, I paid for the publication of German and Italian translations of the article from the Basel paper. The readers of these translations offered a banquet in my honor. The banquet was presided by Senator Gorot. My contribution cost me all the money the Baron left me in his will.

The money was well spent. After all, I became a celebrity, and after six months I was appointed Consul in Havana, where I lived for many years, in order to perfect my proficiency of the Polynesian languages.

“It is fantastic,” observed Castro, holding tightly to his glass of beer.

“Look! Do you know what I would like to be right now?”

“What?”

“A famous genetic or computer engineer. Let us go for it?”

“I am in.”



# Chapter 3

## Intallation

A text editor, like Emacs or femto, has three components:

1. A frontend that inserts characters into a buffer. A buffer is a memory region with an image of a text file. One can see the buffer as a representation of a scratch pad. As such, the frontend provides tools to insert keystrokes at the point indicated by a movable cursor.
2. Editing operations that save buffers as files, delete and insert text, move the cursor around, copy items from one place to another, etc.
3. A scripting language for customizing the editor.

There is a large choice of frontends. Some frontends work with a raster graphics image, which is a dot matrix data structure that represents a grid of pixels. There are also frontends that are specialized in showing letters and other characters via an appropriate display media. The latter sort of frontend is called text-based user interfaces, while the former is called graphical user interface, or GUI for short.

Text-based user interfaces are more confortable on the eyes, since they provide sharper and crisp alphabetical letters. On the other hand, GUI allows for font customization. At present, femtoemacs offers only ncurses, which is a text-based user interface. Therefore, download the most recent version from the distribution site: <https://www.gnu.org/software/ncurses/>



**MAC OS-X.** Unpack and make the distribution archive as shown below:

```
~$ tar xfvz ncurses-6.0.tar.gz
~$ cd ncurses-6.0/
~/ncurses-6.0$ ./configure --enable-widec
~/ncurses-6.0$ make
~/ncurses-6.0$ sudo make install
```

Femto assumes that `libncursesw.a` resides in the following folder:

```
/usr/local/lib/libncursesw.a
```

Therefore, copy the `libncursesw.a` file to `/usr/local/lib/` as shown below:

```
~/ $ cd ncurses-6.0
~/ncurses-6.0$ cd lib
~/ncurses-6.0/lib$ sudo cp libncursesw.a /usr/local/lib/
```

After installing `libncursesw`, enter the folder `Femto-Emacs/` and build the editor for Macintosh:

```
~/ $ cd ~/Femto-Emacs/
~/Femto-Emacs$ make -f Makefile.macosx
```

**Linux.** Use `apt-get` to install the latest version of `libncursesw5-dev`. Since Linux repositories are usually old, download a recent source distribution of `ncurses`, build it, and install it on top of the `apt-get` version, thus:

```
~$ sudo apt-get install libncursesw5-dev
~$ wget http://ftp.gnu.org/gnu/ncurses/ncurses-6.0.tar.gz
~$ tar xfvz ncurses-6.0.tar.gz
~$ cd ncurses-6.0/
~/ncurses-6.0$ ./configure --enable-widec
~/ncurses-6.0$ make
~/ncurses-6.0$ sudo make install
```

After installing `ncursesw`, you can make the editor:

```
~/ $ cd ~/Femto-Emacs/
~/Femto-Emacs$ make
```

Installation is achieved by copying the compiled files to `/usr/local/bin/` and the customization files to your home directory.

```
~/Femto-Emacs/femto$ sudo cp femto /usr/local/bin/
~/Femto-Emacs/femto$ sudo cp femto.boot /usr/local/bin/
~/Femto-Emacs/femto$ cp init.lsp $HOME/
~/Femto-Emacs/femto$ cp aliases.scm $HOME/
```

## 3.1 Ready

You are now ready for action!



It seems that people prefer money to sex. After all, almost everybody says no to sex on one occasion or another. But I have never seen a single person refusing money. Therefore, let us start this tutorial talking about money.

If one wants to calculate a running total of bank deposits, she will make a column of numbers and perform the addition.



What I mean to say is that, if you need to perform the addition  $8 + 26 + 85 + 3$  with pencil and paper, you will probably stack the numbers the same way you did before taking pre-algebra classes in highschool:

$$\begin{array}{r}
 + \quad 8 \\
 26 \\
 85 \\
 3 \\
 \hline
 122
 \end{array}$$

Subtraction is not treated differently:

$$\begin{array}{r}
 - \quad 358 \\
 216 \\
 \hline
 142
 \end{array}$$

Fig. 3.1: Running total


This chapter contains an introduction to the Cambridge prefix notation, which is slightly different from the one you learned in elementary school: The operation and its arguments are put between parentheses. In doing so, one does not need to draw a line under the bottom number, as you can see below:

$$\begin{array}{r}
 (+ \quad 8 \\
 26 \\
 85 \\
 3) \\
 122
 \end{array}$$

The Cambridge prefix notation can be applied to any operation, not only to the four arithmetic functions.

## 3.2 Cambridge prefix notation

Let us summarize what we have learned until now. In pre-algebra, students learn to place arithmetic operators (+, -, × and ÷) between their operands; e.g.  $347+45$ . However, when doing additions and subtractions on paper, they stack the operands.



Lisp programmers put operation and operands between parentheses. The right parenthesis separates the operands from the result, instead of drawing a line under the last operand.



## 3.3 Pictures

Here is the story of a Texan who went on vacation to a beach in Mexico. While he was freely dallying with the local beauties, unbeknownst to him a blackmailer took some rather incriminating photos. After a week long gallivanting, the Texan returns to his ranch in a small town near Austin. Arriving at his door shortly after is the blackmailer full of bad intentions.

Unaware of any malice, the Texan allows the so called photographer to enter and sit in front of his desk. Without delay, the blackmailer spread out

a number of photos on the desk, along with his demands: “For the photo in front of the hotel, that will cost you \$ 25320.00. Well, the one on the beach that’s got to be \$ 56750.00. Finally, this definitively I can’t let go for less than \$ 136000.00.”

Once finished with his presentation, the blackmailer snaps up the photos, and looks to the Texan with a sinister grin, awaiting his reply.

Delighted with the selection of pics, the Texan in an ellated voice says: “I thought I would have no recollection of my wonderful time. I want 3 copies of the hotel shot, half a dozen of the beach. And the last one, I need two copies for myself, and please, send one to my ex-wife. Make sure you leave me your contact details; I might need some more.

**Mixed calculations.** In order to calculate how much the Texan needs to pay his supposed blackmailer, his bookkeeper needs to perform the following operations:

$$3 \times 25320 + 6 \times 56750 + 2 \times 136000 + 136000$$

It should be remembered that multiplications within an expression take priority over additions and subtractions. The bookkeeper must therefore calculate the first two products  $3 \times 25320$  and  $6 \times 56750$ , before performing the first addition. In the Cambridge prefix notation, the internal parentheses pass priority over to the multiplications.

The Texan’s bookkeeper started femtoemacs in order to visit the `finance.scm` file. The text editor creates a memory buffer that mirrors the file contents. By convention, the file and the buffer have the same name.

Initially, the `finance.scm` buffer is empty, but the bookkeeper will fill it with expressions and the corresponding calculations. Here is how to start the text editor:

```
~/Femto-Emacs$ femto finance.scm
```

Listing 3.2 shows what an interaction with a femto buffer looks like.

|  |                    |
|--|--------------------|
| <pre>(+  (* 3 25320)     (* 6 56750)     (* 2 136000)     136000 )</pre> | <pre>[Esc] ]</pre> |
| 824460   |                    |

Listing 3.2: The `finance.scm` buffer

After typing an expression obeying the Cambridge prefix notation syntax, the bookkeeper moves the cursor to the front of the most external right parenthesis. To perform the calculation, he presses and releases the `[Esc]` key, then presses and releases the `[ ]` key. The femtolisp interpreter inserts the result into the buffer. To save the buffer, the bookkeeper keeps the `[Ctrl]` key down, and presses the `[x]` and `[s]` keys in sequence. To exit the editor, he maintains the `[x]` pressed and hits the `[x]` and `[c]` keys one after the other. If there are unsaved files, the editor warns that modified buffers exist, and requires confirmation before quitting.

### 3.4 Time value of money

Suppose that you wanted to buy a \$ 100,000 red Ferrari, and the forecourt salesperson in his eagerness to close a deal gives you the following two payment options:

- Pay \$ 100,000 now **or**
- pay the full \$ 100,000 after a three year grace period.

I am sure that you would choose to pay the \$ 100,000 after three years of grace has finished, although you have the money in a savings account waiting for a business opportunity. But why is this? After all, you will need to pay the debt one way or the other. However, if you keep the money in your power during the grace period, you can earn a few months of fuel from the interest.

You may not know for sure how much interest you will earn in three years, but since the salesperson is not charging you for deferring the payment, whatever you gain is yours to keep.


Unfortunately for you, the above scenario would more than probably not happen in real life. The right to delay payment until some future date is a merchandise with a price tag, which *is called interest by those who think it lawful, and usury by those who do not* (William Blackstone's Commentaries on the Laws of England). Therefore, unless the salesperson is your favorite aunt, the actual offer is like jumping into a tank full of sharks as in the classic James Bond films. It requires a little forethought and understanding of how interest works, before making a decision. Here is a more realistic real estate sales offer:

- \$ 100,000 now **or**
- \$ 115,000 at the end of three years.

What to do when facing an increase in price to cover postponement of payment? The best policy is to ask your banker how much interest she is willing to pay you over your granted grace period.

Since the economy performance is far from spectacular, your banker offers you an interest rate of 2.5%, compound annually. She explains that compound interest arises when interest is paid on both the principal and also on any interest from past years.

### 3.5 Future value



The value of money changes with time. Therefore, the longer you keep control of your money, the higher its value becomes, as it can earn interest. Time Value of Money, or TVM for short, is a concept that conveys the idea that money available now is worth more than the same amount in the future.

If you have \$ 100,000.00 in a savings account now, that amount is called *present value*, since it is what your investment would give you, if you were to spend it today.

Future value of an investment is the amount you have today plus the interest that your investment will bring at the end of a specified period.

The relationship between the present value and the future value is given by the following expression:

$$FV = PV \times (1 + i)^n \quad (3.1)$$

where  $FV$  is the future value,  $PV$  is the present value,  $i$  is the interest rate divided by 100, and  $n$  is the number of periods.

**Postponed payment.** In the case of postponing the payment of a \$ 100,000.00 car for 3 years, at an interest rate of 0.025, the future value of the money

would be 107,689.06; therefore, I stongly recomend against postponing the payment. You have learned how to calculate an expression by pressing the `[Esc][ ]` command. However, there is another way of evaluating an expression.

When you open the femtoemacs editor, there is a one line buffer at the bottom of the screen. If you keep the `[Ctrl]` key pressed, and strike the `[o]` key, the editor will read and evaluate a Cambridge prefix expression from the minibuffer.

```
(+ (* 3 25320)
   (* 6 56750)
   (* 2 136000)
  136000 ) [Esc][ ]
824460
> (* 100000.00 (expt (+ 1.0 0.025) 3)) [Enter]
107689.06
```

Listing 3.3: Command from the minibuffer

## 3.6 Compound interest

Our Texan decides he needs a break. Thus he walks into a New York City bank and asks for the loan officer. He tells a story of how through his doctor's recommendation he was taking it easy at his property in the south of France for two whole years and for such a medical emergency he needs a \$ 10,000.00 loan.

The loan officer said that the interest was a compound 8% a year, but the bank would need some collateral for the loan.

“Well, I have a 60 year old car that I like very much. Of course, I cannot take it with me to France. Would you accept it as collateral?”

Unsure whether or not the old car was worth the amount of the loan, the officer summons the bank manager. The manager inspects the vehicle that was parked on the street in front of the bank. After a close examination, he gives a nod of approval: “It’s a Tucker Torpedo. Give him the loan.”

The Texan quite willingly signed his heirloom over. An employee then drove the old car into the bank’s underground garage and parked it. From time to time, the employee would go, and turn over the engine, to keep the car in good running condition, and gave it an occasional waxing just to maintain it in pristine condition. Two years later the Texan returned, and asked how much he owed the bank. The loan officer started femtoemacs, and calculated the total debt as \$ 11,664.00.



**Interest Calculation.** Let us follow the calculation of the value accumulated in the first year of compound interest at a 8% rate over \$ 10,000.00. Press `Ctrl o` and enter formula 3.1 in the minibuffer:

```
> (* (expt (+ 1.0 0.08) 2) 10000)
11644.00
```

Observe that it was necessary to divide the interest rate by 100, which produces 0.08.

It is possible to define an operation that calculates formula 3.1 given the arguments `fv`, `i` and `n`. The definition is given in listing 3.4. Start the editor from a text terminal:

```
~$ mkdir financing
~$ cd financing
~/financing$ femto fvalue.scm
```

After typing the definition shown in listing 3.4, you must issue the `Ctrl x` `Ctrl s` command to save the buffer. In order to do this, keep the `Ctrl` key pressed down and hit the `x` and `s` keys in sequence.

In order to load the program into femtolisp, press `Ctrl o` and type `(load "fvalue.scm")` in the minibuffer, as shown in listing 3.4. After the loading operation, you can press the `Ctrl o` command again, and type

```
(future-value 10000 8 2)
```

in the minibuffer.

```
;; File: fvalue.scm

(define (future-value pv i n)
  (* (expt (+ (/ i 100.0) 1) n)
     pv)
) ;;end define

(load "fvalue.scm") Enter
#<function>
(future-value 10000 8 2) Enter
11644.00
```

Listing 3.4: Future Value Program

In listing 3.4, text between a semicolon and the end of a line is considered a comment. Therefore, `;; File: fvalue.scm` is a comment. Likewise, `;;end define` is a comment. Comments are ignored by femtolisp, and have the simple function of helping people.

### 3.7 Mortgage

A man with horns, legs and tail of a goat, thick beard, snub nose and pointed ears entered a real estate agency, and expressed his intention of closing a deal. People fled in all directions, thinking that Satan himself was paying them a visit. Deardry seemed to be the only person who remained calm. “What a ignorant, narrow minded, prejudiced lot! I know you are not the devil. You are the Great God Pan! What can I do for you?”

“I would like to buy a house in London. I know that the city is made up of 32 Boroughs and where I buy will make an enormous difference to price, quality of life, and chances of increase in capital value of the property.”

“Well, Sir, with our experience you can rest assured that you will secure your ideal property. Firstly we must decide on what type of property fits your needs and where you want to be. You may consider somewhere like Fulham, Chelsea, Knightsbridge, Kensington or Mayfair. I have properties in all these places. ”

“Chelsea! I like the name.”

“Chelsea is arguably one of the best residential areas in London. It has benefited from it’s close proximity to the west end of the city and is highly sought after by overseas buyers looking to be located in one of the most popular areas in central London. At the moment, I can offer you a fantastic living space in a four bedroomed flat situated behind King’s Road. The price is £10,500,000.”

“I don’t have this kind of cash with me right now, but can get it in a few months of working in a circus. Meanwhile, can you arrange a mortgage for me? ”

“Yes, Yes I can help arrange mortgages in all 32 Boroughs of London. Non-residents can have mortgages up to 70% of the purchase price. Do you have £3,150,000 pounds for the down payment? In mortgage agreements, down payment is the difference between the purchase price of a property and the mortgage loan amount.”

“I know what down payment is. And yes, I can dispose of £3,150,000 pounds.”

“A mortgage insurance is required for borrowers with a down payment of less than 20% of the home’s purchase price. That is not your case. Therefore, the balance of the purchase price after the down payment is deducted is the amount of your mortgage. Let us write a program in femtolisp to find out your estimated monthly payment. The loan amount is £7,350,000 pounds. The interest rate is 10% a year. The length of the mortgage is 20 years. That is the best I can do for you, I am afraid. You are going to pay £97131.00 pounds a month for ten years. After that, the balance of your debt will be

zero. But your visit is a surprise!” The broker exclaimed. “ I never thought I would ever see a true living god wanting to do property deals in London.”

With that, Pan replied: “If property prices were not so high, and interest rate so steep, we would definitely be up for business more often.”



**Loan Amortization.** Amortization refers to the gradual reduction of the loan principal through periodic payments.



Suppose you obtained a 20-year mortgage for a \$ 100,000.00 principal at the interest rate of 6% a year. Calculate the monthly payments.

**Amortization Formula.** Let  $p$  be the present value,  $n$  the number of periods, and  $r$  be the interest rate, i.e., the interest divided by 100. In this

case, the monthly payment for full amortization is given by 3.2. This formula is implemented in listing 3.5.

$$\frac{r \times p \times (1 + r)^n}{(1 + r)^n - 1} \quad (3.2)$$

```
;; File: pmt.scm

(define (pmt
  p ;; present value
  i ;; interest
  n ;; number of periods
  ;; optional parameters
    (r (/ i 100.0))
    (rn (expt (+ 1.0 r) n))
  );;end of parameter list
  (/ (* r p rn)
    (- rn 1))
) ;;end of define

(load "pmt.scm")
#<function>
(pmt (* 10500000.00 0.7) (/ 10.0 12) (* 20 12))
70929.00
```

Listing 3.5: Mortgage for a God

You certainly noticed that the `pmt` function, defined in listing 3.5, has two parameters `r` and `rn`, which the user does not need to express. Fentolisp itself assigns `(/ i 100.0)` to `r` and `(expt (+ 1.0 r) n)` to `rn`.

### 3.8 Lists

Every human and computer language has syntax, i.e., rules for combining components of sentences. In general, a computer language syntax is complex, and the programmer must study it for years before becoming proficient.

Lisp has the simplest syntax of any language. All Lisp constructions are expressed in Cambridge prefix notation: `(operation  $x_1 x_2 x_3 \dots x_n$ )`. This means that Lisp commands, macros, procedures and functions can be written as a pair of parentheses enclosing an operation followed by its arguments. Remember, there is no exception to this rule.

A linked list is a representation for a `xs` sequence in such a way that it is easy and efficient to push a new object to the top of `xs`.

```
> (define aList '(S P Q R))
(S P Q R)
> (cons 'Rome aList)
(Rome S P Q R)
> aList
(S P Q R)
```

The `'(S P Q R)` list of letters is prefixed by a quotation mark because in Lisp lists and programs have the same syntax: The Cambridge prefix notation. The single quotation mark tags the list so the computer will take it at face-value, and so not to be evaluated.

Through the repeated application of the `cons` function, one can build lists of any length by adding new elements to a core.

```
> (define xs '(S P Q R))
(S P Q R)
> (cons 5 (cons 4 (cons 3 (cons 2 (cons 1 xs)) ) ))
(5 4 3 2 1 S P Q R)
> xs
(S P Q R)
```

In the above example, you have noted that repeated application of nested functions cause right parentheses accumulate at the tail of the expression. It is good practice in programming to group these bunches of right parentheses in easily distinguishable patterns.

```
> (cons 'S (cons 'P (cons 'Q '(R)) )) ;4 right parentheses
(1 2 3)
> (+ 51 (* 9 (+ 2 (- 3 (+ 1 2 3)) ) )) ;5 right parentheses
42
> (+ 6 (* 9 (+ 2 (- 3 (+ 4 (- 3))) ))) ;6 right parentheses
42
```

Another way to create easily recognizable patterns is to reorganize the expression in order to interrupt the sequence of right parentheses:

```
> (+ 51 (* (+ 2 (- 3 (+ 1 2 3))) 9))
42
```

The head of a list is its first element. For instance, the head of '(S P Q R) is the 'S element. The tail is the sublist that comes after the head. In the case of '(S P Q R), the tail is '(P Q R). Lisp has two functions, (car xs) and (cdr xs) that selects the head and the tail respectively.

As one can see below, it is possible to reach any element of a list with a sequence of car and cdr.

```
> (define xs '(2 3 4 5 6.0))
(2 3 4 5 6.0)
> xs
(2 3 4 5 6.0)
> (car xs)
2
> (cdr xs)
(3 4 5 6.0)
> (car (cdr xs))
3
> (cdr (cdr xs))
(4 5 6.0)
> (car (cdr (cdr xs)))
4
> (car (cdr (cdr (cdr xs)) ))
5
> (car (cdr (cdr (cdr (cdr xs)) ) ))
6.0
```

### 3.9 Going through a list

In listing 3.6, the `avg` function can be used to calculate the average of a list of numbers. It reaches all elements of the list through successive applications of (cdr s). The list elements are accumulated in `acc`, while the `n` parameter counts the number of (cdr s) applications. When `s` becomes empty, the `acc` accumulator contains the sum of `s`, and `n` contains the number of elements. The average is given by (/ acc n).

In order to fully understand the workings of the `avg` function, we should have waited for the introduction to the `cond-form` given on page 55. The only reason for presenting a complex definition like `avg` so early in this tutorial is to show a grouping pattern of five right parentheses. As was discussed previously, when the number of close parentheses is greater than 3, good programmers distribute these into small groups, so that an individual who

is trying to understand the program can see that the expression is properly closed at a glance.

**For the impatient learner.** However, for the sake of the impatient reader, let us give a preview on how the `cond`-form works.

```
(define (avg s (acc 0) (n 0))
  (cond ( (and (null? s) (= n 0)) 0)
        ( (null? s) (/ acc n) )
        (else (avg (cdr s)
                    (+ (car s) acc)
                    (+ n 1.0)) ) ) )

(load "average.scm")
#<function>
(avg '(3 4 5 6))
4.5
```

Listing 3.6: Going through a list

The `cond`-form consists of a sequence of clauses. In a function definition, a clause has two components: A condition and an expression. The value of the `cond`-form will be given in the first clause that has a true condition. A concrete example will make this statement clear. In the case of listing 3.6, the clauses are:

1. `( (and (null? s) (= n 0)) 0)` – The condition `(null? s)` will be true when `s` is the empty `'()` list. If the user types `(avg '())`, the `(null? s)` expression is true, and `n` is equal to 0. The condition `(and (null? s) (= n 0))` is true, and the `cond`-form returns 0.
2. `( (null? s) (/ acc n) )` – This clause will be activated when the `s` list is `'()` empty, but `n` is greater than 0. If `n` were 0, the first clause would prevent the evaluator from reaching the second clause. The only way to reach the second clause is to go through the list by repeatedly evaluating the third clause. The value of the second clause is `(/ acc n)`, which is the average of the list.
3. `(else (avg (cdr s) (+ (car s) acc) (+ n 1.0)) )` – This clause will be evaluated when none of the previous conditions are true. If the user executes the `(avg '(3 4 5 6))` expression, the evaluator will visit this clause with `s = (3 4 5 6)`, `s = (4 5 6)`, `s = (5 6)` and `s = (6)`. Every time the evaluator falls into the third clause, `(cdr s)` is executed, and `s` loses an element.

**The third clause.** Let us follow the evaluation of `(avg '(3 4 5 6))` as it repeatedly descends through the `cond`-form conditions until it reaches the third clause.

- `(avg '(3 4 5 6))` goes to the `else`-clause, that will call:

`(avg (cdr s) (+ (car s) acc) (+ n 1))`

with `s = (3 4 5 6)`, `acc = 0` and `n = 0`. Since:

`(cdr s) = (4 5 6)`, `(+ (car s) acc) = 3` and `(+ n 1) = 1`,

the `else`-clause expression reduces to `(avg '(4 5 6) 3 1)`.

- `(avg '(4 5 6) 3 1)` goes to the `else`-clause again, that calls:

`(avg (cdr s) (+ (car s) acc) (+ n 1))`

with `s = (4 5 6)`, `acc = 3` and `n = 1`. Since:

`(cdr s) = (5 6)`, `(+ (car s) acc) = 7` and `(+ n 1) = 2`,

the `else`-clause expression reduces to `(avg '(5 6) 7 2)`.

- `(avg '(5 6) 7 2)` visits the `else`-clause once more:

`(avg (cdr s) (+ (car s) acc) (+ n 1))`

with `s = (5 6)`, `acc = 7` and `n = 2`. Since:

`(cdr s) = (6)`, `(+ (car s) acc) = 12` and `(+ n 1) = 3`,

the `else`-clause expression reduces to `(avg '(6) 12 3)`.

- `(avg '(6) 12 3)` evaluates the expression

`(avg (cdr s) (+ (car s) n) (+ n 1))`

for the fourth time, which calls `(avg '() 18 4)`.

- `(avg '() 18 4)` matches the `(null? s)` clause, that calculates the averaging `(/ acc n)` expression with `acc = 18` and `n = 4`.



# Chapter 4

## Femtoemacs commands

In the following cheat sheet, **Spc** denotes the space bar, **C-** is the **Ctrl** prefix, **M-** represents the **Alt** prefix and  $\kappa$  can be any key.

- **C- $\kappa$**  – Press and release **Ctrl** and  $\kappa$  simultaneously

**C-s** then type some text, and press **C-s** again – search a text.

**C-r** then type some text, and press **C-r** again – reverse search.

**C-k** – kill a line.

**C-h** – backspace.

**C-d** – delete char forward.

**C-Spc** then move the cursor – select a region.

**M-w** – save selected region into the kill ring.

**C-w** – kill region.

**C-y** – insert killed or saved region.

**C-g** – cancel minibuffer reading.

**C-a** – go to beginning of line.

**C-e** – go to end of line.

**C-b** – move backward one character.

**C-f** – move forward one character.

**C-n** – move cursor to the next line.

**C-p** – move cursor to the previous line.

**C-l** – refresh screen.

- **C-x C- $\kappa$**  – Keep **Ctrl** down and press  $\kappa$  and  $\kappa$

**C-x C-f** – open a file into a new buffer.

**C-x C-s** – save file.

**C-x C-c** – exit femto.

**Window commands.** One can have more than one window on the screen. Below, you will find commands to cope with this situation.

- **C-x  $\kappa$**  – Press and release **Ctrl** and **x** together, then press  **$\kappa$** 
  - C-x n** – switch buffers.
  - C-x 2** – split window into cursor window and other window.
  - C-x o** – jump to the other window.
  - C-x 1** – close the other window.
  - C-x 0** – close the cursor window.
- **Esc  $\kappa$**  – Press and release the **Esc** key, then press the  **$\kappa$**  key.
  - Esc >** – go to the end of buffer.
  - Esc <** – go to the beginning of buffer.
- **M- $\kappa$**  – Keep the **Alt** key down and press the  **$\kappa$**  key.
  - M-b** – move backward one word.
  - M-f** – move forward one word.
  - M-g** – go to the line given in the minibuffer.
  - M-n** – activate the next buffer.
  - M-r** – query replace.

In order to get acquainted with editing and scripting, let us accompany the Canadian programmer Nia Vardalos, while she explores femtoemacs.

When text is needed for carrying out a command, it is read from the minibuffer, a one line window at the bottom of the screen. For instance, if Nia presses **C-s** for finding a text, the text is read from the minibuffer. After typing the text that she wants to localize, Nia presses **C-s** again to start the search. For abandoning an ongoing command, she may press **C-g**.

To transport a region to another place, Nia presses **C-Spc** to start selection and move the cursor to select the region. Then she presses **C-w** to kill the selection. Finally, she moves the cursor to the insertion place, and presses the **C-y** shortcut.

To copy a region, Nia presses **C-Spc** and moves the cursor to select the region. Then she presses **M-w** to save the selection into the kill ring. Finally, she takes the cursor to the destination where the copy is to be inserted and issues the **C-y** command.

Nia noticed that there are two equivalent ways to issue an **M- $\kappa$**  command. She can press and release the **Esc** key, then strike the  $\kappa$  key. Alternatively, she can keep the **Alt** key down and press the  **$\kappa$**  key.

## Chapter 5

# Arithmetic operations

The femto editor is designed for writing programs. Therefore, Nia decided to learn how to use it through its own scripting language, that is femtolisp.

Nia entered the editor and pressed **C-x C-f** to create the `celsius.scm` buffer. She typed the program below into the buffer.

```
; File: celsius.scm
; Comments are prefixed with semicolon
;; Some people use two semicolons to
;; make comments more visible.
```

```
(define (c2f x)
  (- (/ (* (+ x 40) 9) 5.0) 40)
) ;;end define
```

```
(define (f2c x)
  (- (/ (* (+ x 40) 5.0) 9) 40)
) ;;end define
```

Function `c2f` converts Celsius readings to Fahrenheit. The `define` macro, which defines a function, has four components, the function id, a parameter list, an optional documentation, and a body that contains expressions and commands to carry out the desired calculation. Comments are prefixed with a semicolon. In the case of `c2f`, the id is `c2f`, the parameter list is `(x)`, and the body is `(- (/ (* (+ x 40) 9) 5.0) 40)`.

Lisp programmers prefer the prefix notation: open parentheses, operation, arguments, close parentheses. Therefore, in `c2f`, `(+ x 40)` adds `x` to 40, and `(* (+ x 40) 9)` multiplies  $x + 40$  by 9.

In order to perform a few tests, Nia must initially save the program with **C-x C-s**. Then she presses **C-x 2** to create a window for interacting with

Lisp. After this action, there are two windows on the screen, both showing the `celsius.scm` buffer. The `C-x o` command makes the cursor jump from one window to the other. From the bottom window, Nia presses `C-x C-f` to create the `repl.scm` interaction file.

On the `repl.scm` buffer, Nia can load the `celsius.scm` program and call any application that she has defined herself, or which comes with Lisp. The `C-o` command reads an operation from the minibuffer and executes it. The first operation is loading the `celsius.scm` file, as you can see in figure 5.1. Be sure that you are on the `repl.scm` interaction window when you perform the loading, otherwise you will introduce the `#<function>` extraneous text into the source file.

Let us recall what happened until now. Nia pressed `C-x 2` to split the buffer window, as shown in figure 5.1. Thus she has two buffers in front of her, each with its own window. One of the buffers has a Lisp source file, while the other contains a Lisp interaction. In order to switch from one buffer to the other, Nia press the `C-x o` command.

The command `C-x C-s` saves the Lisp source file.

The `C-o` command followed by `(load "celsius.scm")` on the minibuffer loads the source file.

One can also load the source file by typing `(load "celsius.scm")` on the interaction buffer, then press the `Esc ]` command. After loading the source file either with `C-o` or with the `Esc ]` method, Nia types `(c2f 100)`

```
; File: celsius.scm

(define (c2f x)
  (- (/ (* (+ x 40) 9) 5.0) 40)
);;end define

(define (f2c x)
  (- (/ (* (+ x 40) 5.0) 9) 40)
);;end define

#<function>

(c2f 100)
212.0

> (load "celsius.scm")
```

Listing 5.1: Source file and Iteration Buffer

on the interaction buffer. Then she presses `Esc ]` to insert the calculation of the Fahrenheit reading into the interaction buffer.

Nia often works with a single window. In this case, after typing and saving the source file with `C-x C-s`, she does not split the window before opening the interaction buffer with the `C-x C-f` command. In this case, only one buffer is visible. Nia switches between the interaction buffer and the source file by pressing the `C-x n` command.

Text editing is one of these things that are easier to do than to explain. Therefore, the reader is advised to learn femtoemacs by experimenting with the commands.

## 5.1 let-binding

The `let`-form introduces local variables through a list of `(id value)` pairs. In the basic `let`-binding, a variable cannot depend on previous values that appear in the local list. In the `let*` (let star) binding, one can use previous bindings to calculate the value of a variable, as one can see in figure 5.2. When using a `let` binding, the programmer must bear in mind that it needs parentheses for grouping together the set of `(id value)` pairs, and also parentheses for each pair. Therefore, one must open two parentheses in front of the first pair, one for the list of pairs and the other for the first pair.

You certainly know that the word ‘December’ means the tenth month; it comes from the Latin word for ten, as attested in words such as:

- *decimal* – base ten.
- *decimeter* – tenth part of a meter.
- *decimate* – the killing of every tenth Roman soldier that performed badly in battle.

October is named after the Latin numeral for *eighth*. In fact, the radical OCT- can be translated as *eight*, like in *octave*, *octal*, and *octagon*. One could continue with this analysis, placing September in the seventh, and November in the ninth position in the sequence of months. But everybody and his brother know that December is the twelfth, and that October is the tenth month of the year. Why did the Romans give misleading names to these months?

Rome was purportedly founded by Romulus, who designed a calendar. March was the first month of the year in the Romulus calendar. Therefore, if Nia wants the order for a given month in this mythical calendar, she must subtract 2 from the order in the Gregorian calendar. In doing so, September

becomes the seventh month; October, the eighth; November, the ninth and December, therefore, the tenth month.

Farming and plunder were the main occupations of the Romans, and since winter is not the ideal season for either of these activities, the Romans did not care much for January and February. However, Sosigenes of Alexandria, at the request of Cleopatra and Julius Cæsar, designed the Julian calendar, where January and February, the two deep winter months, appear in positions 1 and 2 respectively. Therefore, a need for a formula that converts from the modern month numbering to the old sequence has arisen.

```
(define (roman-order m)
  (+ m (* (winter m) 12) -2))
```

The above formula will work if (winter m) returns 1 for months 1 and 2, and 0 for months from 3 to 12. The definition below satisfies these requisites.

```
(define (winter m)
  (quotient (- 14 m) 12))
```

```
(define (winter m)
  (quotient (- 14 m) 12))

(define (roman-order m)
  (+ m (* (winter m) 12) -2))

(define (zr y m day)
  (let* ((roman-month (roman-order m))
        (roman-year (- y (winter m)))
        (century (quotient roman-year 100))
        (decade (remainder roman-year 100)) )
    (mod (+ day
            (quotient (- (* 13 roman-month) 1) 5)
            decade
            (quotient decade 4)
            (quotient century 4)
            (* century -2)) 7)) )
```

```
> (load "zeller.scm")
#<function>
> (zr 2016 8 31)
3
```

Listing 5.2: Source file and Iteration Buffer

For months from 3 to 12,  $(- 14\ m)$  produces a number less than 12, and  $(\text{quotient } (- 14\ m)\ 12)$  is equal to 0. Therefore,  $(* (\text{winter } m)\ 12)$  is equal to 0 for all months from March through December, and the conversion formula reduces to  $(+ m\ -2)$ , which means that March will become the Roman month 1, and December will become the Roman month 10. However, since January is month 1, and February is month 2 in the Gregorian calendar,  $(\text{winter } m)$  is equal to 1 for these two months. In the case of month 1, the Roman order is given by  $(+ 1\ (*\ 1\ 12)\ -2)$ , that is equal to 11. For month 2, one has that  $(+ 2\ (*\ (\text{winter } 2)\ 12)\ -2)$  is equal to 12.

The program of figure 5.2 calculates the day of the week through Zeller's congruence. In the definition of  $(\text{zr } y\ m\ \text{day})$ , the *let-star* binds values to the local variables **roman-month**, **roman-year**, **century** and **decade**.

Figure 5.2 shows that the *let* binding avoids recalculating values that appear more than once in a program. This is the case of **roman-year**, that appears four times in the **zr** procedure. Besides this, by identifying important subexpressions with meaningful names, the program becomes clearer and cleaner. After loading the program of figure 5.2, expressions such as  $(\text{zr } 2016\ 8\ 31)$  return a number between 0 and 6, corresponding to Sunday, Monday, Tuesday, Wednesday, Thursday, Friday and Saturday.

## 5.2 True or False

So far, the only tool that Nia has used for programming is combination of functions. However, this is not enough to write programs that reach a decision or make a choice. Scheme has expressions to say “if this is true, do one thing, else do another thing”. Nia could have used one of these decision making expressions to calculate the roman order:

```
(if (< m 3) (+ m 10) (- m 2))
```

The if-else expression says: if the Julian numbering **m** is greater than 2, then subtract 2 from **m**, else add 10 to **m**. The **if-else** expression is much simpler to understand than all that confusing talk about deep winter months.

Besides correcting the month, the  $(\text{winter } m)$  expression was used to correct the year. If the month **m** is 1 or 2, one must subtract 1 from the Gregorian year in order to obtain the Roman year.

You probably know, in all computer languages, *Boolean* is a data type that can have just two values: **#t** for “true” and **#f** for “false”. The procedure  $(< m\ 3)$  returns **#t** if **m** is less than 3, and **#f** otherwise. On the other hand,  $(\text{if } (< m\ 3)\ (+ m\ 10)\ (- m\ 2))$  calculates the expression  $(+ m\ 10)$  if and

only if (`< m 3`) produces the value `#t`. Otherwise, the `if` form calculates the (`- m 2`) expression.

Now, let us analyze the terms of the Zeller's congruence. A normal year has 365 days and 52 weeks. Since 365 is equal to  $(+ (* 7 52) 1)$ , each normal year advances the day of the week by 1. Therefore, the formula has a **decade** component. Every four years February has an extra day, so it is necessary to add (`quotient decade 4`) to the formula.

A century contains 100 years. Therefore, one would expect 25 leap years in a century. But since turn of the century years, such as 1900, are not leap years, the number of leap years in a century reduces to 24. So, in a century the day of the week advances by 124. But (`remainder 124 7`) produces 5, that is equal to  $(- 7 2)$ . Then one needs to subtract 2 for each century. This is done through the term  $(* \text{century } -2)$ .

But every fourth century year is a leap year. Therefore, Zeller needed to add the term (`quotient century 4`) to the formula.

Starting from March, each month has 2 or 3 days beyond 28, that is the approximate duration of a lunar month: 3, 2, 3, 2, 3, 3, 2, 3, 2, 3, 3, 0. Nia noticed that definition

```
(define (acc i) (- (quotient (- (* 13 i) 1) 5) 2))
```

returns the accumulated month contribution to the week day. However, the day chosen to start the week cycle is irrelevant. Therefore, there is no need to subtract 2 from the accumulator.

```
(define (zr y m day)
  (let* ((roman-month (if (< m 3) (+ m 10) (- m 2)))
        (roman-year (if (< m 3) (- y 1) y))
        (century (quotient roman-year 100))
        (decade (remainder roman-year 100)) )
    (mod (+ day
            (quotient (- (* 13 roman-month) 1) 5)
            decade
            (quotient decade 4)
            (quotient century 4)
            (* century -2)) 7)) )
```

```
> (load "zeller.scm")
#<function>
> (zr 2016 8 31)
3
```

Listing 5.3: Making decisions



# Chapter 6

## Sets

A set is a collection of things. You certainly know that collections do not have repeated items. I mean, if a guy or girl has a collection of stickers, s/he does not want to have two copies of the same sticker in his/her collection. If s/he has a repeated item, s/he will trade it for another item that s/he lacks in his/her collection.

It is possible that if your father has a collection of Greek coins, he will willingly accept another drachma in his set. However, the two drachmas are not exactly equal; one of them may be older than the other.

### 6.1 Sets of numbers

Mathematicians collect other things, besides coins, stamps, and slide rules. They collect numbers, for instance; therefore you are supposed to learn a lot about sets of numbers.

**$\mathbb{N}$  is the set of natural integers.** Here is how mathematicians write the elements of  $\mathbb{N}$ :  $\{0, 1, 2, 3, 4 \dots\}$ .

**$\mathbb{Z}$  is the set of integers, i.e.,**  $\mathbb{Z} = \{\dots - 3, -2, -1, 0, 1, 2, 3, 4 \dots\}$ .

Why is the set of integers represented by the letter  $\mathbb{Z}$ ? I do not know, but I can make an educated guess. The set theory was discovered by Georg Ferdinand Ludwig Philipp Cantor, a Russian whose parents were Danish, but who wrote his *Mengenlehre* in German! In German, integers may have some strange name like *Zahlen*.

You may think that set theory is boring; however, many people think that it is quite interesting. For instance, there is an Argentinean that scholars consider to be the greatest writer that lived after the fall of Greek civilization. In

few words, only the Greeks could put forward a better author. You probably heard Chileans saying that Argentines are somewhat conceited. *You know what is the best possible deal? It is to pay a fair price for Argentines, and resell them at what they think is their worth.* However, notwithstanding the opinion of the Chileans, Jorge Luiz Borges is the greatest writer who wrote in a language different from Greek. Do you know what was his favorite subject? It was the Set Theory, or *Der Mengenlehre*, as he liked to call it.

When a mathematician wants to say that an element is a member of a set, he writes something like

$$3 \in \mathbb{Z}$$

If he wants to say that something is not an element of a set, for instance, if he wants to state that  $-3$  is not an element of  $\mathbb{N}$ , he writes:

$$-3 \notin \mathbb{N}$$

Let us summarize the notation that Algebra teachers use, when they explain set theory to their students.

**Vertical bar.** The weird notation  $\{x^2 | x \in \mathbb{N}\}$  represents the set of  $x^2$ , *such that*  $x$  is a member of  $\mathbb{N}$ , or else,  $\{0, 1, 4, 9, 16, 25 \dots\}$

**Conjunction.** In Mathematics, you can use a symbol  $\wedge$  to say **and**; therefore  $x > 2 \wedge x < 5$  means (**and** ( $> x 2$ ) ( $< x 5$ )) in Lisp notation.

**Disjunction.** The expression  $(x < 2) \vee (x > 5)$  means (**or** ( $< x 2$ ) ( $> x 5$ )) in Lisp notation

Using the above notation, you can define the set of rational numbers:

$$\mathbb{Q} = \left\{ \frac{p}{q} \mid p \in \mathbb{Z} \wedge q \in \mathbb{Z} \wedge q \neq 0 \right\}$$

In informal English, this expression means that a rational number is a fraction

$$\frac{p}{q}$$

such that  $p$  is a member of  $\mathbb{Z}$  and  $q$  is also a member of  $\mathbb{Z}$ , submitted to the condition that  $q$  is not equal to 0.

In femtolisp, one can represent a rational number as a Cartesian pair of integers. The expression `(cons p q)`, where `p` and `q` are integers, builds such a pair. For instance, `(cons 5 3)` produces the `'(5 . 3)` pair. N.B. there are spaces before and after the dot.

```

(define f (cons 2 3))

(define g (cons 4 5))

(define (add x y)
  (let ( (numerator (+ (* (car x) (cdr y))
                        (* (car y) (cdr x)) ))
        (denominator (* (cdr x) (cdr y)) ))
    (cons numerator
          denominator)))

> (load "cartesian.scm")
#<function>
> (add f g)
(22 . 5) (add '(3 . 7) '(2 . 5))
(29 . 35)

```

Listing 6.1: Cartesian pairs

In the dotted pair notation of a rational number, the `(car '(5 . 3))` operation retrieves the first element of the pair, i.e., 5. On the other hand, the `(cdr '(5 . 3))` operation returns the second element, which is 3.

Let us assume that Nia wants to add two rational numbers. From elementary arithmetic, Nia knows that the addition of two rational numbers  $P$  and  $Q$  is given by the following expression:

$$\frac{X_a}{X_d} + \frac{Y_a}{Y_d} = \frac{X_a \times Y_d + Y_a \times X_d}{X_d \times Y_d} \quad (6.1)$$

In the dotted pair notation, one has  $X_a = (\text{car } X)$ ,  $X_d = (\text{cdr } X)$ ,  $Y_a = (\text{car } Y)$  and  $Y_d = (\text{cdr } Y)$ . By replacing these values in equation 6.1, one arrives at the following expressions for the numerator and the denominator of the addition:

```

(+ (* (car x) (cdr y))      ;; numerator
  (* (car y) (cdr x)))

(* (cdr x) (cdr y))        ;; denominator

```

Nia used the above expressions for calculating the numerator and denominator of  $X + Y$  in listing 6.1.


## 6.2 Irrational Numbers

At Pythagora's time, the Greeks claimed that any pair of line segments is commensurable, i.e., you can always find a meter, such that the lengths of any two segments are given by integers. The following example will show how the Greek theory of commensurable lengths at work. Consider the square that the Greek in the figure at the bottom of this page is evaluating.

If the Greeks were right, I would be able to find a meter, possibly a very small one, that produces an integer measure for the diagonal of the square, and another integer measure for the side. Suppose that  $p$  is the result of measuring the side of the square, and  $q$  is the result of measuring the diagonal. The Pythagorean theorem states that  $\overline{AC}^2 + \overline{CB}^2 = \overline{AB}^2$ , i.e.,

$$p^2 + p^2 = q^2 \therefore 2p^2 = q^2 \quad (6.2)$$


You can also choose the meter so that  $p$  and  $q$  have no common factors. For instance, if both  $p$  and  $q$  were divisible by 2, you could double the length of the meter, getting values no longer divisible by 2. E.g. if  $p = 20$  and  $q = 18$ , and you double the length of the meter, you get  $p = 10$ , and  $q = 9$ . Thus let us assume that one has chosen a meter so that  $p$  and  $q$  are not simultaneously even. But from equation 6.2, one has that  $q^2$  is even. But if  $q^2$  is even,  $q$  is even too. You can check that the square of an odd number is always an odd number. Since  $q$  is even, you can substitute  $2 \times n$  for it in equation 6.2.



$$2 \times p^2 = q^2 = (2 \times n)^2 = 4 \times n^2 \therefore 2 \times p^2 = 4 \times n^2 \therefore p^2 = 2 \times n^2 \quad (6.3)$$

Equation 6.2 shows that  $q$  is even; equation 6.3 proves that  $p$  is even too. But this is against our assumption that  $p$  and  $q$  are not both even. Therefore,  $p$  and  $q$  cannot be integers in equation 6.2, which you can rewrite as

$$\frac{p}{q} = \sqrt{2}$$



The number  $\sqrt{2}$ , that gives the ratio between the side and the diagonal of any square, is not an element of  $\mathbb{Q}$ , or else,  $\sqrt{2} \notin \mathbb{Q}$ . It was Hypasus of Metapontum, a Greek philosopher, who proved this. The Greeks were a people of wise

men and women. Nevertheless they had the strange habit of consulting with an illiterate peasant girl at Delphi, before doing anything useful. Keeping with this tradition, Hyppasus asked the Delphian priestess— the illiterate girl— what he should do to please Apollo. She told him to measure the side and the diagonal of the god's square altar using the same meter. By proving that the problem was impossible, Hypasus discovered a type of number that can not be written as a fraction. This kind of number is called irrational.

An irrational number is not a crazy, or a stupid number; it is simply a number that you cannot represent as *ratione* (fraction, in Latin).

The set of all numbers, integer, irrational, and rational is called  $\mathbb{R}$ , or the set of real numbers.

Computers are not able to deal with sets that hold a transfinite number of elements. Therefore, femtolisp and all other programming languages replace sets with the concept of type. In femtolisp,  $\mathbb{Z}$  is called **integer**, although the **integer** type does not cover all integers, but enough of them to satisfy your needs. Likewise, a floating point number belongs to the **number** type, which is a subset of  $\mathbb{R}$ .

If  $x \in \mathbf{Int}$ , Lisp programmers say that  $x$  has type **integer**. They also say that  $r$  has type **number** if  $r \in \mathbf{Real}$ .

In femtolisp, rational and irrational numbers are inexact data types. Here are a few functions that produce inexact results:

```
(+  $x_1$   $x_2$  ...  $x_n$ ) – addition
(*  $x_1$   $x_2$  ...  $x_n$ ) – multiplication
(-  $x_1$   $x_2$  ...  $x_n$ ) – subtraction
(/  $x_1$   $x_2$  ...  $x_n$ ) – division
(pow  $x$   $y$ ) –  $x^y$ 
(sin  $x$ ) –  $\sin(x)$ 
(asin  $x$ ) –  $\arcsin(x)$ 
(cos  $x$ ) –  $\cos(x)$ 
(acos  $x$ ) –  $\arcsin(x)$ 
(tan  $x$ ) –  $\tan(x)$ 
(atan  $x$ ) –  $\arctan(x)$ 
(log  $x$ ) – natural logarithm
(log2  $x$ ) – logarithm in base 2
(log10  $x$ ) – logarithm in base 10
```

Integers are distinguished from inexact numbers by the `(integer? x)` predicate. Two important integer functions are `(quotient x y)` and `(mod x y)`. The first function produces the integer division of  $x$  by  $y$ , while the other returns the remainder of the division. You should remember having used these two functions earlier to calculate the Zeller's congruence.

## 6.3 Data types

There are other types besides **integer**, and **number**. Here is a list of primitive types:

**integer** — Integer numbers between  $-2147483648$  and  $2147483647$ . The `(exact? x)` function returns `#t` if `x` is an integer, and `#f` otherwise.

**inexact** — the inexact type represents both rational and irrational numbers, albeit approximately. The `(inexact? x)` function returns `#t` for inexact numbers.

**number** — A number can be either exact or inexact. The `(number? x)` function returns `#t` for numbers, and `#f` for any other type of object.

**String** — A quoted string of characters: `"3.12"`, `"Hippasus"`, `"pen"`, etc. The `(string? x)` function answers `#t` if `x` is a string, and `#f` otherwise. A few important functions that operate on strings are:

- `(string-length s)` returns the number of chars of the `s` string.
- `(substring "Hello, World" 2 5)` operation returns the `"llo"` substring. `(substring "Hello, World" 0 4)` returns the `"Hell"` substring. And so on.

**Char** — Chars have the `#\` prefix: `#\A`, `#\b`, `#\3`, `#\space`, `#\newline`, etc. The `(char? x)` function returns `#t` when `x` is a char. Let `s` be a string such as `"Hello"`. Then, `(string-ref "Hello" 0)` returns the first char of `s`, `(string-ref "Hello" 1)` returns the second char, and so on. One can compare chars with the following functions:

```
(char=? x #\g) — #t if x= #\g
(char>? x #\g) — #t if x comes after the #\g char.
(char<? x #\g) — #t if x comes before the #\g char.
(char>=? x #\g) — #t if x is equal to #\g or comes after it.
(char<=? x #\g) — #t if x is equal to #\g or comes before it.
```

**Pair** — One can use a pair data type both to represent Cartesian pairs and lists. The `(pair? x)` returns `#t` if `x` is a pair, otherwise it returns `#f`. The `'()` empty list is a very important object that one can use as the second element of a pair. The `(null? x)` returns `#t` when `x` is the `'()` empty list.

## 6.4 Functions

A function is a relationship between an argument and a unique value. Let the argument be  $x \in B$ , where  $B$  is a set; then  $B$  is called domain of the function. Let the value be  $f(x) \in C$ , where  $C$  is also a set; then  $C$  is the range of the function. Functions can be represented by tables, or clauses. Let us examine each one of these representations in turn.

### Tables

Let us consider a function that associates **#t** (*true*) or **#f** (*False*) to the letters of the Roman alphabet. If a letter is a vowel, then the value will be **#t**; otherwise, it will be **#f**. The range of such a function is **{#t, #f}**, and the domain is **{a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z}**.

| Domain | Range | Domain | Range | Domain | Range | Domain | Range |
|--------|-------|--------|-------|--------|-------|--------|-------|
| a      | #t    | g      | #f    | m      | #f    | t      | #f    |
| b      | #f    | h      | #f    | n      | #f    | u      | #t    |
| c      | #f    | i      | #t    | o      | #t    | v      | #f    |
| d      | #f    | j      | #f    | p      | #f    | w      | #f    |
| e      | #t    | k      | #f    | q      | #f    | x      | #f    |
| f      | #f    | l      | #f    | r      | #f    | y      | #f    |
|        |       |        |       | s      | #f    | z      | #f    |

### 6.4.1 Clauses

From what you have seen in the last section, you certainly notice that it is pretty tough to represent a function using a table. You must list every case. There are also functions, like  $\sin x$ , whose domain has an infinite number of values, which makes it impossible to list all entries. Even if you were to try to insert only a finite subset of the domain into the table, it wouldn't be easy. Notwithstanding, in the past, people used to build tables. In fact, tables were the only way to calculate many useful functions, like  $(\sin x)$ ,  $(\log x)$ ,  $(\cos x)$ , etc. In 1814 Barlow published his Tables which give factors, squares, cubes, square roots, reciprocals and hyperbolic logs of all numbers from 1 to 10000. In 1631 Briggs published tables of sin functions to 15 places and tan and sec functions to 10 places. I heard the story of a mathematician who published a table of sinus, and made a mistake. Troubled by the fact that around a hundred sailors lost their way due to his mistake, that mathematician committed suicide. This story shows that the use of tables may be hazardous to your health.

In order to understand how to represent a function with clauses, let us revisit the vowel table. Using clauses, that table becomes

```
(define (vowel x)
  (cond ( (or (char=? x #\a)(char=? x #\e)(char=? x #\i)
              (char=? x #\o)(char=? x #\u)) #t)
        (else #f)))
```

Expressions like  $(\text{or } p_1 p_2 \dots p_n)$  has the same meaning as  $p_1 \vee p_2 \dots \vee p_n$ .

Functions have a parameter, also called variable, that represents an element of the domain. Thus, the vowel function has a parameter  $x$ , that represents an element of the set  $\{'a', 'b', 'c', 'd', 'e', 'f', \dots\}$ . Below the name of the function, and its variable, one finds a set of clauses. Each clause has a condition followed by an expression, that gives the value, if that clause applies. Consider the first clause. The expression:

```
(or (char=? #\a)(char=? #\e)(char=? #\i)
    (char=? #\o)(char=? #\u))
```

asks the question: *Is  $x = \text{\#a}$ ,  $x = \text{\#a}$ ,  $x = \text{\#a}$ ,  $x = \text{\#a}$  or  $x = \text{\#a}$ ?* If the answer is yes, the clause value is  $\text{\#t}$ ; in proper functions, the clause value is given by the second clause expression.

Now, let us consider the Fibonacci function, that has such an important role in the book “The Da Vinci Code”. Here is its table for the first 6 entries:

|   |   |   |   |
|---|---|---|---|
| 0 | 1 | 3 | 3 |
| 1 | 1 | 4 | 5 |
| 2 | 2 | 5 | 8 |

Notice that a given functional value is equal to the sum of the two precedent values, i.e.,  $f_{n+1} = (+ f_n f_{n-1})$ . Assume that  $n = 5$ . Then,  $f_6 = (+ f_5 f_4)$ .

Of course, the expression  $f_{n+1} = (+ f_n f_{n-1})$  is true only for  $n > 0$ , since there are not two precedent values for  $n + 1 = 0$ , or  $n + 1 = 1$ . The below programa shows how you can state that a rule is valid only under certain conditions.

```
(define (fib n fn fn-1)
  (cond ((< n 2) fn)
        (else (fib (- n 1) (+ fn fn-1) fn))))

> (load "fibonacci.scm")
#<function>
> (fib 5 1 1)
8
```



**Predicates.** A predicate is a function that gives true and false for output. In Scheme, the only false value is `#f`, but any value that is different from `#f` is considered true. A predicate can be used to discover whether a property is true for a given value. For instance, a sequence of elements such as `'(S P Q R)` is called list. There is also an empty list, that has no elements at all, and is represented by `'()`. Let `xs` be a list. Then, the predicate `(null? xs)` returns `#t` if `xs` is the empty list.

There are predicates designed for performing comparisons. For instance, `(> m 2)` returns `#t` for `m` greater than 2, and `#f` otherwise. Here is a more or less complete list of comparison predicates:

- `(> m n)` – `#t` for `m` greater than `n`.
- `(< m n)` – `#t` for `m` less than `n`.
- `(>= m n)` – `#t` for `m` greater or equal to `n`.
- `(<= m n)` – `#t` for `m` less or equal to `n`.
- `(= m n)` – `#t` if `m` is a number equal to `n`.

The inputs `m` and `n` must be both numbers, if you want the above predicates to work.

A string is a sequence of characters represented between double quotation marks. For instance, `"Sunday"` is a string. Below, there is a short list of string predicates.

- `(string=? s z)` – `#t` if `s` and `z` are equal.
- `(string>? s z)` – `#t` if `s` comes after `z` in the alphabetical order.
- `(string<? s z)` – `#t` if `s` comes before `z` in the alphabetical order.
- `(string<=? s z)` – `#t` if `s` precedes or is equal to `z`.
- `(string>=? s z)` – `#t` if `s` follows or is equal to `z`.

The prefix `#\` identifies isolated characters. Let us assume the following definition:

```
(define s "Nia Vardalos")
```

Then, the characters `#\N` `#\i` `#\a` and `#\space` were retrieved from `s` by the expressions `(string-ref s 0)`, `(string-ref s 1)`, `(string-ref s 2)` and `(string-ref s 3)`, respectively.

The blank space character, control characters, non-graphic characters and all other non-printable characters can be represented by identifiers, such as `#\space`, `#\tab` and `#\newline`.

Character have their own set of predicates, as one should expect.

- `(char=? #\A #\a)` – is `#f` since `#\A` and `#\a` are not equal.
- `(char>? #\z #\a)` – is `#t` since `#\z` comes after `#\a` in the alphabetical order.
- `(char<? #\a #\z)` – is `#t` since `#\a` comes before `#\z` in the alphabetical order.
- `(char<=? #\a #\c)` – is `#t` since the order of `#\a` is less or equal to the order of `#\c`.
- `(char>=? #\a #\c)` – `#f` since the order of `#\a` greater or equal to the order of `#\c`.

Besides predicates, Scheme uses special forms to make decisions. The `(and  $p_1 p_2 \dots p_n$ )` form evaluates the sequence  $p_1, p_2 \dots p_n$  until it reaches  $p_n$  or one of the previous  $p_i$  returns `#f`. In fewer words, the `and`-form stops at the first  $p_i$  that returns `#f` and, if no argument is false, it stops at  $p_n$ . The form returns the value of the last  $p_i$  that it evaluates. The `and`-form returns a value different from `#f` if and only if all  $p_i$  predicates produce values different from `#f` (false).

Like the `and`-form, the `or`-form also stops as soon as it can. In the case of the `or`-form, this means returning true as soon as any of the arguments is true. Remember that true is anything different from `#f`. The `(or  $p_1 p_2 \dots p_n$ )` form returns the value of the first true  $p_i$  predicate.

The `(not P)` form returns `#t` if  $P$  produces `#f`, and evaluates to `#f` if  $P$  is true, i.e., anything different from `#f`.

With the `and`, `or` and `not` forms, Nia can combine primitive functions to define many interesting predicates. For instance, the predicate `(digit? d)` determines whether  $d$  is a digit.

```
(define (digit? d)
  (and (char>=? d #\0)
       (char<=? d #\9)))
```

The predicate `deep-winter?` checks if  $m$  is 1 or 2:

```
(define (deep-winter? m)
  (or (= m 1) (= m 2)))
```

## 6.5 The cond-form

Now that Nia knows how to find an integer between 0 and 6 for the day of the week, she needs a function that produces the corresponding name.

```
(define (week-day n)
  (cond ( (= n 0) 'Sunday)
        ( (= n 1) 'Monday)
        ( (= n 2) 'Tuesday)
        ( (= n 3) 'Wednesday)
        ( (= n 4) 'Thursday)
        ( (= n 5) 'Friday)
        ( else 'Saturday)))

(define (zeller y m day)
  (let* ( (roman-month (if (< m 3) (+ m 10) (- m 2)))
          (roman-year (if (< m 3) (- y 1) y))
          (century (quotient roman-year 100))
          (decade (remainder roman-year 100)) )
    (week-day (mod (+ day
                      (quotient (- (* 13 roman-month) 1) 5)
                      decade
                      (quotient decade 4)
                      (quotient century 4)
                      (* century -2)) 7)) )

> (load "zeller.scm")
#<function>
> (zeller 2018 8 31)
Friday
```

Listing 6.2: Day of the week

The cond-form controls conditional execution, based on a set of clauses. Each clause has a condition followed by a sequence of actions. Lisp starts with the top clause, and proceeds in descending order. It executes the first clause whose condition produces a value different from `#f`. For instance, the first clause condition is the `(= n 0)` predicate. If the predicate `(= n 0)` returns `#t` for the Sunday index, the function `week-day` returns `'Sunday`. If `n = 1`, the second condition holds, and the function produces the symbol `'Monday`. And so on.

## 6.6 Lists

In Lisp, there is a data structure called list, that uses parentheses to represent nested sequences of objects. One can use lists to represent structured data. For instance, in the snippet below, `xor-structure` shows the structure of a combinatorial circuit through nested lists.

```
(define ** 42)

(define xor
  (lambda(A B)
    (or (and A (not B))
        (and (not A) B)) ))

(define xor-structure
  '(or (and A
           (not B))
        (and (not A)
              B)))
```

Although Nia does not know what a combinatorial circuit is, she noticed that the structure defined as `xor-structure` is prefixed by a single quotation mark, that in Lisp parlance is known as quote. Since Scheme uses the same notation for programs and structured data, the computer needs a tag to set data apart from code. Therefore, quote was chosen to indicate that an object is a list, not a procedure that needs to be executed by the computer.

The `define` form creates global variables. In the above source code, the variable `**` is an id for the number 42, while `xor` is the id for a program that calculates the output of a two input exclusive or gate. Of course, Nia could define the `xor` gate as shown below:

```
(define ** 42)

(define (xor A B)
  (or (and A (not B))
      (and (not A) B)) )

(define xor-structure
  '(or (and A
           (not B))
        (and (not A)
              B)))
```

From the examples, Nia discovered that there are two ways of defining the `xor` gate as a combination of `A` input, `B` input, `and` gate, `or` gate and `not` gate. In the first and most popular style, one uses the `(xor A B)` format that is a mirror of the gate application. The advantage of this method is that it spares one nesting level, and shows clearly how to use the definition.

In the second style of defining functions and gates, the id of the abstraction appears immediately after the `define` keyword. The arguments and the body of the definition are introduced by a lambda form:

```
(define xor
  (lambda(A B)
    (or (and A (not B))
        (and (not A) B)) ))
```

This second style is quite remarkable because the abstraction that defines the operation is treated exactly like any other data type existent in the language. In fact, there is no formal difference between the definition of `*x*` as an integer constant, and `xor` as a functional abstraction.

```
; File: lists.scm

(define xor-structure
  '(or (and A (not B))
       (and (not A) B)))

(load "lists.scm")  

(or (and A (not B)) (and (not A) B))|

(car xor-structure)   

or  

(cdr xor-structure)   

((and A (not B))  

 (and (not A) B))  

(car (cdr xor-structure))   

(and A (not B))  

(car (cdr (car (cdr xor-structure)) ))   

A  


(car (cdr (cdr (car (cdr xor-structure)) )))   

(not B)
```


Listing 6.3: List selectors

Although Scheme represents programs and data in the same way, it does not use the same methods to deal with source code and lists. In the case of source code, the compiler translates it into a virtual machine language that the computer can easily and efficiently process.

Data structures, such as lists, have an internal representation with parts. In particular, a list is implemented as a chain of pairs (vide page 46), each pair containing a pointer to a list element, and another pointer to the next pair. Let us assume that `xs` points to the list `'(S P Q R)`. This list corresponds to the following chain of pairs:




The first pair has a pointer to `S`, and another pointer to the second pair. The second pair contains pointers to `P` and to the third pair. The third pair points to `Q` and to the fourth pair. Finally, the fourth pair points to `R` and to the `()` empty list.



The operation `(car xs)` produces the first pointer of the `xs` chain of pairs. In the case of the `'(S P Q R)` list, `(car xs)` returns `S`. On the other hand, `(cdr xs)` yields the pair after the one pointed out by `xs`, i.e., `'(P Q R)`. A sequence of `cdr` applications permits the user to go through the pairs of a list.

|  |
|--|
| <pre>(define spqr   '(S P Q R))</pre>  |
| <pre>(load "spqr.scm") <span style="border: 1px solid black; padding: 0 2px;">Esc</span> <span style="border: 1px solid black; padding: 0 2px;">]</span> (S P Q R)  (cdr spqr) (P Q R)  (cdr (cdr spqr)) (Q R)  (cdr (cdr (cdr spqr))) (R)</pre> |

If all one needs is to represent sequences, then contiguous memory elements could be more practical than pairs. However, as one can see in figure 6.3, a list element can be a nested sublist. In this case, the `car` part of a pair can point down to a sublist branch. The diagram below shows that one can reach any part of a nested list following a chain of `car` and `cdr`. In such a chain, the `cdr` operation advances one pair along the list, and the `car` operation goes down into a sublist. The `cdr` operation is equivalent to a right  $\rightarrow$  arrow, while the `car` operation is acts like a down  $\downarrow$  arrow.



The above example shows the chains and subchains of pairs that one uses to represent the logic circuit below:

```

(define xs
  '(or
    (and A
      (not B))
    (and (not A)
      B)))
  
```

Let us assume that Nia wants to retrieve the `(NOT A)` part of the circuit. Considering that each right  $\rightarrow$  arrow is equivalent to a `cdr` operation, and each down  $\downarrow$  arrow can be interpreted as a `car` operation, she must perform `(car (cdr (car (cdr (cdr xs)))))` to reach the goal.

## 6.7 Processing text from the editor

Let us learn how to retrieve a selection such as "(2016 8 31)" from femtoemacs, transform it into the '(2016 8 31) list, and calculate the corresponding day of the week.

To select the string, press C-Spc at the first character, and move the cursor onto the last character.

The problem is that the clipboard contains a string like "(2016 8 31)", and the `zeller` function defined in needs a list. Therefore, Nia needs a procedure to read a list from a string of characters.

```
(load (home "aliases.scm"))

(define (read-string str)
  (let ( (port (open-input-string str)))
    (begin0 (read port)
      (close-input-port port)) ))
```

All languages open ports for reading things from files. Lisp is no exception, but for the fact that one can open objects like strings, and read complex objects such as a whole list. These powerful features can be seen in the above definition. The `begin0` form evaluates a sequence of expressions, and returns the first one as the result of the whole sequence. The `begin0` was necessary in the definition of `read-string` because Nia needs the result of `(read port)`, and cannot close the port before finishing the reading. The solution for this problem is to execute `(read port)`, the `(close-input-port port)`, and finally return the produce of `(read port)`.

The `week-day` function transform a number `n` between 0 and 6 into strings corresponding to the seven days of the week:

```
(define (week-day n)
  (symbol->string
    (cond ( (= n 0) "Sunday")
          ( (= n 1) "Monday")
          ( (= n 2) "Tuesday")
          ( (= n 3) "Wednesday")
          ( (= n 4) "Thursday")
          ( (= n 5) "Friday")
          ( (= n 6) "Saturday")
          (else "This should not happen"))) ))
```



**Calculating the day of the week.** Zeller congruence, as given in figure 6.2 and repeated below for ready reference, can be used to calculate the day of the week.

```
(define (zeller y m day)
  (let* ((roman-month (if (< m 3) (+ m 10) (- m 2)))
        (roman-year (if (< m 3) (- y 1) y))
        (century (quotient roman-year 100))
        (decade (remainder roman-year 100)) )
    (week-day (mod (+ (quotient (- (* 13 roman-month) 1) 5)
                      decade
                      (quotient decade 4)
                      (quotient century 4)
                      (* century -2)
                      day) 7)) ))
```

The last step is to program a command that calculates the day of the week into the editor. Here Nia uses the `cond`-form again, to select one of many commands that the user may press.

The keys `C-c a`, `C-c b`, until `C-c z` are reserved for customization, which means that you can hook any Lisp program onto them. For instance, if Nia wants to wrap the clipboard contents with the html-tags `<p>` and `</p>`, besides calculating the day of the week, she may define the following keyboard:

```
(define (keyboard key)
  (cond
    ((equal? key "C-c z")
     (let ((date (read-string (cutregion))))
       (insert (apply zeller date)))))
    ((equal? key "C-c p")
     (insert "<p> </p>")
     (backward-char 5))
    ((equal? key "C-c c")
     (end-of-line)
     (insert "<p>-")
     (insert (clipboard))
     (insert "-</p>"))
    (else (insert key))))
```

The `(apply zeller date)` operation applies `zeller` to the three elements of the `date` list, which contains the year, month and day of interest.



**;;Syntax highlight.**

```
;; define syntax highlighting for scheme files
(newlanguage ".scm" ";" "#|" "|#")
(keyword "define")
(keyword "cond")
(keyword "else")
```

```
;; define syntax highlighting for C code
(newlanguage ".c" "//" "/*" "*/")
(keyword "auto")
(keyword "break")
(keyword "case")
(keyword "char")
(keyword "continue")
(keyword "default")
(keyword "do")
(keyword "double")
(keyword "else")
(keyword "enum")
(keyword "extern")
(keyword "float")
(keyword "for")
(keyword "goto")
(keyword "if")
(keyword "int")
(keyword "long")
(keyword "register")
(keyword "return")
(keyword "short")
(keyword "signed")
(keyword "sizeof")
(keyword "static")
(keyword "struct")
(keyword "switch")
(keyword "typedef")
(keyword "union")
(keyword "unsigned")
(keyword "void")
(keyword "volatile")
(keyword "while")
```

## 6.8 The list constructor

Since the `car` and `cdr` operations select the two parts of a pair, they are called *selectors*. Besides the two selectors, lists have a constructor: The operation `(cons x xs)` builds a pair whose first element is `x`, and the remaining elements are grouped in `xs`.

```
(cons 'and '(A B))  
(and A B)
```

One has learned previously that lists must be prefixed by the special quote operator, in order to differentiate them from programs. To make a long story short, quote prevents the evaluation of a list or symbol.

When you first heard about pairs on page 46, it was stated that the first element of a pair is separated from the second by a dot. However, the dot can be omitted if the second element is itself a cartesian pair or the empty list. Then, the much neater `'(3 4)` list syntax is equivalent to the dotted Cartesian `'(3 . (4 . ()))` pair.

A backquote, not to be confused with quote, also prevents evaluation, but the backquote transforms the list into a template. When there appears a comma in the template, Lisp evaluates the expression following the comma and replaces it with the result. If a comma is combined with `@` to produce the `,@` at-sign, then the expression following the at-sign is evaluated to create a list. This list is spliced into place in the template. Templates are specially useful for creating macros, as you will learn below.

Macros are programs that brings a more convenient notation to a standard Lisp form. The syntax of Lisp, that unifies data and programs, makes it possible to create powerful macros that implement Domain Specific Languages (DSLs), speed up coding or create new software paradigms. In fact, the macro system is one of the two features that places Lisp asunder from other languages, the other being its Mathematical Foundations. For learning macros in depth, the reader is referred to Dough Hoyte's book on the subject[4]. The example below can be placed into the `init.lisp` file or into the `aliases.scm` file. Remember that these two configuration files must be copied to your home directory.

```
(define-macro (while-do c r . bdy)
  `(do () ((not ,c) ,r) ,@bdy))
```

In the above macro definition, the `bdy` variable, which comes after a dot, groups all remaining macro parameters. The syntax of Lisp requires that a blank space is inserted before and after the dot.

Nia creates a `repl.scm` buffer and tests the `while-do` macro, as you can see in the following example:

```
(let ( (s '())
      (i 0))
  (while-do (< i 5) n
    (set! s (cons i s))
    (set! i (+ i 1)) )) Esc ]
(4 3 2 1 0)
```

The `(set! i (+ i 1))` operation destructively updates the value of the local variable `i`. For instance, if `i` is equal to 3, the value of `i` is replaced with `(+ i 1)`, what makes `i` equal to 4. On the same token, `(set! s (cons i s))` replaces the value of `s` with `(cons i s)`. Then, if `s = (2 1 0)` and `i = 3`, `(set! s (cons i s))` updates `s` to `(cons 3 '(2 1 0)) = '(3 2 1 0)`.

Destructive updates are not considered good programming practice. In fact, the `set!` operation has an exclamation mark to remember you that it should not be used lightly. By the way, `set!` is pronounced as *set bang*.

The `while-do` macro is not very useful, since Scheme programmers adopt the functional style, which abhor the use of set bang. A much more interesting macro is the Curry operator, that comes pre-defined thus:

```
(define-macro (curry fn x)
  (let ( (g (gensym)))
    `(lambda(,g) (,fn ,g ,x)) ))
```

In order to understand this macro, you must learn the concept of lambda abstraction. You have learned how to define functions that have names. However, Lisp allows the creation of anonymous functions. Suppose that you want to filter the elements of a list, leaving only those that are greater than a given number. You can use the following expression:

```
(filter (lambda(x) (> x 4)) '(3 2 4 1 6 9 8))
(6 9 8)
```

Of course, you could have defined a `g4` function and use it as shown below.

```
(define (g4 x) (> 4 x))

(filter g4 '(3 2 4 1 6 9 8))
(6 9 8)
```

This solution has a flaw: It requires a definition for every number that you want to filter, which is simply impossible. Fortunately, the lambda abstraction comes to your rescue, since it creates a predicate on the fly for every number that you want to filter. The Curry macro is a handier method to define a lambda abstraction:

```
(filter (curry > 4) '(3 2 4 1 6 9 8))
(6 9 8)
```

Perhaps you are not convinced of the necessity of defining the curry macro. After all, who needs to filter a list for elements greater than a given number? I will try to give an answer to this question.

Let us assume that you have a list of words and needs to sort it to build a spell checker. The sorting program is given below.

```
(define (quick-sort s)
  (cond ((null? s) s)
        ((null? (cdr s)) s)
        (else
         (append
          (quick-sort (filter (curry string>? (car s))
                              (cdr s)))
          (list (car s))
          (quick-sort (filter (curry string<=? (car s))
                              (cdr s)))) ) )))

> (load "quick.scm")
#<function>
> (quick-sort '("Caecilia" "Anna" "Priscilla"))
(Anna Caecilia Priscilla)
```

Listing 6.4: The filter function

In listing 6.4, the definition of `quick-sort` calls `quick-sort` itself. When such a thing happens, computer scientists say that the function is recursive.

It is possible to understand how a recursive function works by following its execution step by step. In fact, this has been done for the `avg` function, in section 3.9, page 34. However, a much better approach is to study the function logically.

The `append` function appends its arguments, that are supposed to be lists. Let us assume that the `quick-sort` function was called by the following expression:

```
> (quick-sort '("g" "a" "c" "h" "n" "b"))
```

The `(filter (curry string>? (car s)) (cdr s))` expression will filter all strings that comes before "g" and return the `("a" "c" "b")`. A recursive call to `quick-sort` will sort this list, producing the first argument of `append`, to wit, `("a" "b" "c")`.

The second argument of `append` is given by the `(list (car s))` expression. Since `s= '("g" "a" "c" "h" "n" "b")`, and the `list` function builds a list from its arguments, one has `(list (car s))= '("g")`.

The third argument of `append` will be the sorted list of all strings in `s` that are greater or equal to "g", i.e., `("h" "n")`.

The value of the `(append '("a" "b" "c") '("g") '("h" "n"))` expression produces the final result, that is `("a" "b" "c" "g" "h" "n")`.

# Chapter 7

## Recursion

The mathematician Peano invented a very interesting axiomatic theory for natural numbers. I cannot remember the details, but the idea was something like the following:

1. Zero is a natural number.
2. Every natural number has a successor: The successor of 0 is 1, the successor of 1 is 2, the successor of 2 is 3, and so on.
3. If a property is true for zero and, after assuming that it is true for  $n$ , you prove that it is true for  $n+1$ , then it is true for any natural number.

Did you get the idea? For this very idea can be applied to many other situations. When they asked Myamoto Musashi, the famous Japanese Zen assassin, how he managed to kill a twelve year old boy protected by his mother's 37 samurais<sup>1</sup>, he answered:

*I defeated one of them, then I defeated the remaining 36. To defeat 36, I defeated one of them, then I defeated the remaining 35. To defeat 35, I defeated one of them, then I defeated the remaining 34...*

*...*

*To defeat 2, I defeated one of them, then I defeated the other.*

A close look will show that the function `Append` of Listing 7.1 acts like Musashi. The first clause of `(App xs s)` states that appending a `(null? xs)` list to `s` produces `s`. The second clause of `(App xs s)` states: To append a `xs` list to an `s` list, rewrite the calling `(App xs s)` expression as

---

<sup>1</sup>The boy's father had been killed by Musashi. His uncle met the same fate. His mother hired her late husband's students to protect the child against Musashi.

`(cons (car x) (App (cdr xs) s))`. Let us pick a more concrete instance of the problem.

Nia evaluated `(App '(1 2 3) '(4 5))`. This calling pattern was matched to `(App xs s)` with `xs= '(1 2 3)` and `s= '(4 5)`. Since `(null? xs)` is false, the second clause rewrite the calling pattern as:

$$(\text{cons } (\text{car } xs) (\text{App } (\text{cdr } xs) s))$$

which the inference engine reduces to

$$(\text{cons } 1 (\text{App } '(2 3) '(4 5))) \quad (7.1)$$

The `(App '(2 3) '(4 5))` subpattern matches once again with `(App xs s)`, this time making `xs= '(2 3)` and `s= '(4 5)`. Since `(null? xs)` is false, the second clause holds, and the `(App '(2 3) '(4 5))` is rewritten as

$$(\text{cons } 2 (\text{App } '(3) '(4 5))).$$

Therefore, equation 7.1 becomes:

$$(\text{cons } 1 (\text{cons } 2 (\text{App } '(3) '(4 5)))) \quad (7.2)$$

The calling pattern `(App '(3) '(4 5))` matches to `(App xs s)` with `xs= '(3)` and `s= '(4 5)`. For the last time, the second clause is chosen, and expression 7.2 becomes:

$$(\text{cons } 1 (\text{cons } 2 (\text{cons } 3 (\text{App } '() '(4 5))))) \quad (7.3)$$

The pattern `(App '() '(4 5))` matches to `(App xs s)` with `xs= '()` and `s= '(4 5)`. This time, `(null? xs)` is true, and the calling pattern reduces to `s`, which is equal to `'(4 5)`, and expression 7.3 can be rewritten as:

$$(\text{cons } 1 (\text{cons } 2 (\text{cons } 3 '(4 5)))) = '(1 2 3 4 5)$$

|  |
|--|
| <pre>(define (App xs s)   (cond ( (null? xs) s)         (else (cons (car xs) (App (cdr xs) s)) )))</pre> |
| <pre>&gt; (App '(1 2 3) '(4 5)) (1 2 3 4 5)</pre>  |

Listing 7.1: Append



## 7.1 Classifying rewrite rules

Typically a recursive definition has two kinds of clauses:

1. Trivial cases, which can be resolved using primitive operations.
2. General cases, which can be broken down into simpler cases.

Let us classify the two clauses of `(App xs s)`:

|  |   |
|--|---|
| <code>( (null? xs) s)</code>   | The first clause is certainly trivial   |
| <code>(else<br/>  (cons (car xs)<br/>        (App (cdr xs) s)))</code> | The second equation can be broken down into simpler operations: Appending two lists with one element removed from the first, and then inserting the element left out into the result. |

## 7.2 Quick Sort

Although Hoare's Quick Sort algorithm is of little practical use in these days of BTree everywhere, it gives a good illustration of recursion. The problem that Hoare solved consists of sorting a list.

The `(smaller xs p)` function returns all elements of `s` that are smaller than the `p` pivot. The `(greater xs p)` produces the list of the `s` elements that are greater or equal to `p`. Therefore the `(quick xs)` function partitions `xs` into three lists, then sorts and appends these lists:

- `(smaller (cdr s) (car s))`— numbers smaller than `(car s)`
- `(list (car s))`
- `(greater (cdr s) (car s))`— numbers greater or equal to `(car s)`.

If you sort, then concatenate these three lists, you will end up sorting the original list. A concrete case will make this fact clear. Let `s` be the list `'(4 3 1 5 2 8 7)`. The expression `(quick (smaller (cdr s) (car s)))` returns `'(1 2 3)`. The expression `(quick (greater (cdr s) (car s)))` generates `'(5 7 8)`. Finally, the `(append '(1 2 3) '(4) '(5 7 8))` application returns `'(1 2 3 4 5 7 8)`.

In the quicksort algorithm, there are two trivial cases, the empty `'()` list and lists with a single element, either of which do not require sorting.

Lists with two or more elements are sorted by breaking them into smaller sublists. Since they are closer to the trivial cases, one can assume that the smaller sublists are easier to sort.

Figure 7.2 shows a complete implementation of the quicksort algorithm for a list of numbers.

```
;; File: quicksort.scm

;; Output: elements of xs that are smaller than p

(define (smaller xs p)
  (cond ( (null? xs) xs)
        ( (< (car xs) p)
          (cons (car xs)
                 (smaller (cdr xs) p)))
        (else (smaller (cdr xs) p)) ))

;; Output: elements of xs greater or equal to p

(define (greater xs p)
  (cond ( (null? xs) xs)
        ( (>= (car xs) p)
          (cons (car xs)
                 (greater (cdr xs) p)))
        (else (greater (cdr xs) p)) ))

(define (quick s)
  (cond ( (null? s) s)
        ( (null? (cdr s)) s)
        (else (append
                  (quick (smaller (cdr s) (car s)))
                  (list (car s))
                  (quick (greater (cdr s)
                                  (car s)))))) ))

> (quick '(4 3 1 5 2 8 7))
(1 2 3 4 5 7 8)
```

Listing 7.2: The quicksort algorithm

## 7.3 Named-let

Even before learning recursivity, Nia studied the Fibonacci function on page 52. The Fibonacci function has the undesirable characteristic of requiring two auxiliary arguments. Nia cannot forget to initialize these dummy arguments, otherwise she will get an error message, instead of a result.

The named-let permit the creation of functions with initialized arguments, avoiding the definition of anomalous functions that require manual initialization.

```
(define (fibonacci i)
  (let fn+1 ( (n i) (fn 1) (fn-1 1) )
    (if (< n 2) fn
        (fn+1 (- n 1) (+ fn fn-1) fn)) ))
```

```
> (load "Fibonacci.scm")
#<function>
> (fibonacci 5)
8
```

Listing 7.3: One argument Fibonacci function

The named-let binding is used mainly to loop. In this sense, it is not different from looping facilities that one can find in languages like C or Python. However, the named-let binding has an important advantage over other loop facilities: One can give a meaningful name to scheme loops. For instance, since the loop of figure 7.3 is used to calculate the `fn+1` iteration, Nia put the `fn+1` tag on it.

There is another way to get rid of auxiliary parameters: One can initialize the parameters of a definition with default values, as shown in figure 7.4.

```
(define (avg s (sum 0) (n 0))
  (cond ( (and (null? s) (= n 0)) 0)
        ( (null? s) (/ sum n) )
        (else (avg (cdr s) (+ (car s) sum) (+ n 1.0)) )))
```

```
> (load "defaults.scm")
#<function>
> (avg '(3 4 5 6))
4.5
```

Listing 7.4: Accumulator parameters

## 7.4 Reading data from files

Figure 7.5 reads the contents of a file line by line and insert the corresponding strings into the buffer. However, before sending a string to the buffer, (`port->lines p`) prefixes it with a commented line number.

```
;; File: insFile.scm
;; The procedure (rdLines <filename>) reads
;; a Lisp file, and inserts its contents
;; into the current buffer.

(define (port->lines p)
  (let next-line ( (i 1) (x (read-line p)) )
    (cond ( (eof-object? x) #t)
          (else
           (insert "#") (insert "| ")
           (insert (number->string i))
           (cond ( (< i 10) (insert "   |#" ))
                 ( (< i 100) (insert "  |#" ))
                 (else (insert " |#" ))))
           (insert x) (insert "\n")
           (next-line (+ i 1) (read-line p))))))

(define (rdLines filename)
  (call-with-input-file filename port->lines))

> (load "insFile.scm")
#<function>
> (rdLines "test.scm")
```

Listing 7.5: Lines from file

Lisp has a cleverly designed input system. The `call-with-input-file` procedure has two arguments. The first argument is the file name. The second argument is a single parameter function such as `port->lines`. In the example of figure 7.5, Lisp opens a file, and pass the file descriptor to the `port->lines` procedure.

The definition of (`port->lines p`) assigns a line that it reads from port `p` to the variable `x`. Then `x` is inserted in the buffer, and loop proceeds to read the next line. The iteration stops when end of file is reached.

## 7.5 Writing data to files

Let us assume tha Nia needs a femtolisp program that translates markdown to html. She wants to use the program to publish poems in the internet. Here an example of markdown:

```
# To Helen
## By Edgard Alan Poe

Helen, thy beauty is to me
Like those Necéan barks of yore,
That gently, o'er a perfumed sea,
The weary, way-worn wanderer bore
To his own native shore.

On desperate seas long wont to roam,
Thy hyacinth hair, thy classic face,
Thy Naiad airs have brought me home
To the glory that was Greece,
And the grandeur that was Rome.

Lo! in yon brilliant window-niche
    How statue-like I see thee stand,
The agate lamp within thy hand!
    Ah, Psyche, from the regions which
    Are Holy-Land!
```

The program of listing 7.6 reads a markdown file line by line. If the line starts with the `##` prefix, it will be wrapped in the `h1>.../h1>` html tag. If its first char is the `#\#` prefix, but the second char is different from `#\#`, it will be wrapped in the `<h2>...</h2>` html tag.

The simplified version of the html generator of listing wrtFile treats only titles, line breaks and paragraphs. However, the interested reader will be able to add other html elements.

You have already learned how the procedure `call-with-input-file` works. If you don't remember, take a look at page 72.

The procedure `call-with-output-file` can be applied to a file name and a function with an output port as argument. One could define the output port function, but usually people use a lambda abstraction to perform the magic. Read again the explanation about the lambda abstraction on pages 57 and 64. File input/output must be mastered to perfection.

```

(define (tag i <h> x </h> )
  (let ( (Len (string-length x)))
    (string-append <h>
      (substring x i (- Len 1)) </h> "\n"))))

(define (subtitle? x)
  (and (> (string-length x) 4)
    (char=? (string-ref x 0) #\#)
    (char=? (string-ref x 1) #\#)))

(define (title? x)
  (and (> (string-length x) 3)
    (char=? (string-ref x 0) #\#)))

(define (convert in out)
  (let loop ( (x (read-line in)) )
    (cond ( (eof-object? x) #t)
      ( (subtitle? x)
        (display (tag 2 "<h2>" x "</h2>") out)
        (loop (read-line in)))
      ( (title? x)
        (display (tag 1 "<h1>" x "</h1>") out)
        (loop (read-line in)))
      ( (> (string-length x) 1)
        (display x out)
        (display "<br/>\n" out)
        (loop (read-line in)))
      (else (display "<p/>\n" out)
        (loop (read-line in))) )))

(define (copyFile inFile outFile)
  (call-with-output-file outFile
    (lambda(out) (call-with-input-file inFile
      (lambda(in) (convert in out)))) )))

> (load "toHtml.scm")
#<function>
> (copyFile "toHelen.txt" "helen.html")
#t


```

Listing 7.6: Writing data to a file

## Chapter 8

# Cloud computing

A compiler is a program that reads source code into a language that human beings can handle easily and translates the aforementioned code to an object language that computers can interpret. For instance, Nia writes source code in Scheme. The library `r5rs.scm` translates it into femtolisp. Then a compiler translates femtolisp into instructions that the computer can carry out efficiently.



The problem is that the compiler installed on Nia's machine deals with a language called femtolisp, while Nia works with Scheme. Nia can work in a language different from the compiler only because the library `r5rs.scm` provides a bridge between Scheme and the femtolisp compiler.

In this chapter, you will learn how to write a web application in pure femtolisp. Thus, you can leap frog the translation from Scheme to femtolisp. But firstly, let us learn what cloud computing is.

Cloud computing is an Internet based computer that provides shared processing on demand for those people connected to a service provider. When a company adheres to cloud computing, it avoids infrastructure costs, such as purchasing servers, and keeping them in working order.

The <https://www.cloudorado.com> site shows that provider fees can be pretty steep. However, one can hire a normal hosting service and use it for creating pages that are able to run quite interesting applications.

When you hire a hosting service, you will receive a user name and will be requested to buy a domain name. Let us assume that Nia owns the `medicina.tips` domain, where `MEDICINA` means health care in Latin. The domain may be any sequence of chars, but it is a good idea to choose names that raise interest in Web users. Since doctors usually know some Latin, if one wants to offer expert medical consultancy, `medicina.tips` is a good name. Now that Nia has a user name and a domain, she must install `femtolisp` in her cloud machine. Here is how she enters the shell:

```
~$ ssh -p2222 nia@medicina.tips
nia@medicina.tips's password: ***
```

The 2222 port is used in the secure shell protocol that connects Nia to the cloud computer. She needs a password to complete the connection.

```
Last login: Sun Sep 25 18:03:00 2016 from 179.155.71.6
~$ cd public_html
~/public_html$ mkdir lsp
~/public_html$ cd lsp
~/public_html/lsp$ echo "Addhandler cgi-script .lsp" > .htaccess
```

The `.htaccess` file specifies an extension for running lisp scripts on the web.

The cloud terminal is called `jailshell`. The `jailshell` does not allow Nia to access the `/usr/local` folder. Therefore, she needs to send the `flisp` compiler and `flisp.boot` to her cloud home directory.

```
~/Femto-Emacs/femtolisp$ scp -P2222 flisp nia@medicina.tips:~
nia@medicina.tips's password: ***
~/Femto-Emacs/femtolisp$ scp -P2222 flisp.boot nia@medicina.tips:~
nia@medicina.tips's password: ***
```

An important note: The `scp` command sends files to the cloud. In the example, Nia sends the `flisp` compiler and the `flisp.boot` file to her `nia@medicina.tips` home folder. N.B. The `scp` command takes the `-P2222` port directive with uppercase P, but the `ssh` command requires lowercase p.

Again, all the above procedures are easier to perform than to explain. The best approach is to hire a private tutor who is majoring in Computer Science. Usually, two or three classes are enough to learn `jailshell`, `ssh` and `scp`. If you do not want to spend money with a tutor, you can ask for technical support from your hosting service. If you are a really lucky, the attendant answering your call is sufficiently well informed to help you.



## 8.1 HTML page

Hypertext Markup Language, or html for short, is the most common language used to format documents for presentation on the World Wide Web. Html uses hundreds of different directives to define a layout for web pages. Each directive requires an opening `<tag>` and a closing `</tag>`.

```
<html>
  <head>
    <title>femtolisp tutorial</title>
    <meta http-equiv= 'Content-Type'
      content= 'text/html; charset=utf-8' />
  </head>
  <body>
    <form name='form' method='get'>
      <input type='text' name='temp'>
      <input type='submit' name='btn' value='send'>
    </form>
    <p>La réponse est
> (let ( (str (os.getenv "QUERY_STRING"))
>   (if str (princ str) (princ "vide"))
>   (newline))
    </p>
  </body>
</html>
```

Listing 8.1: qstring.script

In listing 8.1, one can see that an html document may contain lisp snippets for performing calculations. Let us indicate the lisp code with the `>` prefix as the first char of the line.

As you already know, online shops present forms that their clients need to fill out for placing an order. The form of listing 8.1 has two input widgets, a text field and a button. The `<input type='text' name='temp'>` widget is the `temp` text field. Its value is whatever the client types into the field.

The `<input type='submit' name='btn' value='send'>` widget is a button with a fixed value equal to `send`.

Nia Vardalos

La réponse est temp=Nia+Vardalos&btn=send

## 8.2 Script

A program that generates web pages is called a script. Usually, an html page formats the text and presents it on your browser. A dynamic page can use lisp to add calculation to the document.

The result of applying (`copyFile "qstring.script" "qstring.lsp"`) to listing 8.1 is the script given on listing 8.2.

```
#!/home/strue028/flisp
(princ "Content-type: text/html")(newline)(newline)
(princ "<html>\n")
(princ "  <head>\n")
(princ "    <title>femtolisp tutorial</title>\n")
(princ "      <meta http-equiv= 'Content-Type'\n")
(princ "        content= 'text/html; charset=utf-8' />\n")
(princ "    </head>\n")
(princ "  <body>\n")
(princ "    <form name='form' method='get'>\n")
(princ "      <input type='text' name='temp'>\n")
(princ "      <input type='submit' name='btn' value='send'>\n")
(princ "    </form>\n")
(princ "    <p>La réponse est  \n")
  (let ( (str (os.getenv "QUERY_STRING")) )
    (if str (princ str) (princ "vide"))
    (newline))
(princ "    </p>\n")
(princ "</body>\n")
(princ "</html>\n")
(princ "\n")
```

Listing 8.2: qstring.lsp

Listing 8.2 shows the structure of the lisp script. The first line calls the femtolisp compiler. The prefix `#!` is known as shebang and indicates the full path of the compiler.

The script must print the `Content-type: text/html` header followed by two newline chars.

## 8.3 Script generator

The function `(copyFile "qstring.script" "qstring.lsp")` defined in the `webscript.scm` file reads the `qstring.script` line by line.

```
(define (lisp? x)
  (and (> (string.count x) 3)
       (= (aref x 0) (aref ">" 0)) ))

(define (readLn) (io.readline *input-stream*))

(define (convert)
  (let loop ( (x (readLn)) )
    (cond ( (eof-object? x) #t)
          ( (lisp? x)
            (princ (string.sub x 1 (string.count x)))
            (newline)
            (loop (readLn)))
          (else (newline)
                 (princ "(princ ")
                 (write x)
                 (princ ")") (newline)
                 (loop (readLn)) )) ))

(define (copyFile inFile outFile)
  (let ( (in (file inFile :read))
        (out (file outFile :write :create)) )
    (with-output-to out
      (with-input-from in
        (princ "#! /home/strue028/flisp") (newline)
        (princ "(princ \"Content-type: text/html\\\")")
        (princ "(newline)")
        (princ "(newline)")
        (newline) (convert) (newline)))
      (io.close in)
      (io.close out)))
```

Listing 8.3: webscript.scm – Script generator

If the line starts with the `>` prefix, it is a lisp program, and is copied to `qstring.lsp` as is, i.e., with all its legal disclaimer.

&lt;html&gt;

```
(princ "<html>\n")
```

temp=Nia+Vardalos&amp;btn=send

If you enter the `~/Femto-Emacs/femtolisp/` folder, you will find a `flisp` interpreter that can be run independently from the editor. This is the very same femtolisp compiler that was sent to the cloud service provider.

```
~/femtodocs/samples$ ~/Femto-Emacs/femtolisp/flisp
```

**Lisp REPL.** Traditionally, the lisp interaction with the user is called Read Eval Print Loop or REPL for short. The reason is that Lisp reads an expression, evals it, prints the result, and loops back for the next expression.

```
~/femtodocs/samples$ rlwrap ~/Femto-Emacs/femtolisp/flisp
; _
; | _ _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ )
; -----|-----

> (load ``webscript.scm'')

> (copyFile ``qstring.script'' ``qstring.lsp'')
#t

> (exit)

~/femtodocs/samples$ scp -P2222 qstring.lsp nia@medicina.tips:~/
```


## 8.4 Installing a script

Most servers and cloud services run on Linux. Therefore, you cannot compile `femtolisp` in your Macintosh or Windows machine and expect it to work in the cloud. Therefore, find a local Linux machine to build the `flisp` executable. After taking care to avoid these compatibility problems, Nia entered her cloud machine to configure the script.

```
~/femtodocs/samples$ ssh -p2222 strue028@medicina.tips
strue028@medicina.tips's password:
Last login: Sun Sep 25 22:38:25 2016 from 179.155.71.6
[~]# cd public_html
[~/public_html]# cd lsp
[~/public_html/lsp]# cp ~/qstring.lsp .
[~/public_html/lsp]# chmod a+x qstring.lsp
```

By the way, the example is in French to show that `femtolisp` deals with chars used in weird languages.

## 8.5 The GNU Readline Library

Using `flisp` from the command line can be frustrating. When you type something, and spot a mistake at the beginning of the line, you cannot use the  left arrow key to move the cursor to the place where you want to insert the correction.

The bottom line is this, you could run the `flisp` compiler directly from the shell, but since it does not have an editor, it is very uncomfortable. Therefore, it is advisable to install a wrap around the GNU Readline Library. The most popular of such wraps is the `rlwrap` line editor.

```
; _
; | _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ )
; -----|-----

> (load ``webscript.scm'')

> (copyFile ``qstring.script'' ``qstring.lsp'')
  #t

> (exit)
~/femtodocs/samples$ scp -P2222 qstring.lsp nia@medicina.tips:~/
```

To install the `rlwrap` editor on the Macintosh, you can use the homebrew package manager.

```
~/Femto-Emacs/femtolisp$ brew reinstall rlwrap
```

On Linux, launch the `apt-get` manager to install the line editor.

```
~/Femto-Emacs/femtolisp$ apt-get install rlwrap
```

# Chapter 9

## Bugs

It is possible to divide computer errors into three groups:

1. Syntax errors. Code or data do not obey the grammar rules of the language chosen for writing the program.
2. Type errors. The arguments of a function are not of the right type.
3. Specification errors. The code works, but fails to carry out its original specification. The client does not get what he paid for.

In Lisp, forgetting to close parentheses is about the only way to commit a syntax error. After all, the Cambridge prefix notation can be resumed in nested lists. An example will help you to understand what a type error is. The factorial of  $n$  is the product of all integers between 1 and  $n$ . For instance, the factorial of 5 is given by  $1 \times 2 \times 3 \times 4 \times 5$ . Let us build a table for the first eight entries of the factorial function.

|   |   |   |   |   |     |
|---|---|---|---|---|-----|
| 0 | 1 | 2 | 2 | 4 | 24  |
| 1 | 1 | 3 | 6 | 5 | 120 |

If you take a careful look at this table, you will note that it has an interesting property: The factorial of  $n$  is equal to  $n \times \text{factorial}(n-1)$ . Then, the factorial of 5 is equal to  $5 \times \text{factorial}(4)$ . This property is used in the definition of the factorial function given in listing 9.1.

```
(define (fac n (i 1) (f 1) (next-f (* i f)))  
  (if (>= i n) next-f  
      (fac n (+ i 1) next-f) ))
```

Listing 9.1: Factorial function

The domain of the `factorial` function is  $\mathbb{Z}$ . In `femtolisp`, the  $\mathbb{Z}$  set is approximated by the `integer` type, for which the elements must lie in the interval from `-9223372036854775808` to `9223372036854775807`.

If the result of `(fac n)` is greater than `9223372036854775807`, `femtolisp` will produce garbage. For instance, `(fac 20)` produces the correct result: `2432902008176640000`. However `(fac 21)` returns a meaningless sequence of digits. An interesting question is: How to know whether `(fac 20)` produces a correct result? Well, you must design clever tests. For instance, the expression `(quotient (fib n) (fib (- n 1)))` must return `n`. If it does not, the computer is generating garbage.

Since the expression `(= (quotient (fib n) (fib (- n 1))) n)` is true for all values of the `n` variable, it is called *invariant* by people who investigate methods for the writing of correct programs.

```
(define (fact n (i 1) (f 1) (next-f (* i f)))
  (assert (= (quotient next-f f) i))
  (if (>= i n) next-f
      (fact n (+ i 1) next-f)))

> (load "factorial.scm")
#<function>
> (fact 15)
1307674368000
> (fact 21)
(assert-failed (= (quotient next-f f) i))
```


Listing 9.2: Factorial function

In order to avoid specification errors, it is necessary to use logical statements to write a contract between the computer engineer and the client. The contract has three assertions:

1. A precondition that must be true of the parameters for calling the contracted function.
2. A postcondition that is true after running the evaluator. The result returned by the contracted function must be what the client desires.
3. An invariant that is true before and after the execution of the code. The `(assert (= (quotient next-f f) i))` expression interrupts the computation if the invariant ever becomes false, which means that there is an error in the program.



## 9.1 Bugs



The first computer was constructed by Konrad Zuse, a German civil engineer, and his assistant, Ms. Ursula Walk, née Hebekeuser. The first computers, like those of Zuse and Walk, were based on relays. These are bulky electrical devices, typically incorporating an electromagnet, which is activated by a current in one circuit to turn on or off

another circuit. Computers made of such a contrivance were enormous, slow, and unreliable. Therefore, on September 9th, 1945, a moth flew into one of the relays of the Harvard Mark II computer and jammed it. From that time on, *bug* became the standard word to indicate an error that prevents a computer from working as intended.

Due to bugs, compilers of languages like Clean and Haskell frequently return error messages, instead of generating code and running the corresponding programs. The Steel Bank Common Lisp language does not interrupt code generation when the compiler spots a bug, all the same it does issue warnings that help find the problem before the embarrassment of failure being manifest on the client's terminal. Femtolisp does not possess such a kind of oracular compiler. It report errors only when you execute the code.

## 9.2 Missing parenthesis

There is only one kind of bug that femtolisp reports at compile time: missing parenthesis. This bug is annoying, because the compiler does not report its position accurately. For example, try to compile the code of Listing 9.3. The compiler issues the following error message:

```
(load-error fvalue.scm (parse-error read: unexpected end of input))
```

The error is on line 4, where a right parenthesis is missing. Nevertheless, the compiler does not give the smallest hint on where the problem is. Furthermore, the error message is misleading, as it does not mention the parenthesis. It simply complains about an unexpected end of input.

Whenever you receive a message of ‘unexpected end of input’, my advice is to look for a missing parenthesis. However, checking parentheses by hand

over a large file is time consuming and boring. Is it possible to write a new loader with error messages that are more helpful? The answer to this question is yes! In fact, it is very easy to customize Lisp.

```
;; File: fvalue.scm

(define (future-value pv i n)
  (* (expt (+ (/ i 100.0 1) n)
      pv))
) ;; end define

(define (fat n)
  (if (< n 1) 1
      (* (fat (- n 1)) n)))

(define (fn+1 n fn fn-1)
  (if (< n 2) fn
      (fn+1 (- n 1)
              (+ fn fn-1) fn)))

(define (quick xs)
  (if (null? xs) xs
      (append
        (quick (filter (lambda(x) (< x (car xs)))
                        (cdr xs)))
        (list (car xs))
        (quick (filter (lambda(x) (>= x (car xs)))
                        (cdr xs))) )))

#|This loader fails at definition 3|#

(load "manydefs.scm")
(load-error manydefs.scm
  (parse-error read: unexpected end of input))
```

Listing 9.3: Future Value Program

Listing 9.4 shows a loader that informs which expression has an unmatched parenthesis. Besides this, if you add postcondition expressions to the source file, the program will also report specification errors. For example, in listing 9.5, if the postcondition (`assert (= (fn+1 5) 8)`) fails, the

`load-definition` command will inform which assertion did not meet the specifications. Here one has an example of a specification error. For the definition  $f = \lambda(n)(n < 2)?1 : f(n - 1) + f(n - 2)$ , one has that  $f(5) = 5$ . On the other hand,  $f = \lambda(n)(n < 2)?1 : f(n - 1) + f(n - 2)$  produces  $f(5) = 8$ . Both alternatives are correct, but the postcondition shows that the client wants the second. Now that you know the effects, let us see how to perform the magic.

```
;; File: loader.scm

(define (rd i out)
  (trycatch (read out)
    (lambda(x) (insert "#") (insert "|")
      (insert "This loader failed at definition ")
      (insert (number->string i)) (insert "|#\n")) ))

(define (try-to-eval i sexpr)
  (trycatch (eval sexpr)
    (lambda(x) (insert "#") (insert "|")
      (insert "Error in expression ")
      (insert (number->string i))
      (insert "|#\n")) ))

(define (eval-them out)
  (let loop ( (i 1) (sexpr (rd 1 out)))
    (cond ( (eof-object? sexpr) #t)
      ( else (try-to-eval i sexpr)
        (loop (+ i 1) (rd (+ i 1) out))) )))

(define (load-definitions source)
  (call-with-input-file source eval-them))

(load "loader.scm")
#<function>
```

Listing 9.4: Reporting error position

In listing 9.4, a `(trycatch sexpr (lambda(x) ...))` tries to evaluate a Lisp `sexpr`. If the evaluation ends with success, `trycatch` returns the value of the `sexpr`. Otherwise, `trycatch` executes its second argument, which reports the error.

In listing 9.4, the `trycatch` form is used on two occasions. In the `(rd i out)` definition, `trycatch` reports unmatched parentheses.

In `(try-to-eval i sexpr)`, `trycatch` will report runtime errors. Since `femtolisp` defers error reporting to runtime, it is advisable to add `(assert P)` postconditions to the code, in order to detect specification errors.

The `(eval sexpr)` function-call evaluates a Lisp expression. Therefore, if one executes the `(eval '(* 2 21))`, s/he will get 42.

```
;; File: fvalue.scm

(define (future-value pv i n)
  (* (expt (+ (/ i 100.0 1) n)
      pv))
) ;; end define

(define (fat n)
  (if (< n 1) 1
      (* (fat (- n 1)) n)))

(define (fn+1 n (fn 1) (fn-1 1))
  (if (< n 2) fn
      (fn+1 (- n 1)
              (+ fn fn-1) fn )))

(assert (= (fn+1 5) 8))

(define (quick xs)
  (if (null? xs) xs
      (append (quick (filter (lambda(x) (< x (car xs)))
                              (cdr xs)))
                (list (car xs))
                (quick (filter (lambda(x) (>= x (car xs)))
                              (cdr xs))) )))

(load-definitions "manydefs.scm") 
#<function>
```

Listing 9.5: Checking for specification errors

# Chapter 10

## Finite Automaton

A deterministic finite automaton is a finite state machine that accepts or rejects finite strings of chars and only produces a unique computation for each input string. Figure 10.1 below illustrates a deterministic finite automaton using a state diagram. The aforementioned automaton recognizes words and punctuation marks from a text using the Roman alphabet, which is the same as in English. Therefore, this automaton can accept a stream of words and punctuation from an English text.




Fig. 10.1: Finite automaton that recognizes English words

In the automaton of figure 10.1, there are three states:  $q_1$ ,  $q_2$  and  $q_3$ . The automaton remains in the state  $q_1$  as long as the stream produces blank chars, i. e., `#\space`, `#\newline` or `#\tab`. If the computation reaches the end of the string, the automaton returns  $'()$  and stops. If a punctuation mark appears in the stream, the automaton accepts it, and goes to the  $q_2$  state.

```
;; Finite automaton

(define (end-of-string? s n)
  (<= (string-length s) n))

(define (punctuation-mark? c)
  (not (not (string.find ".,:;?!()" c)) ))

(define (tokenize s)
  (ignore-blank 0 s))

(define (ignore-blank n s)
  (cond ( (end-of-string? s n) '())
        ( (char-whitespace? (string-ref s n))
          (ignore-blank (+ n 1) s))
        ( (punctuation-mark? (string-ref s n))
          (cons (substring s n (+ n 1))
                (ignore-blank (+ n 1) s)))
        (else (word n (+ n 1) s)) ))

(define (word i j s)
  (cond ( (end-of-string? s j)
          (list (substring s i j)))
        ( (char-whitespace? (string-ref s j))
          (cons (substring s i j)
                (ignore-blank j s)))
        ( (punctuation-mark? (string-ref s j))
          (cons (substring s i j)
                (ignore-blank j s)))
        (else (word i (+ j 1) s)) ))
```

# Appendix A

## Femtolisp cheat sheet

**Equality predicates.** All lisp dialects provide a plethora of predicates for testing for equality of two objects. Let us perform a few tests to discover the difference between them.

```
~/Femto-Emacs/femtolisp$ rlwrap ./flisp
; -
; | _ _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ ) | _ )
;-----|-----

> (eq? 4.5 (/ 9.0 2))
#f
> (eqv? 4.5 (/ 9.0 2))
#t
> (eq? 'Carmen 'Carmen)
#t
> (eq? 'Carmen (car '(Carmen Micaela)))
#t
> (equal? 4.5 (/ 9.0 2))
#t
> (= 4.5 (/ 9.0 2))
#t
> (= 'Carmen (car '(Carmen Micaela)))
type error: =: expected number, got Carmen
```

It seems that `(equal? x y)` answers true when `x` is visually equal to `y`. The predicate `(= x y)` seems to work for numbers only. The predicate `(eq? x y)` checks whether `x` is the same object as `y`. Finally, `(eqv? x y)` returns `#t` when `x` is equivalent to `y`, whatever this may mean.

**Comparing things.** Predicates such as `(> x y)`, `(>= x y)`, `(< x y)` and `(<= x y)` work for objects of any type.

```
~/Femto-Emacs/femtolisp$ rlwrap ./flisp
> (> 4 3)
#t
> (> "zebra" "horse")
#t
> (>= "abc" "abc")
#t
> (< "abc" "abc")
#f
> (<= "abc" "abc")
#t
```

**Arithmetic operations.** The numerical functions shown below can have any number of arguments.

- Multiplication – `(* x1 x2 x3 ... xn)`
- Addition – `(+ x1 x2 x3 ... xn)`
- Subtraction – `(- x1 x2 x3 ... xn)`
- Division – `(/ x1 x2 x3 ... xn)`

Operations such as `(div0 53 5)` and `(mod0 53 5)` calculates the quotient and remainder of the integer division respectively. All arithmetic operations can be nested at will.

```
> (div0 53 5)
10

> (mod0 53 5)
3

> (+ (* 3 4 5) (/ 3.1416 8))
60.3927

> (define (c2f x) (- (/ (* (+ x 40) 9) 5.0) 40))
#fn(``7000r1|bXwb9T2c0U2bXx;' ' [5.0] c2f)

> (c2f 100)
212.0
```



**File operations.** You have already learned the very basic file operations on chapter 8, page 75.

```
~/femtodocs/samples$ rlwrap ~/Femto-Emacs/femtolisp/flisp
; _
; | _ _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ ) | _ )
; -----|-----
> (let ( (s (file "f.txt" :write :create)))
    (with-output-to s
      (princ '(She walks in beauty))
      (io.close s)))
#t
> (let ( (s (file "f.txt" :read)))
    (with-input-from s
      (prog1 (read)
        (io.close s)) ))
(She walks in beauty)
> (let ( (s (file "f.txt" :read)))
    (with-input-from s
      (read)
      (io.close s)))
#t
> (let* ( (s (file "f.txt" :read))
          (expression (read s)) )
      (io.close s) expression)
(She walks in beauty)
```

Listing A.1: Basic io

In the above example, all reading operations get data from the `s1` stream. The `(prog1 (read) (io.close s1))` sequence reads an expression from the `s1` stream, and closes the stream. The return value of the `prog1` sequence is given by its first expression, i.e., `(read)`.

In order to better understand the necessity of the `prog1` sequencer, the last expression of listing A.1 shows what happens if one simply reads an expression and closes the stream: The result would be `#t`, which would report that the stream was closed successfully, but is not what you want. Of course, `let*` can produce the same effect as the `prog1` sequencer.

The `copyFile` procedure copies the `inF` file into the `outF` file. It calls (`rdprt`) that reads each `x` line of the `in` stream and prints it into the `out` stream until the (`eof-object? x`) predicate becomes true. When the file descriptor reaches the end of a file, any read operation returns an end of file object, which makes the (`eof-object? x`) predicate return `#t` – true.

```
(define (opn fname)
  (trycatch (file fname :write :append)
    (lambda(x) (file fname :write :create)) ))

(define (into fname expr (s (opn fname)))
  (with-output-to s (write expr) (newline) (io.close s)))

(define (readLn) (io.readline *input-stream*))

(define (rdprt)
  (let loop ( (x (readLn)))
    (cond ( (eof-object? x) #t)
      (else (princ x)
        (loop (readLn)) )) ))

(define (copyFile inF outF)
  (let ( (in (file inF :read))
    (out (file outF :write :create)) )
    (with-output-to out
      (with-input-from in (rdprt)))
    (io.close in)
    (io.close out)))

(define (prtFile nm (in (file nm :read)))
  (let loop ( (x (io.getc in)))
    (when (not (eof-object? x))
      (io.putc *output-stream* x)
      (loop (io.getc in)) ))
  (io.close in))
```

Listing A.2: fileio.scm – File Input/Output

Let us test listing A.2, which is stored at the `fileio.scm` file. The (`opn fname`) operation tries to open a file for appending text. If the file does not exist, (`opn fname`) creates it.

The (rdprt) procedure reads lines from a file and prints them into another file. File descriptors are generated from file names by the

```
(copyFile inF outF)
```

procedure. When a file is read beyond the last char, the result is an end-of-file object, that is detected by the (eof-object? x) and stops the read-print-loop in the (rdprt) procedure. The (into fname expr) procedure inserts the expr lisp expression into the fname file as one text line.

```
~/femtodocs/samples$ rlwrap ~/Femto-Emacs/femtolisp/flisp
```

```
; _
; | _ _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ )
;-----|-----
```

```
> (load "fileio.scm")
> (into "byron.txt" '(She walks in pretty))
#t
```

```
> (into "byron.txt" '(like the night))
#t
```

```
> (prtFile "byron.txt")
(She walks in pretty)
(like the night)
#f
```

```
> (copyFile "byron.txt" "byron2.txt")
#t
```

```
> (prtFile "byron2.txt")
(She walks in pretty)
(like the night)
#f
```

The (prtFile nm) procedure prints a file char by char. In the named-let, every time that the (io.getc in) procedure is called, the loop reads one char from the in stream. The (io.putc \*output-stream\* x) prints the x char on the screen. The (when c  $x_1 x_2 \dots x_n$ ) form executes the  $x_1, x_2 \dots x_n$  expressions, when the c condition holds. In the case of the (prtFile fname) procedure, the when-form puts the x char into the \*output-stream\* and loops back to read and print the next char.

**Random access.** The `wrtVector` procedure writes a datum into the `nm` file at a random position given by the `(* i sz)` expression.

The `rdVector` procedure reads an expression from a `(* i sz)` random position of the `nm` file. The `(clear nm i sz)` operation fills a node at `(* i sz)` with blank chars.

```
(define (opn fname)
  (trycatch (file fname :write :append)
    (lambda(err) (file fname :write :create)) ))

(define (clear nm i sz (out (opn nm)))
  (io.seek out (* i sz))
  (let loop ((j sz))
    (when (> j 0)
      (io.putc out #\space)
      (loop (- j 1)) ))
  (io.close out))

(define (wrtVector nm datum i (sz 100))
  (clear nm i sz)
  (let ((out (trycatch (file nm :write :append)
    (lambda(err) (file nm :write :create)) ) ))
    (with-output-to out
      (io.seek out (* i sz))
      (princ datum))
    (io.close out)))

(define (rdVector nm i (sz 100))
  (let ( (in (file nm :read)))
    (with-input-from in
      (io.seek in (* i sz))
      (print (read)))
    (io.close in)))
```

Listing A.3: randomAccess.scm

The file is organized as a sequence of nodes, where each node has a fixed number of chars. In the examples, there are 100 chars in a given node. Node `i` starts at the `(* i sz)` position. For instance, node 2 starts at the `(* 2 100)` position and ends at the `(* 3 100)` position.

To clean a node, the `(io.seek out (* i sz))` places the file descriptor at the first char of the node, and loops through the node size.

Below, you will find a test for listing A.3.

```
~/femtodocs/samples$ rlwrap ~/Femto-Emacs/femtolisp/flisp
; _
; | _ _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ )
; -----|-----
> (load "randomAccess.scm")
#<function>
> (wrtVector "gordon.txt" '(She walks) 0)
#t

> (wrtVector "gordon.txt" '(in beauty) 1)
#t

> (wrtVector "gordon.txt" '(like the night) 2)
#t

> (wrtVector "gordon.txt" '(of cloudless climes) 3)
#t

> (wrtVector "gordon.txt" '(and starry skies) 4)
#t

> (rdVector "gordon.txt" 0)
(She walks)#t

> (rdVector "gordon.txt" 1)
(in beauty)#t

> (rdVector "gordon.txt" 2)
(like the night)#t

> (rdVector "gordon.txt" 3)
(of cloudless climes)#t

> (rdVector "gordon.txt" 4)
(and starry skies)#t

> (rdVector "gordon.txt" 2)
(like the night)#t
```

**A file automaton.** In listing A.4, the `rdword` procedure reads the contents of a file as a list of words. It is implemented as an automaton. To learn what an automaton is, reread chapter 10, page 89.

To test listing A.4, let us create a file with the first and second line of one of the most popular of Byron's poems:

She walks in beauty, like the night  
Of cloudless climes and starry skies.

Now, let us start up `femtolisp`, load the program, and read the words and punctuation marks from the poem. As soon a word is read, it is consed into a list, and the automaton proceeds to read the rest of the text.

```
~/femtodocs/samples $rlwrap ~/femtolisp/flisp
; _
; | _ _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ )
;-----|-----

> (load "wordsFromFile.scm")
#<function>
> (rdList "words.txt")
("She" "walks" "in" "beauty" "," "like"
 "the" "night" "Of" "cloudless" "climes"
 "and" "starry" "skies" ".")
```

The automaton of listing A.4 is based on two procedures, `(io.getc s)` and `(io.peekc s)`. The `(io.getc s)` reads a char from the `s` stream, and advance the file descriptor to the next char. The `(io.peekc s)` procedure peek at a char, but do not advance the file descriptor.

Consider the third clause that appears in the `cond`-form that appears in the definition of the `(word c s xs)` procedure. The clause peeks the next char in the stream, but does not advance the file descriptor. If the char is the end-of-file object, the automaton has finished with the file. Therefore, the clause reverses the `xs` accumulator and casts it into a string. Why one cannot use `io.getc` to check the next character for the end of file?

The short answer is that in the case of clause failure, the char would not be available for last clause.

The long answer is that one could use the `io.getc` procedure. However, the last clause should call the `(begin (io.ungetc s) (io.getc s))` sequence, instead of the `(io.getc s)` procedure. This is necessary, in order to restore the file descriptor that the `(io.getc s)` procedure advanced in the third clause.

The implementation of automata through `io.getc` and `io.peekc` is particularly useful in compiler construction. I believe that the designers of `femtolisp` has provided such a complete set of char reading functions, because they intended to use `femtolisp` in the implementation of the Julia language.

I hope that this much information will be enough for you to figure out how the automaton works.

```
(define (punctuation-mark? c)
  (not (not (string.find ".,:;?!()" c)) ))

(define (ignore-blank c s)
  (cond ( (eof-object? c) '())
        ( (or (eqv? c #\space) (eqv? c #\newline))
          (ignore-blank (io.getc s) s))
        ( (punctuation-mark? c)
          (cons (string c)
                (ignore-blank (io.getc s) s)))
        (else (word c s '()) ) ))

(define (word c s xs)
  (cond ( (eof-object? c)
          (list (apply string (reverse xs))))
        ( (eqv? c #\space)
          (cons (apply string (reverse xs))
                (ignore-blank (io.getc s) s)))
        ( (eof-object? (io.peekc s))
          (list (apply string (reverse (cons c xs)) ) ) )
        ( (punctuation-mark? (io.peekc s))
          (cons (apply string (reverse (cons c xs)))
                (ignore-blank (io.getc s) s)))
        ( (io.eof? s)
          (list (apply string (reverse xs))))
        (else (word (io.getc s) s (cons c xs)) ) ))

(define (rdList fname)
  (let ( (in (file fname :read)))
    (ignore-blank (io.getc in) in)))
```

Listing A.4: Reading words from a file

**List processing.** As all lisp dialects, femtolisp has a plethora of list processing functions. Below, the interested reader will find a demonstration of this kind of function.

```
~/femtodocs/samples$ rlwrap ~/Femto-Emacs/femtolisp/flisp
; _
; | _ _ _ | _ _ | . _ _
; | (-| | | | _ ( _ ) | _ _ | _ ) | _ )
;-----|-----

> (member 4 '(3 5 4 8))
(4 8)
> (assoc "ed" '( ("paul" 42) ("ed" 12) ("ann" 5)))
("ed" 12)
> (list-tail '(a b c d e f) 2)
(c d e f)
> (list-head '(a b c d e f) 2)
(a b)
> (list-ref '(a b c d e f) 2)
c
> (length= '(a b c d e f) 6)
#t
> (length> '(a b c d e f) 3)
(d e f)
> (last-pair '(a b c d e f))
(f)
> (lastcdr '(a b c d e f))
()
> (map! (lambda(x) (* x x)) '(3 4 5))
(9 16 25)
> (filter (lambda(x) (> x 2)) '(3 4 5 6 2 1))
(3 4 5 6)
> (separate (lambda(x) (> x 2)) '(3 4 5 6 2 1))
((*values*) (3 4 5 6) (2 1))
> (count (lambda(x) (> x 2)) '(3 4 5 6 2 1))
4
```



# Bibliography

- [1] Harold Abelson, Gerald Jay Sussman and Julie Sussman. Structure and Interpretation of Computer Programs. The MIT Press, Second Edition, 1996.
- [2] Matthias Felleisen, Robert Bruce Findler, Matthew Flatt, Shriram Krishnamurthi. Available in <http://www.htdp.org>.
- [3] Dorai Sitaram. Teach yourself Scheme in Fixnum Days. Available in <http://ds26gte.github.io/tyscheme/>.
- [4] Doug Hoyte. Let Over Lambda. Hoytech, 2008. ISBN: 978-1-4357-1275-1
- [5] A. Church, A set of postulates for the foundation of logic, Annals of Mathematics, Series 2, 33:346–366 (1932).
- [6] Alonzo Church. The Calculi of Lambda Conversion. Princeton University Press, 1986.