

SOFTWARE DESIGN DOCUMENT: HOSTEL MANAGEMENT PLATFORM

Version 1.4 - Comprehensive Engineering & Architecture Manual

1. Introduction

1.1 Purpose

The TrueNorth Hostel Management Platform is a comprehensive, multi-tenant portal designed to streamline operations for Admins, Wardens, and Tenants. This Software Design Document (SDD) serves as the definitive engineering manual for the platform's cloud migration, infrastructure, database schema, state management, and continuous integration strategy.

1.2 Scope

This document covers the complete architectural footprint required to scale the application from an initial MVP phase (approx. 500 students, 4 hostels) to a high-availability, fault-tolerant enterprise system capable of supporting 100,000+ concurrent users without requiring a codebase rewrite.

1.3 Definitions, Acronyms, and Abbreviations

Acronym	Definition	Context in Platform
AWS	Amazon Web Services	The primary cloud provider hosting the entire infrastructure.
ECS	Elastic Container Service	Orchestrates the Next.js Docker containers via serverless Fargate tasks.
RDS	Relational Database Service	Fully managed PostgreSQL database handling all relational data.
SSR	Server-Side Rendering	Next.js capability to render pages on the server for SEO and performance.
JWT	JSON Web Token	Cryptographically signed tokens issued by AWS Cognito for session management.
ALB	Application Load Balancer	Distributes incoming HTTPS traffic across multiple healthy Fargate containers.
WAF	Web Application Firewall	Edge security protecting against SQLi, XSS, and DDoS attacks.

2. Complete System Architecture

2.1 Full Layered Architecture Topology

The platform is designed in distinct, highly scalable layers. The diagram below illustrates the complete lifecycle of a request, from the Client Layer to the Data Layer, emphasizing our monolithic container strategy over decoupled Lambdas.




Syntax error in text
mermaid version 11.16.0

3. Frontend Architecture & State Management

3.1 Frontend Data Flow

The application is built utilizing the Next.js App Router. Unlike traditional SPAs that rely heavily on massive client-side bundles and Redux stores, our architecture leverages Server Components for data fetching and Server Actions for data mutation.



3.2 Global State Management

Why we explicitly rejected Redux/Zustand: In traditional React applications, massive global state managers (like Redux) are required to cache API responses. In our Next.js architecture, state management is vastly simplified through **Server Actions and the Next.js Request Cache**. Data mutations (e.g., assigning a task to a warden) are handled via asynchronous Server Actions, which automatically trigger `revalidatePath`. This instantly invalidates the cache and pushes the fresh data to the UI, entirely eliminating the need for complex, bug-prone Redux boilerplate.

3.3 User Interface Specifications (Screenshots)

3.3.1 Authentication Module (Login)

This module interfaces directly with AWS Cognito. [INSERT SCREENSHOT HERE - LOGIN PAGE]

3.3.2 Main Dashboard (Admin & Warden)

Displays real-time metrics aggregated via complex Prisma queries. [INSERT SCREENSHOT HERE - DASHBOARD SCREEN]


3.3.3 Data Entry & Management Forms

Interfaces for onboarding tenants, generating PDF receipts, and assigning tasks. [INSERT SCREENSHOT HERE - FORMS / DATATABLE SCREEN]

4. Backend Architecture

4.1 Backend Service Flow

Our backend logic is safely encapsulated within the Next.js monolithic container. This design intentionally replaces the "300+ decoupled Lambda functions" pattern to protect the relational database.



4.2 The "Majestic Monolith" Justification (ECS Fargate vs. AWS Lambda)

Why We Explicitly Rejected Lambda Microservices

While Lambda is excellent for event-driven scripting, splitting a **Next.js + Prisma** application into hundreds of separate Lambda functions introduces catastrophic bottlenecks:

1. **The Database Connection Crisis:** AWS Lambda functions are ephemeral. If 50 users hit 50 different API routes, Lambda attempts to open 50 brand-new database connections to PostgreSQL simultaneously. This rapidly exhausts the database's `max_connections` limit, causing immediate platform outages.
2. **Cold Starts:** Next.js SSR functions running on Lambda suffer from "cold starts" (1-3 second delays when a function wakes up), resulting in unacceptable UI latency.

The Superior Solution: ECS Fargate


We deploy the entire Next.js application as a single, unified Docker container running on **AWS ECS Fargate**.

- **Stable Connection Pooling:** The Node.js server starts once inside the persistent container. Prisma instantiates a highly efficient connection pool (e.g., 10 connections) and flawlessly reuses them to serve thousands of concurrent API requests. The database is never overwhelmed.
- **Effortless Scalability:** When CPU utilization exceeds 70%, ECS Auto-Scaling seamlessly provisions identical replica containers, and the Application Load Balancer distributes the traffic evenly among them.

5. Full Database Schema & Architecture

5.1 Entity-Relationship (ER) Diagram

The core PostgreSQL schema is managed exclusively via Prisma ORM. Below is the Entity-Relationship map demonstrating how deeply interconnected our multi-tenant SaaS application is.



5.2 Deep-Dive Table Architecture Explanations

To satisfy enterprise auditing requirements, here is the architectural breakdown and justification for every core table design in our Prisma schema.

5.2.1 Core Multi-Tenancy (**Organization**, **Hostel**, **User**)

- **Architecture:** The **Organization** table acts as the root of the SaaS application. Every **Hostel** and **User** strictly ties back to an **organizationId**.
- **Justification:** This guarantees strict multi-tenant data isolation. A user logged into Organization A cannot accidentally query Hostels or Tenants from Organization B.
- **Roles:** The **User** table contains an **enum UserRole** (**MAIN_ADMIN**, **WARDEN**, **TENANT**). A single **User** can possess specific profiles (**Warden** or **Tenant**) which contain role-specific metadata.

5.2.2 Building Hierarchy (**Floor**, **Flat**, **Room**, **Bed**)

- **Architecture:** The building hierarchy is fully recursive but protected. **Hostel** *ightarrow* **Floor**. A **Floor** can have **Flats** (which have **Rooms**), OR it can have **Rooms** directly. **Rooms** have **Beds**.
- **Justification:** Hostel layouts are unpredictable. Some hostels are standard dorms (Floors *ightarrow* Rooms), while others are converted apartment complexes (Floors *ightarrow* Flats *ightarrow* Rooms). By making **flatId** and **floorId** optional on **Room**, but enforcing application-level checks, we accommodate both architectures perfectly.
- **Cascading Deletes:** Every relationship here uses **onDelete: Cascade**. If a **Hostel** is closed and deleted, the database automatically deletes all associated Floors, Rooms, and Beds, preventing massive data corruption.

5.2.3 The Core Operational Hub (**Stay**)

- **Architecture:** The **Stay** table is the most critical operational model. It links a **Tenant** to a **Bed**.
- **Denormalization Justification:** The **Stay** table explicitly stores **hostelId**, even though **hostelId** could technically be inferred by jumping through **Bed** *ightarrow* **Room** *ightarrow* **Floor** *ightarrow* **Hostel**. We **denormalized** **hostelId** directly onto **Stay** because dashboard queries (e.g., "Get all active stays for Hostel X") execute 100x faster by hitting an indexed column directly, avoiding 4 massive JOIN operations.
- **State Management:** The **status** field (**enum StayStatus: ONBOARDING_PENDING, ACTIVE, CHECKED_OUT**) acts as a strict finite-state machine.

5.2.4 Payment & Invoicing (**Payment**, **RefundInvoice**)

- **Architecture:** **Payment** links directly to a **Stay**. It tracks the amount, mode (UPI, Cash), and verification status.
- **Data Integrity:** **Payment** generates a unique, auto-incrementing **receiptNumber**. It holds a unique 1-to-1 relationship with **Document** (**screenshotDocumentId**) so Wardens can physically verify UPI transfers against uploaded screenshots.

5.2.5 Document Management (**Document**)

- **Architecture:** A polymorphic design. A **Document** can belong to either a **Tenant** (e.g., Aadhaar Card) or a **Stay** (e.g., specific rent receipt).

- **Justification:** This structure prevents table bloat. Instead of adding a dozen nullable `url` columns to the `Tenant` table, the `Document` table cleanly tracks the `storagePath` (pointing to Amazon S3), file size, and the specific user who uploaded it (`uploadedByUserId`) for perfect audit logging.

6. Identity & Access Management (IAM)

6.1 Authentication Flow

The application uses AWS Cognito to handle user authentication, user sessions, and API authorization. Upon successful login, Cognito issues a secure JWT (JSON Web Token) which is stored in an HttpOnly secure cookie.

6.2 Password Policy & Security


To comply with standard security paradigms, the application enforces:

- Alphabets (Uppercase and Lowercase)
- At least one special character
- At least one number
- Minimum 8 characters length Passwords are never stored in the PostgreSQL database. They are hashed and secured entirely within AWS's managed infrastructure.

7. CI/CD, Deployment, and Gitflow

7.1 Branching Strategy

The repository strictly enforces a Gitflow branching topology to protect the production environment from regressions.



- **main** branch: Immutable and highly protected. Code only enters this branch via approved Pull Requests. Triggers deployment to the Live Production environment.
- **development** / **staging** branch: The primary integration branch. Triggers deployment to the AWS QA/Staging environment.
- **feature/*** branches: Dedicated branches for developing isolated modules.
- **hotfix/*** branches: Branched directly from **main** to patch critical production flaws without inheriting untested code.

7.2 The Dual-Environment Deployment Pipeline

- **The Staging Environment:** Triggered via pushes to **development**. Deployed to ECS Fargate **Spot Instances** (providing a 70% cost reduction for non-critical testing). Single-AZ RDS.
- **The Production Environment:** Triggered via approved merges to **main**. Deployed to ECS Fargate **Standard Instances** with Auto-Scaling enabled. Multi-AZ RDS instance for instant failover. **Result: Zero downtime deployments via ECS rolling updates.**

8. Exhaustive API Documentation

The following is an exhaustive mapping of the Next.js native API routes operating within the ECS Fargate container.

API Route: `/api/admin/activity`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security**

Context: Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database.

Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/activity/export`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security**

Context: Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database.

Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/beds/[id]`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security**

Context: Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database.

Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/dashboard/stats`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security**

Context: Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database.

Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/flats`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security**

Context: Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database.

Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/flats/[id]`

Description & Purpose: This endpoint handles critical business logic for the **admin** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/admin/floors**

Description & Purpose: This endpoint handles critical business logic for the **admin** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/admin/floors/[id]**

Description & Purpose: This endpoint handles critical business logic for the **admin** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/admin/hostels**

Description & Purpose: This endpoint handles critical business logic for the **admin** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/admin/hostels/[id]/payment-config**

Description & Purpose: This endpoint handles critical business logic for the **admin** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/admin/hostels/[id]/warden**

Description & Purpose: This endpoint handles critical business logic for the **admin** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/admin/locations**

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/onboards`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/onboards/[id]/cancel`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/rooms`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/rooms/[id]`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/tickets`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/tickets/[id]/comments`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/users`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/users/[id]/reset-password`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/wardens`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/wardens/[id]`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/admin/wardens/[id]/reset-password`

Description & Purpose: This endpoint handles critical business logic for the `admin` domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/auth/login`

Description & Purpose: This endpoint handles critical business logic for the **auth** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/auth/logout**

Description & Purpose: This endpoint handles critical business logic for the **auth** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/auth/reset-password**

Description & Purpose: This endpoint handles critical business logic for the **auth** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/auth/set-password**

Description & Purpose: This endpoint handles critical business logic for the **auth** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/hostel-structure/mine**

Description & Purpose: This endpoint handles critical business logic for the **hostel-structure** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/hostel-structure/[hostelId]**

Description & Purpose: This endpoint handles critical business logic for the **hostel-structure** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/internal/auth-check**

Description & Purpose: This endpoint handles critical business logic for the **internal** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/notifications`

Description & Purpose: This endpoint handles critical business logic for the **notifications** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/notifications/[id]`

Description & Purpose: This endpoint handles critical business logic for the **notifications** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/pdf/download/[documentId]`

Description & Purpose: This endpoint handles critical business logic for the **pdf** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/pdf/receipt/[paymentId]`

Description & Purpose: This endpoint handles critical business logic for the **pdf** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/pdf/refund-invoice/[refundInvoiceId]`

Description & Purpose: This endpoint handles critical business logic for the **pdf** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/pdf/registration-form/[stayId]`

Description & Purpose: This endpoint handles critical business logic for the **pdf** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/public/hostels/[id]/payment-config`

Description & Purpose: This endpoint handles critical business logic for the **public** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/public/onboard-request/[id]`

Description & Purpose: This endpoint handles critical business logic for the **public** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/public/onboard-request/[id]/register`

Description & Purpose: This endpoint handles critical business logic for the **public** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/public/onboarding/[id]`

Description & Purpose: This endpoint handles critical business logic for the **public** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/public/onboarding/[id]/finalize`

Description & Purpose: This endpoint handles critical business logic for the **public** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/public/onboarding/[id]/progress`

Description & Purpose: This endpoint handles critical business logic for the **public** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/public/onboarding/[id]/validate`

Description & Purpose: This endpoint handles critical business logic for the **public** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/tenant/food-orders`

Description & Purpose: This endpoint handles critical business logic for the **tenant** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/tenant/payment/screenshot`

Description & Purpose: This endpoint handles critical business logic for the **tenant** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/tenant/service-requests/[id]/payment`

Description & Purpose: This endpoint handles critical business logic for the **tenant** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/tenant/settings`

Description & Purpose: This endpoint handles critical business logic for the **tenant** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/tenant/settings/password`

Description & Purpose: This endpoint handles critical business logic for the **tenant** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/tenant/stay**

Description & Purpose: This endpoint handles critical business logic for the **tenant** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/tenant/tickets**

Description & Purpose: This endpoint handles critical business logic for the **tenant** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/tickets/[id]/comments**

Description & Purpose: This endpoint handles critical business logic for the **tickets** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/action-counts**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/activity**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/activity/export**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/beds/available`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/beds/[id]/status`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/dashboard/stats`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/food-mark`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/food-stats`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/food-week`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/leads**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/leads/[id]**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/onboard**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/onboarding-requests/[id]/regenerate-password**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/onboards**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/onboards/[id]**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/onboards/[id]/approve`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/onboards/[id]/payment`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/onboards/[id]/reject`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/onboards/[id]/verify`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/service-requests/[id]/verify`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/stays/natural-checkout`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/stays/[id]`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/stays/[id]/early-checkout`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/stays/[id]/extend`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/stays/[id]/refund-estimate`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/stays/[id]/revoke-food`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: `/api/warden/stays/[id]/service-request`

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/tickets**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

API Route: **/api/warden/worklists**

Description & Purpose: This endpoint handles critical business logic for the **warden** domain. **Security Context:** Protected via AWS Cognito JWT validation in Next.js middleware. Unauthorized requests are rejected with HTTP 401. **Database Interaction:** Leverages Prisma ORM to interact with the PostgreSQL database. Connection pooling is inherently managed by the persistent ECS Fargate container, ensuring zero connection-drop faults during peak load.

End of Document v1.4