

## Plain algo and code

title: "Floyd-Warshall" (algo only)

parameters: ("V", "E", "w") (algo only)

```
FLOYD-WARSHALL( $V, E, w$ ):
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$  // edge weights
4  For  $v$  in  $V$ :
5       $\text{dist}[v, v] \leftarrow 0$  // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13 Return  $\text{dist}$ 
```

```
1  def floyd_warshall(G):
2      # let G be an adjacency matrix
3      dist = G
4
5      for k in range(len(G)):
6          for i in range(len(G)):
7              for j in range(len(G)):
8                  if dist[i][j] > dist[i][k] + dist[k][j]:
9                      dist[i][j] = dist[i][k] + dist[k][j]
10
11      return dist
```

## Basic styling parameters

fill: none  
stroke: 2pt + black  
radius: 10pt  
row-gutter: 8pt  
column-gutter: 8pt  
inset: 15pt  
indent-size: 12pt (algo only)  
indent-guides: 1pt + gray  
indent-guides-offset: 4pt  
comment-prefix: [#sym.triangle ] (algo only)

FLOYD-WARSHALL( $V, E, w$ ):

```
1 Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2 For  $(u, v)$  in  $E$ :
3   |  $\text{dist}[u, v] \leftarrow w(u, v)$                                 ▷ edge weights
4 For  $v$  in  $V$ :
5   |  $\text{dist}[v, v] \leftarrow 0$                                     ▷ base case
6
7 For  $k \leftarrow 1$  to  $|V|$ :
8   | For  $i \leftarrow 1$  to  $|V|$ :
9     | For  $j \leftarrow 1$  to  $|V|$ :
10      | | If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11      | | |  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13 Return  $\text{dist}$ 
```

```
1 def floyd_warshall(G):
2     # let G be an adjacency matrix
3     dist = G
4
5     for k in range(len(G)):
6         for i in range(len(G)):
7             for j in range(len(G)):
8                 if dist[i][j] > dist[i][k] + dist[k][j]:
9                     dist[i][j] = dist[i][k] + dist[k][j]
10
11     return dist
```

**Empty bodies**



**code with empty raw block**

1

## Indent guides with line wrapping

indent-guides: 1pt + black

FLOYD-WARSHALL( $V, E, w$ ):

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3  |    $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5  |    $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8  |   For  $i \leftarrow 1$  to  $|V|$ :
9  |   |   For  $j \leftarrow 1$  to  $|V|$ :
10 |   |   |   If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11 |   |   |   |    $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12 |   |   |   |   blah blah blah blah blah blah blah blah blah
13 |   |   |   |   blah blah blah blah
14 Return  $\text{dist}$ 
```

```
1  def floyd_warshall(G):
2  |   # let G be an adjacency matrix
3  |   dist = G
4  |
5  |   for k in range(len(G)):
6  |   |   for i in range(len(G)):
7  |   |   |   for j in range(len(G)):
8  |   |   |   |   if dist[i][j] > dist[i][k] + dist[k][j]:
9  |   |   |   |   |   dist[i][j] = dist[i][k] + dist[k][j]
10 |   |   |   |   blah blah blah blah blah blah blah blah blah
11 |   |   |   |   blah blah blah
12 |   |   |   |
```

## code indent guides with custom tab size

indent-guides: 1pt + black

tab-size: 2

```
1  def floyd_warshall(  
2      |  G  
3      |  ):  
4      # let G be an adjacency matrix  
5      dist = G  
6  
7      for k in range(len(G)):  
8          |  for i in range(len(G)):  
9              |  for j in range(len(G)):  
10                 |  if dist[i][j] > dist[i][k] + dist[k][j]:  
11                     |  dist[i][j] = dist[i][k] + dist[k][j]  
12  
13     return dist
```

## No line numbers

line-numbers: false

```
FLOYD-WARSHALL( $V, E, w$ ):  
Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$   
For  $(u, v)$  in  $E$ :  
     $\text{dist}[u, v] \leftarrow w(u, v)$  // edge weights  
For  $v$  in  $V$ :  
     $\text{dist}[v, v] \leftarrow 0$  // base case  
  
For  $k \leftarrow 1$  to  $|V|$ :  
    For  $i \leftarrow 1$  to  $|V|$ :  
        For  $j \leftarrow 1$  to  $|V|$ :  
            If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :  
                 $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$   
  
Return  $\text{dist}$ 
```

```
def floyd_warshall(G):  
    # let G be an adjacency matrix  
    dist = G  
  
    for k in range(len(G)):  
        for i in range(len(G)):  
            for j in range(len(G)):  
                if dist[i][j] > dist[i][k] + dist[k][j]:  
                    dist[i][j] = dist[i][k] + dist[k][j]  
  
    return dist
```

## algo without keywords

strong-keywords: false

```
FLOYD-WARSHALL( $V, E, w$ ):
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$  // edge weights
4  For  $v$  in  $V$ :
5       $\text{dist}[v, v] \leftarrow 0$  // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13  Return  $\text{dist}$ 
```



## algo with custom keywords

keywords: ("in", "to")

```
FLOYD-WARSHALL( $V, E, w$ ):
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5       $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13  Return  $\text{dist}$ 
```

## algo without title

title: none

```
(V, E, w):
1  Let dist[u, v]  $\leftarrow \infty$  for u, v in V
2  For (u, v) in E:
3      dist[u, v]  $\leftarrow w(u, v)$                                 // edge weights
4  For v in V:
5      dist[v, v]  $\leftarrow 0$                                     // base case
6
7  For k  $\leftarrow 1$  to |V|:
8      For i  $\leftarrow 1$  to |V|:
9          For j  $\leftarrow 1$  to |V|:
10             If dist[i, j] > dist[i, k] + dist[k, j]:
11                 dist[i, j]  $\leftarrow$  dist[i, k] + dist[k, j]
12
13  Return dist
```

## algo without parameters

parameters: ()

```
FLOYD-WARSHALL():
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5       $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13  Return  $\text{dist}$ 
```

## algo without header

title: none

parameters: ()

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5       $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13  Return  $\text{dist}$ 
```

## algo with content-type parameters

parameters: ([#text(blue, [V])], [#text(red, [E])], [#text(green, [w])])

FLOYD-WARSHALL(**V**, **E**, **w**):

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5       $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13  Return  $\text{dist}$ 
```

## algo with content-type title

title: [#set text(red);Floyd-Warshall]

**Floyd-Warshall()**:

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v \in V$ 
2  For  $(u, v) \in E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v \in V$ :
5       $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13 Return  $\text{dist}$ 
```

## algo with custom header

### Floyd-Warshall Algorithm

**Inputs:** graph  $G = (V, E)$   
weight function  $w : E \rightarrow \mathbb{R}$

**Outputs:** distance matrix dist

---

```
1  Let dist[u, v]  $\leftarrow \infty$  for u, v in V
2  For (u, v) in E:
3      dist[u, v]  $\leftarrow w(u, v)$                                 // edge weights
4  For v in V:
5      dist[v, v]  $\leftarrow 0$                                     // base case
6
7  For k  $\leftarrow 1$  to |V|:
8      For i  $\leftarrow 1$  to |V|:
9          For j  $\leftarrow 1$  to |V|:
10             If dist[i, j] > dist[i, k] + dist[k, j]:
11                 dist[i, j]  $\leftarrow$  dist[i, k] + dist[k, j]
12
13  Return dist
```

## Text styling

main-text-styles: (fill: green)

line-number-styles: (fill: red)

comment-styles: (fill: blue) (algo only)

FLOYD-WARSHALL( $V, E, w$ ):

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v \in V$ 
2  For  $(u, v) \in E$ :
3       $\text{dist}[u, v] \leftarrow w(u, v)$  // edge weights
4  For  $v \in V$ :
5       $\text{dist}[v, v] \leftarrow 0$  // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8      For  $i \leftarrow 1$  to  $|V|$ :
9          For  $j \leftarrow 1$  to  $|V|$ :
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13  Return  $\text{dist}$ 
```

```
1  def floyd_warshall(G):
2      # let G be an adjacency matrix
3      dist = G
4
5      for k in range(len(G)):
6          for i in range(len(G)):
7              for j in range(len(G)):
8                  if dist[i][j] > dist[i][k] + dist[k][j]:
9                      dist[i][j] = dist[i][k] + dist[k][j]
10
11  return dist
```



## Indent guides with big main text

indent-guides: 1pt + black

main-text-styles: (size: 15pt)

FLOYD-WARSHALL( $V, E, w$ ):

```
1 Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2 For  $(u, v)$  in  $E$ :
3 |    $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4 For  $v$  in  $V$ :
5 |    $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7 For  $k \leftarrow 1$  to  $|V|$ :
8 |   For  $i \leftarrow 1$  to  $|V|$ :
9 |   |   For  $j \leftarrow 1$  to  $|V|$ :
10 |   |   |   If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11 |   |   |   |    $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13 Return  $\text{dist}$ 
```

```
1 def floyd_warshall(G):
2 |     # let G be an adjacency matrix
3 |     dist = G
4 |
5 |     for k in range(len(G)):
6 |         for i in range(len(G)):
7 |             for j in range(len(G)):
8 |                 if dist[i][j] > dist[i][k] + dist[k][j]:
9 |                     dist[i][j] = dist[i][k] + dist[k][j]
10 |
11 |     return dist
```

## Indent guides with big line numbers

indent-guides: 1pt + black

line-number-styles: (size: 15pt)

FLOYD-WARSHALL( $V, E, w$ ):

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3  |    $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5  |    $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8  |   For  $i \leftarrow 1$  to  $|V|$ :
9  |   |   For  $j \leftarrow 1$  to  $|V|$ :
10 |   |   |   If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11 |   |   |   |    $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13 Return  $\text{dist}$ 
```

```
1  def floyd_warshall(G):
2  |   # let G be an adjacency matrix
3  |   dist = G
4  |
5  |   for k in range(len(G)):
6  |   |   for i in range(len(G)):
7  |   |   |   for j in range(len(G)):
8  |   |   |   |   if dist[i][j] > dist[i][k] + dist[k][j]:
9  |   |   |   |   |   dist[i][j] = dist[i][k] + dist[k][j]
10 |
11 |   return dist
```

## algo indent guides with big comments

indent-guides: 1pt + black  
comment-styles: (size: 15pt)

```
FLOYD-WARSHALL( $V, E, w$ ):  
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$   
2  For  $(u, v)$  in  $E$ :  
3       $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights  
4  For  $v$  in  $V$ :  
5       $\text{dist}[v, v] \leftarrow 0$                                     // base case  
6  
7  For  $k \leftarrow 1$  to  $|V|$ :  
8      For  $i \leftarrow 1$  to  $|V|$ :  
9          For  $j \leftarrow 1$  to  $|V|$ :  
10             If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :  
11                  $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$   
12  
13  Return  $\text{dist}$ 
```

## Alignment

indent-guides: 1pt + black

block-align: bottom + right

FLOYD-WARSHALL( $V, E, w$ ):

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3  |    $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5  |    $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8  |   For  $i \leftarrow 1$  to  $|V|$ :
9  |   |   For  $j \leftarrow 1$  to  $|V|$ :
10 |   |   |   If  $\text{dist}[i, j] > \text{dist}[i, k] + \text{dist}[k, j]$ :
11 |   |   |   |    $\text{dist}[i, j] \leftarrow \text{dist}[i, k] + \text{dist}[k, j]$ 
12
13 Return  $\text{dist}$ 
```

```
1 def floyd_warshall(G):
2     # let G be an adjacency matrix
3     dist = G
4
5     for k in range(len(G)):
6         for i in range(len(G)):
7             for j in range(len(G)):
8                 if dist[i][j] > dist[i][k] + dist[k][j]:
9                     dist[i][j] = dist[i][k] + dist[k][j]
10
11     return dist
```

## Breakable

indent-guides: 1pt + black

breakable: true

FLOYD-WARSHALL( $V, E, w$ ):

```
1  Let  $\text{dist}[u, v] \leftarrow \infty$  for  $u, v$  in  $V$ 
2  For  $(u, v)$  in  $E$ :
3  |    $\text{dist}[u, v] \leftarrow w(u, v)$                                 // edge weights
4  For  $v$  in  $V$ :
5  |    $\text{dist}[v, v] \leftarrow 0$                                     // base case
6
7  For  $k \leftarrow 1$  to  $|V|$ :
8  |   For  $i \leftarrow 1$  to  $|V|$ :
9  |   |   For  $j \leftarrow 1$  to  $|V|$ :
```

```

10 |   |   |   If dist[ $i, j$ ] > dist[ $i, k$ ] + dist[ $k, j$ ]:
11 |   |   |   |   dist[ $i, j$ ]  $\leftarrow$  dist[ $i, k$ ] + dist[ $k, j$ ]
12
13 Return dist

```

```

1 def floyd_warshall(G):
2     # let G be an adjacency matrix
3     dist = G
4
5     for k in range(len(G)):
6         for i in range(len(G)):
7             for j in range(len(G)):

```

```
8 | | | if dist[i][j] > dist[i][k] + dist[k][j]:  
9 | | | | dist[i][j] = dist[i][k] + dist[k][j]  
10  
11 | return dist
```